

FCC REPORT

Applicant: Shenzhen Chuangdesheng Technology Co., Ltd.

Address of Applicant: Room 805,8/F,F Bldg.,Nanchang 1st Industrial Area, Gushu, Xixiang,Bao'an District, Shenzhen China

Equipment Under Test (EUT)

Product Name: Bluetooth Speaker

Model No.: CDS-821, CDS-822, CDS-823, CDS-824, CDS-825, CDS-826

FCC ID: 2AITOCDS821

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.249:2015

Date of sample receipt: December 12, 2016

Date of Test: December 13-16, 2016

Date of report issued: December 16, 2016

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

A circular logo for GTS (Global United Technology Services) is visible. The logo contains the text "GTS" in the center, "GLOBAL TESTING" below it, and "UNITED TECHNOLOGY SERVICES" around the perimeter. A handwritten signature, "Robinson Lo", is written across the logo.

Robinson Lo

Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the GTS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of GTS or testing done by GTS in connection with, distribution or use of the product described in this report must be approved by GTS in writing.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	December 16, 2016	Original

Prepared By:

Yang. Liu

Date:

December 16, 2016

Project Engineer

Check By:

Andy. Wu

Date:

December 16, 2016

Reviewer

3 Contents

Page

1	COVER PAGE.....	1
2	VERSION.....	2
3	CONTENTS	3
4	TEST SUMMARY	4
4.1	MEASUREMENT UNCERTAINTY	4
5	GENERAL INFORMATION.....	5
5.1	CLIENT INFORMATION	5
5.2	GENERAL DESCRIPTION OF EUT	5
5.3	TEST MODE	7
5.4	DESCRIPTION OF SUPPORT UNITS	7
5.5	TEST FACILITY.....	7
5.6	TEST LOCATION	7
5.7	OTHER INFORMATION REQUESTED BY THE CUSTOMER	7
6	TEST INSTRUMENTS LIST	8
7	TEST RESULTS AND MEASUREMENT DATA.....	9
7.1	ANTENNA REQUIREMENT	9
7.2	CONDUCTED EMISSIONS	10
7.3	RADIATED EMISSION METHOD	13
7.3.1	Field Strength of The Fundamental Signal	15
7.3.2	Spurious emissions.....	16
7.3.3	Bandedge emissions.....	20
7.4	20dB OCCUPY BANDWIDTH	21
8	TEST SETUP PHOTO	23
9	EUT CONSTRUCTIONAL DETAILS	25

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	Pass
Field strength of the fundamental signal	15.249 (a)	Pass
Spurious emissions	15.249 (a) (d)/15.209	Pass
Band edge	15.249 (d)/15.205	Pass
20dB Occupied Bandwidth	15.215 (c)	Pass

Pass: The EUT complies with the essential requirements in the standard.

Remark : Test according to ANSI C63.4:2014 and ANSI C63.10:2013.

4.1 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz ~ 30MHz	$\pm 4.34\text{dB}$	(1)
Radiated Emission	30MHz ~ 1000MHz	$\pm 4.24\text{dB}$	(1)
Radiated Emission	1GHz ~ 26.5GHz	$\pm 4.68\text{dB}$	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	$\pm 3.45\text{dB}$	(1)

Note (1): The measurement uncertainty is for coverage factor of $k=2$ and a level of confidence of 95%.

5 General Information

5.1 Client Information

Applicant:	Shenzhen Chuangdesheng Technology Co., Ltd.
Address of Applicant:	Room 805,8/F,F Bldg.,Nanchang 1st Industrial Area, Gushu,Xixiang, Bao'an District, Shenzhen China
Manufacturer/ Factory:	Shenzhen Chuangdesheng Technology Co., Ltd.
Address of Manufacturer/ Factory:	Room 805,8/F,F Bldg.,Nanchang 1st Industrial Area, Gushu,Xixiang, Bao'an District, Shenzhen China

5.2 General Description of EUT

Product Name:	Bluetooth Speaker
Model No.:	CDS-821, CDS-822, CDS-823, CDS-824, CDS-825, CDS-826
Test Model:	CDS-821
<i>Remark: All above models are identical in the same PCB layout, interior structure and electrical circuits. The only difference is the model name for commercial purpose.</i>	
Operation Frequency:	2402MHz~2480MHz
Channel numbers:	79
Channel separation:	1MHz
Modulation type:	GFSK, Pi/4QPSK, 8DPSK
Antenna Type:	PCB antenna
Antenna gain:	0.937 dBi(declare by Applicant)
Power supply:	DC 4.5V (3*1.5V size"AA") Or DC 5V by USB port

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
⋮	⋮	⋮	⋮	⋮	⋮	⋮	⋮
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz

5.3 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode
<i>Remark: During the test, the dutycycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	

Pre-test mode.

We have verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report and defined as follows:

Axis	X	Y	Z
Field Strength(dBuV/m)	94.66	96.71	95.35

Final Test Mode:

The EUT was tested in GFSK, $\pi/4$ QPSK, 8DPSK modulation, and found the GFSK modulation is the worst case.

According to ANSI C63.4 standards, the test results are both the “worst case” and “worst setup”:

Y axis (see the test setup photo)

5.4 Description of Support Units

Manufacturer	Description	Model	Serial Number
Emerson Network Power	USB Charger	A1299	N/A

5.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 600491**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 600491, June 22, 2016.

- **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, August 15, 2016

5.6 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

Tel: 0755-27798480

Fax: 0755-27798960

5.7 Other Information Requested by the Customer

None.

6 Test Instruments list


Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July 03 2015	July 02 2020
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June 29 2016	June 28 2017
4	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June 29 2016	June 28 2017
5	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June 29 2016	June 28 2017
6	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	9120D-829	GTS208	June 29 2016	June 28 2017
7	Horn Antenna	ETS-LINDGREN	3160	GTS217	June 29 2016	June 28 2017
8	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
9	Coaxial Cable	GTS	N/A	GTS213	June 29 2016	June 28 2017
10	Coaxial Cable	GTS	N/A	GTS211	June 29 2016	June 28 2017
11	Coaxial cable	GTS	N/A	GTS210	June 29 2016	June 28 2017
12	Coaxial Cable	GTS	N/A	GTS212	June 29 2016	June 28 2017
13	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June 29 2016	June 28 2017
14	Amplifier(2GHz-20GHz)	HP	8349B	GTS206	June 29 2016	June 28 2017
15	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June 29 2016	June 28 2017
16	Band filter	Amindeon	82346	GTS219	June 29 2016	June 28 2017
17	Power Meter	Anritsu	ML2495A	GTS540	June 29 2016	June 28 2017
18	Power Sensor	Anritsu	MA2411B	GTS541	June 29 2016	June 28 2017

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.16 2014	May.15 2019
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 29 2016	June. 28 2017
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June. 29 2016	June. 28 2017
4	Artificial Mains Network	SCHWARZBECK MESS	NSLK8127	GTS226	June. 29 2016	June. 28 2017
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	KTJ	TA328	GTS233	June. 29 2016	June. 28 2017

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	ChangChun	DYM3	GTS257	June 29 2016	June 28 2017

7 Test results and Measurement Data

7.1 Antenna requirement


Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
EUT Antenna:	
<i>The antenna is PCB antenna, the best case gain of the antenna is 0.937dBi</i>  Antenna	

7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207		
Test Method:	ANSI C63.10:2013		
Test Frequency Range:	150KHz to 30MHz		
Class / Severity:	Class B		
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test setup:	Reference Plane Test table/Insulation plane <i>Remark</i> E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m		
Test procedure:	1. The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.		
Test Instruments:	Refer to section 6.0 for details		
Test mode:	Refer to section 5.3 for details		
Test results:	Pass		


Measurement data

Line:



Freq MHz	Reading level dBuV	LIISN/ISN factor dB	Cable loss dBuV	level dB	Limit level dBuV	Over limit dB	Remark
0.256	41.46	0.44	0.11	42.01	61.56	-19.55	QP
0.440	42.27	0.40	0.11	42.78	57.07	-14.29	QP
0.767	37.67	0.27	0.13	38.07	56.00	-17.93	QP
1.781	35.98	0.20	0.14	36.32	56.00	-19.68	QP
2.554	36.93	0.20	0.15	37.28	56.00	-18.72	QP
3.041	36.16	0.20	0.15	36.51	56.00	-19.49	QP

Neutral:





Freq MHz	Reading level dBuV	LISN/ISN factor dB	Cable loss dB	level dB	Limit level dBuV	Over limit dB	Remark
0.253	40.89	0.42	0.11	41.42	61.64	-20.22	QP
0.444	40.12	0.38	0.11	40.61	56.98	-16.37	QP
0.775	35.42	0.23	0.13	35.78	56.00	-20.22	QP
1.269	35.86	0.21	0.13	36.20	56.00	-19.80	QP
2.554	37.70	0.20	0.15	38.05	56.00	-17.95	QP
3.041	38.81	0.20	0.15	39.16	56.00	-16.84	QP

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

7.3 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	30MHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		PEAK	1MHz	10Hz	Average Value
Limit: (Field strength of the fundamental signal)	Frequency		Limit (dBuV/m @3m)		Remark
	2400MHz-2483.5MHz		94.00		Average Value
			114.00		Peak Value
Limit: (Spurious Emissions)	Frequency		Limit (dBuV/m @3m)		Remark
	30MHz-88MHz		40.00		Quasi-peak Value
	88MHz-216MHz		43.50		Quasi-peak Value
	216MHz-960MHz		46.00		Quasi-peak Value
	960MHz-1GHz		54.00		Quasi-peak Value
	Above 1GHz		54.00		Average Value
			74.00		Peak Value
Limit: (band edge)	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.				
Test setup:	Below 1GHz				
					
	Above 1GHz				

	
Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

Measurement data:

7.3.1 Field Strength of The Fundamental Signal

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	92.47	27.58	5.39	30.18	95.26	114.00	-18.74	Vertical
2402.00	89.81	27.58	5.39	30.18	92.60	114.00	-21.40	Horizontal
2441.00	90.75	27.55	5.43	30.06	93.67	114.00	-20.33	Vertical
2441.00	88.80	27.55	5.43	30.06	91.72	114.00	-22.28	Horizontal
2480.00	93.65	27.52	5.47	29.93	96.71	114.00	-17.29	Vertical
2480.00	90.42	27.52	5.47	29.93	93.48	114.00	-20.52	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	81.69	27.58	5.39	30.18	84.48	94.00	-9.52	Vertical
2402.00	79.08	27.58	5.39	30.18	81.87	94.00	-12.13	Horizontal
2441.00	79.79	27.55	5.43	30.06	82.71	94.00	-11.29	Vertical
2441.00	76.84	27.55	5.43	30.06	79.76	94.00	-14.24	Horizontal
2480.00	83.01	27.52	5.47	29.93	86.07	94.00	-7.93	Vertical
2480.00	79.68	27.52	5.47	29.93	82.74	94.00	-11.26	Horizontal

NOTE: RBW 3MHz VBW 3MHz peak detector is for PK value , RMS detector is for AV value

7.3.2 Spurious emissions

■ Below 1GHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
31.40	37.78	14.32	0.57	30.09	22.58	40.00	-17.42	Vertical
37.03	29.63	14.82	0.63	30.06	15.02	40.00	-24.98	Vertical
102.00	26.75	14.97	1.21	29.69	13.24	43.50	-30.26	Vertical
176.89	34.56	11.49	1.72	29.29	18.48	43.50	-25.02	Vertical
207.85	38.49	12.80	1.89	29.28	23.90	43.50	-19.60	Vertical
338.40	35.79	16.05	2.57	29.79	24.62	46.00	-21.38	Vertical
31.40	30.84	14.32	0.57	30.09	15.64	40.00	-24.36	Horizontal
51.30	25.74	15.19	0.78	29.99	11.72	40.00	-28.28	Horizontal
102.36	25.25	14.92	1.21	29.68	11.70	43.50	-31.80	Horizontal
175.65	40.86	11.36	1.72	29.30	24.64	43.50	-18.86	Horizontal
203.52	35.00	12.67	1.86	29.23	20.30	43.50	-23.20	Horizontal
382.59	24.83	16.68	2.77	29.58	14.70	46.00	-31.30	Horizontal

■ Above 1GHz

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	37.26	31.78	8.60	32.09	45.55	74.00	-28.45	Vertical
7206.00	31.80	36.15	11.65	32.00	47.60	74.00	-26.40	Vertical
9608.00	31.44	37.95	14.14	31.62	51.91	74.00	-22.09	Vertical
12010.00	*					74.00		Vertical
14412.00	*					74.00		Vertical
4804.00	41.54	31.78	8.60	32.09	49.83	74.00	-24.17	Horizontal
7206.00	33.55	36.15	11.65	32.00	49.35	74.00	-24.65	Horizontal
9608.00	30.86	37.95	14.14	31.62	51.33	74.00	-22.67	Horizontal
12010.00	*					74.00		Horizontal
14412.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	26.08	31.78	8.60	32.09	34.37	54.00	-19.63	Vertical
7206.00	20.49	36.15	11.65	32.00	36.29	54.00	-17.71	Vertical
9608.00	19.57	37.95	14.14	31.62	40.04	54.00	-13.96	Vertical
12010.00	*					54.00		Vertical
14412.00	*					54.00		Vertical
4804.00	30.31	31.78	8.60	32.09	38.60	54.00	-15.40	Horizontal
7206.00	22.66	36.15	11.65	32.00	38.46	54.00	-15.54	Horizontal
9608.00	19.30	37.95	14.14	31.62	39.77	54.00	-14.23	Horizontal
12010.00	*					54.00		Horizontal
14412.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. “*”, means this data is the too weak instrument of signal is unable to test.

Test channel:	Middle channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882.00	37.17	31.85	8.67	32.12	45.57	74.00	-28.43	Vertical
7323.00	31.74	36.37	11.72	31.89	47.94	74.00	-26.06	Vertical
9764.00	31.39	38.35	14.25	31.62	52.37	74.00	-21.63	Vertical
12205.00	*					74.00		Vertical
14646.00	*					74.00		Vertical
4882.00	41.42	31.85	8.67	32.12	49.82	74.00	-24.18	Horizontal
7323.00	33.48	36.37	11.72	31.89	49.68	74.00	-24.32	Horizontal
9764.00	30.80	38.35	14.25	31.62	51.78	74.00	-22.22	Horizontal
12205.00	*					74.00		Horizontal
14646.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882.00	26.02	31.85	8.67	32.12	34.42	54.00	-19.58	Vertical
7323.00	20.45	36.37	11.72	31.89	36.65	54.00	-17.35	Vertical
9764.00	19.53	38.35	14.25	31.62	40.51	54.00	-13.49	Vertical
12205.00	*					54.00		Vertical
14646.00	*					54.00		Vertical
4882.00	30.23	31.85	8.67	32.12	38.63	54.00	-15.37	Horizontal
7323.00	22.61	36.37	11.72	31.89	38.81	54.00	-15.19	Horizontal
9764.00	19.25	38.35	14.25	31.62	40.23	54.00	-13.77	Horizontal
12205.00	*					54.00		Horizontal
14646.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. “*”, means this data is the too weak instrument of signal is unable to test.

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	37.70	31.93	8.73	32.16	46.20	74.00	-27.80	Vertical
7440.00	32.09	36.59	11.79	31.78	48.69	74.00	-25.31	Vertical
9920.00	31.70	38.81	14.38	31.88	53.01	74.00	-20.99	Vertical
12400.00	*					74.00		Vertical
14880.00	*					74.00		Vertical
4960.00	42.07	31.93	8.73	32.16	50.57	74.00	-23.43	Horizontal
7440.00	33.88	36.59	11.79	31.78	50.48	74.00	-23.52	Horizontal
9920.00	31.16	38.81	14.38	31.88	52.47	74.00	-21.53	Horizontal
12400.00	*					74.00		Horizontal
14880.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	26.54	31.93	8.73	32.16	35.04	54.00	-18.96	Vertical
7440.00	20.80	36.59	11.79	31.78	37.40	54.00	-16.60	Vertical
9920.00	19.85	38.81	14.38	31.88	41.16	54.00	-12.84	Vertical
12400.00	*					54.00		Vertical
14880.00	*					54.00		Vertical
4960.00	30.82	31.93	8.73	32.16	39.32	54.00	-14.68	Horizontal
7440.00	23.01	36.59	11.79	31.78	39.61	54.00	-14.39	Horizontal
9920.00	19.62	38.81	14.38	31.88	40.93	54.00	-13.07	Horizontal
12400.00	*					54.00		Horizontal
14880.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. “*”, means this data is the too weak instrument of signal is unable to test.

7.3.3 Bandedge emissions

All of the restriction bands were tested, and only the data of worst case was exhibited.

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	39.69	27.59	5.38	30.18	42.48	74.00	-31.52	Horizontal
2400.00	56.02	27.58	5.39	30.18	58.81	74.00	-15.19	Horizontal
2390.00	39.93	27.59	5.38	30.18	42.72	74.00	-31.28	Vertical
2400.00	57.72	27.58	5.39	30.18	60.51	74.00	-13.49	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	30.96	27.59	5.38	30.18	33.75	54.00	-20.25	Horizontal
2400.00	42.01	27.58	5.39	30.18	44.80	54.00	-9.20	Horizontal
2390.00	30.68	27.59	5.38	30.18	33.47	54.00	-20.53	Vertical
2400.00	43.35	27.58	5.39	30.18	46.14	54.00	-7.86	Vertical

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	41.41	27.53	5.47	29.93	44.48	74.00	-29.52	Horizontal
2500.00	41.19	27.55	5.49	29.93	44.30	74.00	-29.70	Horizontal
2483.50	41.73	27.53	5.47	29.93	44.80	74.00	-29.20	Vertical
2500.00	41.89	27.55	5.49	29.93	45.00	74.00	-29.00	Vertical


Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	33.75	27.53	5.47	29.93	36.82	54.00	-17.18	Horizontal
2500.00	32.21	27.55	5.49	29.93	35.32	54.00	-18.68	Horizontal
2483.50	34.70	27.53	5.47	29.93	37.77	54.00	-16.23	Vertical
2500.00	31.86	27.55	5.49	29.93	34.97	54.00	-19.03	Vertical

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor


7.4 20dB Occupy Bandwidth

Test Requirement:	FCC Part15 C Section 15.249/15.215
Test Method:	ANSI C63.10:2013
Limit:	Operation Frequency range 2400MHz~2483.5MHz
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass


Measurement Data

Test channel	20dB bandwidth(MHz)	Result
Lowest	1.000	Pass
Middle	1.126	Pass
Highest	1.130	Pass


Test plot as follows:



Lowest channel




Middle channel



Highest channel

8 Test Setup Photo



Radiated Emission





Conducted Emission





9 EUT Constructional Details


















-----End-----