



TESTING LABORATORY
CERTIFICATE #4820.01



FCC PART 15.247

TEST REPORT

For

Wynd Technologies, Inc.

2590 Clarebank Way, San Jose, CA95121, U.S.A.

FCC ID: 2AIULHLO001


Report Type: Original Report	Product Name: Wynd Halo
Report Number: RDG190828005-00B	
Report Date: 2019-11-26	
Reviewed By:	Gavin Xu RF Engineer 
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
DECLARATIONS	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	9
SUPPORT EQUIPMENT LIST AND DETAILS	9
SUPPORT CABLE LIST AND DETAILS	9
BLOCK DIAGRAM OF TEST SETUP	9
SUMMARY OF TEST RESULTS.....	10
FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	11
APPLICABLE STANDARD	11
FCC §15.203 - ANTENNA REQUIREMENT.....	12
APPLICABLE STANDARD	12
ANTENNA CONNECTOR CONSTRUCTION	12
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	13
APPLICABLE STANDARD	13
EUT SETUP.....	13
EMI TEST RECEIVER SETUP.....	13
TEST PROCEDURE	14
CORRECTED AMPLITUDE & MARGIN CALCULATION	14
TEST EQUIPMENT LIST AND DETAILS.....	14
TEST DATA	14
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	17
APPLICABLE STANDARD	17
EUT SETUP	17
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	18
TEST PROCEDURE	18
CORRECTED AMPLITUDE & MARGIN CALCULATION	18
TEST EQUIPMENT LIST AND DETAILS.....	19
TEST DATA	19
FCC §15.247(a) (2)–6 dB EMISSION BANDWIDTH.....	29
FCC §15.247(a) (2)–6 dB EMISSION BANDWIDTH.....	29
APPLICABLE STANDARD	29
TEST PROCEDURE	29
TEST EQUIPMENT LIST AND DETAILS.....	29
TEST DATA	30
FCC §15.247(b) (3) - MAXIMUM PEAK CONDUCTED OUTPUT POWER.....	36
APPLICABLE STANDARD	36
TEST PROCEDURE	36

TEST EQUIPMENT LIST AND DETAILS.....	36
TEST DATA	37
FCC §15.247(d)– 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	38
APPLICABLE STANDARD	38
TEST PROCEDURE	38
TEST EQUIPMENT LIST AND DETAILS.....	38
TEST DATA	39
FCC §15.247(e) - POWER SPECTRAL DENSITY	43
APPLICABLE STANDARD	43
TEST PROCEDURE	43
TEST EQUIPMENT LIST AND DETAILS.....	43
TEST DATA	43

GENERAL INFORMATION**Product Description for Equipment under Test (EUT)**

EUT Name:		Wynd Halo
EUT Model:		HLO001
Highest Operation Frequency:		2412-2462MHz
Maximum Peak Output Power (Conducted):		18.01 dBm
Rated Input Voltage:		DC 3.7 V from battery or DC 5V from adapter
Adapter Information	Model:	SK12G-0500100Z
	Input:	AC100-240V 50/60Hz 0.2A Max
	Output:	DC 5V 1A
Serial Number:		190828005
EUT Received Date:		2019/8/30
EUT Received Status:		Good

Objective

This report is prepared on behalf of **Wynd Technologies, Inc.** in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules.

The tests were performed in order to determine the compliance of the EUT with FCC Rules Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

No Related Submittal(s)/Grant(s)

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices. And 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.55 dB, 200M~1GHz: 5.92 dB, 1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “Δ”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA, or any agency of the U.S. Government.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in Engineering Mode, which was provided by the manufacturer.

For 2.4GHz band, total 11 channels are provided:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, 802.11n ht20 modes were test with channel 1,6,11.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations.

EUT Exercise Software


The software “sscom5.13.1.exe” was used for testing, which was provided by manufacturer. The maximum power was configured as below table, that provided by the manufacturer:

Mode	Channel	Frequency (MHz)	Data rate (Mbps)	Power level
802.11 b	Low	2412	1M	Default
	Middle	2437	1M	Default
	High	2462	1M	Default
802.11 g	Low	2412	6M	Default
	Middle	2437	6M	Default
	High	2462	6M	Default
802.11 n20	Low	2412	6.5M	Default
	Middle	2437	6.5M	Default
	High	2462	6.5M	Default

The maximum duty cycle as following table:

Test mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle (%)
802.11b	8.6061	8.7470	98.39
802.11g	1.4258	1.4810	96.27
802.11n ht20	1.3378	1.3930	96.04


802.11b



Date: 5.NOV.2019 10:48:27


80

802.11g



Date: 5.NOV.2019 10:50:06

802.11n ht20



Date: 5.NOV.2019 10:50:55

Equipment Modifications

No modification was made to the EUT.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Apple	Mobile Phone	MGAA2CG/A	FK1R95UYG5QT

Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From	To
Power Cable	yes	No	1.2	adapter	EUT

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC§15.247 (i) & §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
FCC §15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Frequency (MHz)	Antenna Gain		Conducted output power including Tune-up Tolerance		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
	(dBi)	(numeric)	(dBm)	(mW)			
2412-2462	0.5	1.12	18.5	70.79	20.00	0.0156	1.0

Result: The device meet FCC MPE at 20 cm distance

FCC §15.203 - ANTENNA REQUIREMENT**Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has one internal antenna permanently attached to the unit, fulfill the requirement of this section. Please refer to the EUT photos.

Antenna Type	input impedance (Ohm)	Antenna Gain /Frequency Range
PCB	50	0.5 dBi/2.4~2.5GHz


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207(a).

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 30 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the EUT was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Unknown	Coaxial Cable	C-NJNJ-50	C-0200-01	2019-09-05	2020-09-05
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A
R&S	Two-line V-network	ENV 216	101614	2018-12-10	2019-12-10
R&S	EMI Test Receiver	ESCI	101121	2019-05-09	2020-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data

Environmental Conditions

Temperature:	25.7°C
Relative Humidity:	60 %
ATM Pressure:	100.6kPa
Tester:	Sem Xiang
Test Date:	2019-10-28


Test Mode: Transmitting (802.11n20 middle channel was the worst)

AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.157652	43.7	9.000	L1	11.1	21.9	65.6
0.422196	36.5	9.000	L1	9.9	20.9	57.4
0.471031	37.0	9.000	L1	9.9	19.5	56.5
0.744445	33.3	9.000	L1	9.8	22.7	56.0
1.570131	22.0	9.000	L1	9.7	34.0	56.0
10.608147	27.7	9.000	L1	9.8	32.3	60.0

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.159228	27.1	9.000	L1	11.1	28.4	55.5
0.184859	24.5	9.000	L1	10.8	29.8	54.3
0.422196	23.9	9.000	L1	9.9	23.5	47.4
0.452652	26.4	9.000	L1	9.9	20.4	46.8
0.751890	19.8	9.000	L1	9.8	26.2	46.0
1.261437	14.3	9.000	L1	9.8	31.7	46.0



AC120 V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.160820	41.2	9.000	N	11.0	24.2	65.4
0.409780	33.7	9.000	N	10.0	24.0	57.7
0.448170	36.9	9.000	N	9.9	20.0	56.9
0.751890	33.7	9.000	N	9.8	22.3	56.0
1.666725	22.5	9.000	N	9.8	33.5	56.0
10.821371	28.0	9.000	N	9.8	32.0	60.0

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.159228	25.0	9.000	N	11.0	30.5	55.5
0.418016	22.2	9.000	N	9.9	25.3	47.5
0.448170	25.4	9.000	N	9.9	21.5	46.9
0.744445	19.4	9.000	N	9.8	26.6	46.0
1.286792	15.5	9.000	N	9.8	30.5	46.0
2.456957	11.7	9.000	N	9.8	34.3	46.0

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

EUT Setup**Below 1GHz:****Above 1GHz:**

The radiated emission Below 1GHz tests were performed in the 3 meters chamber A, above 1GHz tests were performed in the 3 meters chamber B, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiation Below 1GHz					
R&S	EMI Test Receiver	ESR3	102453	2019-06-26	2020-06-26
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Sunol Sciences	Antenna	JB3	A060611-1	2017-11-10	2020-11-10
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2019-09-05	2020-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2019-09-05	2020-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2019-05-06	2020-05-06
HP	Amplifier	8447D	2727A05902	2019-09-05	2020-09-05
Radiation Above 1GHz					
Agilent	Spectrum Analyzer	E4440A	SG43360054	2019-05-09	2020-05-09
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
ETS-Lindgren	Horn Antenna	3115	000 527 35	2018-10-12	2021-10-12
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2016-11-18	2019-11-18
Unknown	Coaxial Cable	C-SJSJ-50	C-0800-01	2019-09-05	2020-09-05
MITEQ	Amplifier	AFS42-00101800- 25-S-42	2001271	2019-09-05	2020-09-05
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2019-06-27	2020-06-27
E-Microwave	Band-stop Filters	OBSF-2400-2483.5- S	OE01601525	2019-06-16	2020-06-16
Micro-tronics	High Pass Filter	HPM50111	S/N-G217	2019-06-16	2020-06-16

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**


Test Items	Radiation Below 1GHz	Radiation Above 1GHz
Temperature:	25.3°C	25.3°C
Relative Humidity:	40%	40%
ATM Pressure:	100.1 kPa	100.1 kPa
Tester:	Neil Liao	Neil Liao
Test Date:	2019-10-29	2019-10-29

Test Result: Compliance, please Refer to the following data


Test Mode: Transmitting

1) 30MHz-1GHz(802.11n20 mode Middle channel was the worst)

Horizontal:



Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
30.0000	27.64	peak	1.72	29.36	40.00	10.64
127.9700	29.76	peak	-4.76	25.00	43.50	18.50
541.1900	27.12	peak	0.32	27.44	46.00	18.56
748.7700	27.33	peak	3.63	30.96	46.00	15.04
911.7300	33.57	peak	0.24	33.81	46.00	12.19
954.4100	33.53	peak	0.82	34.35	46.00	11.65

Vertical:

Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
30.0000	27.87	peak	1.72	29.59	40.00	10.41
127.9700	28.24	peak	-4.76	23.48	43.50	20.02
596.4800	27.13	peak	0.90	28.03	46.00	17.97
781.7500	26.91	peak	4.39	31.30	46.00	14.70
875.8400	34.18	peak	-0.60	33.58	46.00	12.42
994.1800	33.38	peak	1.49	34.87	54.00	19.13

2) 1-25GHz:**802.11b Mode :**

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2390.00	25.77	PK	H	28.08	1.80	0.00	55.65	74.00	18.35
2390.00	12.92	AV	H	28.08	1.80	0.00	42.80	54.00	11.20
4824.00	56.07	PK	H	32.95	3.19	37.20	55.01	74.00	18.99
4824.00	52.83	AV	H	32.95	3.19	37.20	51.77	54.00	2.23
7236.00	46.73	PK	H	35.81	4.77	37.27	50.04	74.00	23.96
7236.00	34.21	AV	H	35.81	4.77	37.27	37.52	54.00	16.48
Middle Channel: 2437 MHz									
4874.00	57.10	PK	H	33.05	3.26	37.21	56.20	74.00	17.80
4874.00	53.76	AV	H	33.05	3.26	37.21	52.86	54.00	1.14
7311.00	46.82	PK	H	36.01	4.64	37.36	50.11	74.00	23.89
7311.00	35.28	AV	H	36.01	4.64	37.36	38.57	54.00	15.43
High Channel: 2462 MHz									
2483.50	27.46	PK	H	28.27	1.84	0.00	57.57	74.00	16.43
2483.50	13.68	AV	H	28.27	1.84	0.00	43.79	54.00	10.21
4924.00	57.22	PK	H	33.15	3.27	37.22	56.42	74.00	17.59
4924.00	54.16	AV	H	33.15	3.27	37.22	53.36	54.00	0.64
7386.00	46.65	PK	H	36.20	4.51	37.46	49.90	74.00	24.10
7386.00	34.11	AV	H	36.20	4.51	37.46	37.36	54.00	16.64



802.11g Mode :


Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2390.00	26.33	PK	H	28.08	1.80	0.00	56.21	74.00	17.79
2390.00	13.21	AV	H	28.08	1.80	0.00	43.09	54.00	10.91
4824.00	62.97	PK	H	32.95	3.19	37.20	61.91	74.00	12.09
4824.00	48.44	AV	H	32.95	3.19	37.20	47.38	54.00	6.62
7236.00	46.52	PK	H	35.81	4.77	37.27	49.83	74.00	24.17
7236.00	24.87	AV	H	35.81	4.77	37.27	28.18	54.00	25.82
Middle Channel: 2437 MHz									
4874.00	63.10	PK	H	33.05	3.26	37.21	62.20	74.00	11.80
4874.00	48.65	AV	H	33.05	3.26	37.21	47.75	54.00	6.25
7311.00	46.20	PK	H	36.01	4.64	37.36	49.49	74.00	24.51
7311.00	34.12	AV	H	36.01	4.64	37.36	37.41	54.00	16.59
High Channel: 2462 MHz									
2483.50	26.37	PK	H	28.27	1.84	0.00	56.48	74.00	17.52
2483.50	13.57	AV	H	28.27	1.84	0.00	43.68	54.00	10.32
4924.00	63.33	PK	H	33.15	3.27	37.22	62.53	74.00	11.47
4924.00	48.76	AV	H	33.15	3.27	37.22	47.96	54.00	6.04
7386.00	46.79	PK	H	36.20	4.51	37.46	50.04	74.00	23.96
7386.00	34.25	AV	H	36.20	4.51	37.46	37.50	54.00	16.50

802.11n ht20 Mode:



Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2390.00	25.37	PK	H	28.08	1.80	0.00	55.25	74.00	18.75
2390.00	13.23	AV	H	28.08	1.80	0.00	43.11	54.00	10.89
4824.00	63.39	PK	H	32.95	3.19	37.20	62.33	74.00	11.67
4824.00	48.55	AV	H	32.95	3.19	37.20	47.49	54.00	6.51
7236.00	46.27	PK	H	35.81	4.77	37.27	49.58	74.00	24.42
7236.00	35.16	AV	H	35.81	4.77	37.27	38.47	54.00	15.53
Middle Channel: 2437 MHz									
4874.00	63.71	PK	H	33.05	3.26	37.21	62.81	74.00	11.19
4874.00	48.59	AV	H	33.05	3.26	37.21	47.69	54.00	6.31
7311.00	46.78	PK	H	36.01	4.64	37.36	50.07	74.00	23.93
7311.00	34.70	AV	H	36.01	4.64	37.36	37.99	54.00	16.01
High Channel: 2462 MHz									
2483.50	26.67	PK	H	28.27	1.84	0.00	56.78	74.00	17.22
2483.50	13.88	AV	H	28.27	1.84	0.00	43.99	54.00	10.01
4924.00	63.37	PK	H	33.15	3.27	37.22	62.57	74.00	11.43
4924.00	48.31	AV	H	33.15	3.27	37.22	47.51	54.00	6.49
7386.00	46.12	PK	H	36.20	4.51	37.46	49.37	74.00	24.63
7386.00	34.28	AV	H	36.20	4.51	37.46	37.53	54.00	16.47


Test plots(802.11b high channel was the worst)
Horizontal:





Vertical:





FCC §15.247(a) (2)–6 dB EMISSION BANDWIDTH


Applicable Standard

According to FCC §15.247(a) (2)

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2019-01-09	2020-01-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A
E-Microwave	Blocking Control	EMDCB-00036	0E01201048	2019-05-06	2020-05-06

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	26.1°C
Relative Humidity:	42%
ATM Pressure:	101.2 kPa
Tester:	LilyXie
Test Date:	2019-11-05


Test Mode: Transmitting

Test Result: Compliance. Please refer to the following table and plots.


Test mode	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	10.080	≥ 0.5
	Middle	2437	10.000	≥ 0.5
	High	2462	9.600	≥ 0.5
802.11g	Low	2412	16.160	≥ 0.5
	Middle	2437	16.160	≥ 0.5
	High	2462	16.240	≥ 0.5
802.11n ht20	Low	2412	17.520	≥ 0.5
	Middle	2437	17.280	≥ 0.5
	High	2462	17.360	≥ 0.5

Please refer to following plots:


802.11 b_Low




802.11 b_Middle




802.11 b High




802.11 g Low




802.11 g Middle




802.11 g High




802.11 n20 Low



802.11 n20 Middle



802.11 n20_High




Date: 5.NOV.2019 10:25:06

FCC §15.247(b) (3) - MAXIMUM PEAK CONDUCTED OUTPUT POWER**Applicable Standard**

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A
E-Microwave	Blocking Control	EMDCB-00036	0E01201048	2019-05-06	2020-05-06
E-Microwave	Coaxial Attenuators	EMCA10-5RN-6	OE01203239	2019-09-06	2020-09-06
Agilent	USB Wideband Power Sensor	U2022XA	MY5417006	2019-09-23	2020-09-23

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	26.1°C
Relative Humidity:	42%
ATM Pressure:	101.2 kPa
Tester:	LilyXie
Test Date:	2019-11-05

Test Mode: Transmitting

Test Result: Compliance. Please refer to the following table.

Mode	Channel	Frequency (MHz)	Conducted Peak output power (dBm)	Limit (dBm)
802.11 b	Low	2412	13.71	30
	Middle	2437	14.24	
	High	2462	14.79	
802.11 g	Low	2412	17.56	
	Middle	2437	17.64	
	High	2462	17.79	
802.11 n20	Low	2412	17.80	
	Middle	2437	18.01	
	High	2462	17.99	

Note: The data above was tested in conducted mode and the antenna gain is 0.5dBi.

FCC §15.247(d)– 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**Applicable Standard**

According to FCC§15.247(d):In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2019-01-09	2020-01-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A
E-Microwave	Blocking Control	EMDCB-00036	0E01201048	2019-05-06	2020-05-06


* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	26.1°C
Relative Humidity:	42%
ATM Pressure:	101.2 kPa
Tester:	LilyXie
Test Date:	2019-11-05


Please refer to following plots:

802.11 b_Low




Date: 5.NOV.2019 10:04:55

802.11 b_High




Date: 5.NOV.2019 10:08:44


802.11 g Low



802.11 g High




802.11 n20 Low



Date: 5.NOV.2019 10:21:44

802.11 n20 High



Date: 5.NOV.2019 10:26:08

FCC §15.247(e) - POWER SPECTRAL DENSITY**Applicable Standard**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set the RBW = 3 kHz, VBW = 10 kHz, Set the span to 1.5 times the DTS bandwidth.
4. Use the peak marker function to determine the maximum amplitude level.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2019-01-09	2020-01-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A
E-Microwave	Blocking Control	EMDCB-00036	0E01201048	2019-05-06	2020-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	26.1°C
Relative Humidity:	42%
ATM Pressure:	101.2 kPa
Tester:	LilyXie
Test Date:	2019-11-05

Test Mode: Transmitting


Test Result: Compliant. Please refer to the following table and plots

Please refer to following plots:


Mode	Channel	Frequency (MHz)	Result (dBm/3kHz)	Limit (dBm/3kHz)
802.11 b	Low	2412	-12.19	8
	Middle	2437	-12.02	
	High	2462	-10.90	
802.11 g	Low	2412	-15.75	
	Middle	2437	-15.75	
	High	2462	-15.20	
802.11 n20	Low	2412	-15.88	
	Middle	2437	-14.70	
	High	2462	-15.24	

Please refer to following plots:


802.11 b Low




802.11 b Middle




802.11 b High




802.11 g Low




802.11 g Middle




802.11 g High




802.11 n20 Low



802.11 n20 Middle



802.11 n20 High



***** END OF REPORT *****