

Wireless Gateway

GW900-4G-US Ex

Made in Belgium



I-care SRL, Rue René Descartes 18,
7000 Mons, Belgium

Mod#: WG150161L-02

S/N: WGBE25Test29



Placeholder
Certificate



Class I, Div 2, Group ABCD
Ex eb mb IIC T4 Gb

Class I Zone 1 AEx eb mb IIC T4 Gb
(-15 °C ≤ Ta ≤ +59 °C)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause interference.
- (2) This device must accept any interference, including interference that may cause undesired operation.

FCC ID: 2AIV8AG02-02 IC: 33597-AG0202 HVIN: WG150161R13

Contains FCC ID: XMR202008EG91NAXD

Contains IC: 10224A-21EG91NAXDL

24 VDC; P_n = 1.8 W



IP66
Type 4, 4X



**WARNING – READ
MANUAL – DO NOT
CONNECT
OR DISCONNECT
WHEN ENERGIZED –
POTENTIAL
ELECTROSTATIC
CHARGING HAZARD
Electrical Shock
Hazard
Do not open While
powered**



**AVERTISSEMENT –
LIRE LE MANUEL – NE
PAS BRANCHER OU
DÉBRANCHER SOUS
TENSION – RISQUE
POTENTIEL DE
CHARGE
ÉLECTROSTATIQUE
Risque de choc
électrique
Ne pas ouvrir sous
tension**

Wireless Gateway
Certified for FCC



I-care S.R.L. Rue René Descartes 18
1000 Mons, Belgium

Mod# WG150161L-02
S/N: WGRE25Test39



Noticeholder
Certificate

Class 1, Div 2, Group ABCD
Ex eb mb IIC T4 Gb
Class 1 Zone 1 AEx eb mb IIC T4 Gb
(-15 °C ≤ Ta ≤ +55 °C)



This device complies with Part 15 of the FCC Rules. Operation is
subject to the following two conditions:
(1) This device may not cause interference.
(2) This device must accept any interference, including interference
that may cause undesired operation.
FCC ID: 2A918AG27-02 IC: 35597-AG2002 HVIN: WG150161R13
Contains FCC ID: XMR2020081091NAXD
Contains IC: 18224A 21EG91NAXDL
24 VDC, P_n = 1.8 W



IP66
Type 4, 4X



WARNING - READ
MANUAL - DO NOT
CONNECT
OR DISCONNECT
WHEN ENERGIZED -
POTENTIAL
ELECTROSTATIC
CHARGING HAZARD
Electrical Shock
Hazard
Do not open while
powered



AVERTISSEMENT -
LIRE LE MANUEL - NE
PAS BRANCHER OU
DÉBRANCHER SOUS
TENSION - RISQUE
POTENTIEL DE
CHARGE
ÉLECTROSTATIQUE
Risque de choc
électrique
Ne pas ouvrir sous
tension