

FCC 47 CFR MPE REPORT

Beijing Visual World Technology Co.,Ltd.

360 Smart Camera

Model Number: D503

FCC ID: 2AIV9D503

Prepared for : Beijing Visual World Technology Co.,Ltd.

15th Floor and 17th Floor 1701-10A, Building 3, No. 10,
Jiuxianqiao Road Jia, Chaoyang District, Beijing.

Prepared By : EST Technology Co., Ltd.

San Tun Management Zone, Houjie District, Dongguan, China

Tel: 86-769-83081888-808

Report Number: ESTE-R1606050

Date of Test : June 01~ 28, 2016

Date of Report : June 28, 2016

Maximum Permissible Exposure

1、Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a)、Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b)、Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

2、MPE Calculation Method

$$E \text{ (V/m)} = (30 \cdot P \cdot G)^{0.5} / d \quad \text{Power Density: } P_d \text{ (W/m}^2\text{)} = E^2 / 377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

3、Calculated Result and Limit

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain		Power Density (S) (mW /cm2)	Limited of Power Density (S) (mW /cm2)	Test Result
					(dBi)	(Linear)			
IEEE 802.11b	2412	11.93	15.59553	11 ± 2	2.73	1.875	0.00744	1	Compiles
	2442	12.82	19.14256	12 ± 2	2.73	1.875	0.00937	1	Compiles
	2472	13.52	22.49055	13 ± 2	2.73	1.875	0.01180	1	Compiles
IEEE 802.11g	2412	10.62	11.53453	10 ± 2	2.73	1.875	0.00591	1	Compiles
	2442	11.25	13.33521	11 ± 2	2.73	1.875	0.00744	1	Compiles
	2472	12.36	17.21869	12 ± 2	2.73	1.875	0.00937	1	Compiles
IEEE 802.11n HT20	2412	10.43	11.04079	10 ± 2	2.73	1.875	0.00591	1	Compiles
	2442	11.77	15.03142	11 ± 2	2.73	1.875	0.00744	1	Compiles
	2472	12.30	16.98244	12 ± 2	2.73	1.875	0.00937	1	Compiles
IEEE 802.11n HT40	2422	9.57	9.057326	9 ± 2	2.73	1.875	0.00470	1	Compiles
	2442	10.09	10.20939	10 ± 2	2.73	1.875	0.00591	1	Compiles
	2462	11.08	12.82331	11 ± 2	2.73	1.875	0.00744	1	Compiles