

RF Exposure Requirements

Product Description: wireless microphone

Model No.: WM1201, RC-U8009, RC-U2000, RC-U5010, RC-U5008, RC-U6700, RC-U6500,
RC-U9001, RC-U3001, RC-U300

FCC ID: 2AIXFWM1201

According to the KDB 447498 D01 v06 section 4.3.1, for 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz

- Power and distance are rounded to the nearest mW and mm before calculation¹⁷

- The result is rounded to one decimal place for comparison

Calculation Result:

Tx frequency range: 618.3MHz

Device category: Portable device (Distance: 5mm)

Maximum Conducted Output Power: 7.492dBm

Tune-Up output power: 8.0dBm

RF channel transmit frequency: 618.3MHz

Result: 0.992

Limit: 3.0

The exclusion thresholds is $0.992 < 3$, so the transmitter complies with the RF exposure requirements and the SAR is not required.