

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is a controller operating at 2.4G Band. The EUT can be powered by DC 3.0V (2 x 1.5V AAA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna

Modulation Type: GFSK

Antenna Gain: 0.8dBi Max

The normal radiated output power (e.i.r.p) is: -17.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -17.8dBm (tolerance: +/- 3dB).

According to the KDB 447498 V06:

The Maximum peak radiated emission for the EUT is 78.6dBμV/m at 3m in the frequency 2441MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -16.63dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 75.6dBμV/m at 3m in the frequency 2479MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -19.63dBm

which is within the production variation.

The maximum conducted output average power specified is -14.8dBm= 0.033mW

The source- based time-averaging conducted output power
=0.033 mW

The SAR Exclusion Threshold Level:

= $3.0 \cdot (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in GHz})$

= $3.0 \cdot 5 / \text{sqrt}(2.479)$ mW

= 9.54 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.