



**中认信通**

CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



## TEST REPORT

**Applicant: INFINIX MOBILITY LIMITED.**

Address: FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25  
SHAN MEI STREET FOTAN NT HONGKONG

**FCC ID: 2AIZN-X6726B**

**Product Name: Mobile Phone**

**Standard(s): 47 CFR Part 15, Subpart E(15.407)**

**ANSI C63.10-2020**

**KDB 789033 D02 General U-NII Test Procedures New  
Rules v02r01**

The above device has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

**Report Number: 2503S20876E-RF-00D**

**Date Of Issue: 2025-05-20**

**Reviewed By: Calvin Chen**

Title: RF Engineer

**Approved By: Sun Zhong**

Title: Lab Manager

**Test Laboratory: China Certification ICT Co., Ltd (Dongguan)**

No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China

Tel: +86-769-83085888

[www.ccttt.com.cn](http://www.ccttt.com.cn)

**Test Facility**

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

**Declarations**

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

Each test item follows the test standard(s) without deviation.

# CONTENTS

|                                                                     |           |
|---------------------------------------------------------------------|-----------|
| <b>DOCUMENT REVISION HISTORY .....</b>                              | <b>5</b>  |
| <b>1. GENERAL INFORMATION .....</b>                                 | <b>6</b>  |
| <b>1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....</b> | <b>6</b>  |
| 1.1.1 General.....                                                  | 6         |
| 1.1.2 Operation Frequency Detail .....                              | 7         |
| 1.1.3 Antenna Information Detail▲ .....                             | 9         |
| 1.1.4 Accessory Information .....                                   | 9         |
| <b>1.2 DESCRIPTION OF TEST CONFIGURATION .....</b>                  | <b>10</b> |
| 1.2.1 EUT Operation Condition:.....                                 | 10        |
| 1.2.2 Support Equipment List and Details .....                      | 12        |
| 1.2.3 Support Cable List and Details .....                          | 12        |
| 1.2.4 Block Diagram of Test Setup.....                              | 12        |
| <b>1.3 MEASUREMENT UNCERTAINTY .....</b>                            | <b>13</b> |
| <b>2. SUMMARY OF TEST RESULTS .....</b>                             | <b>14</b> |
| <b>3. REQUIREMENTS AND TEST PROCEDURES .....</b>                    | <b>15</b> |
| <b>3.1 AC LINE CONDUCTED EMISSIONS .....</b>                        | <b>15</b> |
| 3.1.1 Applicable Standard.....                                      | 15        |
| 3.1.2 EUT Setup.....                                                | 16        |
| 3.1.3 EMI Test Receiver Setup .....                                 | 16        |
| 3.1.4 Test Procedure .....                                          | 17        |
| 3.1.5 Corrected Amplitude & Margin Calculation.....                 | 17        |
| <b>3.2 RADIATION SPURIOUS EMISSIONS .....</b>                       | <b>18</b> |
| 3.2.1 Applicable Standard.....                                      | 18        |
| 3.2.2 EUT Setup.....                                                | 19        |
| 3.2.3 EMI Test Receiver & Spectrum Analyzer Setup .....             | 20        |
| 3.2.4 Test Procedure .....                                          | 21        |
| 3.2.5 Corrected Amplitude & Margin Calculation.....                 | 21        |
| <b>3.3 EMISSION BANDWIDTH.....</b>                                  | <b>22</b> |
| 3.3.1 Applicable Standard.....                                      | 22        |
| 3.3.2 EUT Setup.....                                                | 22        |
| 3.3.3 Test Procedure .....                                          | 22        |
| <b>3.4 MAXIMUM CONDUCTED OUTPUT POWER.....</b>                      | <b>24</b> |
| 3.4.1 Applicable Standard.....                                      | 24        |
| 3.4.2 EUT Setup.....                                                | 24        |
| 3.4.3 Test Procedure .....                                          | 24        |
| <b>3.5 MAXIMUM POWER SPECTRAL DENSITY .....</b>                     | <b>26</b> |
| 3.5.1 Applicable Standard.....                                      | 26        |
| 3.5.2 EUT Setup.....                                                | 26        |
| 3.5.3 Test Procedure .....                                          | 27        |
| <b>3.6 DUTY CYCLE .....</b>                                         | <b>28</b> |
| 3.6.1 EUT Setup.....                                                | 28        |
| 3.6.2 Test Procedure .....                                          | 28        |
| <b>3.7 ANTENNA REQUIREMENT.....</b>                                 | <b>29</b> |
| 3.7.1 Applicable Standard.....                                      | 29        |
| 3.7.2 Judgment.....                                                 | 29        |
| <b>4. Test DATA AND RESULTS .....</b>                               | <b>30</b> |

**4.1 AC LINE CONDUCTED EMISSIONS ..... 30**

**4.2 RADIATION SPURIOUS EMISSIONS ..... 33**

    4.2.1 9 kHz – 1 GHz .....33

    4.2.2 1 GHz – 40 GHz: .....42

**4.3 RF CONDUCTED DATA ..... 179**

**5. EUT PHOTOGRAPHS ..... 180**

**6. TEST SETUP PHOTOGRAPHS ..... 181**

DOCUMENT REVISION HISTORY

| Revision Number | Report Number      | Description of Revision | Date of Revision |
|-----------------|--------------------|-------------------------|------------------|
| 1.0             | 2503S20876E-RF-00D | Original Report         | 2025-05-20       |

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment under Test (EUT)

#### 1.1.1 General

|                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>EUT Name:</b>                                                                                                                                                                                                                                                                                                                                                                       | Mobile Phone                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>EUT Model:</b>                                                                                                                                                                                                                                                                                                                                                                      | X6726B                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Operation Frequency:</b>                                                                                                                                                                                                                                                                                                                                                            | Band 1:<br>5180-5240 MHz (802.11a/n ht20/ac vht20)<br>5190-5230 MHz (802.11n ht40/ac vht40)<br>5210 MHz (802.11ac vht80)<br>Band 2:<br>5260-5320 MHz (802.11a/n ht20/ac vht20)<br>5270-5310 MHz(802.11n ht40/ac vht40)<br>5290 MHz (802.11ac vht80)<br>Band 3:<br>5500-5720 MHz (802.11a/n ht20/ac vht20)<br>5510-5710 MHz(802.11n ht40/ac vht40)<br>5530-5690 MHz(802.11ac vht80)<br>Band 4:<br>5745-5825 MHz (802.11a/n ht20/ac vht20)<br>5755-5795 MHz (802.11n ht40/ac vht40)<br>5775 MHz (802.11ac vht80) |
| <b>Maximum Average Conducted Output Power:</b>                                                                                                                                                                                                                                                                                                                                         | 12.77dBm in 5150-5250 MHz Band<br>12.97dBm in 5250-5350 MHz Band<br>12.91dBm in 5470-5725 MHz Band<br>9.62dBm in 5725-5850 MHz Band                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Modulation Type:</b>                                                                                                                                                                                                                                                                                                                                                                | 802.11a/n/ac: OFDM-BPSK, QPSK, 16QAM, 64QAM, 256QAM                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Rated Input Voltage:</b>                                                                                                                                                                                                                                                                                                                                                            | DC 3.91V from battery or DC 5.0V/7.5V from adapter                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Sample Number:</b>                                                                                                                                                                                                                                                                                                                                                                  | CE&RE:30YZ-1, 30YZ-3 RF: 30YZ-2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>EUT Received Date:</b>                                                                                                                                                                                                                                                                                                                                                              | 2025/4/3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>EUT Received Status:</b>                                                                                                                                                                                                                                                                                                                                                            | Good                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Note: The EUT has two configurations that Type 1 and Type 2 are electrically identical. Please refer to the declaration letter for more detail, which was provided by manufacturer. Per BT report test, conducted emissions test with Type 2 was the worst, and radiated emissions below 1 GHz test with Type 1 was the worst. Other test item only performs on Type 1 configurations. |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

### 1.1.2 Operation Frequency Detail

For 802.11a/n ht20/ac vht20:

| 5150-5250MHz Band |                 | 5250-5350 MHz Band |                 | 5470-5725 MHz Band |                 | 5725-5850MHz Band |                 |
|-------------------|-----------------|--------------------|-----------------|--------------------|-----------------|-------------------|-----------------|
| Channel           | Frequency (MHz) | Channel            | Frequency (MHz) | Channel            | Frequency (MHz) | Channel           | Frequency (MHz) |
| 36                | 5180            | 52                 | 5260            | 100                | 5500            | 149               | 5745            |
| 40                | 5200            | 56                 | 5280            | 104                | 5520            | 153               | 5765            |
| 44                | 5220            | 60                 | 5300            | 108                | 5540            | 157               | 5785            |
| 48                | 5240            | 64                 | 5320            | 112                | 5560            | 161               | 5805            |
| /                 | /               | /                  | /               | 116                | 5580            | 165               | 5825            |
| /                 | /               | /                  | /               | 120                | 5600            | /                 | /               |
| /                 | /               | /                  | /               | 124                | 5620            | /                 | /               |
| /                 | /               | /                  | /               | 128                | 5640            | /                 | /               |
| /                 | /               | /                  | /               | 132                | 5660            | /                 | /               |
| /                 | /               | /                  | /               | 136                | 5680            | /                 | /               |
| /                 | /               | /                  | /               | 140                | 5700            | /                 | /               |
| /                 | /               | /                  | /               | 144                | 5720            | /                 | /               |

Per section 15.31(m), the below channels were performed the test as below:

| Test Channel | Test Frequency (MHz) |               |               |               |
|--------------|----------------------|---------------|---------------|---------------|
|              | 5150-5250 MHz        | 5250-5350 MHz | 5470-5725 MHz | 5725-5850 MHz |
| Lowest       | 5180                 | 5260          | 5500          | 5745          |
| Middle       | 5200                 | 5280          | 5580          | 5785          |
| Highest      | 5240                 | 5320          | 5700          | 5825          |
| Additional   | /                    | /             | 5720          | /             |

**For 802.11n ht40/ac vht40:**

| 5150-5250MHz |                 | 5250-5350 MHz |                 | 5470-5725 MHz |                 | 5725-5850MHz |                 |
|--------------|-----------------|---------------|-----------------|---------------|-----------------|--------------|-----------------|
| Channel      | Frequency (MHz) | Channel       | Frequency (MHz) | Channel       | Frequency (MHz) | Channel      | Frequency (MHz) |
| 38           | 5190            | 54            | 5270            | 102           | 5510            | 151          | 5755            |
| 46           | 5230            | 62            | 5310            | 110           | 5550            | 159          | 5795            |
| /            | /               | /             | /               | 118           | 5590            | /            | /               |
| /            | /               | /             | /               | 126           | 5630            | /            | /               |
| /            | /               | /             | /               | 134           | 5670            | /            | /               |
| /            | /               | /             | /               | 142           | 5710            | /            | /               |

Per section 15.31(m), the below channels were performed the test as below:

| Test Channel | Test Frequency (MHz) |               |               |               |
|--------------|----------------------|---------------|---------------|---------------|
|              | 5150-5250 MHz        | 5250-5350 MHz | 5470-5725 MHz | 5725-5850 MHz |
| Lowest       | 5190                 | 5270          | 5510          | 5755          |
| Middle       | /                    | /             | 5550          | /             |
| Highest      | 5230                 | 5310          | 5670          | 5795          |
| Additional   | /                    | /             | 5710          | /             |

**For 802.11ac vht80:**

| 5150-5250MHz |                 | 5250-5350 MHz |                 | 5470-5725 MHz |                 | 5725-5850MHz |                 |
|--------------|-----------------|---------------|-----------------|---------------|-----------------|--------------|-----------------|
| Channel      | Frequency (MHz) | Channel       | Frequency (MHz) | Channel       | Frequency (MHz) | Channel      | Frequency (MHz) |
| 42           | 5210            | 58            | 5290            | 106           | 5530            | 155          | 5775            |
| /            | /               | /             | /               | 122           | 5610            | /            | /               |
| /            | /               | /             | /               | 138           | 5690            | /            | /               |

Per section 15.31(m), the below channels were performed the test as below:

| Test Channel | Test Frequency (MHz) |               |               |               |
|--------------|----------------------|---------------|---------------|---------------|
|              | 5150-5250 MHz        | 5250-5350 MHz | 5470-5725 MHz | 5725-5850 MHz |
| Lowest       | /                    | /             | 5530          | /             |
| Middle       | 5210                 | 5290          | /             | 5775          |
| Highest      | /                    | /             | 5610          | /             |
| Additional   | /                    | /             | 5690          | /             |

Note: Additional channels cross the band 5470-5725MHz and 5725-5850 MHz, Conducted output power/ Power Spectral Density/bandwidth test with the additional channel to compliance with stricter limit of the two bands(5470-5725MHz more stricter).

**1.1.3 Antenna Information Detail ▲**

| Antenna                                                                                                                                                                                                                                                                                                                                                                              | Antenna Type | input impedance (Ohm) | Frequency Range | Antenna Gain (dBi) |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-----------------------|-----------------|--------------------|
| ANT12                                                                                                                                                                                                                                                                                                                                                                                | FPC          | 50                    | 5.15~5.85GHz    | -2.06              |
| The Method of §15.203 Compliance:<br><input checked="" type="checkbox"/> Antenna was permanently attached to the unit.<br><input type="checkbox"/> Antenna uses a unique type of connector to attach to the EUT.<br><input type="checkbox"/> Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit. |              |                       |                 |                    |

**1.1.4 Accessory Information**

| Accessory Description | Manufacturer | Model   |
|-----------------------|--------------|---------|
| Adapter               | Infinix      | U180XSA |
| Earphone              | Infinix      | Unknown |

## 1.2 Description of Test Configuration

### 1.2.1 EUT Operation Condition:

|                                                                                                                                 |                                                                                                    |                             |                  |                            |
|---------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|-----------------------------|------------------|----------------------------|
| <b>EUT Operation Mode:</b>                                                                                                      | The system was configured for testing in Engineering Mode, which was provided by the manufacturer. |                             |                  |                            |
| <b>Equipment Modifications:</b>                                                                                                 | No                                                                                                 |                             |                  |                            |
| <b>EUT Exercise Software:</b>                                                                                                   | Engineer mode                                                                                      |                             |                  |                            |
| The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer ▲ : |                                                                                                    |                             |                  |                            |
| <b>5150-5250 MHz Band:</b>                                                                                                      |                                                                                                    |                             |                  |                            |
| <b>Test Modes</b>                                                                                                               | <b>Test Channels</b>                                                                               | <b>Test Frequency (MHz)</b> | <b>Data rate</b> | <b>Power Level Setting</b> |
| 802.11a                                                                                                                         | Lowest                                                                                             | 5180                        | 6Mbps            | 13.5                       |
|                                                                                                                                 | Middle                                                                                             | 5200                        | 6Mbps            | 13.5                       |
|                                                                                                                                 | Highest                                                                                            | 5240                        | 6Mbps            | 13.5                       |
| 802.11n ht20                                                                                                                    | Lowest                                                                                             | 5180                        | MCS0             | 13.5                       |
|                                                                                                                                 | Middle                                                                                             | 5200                        | MCS0             | 13.5                       |
|                                                                                                                                 | Highest                                                                                            | 5240                        | MCS0             | 13.5                       |
| 802.11n ht40                                                                                                                    | Lowest                                                                                             | 5190                        | MCS0             | 13.5                       |
|                                                                                                                                 | Highest                                                                                            | 5230                        | MCS0             | 13.5                       |
| 802.11ac vht80                                                                                                                  | Middle                                                                                             | 5210                        | MCS0             | 13.5                       |
| <b>5250-5350 MHz Band:</b>                                                                                                      |                                                                                                    |                             |                  |                            |
| <b>Test Modes</b>                                                                                                               | <b>Test Channels</b>                                                                               | <b>Test Frequency (MHz)</b> | <b>Data rate</b> | <b>Power Level Setting</b> |
| 802.11a                                                                                                                         | Lowest                                                                                             | 5260                        | 6Mbps            | 13.5                       |
|                                                                                                                                 | Middle                                                                                             | 5280                        | 6Mbps            | 13.5                       |
|                                                                                                                                 | Highest                                                                                            | 5320                        | 6Mbps            | 13.5                       |
| 802.11n ht20                                                                                                                    | Lowest                                                                                             | 5260                        | MCS0             | 13.5                       |
|                                                                                                                                 | Middle                                                                                             | 5280                        | MCS0             | 13.5                       |
|                                                                                                                                 | Highest                                                                                            | 5320                        | MCS0             | 13.5                       |
| 802.11n ht40                                                                                                                    | Lowest                                                                                             | 5270                        | MCS0             | 13.5                       |
|                                                                                                                                 | Highest                                                                                            | 5310                        | MCS0             | 13.5                       |
| 802.11ac vht80                                                                                                                  | Middle                                                                                             | 5290                        | MCS0             | 13.5                       |

| 5470-5725 MHz Band:                                                                                                                                                                                                                                                                                                                                                                 |               |                      |           |                     |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|----------------------|-----------|---------------------|
| Test Modes                                                                                                                                                                                                                                                                                                                                                                          | Test Channels | Test Frequency (MHz) | Data rate | Power Level Setting |
| 802.11a                                                                                                                                                                                                                                                                                                                                                                             | Lowest        | 5500                 | 6Mbps     | 13                  |
|                                                                                                                                                                                                                                                                                                                                                                                     | Middle        | 5580                 | 6Mbps     | 13                  |
|                                                                                                                                                                                                                                                                                                                                                                                     | Highest       | 5700                 | 6Mbps     | 13                  |
|                                                                                                                                                                                                                                                                                                                                                                                     | Cross         | 5720                 | 6Mbps     | 13                  |
| 802.11n ht20                                                                                                                                                                                                                                                                                                                                                                        | Lowest        | 5500                 | MCS0      | 13                  |
|                                                                                                                                                                                                                                                                                                                                                                                     | Middle        | 5580                 | MCS0      | 13                  |
|                                                                                                                                                                                                                                                                                                                                                                                     | Highest       | 5700                 | MCS0      | 13                  |
|                                                                                                                                                                                                                                                                                                                                                                                     | Cross         | 5720                 | MCS0      | 13                  |
| 802.11n ht40                                                                                                                                                                                                                                                                                                                                                                        | Lowest        | 5510                 | MCS0      | 13                  |
|                                                                                                                                                                                                                                                                                                                                                                                     | Highest       | 5550                 | MCS0      | 13                  |
|                                                                                                                                                                                                                                                                                                                                                                                     | Lowest        | 5670                 | MCS0      | 13                  |
|                                                                                                                                                                                                                                                                                                                                                                                     | Cross         | 5710                 | MCS0      | 13                  |
| 802.11ac vht80                                                                                                                                                                                                                                                                                                                                                                      | Lowest        | 5530                 | MCS0      | 13                  |
|                                                                                                                                                                                                                                                                                                                                                                                     | Highest       | 5610                 | MCS0      | 13                  |
|                                                                                                                                                                                                                                                                                                                                                                                     | Cross         | 5690                 | MCS0      | 13                  |
| 5725-5850 MHz Band:                                                                                                                                                                                                                                                                                                                                                                 |               |                      |           |                     |
| Test Modes                                                                                                                                                                                                                                                                                                                                                                          | Test Channels | Test Frequency (MHz) | Data rate | Power Level Setting |
| 802.11a                                                                                                                                                                                                                                                                                                                                                                             | Lowest        | 5745                 | 6Mbps     | 10                  |
|                                                                                                                                                                                                                                                                                                                                                                                     | Middle        | 5785                 | 6Mbps     | 10                  |
|                                                                                                                                                                                                                                                                                                                                                                                     | Highest       | 5825                 | 6Mbps     | 10                  |
| 802.11n ht20                                                                                                                                                                                                                                                                                                                                                                        | Lowest        | 5745                 | MCS0      | 10                  |
|                                                                                                                                                                                                                                                                                                                                                                                     | Middle        | 5785                 | MCS0      | 10                  |
|                                                                                                                                                                                                                                                                                                                                                                                     | Highest       | 5825                 | MCS0      | 10                  |
| 802.11n ht40                                                                                                                                                                                                                                                                                                                                                                        | Lowest        | 5755                 | MCS0      | 10                  |
|                                                                                                                                                                                                                                                                                                                                                                                     | Highest       | 5795                 | MCS0      | 10                  |
| 802.11ac vht80                                                                                                                                                                                                                                                                                                                                                                      | Middle        | 5775                 | MCS0      | 10                  |
| <p>Note:</p> <p>1.The system support 802.11a/n ht20/n ht40/ac vht20/vht40/vht80, the vht20/vht40 were reduced since the identical parameters with 802.11n ht20/ht40.</p> <p>2. The above are the worst-case data rates, which are determined for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations.</p> |               |                      |           |                     |

### 1.2.2 Support Equipment List and Details


| Manufacturer | Description | Model   | Serial Number |
|--------------|-------------|---------|---------------|
| Infinix      | Adapter     | U180XSA | CY07018464C13 |
| Infinix      | Earphone    | Unknown | Unknown       |

### 1.2.3 Support Cable List and Details


| Cable Description | Shielding Type | Ferrite Core | Length (m) | From Port | To       |
|-------------------|----------------|--------------|------------|-----------|----------|
| USB Cable         | No             | No           | 0.8        | Adapter   | EUT      |
| Earphone Cable    | No             | No           | 1.2        | EUT       | Earphone |

### 1.2.4 Block Diagram of Test Setup

AC line conducted emissions:



Spurious Emissions:



### 1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

| Parameter                         | Measurement Uncertainty                                                                                                                      |
|-----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| Occupied Channel Bandwidth        | ±5 %                                                                                                                                         |
| RF output power, conducted        | ±0.61dB                                                                                                                                      |
| Power Spectral Density, conducted | ±0.61 dB                                                                                                                                     |
| Unwanted Emissions, radiated      | 9k~30MHz: 4.12dB, 30M~200MHz: 4.15 dB,<br>200M~1GHz: 5.61 dB, 1G~6GHz: 5.14 dB,<br>6G~18GHz: 5.93 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB |
| Unwanted Emissions, conducted     | ±1.26 dB                                                                                                                                     |
| Temperature                       | ±1℃                                                                                                                                          |
| Humidity                          | ±5%                                                                                                                                          |
| DC and low frequency voltages     | ±0.4%                                                                                                                                        |
| Duty Cycle                        | 1%                                                                                                                                           |
| AC Power Lines Conducted Emission | 2.8 dB (150 kHz to 30 MHz)                                                                                                                   |

## 2. SUMMARY OF TEST RESULTS

| FCC Rules         | Description of Test                    | Result    |
|-------------------|----------------------------------------|-----------|
| FCC §15.203       | Antenna Requirement                    | Compliant |
| FCC §15.207(a)    | AC Line Conducted Emissions            | Compliant |
| FCC §15.407(b)    | Undesirable Emission& Restricted Bands | Compliant |
| FCC§15.407(a) (e) | Emission Bandwidth                     | Compliant |
| FCC§15.407(a) (e) | 99% Occupied Bandwidth                 | Compliant |
| FCC§15.407 (a)    | Maximum Conducted Output Power         | Compliant |
| FCC§15.407 (a)    | Power Spectral Density                 | Compliant |

### 3. REQUIREMENTS AND TEST PROCEDURES

#### 3.1 AC Line Conducted Emissions

##### 3.1.1 Applicable Standard

FCC §15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

| Frequency of emission (MHz) | Conducted limit (dB $\mu$ V) |           |
|-----------------------------|------------------------------|-----------|
|                             | Quasi-peak                   | Average   |
| 0.15-0.5                    | 66 to 56*                    | 56 to 46* |
| 0.5-5                       | 56                           | 46        |
| 5-30                        | 60                           | 50        |

\*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:


(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000  $\mu$ V within the frequency band 535-1705 kHz, as measured using a 50  $\mu$ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

### 3.1.2 EUT Setup



Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

### 3.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range  | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz  |

### 3.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

### 3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

## 3.2 Radiation Spurious Emissions

### 3.2.1 Applicable Standard


FCC §15.407 (b)

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:


- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating solely in the 5.725-5.850 GHz band:
  - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
  - (ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in § 15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in § 15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.
- (8) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.
- (9) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in § 15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in § 15.207.
- (10) The provisions of § 15.205 apply to intentional radiators operating under this section.
- (11) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency band edges as the design of the equipment permits.
- (c) The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization a description of how this requirement is met.

### 3.2.2 EUT Setup


9kHz - 30MHz:




30MHz - 1GHz:



1GHz - 26.5GHz:



**26.5GHz - 40 GHz:**

The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2020. The specification used was FCC 15.209, FCC 15.407 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

**3.2.3 EMI Test Receiver & Spectrum Analyzer Setup**

The system was investigated from 9 kHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

| Frequency Range  | RBW     | Video B/W | IF B/W | Detector               | Measurement |
|------------------|---------|-----------|--------|------------------------|-------------|
| 9 kHz – 150 kHz  | 300 Hz  | 1 kHz     | /      | Peak                   | PK          |
|                  | /       | /         | 200 Hz | Quasi Peak/<br>Average | QP/AV       |
| 150 kHz – 30 MHz | 10 kHz  | 30 kHz    | /      | Peak                   | PK          |
|                  | /       | /         | 9 kHz  | Quasi Peak/<br>Average | QP/AV       |
| 30MHz – 1000 MHz | 100 kHz | 300 kHz   | /      | Peak                   | PK          |
|                  | /       | /         | 120kHz | Quasi Peak             | QP          |

**1GHz- 40GHz:**

Pre-scan:

| Measurement | Duty cycle | RBW  | Video B/W                        | Detector |
|-------------|------------|------|----------------------------------|----------|
| PK          | Any        | 1MHz | 3 MHz                            | Peak     |
| Ave.        | >98%       | 1MHz | 5 kHz                            | Peak     |
|             | <98%       | 1MHz | $\geq 1/T$ , not less than 5 kHz | Peak     |

Note: T is minimum transmission duration

Final measurement for emission identified during the pre-scan:

| Measurement | Duty cycle | RBW  | Video B/W  | Detector |
|-------------|------------|------|------------|----------|
| PK          | Any        | 1MHz | 3 MHz      | Peak     |
| Ave.        | >98%       | 1MHz | 10 Hz      | Peak     |
|             | <98%       | 1MHz | $\geq 1/T$ | Peak     |

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

### 3.2.4 Test Procedure

Data was recorded in Quasi-peak detection mode for frequency range of 9 kHz-1 GHz except 9–90 kHz, 110–490 kHz, employing an average detector, peak and Average detection modes for frequencies above 1 GHz.

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, emission shall be computed as:  $E [dB\mu V/m] = EIRP[dBm] + 95.2$ , for  $d = 3$  meters.

According to C63.10, the above 1G test result shall be extrapolated to the specified distance using an extrapolation Factor of 20dB/decade from 3m to 1.5m

Distance extrapolation Factor =  $20 \log (\text{specific distance } [3m] / \text{test distance } [1.5m])$  dB = 6.02 dB

All emissions under the average limit and under the noise floor have not recorded in the report.

### 3.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

For 9kHz-26.5GHz:

Factor = Antenna Factor + Cable Loss- Amplifier Gain

For 26.5GHz-40GHz

Factor = Antenna Factor + Cable Loss- Amplifier Gain -Distance extrapolation Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

### 3.3 Emission Bandwidth

#### 3.3.1 Applicable Standard


FCC §15.407 (a), (h)

(h)(2) Radar Detection Function of Dynamic Frequency Selection (DFS). U-NII devices operating with any part of its 26 dB emission bandwidth in the 5.25-5.35 GHz and 5.47-5.725 GHz bands shall employ a DFS radar detection mechanism to detect the presence of radar systems and to avoid co-channel operation with radar systems.

FCC §15.407 (e)

Within the 5.725-5.850 GHz and 5.850-5.895 GHz bands, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

#### 3.3.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, the insert loss of this RF cable/attenuator was offset into the setting of test equipment.

#### 3.3.3 Test Procedure

##### 26dB Emission Bandwidth:

According to ANSI C63.10-2020 Section 12.5.2

- Set RBW = shall be in the range of 1% to 5% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = peak.
- Trace mode = max-hold.
- Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is in the range of 1% to 5%.

##### 6 dB emission bandwidth:

According to ANSI C63.10-2020 Section 12.5.1

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- Detector = Peak.
- Trace mode = max-hold.
- Sweep = No faster than coupled (auto) time.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 Db relative to the maximum level measured in the fundamental emission.

**99% Occupied Bandwidth:**

According to ANSI C63.10-2020 Section 12.5.3&6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be at least three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than  $[10 \log (OBW/RBW)]$  below the reference level. Specific guidance is given in 4.1.6.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max-hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing spectral plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

### 3.4 Maximum Conducted Output Power

#### 3.4.1 Applicable Standard

##### FCC §15.407(a) (1)(iv)

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


##### FCC §15.407(a) (2)

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or  $11 \text{ dBm} + 10 \log B$ , where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

##### FCC §15.407(a) (3)(i)

For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

#### 3.4.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, the insert loss of this RF cable/attenuator was offset into the setting of test equipment.

#### 3.4.3 Test Procedure

According to ANSI C63.10-2020 Section 12.4.3.2

Method PM-G is measurement using a gated RF average power meter.

Measurements may be performed using a wideband gated RF power meter provided that the gate

parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

### 3.5 Maximum Power Spectral Density

#### 3.5.1 Applicable Standard

##### FCC §15.407(a) (1)(iv)

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


##### FCC §15.407(a) (2)

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or  $11 \text{ dBm} + 10 \log B$ , where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

##### FCC §15.407(a) (3)(i)

For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

#### 3.5.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, the insert loss of this RF cable/attenuator was offset into the setting of test equipment.

### 3.5.3 Test Procedure

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01

**Duty cycle  $\geq 98\%$**

KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-1 should be applied.

**Duty cycle  $< 98\%$ , duty cycle variations are less than  $\pm 2\%$**


KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-2 should be applied.

**Duty cycle  $< 98\%$ , duty cycle variations exceed  $\pm 2\%$**

KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-3 should be applied.

### 3.6 Duty Cycle

#### 3.6.1 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, the insert loss of this RF cable/attenuator was offset into the setting of test equipment.

#### 3.6.2 Test Procedure

According to ANSI C63.10-2020 Section 12.2

The zero-span mode on a spectrum analyzer or EMI receiver, if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- i) Set the center frequency of the instrument to the center frequency of the transmission.
- ii) Set  $RBW \geq EBW$  if possible; otherwise, set RBW to the largest available value.
- iii) Set  $VBW \geq RBW$ .
- iv) Set detector = peak.
- v) The zero-span measurement method shall not be used unless both RBW and VBW are  $> 50/T$ , where T is defined in item a1) of 12.2, and the number of sweep points across duration T exceeds 100. For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if  $T \leq 16.7\mu s$ .

### **3.7 Antenna Requirement**

#### **3.7.1 Applicable Standard**

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

#### **3.7.2 Judgment**

**Result: Compliant.** Please refer to the Antenna Information detail in Section 1.

4. Test DATA AND RESULTS

4.1 AC Line Conducted Emissions

|                |             |              |                                                                     |
|----------------|-------------|--------------|---------------------------------------------------------------------|
| Sample Number: | 30YZ-3      | Test Date:   | 2025/5/7                                                            |
| Test Site:     | CE          | Test Mode:   | Transmitting (maximum conducted output power mode 802.11a 5320 MHz) |
| Tester:        | David Huang | Test Result: | Pass                                                                |

Environmental Conditions:


|                      |      |                           |    |                        |       |
|----------------------|------|---------------------------|----|------------------------|-------|
| Temperature:<br>(°C) | 25.1 | Relative Humidity:<br>(%) | 44 | ATM Pressure:<br>(kPa) | 100.4 |
|----------------------|------|---------------------------|----|------------------------|-------|

Test Equipment List and Details:

| Manufacturer | Description       | Model   | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|---------|---------------|------------------|----------------------|
| R&S          | LISN              | ENV216  | 101132        | 2025/3/31        | 2026/3/30            |
| R&S          | EMI Test Receiver | ESR3    | 103104        | 2024/5/10        | 2025/5/9             |
| MICRO-COAX   | Coaxial Cable     | UTIFLEX | C-0200-01     | 2025/1/6         | 2026/1/5             |
| Audix        | Test Software     | E3      | 191218 (V9)   | N/A              | N/A                  |


*\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Project No.: 2503S20876E-RF  
Tester: David Huang  
Condition: IFBW:9 kHz Meas Time:0.025sec  
Port: Line  
Note: Transmitting 5G WIFI



| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB) | Result (dBμV) | Limit (dBμV) | Margin (dB) | Detector |
|-----|-----------------|----------------|-------------|---------------|--------------|-------------|----------|
| 1   | 0.180           | 25.22          | 10.45       | 35.67         | 64.46        | 28.79       | QP       |
| 2   | 0.180           | 10.22          | 10.45       | 20.67         | 54.46        | 33.79       | Average  |
| 3   | 0.556           | 37.53          | 10.41       | 47.94         | 56.00        | 8.06        | QP       |
| 4   | 0.556           | 26.41          | 10.41       | 36.82         | 46.00        | 9.18        | Average  |
| 5   | 1.485           | 32.22          | 10.33       | 42.55         | 56.00        | 13.45       | QP       |
| 6   | 1.485           | 24.83          | 10.33       | 35.16         | 46.00        | 10.84       | Average  |
| 7   | 7.696           | 28.35          | 10.41       | 38.76         | 60.00        | 21.24       | QP       |
| 8   | 7.696           | 17.86          | 10.41       | 28.27         | 50.00        | 21.73       | Average  |
| 9   | 9.177           | 33.14          | 10.26       | 43.40         | 60.00        | 16.60       | QP       |
| 10  | 9.177           | 22.80          | 10.26       | 33.06         | 50.00        | 16.94       | Average  |
| 11  | 19.079          | 24.30          | 9.86        | 34.16         | 60.00        | 25.84       | QP       |
| 12  | 19.079          | 14.61          | 9.86        | 24.47         | 50.00        | 25.53       | Average  |

Project No.: 2503S20876E-RF  
Tester: David Huang  
Condition: IFBW:9 kHz Meas Time:0.025sec  
Port: neutral  
Note: Transmitting 5G WIFI



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Result (dBuV) | Limit (dBuV) | Margin (dB) | Detector |
|-----|-----------------|----------------|-------------|---------------|--------------|-------------|----------|
| 1   | 0.162           | 23.91          | 10.26       | 34.17         | 65.39        | 31.22       | QP       |
| 2   | 0.162           | 8.82           | 10.26       | 19.08         | 55.39        | 36.31       | Average  |
| 3   | 0.339           | 24.37          | 10.41       | 34.78         | 59.23        | 24.45       | QP       |
| 4   | 0.339           | 13.65          | 10.41       | 24.06         | 49.23        | 25.17       | Average  |
| 5   | 0.557           | 35.94          | 10.32       | 46.26         | 56.00        | 9.74        | QP       |
| 6   | 0.557           | 23.84          | 10.32       | 34.16         | 46.00        | 11.84       | Average  |
| 7   | 0.701           | 21.42          | 10.11       | 31.53         | 56.00        | 24.47       | QP       |
| 8   | 0.701           | 9.42           | 10.11       | 19.53         | 46.00        | 26.47       | Average  |
| 9   | 1.485           | 29.51          | 10.42       | 39.93         | 56.00        | 16.07       | QP       |
| 10  | 1.485           | 22.23          | 10.42       | 32.65         | 46.00        | 13.35       | Average  |
| 11  | 9.134           | 32.44          | 10.35       | 42.79         | 60.00        | 17.21       | QP       |
| 12  | 9.134           | 21.80          | 10.35       | 32.15         | 50.00        | 17.85       | Average  |

## 4.2 Radiation Spurious Emissions

### 4.2.1 9 kHz – 1 GHz

|                |           |              |              |
|----------------|-----------|--------------|--------------|
| Sample Number: | 30YZ-1    | Test Date:   | 2025/4/14    |
| Test Site:     | 966-2     | Test Mode:   | Transmitting |
| Tester:        | Roinin Fu | Test Result: | Pass         |

#### Environmental Conditions:

|                      |      |                           |    |                           |       |
|----------------------|------|---------------------------|----|---------------------------|-------|
| Temperature:<br>(°C) | 25.3 | Relative Humidity:<br>(%) | 54 | ATM<br>Pressure:<br>(kPa) | 101.4 |
|----------------------|------|---------------------------|----|---------------------------|-------|

#### Test Equipment List and Details:


| Manufacturer    | Description       | Model                 | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-------------------|-----------------------|---------------|------------------|----------------------|
| Sunol Sciences  | Antenna           | JB6                   | A082520-5     | 2023/12/1        | 2026/11/30           |
| BACL            | Loop Antenna      | 1313-1A               | 3110611       | 2023/12/4        | 2026/12/3            |
| Daruikang       | Coaxial Cable     | BNC-JJ-RG58           | C-0300-01     | 2025/1/10        | 2026/1/9             |
| Daruikang       | Coaxial Cable     | BNC-JJ-RG58           | C-0500-01     | 2025/1/10        | 2026/1/9             |
| R&S             | EMI Test Receiver | ESR3                  | 102724        | 2025/2/14        | 2026/2/13            |
| TIMES MICROWAVE | Coaxial Cable     | LMR-600-UltraFlex     | C-0100-03     | 2024/12/3        | 2025/12/2            |
| TIMES MICROWAVE | Coaxial Cable     | LMR-600-UltraFlex     | C-0370-01     | 2024/12/3        | 2025/12/2            |
| XQY             | Coaxial Cable     | XQY-CMR400UF-NJ-NJ-7M | 24056379      | 2024/6/11        | 2025/6/10            |
| Sonoma          | Amplifier         | 310N                  | 186165        | 2024/12/3        | 2025/12/2            |
| Audix           | Test Software     | E3                    | 191218 (V9)   | N/A              | N/A                  |

\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

#### Test Data:


After pre-scan in the X, Y and Z axes of orientation, the worst case is refer to plots.

Project No.: 2503S20876E-RF  
Tester: Roinin Fu  
Condition: RBW:0.3 kHz VBW:1 kHz SWT:0.1 sec  
Polarization: Parallel  
Note: Transmitting Part 15.407\_WIFI




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 0.009              | 29.26             | 35.36            | 64.62              | 128.25            | 63.63          | Peak   |
| 2   | 0.015              | 31.16             | 31.88            | 63.04              | 123.95            | 60.91          | Peak   |
| 3   | 0.024              | 25.30             | 27.53            | 52.83              | 119.97            | 67.14          | Peak   |
| 4   | 0.036              | 27.74             | 23.40            | 51.14              | 116.50            | 65.36          | Peak   |
| 5   | 0.060              | 36.62             | 19.01            | 55.63              | 111.98            | 56.35          | Peak   |
| 6   | 0.108              | 27.07             | 14.30            | 41.37              | 106.97            | 65.60          | Peak   |

Project No.: 2503S20876E-RF  
 Tester: Roinin Fu  
 Condition: RBW:10 kHz VBW:30 kHz SWT:0.1 sec  
 Polarization: Parallel  
 Note: Transmitting Part 15.407\_WIFI




| No.   | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Remark |
|-------|-----------------|----------------|---------------|-----------------|----------------|-------------|--------|
| <hr/> |                 |                |               |                 |                |             |        |
| 1     | 0.164           | 36.91          | 11.67         | 48.58           | 103.30         | 54.72       | Peak   |
| 2     | 0.222           | 37.37          | 8.98          | 46.35           | 100.68         | 54.33       | Peak   |
| 3     | 0.343           | 38.54          | 4.43          | 42.97           | 96.90          | 53.93       | Peak   |
| 4     | 0.532           | 38.42          | 0.59          | 39.01           | 73.07          | 34.06       | Peak   |
| 5     | 2.721           | 31.92          | -8.14         | 23.78           | 69.54          | 45.76       | Peak   |
| 6     | 27.855          | 40.83          | -7.40         | 33.43           | 69.54          | 36.11       | Peak   |

Project No.: 2503S20876E-RF  
Tester: Roinin Fu  
Condition: RBW:0.3 kHz VBW:1 kHz SWT:0.1 sec  
Polarization: Perpendicular  
Note: Transmitting Part 15.407\_WIFI




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 0.010              | 30.83             | 34.75            | 65.58              | 127.81            | 62.23          | Peak   |
| 2   | 0.013              | 29.70             | 33.11            | 62.81              | 125.51            | 62.70          | Peak   |
| 3   | 0.016              | 30.35             | 31.38            | 61.73              | 123.39            | 61.66          | Peak   |
| 4   | 0.024              | 29.08             | 27.57            | 56.65              | 119.99            | 63.34          | Peak   |
| 5   | 0.059              | 35.92             | 19.22            | 55.14              | 112.20            | 57.06          | Peak   |
| 6   | 0.110              | 27.52             | 14.17            | 41.69              | 106.75            | 65.06          | Peak   |

Project No.: 2503S20876E-RF  
 Tester: Roinin Fu  
 Condition: RBW:10 kHz VBW:30 kHz SWT:0.1 sec  
 Polarization: Perpendicular  
 Note: Transmitting Part 15.407\_WIFI




| No.   | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-------|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| <hr/> |                    |                   |                  |                    |                   |                |        |
| 1     | 0.166              | 35.95             | 11.59            | 47.54              | 103.21            | 55.67          | Peak   |
| 2     | 0.202              | 37.75             | 9.92             | 47.67              | 101.51            | 53.84          | Peak   |
| 3     | 0.337              | 38.22             | 4.55             | 42.77              | 97.04             | 54.27          | Peak   |
| 4     | 0.608              | 38.72             | -0.27            | 38.45              | 71.89             | 33.44          | Peak   |
| 5     | 1.282              | 33.27             | -5.20            | 28.07              | 65.27             | 37.20          | Peak   |
| 6     | 29.527             | 40.93             | -7.14            | 33.79              | 69.54             | 35.75          | Peak   |

Project No.: 2503S20876E-RF  
 Tester: Roinin Fu  
 Condition: RBW:0.3 kHz VBW:1 kHz SWT:0.1 sec  
 Polarization: Ground-parallel  
 Note: Transmitting Part 15.407\_WIFI




| No.   | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-------|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| <hr/> |                    |                   |                  |                    |                   |                |        |
| 1     | 0.010              | 28.05             | 34.92            | 62.97              | 127.93            | 64.96          | Peak   |
| 2     | 0.012              | 30.14             | 33.53            | 63.67              | 126.13            | 62.46          | Peak   |
| 3     | 0.015              | 30.94             | 31.90            | 62.84              | 123.97            | 61.13          | Peak   |
| 4     | 0.036              | 24.99             | 23.40            | 48.39              | 116.50            | 68.11          | Peak   |
| 5     | 0.059              | 35.73             | 19.26            | 54.99              | 112.24            | 57.25          | Peak   |
| 6     | 0.110              | 24.53             | 14.20            | 38.73              | 106.79            | 68.06          | Peak   |

Project No.: 2503S20876E-RF  
Tester: Roinin Fu  
Condition: RBW:10 kHz VBW:30 kHz SWT:0.1 sec  
Polarization: Ground-parallel  
Note: Transmitting Part 15.407\_WIFI




| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|--------|
| 1   | 0.184           | 37.50          | 10.72         | 48.22           | 102.29         | 54.07       | Peak   |
| 2   | 0.272           | 39.27          | 6.68          | 45.95           | 98.93          | 52.98       | Peak   |
| 3   | 0.529           | 39.30          | 0.63          | 39.93           | 73.11          | 33.18       | Peak   |
| 4   | 1.172           | 36.45          | -4.81         | 31.64           | 66.07          | 34.43       | Peak   |
| 5   | 5.362           | 32.46          | -8.89         | 23.57           | 69.54          | 45.97       | Peak   |
| 6   | 29.371          | 40.83          | -7.17         | 33.66           | 69.54          | 35.88       | Peak   |

Project No.: 2503S20876E-RF  
Tester: Roinin Fu  
Condition: RBW:100 kHz VBW:300 kHz SWT:0.1 sec  
Polarization: horizontal  
Note: Transmitting Part 15.407\_WIFI



Project No.: 2503S20876E-RF  
 Tester: Roinin Fu  
 Condition: RBW:100 kHz VBW:300 kHz SWT:0.1 sec  
 Polarization: vertical  
 Note: Transmitting Part 15.407\_WIFI



| No.   | Frequency<br>(MHz) | Reading<br>(dBUV) | Factor<br>(dB/m) | Result<br>(dBUV/m) | Limit<br>(dBUV/m) | Margin<br>(dB) | Remark |
|-------|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| <hr/> |                    |                   |                  |                    |                   |                |        |
| 1     | 31.510             | 25.73             | -4.86            | 20.87              | 40.00             | 19.13          | Peak   |
| 2     | 70.584             | 35.82             | -17.22           | 18.60              | 40.00             | 21.40          | Peak   |
| 3     | 113.714            | 28.53             | -11.75           | 16.78              | 43.50             | 26.72          | Peak   |
| 4     | 356.676            | 26.93             | -9.56            | 17.37              | 46.00             | 28.63          | Peak   |
| 5     | 601.427            | 28.97             | -4.63            | 24.34              | 46.00             | 21.66          | Peak   |
| 6     | 916.069            | 28.92             | 0.21             | 29.13              | 46.00             | 16.87          | Peak   |

**4.2.2 1 GHz – 40 GHz:**

|               |            |              |                     |
|---------------|------------|--------------|---------------------|
| Sample Number | 30YZ-1     | Test Date:   | 2025/4/29-2025/4/30 |
| Test Site:    | 966-1      | Test Mode:   | Transmitting        |
| Tester:       | Peter Rong | Test Result: | Pass                |

**Environmental Conditions:**

|                     |           |                           |       |                           |             |
|---------------------|-----------|---------------------------|-------|---------------------------|-------------|
| Temperature:<br>( ) | 26.2-25.1 | Relative Humidity:<br>(%) | 54-58 | ATM<br>Pressure:<br>(kPa) | 101.4-101.7 |
|---------------------|-----------|---------------------------|-------|---------------------------|-------------|

**Test Equipment List and Details:**

| Manufacturer | Description                       | Model                 | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-----------------------------------|-----------------------|---------------|------------------|----------------------|
| ETS-Lindgren | Horn Antenna                      | 3115                  | 9912-5985     | 2023/12/6        | 2026/12/5            |
| R&S          | Spectrum Analyzer                 | FSV40                 | 101591        | 2025/3/31        | 2026/3/30            |
| MICRO-COAX   | Coaxial Cable                     | UFA210A-1-1200-70U300 | 217423-008    | 2025/1/10        | 2026/1/9             |
| MICRO-COAX   | Coaxial Cable                     | UFA210A-1-2362-300300 | 235780-001    | 2025/1/10        | 2026/1/9             |
| A.H          | Preamplifier                      | PAM-0118P             | 628           | 2025/2/21        | 2026/2/20            |
| Audix        | Test Software                     | E3                    | 191218 (V9)   | N/A              | N/A                  |
| PASTERNAK    | Horn Antenna                      | PE9852/2F-20          | 112002        | 2024/2/4         | 2027/2/3             |
| PASTERNAK    | Horn Antenna                      | PE9850/2F-20          | 072001        | 2024/2/4         | 2027/2/3             |
| Quinstar     | Preamplifier                      | QLW-18405536-JO       | 15964001005   | 2025/1/6         | 2026/1/5             |
| MICRO-COAX   | Coaxial Cable                     | UFB142A-1-2362-200200 | 235772-001    | 2025/1/6         | 2026/1/5             |
| JD           | Multiplex Switch Test Control Set | DT7220SCU             | DQ77925       | 2024/8/5         | 2025/8/4             |
| JD           | Filter Switch Unit                | DT7220FSU             | DQ77928       | 2024/8/5         | 2025/8/4             |

*\* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

**Test Data:**

After pre-scan in the X, Y and Z axes of orientation, the worst case is below:

**5150-5250MHz:****802.11a Mode:**

| Frequency<br>(MHz)       | Receiver          |        | Polar<br>(H/V) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------------|-------------------|--------|----------------|------------------|--------------------|-------------------|----------------|
|                          | Reading<br>(dBμV) | Remark |                |                  |                    |                   |                |
| Low Channel: 5180 MHz    |                   |        |                |                  |                    |                   |                |
| 10360.000                | 44.15             | PK     | H              | 2.01             | 46.16              | 68.20             | 22.04          |
| 10360.000                | 44.80             | PK     | V              | 2.01             | 46.81              | 68.20             | 21.39          |
| 15540.000                | 43.86             | PK     | H              | 4.08             | 47.94              | 74.00             | 26.06          |
| 15540.000                | 31.15             | AV     | H              | 4.08             | 35.23              | 54.00             | 18.77          |
| 15540.000                | 43.63             | PK     | V              | 4.08             | 47.71              | 74.00             | 26.29          |
| 15540.000                | 31.05             | AV     | V              | 4.08             | 35.13              | 54.00             | 18.87          |
| Middle Channel: 5200 MHz |                   |        |                |                  |                    |                   |                |
| 10400.000                | 43.73             | PK     | H              | 2.07             | 45.80              | 68.20             | 22.40          |
| 10400.000                | 44.80             | PK     | V              | 2.07             | 46.87              | 68.20             | 21.33          |
| 15600.000                | 42.85             | PK     | H              | 3.92             | 46.77              | 74.00             | 27.23          |
| 15600.000                | 30.08             | AV     | H              | 3.92             | 34.00              | 54.00             | 20.00          |
| 15600.000                | 43.30             | PK     | V              | 3.92             | 47.22              | 74.00             | 26.78          |
| 15600.000                | 31.14             | AV     | V              | 3.92             | 35.06              | 54.00             | 18.94          |
| High Channel: 5240 MHz   |                   |        |                |                  |                    |                   |                |
| 10480.000                | 43.70             | PK     | H              | 2.58             | 46.28              | 68.20             | 21.92          |
| 10480.000                | 43.17             | PK     | V              | 2.58             | 45.75              | 68.20             | 22.45          |
| 15720.000                | 44.06             | PK     | H              | 3.83             | 47.89              | 74.00             | 26.11          |
| 15720.000                | 32.12             | AV     | H              | 3.83             | 35.95              | 54.00             | 18.05          |
| 15720.000                | 43.89             | PK     | V              | 3.83             | 47.72              | 74.00             | 26.28          |
| 15720.000                | 31.27             | AV     | V              | 3.83             | 35.10              | 54.00             | 18.90          |

**802.11n ht20 Mode:**

| Frequency<br>(MHz) | Receiver          |        | Polar<br>(H/V) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------|-------------------|--------|----------------|------------------|--------------------|-------------------|----------------|
|                    | Reading<br>(dBμV) | Remark |                |                  |                    |                   |                |
| Low Channel:       |                   |        |                | 5180             | MHz                |                   |                |
| 10360.000          | 43.83             | PK     | H              | 2.01             | 45.84              | 68.20             | 22.36          |
| 10360.000          | 44.09             | PK     | V              | 2.01             | 46.10              | 68.20             | 22.10          |
| 15540.000          | 42.75             | PK     | H              | 4.08             | 46.83              | 74.00             | 27.17          |
| 15540.000          | 30.24             | AV     | H              | 4.08             | 34.32              | 54.00             | 19.68          |
| 15540.000          | 43.29             | PK     | V              | 4.08             | 47.37              | 74.00             | 26.63          |
| 15540.000          | 31.05             | AV     | V              | 4.08             | 35.13              | 54.00             | 18.87          |
| Middle Channel:    |                   |        |                | 5200             | MHz                |                   |                |
| 10400.000          | 45.74             | PK     | H              | 2.07             | 47.81              | 68.20             | 20.39          |
| 10400.000          | 44.37             | PK     | V              | 2.07             | 46.44              | 68.20             | 21.76          |
| 15600.000          | 43.74             | PK     | H              | 3.92             | 47.66              | 74.00             | 26.34          |
| 15600.000          | 31.56             | AV     | H              | 3.92             | 35.48              | 54.00             | 18.52          |
| 15600.000          | 43.61             | PK     | V              | 3.92             | 47.53              | 74.00             | 26.47          |
| 15600.000          | 31.58             | AV     | V              | 3.92             | 35.50              | 54.00             | 18.50          |
| High Channel:      |                   |        |                | 5240             | MHz                |                   |                |
| 10480.000          | 44.73             | PK     | H              | 2.58             | 47.31              | 68.20             | 20.89          |
| 10480.000          | 44.30             | PK     | V              | 2.58             | 46.88              | 68.20             | 21.32          |
| 15720.000          | 44.80             | PK     | H              | 3.83             | 48.63              | 74.00             | 25.37          |
| 15720.000          | 32.58             | AV     | H              | 3.83             | 36.41              | 54.00             | 17.59          |
| 15720.000          | 43.42             | PK     | V              | 3.83             | 47.25              | 74.00             | 26.75          |
| 15720.000          | 31.27             | AV     | V              | 3.83             | 35.10              | 54.00             | 18.90          |

**802.11n ht40 Mode:**

| Frequency<br>(MHz) | Receiver          |        | Polar<br>(H/V) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------|-------------------|--------|----------------|------------------|--------------------|-------------------|----------------|
|                    | Reading<br>(dBμV) | Remark |                |                  |                    |                   |                |
| Low Channel:       |                   |        |                | 5190             | MHz                |                   |                |
| 10380.000          | 45.45             | PK     | H              | 2.04             | 47.49              | 68.20             | 20.71          |
| 10380.000          | 44.85             | PK     | V              | 2.04             | 46.89              | 68.20             | 21.31          |
| 15570.000          | 44.70             | PK     | H              | 4.00             | 48.70              | 74.00             | 25.30          |
| 15570.000          | 31.56             | AV     | H              | 4.00             | 35.56              | 54.00             | 18.44          |
| 15570.000          | 45.09             | PK     | V              | 4.00             | 49.09              | 74.00             | 24.91          |
| 15570.000          | 31.27             | AV     | V              | 4.00             | 35.27              | 54.00             | 18.73          |
| High Channel:      |                   |        |                | 5230             | MHz                |                   |                |
| 10460.000          | 44.64             | PK     | H              | 2.46             | 47.10              | 68.20             | 21.10          |
| 10460.000          | 45.42             | PK     | V              | 2.46             | 47.88              | 68.20             | 20.32          |
| 15690.000          | 44.55             | PK     | H              | 3.80             | 48.35              | 74.00             | 25.65          |
| 15690.000          | 31.48             | AV     | H              | 3.80             | 35.28              | 54.00             | 18.72          |
| 15690.000          | 43.98             | PK     | V              | 3.80             | 47.78              | 74.00             | 26.22          |
| 15690.000          | 31.03             | AV     | V              | 3.80             | 34.83              | 54.00             | 19.17          |

**802.11ac80 Mode:**

| Frequency<br>(MHz) | Receiver          |        | Polar<br>(H/V) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------|-------------------|--------|----------------|------------------|--------------------|-------------------|----------------|
|                    | Reading<br>(dBμV) | Remark |                |                  |                    |                   |                |
| Middle Channel:    |                   |        |                | 5210             | MHz                |                   |                |
| 10420.000          | 45.42             | PK     | H              | 2.20             | 47.62              | 68.20             | 20.58          |
| 10420.000          | 44.17             | PK     | V              | 2.20             | 46.37              | 68.20             | 21.83          |
| 15630.000          | 44.97             | PK     | H              | 3.88             | 48.85              | 74.00             | 25.15          |
| 15630.000          | 32.09             | AV     | H              | 3.88             | 35.97              | 54.00             | 18.03          |
| 15630.000          | 44.54             | PK     | V              | 3.88             | 48.42              | 74.00             | 25.58          |
| 15630.000          | 31.23             | AV     | V              | 3.88             | 35.11              | 54.00             | 18.89          |

**5250-5350MHz:****802.11a Mode:**

| Frequency<br>(MHz)       | Receiver          |        | Polar<br>(H/V) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------------|-------------------|--------|----------------|------------------|--------------------|-------------------|----------------|
|                          | Reading<br>(dBμV) | Remark |                |                  |                    |                   |                |
| Low Channel: 5260 MHz    |                   |        |                |                  |                    |                   |                |
| 10520.000                | 44.57             | PK     | H              | 2.83             | 47.40              | 68.20             | 20.80          |
| 10520.000                | 44.80             | PK     | V              | 2.83             | 47.63              | 68.20             | 20.57          |
| 15780.000                | 45.46             | PK     | H              | 3.98             | 49.44              | 74.00             | 24.56          |
| 15780.000                | 32.68             | AV     | H              | 3.98             | 36.66              | 54.00             | 17.34          |
| 15780.000                | 44.91             | PK     | V              | 3.98             | 48.89              | 74.00             | 25.11          |
| 15780.000                | 31.86             | AV     | V              | 3.98             | 35.84              | 54.00             | 18.16          |
| Middle Channel: 5280 MHz |                   |        |                |                  |                    |                   |                |
| 10560.000                | 44.22             | PK     | H              | 3.06             | 47.28              | 68.20             | 20.92          |
| 10560.000                | 45.11             | PK     | V              | 3.06             | 48.17              | 68.20             | 20.03          |
| 15840.000                | 44.36             | PK     | H              | 4.22             | 48.58              | 74.00             | 25.42          |
| 15840.000                | 31.20             | AV     | H              | 4.22             | 35.42              | 54.00             | 18.58          |
| 15840.000                | 44.01             | PK     | V              | 4.22             | 48.23              | 74.00             | 25.77          |
| 15840.000                | 31.29             | AV     | V              | 4.22             | 35.51              | 54.00             | 18.49          |
| High Channel: 5320 MHz   |                   |        |                |                  |                    |                   |                |
| 10640.000                | 44.40             | PK     | H              | 3.46             | 47.86              | 74.00             | 26.14          |
| 10640.000                | 31.52             | AV     | H              | 3.46             | 34.98              | 54.00             | 19.02          |
| 10640.000                | 45.07             | PK     | V              | 3.46             | 48.53              | 74.00             | 25.47          |
| 10640.000                | 31.74             | AV     | V              | 3.46             | 35.20              | 54.00             | 18.80          |
| 15960.000                | 45.04             | PK     | H              | 4.44             | 49.48              | 74.00             | 24.52          |
| 15960.000                | 32.06             | AV     | H              | 4.44             | 36.50              | 54.00             | 17.50          |
| 15960.000                | 44.13             | PK     | V              | 4.44             | 48.57              | 74.00             | 25.43          |
| 15960.000                | 31.25             | AV     | V              | 4.44             | 35.69              | 54.00             | 18.31          |

**802.11n ht20 Mode:**

| Frequency<br>(MHz) | Receiver          |        | Polar<br>(H/V) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------|-------------------|--------|----------------|------------------|--------------------|-------------------|----------------|
|                    | Reading<br>(dBμV) | Remark |                |                  |                    |                   |                |
| Low Channel:       |                   |        |                | 5260             | MHz                |                   |                |
| 10520.000          | 46.06             | PK     | H              | 2.83             | 48.89              | 68.20             | 19.31          |
| 10520.000          | 45.71             | PK     | V              | 2.83             | 48.54              | 68.20             | 19.66          |
| 15780.000          | 44.49             | PK     | H              | 3.98             | 48.47              | 74.00             | 25.53          |
| 15780.000          | 32.09             | AV     | H              | 3.98             | 36.07              | 54.00             | 17.93          |
| 15780.000          | 45.04             | PK     | V              | 3.98             | 49.02              | 74.00             | 24.98          |
| 15780.000          | 32.07             | AV     | V              | 3.98             | 36.05              | 54.00             | 17.95          |
| Middle Channel:    |                   |        |                | 5280             | MHz                |                   |                |
| 10560.000          | 44.34             | PK     | H              | 3.06             | 47.40              | 68.20             | 20.80          |
| 10560.000          | 44.17             | PK     | V              | 3.06             | 47.23              | 68.20             | 20.97          |
| 15840.000          | 44.23             | PK     | H              | 4.22             | 48.45              | 74.00             | 25.55          |
| 15840.000          | 31.87             | AV     | H              | 4.22             | 36.09              | 54.00             | 17.91          |
| 15840.000          | 45.19             | PK     | V              | 4.22             | 49.41              | 74.00             | 24.59          |
| 15840.000          | 32.02             | AV     | V              | 4.22             | 36.24              | 54.00             | 17.76          |
| High Channel:      |                   |        |                | 5320             | MHz                |                   |                |
| 10640.000          | 44.64             | PK     | H              | 3.46             | 48.10              | 74.00             | 25.90          |
| 10640.000          | 31.60             | AV     | H              | 3.46             | 35.06              | 54.00             | 18.94          |
| 10640.000          | 44.51             | PK     | V              | 3.46             | 47.97              | 74.00             | 26.03          |
| 10640.000          | 31.50             | AV     | V              | 3.46             | 34.96              | 54.00             | 19.04          |
| 15960.000          | 44.52             | PK     | H              | 4.44             | 48.96              | 74.00             | 25.04          |
| 15960.000          | 31.24             | AV     | H              | 4.44             | 35.68              | 54.00             | 18.32          |
| 15960.000          | 44.54             | PK     | V              | 4.44             | 48.98              | 74.00             | 25.02          |
| 15960.000          | 31.26             | AV     | V              | 4.44             | 35.70              | 54.00             | 18.30          |

**802.11n ht40 Mode:**

| Frequency<br>(MHz) | Receiver          |        | Polar<br>(H/V) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------|-------------------|--------|----------------|------------------|--------------------|-------------------|----------------|
|                    | Reading<br>(dBμV) | Remark |                |                  |                    |                   |                |
| Low Channel:       |                   |        |                | 5270             | MHz                |                   |                |
| 10540.000          | 45.19             | PK     | H              | 2.94             | 48.13              | 68.20             | 20.07          |
| 10540.000          | 45.38             | PK     | V              | 2.94             | 48.32              | 68.20             | 19.88          |
| 15810.000          | 44.24             | PK     | H              | 4.07             | 48.31              | 74.00             | 25.69          |
| 15810.000          | 31.59             | AV     | H              | 4.07             | 35.66              | 54.00             | 18.34          |
| 15810.000          | 44.73             | PK     | V              | 4.07             | 48.80              | 74.00             | 25.20          |
| 15810.000          | 31.48             | AV     | V              | 4.07             | 35.55              | 54.00             | 18.45          |
| High Channel:      |                   |        |                | 5310             | MHz                |                   |                |
| 10620.000          | 44.47             | PK     | H              | 3.38             | 47.85              | 74.00             | 26.15          |
| 10620.000          | 31.58             | AV     | H              | 3.38             | 34.96              | 54.00             | 19.04          |
| 10620.000          | 44.38             | PK     | V              | 3.38             | 47.76              | 74.00             | 26.24          |
| 10620.000          | 31.82             | AV     | V              | 3.38             | 35.20              | 54.00             | 18.80          |
| 15930.000          | 44.30             | PK     | H              | 4.49             | 48.79              | 74.00             | 25.21          |
| 15930.000          | 31.50             | AV     | H              | 4.49             | 35.99              | 54.00             | 18.01          |
| 15930.000          | 44.41             | PK     | V              | 4.49             | 48.90              | 74.00             | 25.10          |
| 15930.000          | 31.53             | AV     | V              | 4.49             | 36.02              | 54.00             | 17.98          |

**802.11ac80 Mode:**

| Frequency<br>(MHz) | Receiver          |        | Polar<br>(H/V) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------|-------------------|--------|----------------|------------------|--------------------|-------------------|----------------|
|                    | Reading<br>(dBμV) | Remark |                |                  |                    |                   |                |
| Middle Channel:    |                   |        |                | 5290             | MHz                |                   |                |
| 10580.000          | 45.10             | PK     | H              | 3.17             | 48.27              | 68.20             | 19.93          |
| 10580.000          | 44.26             | PK     | V              | 3.17             | 47.43              | 68.20             | 20.77          |
| 15870.000          | 44.15             | PK     | H              | 4.37             | 48.52              | 74.00             | 25.48          |
| 15870.000          | 31.16             | AV     | H              | 4.37             | 35.53              | 54.00             | 18.47          |
| 15870.000          | 43.92             | PK     | V              | 4.37             | 48.29              | 74.00             | 25.71          |
| 15870.000          | 31.58             | AV     | V              | 4.37             | 35.95              | 54.00             | 18.05          |

**5470-5725MHz****802.11a Mode:**

| Frequency<br>(MHz) | Receiver          |        | Polar<br>(H/V) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------|-------------------|--------|----------------|------------------|--------------------|-------------------|----------------|
|                    | Reading<br>(dBμV) | Remark |                |                  |                    |                   |                |
| Low Channel:       |                   |        |                | 5500             | MHz                |                   |                |
| 11000.000          | 45.22             | PK     | H              | 3.90             | 49.12              | 74.00             | 24.88          |
| 11000.000          | 32.37             | AV     | H              | 3.90             | 36.27              | 54.00             | 17.73          |
| 11000.000          | 44.54             | PK     | V              | 3.90             | 48.44              | 74.00             | 25.56          |
| 11000.000          | 31.59             | AV     | V              | 3.90             | 35.49              | 54.00             | 18.51          |
| 16500.000          | 44.58             | PK     | H              | 5.33             | 49.91              | 68.20             | 18.29          |
| 16500.000          | 44.86             | PK     | V              | 5.33             | 50.19              | 68.20             | 18.01          |
| Middle Channel:    |                   |        |                | 5580             | MHz                |                   |                |
| 11160.000          | 47.91             | PK     | H              | 3.62             | 51.53              | 74.00             | 22.47          |
| 11160.000          | 35.23             | AV     | H              | 3.62             | 38.85              | 54.00             | 15.15          |
| 11160.000          | 44.38             | PK     | V              | 3.62             | 48.00              | 74.00             | 26.00          |
| 11160.000          | 31.57             | AV     | V              | 3.62             | 35.19              | 54.00             | 18.81          |
| 16740.000          | 43.55             | PK     | H              | 6.57             | 50.12              | 68.20             | 18.08          |
| 16740.000          | 43.66             | PK     | V              | 6.57             | 50.23              | 68.20             | 17.97          |
| High Channel:      |                   |        |                | 5700             | MHz                |                   |                |
| 11400.000          | 47.26             | PK     | H              | 4.62             | 51.88              | 74.00             | 22.12          |
| 11400.000          | 33.13             | AV     | H              | 4.62             | 37.75              | 54.00             | 16.25          |
| 11400.000          | 46.46             | PK     | V              | 4.62             | 51.08              | 74.00             | 22.92          |
| 11400.000          | 32.68             | AV     | V              | 4.62             | 37.30              | 54.00             | 16.70          |
| 17100.000          | 45.41             | PK     | H              | 8.19             | 53.60              | 68.20             | 14.60          |
| 17100.000          | 44.59             | PK     | V              | 8.19             | 52.78              | 68.20             | 15.42          |

**802.11n ht20 Mode:**

| Frequency<br>(MHz) | Receiver          |        | Polar<br>(H/V) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------|-------------------|--------|----------------|------------------|--------------------|-------------------|----------------|
|                    | Reading<br>(dBμV) | Remark |                |                  |                    |                   |                |
| Low Channel:       |                   |        |                | 5500             | MHz                |                   |                |
| 11000.000          | 45.08             | PK     | H              | 3.90             | 48.98              | 74.00             | 25.02          |
| 11000.000          | 32.28             | AV     | H              | 3.90             | 36.18              | 54.00             | 17.82          |
| 11000.000          | 45.28             | PK     | V              | 3.90             | 49.18              | 74.00             | 24.82          |
| 11000.000          | 32.36             | AV     | V              | 3.90             | 36.26              | 54.00             | 17.74          |
| 16500.000          | 44.60             | PK     | H              | 5.33             | 49.93              | 68.20             | 18.27          |
| 16500.000          | 45.04             | PK     | V              | 5.33             | 50.37              | 68.20             | 17.83          |
| Middle Channel:    |                   |        |                | 5580             | MHz                |                   |                |
| 11160.000          | 45.25             | PK     | H              | 3.62             | 48.87              | 74.00             | 25.13          |
| 11160.000          | 32.56             | AV     | H              | 3.62             | 36.18              | 54.00             | 17.82          |
| 11160.000          | 45.65             | PK     | V              | 3.62             | 49.27              | 74.00             | 24.73          |
| 11160.000          | 32.65             | AV     | V              | 3.62             | 36.27              | 54.00             | 17.73          |
| 16740.000          | 45.24             | PK     | H              | 6.57             | 51.81              | 68.20             | 16.39          |
| 16740.000          | 45.17             | PK     | V              | 6.57             | 51.74              | 68.20             | 16.46          |
| High Channel:      |                   |        |                | 5700             | MHz                |                   |                |
| 11400.000          | 45.07             | PK     | H              | 4.62             | 49.69              | 74.00             | 24.31          |
| 11400.000          | 32.11             | AV     | H              | 4.62             | 36.73              | 54.00             | 17.27          |
| 11400.000          | 45.25             | PK     | V              | 4.62             | 49.87              | 74.00             | 24.13          |
| 11400.000          | 32.38             | AV     | V              | 4.62             | 37.00              | 54.00             | 17.00          |
| 17100.000          | 44.91             | PK     | H              | 8.19             | 53.10              | 68.20             | 15.10          |
| 17100.000          | 45.10             | PK     | V              | 8.19             | 53.29              | 68.20             | 14.91          |

**802.11n ht40 Mode:**

| Frequency<br>(MHz) | Receiver          |        | Polar<br>(H/V) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------|-------------------|--------|----------------|------------------|--------------------|-------------------|----------------|
|                    | Reading<br>(dBμV) | Remark |                |                  |                    |                   |                |
| Low Channel:       |                   |        |                | 5510             | MHz                |                   |                |
| 11020.000          | 45.43             | PK     | H              | 3.78             | 49.21              | 74.00             | 24.79          |
| 11020.000          | 32.30             | AV     | H              | 3.78             | 36.08              | 54.00             | 17.92          |
| 11020.000          | 45.03             | PK     | V              | 3.78             | 48.81              | 74.00             | 25.19          |
| 11020.000          | 32.29             | AV     | V              | 3.78             | 36.07              | 54.00             | 17.93          |
| 16530.000          | 44.36             | PK     | H              | 5.58             | 49.94              | 68.20             | 18.26          |
| 16530.000          | 44.21             | PK     | V              | 5.58             | 49.79              | 68.20             | 18.41          |
| Middle Channel:    |                   |        |                | 5550             | MHz                |                   |                |
| 11100.000          | 45.49             | PK     | H              | 3.28             | 48.77              | 74.00             | 25.23          |
| 11100.000          | 32.62             | AV     | H              | 3.28             | 35.90              | 54.00             | 18.10          |
| 11100.000          | 45.03             | PK     | V              | 3.28             | 48.31              | 74.00             | 25.69          |
| 11100.000          | 32.63             | AV     | V              | 3.28             | 35.91              | 54.00             | 18.09          |
| 16650.000          | 44.97             | PK     | H              | 6.26             | 51.23              | 68.20             | 16.97          |
| 16650.000          | 44.83             | PK     | V              | 6.26             | 51.09              | 68.20             | 17.11          |
| High Channel:      |                   |        |                | 5670             | MHz                |                   |                |
| 11340.000          | 44.45             | PK     | H              | 4.49             | 48.94              | 74.00             | 25.06          |
| 11340.000          | 31.68             | AV     | H              | 4.49             | 36.17              | 54.00             | 17.83          |
| 11340.000          | 44.57             | PK     | V              | 4.49             | 49.06              | 74.00             | 24.94          |
| 11340.000          | 31.99             | AV     | V              | 4.49             | 36.48              | 54.00             | 17.52          |
| 17010.000          | 45.29             | PK     | H              | 7.85             | 53.14              | 68.20             | 15.06          |
| 17010.000          | 45.61             | PK     | V              | 7.85             | 53.46              | 68.20             | 14.74          |

**802.11ac80 Mode:**

| Frequency<br>(MHz) | Receiver          |        | Polar<br>(H/V) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------|-------------------|--------|----------------|------------------|--------------------|-------------------|----------------|
|                    | Reading<br>(dBμV) | Remark |                |                  |                    |                   |                |
| Low Channel:       |                   |        |                | 5530             | MHz                |                   |                |
| 11060.000          | 44.03             | PK     | H              | 3.53             | 47.56              | 74.00             | 26.44          |
| 11060.000          | 31.52             | AV     | H              | 3.53             | 35.05              | 54.00             | 18.95          |
| 11060.000          | 44.24             | PK     | V              | 3.53             | 47.77              | 74.00             | 26.23          |
| 11060.000          | 31.06             | AV     | V              | 3.53             | 34.59              | 54.00             | 19.41          |
| 16590.000          | 44.43             | PK     | H              | 6.08             | 50.51              | 68.20             | 17.69          |
| 16590.000          | 45.36             | PK     | V              | 6.08             | 51.44              | 68.20             | 16.76          |
| High Channel:      |                   |        |                | 5610             | MHz                |                   |                |
| 11220.000          | 45.13             | PK     | H              | 3.96             | 49.09              | 74.00             | 24.91          |
| 11220.000          | 32.27             | AV     | H              | 3.96             | 36.23              | 54.00             | 17.77          |
| 11220.000          | 45.05             | PK     | V              | 3.96             | 49.01              | 74.00             | 24.99          |
| 11220.000          | 32.56             | AV     | V              | 3.96             | 36.52              | 54.00             | 17.48          |
| 16830.000          | 45.12             | PK     | H              | 7.27             | 52.39              | 68.20             | 15.81          |
| 16830.000          | 44.76             | PK     | V              | 7.27             | 52.03              | 68.20             | 16.17          |

**5725-5850MHz****802.11a Mode:**

| Frequency<br>(MHz) | Receiver          |        | Polar<br>(H/V) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------|-------------------|--------|----------------|------------------|--------------------|-------------------|----------------|
|                    | Reading<br>(dBμV) | Remark |                |                  |                    |                   |                |
| Low Channel:       |                   |        |                | 5745             | MHz                |                   |                |
| 11490.000          | 46.07             | PK     | H              | 4.77             | 50.84              | 74.00             | 23.16          |
| 11490.000          | 32.41             | AV     | H              | 4.77             | 37.18              | 54.00             | 16.82          |
| 11490.000          | 45.58             | PK     | V              | 4.77             | 50.35              | 74.00             | 23.65          |
| 11490.000          | 32.42             | AV     | V              | 4.77             | 37.19              | 54.00             | 16.81          |
| 17235.000          | 44.22             | PK     | H              | 9.20             | 53.42              | 68.20             | 14.78          |
| 17235.000          | 44.69             | PK     | V              | 9.20             | 53.89              | 68.20             | 14.31          |
| Middle Channel:    |                   |        |                | 5785             | MHz                |                   |                |
| 11570.000          | 44.77             | PK     | H              | 5.25             | 50.02              | 74.00             | 23.98          |
| 11570.000          | 32.04             | AV     | H              | 5.25             | 37.29              | 54.00             | 16.71          |
| 11570.000          | 45.25             | PK     | V              | 5.25             | 50.50              | 74.00             | 23.50          |
| 11570.000          | 32.48             | AV     | V              | 5.25             | 37.73              | 54.00             | 16.27          |
| 17355.000          | 44.18             | PK     | H              | 10.13            | 54.31              | 68.20             | 13.89          |
| 17355.000          | 44.28             | PK     | V              | 10.13            | 54.41              | 68.20             | 13.79          |
| High Channel:      |                   |        |                | 5825             | MHz                |                   |                |
| 11650.000          | 47.14             | PK     | H              | 5.55             | 52.69              | 74.00             | 21.31          |
| 11650.000          | 33.87             | AV     | H              | 5.55             | 39.42              | 54.00             | 14.58          |
| 11650.000          | 46.52             | PK     | V              | 5.55             | 52.07              | 74.00             | 21.93          |
| 11650.000          | 33.58             | AV     | V              | 5.55             | 39.13              | 54.00             | 14.87          |
| 17475.000          | 45.02             | PK     | H              | 10.91            | 55.93              | 68.20             | 12.27          |
| 17475.000          | 45.63             | PK     | V              | 10.91            | 56.54              | 68.20             | 11.66          |

**802.11n ht20 Mode:**

| Frequency<br>(MHz) | Receiver          |        | Polar<br>(H/V) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------|-------------------|--------|----------------|------------------|--------------------|-------------------|----------------|
|                    | Reading<br>(dBμV) | Remark |                |                  |                    |                   |                |
| Low Channel:       |                   |        |                | 5745             | MHz                |                   |                |
| 11490.000          | 44.78             | PK     | H              | 4.77             | 49.55              | 74.00             | 24.45          |
| 11490.000          | 31.91             | AV     | H              | 4.77             | 36.68              | 54.00             | 17.32          |
| 11490.000          | 44.98             | PK     | V              | 4.77             | 49.75              | 74.00             | 24.25          |
| 11490.000          | 32.05             | AV     | V              | 4.77             | 36.82              | 54.00             | 17.18          |
| 17235.000          | 44.19             | PK     | H              | 9.20             | 53.39              | 68.20             | 14.81          |
| 17235.000          | 44.36             | PK     | V              | 9.20             | 53.56              | 68.20             | 14.64          |
| Middle Channel:    |                   |        |                | 5785             | MHz                |                   |                |
| 11570.000          | 44.51             | PK     | H              | 5.25             | 49.76              | 74.00             | 24.24          |
| 11570.000          | 31.59             | AV     | H              | 5.25             | 36.84              | 54.00             | 17.16          |
| 11570.000          | 44.78             | PK     | V              | 5.25             | 50.03              | 74.00             | 23.97          |
| 11570.000          | 31.72             | AV     | V              | 5.25             | 36.97              | 54.00             | 17.03          |
| 17355.000          | 44.66             | PK     | H              | 10.13            | 54.79              | 68.20             | 13.41          |
| 17355.000          | 44.83             | PK     | V              | 10.13            | 54.96              | 68.20             | 13.24          |
| High Channel:      |                   |        |                | 5825             | MHz                |                   |                |
| 11650.000          | 46.49             | PK     | H              | 5.55             | 52.04              | 74.00             | 21.96          |
| 11650.000          | 33.72             | AV     | H              | 5.55             | 39.27              | 54.00             | 14.73          |
| 11650.000          | 48.10             | PK     | V              | 5.55             | 53.65              | 74.00             | 20.35          |
| 11650.000          | 33.74             | AV     | V              | 5.55             | 39.29              | 54.00             | 14.71          |
| 17475.000          | 43.90             | PK     | H              | 10.91            | 54.81              | 68.20             | 13.39          |
| 17475.000          | 44.12             | PK     | V              | 10.91            | 55.03              | 68.20             | 13.17          |

**802.11n ht40 Mode:**

| Frequency<br>(MHz) | Receiver          |        | Polar<br>(H/V) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------|-------------------|--------|----------------|------------------|--------------------|-------------------|----------------|
|                    | Reading<br>(dBμV) | Remark |                |                  |                    |                   |                |
| Low Channel:       |                   |        |                | 5755             | MHz                |                   |                |
| 11510.000          | 45.01             | PK     | H              | 4.86             | 49.87              | 74.00             | 24.13          |
| 11510.000          | 32.14             | AV     | H              | 4.86             | 37.00              | 54.00             | 17.00          |
| 11510.000          | 44.10             | PK     | V              | 4.86             | 48.96              | 74.00             | 25.04          |
| 11510.000          | 31.56             | AV     | V              | 4.86             | 36.42              | 54.00             | 17.58          |
| 17265.000          | 44.58             | PK     | H              | 9.40             | 53.98              | 68.20             | 14.22          |
| 17265.000          | 44.63             | PK     | V              | 9.40             | 54.03              | 68.20             | 14.17          |
| High Channel:      |                   |        |                | 5795             | MHz                |                   |                |
| 11590.000          | 45.08             | PK     | H              | 5.38             | 50.46              | 74.00             | 23.54          |
| 11590.000          | 32.28             | AV     | H              | 5.38             | 37.66              | 54.00             | 16.34          |
| 11590.000          | 45.78             | PK     | V              | 5.38             | 51.16              | 74.00             | 22.84          |
| 11590.000          | 32.95             | AV     | V              | 5.38             | 38.33              | 54.00             | 15.67          |
| 17385.000          | 45.02             | PK     | H              | 10.41            | 55.43              | 68.20             | 12.77          |
| 17385.000          | 44.24             | PK     | V              | 10.41            | 54.65              | 68.20             | 13.55          |


**802.11ac80 Mode:**

| Frequency<br>(MHz) | Receiver          |        | Polar<br>(H/V) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------|-------------------|--------|----------------|------------------|--------------------|-------------------|----------------|
|                    | Reading<br>(dBμV) | Remark |                |                  |                    |                   |                |
| Middle Channel:    |                   |        |                | 5775             | MHz                |                   |                |
| 11550.000          | 44.85             | PK     | H              | 5.12             | 49.97              | 74.00             | 24.03          |
| 11550.000          | 31.95             | AV     | H              | 5.12             | 37.07              | 54.00             | 16.93          |
| 11550.000          | 44.68             | PK     | V              | 5.12             | 49.80              | 74.00             | 24.20          |
| 11550.000          | 31.96             | AV     | V              | 5.12             | 37.08              | 54.00             | 16.92          |
| 17325.000          | 44.36             | PK     | H              | 9.86             | 54.22              | 68.20             | 13.98          |
| 17325.000          | 44.01             | PK     | V              | 9.86             | 53.87              | 68.20             | 14.33          |


Worst radiation spurious emissions margin test plots for each mode

Note: for 18 – 40 GHz range, test was performed on the maximum power mode.

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: horizontal  
Note: a High Channel 5240 MHz Band 1




Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: vertical  
Note: a High Channel 5240 MHz Band 1




| No. | Frequency (MHz) | Reading (dBUV) | Factor (dB/m) | Result (dBUV/m) | Limit (dBUV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|--------|
| 1   | 5518.000        | 43.96          | -4.02         | 39.94           | 68.20          | 28.26       | Peak   |

Project No.: 2503S20876E-RF  
 Tester: Peter Rong  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
 Polarization: horizontal  
 Note: a High Channel 5240MHz Band 1




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 10480.000          | 43.70             | 2.58             | 46.28              | 68.20             | 21.92          | Peak    |
| 2   | 15720.000          | 44.06             | 3.83             | 47.89              | 74.00             | 26.11          | Peak    |
| 3   | 15720.000          | 32.12             | 3.83             | 35.95              | 54.00             | 18.05          | Average |
| 4   | 17764.800          | 44.80             | 13.37            | 58.17              | 74.00             | 15.83          | Peak    |
| 5   | 17764.800          | 32.91             | 13.37            | 46.28              | 54.00             | 7.72           | Average |

Project No.: 2503S20876E-RF  
 Tester: Peter Rong  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
 Polarization: vertical  
 Note: a High Channel 5240MHz Band 1




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 10480.000          | 43.17             | 2.58             | 45.75              | 68.20             | 22.45          | Peak    |
| 2   | 15720.000          | 43.89             | 3.83             | 47.72              | 74.00             | 26.28          | Peak    |
| 3   | 15720.000          | 31.27             | 3.83             | 35.10              | 54.00             | 18.90          | Average |
| 4   | 17800.800          | 44.60             | 13.55            | 58.15              | 74.00             | 15.85          | Peak    |
| 5   | 17800.800          | 32.81             | 13.55            | 46.36              | 54.00             | 7.64           | Average |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: horizontal  
Note: n20 High Channel 5240 MHz Band 1




Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: vertical  
Note: n20 High Channel 5240 MHz Band 1




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBUV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5965.000           | 45.83             | -3.94            | 41.89              | 68.20             | 26.31          | Peak   |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
Polarization: horizontal  
Note: n20 High Channel 5240MHz Band 1




Project No.: 2503S20876E-RF  
 Tester: Peter Rong  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
 Polarization: vertical  
 Note: n20 High Channel 5240MHz Band 1




| No. | Frequency<br>(MHz) | Reading<br>(dB $\mu$ V) | Factor<br>(dB/m) | Result<br>(dB $\mu$ V/m) | Limit<br>(dB $\mu$ V/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------------|------------------|--------------------------|-------------------------|----------------|---------|
| 1   | 10480.000          | 44.30                   | 2.58             | 46.88                    | 68.20                   | 21.32          | Peak    |
| 2   | 15720.000          | 43.42                   | 3.83             | 47.25                    | 74.00                   | 26.75          | Peak    |
| 3   | 15720.000          | 31.27                   | 3.83             | 35.10                    | 54.00                   | 18.90          | Average |
| 4   | 17772.000          | 44.39                   | 13.42            | 57.81                    | 74.00                   | 16.19          | Peak    |
| 5   | 17772.000          | 32.44                   | 13.42            | 45.86                    | 54.00                   | 8.14           | Average |


Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: horizontal  
Note: n40 Low Channel 5190 MHz Band 1



Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: vertical  
Note: n40 Low Channel 5190 MHz Band 1




Project No.: 2503S20876E-RF  
 Tester: Peter Rong  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
 Polarization: horizontal  
 Note: n40 Low Channel 5190MHz Band 1



| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 10380.000          | 45.45             | 2.04             | 47.49              | 68.20             | 20.71          | Peak    |
| 2   | 15570.000          | 44.70             | 4.00             | 48.70              | 74.00             | 25.30          | Peak    |
| 3   | 15570.000          | 31.56             | 4.00             | 35.56              | 54.00             | 18.44          | Average |
| 4   | 17748.000          | 44.53             | 13.30            | 57.83              | 74.00             | 16.17          | Peak    |
| 5   | 17748.000          | 31.97             | 13.30            | 45.27              | 54.00             | 8.73           | Average |

Project No.: 2503S20876E-RF  
 Tester: Peter Rong  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
 Polarization: vertical  
 Note: n40 Low Channel 5190MHz Band 1




| No. | Frequency<br>(MHz) | Reading<br>(dB $\mu$ V) | Factor<br>(dB/m) | Result<br>(dB $\mu$ V/m) | Limit<br>(dB $\mu$ V/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------------|------------------|--------------------------|-------------------------|----------------|---------|
| 1   | 10380.000          | 44.85                   | 2.04             | 46.89                    | 68.20                   | 21.31          | Peak    |
| 2   | 15570.000          | 45.09                   | 4.00             | 49.09                    | 74.00                   | 24.91          | Peak    |
| 3   | 15570.000          | 31.27                   | 4.00             | 35.27                    | 54.00                   | 18.73          | Average |
| 4   | 17812.800          | 44.06                   | 13.55            | 57.61                    | 74.00                   | 16.39          | Peak    |
| 5   | 17812.800          | 31.57                   | 13.55            | 45.12                    | 54.00                   | 8.88           | Average |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: horizontal  
Note: ac80 Middle Channel 5210 MHz Band 1




Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: vertical  
Note: ac80 Middle Channel 5210 MHz Band 1




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBUV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5859.000           | 45.42             | -4.32            | 41.10              | 68.20             | 27.10          | Peak   |

Project No.: 2503S20876E-RF  
 Tester: Peter Rong  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
 Polarization: horizontal  
 Note: ac80 Middle Channel 5210MHz Band 1




| No. | Frequency<br>(MHz) | Reading<br>(dB $\mu$ V) | Factor<br>(dB/m) | Result<br>(dB $\mu$ V/m) | Limit<br>(dB $\mu$ V/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------------|------------------|--------------------------|-------------------------|----------------|---------|
| 1   | 10420.000          | 45.42                   | 2.20             | 47.62                    | 68.20                   | 20.58          | Peak    |
| 2   | 15630.000          | 44.97                   | 3.88             | 48.85                    | 74.00                   | 25.15          | Peak    |
| 3   | 15630.000          | 32.09                   | 3.88             | 35.97                    | 54.00                   | 18.03          | Average |
| 4   | 17748.000          | 44.55                   | 13.30            | 57.85                    | 74.00                   | 16.15          | Peak    |
| 5   | 17748.000          | 31.56                   | 13.30            | 44.86                    | 54.00                   | 9.14           | Average |

Project No.: 2503S20876E-RF  
 Tester: Peter Rong  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
 Polarization: vertical  
 Note: ac80 Middle Channel 5210MHz Band 1




| No. | Frequency<br>(MHz) | Reading<br>(dB $\mu$ V) | Factor<br>(dB/m) | Result<br>(dB $\mu$ V/m) | Limit<br>(dB $\mu$ V/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------------|------------------|--------------------------|-------------------------|----------------|---------|
| 1   | 10420.000          | 44.17                   | 2.20             | 46.37                    | 68.20                   | 21.83          | Peak    |
| 2   | 15630.000          | 44.54                   | 3.88             | 48.42                    | 74.00                   | 25.58          | Peak    |
| 3   | 15630.000          | 31.23                   | 3.88             | 35.11                    | 54.00                   | 18.89          | Average |
| 4   | 17728.800          | 45.05                   | 13.21            | 58.26                    | 74.00                   | 15.74          | Peak    |
| 5   | 17728.800          | 32.16                   | 13.21            | 45.37                    | 54.00                   | 8.63           | Average |


Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: horizontal  
Note: a High Channel 5320 MHz Band 2



Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: vertical  
Note: a High Channel 5320 MHz Band 2




Project No.: 2503S20876E-RF  
 Tester: Peter Rong  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
 Polarization: horizontal  
 Note: a High Channel 5320MHz Band 2




| No.   | Frequency<br>(MHz) | Reading<br>(dB $\mu$ V) | Factor<br>(dB/m) | Result<br>(dB $\mu$ V/m) | Limit<br>(dB $\mu$ V/m) | Margin<br>(dB) | Remark  |
|-------|--------------------|-------------------------|------------------|--------------------------|-------------------------|----------------|---------|
| <hr/> |                    |                         |                  |                          |                         |                |         |
| 1     | 10640.000          | 44.40                   | 3.46             | 47.86                    | 74.00                   | 26.14          | Peak    |
| 2     | 10640.000          | 31.52                   | 3.46             | 34.98                    | 54.00                   | 19.02          | Average |
| 3     | 15960.000          | 45.04                   | 4.44             | 49.48                    | 74.00                   | 24.52          | Peak    |
| 4     | 15960.000          | 32.06                   | 4.44             | 36.50                    | 54.00                   | 17.50          | Average |
| 5     | 17808.000          | 43.55                   | 13.55            | 57.10                    | 74.00                   | 16.90          | Peak    |
| 6     | 17808.000          | 31.16                   | 13.55            | 44.71                    | 54.00                   | 9.29           | Average |

Project No.: 2503S20876E-RF  
 Tester: Peter Rong  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
 Polarization: vertical  
 Note: a High Channel 5320MHz Band 2




| No.   | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-------|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| <hr/> |                    |                   |                  |                    |                   |                |         |
| 1     | 10640.000          | 45.07             | 3.46             | 48.53              | 74.00             | 25.47          | Peak    |
| 2     | 10640.000          | 31.74             | 3.46             | 35.20              | 54.00             | 18.80          | Average |
| 3     | 15960.000          | 44.13             | 4.44             | 48.57              | 74.00             | 25.43          | Peak    |
| 4     | 15960.000          | 31.25             | 4.44             | 35.69              | 54.00             | 18.31          | Average |
| 5     | 17810.400          | 44.36             | 13.55            | 57.91              | 74.00             | 16.09          | Peak    |
| 6     | 17810.400          | 30.55             | 13.55            | 44.10              | 54.00             | 9.90           | Average |


Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: horizontal  
Note: n20 Middle Channel 5280 MHz Band 2



Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: vertical  
Note: n20 Middle Channel 5280 MHz Band 2




Project No.: 2503S20876E-RF  
 Tester: Peter Rong  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
 Polarization: horizontal  
 Note: n20 Middle Channel 5280MHz Band 2




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 10560.000          | 44.34             | 3.06             | 47.40              | 68.20             | 20.80          | Peak    |
| 2   | 15840.000          | 44.23             | 4.22             | 48.45              | 74.00             | 25.55          | Peak    |
| 3   | 15840.000          | 31.87             | 4.22             | 36.09              | 54.00             | 17.91          | Average |
| 4   | 17736.000          | 44.37             | 13.25            | 57.62              | 74.00             | 16.38          | Peak    |
| 5   | 17736.000          | 31.95             | 13.25            | 45.20              | 54.00             | 8.80           | Average |

Project No.: 2503S20876E-RF  
 Tester: Peter Rong  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
 Polarization: vertical  
 Note: n20 Middle Channel 5280MHz Band 2




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 10560.000          | 44.17             | 3.06             | 47.23              | 68.20             | 20.97          | Peak    |
| 2   | 15840.000          | 45.19             | 4.22             | 49.41              | 74.00             | 24.59          | Peak    |
| 3   | 15840.000          | 32.02             | 4.22             | 36.24              | 54.00             | 17.76          | Average |
| 4   | 17791.200          | 44.76             | 13.50            | 58.26              | 74.00             | 15.74          | Peak    |
| 5   | 17791.200          | 31.65             | 13.50            | 45.15              | 54.00             | 8.85           | Average |


Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: horizontal  
Note: n40 High Channel 5310 MHz Band 2



Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: vertical  
Note: n40 High Channel 5310 MHz Band 2




Project No.: 2503S20876E-RF  
 Tester: Peter Rong  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
 Polarization: horizontal  
 Note: n40 High Channel 5310MHz Band 2




| No.   | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-------|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| <hr/> |                    |                   |                  |                    |                   |                |         |
| 1     | 10620.000          | 44.47             | 3.38             | 47.85              | 74.00             | 26.15          | Peak    |
| 2     | 10620.000          | 31.58             | 3.38             | 34.96              | 54.00             | 19.04          | Average |
| 3     | 15930.000          | 44.30             | 4.49             | 48.79              | 74.00             | 25.21          | Peak    |
| 4     | 15930.000          | 31.50             | 4.49             | 35.99              | 54.00             | 18.01          | Average |
| 5     | 17798.400          | 44.18             | 13.55            | 57.73              | 74.00             | 16.27          | Peak    |
| 6     | 17798.400          | 31.27             | 13.55            | 44.82              | 54.00             | 9.18           | Average |


Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
Polarization: vertical  
Note: n40 High Channel 5310MHz Band 2



Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: horizontal  
Note: ac80 Middle Channel 5290 MHz Band 2




Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: vertical  
Note: ac80 Middle Channel 5290 MHz Band 2




| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|--------|
| 1   | 5973.000        | 46.64          | -3.99         | 42.65           | 68.20          | 25.55       | Peak   |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
Polarization: horizontal  
Note: ac80 Middle Channel 5290MHz Band 2




Project No.: 2503S20876E-RF  
 Tester: Peter Rong  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
 Polarization: vertical  
 Note: ac80 Middle Channel 5290MHz Band 2




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 10580.000          | 44.26             | 3.17             | 47.43              | 68.20             | 20.77          | Peak    |
| 2   | 15870.000          | 43.92             | 4.37             | 48.29              | 74.00             | 25.71          | Peak    |
| 3   | 15870.000          | 31.58             | 4.37             | 35.95              | 54.00             | 18.05          | Average |
| 4   | 17731.200          | 44.75             | 13.21            | 57.96              | 74.00             | 16.04          | Peak    |
| 5   | 17731.200          | 31.31             | 13.21            | 44.52              | 54.00             | 9.48           | Average |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: horizontal  
Note: a High Channel 5700MHz Band 3




Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: vertical  
Note: a High Channel 5700MHz Band 3




| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|--------|
| 1   | 5954.000        | 46.20          | -3.88         | 42.32           | 68.20          | 25.88       | Peak   |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
Polarization: horizontal  
Note: a High Channel 5700MHz Band 3




| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Remark  |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|---------|
| 1   | 11400.000       | 47.26          | 4.62          | 51.88           | 74.00          | 22.12       | Peak    |
| 2   | 11400.000       | 33.13          | 4.62          | 37.75           | 54.00          | 16.25       | Average |
| 3   | 17100.000       | 45.41          | 8.19          | 53.60           | 68.20          | 14.60       | Peak    |
| 4   | 17750.400       | 45.09          | 13.31         | 58.40           | 74.00          | 15.60       | Peak    |
| 5   | 17750.400       | 31.92          | 13.31         | 45.23           | 54.00          | 8.77        | Average |

Project No.: 2503S20876E-RF  
 Tester: Peter Rong  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
 Polarization: vertical  
 Note: a High Channel 5700MHz Band 3




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 11400.000          | 46.46             | 4.62             | 51.08              | 74.00             | 22.92          | Peak    |
| 2   | 11400.000          | 32.68             | 4.62             | 37.30              | 54.00             | 16.70          | Average |
| 3   | 17100.000          | 44.59             | 8.19             | 52.78              | 68.20             | 15.42          | Peak    |
| 4   | 17784.000          | 44.37             | 13.47            | 57.84              | 74.00             | 16.16          | Peak    |
| 5   | 17784.000          | 31.16             | 13.47            | 44.63              | 54.00             | 9.37           | Average |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: horizontal  
Note: n20 High Channel 5700MHz Band 3




| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|--------|
| 1   | 5969.000        | 45.78          | -3.97         | 41.81           | 68.20          | 26.39       | Peak   |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: vertical  
Note: n20 High Channel 5700MHz Band 3




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5955.000           | 45.63             | -3.88            | 41.75              | 68.20             | 26.45          | Peak   |

Project No.: 2503S20876E-RF  
 Tester: Peter Rong  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
 Polarization: horizontal  
 Note: n20 High Channel 5700MHz Band 3




| No.   | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBUV/m) | Limit<br>(dBUV/m) | Margin<br>(dB) | Remark  |
|-------|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| <hr/> |                    |                   |                  |                    |                   |                |         |
| 1     | 11400.000          | 45.07             | 4.62             | 49.69              | 74.00             | 24.31          | Peak    |
| 2     | 11400.000          | 32.11             | 4.62             | 36.73              | 54.00             | 17.27          | Average |
| 3     | 17100.000          | 44.91             | 8.19             | 53.10              | 68.20             | 15.10          | Peak    |
| 4     | 17808.000          | 45.40             | 13.55            | 58.95              | 74.00             | 15.05          | Peak    |
| 5     | 17808.000          | 31.48             | 13.55            | 45.03              | 54.00             | 8.97           | Average |

Project No.: 2503S20876E-RF  
 Tester: Peter Rong  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
 Polarization: vertical  
 Note: n20 High Channel 5700MHz Band 3




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 11400.000          | 45.25             | 4.62             | 49.87              | 74.00             | 24.13          | Peak    |
| 2   | 11400.000          | 32.38             | 4.62             | 37.00              | 54.00             | 17.00          | Average |
| 3   | 17100.000          | 45.10             | 8.19             | 53.29              | 68.20             | 14.91          | Peak    |
| 4   | 17817.600          | 43.88             | 13.55            | 57.43              | 74.00             | 16.57          | Peak    |
| 5   | 17817.600          | 30.53             | 13.55            | 44.08              | 54.00             | 9.92           | Average |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: horizontal  
Note: n40 High Channel 5670MHz Band 3




| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|--------|
| 1   | 5972.000        | 46.23          | -3.99         | 42.24           | 68.20          | 25.96       | Peak   |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: vertical  
Note: n40 High Channel 5670MHz Band 3




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5975.000           | 46.51             | -4.01            | 42.50              | 68.20             | 25.70          | Peak   |

Project No.: 2503S20876E-RF  
 Tester: Peter Rong  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
 Polarization: horizontal  
 Note: n40 High Channel 5670MHz Band 3




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 11340.000          | 44.45             | 4.49             | 48.94              | 74.00             | 25.06          | Peak    |
| 2   | 11340.000          | 31.68             | 4.49             | 36.17              | 54.00             | 17.83          | Average |
| 3   | 17010.000          | 45.29             | 7.85             | 53.14              | 68.20             | 15.06          | Peak    |
| 4   | 17750.400          | 44.33             | 13.31            | 57.64              | 74.00             | 16.36          | Peak    |
| 5   | 17750.400          | 31.31             | 13.31            | 44.62              | 54.00             | 9.38           | Average |

Project No.: 2503S20876E-RF  
 Tester: Peter Rong  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
 Polarization: vertical  
 Note: n40 High Channel 5670MHz Band 3




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 11340.000          | 44.57             | 4.49             | 49.06              | 74.00             | 24.94          | Peak    |
| 2   | 11340.000          | 31.99             | 4.49             | 36.48              | 54.00             | 17.52          | Average |
| 3   | 17010.000          | 45.61             | 7.85             | 53.46              | 68.20             | 14.74          | Peak    |
| 4   | 17817.600          | 44.31             | 13.55            | 57.86              | 74.00             | 16.14          | Peak    |
| 5   | 17817.600          | 30.74             | 13.55            | 44.29              | 54.00             | 9.71           | Average |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: horizontal  
Note: ac80 High Channel 5610MHz Band 3




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5963.000           | 46.63             | -3.92            | 42.71              | 68.20             | 25.49          | Peak   |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: vertical  
Note: ac80 High Channel 5610MHz Band 3




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5958.000           | 45.30             | -3.89            | 41.41              | 68.20             | 26.79          | Peak   |

Project No.: 2503S20876E-RF  
 Tester: Peter Rong  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
 Polarization: horizontal  
 Note: ac80 High Channel 5610MHz Band 3




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 11220.000          | 45.13             | 3.96             | 49.09              | 74.00             | 24.91          | Peak    |
| 2   | 11220.000          | 32.27             | 3.96             | 36.23              | 54.00             | 17.77          | Average |
| 3   | 16830.000          | 45.12             | 7.27             | 52.39              | 68.20             | 15.81          | Peak    |
| 4   | 17757.600          | 44.13             | 13.35            | 57.48              | 74.00             | 16.52          | Peak    |
| 5   | 17757.600          | 31.46             | 13.35            | 44.81              | 54.00             | 9.19           | Average |


Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
Polarization: vertical  
Note: ac80 High Channel 5610MHz Band 3



Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: horizontal  
Note: a High Channel 5825MHz Band 4




Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: vertical  
Note: a High Channel 5825MHz Band 4




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5954.000           | 47.00             | -3.88            | 43.12              | 68.20             | 25.08          | Peak   |

Project No.: 2503S20876E-RF  
 Tester: Peter Rong  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
 Polarization: horizontal  
 Note: a High Channel 5825MHz Band 4




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 11650.000          | 47.14             | 5.55             | 52.69              | 74.00             | 21.31          | Peak    |
| 2   | 11650.000          | 33.87             | 5.55             | 39.42              | 54.00             | 14.58          | Average |
| 3   | 17475.000          | 45.02             | 10.91            | 55.93              | 68.20             | 12.27          | Peak    |
| 4   | 17784.000          | 43.89             | 13.47            | 57.36              | 74.00             | 16.64          | Peak    |
| 5   | 17784.000          | 30.69             | 13.47            | 44.16              | 54.00             | 9.84           | Average |

Project No.: 2503S20876E-RF  
 Tester: Peter Rong  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
 Polarization: vertical  
 Note: a High Channel 5825MHz Band 4




| No.   | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-------|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| <hr/> |                    |                   |                  |                    |                   |                |         |
| 1     | 11650.000          | 46.52             | 5.55             | 52.07              | 74.00             | 21.93          | Peak    |
| 2     | 11650.000          | 33.58             | 5.55             | 39.13              | 54.00             | 14.87          | Average |
| 3     | 17475.000          | 45.63             | 10.91            | 56.54              | 68.20             | 11.66          | Peak    |
| 4     | 17740.800          | 44.39             | 13.26            | 57.65              | 74.00             | 16.35          | Peak    |
| 5     | 17740.800          | 31.27             | 13.26            | 44.53              | 54.00             | 9.47           | Average |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
Polarization: Horizontal  
Note: a High Channel 5825MHz Band 4




| No.   | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-------|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| <hr/> |                    |                   |                  |                    |                   |                |         |
| 1     | 19796.200          | 50.40             | 7.91             | 58.31              | 74.00             | 15.69          | Peak    |
| 2     | 19796.200          | 37.45             | 7.91             | 45.36              | 54.00             | 8.64           | Average |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
Polarization: Vertical  
Note: a High Channel 5825MHz Band 4




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 20070.600          | 50.71             | 6.87             | 57.58              | 74.00             | 16.42          | Peak    |
| 2   | 20070.600          | 38.00             | 6.87             | 44.87              | 54.00             | 9.13           | Average |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: horizontal  
Note: n20 High Channel 5825MHz Band 4




Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: vertical  
Note: n20 High Channel 5825MHz Band 4




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5964.000           | 46.66             | -3.94            | 42.72              | 68.20             | 25.48          | Peak   |

Project No.: 2503S20876E-RF  
 Tester: Peter Rong  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
 Polarization: horizontal  
 Note: n20 High Channel 5825MHz Band 4




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 11650.000          | 46.49             | 5.55             | 52.04              | 74.00             | 21.96          | Peak    |
| 2   | 11650.000          | 33.72             | 5.55             | 39.27              | 54.00             | 14.73          | Average |
| 3   | 17475.000          | 43.90             | 10.91            | 54.81              | 68.20             | 13.39          | Peak    |
| 4   | 17793.600          | 43.91             | 13.51            | 57.42              | 74.00             | 16.58          | Peak    |
| 5   | 17793.600          | 31.07             | 13.51            | 44.58              | 54.00             | 9.42           | Average |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
Polarization: vertical  
Note: n20 High Channel 5825MHz Band 4




| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Remark  |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|---------|
| 1   | 11650.000       | 48.10          | 5.55          | 53.65           | 74.00          | 20.35       | Peak    |
| 2   | 11650.000       | 33.74          | 5.55          | 39.29           | 54.00          | 14.71       | Average |
| 3   | 17475.000       | 44.12          | 10.91         | 55.03           | 68.20          | 13.17       | Peak    |
| 4   | 17786.400       | 44.45          | 13.49         | 57.94           | 74.00          | 16.06       | Peak    |
| 5   | 17786.400       | 31.08          | 13.49         | 44.57           | 54.00          | 9.43        | Average |


Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: horizontal  
Note: n40 High Channel 5795MHz Band 4



Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: vertical  
Note: n40 High Channel 5795MHz Band 4




Project No.: 2503S20876E-RF  
 Tester: Peter Rong  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
 Polarization: horizontal  
 Note: n40 High Channel 5795MHz Band 4




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 11590.000          | 45.08             | 5.38             | 50.46              | 74.00             | 23.54          | Peak    |
| 2   | 11590.000          | 32.28             | 5.38             | 37.66              | 54.00             | 16.34          | Average |
| 3   | 17385.000          | 45.02             | 10.41            | 55.43              | 68.20             | 12.77          | Peak    |
| 4   | 17796.000          | 44.83             | 13.54            | 58.37              | 74.00             | 15.63          | Peak    |
| 5   | 17796.000          | 31.82             | 13.54            | 45.36              | 54.00             | 8.64           | Average |

Project No.: 2503S20876E-RF  
 Tester: Peter Rong  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
 Polarization: vertical  
 Note: n40 High Channel 5795MHz Band 4




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 11590.000          | 45.78             | 5.38             | 51.16              | 74.00             | 22.84          | Peak    |
| 2   | 11590.000          | 32.95             | 5.38             | 38.33              | 54.00             | 15.67          | Average |
| 3   | 17385.000          | 44.24             | 10.41            | 54.65              | 68.20             | 13.55          | Peak    |
| 4   | 17736.000          | 44.34             | 13.25            | 57.59              | 74.00             | 16.41          | Peak    |
| 5   | 17736.000          | 30.91             | 13.25            | 44.16              | 54.00             | 9.84           | Average |


Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: horizontal  
Note: ac80 Middle Channel 5775MHz Band 4



Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: vertical  
Note: ac80 Middle Channel 5775MHz Band 4




Project No.: 2503S20876E-RF  
 Tester: Peter Rong  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
 Polarization: horizontal  
 Note: ac80 Middle Channel 5775MHz Band 4




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 11550.000          | 44.85             | 5.12             | 49.97              | 74.00             | 24.03          | Peak    |
| 2   | 11550.000          | 31.95             | 5.12             | 37.07              | 54.00             | 16.93          | Average |
| 3   | 17325.000          | 44.36             | 9.86             | 54.22              | 68.20             | 13.98          | Peak    |
| 4   | 17805.600          | 44.18             | 13.55            | 57.73              | 74.00             | 16.27          | Peak    |
| 5   | 17805.600          | 30.72             | 13.55            | 44.27              | 54.00             | 9.73           | Average |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
Polarization: vertical  
Note: ac80 Middle Channel 5775MHz Band 4




Band edge test plots

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Horizontal  
Note: a Low Channel 5180 MHz Band 1




| No.   | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-------|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| <hr/> |                    |                   |                  |                    |                   |                |        |
| 1     | 5150.000           | 56.25             | -4.61            | 51.64              | 74.00             | 22.36          | Peak   |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Vertical  
Note: a Low Channel 5180 MHz Band 1




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5150.000           | 55.61             | -4.61            | 51.00              | 74.00             | 23.00          | Peak   |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Horizontal  
Note: a High Channel 5240 MHz Band 1




| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|--------|
| 1   | 5350.000        | 55.36          | -4.52         | 50.84           | 74.00          | 23.16       | Peak   |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Vertical  
Note: a High Channel 5240 MHz Band 1




| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|--------|
| 1   | 5350.000        | 55.95          | -4.52         | 51.43           | 74.00          | 22.57       | Peak   |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Horizontal  
Note: n20 Low Channel 5180 MHz Band 1




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5150.000           | 55.51             | -4.61            | 50.90              | 74.00             | 23.10          | Peak   |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Vertical  
Note: n20 Low Channel 5180 MHz Band 1




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5150.000           | 56.13             | -4.61            | 51.52              | 74.00             | 22.48          | Peak   |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Horizontal  
Note: n20 High Channel 5240 MHz Band 1




| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|--------|
| 1   | 5350.000        | 55.79          | -4.52         | 51.27           | 74.00          | 22.73       | Peak   |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Vertical  
Note: n20 High Channel 5240 MHz Band 1




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|--------|
| 1   | 5350.000        | 56.20          | -4.52         | 51.68           | 74.00          | 22.32       | Peak   |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
Polarization: Horizontal  
Note: n40 Low Channel 5190 MHz Band 1




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 5150.000           | 66.08             | -4.61            | 61.47              | 74.00             | 12.53          | Peak    |
| 2   | 5150.000           | 48.17             | -4.61            | 43.56              | 54.00             | 10.44          | Average |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
Polarization: Vertical  
Note: n40 Low Channel 5190 MHz Band 1




Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Horizontal  
Note: n40 High Channel 5230 MHz Band 1




| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|--------|
| 1   | 5350.000        | 55.60          | -4.52         | 51.08           | 74.00          | 22.92       | Peak   |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Vertical  
Note: n40 High Channel 5230 MHz Band 1




| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|--------|
| 1   | 5350.000        | 55.82          | -4.52         | 51.30           | 74.00          | 22.70       | Peak   |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
Polarization: Horizontal  
Note: ac80 Middle Channel 5210 MHz Band 1




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 5150.000           | 62.42             | -4.61            | 57.81              | 74.00             | 16.19          | Peak    |
| 2   | 5150.000           | 49.13             | -4.61            | 44.52              | 54.00             | 9.48           | Average |
| 3   | 5350.000           | 56.82             | -4.52            | 52.30              | 74.00             | 21.70          | Peak    |
| 4   | 5350.000           | 44.17             | -4.52            | 39.65              | 54.00             | 14.35          | Average |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
Polarization: Vertical  
Note: ac80 Middle Channel 5210 MHz Band 1




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 5150.000           | 59.79             | -4.61            | 55.18              | 74.00             | 18.82          | Peak    |
| 2   | 5150.000           | 46.76             | -4.61            | 42.15              | 54.00             | 11.85          | Average |
| 3   | 5350.000           | 56.98             | -4.52            | 52.46              | 74.00             | 21.54          | Peak    |
| 4   | 5350.000           | 43.80             | -4.52            | 39.28              | 54.00             | 14.72          | Average |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Horizontal  
Note: a Low Channel 5260 MHz Band 2




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5150.000           | 56.00             | -4.61            | 51.39              | 74.00             | 22.61          | Peak   |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Vertical  
Note: a Low Channel 5260 MHz Band 2




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5150.000           | 55.22             | -4.61            | 50.61              | 74.00             | 23.39          | Peak   |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Horizontal  
Note: a High Channel 5320 MHz Band 2




| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|--------|
| 1   | 5350.000        | 56.89          | -4.52         | 52.37           | 74.00          | 21.63       | Peak   |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Vertical  
Note: a High Channel 5320 MHz Band 2




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5350.000           | 56.08             | -4.52            | 51.56              | 74.00             | 22.44          | Peak   |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Horizontal  
Note: n20 Low Channel 5260 MHz Band 2




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5150.000           | 55.86             | -4.61            | 51.25              | 74.00             | 22.75          | Peak   |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Vertical  
Note: n20 Low Channel 5260 MHz Band 2




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5150.000           | 56.47             | -4.61            | 51.86              | 74.00             | 22.14          | Peak   |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
Polarization: Horizontal  
Note: n20 High Channel 5320 MHz Band 2




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 5350.000           | 57.52             | -4.52            | 53.00              | 74.00             | 21.00          | Peak    |
| 2   | 5350.000           | 44.81             | -4.52            | 40.29              | 54.00             | 13.71          | Average |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
Polarization: Vertical  
Note: n20 High Channel 5320 MHz Band 2




| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Remark  |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|---------|
| 1   | 5350.000        | 55.63          | -4.52         | 51.11           | 74.00          | 22.89       | Peak    |
| 2   | 5350.000        | 44.17          | -4.52         | 39.65           | 54.00          | 14.35       | Average |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Horizontal  
Note: n40 Low Channel 5270 MHz Band 2




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBUV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5150.000           | 56.61             | -4.61            | 52.00              | 74.00             | 22.00          | Peak   |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Vertical  
Note: n40 Low Channel 5270 MHz Band 2




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5150.000           | 55.25             | -4.61            | 50.64              | 74.00             | 23.36          | Peak   |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
Polarization: Horizontal  
Note: n40 High Channel 5310 MHz Band 2




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 5350.000           | 67.03             | -4.52            | 62.51              | 74.00             | 11.49          | Peak    |
| 2   | 5350.000           | 47.10             | -4.52            | 42.58              | 54.00             | 11.42          | Average |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
Polarization: Vertical  
Note: n40 High Channel 5310 MHz Band 2




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 5350.000           | 63.12             | -4.52            | 58.60              | 74.00             | 15.40          | Peak    |
| 2   | 5350.000           | 44.81             | -4.52            | 40.29              | 54.00             | 13.71          | Average |

Project No.: 2503S20876E-RF  
 Tester: Peter Rong  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
 Polarization: Horizontal  
 Note: ac80 Middle Channel 5290 MHz Band 2




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBUV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 5150.000           | 55.63             | -4.61            | 51.02              | 74.00             | 22.98          | Peak    |
| 2   | 5150.000           | 43.86             | -4.61            | 39.25              | 54.00             | 14.75          | Average |
| 3   | 5350.000           | 63.21             | -4.52            | 58.69              | 74.00             | 15.31          | Peak    |
| 4   | 5350.000           | 45.58             | -4.52            | 41.06              | 54.00             | 12.94          | Average |

Project No.: 2503S20876E-RF  
Tester: Peter Rong  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
Polarization: Vertical  
Note: ac80 Middle Channel 5290 MHz Band 2




| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Remark  |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|---------|
| 1   | 5150.000        | 55.53          | -4.61         | 50.92           | 74.00          | 23.08       | Peak    |
| 2   | 5150.000        | 43.30          | -4.61         | 38.69           | 54.00          | 15.31       | Average |
| 3   | 5350.000        | 59.02          | -4.52         | 54.50           | 74.00          | 19.50       | Peak    |
| 4   | 5350.000        | 45.88          | -4.52         | 41.36           | 54.00          | 12.64       | Average |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Horizontal  
Note: a Low Channel 5500 Mhz Band 3




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 5460.000           | 55.65             | -4.37            | 51.28              | 74.00             | 22.72          | Peak    |
| 2   | 5460.000           | 43.62             | -4.37            | 39.25              | 54.00             | 14.75          | Average |
| 3   | 5470.000           | 58.62             | -4.29            | 54.33              | 68.20             | 13.87          | Peak    |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Vertical  
Note: a Low Channel 5500 Mhz Band 3




| No.   | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Remark  |
|-------|-----------------|----------------|---------------|-----------------|----------------|-------------|---------|
| <hr/> |                 |                |               |                 |                |             |         |
| 1     | 5460.000        | 56.19          | -4.37         | 51.82           | 74.00          | 22.18       | Peak    |
| 2     | 5460.000        | 44.05          | -4.37         | 39.68           | 54.00          | 14.32       | Average |
| 3     | 5470.000        | 55.92          | -4.29         | 51.63           | 68.20          | 16.57       | Peak    |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Horizontal  
Note: a High Channel 5700 Mhz Band 3




| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|--------|
| 1   | 5725.000        | 55.82          | -4.06         | 51.76           | 68.20          | 16.44       | Peak   |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Vertical  
Note: a High Channel 5700 Mhz Band 3




| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|--------|
| 1   | 5725.000        | 57.16          | -4.06         | 53.10           | 68.20          | 15.10       | Peak   |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Horizontal  
Note: n20 Low Channel 5500 Mhz Band 3




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 5460.000           | 57.19             | -4.37            | 52.82              | 74.00             | 21.18          | Peak    |
| 2   | 5460.000           | 44.42             | -4.37            | 40.05              | 54.00             | 13.95          | Average |
| 3   | 5470.000           | 60.67             | -4.29            | 56.38              | 68.20             | 11.82          | Peak    |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Vertical  
Note: n20 Low Channel 5500 Mhz Band 3




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 5460.000           | 57.27             | -4.37            | 52.90              | 74.00             | 21.10          | Peak    |
| 2   | 5460.000           | 44.58             | -4.37            | 40.21              | 54.00             | 13.79          | Average |
| 3   | 5470.000           | 57.10             | -4.29            | 52.81              | 68.20             | 15.39          | Peak    |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Horizontal  
Note: n20 High Channel 5700 Mhz Band 3




| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|--------|
| 1   | 5725.000        | 59.83          | -4.06         | 55.77           | 68.20          | 12.43       | Peak   |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Vertical  
Note: n20 High Channel 5700 Mhz Band 3




| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|--------|
| 1   | 5725.000        | 57.86          | -4.06         | 53.80           | 68.20          | 14.40       | Peak   |

Project No.: 2503S20876E-RF  
 Tester: Mack Huang  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
 Polarization: Horizontal  
 Note: n40 Low Channel 5510 Mhz Band 3




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 5460.000           | 63.00             | -4.37            | 58.63              | 74.00             | 15.37          | Peak    |
| 2   | 5460.000           | 50.62             | -4.37            | 46.25              | 54.00             | 7.75           | Average |
| 3   | 5470.000           | 68.34             | -4.29            | 64.05              | 68.20             | 4.15           | Peak    |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
Polarization: Vertical  
Note: n40 Low Channel 5510 Mhz Band 3




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 5460.000           | 56.22             | -4.37            | 51.85              | 74.00             | 22.15          | Peak    |
| 2   | 5460.000           | 44.04             | -4.37            | 39.67              | 54.00             | 14.33          | Average |
| 3   | 5470.000           | 61.60             | -4.29            | 57.31              | 68.20             | 10.89          | Peak    |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Horizontal  
Note: n40 High Channel 5670 Mhz Band 3




| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|--------|
| 1   | 5725.000        | 55.92          | -4.06         | 51.86           | 68.20          | 16.34       | Peak   |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Vertical  
Note: n40 High Channel 5670 Mhz Band 3




| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|--------|
| 1   | 5725.000        | 55.19          | -4.06         | 51.13           | 68.20          | 17.07       | Peak   |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto  
Polarization: Horizontal  
Note: ac80 Low Channel 5530 Mhz Band 3




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 5460.000           | 58.00             | -4.37            | 53.63              | 74.00             | 20.37          | Peak    |
| 2   | 5460.000           | 45.76             | -4.37            | 41.39              | 54.00             | 12.61          | Average |
| 3   | 5470.000           | 60.77             | -4.29            | 56.48              | 68.20             | 11.72          | Peak    |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Vertical  
Note: ac80 Low Channel 5530 Mhz Band 3




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|---------|
| 1   | 5460.000           | 55.64             | -4.37            | 51.27              | 74.00             | 22.73          | Peak    |
| 2   | 5460.000           | 43.94             | -4.37            | 39.57              | 54.00             | 14.43          | Average |
| 3   | 5470.000           | 56.16             | -4.29            | 51.87              | 68.20             | 16.33          | Peak    |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Horizontal  
Note: ac80 High Channel 5610 Mhz Band 3




| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|--------|
| 1   | 5725.000        | 56.16          | -4.06         | 52.10           | 68.20          | 16.10       | Peak   |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Vertical  
Note: ac80 High Channel 5610 Mhz Band 3




| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|--------|
| 1   | 5725.000        | 55.71          | -4.06         | 51.65           | 68.20          | 16.55       | Peak   |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Horizontal  
Note: a Low Channel 5745 MHz Band 4




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5650.000           | 56.46             | -3.89            | 52.57              | 68.20             | 15.63          | Peak   |
| 2   | 5700.000           | 55.32             | -4.15            | 51.17              | 105.20            | 54.03          | Peak   |
| 3   | 5720.000           | 55.60             | -4.08            | 51.52              | 110.80            | 59.28          | Peak   |
| 4   | 5725.000           | 56.93             | -4.06            | 52.87              | 122.20            | 69.33          | Peak   |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Vertical  
Note: a Low Channel 5745 MHz Band 4




| No. | Frequency (MHz) | Reading (dBμV) | Factor (dB/m) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) | Remark |
|-----|-----------------|----------------|---------------|-----------------|----------------|-------------|--------|
| 1   | 5650.000        | 55.52          | -3.89         | 51.63           | 68.20          | 16.57       | Peak   |
| 2   | 5700.000        | 55.70          | -4.15         | 51.55           | 105.20         | 53.65       | Peak   |
| 3   | 5720.000        | 55.78          | -4.08         | 51.70           | 110.80         | 59.10       | Peak   |
| 4   | 5725.000        | 55.92          | -4.06         | 51.86           | 122.20         | 70.34       | Peak   |

Project No.: 2503S20876E-RF  
 Tester: Mack Huang  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
 Polarization: Horizontal  
 Note: a High Channel 5825 MHz Band 4




| No.   | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-------|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| <hr/> |                    |                   |                  |                    |                   |                |        |
| 1     | 5850.000           | 56.13             | -4.30            | 51.83              | 122.20            | 70.37          | Peak   |
| 2     | 5855.000           | 56.50             | -4.31            | 52.19              | 110.80            | 58.61          | Peak   |
| 3     | 5875.000           | 55.25             | -4.36            | 50.89              | 105.20            | 54.31          | Peak   |
| 4     | 5925.000           | 55.24             | -4.14            | 51.10              | 68.20             | 17.10          | Peak   |

Project No.: 2503S20876E-RF  
 Tester: Mack Huang  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
 Polarization: Vertical  
 Note: a High Channel 5825 MHz Band 4




| No.   | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-------|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| <hr/> |                    |                   |                  |                    |                   |                |        |
| 1     | 5850.000           | 57.33             | -4.30            | 53.03              | 122.20            | 69.17          | Peak   |
| 2     | 5855.000           | 55.61             | -4.31            | 51.30              | 110.80            | 59.50          | Peak   |
| 3     | 5875.000           | 56.11             | -4.36            | 51.75              | 105.20            | 53.45          | Peak   |
| 4     | 5925.000           | 56.39             | -4.14            | 52.25              | 68.20             | 15.95          | Peak   |

Project No.: 2503S20876E-RF  
 Tester: Mack Huang  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
 Polarization: Horizontal  
 Note: n20 Low Channel 5745 MHz Band 4




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5650.000           | 55.47             | -3.89            | 51.58              | 68.20             | 16.62          | Peak   |
| 2   | 5700.000           | 56.47             | -4.15            | 52.32              | 105.20            | 52.88          | Peak   |
| 3   | 5720.000           | 55.59             | -4.08            | 51.51              | 110.80            | 59.29          | Peak   |
| 4   | 5725.000           | 61.11             | -4.06            | 57.05              | 122.20            | 65.15          | Peak   |

Project No.: 2503S20876E-RF  
 Tester: Mack Huang  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
 Polarization: Vertical  
 Note: n20 Low Channel 5745 MHz Band 4




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5650.000           | 55.48             | -3.89            | 51.59              | 68.20             | 16.61          | Peak   |
| 2   | 5700.000           | 56.28             | -4.15            | 52.13              | 105.20            | 53.07          | Peak   |
| 3   | 5720.000           | 56.29             | -4.08            | 52.21              | 110.80            | 58.59          | Peak   |
| 4   | 5725.000           | 57.85             | -4.06            | 53.79              | 122.20            | 68.41          | Peak   |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Horizontal  
Note: n20 High Channel 5825 MHz Band 4




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5850.000           | 54.33             | -4.30            | 50.03              | 122.20            | 72.17          | Peak   |
| 2   | 5855.000           | 54.70             | -4.31            | 50.39              | 110.80            | 60.41          | Peak   |
| 3   | 5875.000           | 54.41             | -4.36            | 50.05              | 105.20            | 55.15          | Peak   |
| 4   | 5925.000           | 56.29             | -4.14            | 52.15              | 68.20             | 16.05          | Peak   |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Vertical  
Note: n20 High Channel 5825 MHz Band 4




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5850.000           | 55.56             | -4.30            | 51.26              | 122.20            | 70.94          | Peak   |
| 2   | 5855.000           | 55.49             | -4.31            | 51.18              | 110.80            | 59.62          | Peak   |
| 3   | 5875.000           | 53.89             | -4.36            | 49.53              | 105.20            | 55.67          | Peak   |
| 4   | 5925.000           | 55.83             | -4.14            | 51.69              | 68.20             | 16.51          | Peak   |

Project No.: 2503S20876E-RF  
 Tester: Mack Huang  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
 Polarization: Horizontal  
 Note: n40 Low Channel 5755 MHz Band 4




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5650.000           | 56.23             | -3.89            | 52.34              | 68.20             | 15.86          | Peak   |
| 2   | 5700.000           | 55.52             | -4.15            | 51.37              | 105.20            | 53.83          | Peak   |
| 3   | 5720.000           | 66.33             | -4.08            | 62.25              | 110.80            | 48.55          | Peak   |
| 4   | 5725.000           | 66.92             | -4.06            | 62.86              | 122.20            | 59.34          | Peak   |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Vertical  
Note: n40 Low Channel 5755 MHz Band 4




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5650.000           | 53.59             | -3.89            | 49.70              | 68.20             | 18.50          | Peak   |
| 2   | 5700.000           | 55.57             | -4.15            | 51.42              | 105.20            | 53.78          | Peak   |
| 3   | 5720.000           | 61.50             | -4.08            | 57.42              | 110.80            | 53.38          | Peak   |
| 4   | 5725.000           | 61.43             | -4.06            | 57.37              | 122.20            | 64.83          | Peak   |

Project No.: 2503S20876E-RF  
 Tester: Mack Huang  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
 Polarization: Horizontal  
 Note: n40 High Channel 5795 MHz Band 4




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5850.000           | 55.59             | -4.30            | 51.29              | 122.20            | 70.91          | Peak   |
| 2   | 5855.000           | 54.96             | -4.31            | 50.65              | 110.80            | 60.15          | Peak   |
| 3   | 5875.000           | 54.56             | -4.36            | 50.20              | 105.20            | 55.00          | Peak   |
| 4   | 5925.000           | 55.48             | -4.14            | 51.34              | 68.20             | 16.86          | Peak   |

Project No.: 2503S20876E-RF  
 Tester: Mack Huang  
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
 Polarization: Vertical  
 Note: n40 High Channel 5795 MHz Band 4




| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5850.000           | 56.10             | -4.30            | 51.80              | 122.20            | 70.40          | Peak   |
| 2   | 5855.000           | 55.83             | -4.31            | 51.52              | 110.80            | 59.28          | Peak   |
| 3   | 5875.000           | 55.68             | -4.36            | 51.32              | 105.20            | 53.88          | Peak   |
| 4   | 5925.000           | 55.96             | -4.14            | 51.82              | 68.20             | 16.38          | Peak   |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Horizontal  
Note: ac80 Middle Channel 5775 MHz Band 4



| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5650.000           | 55.73             | -3.89            | 51.84              | 68.20             | 16.36          | Peak   |
| 2   | 5700.000           | 57.73             | -4.15            | 53.58              | 105.20            | 51.62          | Peak   |
| 3   | 5720.000           | 60.50             | -4.08            | 56.42              | 110.80            | 54.38          | Peak   |
| 4   | 5725.000           | 60.40             | -4.06            | 56.34              | 122.20            | 65.86          | Peak   |
| 5   | 5850.000           | 56.09             | -4.30            | 51.79              | 122.20            | 70.41          | Peak   |
| 6   | 5855.000           | 55.62             | -4.31            | 51.31              | 110.80            | 59.49          | Peak   |
| 7   | 5875.000           | 55.92             | -4.36            | 51.56              | 105.20            | 53.64          | Peak   |
| 8   | 5925.000           | 55.80             | -4.14            | 51.66              | 68.20             | 16.54          | Peak   |

Project No.: 2503S20876E-RF  
Tester: Mack Huang  
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec  
Polarization: Vertical  
Note: ac80 Middle Channel 5775 MHz Band 4



| No. | Frequency<br>(MHz) | Reading<br>(dBμV) | Factor<br>(dB/m) | Result<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|------------------|--------------------|-------------------|----------------|--------|
| 1   | 5650.000           | 55.72             | -3.89            | 51.83              | 68.20             | 16.37          | Peak   |
| 2   | 5700.000           | 56.18             | -4.15            | 52.03              | 105.20            | 53.17          | Peak   |
| 3   | 5720.000           | 56.54             | -4.08            | 52.46              | 110.80            | 58.34          | Peak   |
| 4   | 5725.000           | 56.04             | -4.06            | 51.98              | 122.20            | 70.22          | Peak   |
| 5   | 5850.000           | 56.39             | -4.30            | 52.09              | 122.20            | 70.11          | Peak   |
| 6   | 5855.000           | 56.37             | -4.31            | 52.06              | 110.80            | 58.74          | Peak   |
| 7   | 5875.000           | 55.72             | -4.36            | 51.36              | 105.20            | 53.84          | Peak   |
| 8   | 5925.000           | 55.68             | -4.14            | 51.54              | 68.20             | 16.66          | Peak   |

### **4.3 RF Conducted Data**

Please refer to Annex "2503S20876E-RF-00D\_Appendix A" for detail test data.

## **5. EUT PHOTOGRAPHS**

---

Please refer to the attachment 2503S20876E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and 2503S20876E-RF-INP EUT INTERNAL PHOTOGRAPHS

## **6. TEST SETUP PHOTOGRAPHS**

---

Please refer to the attachment 2503S20876E-RF-00D-TSP TEST SETUP PHOTOGRAPHS.

**===== END OF REPORT =====**