



# FCC RF Test Report

## (WCDMA)

**Applicant:** INFINIX MOBILITY LIMITED

**Address of Applicant:** FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE  
19-25 SHAN MEI STREET FOTAN NT HONGKONG

**Equipment Under Test (EUT)**

Product Name: Mobile Phone

Model No.: X6833B

Trade Mark: Infinix

**FCC ID:** 2AIZN-X6833B

**Applicable Standards:** FCC CFR Title 47 Part 2, 22H, 24E, 27L

**Date of Sample Receipt:** 13 Feb., 2023

**Date of Test:** 14 Feb., to 21 Mar., 2023

**Date of Report Issued:** 22 Mar., 2023

**Test Result:** PASS

**Tested by:**

*Tanet Wei*  
Test Engineer

**Date:**

*22 Mar., 2023*

**Reviewed by:**

*Wenwen Zhang*  
Project Engineer

**Date:**

*22 Mar., 2023*

**Approved by:**

*Wenwen Zhang*  
Manager

**Date:**

*22 Mar., 2023*

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in above the application standard version. Test results reported herein relate only to the item(s) tested.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

## 1 Version

| Version No. | Date          | Description |
|-------------|---------------|-------------|
| 00          | 22 Mar., 2023 | Original    |
|             |               |             |
|             |               |             |
|             |               |             |
|             |               |             |

## 2 Contents

Page

|                                                                   |           |
|-------------------------------------------------------------------|-----------|
| <b>Cover Page .....</b>                                           | <b>1</b>  |
| <b>1 Version .....</b>                                            | <b>2</b>  |
| <b>2 Contents.....</b>                                            | <b>3</b>  |
| <b>3 General Information.....</b>                                 | <b>4</b>  |
| 3.1 Client Information .....                                      | 4         |
| 3.2 General Description of E.U.T. ....                            | 4         |
| 3.3 Test Mode and Environment .....                               | 5         |
| 3.4 Description of Test Auxiliary Equipment .....                 | 5         |
| 3.5 Measurement Uncertainty .....                                 | 5         |
| 3.6 Additions to, Deviations, or Exclusions from the Method ..... | 5         |
| 3.7 Laboratory Facility .....                                     | 5         |
| 3.8 Laboratory Location.....                                      | 6         |
| 3.9 Test Instruments List .....                                   | 6         |
| <b>4 Measurement Setup and Procedure .....</b>                    | <b>7</b>  |
| 4.1 Test Channel .....                                            | 7         |
| 4.2 Test Setup .....                                              | 8         |
| 4.3 Test Procedure .....                                          | 9         |
| <b>5 Test Results.....</b>                                        | <b>10</b> |
| 5.1 Summary .....                                                 | 10        |
| 5.1.1 Clause and Data Summary.....                                | 10        |
| 5.1.2 Test Limit.....                                             | 11        |
| 5.2 Field Strength of Spurious Radiation Measurement .....        | 12        |

### 3 General Information

#### 3.1 Client Information

|               |                                                                                                                        |
|---------------|------------------------------------------------------------------------------------------------------------------------|
| Applicant:    | INFINIX MOBILITY LIMITED                                                                                               |
| Address:      | FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI STREET FOTAN NT HONGKONG                                |
| Manufacturer: | INFINIX MOBILITY LIMITED                                                                                               |
| Address:      | FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI STREET FOTAN NT HONGKONG                                |
| Factory:      | SHENZHEN TECNO TECHNOLOGY CO., LTD.                                                                                    |
| Address:      | 101, Building 24, Waijing Industrial Park, Fumin Community, Fucheng Street, Longhua District, Shenzhen City, P.R.China |

#### 3.2 General Description of E.U.T.

|                            |                                                                                                                                                     |                                 |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| Product Name:              | Mobile Phone                                                                                                                                        |                                 |
| Model No.:                 | X6833B                                                                                                                                              |                                 |
| Operation Frequency Range: | WCDMA band II:                                                                                                                                      | 1852.4 MHz - 1907.6 MHz         |
|                            | WCDMA band IV:                                                                                                                                      | 1712.4 MHz - 1752.6 MHz         |
|                            | WCDMA band V:                                                                                                                                       | 826.4 MHz - 846.6 MHz           |
| Modulation Type:           | <input checked="" type="checkbox"/> RMC(QPSK) <input checked="" type="checkbox"/> HSUPA(QPSK) <input checked="" type="checkbox"/> HSDPA(QPSK,16QAM) |                                 |
| Antenna Type:              | Internal Antenna                                                                                                                                    |                                 |
| Antenna Gain:              | WCDMA band II:                                                                                                                                      | -0.5 dBi (declare by Applicant) |
|                            | WCDMA band IV:                                                                                                                                      | -0.7 dBi (declare by Applicant) |
|                            | WCDMA band V:                                                                                                                                       | -1.5 dBi (declare by Applicant) |
| Power Supply:              | Rechargeable Li-ion Polymer Battery DC3.87V, 4900mAh                                                                                                |                                 |
| AC Adapter:                | Model: U450XSA<br>Input: AC100-240V, 50/60Hz, 1.8A<br>Output: DC 5.0V, 2.0A or 11.0V, 4.1A MAX                                                      |                                 |
| Test Sample Condition:     | The test samples were provided in good working order with no visible defects.                                                                       |                                 |

### 3.3 Test Mode and Environment

| Test Mode:                                                                                                                                                                                                                                                                                                                                                                              |                                                                 |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------|
| RMC mode:                                                                                                                                                                                                                                                                                                                                                                               | Keep the EUT communication with simulated station in RMC mode   |
| HSDPA mode:                                                                                                                                                                                                                                                                                                                                                                             | Keep the EUT communication with simulated station in HSDPA mode |
| HSUPA mode:                                                                                                                                                                                                                                                                                                                                                                             | Keep the EUT communication with simulated station in HSUPA mode |
| <b>Remark:</b> The EUT has been tested under continuous transmitting mode. Channel Low, Mid and High for each type band with rated data rate were chosen for full testing. The field strength of spurious radiation emission was measured as EUT stand-up position (H mode) and lie down position (E1, E2 mode) for these modes. Just the worst case position (H mode) shown in report. |                                                                 |
| Operating Environment:                                                                                                                                                                                                                                                                                                                                                                  |                                                                 |
| Temperature:                                                                                                                                                                                                                                                                                                                                                                            | Normal: 15°C ~ 35°C, Extreme: -30°C ~ +50°C                     |
| Humidity:                                                                                                                                                                                                                                                                                                                                                                               | 20 % ~ 75 % RH                                                  |
| Atmospheric Pressure:                                                                                                                                                                                                                                                                                                                                                                   | 1008 mbar                                                       |
| Voltage:                                                                                                                                                                                                                                                                                                                                                                                | Nominal: 3.87 Vdc, Extreme: Low 3.45 Vdc, High 4.45 Vdc         |

### 3.4 Description of Test Auxiliary Equipment

| Test Equipment    | Manufacturer | Model No. | Serial No. |
|-------------------|--------------|-----------|------------|
| Simulated Station | Anritsu      | MT8820C   | 6201026545 |

### 3.5 Measurement Uncertainty

| Parameter                                                                                                                                                                                                                                                                                                            | Expanded Uncertainty<br>(Confidence of 95%(U = 2Uc(y))) |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------|
| Radiated Emission (30MHz ~ 1GHz) (3m SAC)                                                                                                                                                                                                                                                                            | 3.8 dB                                                  |
| Radiated Emission (1GHz ~ 18GHz) (3m SAC)                                                                                                                                                                                                                                                                            | 3.6 dB                                                  |
| Radiated Emission (18GHz ~ 40GHz) (3m SAC)                                                                                                                                                                                                                                                                           | 5.34 dB                                                 |
| <b>Note:</b> All the measurement uncertainty value were shown with a coverage k=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance. |                                                         |

### 3.6 Additions to, Deviations, or Exclusions from the Method

|    |
|----|
| No |
|----|

### 3.7 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Designation No.: CN1211**

JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber and 10m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L15527**

JianYan Testing Group Shenzhen Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L15527.

● **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

### 3.8 Laboratory Location

JianYan Testing Group Shenzhen Co., Ltd.

Address: No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info-JYTee@lets.com, Website: <http://jyt.lets.com>

### 3.9 Test Instruments List

| Radiated Emission(3m SAC):    |                 |                 |                  |                      |                          |
|-------------------------------|-----------------|-----------------|------------------|----------------------|--------------------------|
| Test Equipment                | Manufacturer    | Model No.       | Manage No.       | Cal. Date (mm-dd-yy) | Cal. Due date (mm-dd-yy) |
| 3m SAC                        | ETS             | 9m*6m*6m        | WXJ001-1         | 04-14-2021           | 04-13-2024               |
| Loop Antenna                  | Schwarzbeck     | FMZB 1519 B     | WXJ002-4         | 02-09-2023           | 02-08-2024               |
| BiConiLog Antenna             | Schwarzbeck     | VULB9163        | WXJ002           | 02-09-2023           | 02-08-2024               |
| Biconical Antenna             | Schwarzbeck     | VUBA9117        | WXJ002-1         | 07-02-2021           | 07-01-2024               |
| Horn Antenna                  | Schwarzbeck     | BBHA9120D       | WXJ002-2         | 02-09-2023           | 02-08-2024               |
| Horn Antenna                  | Schwarzbeck     | BBHA9120D       | WXJ002-3         | 04-07-2022           | 04-06-2023               |
| Horn Antenna                  | Schwarzbeck     | BBHA9170        | WXJ002-5         | 04-07-2022           | 04-06-2023               |
| Horn Antenna                  | Schwarzbeck     | BBHA9170        | WXJ002-6         | 04-07-2022           | 04-06-2023               |
| Pre-amplifier (30MHz ~ 1GHz)  | Schwarzbeck     | BBV9743B        | WXJ001-2         | 01-10-2023           | 01-09-2024               |
| Pre-amplifier (1GHz ~ 18GHz)  | SKET            | LNPA_0118G-50   | WXJ001-3         | 01-10-2023           | 01-09-2024               |
| Pre-amplifier (18GHz ~ 40GHz) | RF System       | TRLA-180400G45B | WXJ002-7         | 03-30-2022           | 03-29-2023               |
| EMI Test Receiver             | Rohde & Schwarz | ESRP7           | WXJ003-1         | 01-11-2023           | 01-10-2024               |
| Spectrum Analyzer             | Rohde & Schwarz | FSP 30          | WXJ004           | 01-10-2023           | 01-09-2024               |
| Spectrum Analyzer             | KEYSIGHT        | N9010B          | WXJ004-2         | 10-17-2022           | 10-16-2023               |
| Coaxial Cable (30MHz ~ 1GHz)  | JYTSZ           | JYT3M-1G-NN-8M  | WXG001-4         | 01-18-2023           | 01-17-2024               |
| Coaxial Cable (1GHz ~ 18GHz)  | JYTSZ           | JYT3M-18G-NN-8M | WXG001-5         | 01-18-2023           | 01-17-2024               |
| Coaxial Cable (18GHz ~ 40GHz) | JYTSZ           | JYT3M-40G-SS-8M | WXG001-7         | 01-18-2023           | 01-17-2024               |
| Band Reject Filter Group      | Tonscend        | JS0806-F        | WXJ089           | N/A                  |                          |
| Test Software                 | Tonscend        | TS+             | Version: 3.0.0.1 |                      |                          |

| Conducted Method:            |                 |           |                     |                      |                          |
|------------------------------|-----------------|-----------|---------------------|----------------------|--------------------------|
| Test Equipment               | Manufacturer    | Model No. | Manage No.          | Cal. Date (mm-dd-yy) | Cal. Due date (mm-dd-yy) |
| Spectrum Analyzer            | Agilent         | N9020A    | WXJ004-1            | 10-17-2022           | 10-16-2023               |
| Simulated Station            | Rohde & Schwarz | CMW500    | WXJ081              | 06-29-2022           | 06-28-2023               |
| Temperature Humidity Chamber | ZHONG ZHI       | CZ-A-80D  | WXJ032-3            | 03-19-2021           | 03-18-2023               |
| DC Power Supply              | Keysight        | E3642A    | WXJ025-2            | N/A                  |                          |
| RF Control Unit              | Tonscend        | JS0806-1  | WXG010              | N/A                  |                          |
| Band Reject Filter Group     | Tonscend        | JS0806-F  | WXG010-1            | N/A                  |                          |
| Test Software                | Tonscend        | TS+       | Version: 2.6.9.0526 |                      |                          |

## 4 Measurement Setup and Procedure

### 4.1 Test Channel


According to ANSI C63.26-2015 chapter 5.1.2.1 Table 2 requirement, select lowest channel, middle channel, and highest channel in the frequency range in which device operates for testing. The detailed frequency points are as follows:

| WCDMA band II  |                 |                |                 |                 |                 |
|----------------|-----------------|----------------|-----------------|-----------------|-----------------|
| Lowest channel |                 | Middle channel |                 | Highest channel |                 |
| Channel No.    | Frequency (MHz) | Channel No.    | Frequency (MHz) | Channel No.     | Frequency (MHz) |
| 9262           | 1852.4          | 9400           | 1880.0          | 9538            | 1907.6          |
| WCDMA band IV  |                 |                |                 |                 |                 |
| Lowest channel |                 | Middle channel |                 | Highest channel |                 |
| Channel No.    | Frequency (MHz) | Channel No.    | Frequency (MHz) | Channel No.     | Frequency (MHz) |
| 1312           | 1712.4          | 1413           | 1732.6          | 1513            | 1752.6          |
| WCDMA band V   |                 |                |                 |                 |                 |
| Lowest channel |                 | Middle channel |                 | Highest channel |                 |
| Channel No.    | Frequency (MHz) | Channel No.    | Frequency (MHz) | Channel No.     | Frequency (MHz) |
| 4132           | 826.4           | 4183           | 836.6           | 4233            | 846.6           |


## 4.2 Test Setup

### 1) Radiated emission measurement:


Below 1GHz (3m SAC)



Above 1GHz (3m SAC)



### 2) Conducted test method



### 4.3 Test Procedure

| Test method           | Test step                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Radiated emission     | <p><b>For below 1GHz:</b></p> <ol style="list-style-type: none"> <li>The EUT was placed on the table top of a rotating table 0.8 m the ground at a 3 m semi anechoic chamber. The measurement distance from the EUT to the receiving antenna is 3 m.</li> <li>EUT works in each mode of operation that needs to be tested , and having the EUT continuously working, respectively on 3 axis (X, Y &amp; Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations.</li> <li>Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.</li> </ol> <p><b>For above 1GHz:</b></p> <ol style="list-style-type: none"> <li>The EUT was placed on the table top of a rotating table 1.5 m the ground at a 3 m fully anechoic room. The measurement distance from the EUT to the receiving antenna is 3 m.</li> <li>EUT works in each mode of operation that needs to be tested , and having the EUT continuously working, respectively on 3 axis (X, Y &amp; Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations.</li> <li>Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.</li> </ol> |
| Conducted test method | <ol style="list-style-type: none"> <li>The WCDMA antenna port of EUT was connected to the test port of the test system through an RF cable.</li> <li>The EUT is keeping in continuous transmission mode and tested in all modulation modes.</li> <li>Open the test software, prepare a test plan, and control the system through the software. After the test is completed, the test report is exported through the test software.</li> </ol>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |

## 5 Test Results

### 5.1 Summary

#### 5.1.1 Clause and Data Summary

| Test items                                                                                                                                                                                                                                                                                                    | Standard clause                                                           | Test data        | Result |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|------------------|--------|
| RF Exposure (SAR)                                                                                                                                                                                                                                                                                             | Part 1.1307<br>Part 2.1093                                                | See SAR Report   | Pass   |
| RF Output Power                                                                                                                                                                                                                                                                                               | Part 2.1046<br>Part 22.913 (a)(5)<br>Part 24.232 (c)<br>Part 27.50 (d)(4) | Appendix – WCDMA | Pass   |
| Peak-to-Average Power Ratio                                                                                                                                                                                                                                                                                   | Part 24.232 (d)<br>Part 27.50(d)(5)                                       | Appendix – WCDMA | Pass   |
| Modulation Characteristics                                                                                                                                                                                                                                                                                    | Part 2.1047                                                               | Appendix – WCDMA | Pass   |
| 26dB Emission Bandwidth<br>99% Occupied Bandwidth                                                                                                                                                                                                                                                             | Part 2.1049                                                               | Appendix – WCDMA | Pass   |
| Out of Band Emission at Antenna<br>Terminals                                                                                                                                                                                                                                                                  | Part 2.1051<br>Part 22.917 (a)<br>Part 24.238 (a)<br>Part 27.53(h)        | Appendix – WCDMA | Pass   |
| Field Strength of Spurious Radiation                                                                                                                                                                                                                                                                          | Part 2.1053<br>Part 22.917 (a)<br>Part 24.238 (a)<br>Part 27.53(h)        | See Section 5.2  | Pass   |
| Frequency Stability vs. Temperature                                                                                                                                                                                                                                                                           | Part 22.355<br>Part 24.235<br>Part 27.54<br>Part 2.1055(a)(1)(b)          | Appendix – WCDMA | Pass   |
| Frequency Stability vs. Voltage                                                                                                                                                                                                                                                                               | Part 22.355<br>Part 24.235<br>Part 27.54<br>Part 2.1055(d)(2)             | Appendix – WCDMA | Pass   |
| <b>Remark:</b><br>1. Pass: The EUT complies with the essential requirements in the standard.<br>2. The cable insertion loss used by "RF Output Power" and other conduction measurement items is 0.5dB (Fundamental Frequency below 1GHz)/1.0dB (Fundamental Frequency above 1GHz) (provided by the customer). |                                                                           |                  |        |
| <b>Test Method:</b>                                                                                                                                                                                                                                                                                           | ANSI/TIA-603-E-2016<br>ANSI C63.26-2015                                   |                  |        |

## 5.1.2 Test Limit

| Test items                                                                            | Limit                                                                                                                                                                                                                   |
|---------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RF Output Power                                                                       | <b>WCDMA band II:</b> 2W EIRP<br><b>WCDMA band IV:</b> 1W EIRP<br><b>WCDMA band V:</b> 7W ERP                                                                                                                           |
| Peak-to-Average Power Ratio                                                           | The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB                                                                                                                                                |
| Modulation Characteristics                                                            | N/A                                                                                                                                                                                                                     |
| 26dB Emission Bandwidth<br>99% Occupied Bandwidth                                     | N/A                                                                                                                                                                                                                     |
| Out of Band Emission at Antenna Terminals<br><br>Field Strength of Spurious Radiation | The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.                                           |
| Frequency Stability vs. Temperature<br><br>Frequency Stability vs. Voltage            | <b>WCDMA band II:</b><br>The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.                                                               |
|                                                                                       | <b>WCDMA band IV:</b><br>The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.                                                            |
|                                                                                       | <b>WCDMA band V:</b><br>Except as otherwise provided in this part, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table C-1 of this section. |

TABLE C-1—FREQUENCY TOLERANCE FOR TRANSMITTERS IN THE PUBLIC MOBILE SERVICES

| Frequency range (MHz) | Base, fixed (ppm) | Mobile >3 watts (ppm) | Mobile ≤3 watts (ppm) |
|-----------------------|-------------------|-----------------------|-----------------------|
| 25 to 50              | 20.0              | 20.0                  | 50.0                  |
| 50 to 450             | 5.0               | 5.0                   | 50.0                  |
| 450 to 512            | 2.5               | 5.0                   | 5.0                   |
| 821 to 896            | 1.5               | 2.5                   | 2.5                   |
| 928 to 929            | 5.0               | n/a                   | n/a                   |
| 929 to 960            | 1.5               | n/a                   | n/a                   |
| 2110 to 2220          | 10.0              | n/a                   | n/a                   |

## 5.2 Field Strength of Spurious Radiation Measurement

| WCDMA band II                                                                                                      |                     |             |             |             |             |              |
|--------------------------------------------------------------------------------------------------------------------|---------------------|-------------|-------------|-------------|-------------|--------------|
| Lowest channel                                                                                                     |                     |             |             |             |             |              |
| Frequency (MHz)                                                                                                    | Reading Level (dBm) | Factor (dB) | Level (dBm) | Limit (dBm) | Margin (dB) | Polarization |
| 3704.80                                                                                                            | -49.55              | -1.34       | -50.89      | -13.00      | 37.89       | Vertical     |
| 5557.20                                                                                                            | -50.41              | 5.49        | -44.92      | -13.00      | 31.92       | Vertical     |
| 3704.80                                                                                                            | -49.14              | -1.83       | -50.97      | -13.00      | 37.97       | Horizontal   |
| 5557.20                                                                                                            | -50.64              | 3.83        | -46.81      | -13.00      | 33.81       | Horizontal   |
| Middle channel                                                                                                     |                     |             |             |             |             |              |
| Frequency (MHz)                                                                                                    | Reading Level (dBm) | Factor (dB) | Level (dBm) | Limit (dBm) | Margin (dB) | Polarization |
| 3760.00                                                                                                            | -49.59              | -1.06       | -50.65      | -13.00      | 37.65       | Vertical     |
| 5640.00                                                                                                            | -50.81              | 7.14        | -43.67      | -13.00      | 30.67       | Vertical     |
| 3760.00                                                                                                            | -49.34              | -1.55       | -50.89      | -13.00      | 37.89       | Horizontal   |
| 5640.00                                                                                                            | -50.86              | 4.45        | -46.41      | -13.00      | 33.41       | Horizontal   |
| Highest channel                                                                                                    |                     |             |             |             |             |              |
| Frequency (MHz)                                                                                                    | Reading Level (dBm) | Factor (dB) | Level (dBm) | Limit (dBm) | Margin (dB) | Polarization |
| 3815.20                                                                                                            | -49.95              | -0.77       | -50.72      | -13.00      | 37.72       | Vertical     |
| 5722.80                                                                                                            | -51.04              | 8.52        | -42.52      | -13.00      | 29.52       | Vertical     |
| 3815.20                                                                                                            | -49.25              | -1.25       | -50.50      | -13.00      | 37.50       | Horizontal   |
| 5722.80                                                                                                            | -51.16              | 5.82        | -45.34      | -13.00      | 32.34       | Horizontal   |
| <b>Remark:</b><br>1. The emission levels of below 1 GHz are lower than the limit 10dB, so not show in test report. |                     |             |             |             |             |              |

| WCDMA band IV                                                                                                      |                     |             |             |             |             |              |
|--------------------------------------------------------------------------------------------------------------------|---------------------|-------------|-------------|-------------|-------------|--------------|
| Lowest channel                                                                                                     |                     |             |             |             |             |              |
| Frequency (MHz)                                                                                                    | Reading Level (dBm) | Factor (dB) | Level (dBm) | Limit (dBm) | Margin (dB) | Polarization |
| 3424.40                                                                                                            | -48.01              | -4.09       | -52.10      | -13.00      | 39.10       | Vertical     |
| 5136.60                                                                                                            | -50.03              | 4.64        | -45.39      | -13.00      | 32.39       | Vertical     |
| 6848.80                                                                                                            | -51.81              | 10.69       | -41.12      | -13.00      | 28.12       | Vertical     |
| 3424.40                                                                                                            | -48.45              | -4.19       | -52.64      | -13.00      | 39.64       | Horizontal   |
| 5136.60                                                                                                            | -50.71              | 4.17        | -46.54      | -13.00      | 33.54       | Horizontal   |
| 6848.80                                                                                                            | -51.12              | 9.63        | -41.49      | -13.00      | 28.49       | Horizontal   |
| Middle channel                                                                                                     |                     |             |             |             |             |              |
| Frequency (MHz)                                                                                                    | Reading Level (dBm) | Factor (dB) | Level (dBm) | Limit (dBm) | Margin (dB) | Polarization |
| 3464.80                                                                                                            | -48.1               | -3.00       | -51.10      | -13.00      | 38.10       | Vertical     |
| 5197.20                                                                                                            | -49.84              | 4.10        | -45.74      | -13.00      | 32.74       | Vertical     |
| 6929.60                                                                                                            | -51.74              | 11.18       | -40.56      | -13.00      | 27.56       | Vertical     |
| 3464.80                                                                                                            | -48.44              | -3.11       | -51.55      | -13.00      | 38.55       | Horizontal   |
| 5197.20                                                                                                            | -50.24              | 3.6         | -46.64      | -13.00      | 33.64       | Horizontal   |
| 6929.60                                                                                                            | -50.73              | 9.86        | -40.87      | -13.00      | 27.87       | Horizontal   |
| Highest channel                                                                                                    |                     |             |             |             |             |              |
| Frequency (MHz)                                                                                                    | Reading Level (dBm) | Factor (dB) | Level (dBm) | Limit (dBm) | Margin (dB) | Polarization |
| 3505.20                                                                                                            | -48.20              | -2.01       | -50.21      | -13.00      | 37.21       | Vertical     |
| 5257.80                                                                                                            | -49.77              | 3.73        | -46.04      | -13.00      | 33.04       | Vertical     |
| 7010.40                                                                                                            | -51.52              | 11.08       | -40.44      | -13.00      | 27.44       | Vertical     |
| 3505.20                                                                                                            | -48.45              | -2.16       | -50.61      | -13.00      | 37.61       | Horizontal   |
| 5257.80                                                                                                            | -49.98              | 3.33        | -46.65      | -13.00      | 33.65       | Horizontal   |
| 7010.40                                                                                                            | -50.75              | 9.57        | -41.18      | -13.00      | 28.18       | Horizontal   |
| <b>Remark:</b><br>1. The emission levels of below 1 GHz are lower than the limit 10dB, so not show in test report. |                     |             |             |             |             |              |

| WCDMA band V                                                                                                       |                     |             |             |             |             |              |
|--------------------------------------------------------------------------------------------------------------------|---------------------|-------------|-------------|-------------|-------------|--------------|
| Lowest channel                                                                                                     |                     |             |             |             |             |              |
| Frequency (MHz)                                                                                                    | Reading Level (dBm) | Factor (dB) | Level (dBm) | Limit (dBm) | Margin (dB) | Polarization |
| 1652.80                                                                                                            | -49.02              | -11.41      | -60.43      | -13.00      | 47.43       | Vertical     |
| 2479.20                                                                                                            | -46.07              | -6.45       | -52.52      | -13.00      | 39.52       | Vertical     |
| 3305.60                                                                                                            | -48.60              | -4.89       | -53.49      | -13.00      | 40.49       | Vertical     |
| 1652.80                                                                                                            | -49.79              | -11.32      | -61.11      | -13.00      | 48.11       | Horizontal   |
| 2479.20                                                                                                            | -41.61              | -6.78       | -48.39      | -13.00      | 35.39       | Horizontal   |
| 3305.60                                                                                                            | -49.88              | -5.17       | -55.05      | -13.00      | 42.05       | Horizontal   |
| Middle channel                                                                                                     |                     |             |             |             |             |              |
| Frequency (MHz)                                                                                                    | Reading Level (dBm) | Factor (dB) | Level (dBm) | Limit (dBm) | Margin (dB) | Polarization |
| 1673.20                                                                                                            | -49                 | -11.47      | -60.47      | -13.00      | 47.47       | Vertical     |
| 2509.80                                                                                                            | -46.26              | -6.40       | -52.66      | -13.00      | 39.66       | Vertical     |
| 3346.40                                                                                                            | -48.43              | -4.96       | -53.39      | -13.00      | 40.39       | Vertical     |
| 1673.20                                                                                                            | -49.67              | -11.39      | -61.06      | -13.00      | 48.06       | Horizontal   |
| 2509.80                                                                                                            | -41.79              | -6.72       | -48.51      | -13.00      | 35.51       | Horizontal   |
| 3346.40                                                                                                            | -50                 | -5.17       | -55.17      | -13.00      | 42.17       | Horizontal   |
| Highest channel                                                                                                    |                     |             |             |             |             |              |
| Frequency (MHz)                                                                                                    | Reading Level (dBm) | Factor (dB) | Level (dBm) | Limit (dBm) | Margin (dB) | Polarization |
| 1697.60                                                                                                            | -48.94              | -11.54      | -60.48      | -13.00      | 47.48       | Vertical     |
| 2546.40                                                                                                            | -46.14              | -6.24       | -52.38      | -13.00      | 39.38       | Vertical     |
| 3395.20                                                                                                            | -48.93              | -5.05       | -53.98      | -13.00      | 40.98       | Vertical     |
| 1697.60                                                                                                            | -49.35              | -11.48      | -60.83      | -13.00      | 47.83       | Horizontal   |
| 2546.40                                                                                                            | -41.34              | -6.56       | -47.90      | -13.00      | 34.90       | Horizontal   |
| 3395.20                                                                                                            | -49.66              | -5.16       | -54.82      | -13.00      | 41.82       | Horizontal   |
| <b>Remark:</b><br>1. The emission levels of below 1 GHz are lower than the limit 10dB, so not show in test report. |                     |             |             |             |             |              |

-----End of report-----