









Report No.: WSCT-ANAB-R&E250900074A-BT Issued Date: 19 December 2025














Report No.: WSCT-ANAB-R&E250900074A-BT Issued Date: 19 December 2025



6.11. Radiated Spurious Emission Measurement

6.11.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.209			
Test Method:	ANSI C63.10:2020			
Frequency Range:	9 kHz to 25 GHz			
Measurement Distance:	3 m			
Antenna Polarization:	Horizontal & Vertical			
Receiver Setup:	Frequency	Detector	RBW	VBW
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz
	30MHz-1GHz	Quasi-peak	100KHz	300KHz
	Above 1GHz	Peak	1MHz	3MHz
Limit:	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Remark
	0.009-0.490	2400/F(KHz)	300	Quasi-peak Value
	0.490-1.705	24000/F(KHz)	30	Quasi-peak Value
	1.705-30	30	30	Quasi-peak Value
	30-88	100	3	Quasi-peak Value
Test setup:	88-216	150	3	Peak Value
	216-960	200	3	Peak Value
	Above 960	500	3	Average Value
	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector
	Above 1GHz	500	3	Average
		5000	3	Peak
	For radiated emissions below 30MHz			
				
	30MHz to 1GHz			

	 Above 1GHz 
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. The testing follows the guidelines in Spurious Radiated Emissions of ANSI C63.10:2020 Measurement Guidelines. 2. For the radiated emission test below 1GHz: The EUT was placed on a turntable with 0.8 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level. For the radiated emission test above 1GHz: Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final

	measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Use the following spectrum analyzer settings: (1) Span shall wide enough to fully capture the emission being measured; (2) Set RBW=100 kHz for $f < 1$ GHz, RBW=1MHz for $f > 1$GHz ; VBW$\geq$RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak (3) For average measurement: use duty cycle correction factor method per 15.35(c). Duty cycle = On time/100 milliseconds On time = $N_1 \cdot L_1 + N_2 \cdot L_2 + \dots + N_{n-1} \cdot L_{n-1} + N_n \cdot L_n$ Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc. Average Emission Level = Peak Emission Level + $20 \cdot \log(\text{Duty cycle})$ Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
Test results:	PASS

Note 1: The symbol of "--" in the table which means not application.

Note 2: For the test data above 1 GHz, According the ANSI C63.10-2020, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note 3: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note 4: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and normal link mode is worst.


Report No.: WSCT-ANAB-R&E250900074A-BT Issued Date: 19 December 2025

6.11.2. Test Data

Please refer to following diagram for individual

Below 1GHz

Horizontal:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		50.3700	34.18	-7.51	26.67	40.00	-13.33	QP
2		173.5600	34.48	-8.09	26.39	43.50	-17.11	QP
3		276.3800	36.88	-7.60	29.28	46.00	-16.72	QP
4		695.4200	27.22	3.00	30.22	46.00	-15.78	QP
5	*	846.7400	27.16	5.83	32.99	46.00	-13.01	QP
6		992.2400	26.25	7.88	34.13	54.00	-19.87	QP

Report No.: WSCT-ANAB-R&E250900074A-BT Issued Date: 19 December 2025
Vertical:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	33.8800	55.10	-20.53	34.57	40.00	-5.43	QP
2		84.3198	52.26	-20.20	32.06	40.00	-7.94	QP
3		170.6500	48.57	-19.83	28.74	43.50	-14.76	QP
4		580.9600	46.27	-17.83	28.44	46.00	-17.56	QP
5		813.7599	48.05	-16.57	31.48	46.00	-14.52	QP
6		959.2599	49.21	-15.55	33.66	46.00	-12.34	QP

Note1:

Freq.= Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss - Amplifier factor.

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard

Margin (dB) = Measurement (dBuV) – Limits (dBuV)

Report No.: WSCT-ANAB-R&E250900074A-BT Issued Date: 19 December 2025

Above 1GHz


Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious above 18G is noise only, do not show on the report.

GFSK

Low channel: 2402MHz


Horizontal:

**Suspected Data List**

NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1101.2500	38.76	24.35	14.41	74	-35.24	337.8	Horizontal	PK	Pass
1	1101.2500	28.63	24.35	4.28	54	-25.37	337.8	Horizontal	AV	Pass
2	2439.3750	46.62	27.39	19.23	74	-27.38	53.5	Horizontal	PK	Pass
2	2439.3750	38.49	27.39	11.1	54	-15.51	53.5	Horizontal	AV	Pass
3	5742.5000	65.14	32.39	32.75	74	-8.86	301	Horizontal	PK	Pass
3	5742.5000	48.95	32.39	16.56	54	-5.05	301	Horizontal	AV	Pass
4	6964.5000	42.87	6.24	36.63	74	-31.13	360	Horizontal	PK	Pass
4	6964.5000	34.57	6.24	28.33	54	-19.43	360	Horizontal	AV	Pass
5	11034.0000	48.66	15.73	32.93	74	-25.34	215.6	Horizontal	PK	Pass
5	11034.0000	40.24	15.73	24.51	54	-13.76	215.6	Horizontal	AV	Pass
6	17910.0000	53.72	23.33	30.39	74	-20.28	228.8	Horizontal	PK	Pass
6	17910.0000	46.62	23.33	23.29	54	-7.38	228.8	Horizontal	AV	Pass

Report No.: WSCT-ANAB-R&E250900074A-BT Issued Date: 19 December 2025

Vertical:




Suspected Data List

NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1265.0000	40.23	24.63	15.6	74	-33.77	219.7	Vertical	PK	Pass
1	1265.0000	30.17	24.63	5.54	54	-23.83	219.7	Vertical	AV	Pass
2	2438.7500	47.15	27.39	19.76	74	-26.85	144.3	Vertical	PK	Pass
2	2438.7500	38.63	27.39	11.24	54	-15.37	144.3	Vertical	AV	Pass
3	5799.3750	62.62	32.48	30.14	74	-11.38	115.7	Vertical	PK	Pass
3	5799.3750	48.13	32.48	15.65	54	-5.87	115.7	Vertical	AV	Pass
4	7123.5000	36.48	6.84	29.64	74	-37.52	253.9	Vertical	PK	Pass
4	7123.5000	28.7	6.84	21.86	54	-25.3	253.9	Vertical	AV	Pass
5	10420.5000	42.76	13.66	29.1	74	-31.24	97.3	Vertical	PK	Pass
5	10420.5000	34.95	13.66	21.29	54	-19.05	97.3	Vertical	AV	Pass
6	17863.5000	52.68	23.03	29.65	74	-21.32	360	Vertical	PK	Pass
6	17863.5000	45.6	23.03	22.57	54	-8.4	360	Vertical	AV	Pass

Report No.: WSCT-ANAB-R&E250900074A-BT Issued Date: 19 December 2025

Middle channel: 2441MHz

Horizontal:




Suspected Data List

NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1147.5000	38.35	24.37	13.98	74	-35.65	359.5	Horizontal	PK	Pass
1	1147.5000	29.06	24.37	4.69	54	-24.94	359.5	Horizontal	AV	Pass
2	2460.0000	47.29	27.46	19.83	74	-26.71	140.7	Horizontal	PK	Pass
2	2460.0000	37.27	27.46	9.81	54	-16.73	140.7	Horizontal	AV	Pass
3	5744.3750	65.75	32.39	33.36	74	-8.25	-0.1	Horizontal	PK	Pass
3	5744.3750	48.19	32.39	15.8	54	-5.81	-0.1	Horizontal	AV	Pass
4	7213.5000	42.48	6.99	35.49	74	-31.52	360.1	Horizontal	PK	Pass
4	7213.5000	34.98	6.99	27.99	54	-19.02	360.1	Horizontal	AV	Pass
5	10665.0000	46.51	14.54	31.97	74	-27.49	69.8	Horizontal	PK	Pass
5	10665.0000	38.86	14.54	24.32	54	-15.14	69.8	Horizontal	AV	Pass
6	17910.0000	55.05	23.33	31.72	74	-18.95	145.2	Horizontal	PK	Pass
6	17910.0000	46.65	23.33	23.32	54	-7.35	145.2	Horizontal	AV	Pass

Report No.: WSCT-ANAB-R&E250900074A-BT Issued Date: 19 December 2025

Vertical:




Suspected Data List

NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1543.7500	40.99	24.96	16.03	74	-33.01	0	Vertical	PK	Pass
1	1543.7500	30.87	24.96	5.91	54	-23.13	0	Vertical	AV	Pass
2	2438.7500	53.62	27.39	26.23	74	-20.38	171.8	Vertical	PK	Pass
2	2438.7500	38.23	27.39	10.84	54	-15.77	171.8	Vertical	AV	Pass
3	5746.2500	71.41	32.39	39.02	74	-2.59	71.4	Vertical	PK	Pass
3	5746.2500	48.66	32.39	16.27	54	-5.34	71.4	Vertical	AV	Pass
4	6759.0000	41.28	5.44	35.84	74	-32.72	357	Vertical	PK	Pass
4	6759.0000	33.91	5.44	28.47	54	-20.09	357	Vertical	AV	Pass
5	10954.5000	47.25	15.37	31.88	74	-26.75	273	Vertical	PK	Pass
5	10954.5000	39.81	15.37	24.44	54	-14.19	273	Vertical	AV	Pass
6	17931.0000	53.68	23.46	30.22	74	-20.32	140.3	Vertical	PK	Pass
6	17931.0000	46.69	23.46	23.23	54	-7.31	140.3	Vertical	AV	Pass

Report No.: WSCT-ANAB-R&E250900074A-BT Issued Date: 19 December 2025

High channel: 2480MHz

Horizontal:




Suspected Data List

NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1128.1250	38.29	24.36	13.93	74	-35.71	174.2	Horizontal	PK	Pass
1	1128.1250	29.3	24.36	4.94	54	-24.7	174.2	Horizontal	AV	Pass
2	2440.6250	46.66	27.4	19.26	74	-27.34	75	Horizontal	PK	Pass
2	2440.6250	37.74	27.4	10.34	54	-16.26	75	Horizontal	AV	Pass
3	5725.0000	58.49	32.36	26.13	74	-15.51	2.9	Horizontal	PK	Pass
3	5725.0000	48.8	32.36	16.44	54	-5.2	2.9	Horizontal	AV	Pass
4	6375.0000	40.67	4.52	36.15	74	-33.33	57.8	Horizontal	PK	Pass
4	6375.0000	33.84	4.52	29.32	54	-20.16	57.8	Horizontal	AV	Pass
5	10534.5000	46.29	14.07	32.22	74	-27.71	48.3	Horizontal	PK	Pass
5	10534.5000	38.8	14.07	24.73	54	-15.2	48.3	Horizontal	AV	Pass
6	17875.5000	54.06	23.11	30.95	74	-19.94	16.4	Horizontal	PK	Pass
6	17875.5000	46.32	23.11	23.21	54	-7.68	16.4	Horizontal	AV	Pass

Report No.: WSCT-ANAB-R&E250900074A-BT Issued Date: 19 December 2025

Vertical:



Suspected Data List

NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1173.7500	38.23	24.39	13.84	74	-35.77	243.5	Vertical	PK	Pass
1	1173.7500	29	24.39	4.61	54	-25	243.5	Vertical	AV	Pass
2	2438.7500	47.11	27.39	19.72	74	-26.89	79.8	Vertical	PK	Pass
2	2438.7500	38.46	27.39	11.07	54	-15.54	79.8	Vertical	AV	Pass
3	5740.6250	60.2	32.38	27.82	74	-13.8	24.8	Vertical	PK	Pass
3	5740.6250	48.23	32.38	15.85	54	-5.77	24.8	Vertical	AV	Pass
4	7203.0000	42.68	7	35.68	74	-31.32	230.1	Vertical	PK	Pass
4	7203.0000	35.03	7	28.03	54	-18.97	230.1	Vertical	AV	Pass
5	10953.0000	47.8	15.35	32.45	74	-26.2	344.8	Vertical	PK	Pass
5	10953.0000	39.72	15.35	24.37	54	-14.28	344.8	Vertical	AV	Pass
6	17902.5000	54.79	23.28	31.51	74	-19.21	256.4	Vertical	PK	Pass
6	17902.5000	46.68	23.28	23.4	54	-7.32	256.4	Vertical	AV	Pass

Note:

- The emission levels of other frequencies are very lower than the limit and not show in test report.
- Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.
- Data of measurement shown "----" in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
- Measurements were conducted in all three modulation (GFSK, Pi/4 DQPSK, 8DPSK), and the worst case Mode (GFSK) was submitted only.
- EUT has been tested in unfolded states, and the report only reflects data in the unfolded state (worst-case scenario)

Note: Freq. = Emission frequency in MHz

Reading level (dBμV) = Receiver reading

Corr. Factor (dB) = Attenuation factor + Cable loss

Level (dBμV) = Reading level (dBμV) + Corr. Factor (dB)

Limit (dBμV) = Limit stated in standard

Margin (dB) = Level (dBμV) – Limits (dBμV)

6.11.3. Restricted Bands Requirements

Bluetooth (GFSK, Pi/4-DQPSK, 8DPSK) mode have been tested, and the worst result GFSK model was report as below

Frequency	Reading	Correct Factor	Emission Level	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel							
2387	66.46	-5.24	61.22	74	12.78	H	PK
2387	54.39	-5.24	49.15	54	4.85	H	AV
2387	67.10	-4.87	62.23	74	11.77	V	PK
2387	54.29	-4.87	49.42	54	4.58	V	AV
2390	65.94	-5.24	60.70	74	13.30	H	PK
2390	53.08	-5.24	47.84	54	6.16	H	AV
2390	68.36	-4.87	63.49	74	10.51	V	PK
2390	54.80	-4.87	49.93	54	4.07	V	AV
High Channel							
2483.5	65.93	-5.24	60.69	74	13.31	H	PK
2483.5	54.37	-5.24	49.13	54	4.87	H	AV
2483.5	67.68	-4.87	62.81	74	11.19	V	PK
2483.5	53.24	-4.87	48.37	54	5.63	V	AV

Note: Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = Attenuation factor + Cable loss

Level (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard

Margin (dB) = Level (dBuV) – Limits (dBuV)

Report No.: WSCT-ANAB-R&E250900074A-BT Issued Date: 19 December 2025

7. Test Setup Photographs

Please refer to Annex "Set Up Photos-15C" for test setup photos

*******END OF REPORT*******