

# TEST REPORT

**FCC ID: 2AIZN-XE37R****Product: True Wireless Earbuds****Model No.: XE37****Trade Mark: Infinix****Report No.: WSCT-ANAB-R&E250100006A-15B****Issued Date: 21 February 2025****Issued for:****INFINIX MOBILITY LIMITED****FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI  
STREET FOTAN NT HONGKONG****Issued By:****World Standardization Certification & Testing Group(Shenzhen) Co., Ltd.  
Building A-B, Baoli'an Industrial Park, No.58 and 60, Tangtuo Avenue, Shiyan  
Street, Bao'an District, Shenzhen City, Guangdong Province, China.****TEL: +86-755-26996192****FAX: +86-755-86376605**

**Note:** This report shall not be reproduced except in full, without the written approval of World Standardization Certification & Testing Group (Shenzhen) Co., Ltd. This document may be altered or revised by World Standardization Certification & Testing Group (Shenzhen) Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.



## TABLE OF CONTENTS

|                                                          |           |
|----------------------------------------------------------|-----------|
| <b>1. Test Certification .....</b>                       | <b>3</b>  |
| <b>2. GENERAL DESCRIPTION OF EUT .....</b>               | <b>4</b>  |
| <b>3. Test Result Summary .....</b>                      | <b>5</b>  |
| <b>4. TEST METHODOLOGY .....</b>                         | <b>6</b>  |
| 4.1. CONFIGURATION OF SYSTEM UNDER TEST .....            | 7         |
| 4.2. DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE) ..... | 8         |
| <b>5. MEASUREMENT INSTRUMENTS .....</b>                  | <b>9</b>  |
| <b>6. Facilities and Accreditations .....</b>            | <b>10</b> |
| 6.1. FACILITIES .....                                    | 10        |
| 6.2. ACCREDITATIONS .....                                | 10        |
| 6.3. MEASUREMENT UNCERTAINTY .....                       | 10        |
| <b>7. EMC EMISSION TEST .....</b>                        | <b>12</b> |
| 7.1. CONDUCTED EMISSION MEASUREMENT .....                | 12        |
| 7.2. TEST RESULTS .....                                  | 14        |
| 7.3. RADIATED EMISSION MEASUREMENT .....                 | 16        |
| <b>8. Test Setup Photographs .....</b>                   | <b>23</b> |

Report No.: WSCT-ANAB-R&amp;E250100006A-15B

# 1. Test Certification

**Product:** True Wireless Earbuds  
**Model No.:** XE37  
**Trade Mark:** Infinix  
**Applicant:** **INFINIX MOBILITY LIMITED**  
FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25  
SHAN MEI STREET FOTAN NT HONGKONG  
**Manufacturer:** **INFINIX MOBILITY LIMITED**  
FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25  
SHAN MEI STREET FOTAN NT HONGKONG  
**Date of receipt:** 17 January 2025  
**Date of Test:** 18 January 2025 ~ 19 February 2025  
**Applicable Standards:** FCC CFR Title 47 Part 15 Subpart B


The above equipment has been tested by World Standardization Certification & Testing Group(Shenzhen) Co., Ltd. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By:



(Jiang Guanliang)

Checked By:



(Qin Shuiquan)

Approved By:



(Li Huaibi)

Date:



Report No.: WSCT-ANAB-R&amp;E250100006A-15B

## 2. GENERAL DESCRIPTION OF EUT

|                   |                                                                                           |
|-------------------|-------------------------------------------------------------------------------------------|
| Product Name:     | True Wireless Earbuds                                                                     |
| Model :           | XE37                                                                                      |
| Trade Mark:       | Infinix                                                                                   |
| Operating Voltage | Li-ion Polymer Battery: 1054<br>Nominal Voltage: 3.85V<br>Rated Capacity: 45mAh/0.17325Wh |
| Test Voltage      | 120Vac,60Hz                                                                               |
| Remark:           | N/A.                                                                                      |

Note: 1. N/A stands for no applicable.

2. Antenna gain provided by the applicant

Report No.: WSCT-ANAB-R&amp;E250100006A-15B

### 3. Test Result Summary

| Requirement        | CFR 47 Section | Result |
|--------------------|----------------|--------|
| CONDUCTED EMISSION | §15.107        | PASS   |
| RADIATED EMISSION  | §15.109        | PASS   |

**Note:**

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

Report No.: WSCT-ANAB-R&amp;E250100006A-15B

## 4. TEST METHODOLOGY

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.


| Pretest Mode | Description          |
|--------------|----------------------|
| Mode 1       | Charging             |
| Mode 2       | Bluetooth            |
| Mode 3       | Bluetooth + charging |

Note: Bluetooth earphones cannot be turned on while charging in the charging compartment.

Report No.: WSCT-ANAB-R&amp;E250100006A-15B

## 4.1. CONFIGURATION OF SYSTEM UNDER TEST

Mode 1&amp; Mode 3



&amp; Mode 2



(EUT: True Wireless Earbuds )

| I/O Port of EUT |      |                            |             |
|-----------------|------|----------------------------|-------------|
| I/O Port Type   | Q'TY | Cable                      | Tested with |
| Power           | 1    | 0.5m USB cable, unshielded | /           |
| Earphone        | /    | /                          | /           |

Report No.: WSCT-ANAB-R&amp;E250100006A-15B

## 4.2. DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Item | Equipment | Mfr/Brand | Model/Type No. | Series No. | Note |
|------|-----------|-----------|----------------|------------|------|
| 1    | Adapter   | /         | /              | /          | /    |
| 2    | Keyboard  | /         | /              | /          | /    |
| 3    | Mouse     | /         | /              | /          | /    |

**Note:**

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

Report No.: WSCT-ANAB-R&amp;E250100006A-15B

## 5. MEASUREMENT INSTRUMENTS

| Kind of Equipment  | Manufacturer | Type No.    | Serial No.  | Last Calibrated | Calibrated until |
|--------------------|--------------|-------------|-------------|-----------------|------------------|
| Test software      | -            | EZ-EMC      | CON-03A     | -               | -                |
| ESCI Test Receiver | R&S          | ESCI        | 100005      | 11/05/2024      | 11/04/2025       |
| LISN               | AFJ          | LS16        | 16010222119 | 11/05/2024      | 11/04/2025       |
| LISN(EUT)          | Mestec       | AN3016      | 04/10040    | 11/05/2024      | 11/04/2025       |
| pre-amplifier      | CDSI         | PAP-1G18-38 | -           | 11/05/2024      | 11/04/2025       |
| System Controller  | CT           | SC100       | -           | 11/05/2024      | 11/04/2025       |
| Bi-log Antenna     | Chase        | CBL6111C    | 2576        | 11/05/2024      | 11/04/2025       |
| Spectrum analyzer  | R&S          | FSU26       | 200409      | 11/05/2024      | 11/04/2025       |
| Horn Antenna       | SCHWARZBECK  | 9120D       | 1141        | 11/05/2024      | 11/04/2025       |
| Bi-log Antenna     | SCHWARZBECK  | VULB9168    | 01488       | 07/29/2024      | 07/28/2025       |
| Pre Amplifier      | H.P.         | HP8447E     | 2945A02715  | 11/05/2024      | 11/04/2025       |
| 9*6*6 Anechoic     | -            | -           | -           | 11/05/2024      | 11/04/2025       |

Report No.: WSCT-ANAB-R&amp;E250100006A-15B

## 6. Facilities and Accreditations

### 6.1. Facilities

All measurement facilities used to collect the measurement data are located at

**World Standardization Certification & Testing Group (Shenzhen) Co., Ltd.**

**Building A-B, Baoli'an Industrial Park, No.58 and 60, Tangtuo Avenue, Shiyan Street, Bao'an District, Shenzhen City, Guangdong Province, China.**

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

### 6.2. ACCREDITATIONS

#### ANAB - Certificate Number: AT-3951

The EMC Laboratory has been accredited by the American Association for Laboratory Accreditation (ANAB). Certification Number: AT-3951

### 6.3. Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

| No. | Item                    | MU                 |
|-----|-------------------------|--------------------|
| 1   | Conducted Emission Test | $\pm 3.2\text{dB}$ |

Report No.: WSCT-ANAB-R&E250100006A-15B

|   |                                |                           |
|---|--------------------------------|---------------------------|
| 2 | RF power, conducted            | $\pm 0.16\text{dB}$       |
| 3 | Spurious emissions, conducted  | $\pm 0.21\text{dB}$       |
| 4 | All emissions, radiated(<1GHz) | $\pm 4.7\text{dB}$        |
| 5 | All emissions, radiated(>1GHz) | $\pm 4.7\text{dB}$        |
| 6 | Temperature                    | $\pm 0.5^{\circ}\text{C}$ |
| 7 | Humidity                       | $\pm 2.0\%$               |

## 7. EMC EMISSION TEST

### 7.1. CONDUCTED EMISSION MEASUREMENT

#### 7.1.1. POWER LINE CONDUCTED EMISSION LIMITS

| FREQUENCY (MHz) | Class A (dBUV) |         | Class B (dBUV) |           | Standard |
|-----------------|----------------|---------|----------------|-----------|----------|
|                 | Quasi-peak     | Average | Quasi-peak     | Average   |          |
| 0.15 -0.5       | 79.00          | 66.00   | 66 - 56 *      | 56 - 46 * | FCC      |
| 0.50 -5.0       | 73.00          | 60.00   | 56.00          | 46.00     | FCC      |
| 5.0 -30.0       | 73.00          | 60.00   | 60.00          | 50.00     | FCC      |

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver


| Receiver Parameters | Setting  |
|---------------------|----------|
| Attenuation         | 10 dB    |
| Start Frequency     | 0.15 MHz |
| Stop Frequency      | 30 MHz   |
| IF Bandwidth        | 9 kHz    |

Report No.: WSCT-ANAB-R&E250100006A-15B

## TEST PROCEDURE

- The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.


## TEST SETUP



## 7.2. Test Results

|             |          |                   |        |
|-------------|----------|-------------------|--------|
| Temperature | 20 °C    | Relative Humidity | 48%    |
| Pressure    | 1010 hPa | Test Mode         | Mode 3 |


### Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|
| 1   | 0.1905          | 14.07          | 20.70       | 34.77        | 64.01        | -29.24      | QP       |
| 2   | 0.1905          | -6.76          | 20.70       | 13.94        | 54.01        | -40.07      | AVG      |
| 3 * | 0.6809          | 16.50          | 20.54       | 37.04        | 56.00        | -18.96      | QP       |
| 4   | 0.6809          | 1.40           | 20.54       | 21.94        | 46.00        | -24.06      | AVG      |
| 5   | 1.9050          | 8.68           | 20.62       | 29.30        | 56.00        | -26.70      | QP       |
| 6   | 1.9050          | -6.76          | 20.62       | 13.86        | 46.00        | -32.14      | AVG      |
| 7   | 3.4755          | 11.52          | 20.59       | 32.11        | 56.00        | -23.89      | QP       |
| 8   | 3.4755          | -4.58          | 20.59       | 16.01        | 46.00        | -29.99      | AVG      |
| 9   | 5.5275          | 12.48          | 20.55       | 33.03        | 60.00        | -26.97      | QP       |
| 10  | 5.5275          | -3.08          | 20.55       | 17.47        | 50.00        | -32.53      | AVG      |
| 11  | 7.1295          | 12.90          | 20.51       | 33.41        | 60.00        | -26.59      | QP       |
| 12  | 7.1295          | -3.82          | 20.51       | 16.69        | 50.00        | -33.31      | AVG      |

Report No.: WSCT-ANAB-R&E250100006A-15B

## Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|
| 1   | 0.1680          | 12.74          | 20.72       | 33.46        | 65.06        | -31.60      | QP       |
| 2   | 0.1680          | -6.94          | 20.72       | 13.78        | 55.06        | -41.28      | AVG      |
| 3   | 0.5370          | 12.17          | 20.52       | 32.69        | 56.00        | -23.31      | QP       |
| 4   | 0.5370          | -8.11          | 20.52       | 12.41        | 46.00        | -33.59      | AVG      |
| 5 * | 0.6855          | 17.47          | 20.54       | 38.01        | 56.00        | -17.99      | QP       |
| 6   | 0.6855          | -2.49          | 20.54       | 18.05        | 46.00        | -27.95      | AVG      |
| 7   | 0.9645          | 8.86           | 20.65       | 29.51        | 56.00        | -26.49      | QP       |
| 8   | 0.9645          | -8.65          | 20.65       | 12.00        | 46.00        | -34.00      | AVG      |
| 9   | 2.0355          | 8.18           | 20.61       | 28.79        | 56.00        | -27.21      | QP       |
| 10  | 2.0355          | -6.23          | 20.61       | 14.38        | 46.00        | -31.62      | AVG      |
| 11  | 8.8260          | 8.51           | 20.47       | 28.98        | 60.00        | -31.02      | QP       |
| 12  | 8.8260          | -8.39          | 20.47       | 12.08        | 50.00        | -37.92      | AVG      |

### Note1:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = LISN Factor + Cable loss

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard

Margin (dB) = Measurement (dBuV) - Limits (dBuV)

Q.P. = Quasi-Peak AVG = average

\* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

## 7.3. RADIATED EMISSION MEASUREMENT

### 7.3.1. Radiated Emission Limits

The field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

| Frequencies (MHz) | Field Strength (micromvolts/meter) | Measurement Distance (meters) |
|-------------------|------------------------------------|-------------------------------|
| 0.009~0.490       | 2400/F(KHz)                        | 300                           |
| 0.490~1.705       | 24000/F(KHz)                       | 30                            |
| 1.705~30.0        | 30                                 | 30                            |
| 30~88             | 100                                | 3                             |
| 88~216            | 150                                | 3                             |
| 216~960           | 200                                | 3                             |
| Above 960         | 500                                | 3                             |

### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

| FREQUENCY (MHz) | Limit (dBuV/m) (at 3M) |         |
|-----------------|------------------------|---------|
|                 | PEAK                   | AVERAGE |
| Above 1000      | 74                     | 54      |

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15B.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

| Spectrum Parameter                    | Setting                                         |
|---------------------------------------|-------------------------------------------------|
| Attenuation                           | Auto                                            |
| Start Frequency                       | 1000 MHz                                        |
| Stop Frequency                        | 10th carrier harmonic                           |
| RB / VB (emission in restricted band) | 1 MHz / 1 MHz for Peak, 1 MHz / 1Hz for Average |

| Receiver Parameter     | Setting                          |
|------------------------|----------------------------------|
| Attenuation            | Auto                             |
| Start ~ Stop Frequency | 9kHz~150kHz / RB 200Hz for QP    |
| Start ~ Stop Frequency | 150kHz~30MHz / RB 9kHz for QP    |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB 120kHz for QP |

Report No.: WSCT-ANAB-R&amp;E250100006A-15B


**TEST PROCEDURE**

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.


Report No.: WSCT-ANAB-R&E250100006A-15B

## TEST SETUP

(A) Radiated Emission Test-Up Frequency 30MHz~1GHz



(B) Radiated Emission Test-Up Frequency Above 1GHz



Report No.: WSCT-ANAB-R&E250100006A-15B


### 7.3.2. Test Results

|             |          |                   |        |
|-------------|----------|-------------------|--------|
| Temperature | 20 °C    | Relative Humidity | 48%    |
| Pressure    | 1010 hPa | Test Mode         | Mode 2 |

Please refer to following diagram for individual

Below 1GHz


Horizontal:



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 38.2455         | 31.03          | -19.27        | 11.76          | 40.00          | -28.24      | QP       |
| 2   | 72.0528         | 30.98          | -22.60        | 8.38           | 40.00          | -31.62      | QP       |
| 3   | 140.8351        | 29.42          | -19.95        | 9.47           | 43.50          | -34.03      | QP       |
| 4   | 303.9431        | 29.59          | -20.08        | 9.51           | 46.00          | -36.49      | QP       |
| 5   | 559.9560        | 29.47          | -14.79        | 14.68          | 46.00          | -31.32      | QP       |
| 6 * | 824.9583        | 39.19          | -10.66        | 28.53          | 46.00          | -17.47      | QP       |

Report No.: WSCT-ANAB-R&E250100006A-15B

Vertical:



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1 * | 36.2064         | 36.04          | -19.44        | 16.60          | 40.00          | -23.40      | QP       |
| 2   | 64.5461         | 30.57          | -21.19        | 9.38           | 40.00          | -30.62      | QP       |
| 3   | 129.6950        | 29.23          | -20.60        | 8.63           | 43.50          | -34.87      | QP       |
| 4   | 263.7034        | 28.84          | -21.53        | 7.31           | 46.00          | -38.69      | QP       |
| 5   | 557.5070        | 29.39          | -14.80        | 14.59          | 46.00          | -31.41      | QP       |
| 6   | 809.2006        | 29.86          | -10.70        | 19.16          | 46.00          | -26.84      | QP       |

Note1:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss - Amplifier factor.

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard


Margin (dB) = Measurement (dBuV) – Limits (dBuV)

Report No.: WSCT-ANAB-R&E250100006A-15B

## TEST RESULTS

Above 1GHz(1~26GHz) :( Mode 2—worst case)


Horizontal:



| No.  | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|------|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1    | 1400.000        | 36.20          | -7.42         | 28.78          | 74.00          | -45.22      | peak     |
| 2    | 1400.000        | 27.24          | -7.42         | 19.82          | 54.00          | -34.18      | AVG      |
| 3    | 2444.375        | 44.75          | -3.88         | 40.87          | 74.00          | -33.13      | peak     |
| 4    | 2444.375        | 39.32          | -3.88         | 35.44          | 54.00          | -18.56      | AVG      |
| 5    | 3338.750        | 34.15          | -1.51         | 32.64          | 74.00          | -41.36      | peak     |
| 6    | 3338.750        | 24.70          | -1.51         | 23.19          | 54.00          | -30.81      | AVG      |
| 7    | 4250.625        | 32.94          | 1.98          | 34.92          | 74.00          | -39.08      | peak     |
| 8    | 4250.625        | 23.62          | 1.98          | 25.60          | 54.00          | -28.40      | AVG      |
| 9    | 5184.375        | 38.20          | 5.85          | 44.05          | 74.00          | -29.95      | peak     |
| 10   | 5184.375        | 30.84          | 5.85          | 36.69          | 54.00          | -17.31      | AVG      |
| 11   | 5826.250        | 37.97          | 8.64          | 46.61          | 74.00          | -27.39      | peak     |
| 12 * | 5826.250        | 31.16          | 8.64          | 39.80          | 54.00          | -14.20      | AVG      |

Report No.: WSCT-ANAB-R&E250100006A-15B

Vertical:



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 1621.250        | 36.79          | -7.37         | 29.42          | 74.00          | -44.58      | peak     |
| 2   | 1621.250        | 27.58          | -7.37         | 20.21          | 54.00          | -33.79      | AVG      |
| 3   | 2426.875        | 43.09          | -3.96         | 39.13          | 74.00          | -34.87      | peak     |
| 4 * | 2426.875        | 39.23          | -3.96         | 35.27          | 54.00          | -18.73      | AVG      |
| 5   | 3358.125        | 34.66          | -1.46         | 33.20          | 74.00          | -40.80      | peak     |
| 6   | 3358.125        | 25.16          | -1.46         | 23.70          | 54.00          | -30.30      | AVG      |
| 7   | 4229.375        | 32.91          | 1.89          | 34.80          | 74.00          | -39.20      | peak     |
| 8   | 4229.375        | 23.61          | 1.89          | 25.50          | 54.00          | -28.50      | AVG      |
| 9   | 5186.250        | 37.11          | 5.86          | 42.97          | 74.00          | -31.03      | peak     |
| 10  | 5186.250        | 28.91          | 5.86          | 34.77          | 54.00          | -19.23      | AVG      |
| 11  | 5844.375        | 32.76          | 8.76          | 41.52          | 74.00          | -32.48      | peak     |
| 12  | 5844.375        | 22.92          | 8.76          | 31.68          | 54.00          | -22.32      | AVG      |

Remark:

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Freq. = Emission frequency in MHz

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

Over = Emission Level - Limit.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.

Report No.: WSCT-ANAB-R&amp;E250100006A-15B

## 8. Test Setup Photographs

Please refer to the attachment "Set Up Photos-15B" for relevant test setup photos

**\*\*\*\*\*END OF REPORT\*\*\*\*\***