







Report No.: WSCT-ANAB-R&E260500043A-LE Issued Date: 02 June 2026



Report No.: WSCT-ANAB-R&E260500043A-LE Issued Date: 02 June 2026





Report No.: WSCT-ANAB-R&E260500043A-LE Issued Date: 02 June 2026





Report No.: WSCT-ANAB-R&E260500043A-LE Issued Date: 02 June 2026
Conducted RF Spurious Emission





Report No.: WSCT-ANAB-R&E260500043A-LE Issued Date: 02 June 2026





Report No.: WSCT-ANAB-R&E260500043A-LE Issued Date: 02 June 2026




Report No.: WSCT-ANAB-R&E260500043A-LE Issued Date: 02 June 2026







6.7. Radiated Spurious Emission Measurement

6.7.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.209			
Test Method:	ANSI C63.10:2020			
Frequency Range:	9 kHz to 25 GHz			
Measurement Distance:	3 m			
Antenna Polarization:	Horizontal & Vertical			
Operation mode:	Refer to item 4.1			
Receiver Setup:	Frequency	Detector	RBW	VBW
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz
	30MHz-1GHz	Quasi-peak	100KHz	300KHz
	Above 1GHz	Peak	1MHz	3MHz
Limit:				Remark
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz
	30MHz-1GHz	Quasi-peak	100KHz	300KHz
	Above 1GHz	Peak	1MHz	3MHz
Test setup:	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	
	0.009-0.490	2400/F(KHz)	300	
	0.490-1.705	24000/F(KHz)	30	
	1.705-30	30	30	
	30-88	100	3	
Test setup:	88-216	150	3	
	216-960	200	3	
	Above 960	500	3	
	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector
	Above 1GHz	500	3	Average
		5000	3	Peak
For radiated emissions below 30MHz				
				
30MHz to 1GHz				



Above 1GHz



Test Procedure:

- For the radiated emission test below 1GHz:
The EUT was placed on a turntable with 0.1 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level.
For the radiated emission test above 1GHz:
Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- Corrected Reading: Antenna Factor + Cable Loss +

	Read Level - Preamplifier Factor = Level 3. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported. 4. Use the following spectrum analyzer settings: (1) Span shall wide enough to fully capture the emission being measured; (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold; (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement. For average measurement: VBW = 10 Hz, when duty cycle is no less than 98 percent. VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
Test mode:	Refer to section 4.1 for details
Test results:	PASS

Note 1: The symbol of "--" in the table which means not application.

Note 2: For the test data above 1 GHz, According the ANSI C63.10-2020, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note 3: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.


Note 4: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and normal link mode is worst.

Report No.: WSCT-ANAB-R&E260500043A-LE Issued Date: 02 June 2026

6.7.2. Test Data

Please refer to following diagram for individual
Below 1GHz


Horizontal:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		53.2800	29.47	-7.45	22.02	40.00	-17.98	QP
2		143.4900	25.59	-7.07	18.52	43.50	-24.98	QP
3		413.1500	26.43	-3.13	23.30	46.00	-22.70	QP
4		521.7900	26.49	-0.47	26.02	46.00	-19.98	QP
5		787.5700	25.93	4.57	30.50	46.00	-15.50	QP
6	*	897.1800	25.03	6.61	31.64	46.00	-14.36	QP

Report No.: WSCT-ANAB-R&E260500043A-LE Issued Date: 02 June 2026

Vertical:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		38.7300	46.21	-20.52	25.69	40.00	-14.31	QP
2		97.9000	47.33	-20.21	27.12	43.50	-16.38	QP
3		389.8700	42.49	-18.82	23.67	46.00	-22.33	QP
4		535.3700	44.01	-18.07	25.94	46.00	-20.06	QP
5		726.4600	45.72	-17.05	28.67	46.00	-17.33	QP
6	*	947.6200	47.49	-15.63	31.86	46.00	-14.14	QP

Note1:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss - Amplifier factor.

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard

Margin (dB) = Measurement (dBuV) – Limits (dBuV)

Report No.: WSCT-ANAB-R&E260500043A-LE Issued Date: 02 June 2026

Above 1GHz


Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious above 18G is noise only, do not show on the report.

Note 3 BLE 1M and 2M both tested the report and only recorded the worst-case scenario 1M:

Low channel: 2402MHz


Horizontal:

**Susputed Data List**

NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1203.7500	38.98	24.41	14.57	74	-35.02	4.2	Horizontal	PK	Pass
1	1203.7500	29.71	24.41	5.3	54	-24.29	4.2	Horizontal	AV	Pass
2	2450.0000	48.62	27.43	21.19	74	-25.38	339.9	Horizontal	PK	Pass
2	2450.0000	38.77	27.43	11.34	54	-15.23	339.9	Horizontal	AV	Pass
3	5220.0000	59.12	31.78	27.34	74	-14.88	162.3	Horizontal	PK	Pass
3	5220.0000	46.45	31.78	14.67	54	-7.55	162.3	Horizontal	AV	Pass
4	8328.0000	39	8.98	30.02	74	-35	51.9	Horizontal	PK	Pass
4	8328.0000	31.09	8.98	22.11	54	-22.91	51.9	Horizontal	AV	Pass
5	10446.0000	42.73	13.73	29	74	-31.27	1.4	Horizontal	PK	Pass
5	10446.0000	35.51	13.73	21.78	54	-18.49	1.4	Horizontal	AV	Pass
6	14091.0000	49.52	19.03	30.49	74	-24.48	0.5	Horizontal	PK	Pass
6	14091.0000	41.86	19.03	22.83	54	-12.14	0.5	Horizontal	AV	Pass

Report No.: WSCT-ANAB-R&E260500043A-LE Issued Date: 02 June 2026

Vertical:




Suspected Data List

NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1311.8750	38.97	24.79	14.18	74	-35.03	359.5	Vertical	PK	Pass
1	1311.8750	30.78	24.79	5.99	54	-23.22	359.5	Vertical	AV	Pass
2	2480.6250	47.32	27.53	19.79	74	-26.68	358.7	Vertical	PK	Pass
2	2480.6250	38.4	27.53	10.87	54	-15.6	358.7	Vertical	AV	Pass
3	5226.8750	61.24	31.78	29.46	74	-12.76	83.4	Vertical	PK	Pass
3	5226.8750	46.62	31.78	14.84	54	-7.38	83.4	Vertical	AV	Pass
4	7810.5000	37.78	7.99	29.79	74	-36.22	65	Vertical	PK	Pass
4	7810.5000	30.03	7.99	22.04	54	-23.97	65	Vertical	AV	Pass
5	9735.0000	41.13	11.72	29.41	74	-32.87	230	Vertical	PK	Pass
5	9735.0000	34.14	11.72	22.42	54	-19.86	230	Vertical	AV	Pass
6	15151.5000	50.61	19.52	31.09	74	-23.39	182.2	Vertical	PK	Pass
6	15151.5000	42.32	19.52	22.8	54	-11.68	182.2	Vertical	AV	Pass

Report No.: WSCT-ANAB-R&E260500043A-LE Issued Date: 02 June 2026

Middle channel: 2440MHz

Horizontal:




Suspected Data List

NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1756.2500	40.49	24.98	15.51	74	-33.51	344.4	Horizontal	PK	Pass
1	1756.2500	31.95	24.98	6.97	54	-22.05	344.4	Horizontal	AV	Pass
2	2400.6250	46.47	27.26	19.21	74	-27.53	-0.1	Horizontal	PK	Pass
2	2400.6250	38.5	27.26	11.24	54	-15.5	-0.1	Horizontal	AV	Pass
3	5178.7500	64.76	31.74	33.02	74	-9.24	88.2	Horizontal	PK	Pass
3	5178.7500	46.12	31.74	14.38	54	-7.88	88.2	Horizontal	AV	Pass
4	8122.5000	38.09	8.55	29.54	74	-35.91	181	Horizontal	PK	Pass
4	8122.5000	31.08	8.55	22.53	54	-22.92	181	Horizontal	AV	Pass
5	9832.5000	42.47	11.98	30.49	74	-31.53	111.7	Horizontal	PK	Pass
5	9832.5000	34.26	11.98	22.28	54	-19.74	111.7	Horizontal	AV	Pass
6	13488.0000	45.77	17.64	28.13	74	-28.23	97.4	Horizontal	PK	Pass
6	13488.0000	38.94	17.64	21.3	54	-15.06	97.4	Horizontal	AV	Pass

Report No.: WSCT-ANAB-R&E260500043A-LE Issued Date: 02 June 2026

Vertical:




Suspected Data List

NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1334.3750	39.53	24.87	14.66	74	-34.47	359.5	Vertical	PK	Pass
1	1334.3750	30.15	24.87	5.28	54	-23.85	359.5	Vertical	AV	Pass
2	2453.7500	50.02	27.44	22.58	74	-23.98	358.8	Vertical	PK	Pass
2	2453.7500	38.18	27.44	10.74	54	-15.82	358.8	Vertical	AV	Pass
3	5185.6250	64.1	31.75	32.35	74	-9.9	283	Vertical	PK	Pass
3	5185.6250	46.25	31.75	14.5	54	-7.75	283	Vertical	AV	Pass
4	8415.0000	38.95	9.11	29.84	74	-35.05	325.5	Vertical	PK	Pass
4	8415.0000	31.52	9.11	22.41	54	-22.48	325.5	Vertical	AV	Pass
5	10269.0000	42.59	13.2	29.39	74	-31.41	240.6	Vertical	PK	Pass
5	10269.0000	35.25	13.2	22.05	54	-18.75	240.6	Vertical	AV	Pass
6	14173.5000	49.38	18.95	30.43	74	-24.62	359.9	Vertical	PK	Pass
6	14173.5000	41.89	18.95	22.94	54	-12.11	359.9	Vertical	AV	Pass

Report No.: WSCT-ANAB-R&E260500043A-LE Issued Date: 02 June 2026

High channel: 2480MHz

Horizontal:




Suspected Data List

NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1266.8750	38.97	24.63	14.34	74	-35.03	133.5	Horizontal	PK	Pass
1	1266.8750	29.84	24.63	5.21	54	-24.16	133.5	Horizontal	AV	Pass
2	2516.2500	48.63	27.62	21.01	74	-25.37	-0.1	Horizontal	PK	Pass
2	2516.2500	37.48	27.62	9.86	54	-16.52	-0.1	Horizontal	AV	Pass
3	5184.3750	66.83	31.75	35.08	74	-7.17	55.8	Horizontal	PK	Pass
3	5184.3750	46.32	31.75	14.57	54	-7.68	55.8	Horizontal	AV	Pass
4	7059.0000	36.05	6.55	29.5	74	-37.95	73.4	Horizontal	PK	Pass
4	7059.0000	29.19	6.55	22.64	54	-24.81	73.4	Horizontal	AV	Pass
5	10227.0000	43.08	13.06	30.02	74	-30.92	95	Horizontal	PK	Pass
5	10227.0000	34.94	13.06	21.88	54	-19.06	95	Horizontal	AV	Pass
6	14127.0000	49.22	18.99	30.23	74	-24.78	191.8	Horizontal	PK	Pass
6	14127.0000	42.08	18.99	23.09	54	-11.92	191.8	Horizontal	AV	Pass

Report No.: WSCT-ANAB-R&E260500043A-LE Issued Date: 02 June 2026

Vertical:



Suspected Data List

NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1375.6250	39.13	25.01	14.12	74	-34.87	274.6	Vertical	PK	Pass
1	1375.6250	30.04	25.01	5.03	54	-23.96	274.6	Vertical	AV	Pass
2	2484.3750	46.28	27.55	18.73	74	-27.72	89.4	Vertical	PK	Pass
2	2484.3750	37.52	27.55	9.97	54	-16.48	89.4	Vertical	AV	Pass
3	5178.7500	63.33	31.74	31.59	74	-10.67	357.3	Vertical	PK	Pass
3	5178.7500	46.16	31.74	14.42	54	-7.84	357.3	Vertical	AV	Pass
4	8214.0000	38.61	8.79	29.82	74	-35.39	0.5	Vertical	PK	Pass
4	8214.0000	31	8.79	22.21	54	-23	0.5	Vertical	AV	Pass
5	9652.5000	42.97	11.5	31.47	74	-31.03	127.1	Vertical	PK	Pass
5	9652.5000	33.51	11.5	22.01	54	-20.49	127.1	Vertical	AV	Pass
6	14017.5000	50.23	19.11	31.12	74	-23.77	86.6	Vertical	PK	Pass
6	14017.5000	42.34	19.11	23.23	54	-11.66	86.6	Vertical	AV	Pass

Note:

1. All emissions not reported were more than 20dB below the specified limit or in the noise floor.
2. Emission Level= Reading Level + Probe Factor +Cable Loss.
3. Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. EUT has been tested in unfolded states, and the report only reflects data in the unfolded state (worst-case scenario)

Note: Freq. = Emission frequency in MHz

Reading level (dBμV) = Receiver reading

Corr. Factor (dB) = Attenuation factor + Cable loss

Level (dBμV) = Reading level (dBμV) + Corr. Factor (dB)

Limit (dBμV) = Limit stated in standard


Margin (dB) = Level (dBμV) – Limits (dBμV)

6.7.3. Restricted Bands Requirements

Test result for GFSK Mode (BLE 1M the worst case)


Low channel

Horizontal:



Suspected Data List										
NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2335.9000	20.75	-9.44	30.19	74	-53.25	61.4	Horizontal	PK	Pass
1	2335.9000	7.27	-9.44	16.71	54	-46.73	61.4	Horizontal	AV	Pass
2	2359.6750	20.38	-9.33	29.71	74	-53.62	360.1	Horizontal	PK	Pass
2	2359.6750	7.21	-9.33	16.54	54	-46.79	360.1	Horizontal	AV	Pass
3	2385.8625	20.14	-9.2	29.34	74	-53.86	360.1	Horizontal	PK	Pass
3	2385.8625	7.38	-9.2	16.58	54	-46.62	360.1	Horizontal	AV	Pass


Vertical:



Suspected Data List										
NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2335.9000	20.06	-9.44	29.5	74	-53.94	25.1	Vertical	PK	Pass
1	2335.9000	7.35	-9.44	16.79	54	-46.65	25.1	Vertical	AV	Pass
2	2359.6625	19.9	-9.33	29.23	74	-54.1	153	Vertical	PK	Pass
2	2359.6625	6.85	-9.33	16.18	54	-47.15	153	Vertical	AV	Pass
3	2382.4375	20.1	-9.21	29.31	74	-53.9	318	Vertical	PK	Pass
3	2382.4375	6.98	-9.21	16.19	54	-47.02	318	Vertical	AV	Pass


Report No.: WSCT-ANAB-R&E260500043A-LE Issued Date: 02 June 2026

High channel
Horizontal:



Susputed Data List										
NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2472.9962	24.89	-8.68	33.57	74	-49.11	351.4	Horizontal	PK	Pass
1	2472.9962	8.81	-8.68	17.49	54	-45.19	351.4	Horizontal	AV	Pass
2	2484.5312	21.16	-8.6	29.76	74	-52.84	204.4	Horizontal	PK	Pass
2	2484.5312	7.32	-8.6	15.92	54	-46.68	204.4	Horizontal	AV	Pass
3	2494.4163	21.7	-8.54	30.24	74	-52.3	22.8	Horizontal	PK	Pass
3	2494.4163	7.57	-8.54	16.11	54	-46.43	22.8	Horizontal	AV	Pass

Vertical:



Susputed Data List										
NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2475.1188	26.61	-8.66	35.27	74	-47.39	360	Vertical	PK	Pass
1	2475.1188	9.15	-8.66	17.81	54	-44.85	360	Vertical	AV	Pass
2	2485.0637	21.9	-8.6	30.5	74	-52.1	352.9	Vertical	PK	Pass
2	2485.0637	8.18	-8.6	16.78	54	-45.82	352.9	Vertical	AV	Pass
3	2491.2662	22.81	-8.56	31.37	74	-51.19	314.9	Vertical	PK	Pass
3	2491.2662	9.26	-8.56	17.82	54	-44.74	314.9	Vertical	AV	Pass

Note: Freq. = Emission frequency in MHz
 Reading level (dBμV) = Receiver reading
 Corr. Factor (dB) = Attenuation factor + Cable loss
 Level (dBμV) = Reading level (dBμV) + Corr. Factor (dB)
 Limit (dBμV) = Limit stated in standard
 Margin (dB) = Level (dBμV) – Limits (dBμV)

Report No.: WSCT-ANAB-R&E260500043A-LE Issued Date: 02 June 2026

7. Test Setup Photographs

Please refer to Annex "Test Setup photos-15C" for test setup photos

*******END OF REPORT*******