







Report No.: WSCT-ANAB-R&E260500043A-BT Issued Date: 02 June 2026





Report No.: WSCT-ANAB-R&E260500043A-BT Issued Date: 02 June 2026





Report No.: WSCT-ANAB-R&E260500043A-BT Issued Date: 02 June 2026



Report No.: WSCT-ANAB-R&E260500043A-BT Issued Date: 02 June 2026






Report No.: WSCT-ANAB-R&E260500043A-BT Issued Date: 02 June 2026



6.11. Radiated Spurious Emission Measurement

6.11.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.209			
Test Method:	ANSI C63.10:2020			
Frequency Range:	9 kHz to 25 GHz			
Measurement Distance:	3 m			
Antenna Polarization:	Horizontal & Vertical			
Receiver Setup:	Frequency	Detector	RBW	VBW
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz
	30MHz-1GHz	Quasi-peak	100KHz	300KHz
	Above 1GHz	Peak	1MHz	3MHz
Limit:	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Remark
	0.009-0.490	2400/F(KHz)	300	Quasi-peak Value
	0.490-1.705	24000/F(KHz)	30	Quasi-peak Value
	1.705-30	30	30	Quasi-peak Value
	30-88	100	3	Quasi-peak Value
Test setup:	88-216	150	3	Peak Value
	216-960	200	3	Peak Value
	Above 960	500	3	Average Value
	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector
	Above 1GHz	500	3	Average
		5000	3	Peak
For radiated emissions below 30MHz				
				
30MHz to 1GHz				

	 Above 1GHz 
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. The testing follows the guidelines in Spurious Radiated Emissions of ANSI C63.10:2020 Measurement Guidelines. 2. For the radiated emission test below 1GHz: The EUT was placed on a turntable with 0.8 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level. For the radiated emission test above 1GHz: Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which

	maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Use the following spectrum analyzer settings: (1) Span shall wide enough to fully capture the emission being measured; (2) Set RBW=100 kHz for $f < 1$ GHz, RBW=1MHz for $f > 1$GHz ; VBW$\geq$RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak (3) For average measurement: use duty cycle correction factor method per 15.35(c). Duty cycle = On time/100 milliseconds On time = $N_1 \cdot L_1 + N_2 \cdot L_2 + \dots + N_{n-1} \cdot L_{n-1} + N_n \cdot L_n$ Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc Average Emission Level = Peak Emission Level + $20 \cdot \log(\text{Duty cycle})$ Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
Test results:	PASS

Note 1: The symbol of "--" in the table which means not application.

Note 2: For the test data above 1 GHz, According the ANSI C63.10-2020, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note 3: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note 4: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and normal link mode is worst.


Report No.: WSCT-ANAB-R&E260500043A-BT Issued Date: 02 June 2026

6.11.2. Test Data

Please refer to following diagram for individual

Below 1GHz

Horizontal:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		50.3700	29.52	-7.51	22.01	40.00	-17.99	QP
2		140.5800	27.44	-7.15	20.29	43.50	-23.21	QP
3		394.7200	26.08	-3.71	22.37	46.00	-23.63	QP
4		599.3900	24.96	1.32	26.28	46.00	-19.72	QP
5		715.7900	26.48	3.41	29.89	46.00	-16.11	QP
6	*	880.6900	24.89	6.49	31.38	46.00	-14.62	QP

Report No.: WSCT-ANAB-R&E260500043A-BT Issued Date: 02 June 2026

Vertical:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	38.7300	46.81	-20.52	26.29	40.00	-13.71	QP
2		97.9000	47.11	-20.21	26.90	43.50	-16.60	QP
3		396.6600	41.37	-18.78	22.59	46.00	-23.41	QP
4		612.0000	44.71	-17.66	27.05	46.00	-18.95	QP
5		767.2000	45.93	-16.84	29.09	46.00	-16.91	QP
6		957.3200	47.61	-15.57	32.04	46.00	-13.96	QP

Note1:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss - Amplifier factor.

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard

Margin (dB) = Measurement (dBuV) – Limits (dBuV)

Report No.: WSCT-ANAB-R&E260500043A-BT Issued Date: 02 June 2026

Above 1GHz


Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious above 18G is noise only, do not show on the report.

GFSK

Low channel: 2402MHz

Horizontal:




Suspected Data List

NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1095.6250	39.24	24.35	14.89	74	-34.76	122.8	Horizontal	PK	Pass
1	1095.6250	29.23	24.35	4.88	54	-24.77	122.8	Horizontal	AV	Pass
2	2450.6250	47.25	27.43	19.82	74	-26.75	254.3	Horizontal	PK	Pass
2	2450.6250	38.68	27.43	11.25	54	-15.32	254.3	Horizontal	AV	Pass
3	5184.3750	60.08	31.75	28.33	74	-13.92	265	Horizontal	PK	Pass
3	5184.3750	46.26	31.75	14.51	54	-7.74	265	Horizontal	AV	Pass
4	8041.5000	38.01	8.36	29.65	74	-35.99	226.4	Horizontal	PK	Pass
4	8041.5000	30.85	8.36	22.49	54	-23.15	226.4	Horizontal	AV	Pass
5	11746.5000	46.69	16.11	30.58	74	-27.31	1	Horizontal	PK	Pass
5	11746.5000	41.04	16.11	24.93	54	-12.96	1	Horizontal	AV	Pass
6	17847.0000	53.28	22.92	30.36	74	-20.72	141.5	Horizontal	PK	Pass
6	17847.0000	45.6	22.92	22.68	54	-8.4	141.5	Horizontal	AV	Pass

Report No.: WSCT-ANAB-R&E260500043A-BT Issued Date: 02 June 2026

Vertical:




Suspected Data List

NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1937.5000	53.08	25.62	27.46	74	-20.92	116.8	Vertical	PK	Pass
1	1937.5000	32.75	25.62	7.13	54	-21.25	116.8	Vertical	AV	Pass
2	2468.7500	48.02	27.49	20.53	74	-25.98	186.2	Vertical	PK	Pass
2	2468.7500	36.68	27.49	9.19	54	-17.32	186.2	Vertical	AV	Pass
3	3465.6250	57.33	28.48	28.85	74	-16.67	71.4	Vertical	PK	Pass
3	3465.6250	38.83	28.48	10.35	54	-15.17	71.4	Vertical	AV	Pass
4	8275.5000	38.67	8.9	29.77	74	-35.33	1.1	Vertical	PK	Pass
4	8275.5000	31	8.9	22.1	54	-23	1.1	Vertical	AV	Pass
5	9738.0000	42.37	11.73	30.64	74	-31.63	329.2	Vertical	PK	Pass
5	9738.0000	34.23	11.73	22.5	54	-19.77	329.2	Vertical	AV	Pass
6	15337.5000	49.5	18.24	31.26	74	-24.5	194.2	Vertical	PK	Pass
6	15337.5000	40.92	18.24	22.68	54	-13.08	194.2	Vertical	AV	Pass

Report No.: WSCT-ANAB-R&E260500043A-BT Issued Date: 02 June 2026

Middle channel: 2441MHz

Horizontal:




Susputed Data List

NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1438.1250	39.79	25.06	14.73	74	-34.21	71.6	Horizontal	PK	Pass
1	1438.1250	31.1	25.06	6.04	54	-22.9	71.6	Horizontal	AV	Pass
2	2520.0000	49.58	27.62	21.96	74	-24.42	236.6	Horizontal	PK	Pass
2	2520.0000	36.25	27.62	8.63	54	-17.75	236.6	Horizontal	AV	Pass
3	5180.6250	65.76	31.74	34.02	74	-8.24	-0.1	Horizontal	PK	Pass
3	5180.6250	46.29	31.74	14.55	54	-7.71	-0.1	Horizontal	AV	Pass
4	8142.0000	38.22	8.6	29.62	74	-35.78	188.2	Horizontal	PK	Pass
4	8142.0000	31	8.6	22.4	54	-23	188.2	Horizontal	AV	Pass
5	10014.0000	42.15	12.39	29.76	74	-31.85	164.2	Horizontal	PK	Pass
5	10014.0000	33.69	12.39	21.3	54	-20.31	164.2	Horizontal	AV	Pass
6	13680.0000	48.15	18.2	29.95	74	-25.85	337.6	Horizontal	PK	Pass
6	13680.0000	41.01	18.2	22.81	54	-12.99	337.6	Horizontal	AV	Pass

Report No.: WSCT-ANAB-R&E260500043A-BT Issued Date: 02 June 2026

Vertical:




Suspected Data List

NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1137.5000	38.73	24.37	14.36	74	-35.27	125.2	Vertical	PK	Pass
1	1137.5000	29.4	24.37	5.03	54	-24.6	125.2	Vertical	AV	Pass
2	2438.1250	47.28	27.39	19.89	74	-26.72	185	Vertical	PK	Pass
2	2438.1250	38.47	27.39	11.08	54	-15.53	185	Vertical	AV	Pass
3	4418.1250	52.61	30.45	22.16	74	-21.39	-0.1	Vertical	PK	Pass
3	4418.1250	43.4	30.45	12.95	54	-10.6	-0.1	Vertical	AV	Pass
4	7635.0000	37.43	7.95	29.48	74	-36.57	238.4	Vertical	PK	Pass
4	7635.0000	30.33	7.95	22.38	54	-23.67	238.4	Vertical	AV	Pass
5	9762.0000	41.48	11.79	29.69	74	-32.52	187	Vertical	PK	Pass
5	9762.0000	34.07	11.79	22.28	54	-19.93	187	Vertical	AV	Pass
6	11884.5000	45.73	16.47	29.26	74	-28.27	118.8	Vertical	PK	Pass
6	11884.5000	38.34	16.47	21.87	54	-15.66	118.8	Vertical	AV	Pass

Report No.: WSCT-ANAB-R&E260500043A-BT Issued Date: 02 June 2026

High channel: 2480MHz

Horizontal:




Suspected Data List

NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1453.7500	40.61	25.05	15.56	74	-33.39	339.9	Horizontal	PK	Pass
1	1453.7500	31.28	25.05	6.23	54	-22.72	339.9	Horizontal	AV	Pass
2	2456.2500	47.1	27.45	19.65	74	-26.9	176.6	Horizontal	PK	Pass
2	2456.2500	38.03	27.45	10.58	54	-15.97	176.6	Horizontal	AV	Pass
3	3908.7500	51.41	29.48	21.93	74	-22.59	140.8	Horizontal	PK	Pass
3	3908.7500	42	29.48	12.52	54	-12	140.8	Horizontal	AV	Pass
4	7708.5000	37.52	7.96	29.56	74	-36.48	258.7	Horizontal	PK	Pass
4	7708.5000	30.42	7.96	22.46	54	-23.58	258.7	Horizontal	AV	Pass
5	10479.0000	43.74	13.86	29.88	74	-30.26	219.3	Horizontal	PK	Pass
5	10479.0000	35.82	13.86	21.96	54	-18.18	219.3	Horizontal	AV	Pass
6	15171.0000	49.15	19.37	29.78	74	-24.85	121.3	Horizontal	PK	Pass
6	15171.0000	42.11	19.37	22.74	54	-11.89	121.3	Horizontal	AV	Pass

Report No.: WSCT-ANAB-R&E260500043A-BT Issued Date: 02 June 2026

Vertical:



Suspected Data List

NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1381.2500	39.5	25.03	14.47	74	-34.5	262.7	Vertical	PK	Pass
1	1381.2500	31.14	25.03	6.11	54	-22.86	262.7	Vertical	AV	Pass
2	2524.3750	48.03	27.63	20.4	74	-25.97	152.8	Vertical	PK	Pass
2	2524.3750	36.74	27.63	9.11	54	-17.26	152.8	Vertical	AV	Pass
3	5181.8750	66.37	31.75	34.62	74	-7.63	0	Vertical	PK	Pass
3	5181.8750	46.36	31.75	14.61	54	-7.64	0	Vertical	AV	Pass
4	8098.5000	39.32	8.48	30.84	74	-34.68	17.3	Vertical	PK	Pass
4	8098.5000	30.73	8.48	22.25	54	-23.27	17.3	Vertical	AV	Pass
5	10141.5000	42.11	12.79	29.32	74	-31.89	137.9	Vertical	PK	Pass
5	10141.5000	34.78	12.79	21.99	54	-19.22	137.9	Vertical	AV	Pass
6	13639.5000	49.18	18.08	31.1	74	-24.82	256.3	Vertical	PK	Pass
6	13639.5000	41.36	18.08	23.28	54	-12.64	256.3	Vertical	AV	Pass

Note:

- The emission levels of other frequencies are very lower than the limit and not show in test report.
- Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.
- Data of measurement shown "----" in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
- Measurements were conducted in all three modulation (GFSK, Pi/4 DQPSK, 8DPSK), and the worst case Mode (GFSK) was submitted only.
- EUT has been tested in unfolded states, and the report only reflects data in the unfolded state (worst-case scenario)

Note: Freq. = Emission frequency in MHz

Reading level (dBμV) = Receiver reading

Corr. Factor (dB) = Attenuation factor + Cable loss

Level (dBμV) = Reading level (dBμV) + Corr. Factor (dB)

Limit (dBμV) = Limit stated in standard

Margin (dB) = Level (dBμV) – Limits (dBμV)

Report No.: WSCT-ANAB-R&E260500043A-BT Issued Date: 02 June 2026


6.11.3. Restricted Bands Requirements

Bluetooth (GFSK, Pi/4-DQPSK, 8DPSK) mode have been tested, and the worst result GFSK model was report as below

GFSK

Low channel


Horizontal:



Susputed Data List

NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2338.3750	21.11	-9.43	30.54	74	-52.89	353.4	Horizontal	PK	Pass
1	2338.3750	7.54	-9.43	16.97	54	-46.46	353.4	Horizontal	AV	Pass
2	2365.2750	22	-9.3	31.3	74	-52	0	Horizontal	PK	Pass
2	2365.2750	6.53	-9.3	15.83	54	-47.47	0	Horizontal	AV	Pass
3	2392.6875	22.07	-9.16	31.23	74	-51.93	189.8	Horizontal	PK	Pass
3	2392.6875	7.45	-9.16	16.61	54	-46.55	189.8	Horizontal	AV	Pass

Vertical:




Susputed Data List

NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2325.2000	19.4	-9.48	28.88	74	-54.6	289.7	Vertical	PK	Pass
1	2325.2000	6.34	-9.48	15.82	54	-47.66	289.7	Vertical	AV	Pass
2	2354.8750	19.49	-9.34	28.83	74	-54.51	360	Vertical	PK	Pass
2	2354.8750	6.75	-9.34	16.09	54	-47.25	360	Vertical	AV	Pass
3	2381.2750	19.87	-9.22	29.09	74	-54.13	192.9	Vertical	PK	Pass
3	2381.2750	7.04	-9.22	16.26	54	-46.96	192.9	Vertical	AV	Pass


Report No.: WSCT-ANAB-R&E260500043A-BT Issued Date: 02 June 2026

High channel
Horizontal:



Suspected Data List										
NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2475.1600	50.41	-8.66	59.07	74	-23.59	295.2	Horizontal	PK	Pass
1	2475.1600	9.65	-8.66	18.31	54	-44.35	295.2	Horizontal	AV	Pass
2	2484.8575	48.32	-8.6	56.92	74	-25.68	292.8	Horizontal	PK	Pass
2	2484.8575	9.06	-8.6	17.66	54	-44.94	292.8	Horizontal	AV	Pass
3	2490.8125	24.76	-8.57	33.33	74	-49.24	285.6	Horizontal	PK	Pass
3	2490.8125	8.22	-8.57	16.79	54	-45.78	285.6	Horizontal	AV	Pass

Vertical:



Suspected Data List										
NO.	Freq. [MHz]	Level [dB(uV)]	Factor [dB]	Reading [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2474.8113	30.47	-8.67	39.14	74	-43.53	29.2	Vertical	PK	Pass
1	2474.8113	8.48	-8.67	17.15	54	-45.52	29.2	Vertical	AV	Pass
2	2484.4188	20.48	-8.6	29.08	74	-53.52	231.2	Vertical	PK	Pass
2	2484.4188	7.76	-8.6	16.36	54	-46.24	231.2	Vertical	AV	Pass
3	2492.2188	21.16	-8.56	29.72	74	-52.84	29.2	Vertical	PK	Pass
3	2492.2188	7.55	-8.56	16.11	54	-46.45	29.2	Vertical	AV	Pass

Note: Freq. = Emission frequency in MHz
 Reading level (dBμV) = Receiver reading
 Corr. Factor (dB) = Attenuation factor + Cable loss
 Level (dBμV) = Reading level (dBμV) + Corr. Factor (dB)
 Limit (dBμV) = Limit stated in standard
 Margin (dB) = Level (dBμV) – Limits (dBμV)

7. Test Setup Photographs

Please refer to Annex "Test Setup photos-15C" for test setup photos

*******END OF REPORT*******