NVLAP TESTING

NVLAP LAB CODE 600341-0

BACL Bay Area Compliance Labs Corp.

FCC SAR TEST REPORT

Applicant: **INFINIX MOBILITY LIMITED**

Address: **FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI STREET FOTAN NT HONGKONG**

Product Name: **Mobile Phone**

FCC ID: **2AIZN-YYS-X6725**

Standard(s): **47 CFR Part 2(2.1093)**

Report Number: **2502R24398E-20**

Report Date: **2025/04/22**

The above device has been tested and found compliant with the requirement of the relative standards by Bay Area Compliance Laboratories Corp. (Dongguan).

Mark Dong

Reviewed By: Mark Dong

Title: SAR Engineer

Brave Lu

Approved By: Brave Lu

Title: SAR Supervisor

Bay Area Compliance Laboratories Corp. (Dongguan)
No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China

Tel: +86-769-86858888
Fax: +86-769-86858891
www.baclcorp.com.cn

Note: The information marked ▲ is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with ★.This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government. Each test item follows the test standard(s) without deviation.

SAR TEST RESULTS SUMMARY

Mode		Max. Reported SAR Level(s) (W/kg)	Limit (W/kg)
GSM 850	1g Head SAR	1.03	1.6
	1g Body SAR	0.68	
PCS 1900	1g Head SAR	1.00	
	1g Body SAR	0.42	
WCDMA Band 2	1g Head SAR	0.79	
	1g Body SAR	0.63	
WCDMA Band 4	1g Head SAR	1.14	
	1g Body SAR	0.46	
WCDMA Band 5	1g Head SAR	0.81	
	1g Body SAR	0.56	
LTE Band 2	1g Head SAR	0.78	
	1g Body SAR	0.63	
LTE Band 5	1g Head SAR	**1.15**	
	1g Body SAR	0.50	
LTE Band 7	1g Head SAR	0.80	
	1g Body SAR	**1.12**	
LTE Band 12&17	1g Head SAR	0.77	
	1g Body SAR	0.36	
LTE Band 13	1g Head SAR	0.53	
	1g Body SAR	0.30	
LTE Band 38	1g Head SAR	0.67	
	1g Body SAR	0.93	
LTE Band 41	1g Head SAR	0.56	
	1g Body SAR	0.79	
LTE Band 66&4	1g Head SAR	1.00	
	1g Body SAR	0.39	
WLAN 2.4G	1g Head SAR	0.27	
	1g Body SAR	0.19	
Simultaneous	1g Head SAR	**1.55**	
	1g Body SAR	**1.32**	
	1g Body SAR	**1.32(Hotspot)**	

Applicable Standards	**FCC 47 CFR part 2.1093** Radiofrequency radiation exposure evaluation: portable devices
	IEEE1528:2013 IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
	KDB procedures KDB 447498 D01 General RF Exposure Guidance v06 KDB 648474 D04 Handset SAR v01r03 KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04 KDB 865664 D02 RF Exposure Reporting v01r02 KDB 941225 D01 3G SAR Procedures v03r01 KDB 941225 D05 SAR for LTE Devices v02r05 KDB 941225 D06 Hotspot Mode v02r01 KDB 248227 D01 802.11 Wi-Fi SAR v02r02

Note: This wireless device has been shown to be capable of compliance for localized specific absorption rate (SAR) for General Population/Uncontrolled Exposure limits specified in **FCC 47 CFR part 2.1093** and has been tested in accordance with the measurement procedures specified in IEEE 1528-2013 and RF exposure KDB procedures.
The results and statements contained in this report pertain only to the device(s) evaluated.

CONTENTS

SAR TEST RESULTS SUMMARY 2
DOCUMENT REVISION HISTORY 6
1. GENERAL INFORMATION 7
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 7
2. REFERENCE, STANDARDS, AND GUIDELINES 8
2.1 SAR LIMITS 8
2.2 TEST FACILITY 9
3. DESCRIPTION OF TEST SYSTEM 10
4. EQUIPMENT LIST AND CALIBRATION 15
4.1 EQUIPMENTS LIST & CALIBRATION INFORMATION 15
5. SAR MEASUREMENT SYSTEM VERIFICATION 16
5.1 LIQUID VERIFICATION 16
5.2 LIQUID VERIFICATION RESULTS 16
5.3 SYSTEM ACCURACY VERIFICATION 20
5.4 SYSTEM ACCURACY CHECK RESULTS 20
5.5 SAR SYSTEM VALIDATION DATA 21
6. EUT TEST STRATEGY AND METHODOLOGY 34
6.1 TEST POSITIONS FOR DEVICE OPERATING NEXT TO A PERSON'S EAR 34
6.2 CHEEK/TOUCH POSITION 35
6.3 EAR/TILT POSITION 35
6.4 TEST POSITIONS FOR BODY-WORN AND OTHER CONFIGURATIONS 36
6.5 TEST DISTANCE FOR SAR EVALUATION 36
6.6 SAR EVALUATION PROCEDURE 37
7. CONDUCTED OUTPUT POWER MEASUREMENT 38
7.1 TEST PROCEDURE 38
7.2 RADIO CONFIGURATION 38
7.3 MAXIMUM TARGET OUTPUT POWER 44
7.4 TEST RESULTS: 46
8. STANDALONE SAR TEST EXCLUSION CONSIDERATIONS 72
8.1 ANTENNAS LOCATION: 72
8.2 ANTENNA DISTANCE TO EDGE 72
8.3 STANDALONE SAR TEST EXCLUSION CONSIDERATIONS 73
8.4 STANDALONE SAR ESTIMATION: 74
8.5 SAR TEST EXCLUSION FOR THE EUT EDGE CONSIDERATIONS RESULT 74

9. SAR MEASUREMENT RESULTS 76
9.1 SAR TEST DATA 76
10. MEASUREMENT VARIABILITY 106
11. SAR SIMULTANEOUS TRANSMISSION DESCRIPTION 107
11.1 SIMULTANEOUS TRANSMISSION: 107
11.2 SIMULTANEOUS SAR TEST EXCLUSION CONSIDERATIONS: 107
APPENDIX A - MEASUREMENT UNCERTAINTY 108
APPENDIX B - SAR PLOTS 109
APPENDIX C - EUT TEST POSITION PHOTOS 110
APPENDIX D - PROBE CALIBRATION CERTIFICATES 111
APPENDIX E - DIPOLE CALIBRATION CERTIFICATES 112

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2502R24398E-20	Original Report	2025/04/22

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	Mobile Phone
EUT Model:	X6725
Device Type:	Portable
Exposure Category:	Population / Uncontrolled
Antenna Type(s):	Internal Antenna
Body-Worn Accessories:	None
Proximity Sensor:	None
Carrier Aggregation:	None
Operation Modes:	GSM Voice, GPRS Data, WCDMA(R99 (Voice+Data), HSUPA/HSDPA/DC-HSDPA/HSPA+), FDD-LTE, TDD-LTE,WLAN, Bluetooth
Frequency Band:	GSM 850: 824-849 MHz(TX); 869-894 MHz(RX)
	PCS 1900: 1850-1910 MHz(TX); 1930-1990 MHz(RX)
	WCDMA Band 2: 1850-1910 MHz(TX); 1930-1990 MHz(RX)
	WCDMA Band 4: 1710-1755 MHz(TX); 2110-2155 MHz(RX)
	WCDMA Band 5: 824-849 MHz(TX); 869-894 MHz(RX)
	LTE Band 2: 1850-1910 MHz(TX); 1930-1990 MHz(RX)
	LTE Band 4: 1710-1755 MHz(TX); 2110-2155 MHz(RX)
	LTE Band 5: 824-849 MHz(TX); 869-894 MHz(RX)
	LTE Band 7: 2500-2570 MHz(TX); 2620-2690 MHz(RX)
	LTE Band 12: 699-716 MHz(TX); 729-746 MHz(RX)
	LTE Band 13:777-787MHz(TX);746-756MHz(RX)
	LTE Band 17: 704-716 MHz(TX); 734-746 MHz(RX)
	LTE Band 38: 2570-2620MHz(TX);2570-2620MHz(RX)
	LTE Band 41: 2496-2690 MHz(TX); 2496-2690 MHz(RX)
	LTE Band 66: 1710-1780 MHz(TX); 2110-2200 MHz(RX)
	WLAN 2.4G: 2412-2462 MHz (TX/RX)
	WLAN 5.2G: 5150 -5250 MHz(TX/RX)
	WLAN 5.3G: 5250-5350 MHz(TX/RX)
	WLAN 5.6G: 5470-5725 MHz(TX/RX)
	WLAN 5.8G: 5725-5850 MHz(TX/RX)
	Bluetooth: 2402-2480MHz(TX/RX)
	BLE 1M: 2402-2480MHz(TX/RX)
	BLE 2M: 2404-2478MHz(TX/RX)
Dimensions (L*W*H):	165mm (L) *76mm (W) *9mm (H)
Rated Input Voltage:	DC 3.85 V from Rechargeable Battery
Serial Number:	2Z9H-1
Normal Operation:	Head and Body
EUT Received Date:	2025/03/11
Test Date:	2025/03/29~2025/04/09
EUT Received Status:	Good

2. REFERENCE, STANDARDS, AND GUIDELINES

FCC:

The Report and Order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g as recommended by the ANSI/IEEE standard C95.1-1992 [6] for an uncontrolled environment (Paragraph 65). According to the Supplement C of OET Bulletin 65 “Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under “worst-case” conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

This report describes the methodology and results of experiments performed on wireless data terminal. The objective was to determine if there is RF radiation and if radiation is found, what is the extent of radiation with respect to safety limits. SAR (Specific Absorption Rate) is the measure of RF exposure determined by the amount of RF energy absorbed by human body (or its parts) – to determine how the RF energy couples to the body or head which is a primary health concern for body worn devices. The limit below which the exposure to RF is considered safe by regulatory bodies in North America is 1.6 mW/g average over 1 gram of tissue mass.

2.1 SAR Limits

FCC Limit

EXPOSURE LIMITS	SAR (W/kg)	
	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)
Spatial Average (averaged over the whole body)	0.08	0.4
Spatial Peak (averaged over any 1 g of tissue)	**1.6**	8
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4	20

Population/Uncontrolled Environments are defined as locations where there is the exposure of individual who have no knowledge or control of their exposure.

Occupational/Controlled Environments are defined as locations where there is exposure that maybe incurred by people who are aware of the potential for exposure (i.e. as a result of employment or occupation).

General Population/Uncontrolled environments Spatial Peak limit 1.6W/kg (FCC) applied to the EUT.

2.2 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. :829273, the FCC Designation No. : CN5044.

3. DESCRIPTION OF TEST SYSTEM

These measurements were performed with the automated near-field scanning system DASY5 from Schmid & Partner Engineering AG (SPEAG) which is the Fifth generation of the system shown in the figure hereinafter:

DASY5 System Description

The DASY5 system for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal application, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running Win7 professional operating system and the DASY52 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

DASY5 Measurement Server

The DASY5 measurement server is based on a PC/104 CPU board with a 400MHz Intel ULV Celeron, 128MB chip-disk and 128MB RAM. The necessary circuits for communication with the DAE4 (or DAE3) electronics box, as well as the 16 bit AD-converter system for optical detection and digital I/O interface are contained on the DASY5 I/O board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all real-time data evaluation of field measurements and surface detection, controls robot movements and handles safety operation. The PC operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with an expansion port which is reserved for future applications. Please note that this expansion port does not have a standardized point out, and therefore only devices provided by SPEAG can be connected. Devices from any other supplier could seriously damage the measurement server.

Data Acquisition Electronics

The data acquisition electronics (DAE4) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

The input impedance of both the DAE4 as well as of the DAE3 box is 200MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

ES3DV3 E-Field Probes

Frequency	10 MHz - 4 GHz Linearity: ± 0.2 dB (30 MHz to 4 GHz)
Directivity	± 0.2 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)
Dynamic Range	5 µW/g to > 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 µW/g)
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 2.0 mm
Application	General dosimetry up to 4 GHz Dosimetry in strong gradient fields Compliance tests of mobile phones
Compatibility	DASY3, DASY4, DASY52, DASY6, DASY8 SAR, EASY6, EASY4/MRI

SAM Twin Phantom

The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region, where shell thickness
increases to 6 mm). The phantom has three measurement areas:
_ Left Head
_ Right Head
_ Flat phantom

The phantom table for the DASY systems based on the robots have the size of 100 x 50 x 85 cm (L x W x H).
For easy dislocation these tables have fork lift cut outs at the bottom.
The bottom plate contains three pairs of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. Only one device holder is necessary if two phantoms are used (e.g., for different liquids)

A white cover is provided to cover the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. Free space scans of devices on top of this phantom cover are possible.
Three reference marks are provided on the phantom counter. These reference marks are used to teach the absolute phantom position relative to the robot.

Robots

The DASY5 system uses the high precision industrial robot. The robot offers the same features important for our application:

- High precision (repeatability 0.02mm)
- High reliability (industrial design)
- Low maintenance costs (virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements (brushless synchrony motors; no stepper motors)
- Low ELF interference (motor control fields shielded via the closed metallic construction shields)

The above mentioned robots are controlled by the Staubli CS7MB robot controllers. All information regarding the use and maintenance of the robot arm and the robot controller is contained on the CDs delivered along with the robot. Paper manuals are available upon request direct from Staubli.

Area Scans

Area scans are defined prior to the measurement process being executed with a user defined variable spacing between each measurement point (integral) allowing low uncertainty measurements to be conducted. Scans defined for FCC applications utilize a 15mm2 step integral, with 1.5mm interpolation used to locate the peak SAR area used for zoom scan assessments.

Where the system identifies multiple SAR peaks (which are within 25% of peak value) the system will provide the user with the option of assessing each peak location individually for zoom scan averaging.

Zoom Scan (Cube Scan Averaging)

The averaging zoom scan volume utilized in the DASY5 software is in the shape of a cube and the side dimension of a 1 g or 10 g mass is dependent on the density of the liquid representing the simulated tissue. A density of 1000 kg/m^3 is used to represent the head and body tissue density and not the phantom liquid density, in order to be consistent with the definition of the liquid dielectric properties, i.e. the side length of the 1g cube is 10mm,with the side length of the 10g cube is 21.5mm.

When the cube intersects with the surface of the phantom, it is oriented so that 3 vertices touch the surface of the shell or the center of a face is tangent to the surface. The face of the cube closest to the surface is modified in order to conform to the tangent surface.

The zoom scan integer steps can be user defined so as to reduce uncertainty, but normal practice for typical test applications (including FCC) utilize a physical step of 7 x7 x 7 (5mmx5mmx5mm) providing a volume of 30 mm in the X & Y & Z axis.

Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE 1528-2013

Recommended Tissue Dielectric Parameters for Head liquid

Table 3—Target dielectric properties of head tissue-equivalent material in the 300 MHz to 6000 MHz frequency range

Frequency (MHz)	Relative permittivity (ε'_r)	Conductivity (σ) (S/m)
300	45.3	0.87
450	43.5	0.87
750	*41.9*	*0.89*
835	41.5	0.90
900	41.5	0.97
1450	40.5	1.20
1500	*40.4*	*1.23*
1640	*40.2*	*1.31*
1750	*40.1*	*1.37*
1800	40.0	1.40
1900	40.0	1.40
2000	40.0	1.40
2100	*39.8*	*1.49*
2300	*39.5*	*1.67*
2450	39.2	1.80
2600	*39.0*	*1.96*
3000	38.5	2.40
3500	*37.9*	*2.91*
4000	*37.4*	*3.43*
4500	*36.8*	*3.94*
5000	*36.2*	*4.45*
5200	*36.0*	*4.66*
5400	*35.8*	*4.86*
5600	*35.5*	*5.07*
5800	35.3	5.27
6000	*35.1*	*5.48*

NOTE—For convenience, permittivity and conductivity values at some frequencies that are not part of the original data from Drossos et al. [B60] or the extension to 5800 MHz are provided (i.e., the values shown in italics). These values were linearly interpolated between the values in this table that are immediately above and below these values, except the values at 6000 MHz that were linearly extrapolated from the values at 3000 MHz and 5800 MHz.

4. EQUIPMENT LIST AND CALIBRATION

4.1 Equipments List & Calibration Information

Equipment	Model	S/N	Calibration Date	Calibration Due Date
DASY5 Test Software	DASY52.10	N/A	NCR	NCR
DASY5 Measurement Server	DASY5 4.5.12	1470	NCR	NCR
Data Acquisition Electronics	DAE4	772	2025/2/17	2026/2/16
E-Field Probe	ES3DV3	3220	2024/10/15	2025/10/14
Mounting Device	MD4HHTV5	SD 000 H01 KA	NCR	NCR
Twin SAM	Twin SAM V5.0	1874	NCR	NCR
Dipole, 750 MHz	D750V3	1167	2022/10/31	2025/10/30
Dipole, 1750 MHz	D1750V2	1141	2024/6/17	2027/6/16
Dipole, 1900 MHz	D1900V2	543	2022/11/2	2025/11/1
Dipole, 2450 MHz	D2450V2	971	2024/6/15	2027/6/14
Dipole, 2600 MHz	D2600V2	1132	2022/11/1	2025/10/31
Simulated Tissue Liquid Head	HBBL600-10000V6	SL AAH U16 BC (Batch:220809-1)	Each Time	/
Network Analyzer	8753C +85047A	3029A01355 +3033A02857	2024/5/9	2025/5/8
Dielectric assessment kit	1253	SM DAK 040 CA	NCR	NCR
synthesized signal generator	8665B	3438a00584	2024/10/18	2025/10/17
EPM Series Power Meter	E4419B	MY45103907	2024/10/18	2025/10/17
Power Sensor	8482A	US37296108	2024/10/19	2025/10/18
Power Meter	EPM-441A	GB37481494	2024/10/19	2025/10/18
Power Amplifier	ZHL-5W-202-S+	416402204	NCR	NCR
Power Amplifier	ZVE-6W-83+	637202210	NCR	NCR
Directional Coupler	441493	520Z	NCR	NCR
Attenuator	20dB, 100W	LN749	NCR	NCR
Attenuator	6dB, 150W	2754	NCR	NCR
Thermometer	DTM3000	3635	2024/8/12	2025/8/11
Hygrothermograph	HTC-2	EM072	2024/11/4	2025/11/3
Wireless communication tester	8960	MY50266471	2024/9/5	2025/9/4
Wideband Radio Communication Tester	CMW500	147473	2024/9/5	2025/9/4
Spectrum Analyzer	FSV40	101589	2024/09/05	2025/09/04

5. SAR MEASUREMENT SYSTEM VERIFICATION

5.1 Liquid Verification



5.2 Liquid Verification Results

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ε_r	σ (S/m)	ε_r	σ (S/m)	$\Delta\varepsilon_r$	Δσ (S/m)	
704	Simulated Tissue Liquid Head	43.635	0.893	42.15	0.89	3.52	0.34	±5
707.5	Simulated Tissue Liquid Head	43.617	0.894	42.13	0.89	3.53	0.45	±5
711	Simulated Tissue Liquid Head	43.589	0.896	42.11	0.89	3.51	0.67	±5
750	Simulated Tissue Liquid Head	42.906	0.913	41.9	0.89	2.4	2.58	±5

**Liquid Verification above was performed on 2025/03/29.*

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ε_r	σ (S/m)	ε_r	σ (S/m)	$\Delta\varepsilon_r$	Δσ (S/m)	
750	Simulated Tissue Liquid Head	43.127	0.892	41.9	0.89	2.93	0.22	±5
782	Simulated Tissue Liquid Head	42.677	0.911	41.75	0.89	2.22	2.36	±5

**Liquid Verification above was performed on 2025/03/30.*

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ε_r	σ (S/m)	ε_r	σ (S/m)	$\Delta\varepsilon_r$	Δσ (S/m)	
750	Simulated Tissue Liquid Head	43.049	0.905	41.9	0.89	2.74	1.69	±5
826.4	Simulated Tissue Liquid Head	42.083	0.924	41.54	0.90	1.31	2.67	±5
829	Simulated Tissue Liquid Head	42.035	0.925	41.53	0.90	1.22	2.78	±5
836.5	Simulated Tissue Liquid Head	41.962	0.929	41.50	0.90	1.11	3.22	±5
836.6	Simulated Tissue Liquid Head	41.961	0.929	41.50	0.90	1.11	3.22	±5
844	Simulated Tissue Liquid Head	41.843	0.932	41.50	0.91	0.83	2.42	±5
846.6	Simulated Tissue Liquid Head	41.785	0.932	41.50	0.91	0.69	2.42	±5

**Liquid Verification above was performed on 2025/03/31.*

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ε_r	σ (S/m)	ε_r	σ (S/m)	$\Delta\varepsilon_r$	Δσ (S/m)	
750	Simulated Tissue Liquid Head	43.181	0.894	41.9	0.89	3.06	0.45	±5
824.2	Simulated Tissue Liquid Head	42.122	0.923	41.55	0.90	1.38	2.56	±5
826.4	Simulated Tissue Liquid Head	42.008	0.927	41.54	0.90	1.13	3	±5
836.6	Simulated Tissue Liquid Head	41.865	0.939	41.50	0.90	0.88	4.33	±5
846.6	Simulated Tissue Liquid Head	41.733	0.946	41.50	0.91	0.56	3.96	±5
848.8	Simulated Tissue Liquid Head	41.701	0.949	41.50	0.91	0.48	4.29	±5

**Liquid Verification above was performed on 2025/04/01.*

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ε_r	σ (S/m)	ε_r	σ (S/m)	$\Delta\varepsilon_r$	Δσ (S/m)	
750	Simulated Tissue Liquid Head	43.158	0.886	41.9	0.89	3	-0.45	±5
829	Simulated Tissue Liquid Head	42.035	0.925	41.53	0.90	1.22	2.78	±5
836.5	Simulated Tissue Liquid Head	41.984	0.927	41.50	0.90	1.17	3	±5
844	Simulated Tissue Liquid Head	41.843	0.932	41.50	0.91	0.83	2.42	±5

**Liquid Verification above was performed on 2025/04/02.*

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ε_r	σ (S/m)	ε_r	σ (S/m)	$\Delta\varepsilon_r$	Δσ (S/m)	
1712.4	Simulated Tissue Liquid Head	39.578	1.352	40.13	1.35	-1.38	0.15	±5
1732.6	Simulated Tissue Liquid Head	39.493	1.364	40.12	1.36	-1.56	0.29	±5
1750	Simulated Tissue Liquid Head	39.411	1.375	40.10	1.37	-1.72	0.36	±5
1752.6	Simulated Tissue Liquid Head	39.408	1.376	40.09	1.37	-1.70	0.44	±5

**Liquid Verification above was performed on 2025/04/02.*

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ε_r	σ (S/m)	ε_r	σ (S/m)	$\Delta\varepsilon_r$	Δσ (S/m)	
1720	Simulated Tissue Liquid Head	39.542	1.357	40.13	1.35	-1.47	0.52	±5
1745	Simulated Tissue Liquid Head	39.429	1.371	40.10	1.37	-1.67	0.07	±5
1750	Simulated Tissue Liquid Head	39.407	1.373	40.10	1.37	-1.73	0.22	±5
1770	Simulated Tissue Liquid Head	39.338	1.385	40.06	1.38	-1.80	0.36	±5

**Liquid Verification above was performed on 2025/04/03.*

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ε_r	σ (S/m)	ε_r	σ (S/m)	$\Delta\varepsilon_r$	Δσ (S/m)	
1850.2	Simulated Tissue Liquid Head	39.931	1.428	40.00	1.40	-0.17	2	±5
1852.4	Simulated Tissue Liquid Head	39.903	1.429	40.00	1.40	-0.24	2.07	±5
1880	Simulated Tissue Liquid Head	39.663	1.432	40.00	1.40	-0.84	2.29	±5
1900	Simulated Tissue Liquid Head	39.635	1.435	40.00	1.40	-0.91	2.5	±5
1907.6	Simulated Tissue Liquid Head	39.563	1.436	40.00	1.40	-1.09	2.57	±5
1909.8	Simulated Tissue Liquid Head	39.543	1.436	40.00	1.40	-1.14	2.57	±5

**Liquid Verification above was performed on 2025/04/04.*

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ε_r	σ (S/m)	ε_r	σ (S/m)	$\Delta\varepsilon_r$	Δσ (S/m)	
1860	Simulated Tissue Liquid Head	39.808	1.431	40.00	1.40	-0.48	2.21	±5
1880	Simulated Tissue Liquid Head	39.609	1.458	40.00	1.40	-0.98	4.14	±5
1900	Simulated Tissue Liquid Head	39.572	1.469	40.00	1.40	-1.07	4.93	±5

**Liquid Verification above was performed on 2025/04/05.*

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ε_r	σ (S/m)	ε_r	σ (S/m)	$\Delta\varepsilon_r$	Δσ (S/m)	
2450	Simulated Tissue Liquid Head	40.618	1.783	39.20	1.80	3.62	-0.94	±5
2506	Simulated Tissue Liquid Head	40.315	1.885	39.13	1.86	3.03	1.34	±5
2510	Simulated Tissue Liquid Head	40.3	1.891	39.12	1.86	3.02	1.67	±5
2535	Simulated Tissue Liquid Head	40.227	1.931	39.09	1.89	2.91	2.17	±5
2549.5	Simulated Tissue Liquid Head	40.167	1.953	39.07	1.91	2.81	2.25	±5

**Liquid Verification above was performed on 2025/04/06.*

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ε_r	σ (S/m)	ε_r	σ (S/m)	$\Delta\varepsilon_r$	Δσ (S/m)	
2560	Simulated Tissue Liquid Head	40.226	1.987	39.05	1.92	3.01	3.49	±5
2593	Simulated Tissue Liquid Head	39.684	2.018	39.01	1.95	1.73	3.49	±5
2600	Simulated Tissue Liquid Head	39.574	2.028	39.00	1.96	1.47	3.47	±5
2636.5	Simulated Tissue Liquid Head	38.977	2.064	38.95	2	0.07	3.2	±5
2680	Simulated Tissue Liquid Head	38.255	2.113	38.9	2.05	-1.66	3.07	±5

**Liquid Verification above was performed on 2025/04/07.*

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ε_r	σ (S/m)	ε_r	σ (S/m)	$\Delta\varepsilon_r$	Δσ (S/m)	
2580	Simulated Tissue Liquid Head	39.894	2.005	39.03	1.94	2.21	3.35	±5
2595	Simulated Tissue Liquid Head	39.653	2.021	39.01	1.95	1.65	3.64	±5
2600	Simulated Tissue Liquid Head	39.496	2.031	39.00	1.96	1.27	3.62	±5
2610	Simulated Tissue Liquid Head	39.413	2.038	38.99	1.97	1.08	3.45	±5

**Liquid Verification above was performed on 2025/04/08.*

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		ε_r	σ (S/m)	ε_r	σ (S/m)	$\Delta\varepsilon_r$	Δσ (S/m)	
2412	Simulated Tissue Liquid Head	40.779	1.744	39.28	1.77	3.82	-1.47	±5
2437	Simulated Tissue Liquid Head	40.605	1.779	39.23	1.79	3.5	-0.61	±5
2450	Simulated Tissue Liquid Head	40.553	1.802	39.20	1.80	3.45	0.11	±5
2462	Simulated Tissue Liquid Head	40.508	1.818	39.18	1.81	3.39	0.44	±5

**Liquid Verification above was performed on 2025/04/09.*

5.3 System Accuracy Verification

Prior to the assessment, the system validation kit was used to test whether the system was operating within its specifications of ±10%. The validation results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

The spacing distances in the **System Verification Setup Block Diagram** is given by the following:

a) s = 15 mm ± 0,2 mm for 300 MHz ≤ f ≤ 1 000 MHz;
b) s = 10 mm ± 0,2 mm for 1 000 MHz < f ≤ 3 000 MHz;
c) s = 10 mm ± 0,2 mm for 3 000 MHz < f ≤ 6 000 MHz.

System Verification Setup Block Diagram



5.4 System Accuracy Check Results

Date	Frequency Band (MHz)	Liquid Type	Input Power (mW)	Measured SAR (W/kg)		Normalized to 1W (W/kg)	Target Value (W/Kg)	Delta (%)	Tolerance (%)
2025/03/29	750	Simulated Tissue Liquid Head	100	1g	0.831	8.31	8.48	-2.00	±10
2025/03/30	750	Simulated Tissue Liquid Head	100	1g	0.821	8.21	8.48	-3.18	±10
2025/03/31	750	Simulated Tissue Liquid Head	100	1g	0.846	8.46	8.48	-0.24	±10
2025/04/01	750	Simulated Tissue Liquid Head	100	1g	0.838	8.38	8.48	-1.18	±10
2025/04/02	750	Simulated Tissue Liquid Head	100	1g	0.818	8.18	8.48	-3.54	±10
2025/04/02	1750	Simulated Tissue Liquid Head	100	1g	3.42	34.2	36.1	-5.26	±10
2025/04/03	1750	Simulated Tissue Liquid Head	100	1g	3.55	35.5	36.1	-1.66	±10
2025/04/04	1900	Simulated Tissue Liquid Head	100	1g	4.10	41.0	40.2	1.99	±10
2025/04/05	1900	Simulated Tissue Liquid Head	100	1g	4.22	42.2	40.2	4.98	±10
2025/04/06	2450	Simulated Tissue Liquid Head	100	1g	4.84	48.4	52.7	-8.16	±10
2025/04/09	2450	Simulated Tissue Liquid Head	100	1g	4.99	49.9	52.7	-5.31	±10
2025/04/07	2600	Simulated Tissue Liquid Head	100	1g	5.19	51.9	55.8	-6.99	±10
2025/04/08	2600	Simulated Tissue Liquid Head	100	1g	5.34	53.4	55.8	-4.3	±10

Note:
All the SAR values are normalized to 1Watt forward power.

5.5 SAR SYSTEM VALIDATION DATA

System Performance 750 MHz Head was performed on 2025/03/29

DUT: D750V3; Type: 750 MHz; Serial: 1167

Communication System: CW (0); Frequency: 750 MHz; Duty Cycle: 1:1
Medium parameters used: f = 750 MHz; σ = 0.913 S/m; ε_r = 42.906; ρ = 1000 kg/m^3;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3220; ConvF(6.68, 6.68, 6.68) @ 750 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

Area Scan (6x15x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 0.893 W/kg

Zoom Scan (5x5x7) /Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 29.78 V/m; Power Drift = 0.18 dB
Peak SAR (extrapolated) = 1.13 W/kg
SAR(1 g) = 0.831 W/kg; SAR(10 g) = 0.596 W/kg
Maximum value of SAR (measured) = 0.944 W/kg



0 dB = 0.944 W/kg = -0.25 dBW/kg

System Performance 750 MHz Head was performed on 2025/03/30

DUT: D750V3; Type: 750 MHz; Serial: 1167

Communication System: CW (0); Frequency: 750 MHz; Duty Cycle: 1:1
Medium parameters used: f = 750 MHz; σ = 0.892 S/m; ε_r = 43.127; ρ = 1000 kg/m^3;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3220; ConvF(6.68, 6.68, 6.68) @ 750 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

Area Scan (6x15x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 0.876 W/kg

Zoom Scan (5x5x7) /Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 26.42 V/m; Power Drift = 0.13 dB
Peak SAR (extrapolated) = 1.08 W/kg
SAR(1 g) = 0.821 W/kg; SAR(10 g) = 0.584 W/kg
Maximum value of SAR (measured) = 0.918 W/kg



0 dB = 0.918 W/kg = -0.37 dBW/kg

System Performance 750 MHz Head was performed on 2025/03/31

DUT: D750V3; Type: 750 MHz; Serial: 1167

Communication System: CW (0); Frequency: 750 MHz; Duty Cycle: 1:1
Medium parameters used: f = 750 MHz; σ = 0.905 S/m; ε_r = 43.049; ρ = 1000 kg/m^3;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3220; ConvF(6.68, 6.68, 6.68) @ 750 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

Area Scan (7x15x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 0.917 W/kg

Zoom Scan (5x5x7) /Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 32.15 V/m; Power Drift = 0.14 dB
Peak SAR (extrapolated) = 1.26 W/kg
SAR(1 g) = 0.846 W/kg; SAR(10 g) = 0.592 W/kg
Maximum value of SAR (measured) = 0.969 W/kg



0 dB = 0.969 W/kg = -0.14 dBW/kg

System Performance 750 MHz Head was performed on 2025/04/01

DUT: D750V3; Type: 750 MHz; Serial: 1167

Communication System: CW (0); Frequency: 750 MHz; Duty Cycle: 1:1
Medium parameters used: f = 750 MHz; σ = 0.894 S/m; ε_r = 43.181; ρ = 1000 kg/m^3;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3220; ConvF(6.68, 6.68, 6.68) @ 750 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

Area Scan (7x15x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 0.901 W/kg

Zoom Scan (5x5x7) /Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 30.12 V/m; Power Drift = 0.19 dB
Peak SAR (extrapolated) = 1.17 W/kg
SAR(1 g) = 0.838 W/kg; SAR(10 g) = 0.599 W/kg
Maximum value of SAR (measured) = 0.951 W/kg



0 dB = 0.951 W/kg = -0.22 dBW/kg

System Performance 750 MHz Head was performed on 2025/04/02

DUT: D750V3; Type: 750 MHz; Serial: 1167

Communication System: CW (0); Frequency: 750 MHz; Duty Cycle: 1:1
Medium parameters used: f = 750 MHz; σ = 0.886 S/m; ε_r = 43.158; ρ = 1000 kg/m^3;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3220; ConvF(6.68, 6.68, 6.68) @ 750 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

Area Scan (6x15x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 0.872 W/kg

Zoom Scan (5x5x7) /Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 26.65 V/m; Power Drift = 0.13 dB
Peak SAR (extrapolated) = 1.05 W/kg
SAR(1 g) = 0.818 W/kg; SAR(10 g) = 0.575 W/kg
Maximum value of SAR (measured) = 0.929 W/kg



0 dB = 0.929 W/kg = -0.32 dBW/kg

System Performance 1750 MHz Head was performed on 2025/04/02

DUT: D1750V2; Type: 1750 MHz; Serial: 1141

Communication System: CW (0); Frequency: 1750 MHz; Duty Cycle: 1:1
Medium parameters used: f = 1750 MHz; σ = 1.375 S/m; ε_r = 39.411; ρ = 1000 kg/m^3;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3220; ConvF(5.53, 5.53, 5.53) @ 1750 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 3.92 W/kg

Zoom Scan (5x5x7) /Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 44.24 V/m; Power Drift = -0.08 dB
Peak SAR (extrapolated) = 5.06 W/kg
SAR(1 g) = 3.42 W/kg; SAR(10 g) = 2.11 W/kg
Maximum value of SAR (measured) = 4.08 W/kg



0 dB = 4.08 W/kg = 6.11 dBW/kg

System Performance 1750 MHz Head was performed on 2025/04/03

DUT: D1750V2; Type: 1750 MHz; Serial: 1141

Communication System: CW (0); Frequency: 1750 MHz; Duty Cycle: 1:1
Medium parameters used: f = 1750 MHz; σ = 1.373 S/m; ε_r = 39.407; ρ = 1000 kg/m^3;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3220; ConvF(5.53, 5.53, 5.53) @ 1750 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 4.67 W/kg

Zoom Scan (5x5x7) /Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 46.85 V/m; Power Drift = -0.19 dB
Peak SAR (extrapolated) = 5.69 W/kg
SAR(1 g) = 3.55 W/kg; SAR(10 g) = 2.13 W/kg
Maximum value of SAR (measured) = 4.19 W/kg



0 dB = 4.19 W/kg = 6.22 dBW/kg

System Performance 1900 MHz Head was performed on 2025/04/04

DUT: D1900V2; Type: 1900 MHz; Serial: 543

Communication System: CW (0); Frequency: 1900 MHz; Duty Cycle: 1:1
Medium parameters used: f = 1900 MHz; σ = 1.435 S/m; ε_r = 39.635; ρ = 1000 kg/m^3;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3220; ConvF(5.24, 5.24, 5.24) @ 1900 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 4.68 W/kg

Zoom Scan (5x5x7) /Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 54.24 V/m; Power Drift = 0.06 dB
Peak SAR (extrapolated) = 6.23 W/kg
SAR(1 g) = 4.1 W/kg; SAR(10 g) = 2.05 W/kg
Maximum value of SAR (measured) = 4.88 W/kg



0 dB = 4.88 W/kg = 6.88 dBW/kg

System Performance 1900 MHz Head was performed on 2025/04/05

DUT: D1900V2; Type: 1900 MHz; Serial: 543

Communication System: CW (0); Frequency: 1900 MHz; Duty Cycle: 1:1
Medium parameters used: f = 1900 MHz; σ = 1.469 S/m; ε_r = 39.572; ρ = 1000 kg/m^3;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3220; ConvF(5.24, 5.24, 5.24) @ 1900 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 4.89 W/kg

Zoom Scan (5x5x7) /Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 59.37 V/m; Power Drift = 0.17 dB
Peak SAR (extrapolated) = 6.46 W/kg
SAR(1 g) = 4.22 W/kg; SAR(10 g) = 2.14 W/kg
Maximum value of SAR (measured) = 4.96 W/kg



0 dB = 4.96 W/kg = 6.95 dBW/kg

System Performance 2450 MHz Head was performed on 2025/04/06

DUT: D2450V2; Type: 2450 MHz; Serial: 971

Communication System: CW (0); Frequency: 2450 MHz; Duty Cycle: 1:1
Medium parameters used: f = 2450 MHz; σ = 1.783 S/m; ε_r = 40.618; ρ = 1000 kg/m^3;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3220; ConvF(4.83, 4.83, 4.83) @ 2450 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

Area Scan (7x11x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (measured) = 5.27 W/kg

Zoom Scan (7x7x7) /Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 50.76 V/m; Power Drift = 0.16dB
Peak SAR (extrapolated) = 7.93 W/kg
SAR(1 g) = 4.84 W/kg; SAR(10 g) = 2.67 W/kg
Maximum value of SAR (measured) = 6.03 W/kg



0 dB = 6.03 W/kg = 7.80 dBW/kg

System Performance 2450 MHz Head was performed on 2025/04/09

DUT: D2450V2; Type: 2450 MHz; Serial: 971

Communication System: CW (0); Frequency: 2450 MHz; Duty Cycle: 1:1
Medium parameters used: f = 2450 MHz; σ = 1.802 S/m; ε_r = 40.553; ρ = 1000 kg/m^3;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3220; ConvF(4.83, 4.83, 4.83) @ 2450 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

Area Scan (7x10x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (measured) = 5.58 W/kg

Zoom Scan (7x7x7) /Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 56.67 V/m; Power Drift = 0.12 dB
Peak SAR (extrapolated) = 8.05 W/kg
SAR(1 g) = 4.99 W/kg; SAR(10 g) = 2.72 W/kg
Maximum value of SAR (measured) = 6.16 W/kg



0 dB = 6.16 W/kg = 7.90 dBW/kg

System Performance 2600 MHz Head was performed on 2025/04/07

DUT: D2600V2; Type: 2600 MHz; Serial: 1132

Communication System: CW (0); Frequency: 2600 MHz; Duty Cycle: 1:1
Medium parameters used: f = 2600 MHz; σ = 2.028 S/m; ε_r = 39.574; ρ = 1000 kg/m^3;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3220; ConvF(4.66, 4.66, 4.66) @ 2600 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

Area Scan (7x11x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (measured) = 6.29 W/kg

Zoom Scan (7x7x7) /Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 54.38 V/m; Power Drift = -0.11 dB
Peak SAR (extrapolated) = 8.76 W/kg
SAR(1 g) = 5.19 W/kg; SAR(10 g) = 2.76 W/kg
Maximum value of SAR (measured) = 6.43 W/kg



0 dB = 6.43 W/kg = 8.08 dBW/kg

System Performance 2600 MHz Head was performed on 2025/04/08

DUT: D2600V2; Type: 2600 MHz; Serial: 1132

Communication System: CW (0); Frequency: 2600 MHz; Duty Cycle: 1:1
Medium parameters used: f = 2600 MHz; σ = 2.031 S/m; ε_r = 39.496; ρ = 1000 kg/m^3;
Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3220; ConvF(4.66, 4.66, 4.66) @ 2600 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

Area Scan (7x11x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (measured) = 6.67 W/kg

Zoom Scan (7x7x7) /Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 57.52 V/m; Power Drift = -0.16 dB
Peak SAR (extrapolated) = 8.91 W/kg
SAR(1 g) = 5.34 W/kg; SAR(10 g) = 2.79 W/kg
Maximum value of SAR (measured) = 6.68 W/kg



0 dB = 6.68 W/kg = 8.25 dBW/kg

6. EUT TEST STRATEGY AND METHODOLOGY

6.1 Test Positions for Device Operating Next to a Person's Ear

This category includes most wireless handsets with fixed, retractable or internal antennas located toward the top half of the device, with or without a foldout, sliding or similar keypad cover. The handset should have its earpiece located within the upper ¼ of the device, either along the centerline or off-centered, as perceived by its users. This type of handset should be positioned in a normal operating position with the "test device reference point" located along the "vertical centerline" on the front of the device aligned to the "ear reference point". The "test device reference point" should be located at the same level as the center of the earpiece region. The "vertical centerline" should bisect the front surface of the handset at its top and bottom edges. A "ear reference point" is located on the outer surface of the head phantom on each ear spacer. It is located 1.5 cm above the center of the ear canal entrance in the "phantom reference plane" defined by the three lines joining the center of each "ear reference point" (left and right) and the tip of the mouth.

A handset should be initially positioned with the earpiece region pressed against the ear spacer of a head phantom. For the SCC-34/SC-2 head phantom, the device should be positioned parallel to the "N-F" line defined along the base of the ear spacer that contains the "ear reference point". For interim head phantoms, the device should be positioned parallel to the cheek for maximum RF energy coupling. The "test device reference point" is aligned to the "ear reference point" on the head phantom and the "vertical centerline" is aligned to the "phantom reference plane". This is called the "initial ear position". While maintaining these three alignments, the body of the handset is gradually adjusted to each of the following positions for evaluating SAR:





6.2 Cheek/Touch Position

1. The device is brought toward the mouth of the head phantom by pivoting against the "ear reference point" or along the "N-F" line for the SCC-34/SC-2 head phantom.
2. This test position is established:
   3. When any point on the display, keypad or mouthpiece portions of the handset is in contact with the phantom.
   4. (or) When any portion of a foldout, sliding or similar keypad cover opened to its intended self-adjusting normal use position is in contact with the cheek or mouth of the phantom.
5. For existing head phantoms – when the handset loses contact with the phantom at the pivoting point, rotation should continue until the device touches the cheek of the phantom or breaks its last contact from the ear spacer.

Cheek /Touch Position



6.3 Ear/Tilt Position

With the handset aligned in the "Cheek/Touch Position":

1) If the earpiece of the handset is not in full contact with the phantom's ear spacer (in the "Cheek/Touch position") and the peak SAR location for the "Cheek/Touch" position is located at the ear spacer region or corresponds to the earpiece region of the handset, the device should be returned to the "initial ear position" by rotating it away from the mouth until the earpiece is in full contact with the ear spacer.

2) (otherwise) The handset should be moved (translated) away from the cheek perpendicular to the line passes through both "ear reference points" (note: one of these ear reference points may not physically exist on a split head model) for approximate 2-3 cm. While it is in this position, the device handset is tilted away from the mouth with respect to the "test device reference point" until the inside angle between the vertical centerline on the front surface of the phone and the horizontal line passing through the ear reference point is by 15 80°. After the tilt, it is then moved (translated) back toward the head perpendicular to the line passes through both "ear reference points" until the device touches the phantom or the ear spacer. If the antenna touches the head first, the positioning process should be repeated with a tilt angle less than 15° so that the device and its antenna would touch the phantom simultaneously. This test position may require a device holder or positioner to achieve the translation and tilting with acceptable positioning repeatability.

If a device is also designed to transmit with its keypad cover closed for operating in the head position, such positions should also be considered in the SAR evaluation. The device should be tested on the left and right side of the head phantom in the "Cheek/Touch" and "Ear/Tilt" positions. When applicable, each configuration should be tested with the antenna in its fully extended and fully retracted positions. These test configurations should be tested at the high, middle and low frequency channels of each operating mode; for example, AMPS, CDMA, and TDMA. If the SAR measured at the middle channel for each test configuration (left, right, Cheek/Touch, Tilt/Ear, extended and retracted) is at least 2.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).

If the transmission band of the test device is less than 10 MHz, testing at the high and low frequency channels is optional.

Ear /Tilt 15° Position



6.4 Test positions for body-worn and other configurations

Body-worn operating configurations should be tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in normal use configurations. Devices with a headset output should be tested with a headset connected to the device. When multiple accessories that do not contain metallic components are supplied with the device, the device may be tested with only the accessory that dictates the closest spacing to the body. When multiple accessories that contain metallic components are supplied with the device, the device must be tested with each accessory that contains a unique metallic component. If multiple accessories share an identical metallic component (e.g., the same metallic belt-clip used with different holsters with no other metallic components), only the accessory that dictates the closest spacing to the body must be tested.

Body-worn accessories may not always be supplied or available as options for some devices that are intended to be authorized for body-worn use. A separation distance of 1.5 cm between the back of the device and a flat phantom is recommended for testing body-worn SAR compliance under such circumstances. Other separation distances may be used, but they should not exceed 2.5 cm. In these cases, the device may use body-worn accessories that provide a separation distance greater than that tested for the device provided however that the accessory contains no metallic components.



Figure 5 – Test positions for body-worn devices

6.5 Test Distance for SAR Evaluation

For Body Mode (1g Body SAR) the EUT(Equipment Under Test) is set 10mm away from the phantom, the test distance is 10mm.

6.6 SAR Evaluation Procedure

The evaluation was performed with the following procedure:

Step 1: Measurement of the SAR value at a fixed location above the ear point or central position was used as a reference value for assessing the power drop. The SAR at this point is measured at the start of the test and then again at the end of the testing.

Step 2: The SAR distribution at the exposed side of the head was measured at a distance of 4 mm from the inner surface of the shell. The area covered the entire dimension of the head or radiating structures of the EUT, the horizontal grid spacing was 15 mm x 15 mm, and the SAR distribution was determined by integrated grid of 1.5mm x 1.5mm. Based on these data, the area of the maximum absorption was determined by spline interpolation. The first Area Scan covers the entire dimension of the EUT to ensure that the hotspot was correctly identified.

Step 3: Around this point, a volume of 30 mm x 30 mm x 30 mm was assessed by measuring 7x 7 x 7 points. On the basis of this data set, the spatial peak SAR value was evaluated under the following procedure:

1) The data at the surface were extrapolated, since the center of the dipoles is 1.2 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.3 mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.

2) The maximum interpolated value was searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g or 10 g) were computed by the 3D-Spline interpolation algorithm. The 3D-Spline is composed of three one dimensional splines with the “Not a knot"-condition (in x, y and z-directions). The volume was integrated with the trapezoidal-algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the averages.

All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.

Step 4: Re-measurement of the SAR value at the same location as in Step 1. If the value changed by more than 5%, the evaluation was repeated.

7. CONDUCTED OUTPUT POWER MEASUREMENT

7.1 Test Procedure

The RF output of the transmitter was connected to the input of the Wireless Communication Test Set through Connector.



GSM/WCDMA/LTE

The RF output of the transmitter was connected to the input port of the Power Meter through Connector.



WLAN/BT

7.2 Radio Configuration

The power measurement was configured by the Wireless Communication Test Set.

GSM/GPRS

Function: Menu select > GSM Mobile Station > GSM 850/1900
Press Connection control to choose the different menus
Press RESET > choose all the reset all settings
Connection Press Signal Off to turn off the signal and change settings
Network Support > GSM + GPRS or GSM + EGSM
Main Service > Packet Data
Service selection > Test Mode A – Auto Slot Config. off
MS Signal Press Slot Config Bottom on the right twice to select and change the number of time slots and power setting
> Slot configuration > Uplink/Gamma
> 33 dBm for GPRS 850
> 30 dBm for GPRS 1900
BS Signal Enter the same channel number for TCH channel (test channel) and BCCH channel
Frequency Offset > + 0 Hz
Mode > BCCH and TCH
BCCH Level > -85 dBm (May need to adjust if link is not stabe)
BCCH Channel > choose desire test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel]

Channel Type > Off
P0 > 4 dB
Slot Config >Unchanged (if already set under MS signal)
TCH > choose desired test channel
Hopping > Off

Main Timeslot > 3
Network Coding Scheme > CS4 (GPRS)
Bit Stream >2E9-1 PSR Bit Stream
AF/RF Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input
Connection Press Signal on to turn on the signal and change settings

WCDMA Release 99

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP
TS34.121-1 specification. The EUT has a nominal maximum output power of 24dBm (+1.7/-3.7).

WCDMA General Settings	Loopback Mode	Test Mode 1
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	β_c/β_d	8/15

HSDPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP
TS34.121-1 specification.

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subset	1	2	3	4
WCDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set1			
	Power Control Algorithm	Algorithm2			
	β_c	2/15	12/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	β_d(SF)	64			
	β_c/β_d	2/15	12/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
	MPR(dB)	0	0	0.5	0.5
HSDPA Specific Settings	DACK	8			
	DNAK	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback	4ms			
	CQI Repetition Factor	2			
	Ahs=βhs/ βc	30/15			

HSUPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP
TS34.121-1 specification.

	Mode	HSUPA	HSUPA	HSUPA	HSUPA	HSUPA
	Subset	**1**	**2**	**3**	**4**	**5**
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set1				
	HSUPA Test	HSUPA Loopback				
	Power Control Algorithm	Algorithm2				
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	0
	β_{ec}	209/225	12/15	30/15	2/15	5/15
	β_c/β_d	11/15	6/15	15/9	2/15	-
	β_{hs}	22/15	12/15	30/15	4/15	5/15
	CM(dB)	1.0	3.0	2.0	3.0	1.0
	MPR(dB)	0	2	1	2	0
HSDPA Specific Settings	DACK	8				
	DNAK	8				
	DCQI	8				
	Ack-Nack repetition factor	3				
	CQI Feedback	4ms				
	CQI Repetition Factor	2				
	Ahs=β_{hs}/ β_c	30/15				
HSUPA Specific Settings	DE-DPCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI	75	67	92	71	81
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9
	Reference E_FCls	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27		E-TFCI 11 E-TFCI PO4 E-TFCI 92 E-TFCI PO 18	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27	

DC-HSDPA

The following tests were conducted according to the test requirements in Table C.8.1.12 of 3GPP TS 34.121-1

Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table. Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		

HSPA+

Sub-test	β_c (Note3)	β_d	β_{HS} (Note1)	β_{ec}	β_{ed} (2xSF2) (Note 4)	β_{ed} (2xSF4) (Note 4)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 4)	E-TFCI (Note 5)	E-TFCI (boost)
1	1	0	30/15	30/15	$\beta_{ed}1$: 30/15 $\beta_{ed}2$: 30/15	$\beta_{ec}3$: 24/15 $\beta_{ec}4$: 24/15	3.5	2.5	14	105	105

Note 1: Δ_{ACK}, Δ_{NACK} and Δ_{CQI} = 30/15 with β_{hs} = 30/15 * β_c.
Note 2: CM = 3.5 and the MPR is based on the relative CM difference, MPR = MAX(CM-1,0).
Note 3: DPDCH is not configured, therefore the β_c is set to 1 and β_d = 0 by default.
Note 4: β_{ed} can not be set directly; it is set by Absolute Grant Value.
Note 5: All the sub-tests require the UE to transmit 2SF2+2SF4 16QAM EDCH and they apply for UE using E-DPDCH category 7. E-DCH TTI is set to 2ms TTI and E-DCH table index = 2. To support these E-DCH configurations DPDCH is not allocated. The UE is signalled to use the extrapolation algorithm.

The following tests were conducted according to the test requirements in Table C.11.1.4 of 3GPP TS 34.121-1

FDD-LTE

For UE Power Class 1 and 3, the allowed Maximum Power Reduction (MPR) for the maximum output power in Table 6.2.2-1due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1 and 3

Modulation	Channel bandwidth / Transmission bandwidth (N_{RB})						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

For UE Power Class 1 and 3 the specific requirements and identified sub clauses are specified in Table 6.2.4-1 along with the allowed A-MPR values that may be used to meet these requirements. The allowed A-MPR values specified below in Table 6.2.4.-1 to 6.2.4-15 are in addition to the allowed MPR requirements specified in sub clause 6.2.3.

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (subclause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N_{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	N/A
NS_03	6.6.2.2.1	2, 4,10, 23, 25, 35, 36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
			10, 15, 20	Table 6.2.4-4	
NS_05	6.6.3.3.1	1	10,15,20	≥ 50	≤ 1
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.6-1	N/A
NS_07	6.6.2.2.3 6.6.3.3.2	13	10	Table 6.2.4-2	
NS_08	6.6.3.3.3	19	10, 15	> 44	≤ 3
NS_09	6.6.3.3.4	21	10, 15	> 40	≤ 1
				> 55	≤ 2
NS_10		20	15, 20	Table 6.2.4-3	
NS_11	6.6.2.2.1	23	1.4, 3, 5, 10, 15, 20	Table 6.2.4-5	
NS_12	6.6.3.3.5	26	1.4, 3, 5	Table 6.2.4-6	
NS_13	6.6.3.3.6	26	5	Table 6.2.4-7	
NS_14	6.6.3.3.7	26	10, 15	Table 6.2.4-8	
NS_15	6.6.3.3.8	26	1.4, 3, 5, 10, 15	Table 6.2.4-9 Table 6.2.4-10	
NS_16	6.6.3.3.9	27	3, 5, 10	Table 6.2.4-11, Table 6.2.4-12, Table 6.2.4-13	
NS_17	6.6.3.3.10	28	5, 10	Table 5.6-1	N/A
NS_18	6.6.3.3.11	28	5	≥ 2	≤ 1
			10, 15, 20	≥ 1	≤ 4
NS_19	6.6.3.3.12	44	10, 15, 20	Table 6.2.4-14	
NS_20	6.2.2 6.6.2.2.1 6.6.3.2	23	5, 10, 15, 20	Table 6.2.4-15	
...					
NS_32	-	-	-	-	-

TDD-LTE

LTE TDD Band 41 supports 3GPP TS 36.211 section 4.2 for Type 2 Frame Structure and Table 4.2-2 for uplink-downlink configurations and Table 4.2-1 for Special subframe configurations.

Table 4.2-1: Configuration of special subframe (lengths of DwPTS/GP/UpPTS).

Special subframe configuration	Normal cyclic prefix in downlink			Extended cyclic prefix in downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
0	$6592 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$	$7680 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$
1	$19760 \cdot T_s$			$20480 \cdot T_s$		
2	$21952 \cdot T_s$			$23040 \cdot T_s$		
3	$24144 \cdot T_s$			$25600 \cdot T_s$		
4	$26336 \cdot T_s$			$7680 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$
5	$6592 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$	$20480 \cdot T_s$		
6	$19760 \cdot T_s$			$23040 \cdot T_s$		
7	$21952 \cdot T_s$			$12800 \cdot T_s$		
8	$24144 \cdot T_s$			-	-	-
9	$13168 \cdot T_s$			-	-	-

Table 4.2-2: Uplink-downlink configurations.

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

Calculated Duty Cycle

Uplink-Downlink Configuration	Downlink-to-Uplink Switch-point Periodicity	Subframe Number										Calculated Duty Cycle (%)
		0	1	2	3	4	5	6	7	8	9	
0	5 ms	D	S	U	U	U	D	S	U	U	U	63.33
1	5 ms	D	S	U	U	D	D	S	U	U	D	43.33
2	5 ms	D	S	U	D	D	D	S	U	D	D	23.33
3	10 ms	D	S	U	U	U	D	D	D	D	D	31.67
4	10 ms	D	S	U	U	D	D	D	D	D	D	21.67
5	10 ms	D	S	U	D	D	D	D	D	D	D	11.67
6	5 ms	D	S	U	U	U	D	S	U	U	D	53.33

We used configuration 0 for LTE Band 38/41 SAR test, that is 63.33%(1:1.58)for duty cycle.

7.3 Maximum Target Output Power

Max Target Power(dBm)			
Mode/Band	Channel		
	Low	Middle	High
GSM 850	30.5	30.5	30.5
GPRS 1 TX Slot	30.5	30.5	30.0
GPRS 2 TX Slot	30.5	30.0	30.0
GPRS 3 TX Slot	29.0	29.0	29.0
GPRS 4 TX Slot	27.0	27.0	27.0
PCS 1900	27.0	27.0	27.0
GPRS 1 TX Slot	27.0	27.0	27.0
GPRS 2 TX Slot	26.5	26.5	26.5
GPRS 3 TX Slot	26.0	26.0	26.0
GPRS 4 TX Slot	23.5	23.5	24.0
WCDMA Band 2	15.0	15.0	15.0
HSDPA	15.0	15.0	15.0
HSUPA	15.0	15.0	15.0
DC-HSDPA	15.0	15.0	15.0
HSPA+	15.0	15.0	15.0
WCDMA Band 4	14.5	15.0	14.5
HSDPA	15.0	15.0	15.0
HSUPA	15.0	15.0	15.0
DC-HSDPA	15.0	15.0	15.0
HSPA+	15.0	15.0	15.0
WCDMA Band 5	23.5	23.5	23.5
HSDPA	23.0	23.5	23.5
HSUPA	24.0	23.5	23.5
DC-HSDPA	23.0	22.0	23.5
HSPA+	23.5	23.5	23.5
LTE Band 2 1RB	16.5	16.5	16.5
LTE Band 2 50%RB	15.0	15.0	15.0
LTE Band 2 100%RB	15.0	15.0	15.0
LTE Band 4 1RB	17.5	17.5	17.5
LTE Band 4 50%RB	16.5	16.5	16.5
LTE Band 4 100%RB	16.5	16.5	16.5
LTE Band 5 1RB	24.5	24.5	24.5
LTE Band 5 50%RB	23.0	23.0	23.0
LTE Band 5 100%RB	23.0	23.0	23.0
LTE Band 7 1RB	14.5	16.0	14.5
LTE Band 7 50%RB	13.5	14.5	14.5
LTE Band 7 100%RB	13.5	14.5	14.5
LTE Band 12 1RB	25.0	25.0	25.0
LTE Band 12 50%RB	23.0	23.0	23.0
LTE Band 12 100%RB	23.0	23.0	23.0
LTE Band 13 1RB	/	24.0	/
LTE Band 13 50%RB	/	23.5	/
LTE Band 13 100%RB	/	23.0	/
LTE Band 17 1RB	25.0	25.0	25.0

Max Target Power(dBm)			
Mode/Band	Channel		
	Low	Middle	High
LTE Band 17 50%RB	23.0	23.0	23.0
LTE Band 17 100%RB	23.0	23.0	23.0
LTE Band 38 1RB	19.6	19.6	17.5
LTE Band 38 50%RB	18.5	18.5	19.0
LTE Band 38 100%RB	18.5	18.5	18.5
LTE Band 41 1RB	19.5	20.0	18.0
LTE Band 41 50%RB	18.5	18.5	18.5
LTE Band 41 100%RB	18.5	18.5	18.5
LTE Band 66 1RB	17.5	17.5	17.5
LTE Band 66 50%RB	16.5	16.5	16.5
LTE Band 66 100%RB	16.0	16.0	16.0
WLAN 2.4G(802.11b)	16.0	16.0	17.0
WLAN 2.4G(802.11g)	11.5	11.5	13.0
WLAN 2.4G(802.11n20)	14.0	13.5	14.5
WLAN 5.2G(802.11a)	8.1	8.1	8.1
WLAN 5.2G(802.11n20)	8.1	8.1	8.1
WLAN 5.2G(802.11n40)	8.1	/	8.1
WLAN 5.2G(802.11ac80)	/	8.1	/
WLAN 5.3G(802.11a)	8.1	8.1	8.1
WLAN 5.3G(802.11n20)	8.1	8.1	8.1
WLAN 5.3G(802.11n40)	8.1	/	8.1
WLAN 5.3G(802.11ac80)	/	8.1	/
WLAN 5.6G(802.11a)	7.9	7.9	7.9
WLAN 5.6G(802.11n20)	7.9	7.9	7.9
WLAN 5.6G(802.11n40)	7.9	7.9	7.9
WLAN 5.6G(802.11ac80)	7.9	7.9	7.9
WLAN 5.8G(802.11a)	7.9	7.9	7.9
WLAN 5.8G(802.11n20)	7.9	7.9	7.9
WLAN 5.8G(802.11n40)	7.9	/	7.9
WLAN 5.8G(802.11ac80)	/	7.9	/
BT (GFSK)	2	2	2.5
BT (π/4-DQPSK)	1	1	1
BT (8DPSK)	2	2	2
BLE 1M	-3.0	-3.0	-3.0
BLE 2M	-2.5	-2.5	-2.5

Note: The Maximum Target Power for LTE bands corresponds to their maximum power in QPSK modes with maximum bandwidth.

7.4 Test Results:

GSM:

Band	Channel No.	Frequency (MHz)	RF Output Power (dBm)
GSM 850	251	848.8	29.87
	128	824.2	30.03
	190	836.6	**30.11**
PCS 1900	810	1909.8	**26.56**
	512	1850.2	26.45
	661	1880	26.52

GPRS:

Band	Channel No.	Frequency (MHz)	RF Output Power (dBm)			
			1 slot	2 slots	3 slots	4 slots
GSM 850	128	824.2	**30.22**	30.10	28.86	26.86
	190	836.6	30.03	29.98	28.87	26.71
	251	848.8	29.94	29.83	28.63	26.65
PCS 1900	512	1850.2	26.57	26.32	25.54	23.42
	661	1880	**26.58**	26.45	25.39	23.39
	810	1909.8	26.50	26.36	25.62	23.48

For SAR, the time based average power is relevant, the difference in between depends on the duty cycle of the TDMA signal.

Number of Time slot	1	2	3	4
Duty Cycle	1:8	1:4	1:2.66	1:2
Time based Ave. power compared to slotted Ave. power	-9 dB	-6 dB	-4.25 dB	-3 dB
Crest Factor	8	4	2.66	2

The time based average power for GSM

Band	Channel No.	Frequency (MHz)	RF Output Power (dBm)
GSM 850	251	848.8	20.87
	128	824.2	21.03
	190	836.6	**21.11**
PCS 1900	810	1909.8	**17.56**
	512	1850.2	17.45
	661	1880	17.52

The time based average power for GPRS

Band	Channel No.	Frequency (MHz)	RF Output Power (dBm)			
			1 slot	2 slots	3 slots	4 slots
GSM 850	128	824.2	21.22	24.10	24.61	23.86
	190	836.6	21.03	23.98	**24.62**	23.71
	251	848.8	20.94	23.83	24.38	23.65
PCS 1900	512	1850.2	17.57	20.32	21.29	20.42
	661	1880	17.58	20.45	21.14	20.39
	810	1909.8	17.50	20.36	**21.37**	20.48

Note:
1. Rohde & Schwarz Radio Communication Tester (CMW500) was used for the measurement of GSM peak and average output power for active timeslots.
2. For GSM voice, 1 timeslot has been activated with power level 5 (850 MHz band) and 0 (1900 MHz band).
3. For GPRS, 1, 2, 3 and 4 timeslots has been activated separately with power level 3(850 MHz band) and 3(1900 MHz band).

WCDMA:

WCDMA Band 2:

Test Mode	Conducted Average Output Power(dBm)		
	Lowest Channel	Middle Channel	Highest Channel
WCDMA	14.59	**14.61**	14.46
HSDPA Subset 1	14.20	14.17	14.09
HSDPA Subset 2	14.60	14.69	14.57
HSDPA Subset 3	13.58	13.66	13.67
HSDPA Subset 4	14.20	14.17	14.34
HSUPA Subset 1	14.73	14.71	14.71
HSUPA Subset 2	14.67	14.82	14.62
HSUPA Subset 3	14.73	14.78	14.80
HSUPA Subset 4	14.82	14.82	14.78
HSUPA Subset 5	14.70	14.80	14.61
DC-HSDPA Subset 1	14.66	14.71	14.72
DC-HSDPA Subset 2	14.66	14.67	14.70
DC-HSDPA Subset 3	14.73	14.71	14.73
DC-HSDPA Subset 4	14.69	14.83	14.77
HSPA+ Subset 1	14.70	14.68	14.66

WCDMA Band 4:

Test Mode	Conducted Average Output Power(dBm)		
	Lowest Channel	Middle Channel	Highest Channel
WCDMA	14.26	**14.62**	14.24
HSDPA Subset 1	13.55	14.12	13.89
HSDPA Subset 2	14.14	14.74	14.56
HSDPA Subset 3	14.22	14.86	14.51
HSDPA Subset 4	14.12	14.88	14.52
HSUPA Subset 1	14.31	14.95	14.68
HSUPA Subset 2	14.34	14.95	14.81
HSUPA Subset 3	14.26	14.97	14.77
HSUPA Subset 4	14.39	14.99	14.77
HSUPA Subset 5	14.34	14.90	14.70
DC-HSDPA Subset 1	14.15	14.29	14.07
DC-HSDPA Subset 2	14.22	14.41	14.52
DC-HSDPA Subset 3	14.07	14.42	14.39
DC-HSDPA Subset 4	14.07	14.43	14.42
HSPA+ Subset 1	14.30	14.76	14.69

WCDMA Band 5:

Test Mode	Conducted Average Output Power(dBm)		
	Lowest Channel	Middle Channel	Highest Channel
WCDMA	23.31	23.36	**23.47**
HSDPA Subset 1	22.51	21.93	22.13
HSDPA Subset 2	22.52	23.43	23.22
HSDPA Subset 3	22.34	21.97	22.11
HSDPA Subset 4	22.23	21.77	21.99
HSUPA Subset 1	22.39	23.32	23.16
HSUPA Subset 2	23.61	23.32	23.14
HSUPA Subset 3	23.65	23.44	23.13
HSUPA Subset 4	23.55	23.33	23.23
HSUPA Subset 5	23.47	23.39	23.19
DC-HSDPA Subset 1	22.35	21.90	23.24
DC-HSDPA Subset 2	22.60	21.88	23.11
DC-HSDPA Subset 3	22.42	21.91	23.08
DC-HSDPA Subset 4	22.32	21.78	23.04
HSPA+ Subset 1	23.30	23.36	23.35

Note:
1. The default test configuration is to measure SAR with an established radio link between the EUT and a communication test set using a 12.2 kbps RMC (reference measurement Channel) Configured in All 1.
2. KDB 941225 D01-Body SAR is not required for HSDPA/HSUPA/DC-HSDPA/HSPA+ when the maximum average output of each RF channel is less than ¼ dB higher than measured 12.2kbps RMC or the maximum SAR for 12.2kbps RMC is < 75% of SAR limit.

LTE Band 2:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	RB1#0	14.96	15.50	15.09
		RB1#3	15.24	15.67	15.17
		RB1#5	15.18	15.44	15.03
		RB3#0	15.30	15.39	15.23
		RB3#1	15.27	15.38	15.31
		RB3#3	15.29	15.31	15.17
		RB6#0	14.15	14.40	14.20
	16QAM	RB1#0	13.79	14.67	14.05
		RB1#3	14.14	14.76	14.23
		RB1#5	13.99	14.52	13.97
		RB3#0	14.36	14.60	14.39
		RB3#1	14.37	14.80	14.52
		RB3#3	14.37	14.80	14.47
		RB6#0	13.33	13.43	13.52
3M	QPSK	RB1#0	15.14	15.80	15.88
		RB1#8	15.43	15.28	15.24
		RB1#14	15.45	15.06	14.95
		RB8#0	14.27	14.53	14.19
		RB8#4	14.33	14.52	14.21
		RB8#7	14.25	14.48	14.18
		RB15#0	14.23	14.48	14.33
	16QAM	RB1#0	14.43	14.14	14.21
		RB1#8	14.75	14.21	14.28
		RB1#14	14.56	14.02	14.14
		RB8#0	13.40	13.43	13.30
		RB8#4	13.58	13.53	13.41
		RB8#7	13.43	13.47	13.27
		RB15#0	13.28	13.57	13.24
5M	QPSK	RB1#0	14.86	15.61	15.65
		RB1#12	15.47	15.38	15.46
		RB1#24	15.06	14.94	14.76
		RB12#0	14.09	14.43	14.30
		RB12#7	14.42	14.50	14.42
		RB12#13	14.33	14.26	14.22
		RB25#0	14.29	14.42	14.15
	16QAM	RB1#0	14.43	14.20	14.03
		RB1#12	15.06	14.47	14.47
		RB1#24	14.72	13.97	13.94
		RB12#0	13.23	13.54	13.24
		RB12#7	13.65	13.61	13.45
		RB12#13	13.59	13.47	13.38
		RB25#0	13.43	13.46	13.37

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
10M	QPSK	RB1#0	14.97	15.81	11.43
		RB1#25	15.61	15.22	15.39
		RB1#49	15.98	15.54	15.40
		RB25#0	14.10	14.51	14.63
		RB25#12	14.48	14.54	14.38
		RB25#25	14.80	14.65	14.63
		RB50#0	14.36	14.59	14.56
	16QAM	RB1#0	14.18	14.24	14.53
		RB1#25	14.69	14.29	14.37
		RB1#49	15.27	14.49	14.53
		RB25#0	13.27	13.62	13.78
		RB25#12	13.49	13.67	13.83
		RB25#25	13.89	13.80	13.78
		RB50#0	13.57	13.75	13.62
15M	QPSK	RB1#0	15.15	11.71	15.60
		RB1#37	15.57	15.40	15.19
		RB1#74	15.93	15.34	14.93
		RB36#0	14.31	14.68	14.57
		RB36#20	14.44	14.37	14.27
		RB36#39	14.72	14.41	14.29
		RB75#0	14.45	14.47	14.42
	16QAM	RB1#0	14.33	14.87	14.71
		RB1#37	14.77	14.61	14.34
		RB1#74	15.14	14.54	14.02
		RB36#0	13.54	13.67	13.59
		RB36#20	13.54	13.46	13.39
		RB36#39	13.86	13.48	13.24
		RB75#0	13.71	13.60	13.40
20M	QPSK	RB1#0	15.14	14.53	**16.23**
		RB1#49	15.08	15.35	15.40
		RB1#99	15.67	16.08	15.50
		RB50#0	14.47	14.72	14.69
		RB50#24	14.44	14.51	14.61
		RB50#50	14.47	14.71	14.46
		RB100#0	14.41	14.62	14.73
	16QAM	RB1#0	14.28	15.79	16.00
		RB1#49	14.49	14.74	15.06
		RB1#99	14.95	15.39	15.02
		RB50#0	13.47	14.02	13.95
		RB50#24	13.44	13.63	13.61
		RB50#50	13.69	13.77	13.42
		RB100#0	13.49	13.96	13.70

LTE Band 4:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	RB1#0	15.72	16.71	16.13
		RB1#3	15.91	16.46	16.04
		RB1#5	15.79	16.35	15.81
		RB3#0	15.62	16.57	16.20
		RB3#1	15.82	16.70	16.11
		RB3#3	15.74	16.65	15.94
		RB6#0	15.01	15.57	15.10
	16QAM	RB1#0	15.36	15.38	15.01
		RB1#3	15.58	15.39	15.21
		RB1#5	15.48	15.26	14.85
		RB3#0	15.39	15.86	15.45
		RB3#1	15.60	15.86	15.43
		RB3#3	15.40	15.74	15.45
		RB6#0	14.17	14.79	14.50
3M	QPSK	RB1#0	16.35	16.45	16.48
		RB1#8	16.53	16.35	16.17
		RB1#14	16.60	16.38	15.93
		RB8#0	15.62	15.45	15.49
		RB8#4	15.78	15.72	15.27
		RB8#7	15.71	15.56	15.28
		RB15#0	15.55	15.61	15.20
	16QAM	RB1#0	15.85	15.10	15.48
		RB1#8	16.07	15.49	15.33
		RB1#14	16.10	15.35	15.11
		RB8#0	14.87	14.59	14.48
		RB8#4	14.99	14.62	14.50
		RB8#7	14.83	14.70	14.21
		RB15#0	14.84	14.61	14.50
5M	QPSK	RB1#0	15.89	15.96	16.33
		RB1#12	16.40	16.68	16.57
		RB1#24	15.89	16.31	15.61
		RB12#0	15.51	15.39	15.45
		RB12#7	15.78	15.69	15.57
		RB12#13	15.63	15.67	15.28
		RB25#0	15.56	15.45	15.38
	16QAM	RB1#0	15.77	15.10	15.18
		RB1#12	16.37	15.72	15.59
		RB1#24	15.96	15.29	14.89
		RB12#0	14.73	14.55	14.50
		RB12#7	14.95	14.76	14.63
		RB12#13	14.86	14.70	14.22
		RB25#0	14.93	14.54	14.35

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
10M	QPSK	RB1#0	16.13	16.13	16.99
		RB1#25	16.42	16.39	16.38
		RB1#49	16.95	17.02	16.42
		RB25#0	15.61	15.43	15.84
		RB25#12	15.64	15.67	15.67
		RB25#25	16.05	16.02	15.71
		RB50#0	15.88	15.78	15.81
	16QAM	RB1#0	15.76	14.98	15.79
		RB1#25	16.20	15.39	15.54
		RB1#49	16.63	16.11	15.75
		RB25#0	14.73	14.48	14.98
		RB25#12	14.88	14.79	14.81
		RB25#25	15.23	15.03	14.95
		RB50#0	14.93	14.70	14.93
15M	QPSK	RB1#0	16.55	16.35	16.65
		RB1#37	16.62	16.59	16.59
		RB1#74	16.91	17.01	15.85
		RB36#0	15.83	15.51	15.86
		RB36#20	15.94	15.72	15.68
		RB36#39	16.15	16.04	15.52
		RB75#0	15.95	15.74	15.61
	16QAM	RB1#0	16.10	15.54	15.84
		RB1#37	16.23	15.73	15.63
		RB1#74	16.64	16.36	15.12
		RB36#0	15.01	14.50	15.04
		RB36#20	14.93	14.74	14.72
		RB36#39	15.18	14.99	14.40
		RB75#0	15.16	14.71	14.71
20M	QPSK	RB1#0	16.57	16.77	15.51
		RB1#49	16.38	16.41	16.54
		RB1#99	17.31	**17.35**	16.59
		RB50#0	16.08	15.99	16.28
		RB50#24	15.87	15.74	15.80
		RB50#50	16.14	16.13	15.79
		RB100#0	16.08	16.05	15.96
	16QAM	RB1#0	16.46	16.04	17.07
		RB1#49	16.25	15.96	16.33
		RB1#99	17.11	16.85	16.39
		RB50#0	15.04	14.50	15.29
		RB50#24	14.95	14.66	14.97
		RB50#50	15.27	15.20	15.00
		RB100#0	15.21	15.03	14.94

LTE Band 5:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	RB1#0	23.99	23.86	23.85
		RB1#3	23.95	23.92	23.72
		RB1#5	24.17	23.94	23.76
		RB3#0	23.49	23.58	23.31
		RB3#1	23.70	23.47	23.32
		RB3#3	23.62	23.58	23.41
		RB6#0	22.53	22.30	22.32
	16QAM	RB1#0	24.39	23.27	23.93
		RB1#3	**24.40**	23.35	24.10
		RB1#5	24.32	23.33	24.03
		RB3#0	22.56	22.27	22.53
		RB3#1	22.57	22.28	22.49
		RB3#3	22.62	22.23	22.53
		RB6#0	21.06	21.45	21.48
3M	QPSK	RB1#0	24.07	24.00	24.12
		RB1#8	23.97	24.11	24.00
		RB1#14	24.08	23.91	24.04
		RB8#0	22.52	22.41	22.36
		RB8#4	22.54	22.30	22.46
		RB8#7	22.45	22.34	22.37
		RB15#0	22.39	22.65	22.35
	16QAM	RB1#0	23.87	23.16	24.12
		RB1#8	24.30	23.34	23.95
		RB1#14	24.24	23.43	23.83
		RB8#0	21.64	21.36	21.25
		RB8#4	21.73	21.53	21.23
		RB8#7	21.59	21.68	21.23
		RB15#0	21.41	21.25	21.46
5M	QPSK	RB1#0	24.36	19.87	23.96
		RB1#12	24.19	23.96	23.85
		RB1#24	24.05	23.97	23.96
		RB12#0	22.55	22.50	22.45
		RB12#7	22.55	22.52	22.40
		RB12#13	22.38	22.38	22.39
		RB25#0	22.38	22.47	22.43
	16QAM	RB1#0	23.52	23.73	23.10
		RB1#12	23.39	23.76	22.99
		RB1#24	23.41	23.80	22.97
		RB12#0	21.33	21.45	21.29
		RB12#7	21.38	21.61	21.36
		RB12#13	21.35	21.39	21.33
		RB25#0	21.48	21.70	21.51

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
10M	QPSK	RB1#0	24.30	24.16	24.12
		RB1#25	24.03	24.11	24.14
		RB1#49	23.99	24.02	24.27
		RB25#0	22.30	22.43	22.44
		RB25#12	22.45	22.53	22.39
		RB25#25	22.23	22.53	22.41
		RB50#0	22.47	22.43	22.61
	16QAM	RB1#0	23.76	23.44	24.15
		RB1#25	23.52	23.44	23.98
		RB1#49	23.43	23.36	24.07
		RB25#0	21.53	21.68	21.43
		RB25#12	21.63	21.80	21.41
		RB25#25	21.34	21.66	21.40
		RB50#0	21.46	21.62	21.44

LTE Band 7:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5M	QPSK	RB1#0	13.63	12.16	14.98
		RB1#12	14.45	14.66	14.29
		RB1#24	13.87	14.14	13.60
		RB12#0	13.19	13.62	13.46
		RB12#7	13.46	13.92	13.58
		RB12#13	13.37	13.76	13.29
		RB25#0	13.27	13.82	13.33
	16QAM	RB1#0	13.34	13.31	13.23
		RB1#12	13.93	13.98	13.71
		RB1#24	13.58	13.51	12.88
		RB12#0	12.20	12.81	12.56
		RB12#7	12.47	12.97	12.70
		RB12#13	12.36	12.90	12.36
		RB25#0	12.22	12.82	12.37
10M	QPSK	RB1#0	13.62	10.92	15.66
		RB1#25	14.25	14.55	14.34
		RB1#49	14.41	14.71	14.47
		RB25#0	12.84	13.76	13.84
		RB25#12	13.05	13.85	13.84
		RB25#25	13.37	14.11	13.84
		RB50#0	13.17	14.04	13.83
	16QAM	RB1#0	12.94	13.42	13.79
		RB1#25	13.56	13.73	13.70
		RB1#49	13.76	13.94	13.76
		RB25#0	11.91	13.03	13.03
		RB25#12	12.23	13.01	13.09
		RB25#25	12.45	13.38	13.04
		RB50#0	12.18	13.10	12.91
15M	QPSK	RB1#0	13.39	11.92	14.54
		RB1#37	14.23	14.61	14.14
		RB1#74	14.12	14.86	13.42
		RB36#0	13.02	13.82	13.61
		RB36#20	13.17	13.84	13.36
		RB36#39	13.29	14.09	13.23
		RB75#0	13.13	14.02	13.44
	16QAM	RB1#0	13.06	13.90	13.69
		RB1#37	13.43	14.04	13.30
		RB1#74	13.50	14.24	12.73
		RB36#0	12.06	12.89	12.85
		RB36#20	12.17	12.92	12.39
		RB36#39	12.26	13.04	12.24
		RB75#0	12.15	13.05	12.42

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
20M	QPSK	RB1#0	14.00	15.04	13.27
		RB1#49	13.96	14.52	14.26
		RB1#99	14.28	**15.82**	13.83
		RB50#0	13.23	14.13	14.00
		RB50#24	13.05	14.01	13.76
		RB50#50	13.28	14.39	13.44
		RB100#0	13.23	14.20	13.72
	16QAM	RB1#0	13.37	14.66	15.09
		RB1#49	13.38	14.12	14.13
		RB1#99	13.47	14.78	13.83
		RB50#0	12.28	13.20	13.10
		RB50#24	12.25	12.98	12.78
		RB50#50	12.24	13.22	12.46
		RB100#0	12.20	13.31	12.71

LTE Band 12:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	RB1#0	24.41	24.31	24.22
		RB1#3	24.36	24.47	23.88
		RB1#5	24.38	24.40	23.94
		RB3#0	23.82	23.75	23.53
		RB3#1	23.67	23.65	23.64
		RB3#3	23.76	23.74	23.63
		RB6#0	22.67	22.60	22.53
	16QAM	RB1#0	23.41	23.41	23.77
		RB1#3	23.45	23.28	23.76
		RB1#5	23.51	23.33	23.81
		RB3#0	22.75	23.15	22.71
		RB3#1	22.61	23.03	22.51
		RB3#3	22.74	22.95	22.66
		RB6#0	21.50	21.83	21.49
3M	QPSK	RB1#0	24.27	24.38	24.12
		RB1#8	24.38	24.41	24.25
		RB1#14	24.20	**24.51**	24.27
		RB8#0	22.81	22.80	22.55
		RB8#4	22.72	22.77	22.52
		RB8#7	22.65	22.75	22.61
		RB15#0	22.84	22.81	22.56
	16QAM	RB1#0	24.06	23.44	23.73
		RB1#8	23.38	23.41	23.62
		RB1#14	23.33	23.35	23.78
		RB8#0	21.88	21.74	21.37
		RB8#4	21.82	21.64	21.46
		RB8#7	21.63	21.73	21.32
		RB15#0	21.74	21.49	21.53
5M	QPSK	RB1#0	24.45	24.15	17.18
		RB1#12	24.40	24.29	24.08
		RB1#24	24.30	24.22	24.13
		RB12#0	22.66	22.76	22.61
		RB12#7	22.67	22.67	22.57
		RB12#13	22.66	22.58	22.75
		RB25#0	22.68	22.81	22.53
	16QAM	RB1#0	23.30	23.33	22.58
		RB1#12	23.21	23.37	22.73
		RB1#24	23.08	23.20	22.66
		RB12#0	21.62	21.61	21.46
		RB12#7	21.69	21.61	21.57
		RB12#13	21.64	21.62	21.59
		RB25#0	21.72	21.85	21.67

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
10M	QPSK	RB1#0	24.44	24.12	24.29
		RB1#25	24.40	24.39	24.36
		RB1#49	24.45	24.22	24.24
		RB25#0	22.68	22.70	22.65
		RB25#12	22.54	22.75	22.75
		RB25#25	22.73	22.70	22.75
		RB50#0	22.63	22.65	22.78
	16QAM	RB1#0	23.30	23.14	23.68
		RB1#25	23.34	23.40	23.70
		RB1#49	23.44	23.08	23.76
		RB25#0	21.73	21.87	21.66
		RB25#12	21.61	21.79	21.42
		RB25#25	21.95	21.79	21.58
		RB50#0	21.64	21.71	21.58

LTE Band 13:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5M	QPSK	RB1#0	23.55	/	20.31
		RB1#12	23.47	/	23.13
		RB1#24	23.40	/	23.00
		RB12#0	22.71	/	22.77
		RB12#7	22.78	/	22.82
		RB12#13	22.96	/	22.76
		RB25#0	21.83	/	21.81
	16QAM	RB1#0	22.13	/	22.03
		RB1#12	22.18	/	22.04
		RB1#24	22.21	/	21.79
		RB12#0	21.80	/	21.75
		RB12#7	21.74	/	21.71
		RB12#13	21.77	/	21.74
		RB25#0	21.97	/	21.87
10M	QPSK	RB1#0	/	23.45	/
		RB1#25	/	**23.68**	/
		RB1#49	/	23.43	/
		RB25#0	/	22.74	/
		RB25#12	/	23.07	/
		RB25#25	/	22.86	/
		RB50#0	/	22.87	/
	16QAM	RB1#0	/	22.42	/
		RB1#25	/	22.64	/
		RB1#49	/	22.29	/
		RB25#0	/	21.94	/
		RB25#12	/	21.90	/
		RB25#25	/	22.00	/
		RB50#0	/	22.01	/

LTE Band 17:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5M	QPSK	RB1#0	23.89	24.36	21.17
		RB1#12	23.75	24.19	24.14
		RB1#24	**24.48**	24.03	24.23
		RB12#0	22.67	22.67	22.40
		RB12#7	22.64	22.62	22.62
		RB12#13	22.57	22.49	22.47
		RB25#0	22.72	22.77	22.65
	16QAM	RB1#0	23.16	23.49	22.60
		RB1#12	23.11	23.27	22.67
		RB1#24	23.21	23.11	22.87
		RB12#0	21.82	21.64	21.50
		RB12#7	21.58	21.54	21.46
		RB12#13	21.81	21.42	21.53
		RB25#0	21.86	21.70	21.68
10M	QPSK	RB1#0	24.33	24.35	23.99
		RB1#25	24.34	24.26	24.38
		RB1#49	24.34	24.47	24.20
		RB25#0	22.74	22.78	22.72
		RB25#12	22.60	22.58	22.80
		RB25#25	22.49	22.51	22.59
		RB50#0	22.82	22.55	22.74
	16QAM	RB1#0	23.39	23.35	23.73
		RB1#25	23.44	23.31	23.65
		RB1#49	23.32	23.19	23.71
		RB25#0	21.71	21.97	21.80
		RB25#12	21.73	21.66	21.54
		RB25#25	21.70	21.67	21.60
		RB50#0	21.77	21.56	21.66

LTE Band 38:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5M	QPSK	RB1#0	17.12	16.59	17.73
		RB1#12	17.6	16.96	17.62
		RB1#24	17.05	16.53	17.01
		RB12#0	16.93	16.85	17.01
		RB12#7	17.26	16.91	17.02
		RB12#13	17.13	16.77	16.91
		RB25#0	17.11	16.72	17.05
	16QAM	RB1#0	16.97	16.94	16.9
		RB1#12	17.6	17.54	17.35
		RB1#24	17.08	17.04	16.74
		RB12#0	15.98	16.3	16.17
		RB12#7	16.39	15.99	16
		RB12#13	16.35	16.25	16.25
		RB25#0	16.43	15.74	15.99
10M	QPSK	RB1#0	17.1	15.72	17.71
		RB1#25	17.22	16.83	17.74
		RB1#49	17.7	17.22	17.71
		RB25#0	17.08	17.08	17.69
		RB25#12	17.18	17.06	17.84
		RB25#25	17.4	17.21	18.09
		RB50#0	17.41	17.14	17.86
	16QAM	RB1#0	17.49	17.33	17.71
		RB1#25	17.6	17.2	18.16
		RB1#49	18.08	17.71	18.13
		RB25#0	16.1	16.36	16.78
		RB25#12	16.28	16.35	16.93
		RB25#25	16.47	16.23	17.2
		RB50#0	16.23	16.66	16.96
15M	QPSK	RB1#0	18.41	17.54	17.56
		RB1#37	18.52	16.93	17.03
		RB1#74	18.35	17.11	16
		RB36#0	17.74	18	18.31
		RB36#20	17.76	17.72	18.13
		RB36#39	17.87	17.85	18.13
		RB75#0	17.79	17.83	18.17
	16QAM	RB1#0	18.14	18.56	18.42
		RB1#37	18.15	18.17	18.08
		RB1#74	18.18	18.15	18
		RB36#0	16.64	17.02	17.35
		RB36#20	16.61	16.71	17.11
		RB36#39	16.81	16.75	17.18
		RB75#0	16.79	16.93	17.15

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
20M	QPSK	RB1#0	19.13	**19.25**	17.11
		RB1#49	18.62	18.44	16.05
		RB1#99	18.79	19.17	16.41
		RB50#0	18.1	18.4	18.54
		RB50#24	17.87	17.95	18.06
		RB50#50	18.03	18.07	18.15
		RB100#0	18.02	18.17	18.27
	16QAM	RB1#0	18.27	19.01	19.04
		RB1#49	18.18	17.96	18.25
		RB1#99	18.09	18.38	18.72
		RB50#0	17.14	17.34	17.32
		RB50#24	16.91	16.97	16.92
		RB50#50	16.79	16.86	16.96
		RB100#0	16.98	17.23	17.3

LTE Band 41:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	2549.5 MHz	Middle Channel (dBm)	2636.5 MHz	High Channel (dBm)
5M	QPSK	RB1#0	19.62	17.67	17.65	18.47	18.35
		RB1#12	**19.83**	17.03	16.88	18.98	18.89
		RB1#24	19.43	16.41	16.36	18.24	18.14
		RB12#0	16.84	17.2	17.1	17.2	17.13
		RB12#7	16.97	17.23	17.24	17.43	17.35
		RB12#13	16.85	17.24	17.13	17.12	17
		RB25#0	16.9	17.19	17.22	17.06	17.1
	16QAM	RB1#0	16.62	16.8	16.82	16.96	16.96
		RB1#12	17.32	17.42	17.32	17.38	17.31
		RB1#24	16.76	16.71	16.71	16.78	16.63
		RB12#0	16.18	16.38	16.24	16.13	16
		RB12#7	16.47	16.32	16.22	16.16	16.04
		RB12#13	16.19	16.07	16.07	15.93	15.89
		RB25#0	16.13	16.26	16.13	16.06	16.06
10M	QPSK	RB1#0	19.34	17.25	17.15	17.16	17.08
		RB1#25	19.29	16.7	16.59	17.93	17.93
		RB1#49	19.81	16.96	16.99	17.9	17.93
		RB25#0	17.28	17.5	17.41	16.86	16.88
		RB25#12	17.26	17.51	17.37	17.04	16.92
		RB25#25	17.41	17.74	17.63	16.96	17
		RB50#0	17.19	17.51	17.53	17.1	17.11
	16QAM	RB1#0	16.95	17.07	17.02	16.83	16.86
		RB1#25	17.11	17.1	17.11	16.99	17.01
		RB1#49	17.47	17.38	17.38	17.07	17.01
		RB25#0	16.37	16.42	16.41	15.92	15.97
		RB25#12	16.35	16.38	16.32	16.02	16
		RB25#25	16.54	16.25	16.27	16.04	16.02
		RB50#0	16.41	16.27	16.2	16.16	16.1
15M	QPSK	RB1#0	18.65	16.87	16.75	16.17	16.2
		RB1#37	18.78	16.58	16.43	15.85	15.9
		RB1#74	18.92	16.23	16.12	15.71	15.64
		RB36#0	17.19	17.51	17.49	17.38	17.23
		RB36#20	17.12	17.36	17.39	17.09	17.13
		RB36#39	17.3	17.42	17.37	16.99	16.91
		RB75#0	17.31	17.49	17.38	17.16	17.11
	16QAM	RB1#0	17.05	17.39	17.29	17.34	17.34
		RB1#37	17.24	17.1	17.01	17.11	17.13
		RB1#74	17.36	16.96	16.96	16.89	16.83
		RB36#0	16.36	16.47	16.41	16.22	16.19
		RB36#20	16.36	16.3	16.26	15.99	15.94
		RB36#39	16.43	16.32	16.25	15.88	15.86
		RB75#0	16.48	16.21	16.17	16.03	16.01

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	2549.5 MHz	Middle Channel (dBm)	2636.5 MHz	High Channel (dBm)
20M	QPSK	RB1#0	18.75	17.88	19.76	16.42	16.37
		RB1#49	18.49	17.93	19.28	17.86	17.8
		RB1#99	19.26	17.82	19.29	17.87	17.76
		RB50#0	17.38	18.39	18.31	18.35	18.28
		RB50#24	17.3	18.09	17.95	17.9	17.82
		RB50#50	17.49	18.16	18.06	17.75	17.79
		RB100#0	17.3	18.08	18.01	17.35	17.31
	16QAM	RB1#0	17.27	18.71	18.73	18.76	18.66
		RB1#49	17.07	18.17	18.2	17.84	17.87
		RB1#99	17.71	18.32	18.24	17.88	17.85
		RB50#0	16.45	17.17	17.12	17.18	17.08
		RB50#24	16.33	16.95	16.87	16.78	16.76
		RB50#50	16.82	17	16.93	16.65	16.56
		RB100#0	16.62	16.96	16.91	16.8	16.84

LTE Band 66:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	RB1#0	16.11	16.22	15.74
		RB1#3	16.43	16.49	16.14
		RB1#5	16.11	16.21	15.90
		RB3#0	16.28	16.32	15.81
		RB3#1	16.29	16.39	16.02
		RB3#3	16.37	16.38	15.92
		RB6#0	15.28	15.26	15.02
	16QAM	RB1#0	15.50	15.49	15.11
		RB1#3	15.76	15.55	15.47
		RB1#5	15.60	15.36	15.26
		RB3#0	15.41	15.54	15.23
		RB3#1	15.41	15.66	15.21
		RB3#3	15.37	15.46	15.14
		RB6#0	14.21	14.27	14.05
3M	QPSK	RB1#0	16.34	16.32	15.51
		RB1#8	16.51	16.42	15.73
		RB1#14	16.40	16.29	15.73
		RB8#0	15.42	15.63	14.81
		RB8#4	15.54	15.59	15.12
		RB8#7	15.55	15.46	15.01
		RB15#0	15.48	15.55	14.97
	16QAM	RB1#0	15.52	15.79	14.86
		RB1#8	15.77	15.85	15.19
		RB1#14	15.72	15.76	15.14
		RB8#0	14.53	14.53	13.88
		RB8#4	14.63	14.53	14.07
		RB8#7	14.48	14.40	14.08
		RB15#0	14.57	14.42	13.95
5M	QPSK	RB1#0	15.96	16.12	14.95
		RB1#12	16.76	16.60	15.76
		RB1#24	16.10	16.02	15.58
		RB12#0	15.37	15.47	14.42
		RB12#7	15.52	15.61	14.84
		RB12#13	15.47	15.37	14.85
		RB25#0	15.48	15.46	14.81
	16QAM	RB1#0	15.34	15.66	14.45
		RB1#12	15.93	15.97	15.40
		RB1#24	15.41	15.44	15.08
		RB12#0	14.40	14.51	13.53
		RB12#7	14.63	14.65	13.74
		RB12#13	14.44	14.32	13.89
		RB25#0	14.62	14.23	13.57

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
10M	QPSK	RB1#0	15.91	16.29	10.18
		RB1#25	16.13	16.52	14.95
		RB1#49	16.78	16.53	16.14
		RB25#0	15.15	15.58	14.08
		RB25#12	15.38	15.55	14.40
		RB25#25	15.67	15.69	15.00
		RB50#0	15.35	15.63	14.62
	16QAM	RB1#0	15.18	15.77	13.68
		RB1#25	15.59	15.79	14.50
		RB1#49	16.21	15.95	15.52
		RB25#0	14.25	14.40	12.80
		RB25#12	14.17	14.52	13.29
		RB25#25	14.53	14.67	13.92
		RB50#0	14.36	14.46	13.43
15M	QPSK	RB1#0	16.34	16.48	11.05
		RB1#37	16.36	16.48	15.36
		RB1#74	16.83	16.13	16.54
		RB36#0	15.33	15.76	14.64
		RB36#20	15.43	15.60	14.89
		RB36#39	15.70	15.52	15.59
		RB75#0	15.56	15.65	15.12
	16QAM	RB1#0	15.51	16.04	14.75
		RB1#37	15.75	15.89	14.97
		RB1#74	16.11	15.74	16.07
		RB36#0	14.20	14.59	13.49
		RB36#20	14.36	14.66	13.71
		RB36#39	14.64	14.55	14.43
		RB75#0	14.52	14.54	13.86
20M	QPSK	RB1#0	16.60	16.08	15.92
		RB1#49	16.25	16.65	15.53
		RB1#99	**17.27**	16.56	17.24
		RB50#0	15.47	16.01	14.92
		RB50#24	15.45	15.75	14.64
		RB50#50	15.81	15.60	15.45
		RB100#0	15.72	15.74	15.24
	16QAM	RB1#0	16.04	16.27	15.63
		RB1#49	15.76	15.78	14.79
		RB1#99	16.73	15.90	16.65
		RB50#0	14.40	14.82	13.78
		RB50#24	14.46	14.60	13.61
		RB50#50	14.72	14.51	14.35
		RB100#0	14.60	14.79	13.95

WLAN: 2.4G

Mode	Channel frequency (MHz)	Data Rate	Duty cycle (%)	Average Output Power (dBm)
802.11b	2412	1M	98.15	15.94
	2437			15.72
	2462			**16.73**
802.11g	2412	6M	/	11.46
	2437			11.06
	2462			12.75
802.11n20	2412	MCS0	/	13.63
	2437			13.03
	2462			14.46

Test Modes	Ton (ms)	Ton+off (ms)	Duty cycle (%)	Scaled Factor (1/duty cycle)
802.11b_2437MHz	8.376	8.534	98.15	1.02

Duty Cycle	
802.11b_2437MHz	

Note: The duty cycle was measured under radiation method.

WLAN: 5.2G

Mode	Channel frequency (MHz)	Data Rate	Average Output Power (dBm)
802.11a	5180	6Mbps	7.66
	5200		7.36
	5240		**8.01**
802.11n20	5180	MCS0	7.67
	5200		7.33
	5240		7.53
802.11n40	5190	MCS0	7.68
	5230		7.94
802.11ac80	5210	MCS0	7.40

Note:
1.The system support 802.11a/n20/n40/ac20/ac40/ac80, the ac20 and ac40 were reduced since the identical parameters with 802.11n20 and n40.

WLAN: 5.3G

Mode	Channel frequency (MHz)	Data Rate	Average Output Power (dBm)
802.11a	5260	6Mbps	7.97
	5280		**8.07**
	5320		8.04
802.11n20	5260	MCS0	7.98
	5280		7.49
	5320		7.15
802.11n40	5270	MCS0	8.01
	5310		7.92
802.11ac80	5290	MCS0	8.02

Note:
1.The system support 802.11a/n20/n40/ac20/ac40/ac80, the ac20 and ac40 were reduced since the identical parameters with 802.11n20 and n40.

WLAN: 5.6G

Mode	Channel frequency (MHz)	Data Rate	Average Output Power (dBm)
802.11a	5500	6Mbps	7.08
	5580		7.82
	5700		**7.87**
802.11n20	5500	MCS0	7.24
	5580		7.85
	5700		6.62
802.11n40	5510	MCS0	7.70
	5590		7.17
	5670		7.51
802.11ac80	5530	MCS0	6.85
	5610		7.39
	5690		7.22

Note:
1.The system support 802.11a/n20/n40/ac20/ac40/ac80, the ac20 and ac40 were reduced since the identical parameters with 802.11n20 and n40.

WLAN: 5.8G

Mode	Channel frequency (MHz)	Data Rate	Average Output Power (dBm)
802.11a	5745	6Mbps	7.50
	5785		7.24
	5825		7.04
802.11n20	5745	MCS0	7.27
	5785		7.09
	5825		7.05
802.11n40	5755	MCS0	7.54
	5795		7.22
802.11ac80	5775	MCS0	**7.89**

Note:
1.The system support 802.11a/n20/n40/ac20/ac40/ac80, the ac20 and ac40 were reduced since the identical parameters with 802.11n20 and n40.

Bluetooth:

Mode	Channel frequency (MHz)	RF Output Power (dBm)
GFSK	2402	1.03
	2441	0.28
	2480	1.32
	2474	**1.95**
π/4-DQPSK	2402	0.42
	2441	-0.37
	2480	0.46
	2469	0.85
8DPSK	2402	0.92
	2441	0.11
	2480	0.83
	2470	1.33
BLE 1M	2402	-3.37
	2440	-3.90
	2480	-3.60
BLE 2M	2404	-3.25
	2440	-3.36
	2478	-3.17

8. STANDALONE SAR TEST EXCLUSION CONSIDERATIONS

8.1 Antennas Location:



Antenna	Supported Bands
WWAN ANT0	GSM850, PCS1900,WCDMA B2/4/5, LTE B2/4/5/7/12/13/17/38/41/66
WWAN ANT1	GSM850, PCS1900,WCDMA B2/4/5, LTE B2/4/5/7/12/13/17/38/41/66
ANT12	WLAN 2.4G + WLAN 5G + Bluetooth/BLE

8.2 Antenna Distance To Edge

Antenna Distance To Edge(mm)						
Antenna	**Back**	**Front**	**Left**	**Right**	**Top**	**Bottom**
WWAN ANT0	< 5	< 5	< 5	< 5	158	< 5
WWAN ANT1	< 5	< 5	< 5	40	< 5	147
WLAN/BT Antenna	< 5	< 5	62	< 5	< 5	150

8.3 Standalone SAR test exclusion considerations

Mode	Frequency (MHz)	Output Power (dBm)	Output Power (mW)	Distance (mm)	Calculated value	Threshold (1-g)	SAR Test Exclusion
WLAN 2.4G	2462	17	50.12	0	15.7	3	NO
WLAN 5.2G	5240	8.1	6.46	0	3.0	3	YES
WLAN 5.3G	5230	8.1	6.46	0	3.0	3	YES
WLAN 5.6G	5700	7.9	6.17	0	3.0	3	YES
WLAN 5.8G	5825	7.9	6.17	0	3.0	3	YES
Bluetooth	2480	2.5	1.78	0	0.6	3	YES

Note: The WLAN based average power for calculation. and bluetooth based peak output power for calculation.

NOTE:
The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] ·
[√f(GHz)] ≤ 3.0 for 1-g SAR and ≤7.5 for 10-g extremity SAR, where
1. f(GHz) is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

8.4 Standalone SAR estimation:

Mode	Frequency (MHz)	Output Power (dBm)	Output Power (mW)	Distance (mm)	Estimated 1-g (W/kg)
WLAN 5.2G Head	5240	8.1	6.46	0	0.39
WLAN 5.2G Body	5240	8.1	6.46	10	0.2
WLAN 5.3G Head	5320	8.1	6.46	0	0.4
WLAN 5.3G Body	5320	8.1	6.46	10	0.2
WLAN 5.6G Head	5700	7.9	6.17	0	0.39
WLAN 5.6G Body	5700	7.9	6.17	10	0.2
WLAN 5.8G Head	5825	7.9	6.17	0	0.4
WLAN 5.8G Body	5825	7.9	6.17	10	0.2
BT Head	2480	2.5	1.78	0	0.08
BT Body	2480	2.5	1.78	10	0.04

Note: The bluetooth based peak power for calculation.

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:
[(max. power of channel, including tune-up tolerance , mW)/(min. test separation distance,mm)] ·
[√f(GHz)/x]
W/kg for test separation distances ≤50 mm;
where x = 7.5 for 1-g SAR.
When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion

8.5 SAR test exclusion for the EUT edge considerations Result

Mode	Back	Front	Left	Right	Top	Bottom
BT/WLAN 5G	Exclusion*	Exclusion*	Exclusion*	Exclusion*	Exclusion*	Exclusion*
WLAN 2.4G	**Required**	**Required**	Exclusion	**Required**	**Required**	Exclusion
WWAN ANT0	**Required**	**Required**	**Required**	**Required**	Exclusion	**Required**
WWAN ANT1	**Required**	**Required**	**Required**	Exclusion	**Required**	Exclusion

Note:

Required: The distance to Edge is less than 25mm, testing is required.
Exclusion*: SAR test exclusion evaluation has been done above.
Exclusion: The distance to Edge is more than 25 mm, testing is not required.

Extremity Exposure Considerations

Per KDB 648474 D04 D04v01r03, this device is considered a "Phablet" since the diagonal dimension is >160mm and < 200mm, when hotspot mode applies, extremity SAR is required only for the surfaces and edges with hotspot mode scaled to the maximum output power (with tolerance is 1g SAR > 1.2W/kg)

Extremity Exposure Condition		
Worst Mode	**Hotspot SAR value**	**Extremity Condition Test**
LTE Band 7	1.12W/kg	Exclusion

9. SAR MEASUREMENT RESULTS

This page summarizes the results of the performed dosimetric evaluation.

9.1 SAR Test Data

Environmental Conditions

Temperature:	22.5-23.4 ℃	22.1-22.6℃	21.2-21.8 ℃	21.4-22 ℃	21.7-22.5 ℃
Relative Humidity:	40%	31%	39%	36%	37%
ATM Pressure:	101.3 kPa	101.6 kPa	101.5 kPa	101.4 kPa	101.4 kPa
Test Date:	2025/03/29	2025/03/30	2025/03/31	2025/04/01	2025/04/02

Testing was performed by Lily Yang, Musk Huang, Led Lu.

Temperature:	22.2-22.8 ℃	22.1-22.6℃	21.8-22.6 ℃	21.5-22.4 ℃	21.7-22.3 ℃
Relative Humidity:	32%	36%	39%	35%	35%
ATM Pressure:	101.4 kPa	101 kPa	101.1 kPa	101.5 kPa	101.1 kPa
Test Date:	2025/04/03	2025/04/04	2025/04/05	2025/04/06	2025/04/07

Testing was performed by Lily Yang, Musk Huang, Led Lu.

Temperature:	22.2-22.8 ℃	22.8-23.6℃	/	/	/
Relative Humidity:	33%	35%	/	/	/
ATM Pressure:	101 kPa	100.8 kPa	/	/	/
Test Date:	2025/04/08	2025/04/09	/	/	/

Testing was performed by Lily Yang, Musk Huang, Led Lu.

GSM 850 (ANT0):

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
					Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	824.2	GPRS	/	/	/	/	/	/
	836.6	GPRS	28.87	29.0	1.030	0.113	**0.12**	1#
	848.8	GPRS	/	/	/	/	/	/
Head Left Tilt	824.2	GPRS	/	/	/	/	/	/
	836.6	GPRS	28.87	29.0	1.030	0.079	0.08	/
	848.8	GPRS	/	/	/	/	/	/
Head Right Cheek	824.2	GPRS	/	/	/	/	/	/
	836.6	GPRS	28.87	29.0	1.030	0.083	0.09	/
	848.8	GPRS	/	/	/	/	/	/
Head Right Tilt	824.2	GPRS	/	/	/	/	/	/
	836.6	GPRS	28.87	29.0	1.030	0.033	0.04	/
	848.8	GPRS	/	/	/	/	/	/
Body Front (10mm)	824.2	GPRS	/	/	/	/	/	/
	836.6	GPRS	28.87	29.0	1.030	0.212	**0.22**	2#
	848.8	GPRS	/	/	/	/	/	/
Body Back (10mm)	824.2	GPRS	/	/	/	/	/	/
	836.6	GPRS	28.87	29.0	1.030	0.172	0.18	/
	848.8	GPRS	/	/	/	/	/	/
Body Left (10mm)	824.2	GPRS	/	/	/	/	/	/
	836.6	GPRS	28.87	29.0	1.030	0.037	0.04	/
	848.8	GPRS	/	/	/	/	/	/
Body Right (10mm)	824.2	GPRS	/	/	/	/	/	/
	836.6	GPRS	28.87	29.0	1.030	0.105	0.11	/
	848.8	GPRS	/	/	/	/	/	/
Body Bottom (10mm)	824.2	GPRS	/	/	/	/	/	/
	836.6	GPRS	28.87	29.0	1.030	0.111	0.12	/
	848.8	GPRS	/	/	/	/	/	/

Note: The test data above was performed on 2025/04/01.

Note:
1. When the 1-g SAR is ≤ 0.8W/Kg, testing for other channels are optional.
2. The EUT transmit and receive through the same GSM antenna while testing SAR.
3. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
4. When the maximum output power variation across the required test channels is > 0.5 dB, instead of the middle channel, the highest output power channel must be used.
5. The Multi-slot Classes of EUT is Class 12 which has maximum 4 Downlink slots and 4 Uplink slots, the maximum active slots is 5, when perform the multiple slots scan, 2DL+3UL is the worst case.
6. The max. time based average power of GSM/GPRS mode was selected to Head/Body SAR testing.

GSM 850 (ANT1):

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
					Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	824.2	GPRS	28.86	29.0	1.033	0.900	0.93	/
	836.6	GPRS	28.87	29.0	1.030	0.998	**1.03**	3#
	848.8	GPRS	28.63	29.0	1.089	0.887	0.97	/
Head Left Tilt	824.2	GPRS	28.86	29.0	1.033	0.824	0.85	/
	836.6	GPRS	28.87	29.0	1.030	0.899	0.93	/
	848.8	GPRS	28.63	29.0	1.089	0.805	0.88	/
Head Right Cheek	824.2	GPRS	28.86	29.0	1.033	0.827	0.85	/
	836.6	GPRS	28.87	29.0	1.030	0.907	0.93	/
	848.8	GPRS	28.63	29.0	1.089	0.802	0.87	/
Head Right Tilt	824.2	GPRS	28.86	29.0	1.033	0.917	0.95	/
	836.6	GPRS	28.87	29.0	1.030	0.947	0.98	/
	848.8	GPRS	28.63	29.0	1.089	0.804	0.88	/
Body Front (10mm)	824.2	GPRS	/	/	/	/	/	/
	836.6	GPRS	28.87	29.0	1.030	0.648	0.67	/
	848.8	GPRS	/	/	/	/	/	/
Body Back (10mm)	824.2	GPRS	/	/	/	/	/	/
	836.6	GPRS	28.87	29.0	1.030	0.585	0.60	/
	848.8	GPRS	/	/	/	/	/	/
Body Left (10mm)	824.2	GPRS	/	/	/	/	/	/
	836.6	GPRS	28.87	29.0	1.030	0.311	0.32	/
	848.8	GPRS	/	/	/	/	/	/
Body Top (10mm)	824.2	GPRS	/	/	/	/	/	/
	836.6	GPRS	28.87	29.0	1.030	0.660	**0.68**	4#
	848.8	GPRS	/	/	/	/	/	/

Note: The test data above was performed on 2025/04/01.

Note:
1. When the 1-g SAR is ≤ 0.8W/Kg, testing for other channels are optional.
2. The EUT transmit and receive through the same GSM antenna while testing SAR.
3. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
4. When the maximum output power variation across the required test channels is > 0.5 dB, instead of the middle channel, the highest output power channel must be used.
5. The Multi-slot Classes of EUT is Class 12 which has maximum 4 Downlink slots and 4 Uplink slots, the maximum active slots is 5, when perform the multiple slots scan, 2DL+3UL is the worst case.
6. The max. time based average power of GSM/GPRS mode was selected to Head/Body SAR testing.

PCS 1900 (ANT0):

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
					Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	1850.2	GPRS	/	/	/	/	/	/
	1880	GPRS	25.39	26.0	1.151	0.086	**0.10**	5#
	1909.8	GPRS	/	/	/	/	/	/
Head Left Tilt	1850.2	GPRS	/	/	/	/	/	/
	1880	GPRS	25.39	26.0	1.151	0.053	0.06	/
	1909.8	GPRS	/	/	/	/	/	/
Head Right Cheek	1850.2	GPRS	/	/	/	/	/	/
	1880	GPRS	25.39	26.0	1.151	0.066	0.08	/
	1909.8	GPRS	/	/	/	/	/	/
Head Right Tilt	1850.2	GPRS	/	/	/	/	/	/
	1880	GPRS	25.39	26.0	1.151	0.051	0.06	/
	1909.8	GPRS	/	/	/	/	/	/
Body Front (10mm)	1850.2	GPRS	/	/	/	/	/	/
	1880	GPRS	25.39	26.0	1.151	0.071	0.08	/
	1909.8	GPRS	/	/	/	/	/	/
Body Back (10mm)	1850.2	GPRS	/	/	/	/	/	/
	1880	GPRS	25.39	26.0	1.151	0.338	**0.39**	6#
	1909.8	GPRS	/	/	/	/	/	/
Body Left (10mm)	1850.2	GPRS	/	/	/	/	/	/
	1880	GPRS	25.39	26.0	1.151	0.053	0.06	/
	1909.8	GPRS	/	/	/	/	/	/
Body Right (10mm)	1850.2	GPRS	/	/	/	/	/	/
	1880	GPRS	25.39	26.0	1.151	0.033	0.04	/
	1909.8	GPRS	/	/	/	/	/	/
Body Bottom (10mm)	1850.2	GPRS	/	/	/	/	/	/
	1880	GPRS	25.39	26.0	1.151	0.196	0.23	/
	1909.8	GPRS	/	/	/	/	/	/

Note: The test data above was performed on 2025/04/04.

Note:
1. When the 1-g SAR is ≤ 0.8W/Kg, testing for other channels are optional.
2. The EUT transmit and receive through the same GSM antenna while testing SAR.
3. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
4. When the maximum output power variation across the required test channels is > 0.5 dB, instead of the middle channel, the highest output power channel must be used.
5. The Multi-slot Classes of EUT is Class 12 which has maximum 4 Downlink slots and 4 Uplink slots, the maximum active slots is 5, when perform the multiple slots scan, 2DL+3UL is the worst case.
6. The max. time based average power of GSM/GPRS mode was selected to Head/Body SAR testing.

PCS 1900 (ANT1):

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
					Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	1850.2	GPRS	/	/	/	/	/	/
	1880	GPRS	25.39	26.0	1.151	0.294	0.34	/
	1909.8	GPRS	/	/	/	/	/	/
Head Left Tilt	1850.2	GPRS	/	/	/	/	/	/
	1880	GPRS	25.39	26.0	1.151	0.377	0.43	/
	1909.8	GPRS	/	/	/	/	/	/
Head Right Cheek	1850.2	GPRS	/	/	/	/	/	/
	1880	GPRS	25.39	26.0	1.151	0.627	0.72	/
	1909.8	GPRS	/	/	/	/	/	/
Head Right Tilt	1850.2	GPRS	25.54	26.0	1.112	0.851	0.95	/
	1880	GPRS	25.39	26.0	1.151	0.865	**1.00**	7#
	1909.8	GPRS	25.62	26.0	1.091	0.890	0.97	/
Body Front (10mm)	1850.2	GPRS	/	/	/	/	/	/
	1880	GPRS	25.39	26.0	1.151	0.167	0.19	/
	1909.8	GPRS	/	/	/	/	/	/
Body Back (10mm)	1850.2	GPRS	/	/	/	/	/	/
	1880	GPRS	25.39	26.0	1.151	0.283	0.33	/
	1909.8	GPRS	/	/	/	/	/	/
Body Left (10mm)	1850.2	GPRS	/	/	/	/	/	/
	1880	GPRS	25.39	26.0	1.151	0.094	0.11	/
	1909.8	GPRS	/	/	/	/	/	/
Body Top (10mm)	1850.2	GPRS	/	/	/	/	/	/
	1880	GPRS	25.39	26.0	1.151	0.362	**0.42**	8#
	1909.8	GPRS	/	/	/	/	/	/

Note: The test data above was performed on 2025/04/04.

Note:
1. When the 1-g SAR is ≤ 0.8W/Kg, testing for other channels are optional.
2. The EUT transmit and receive through the same GSM antenna while testing SAR.
3. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
4. When the maximum output power variation across the required test channels is > 0.5 dB, instead of the middle channel, the highest output power channel must be used.
5. The Multi-slot Classes of EUT is Class 12 which has maximum 4 Downlink slots and 4 Uplink slots, the maximum active slots is 5, when perform the multiple slots scan, 2DL+3UL is the worst case.
6. The max. time based average power of GSM/GPRS mode was selected to Head/Body SAR testing.

WCDMA Band 2 (ANT0):

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
					Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	14.61	15.0	1.094	0.111	**0.12**	9#
	1907.6	RMC	/	/	/	/	/	/
Head Left Tilt	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	14.61	15.0	1.094	0.078	0.09	/
	1907.6	RMC	/	/	/	/	/	/
Head Right Cheek	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	14.61	15.0	1.094	0.084	0.09	/
	1907.6	RMC	/	/	/	/	/	/
Head Right Tilt	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	14.61	15.0	1.094	0.091	0.10	/
	1907.6	RMC	/	/	/	/	/	/
Body Front (10mm)	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	14.61	15.0	1.094	0.090	0.10	/
	1907.6	RMC	/	/	/	/	/	/
Body Back (10mm)	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	14.61	15.0	1.094	0.572	**0.63**	10#
	1907.6	RMC	/	/	/	/	/	/
Body Left (10mm)	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	14.61	15.0	1.094	0.074	0.08	/
	1907.6	RMC	/	/	/	/	/	/
Body Right (10mm)	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	14.61	15.0	1.094	0.047	0.05	/
	1907.6	RMC	/	/	/	/	/	/
Body Bottom (10mm)	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	14.61	15.0	1.094	0.260	0.28	/
	1907.6	RMC	/	/	/	/	/	/

Note: The test data above was performed on 2025/04/04.

WCDMA Band 2 (ANT1):

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
					Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	14.61	15.0	1.094	0.276	0.30	/
	1907.6	RMC	/	/	/	/	/	/
Head Left Tilt	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	14.61	15.0	1.094	0.352	0.39	/
	1907.6	RMC	/	/	/	/	/	/
Head Right Cheek	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	14.61	15.0	1.094	0.507	0.55	/
	1907.6	RMC	/	/	/	/	/	/
Head Right Tilt	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	14.61	15.0	1.094	0.724	**0.79**	11#
	1907.6	RMC	/	/	/	/	/	/
Body Front (10mm)	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	14.61	15.0	1.094	0.134	0.15	/
	1907.6	RMC	/	/	/	/	/	/
Body Back (10mm)	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	14.61	15.0	1.094	0.235	0.26	/
	1907.6	RMC	/	/	/	/	/	/
Body Left (10mm)	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	14.61	15.0	1.094	0.069	0.08	/
	1907.6	RMC	/	/	/	/	/	/
Body Top (10mm)	1852.4	RMC	/	/	/	/	/	/
	1880	RMC	14.61	15.0	1.094	0.309	**0.34**	12#
	1907.6	RMC	/	/	/	/	/	/

Note: The test data above was performed on 2025/04/04.

WCDMA Band 4 (ANT0):

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
					Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	1712.4	RMC	/	/	/	/	/	/
	1732.6	RMC	14.62	15	1.091	0.051	0.06	/
	1752.6	RMC	/	/	/	/	/	/
Head Left Tilt	1712.4	RMC	/	/	/	/	/	/
	1732.6	RMC	14.62	15	1.091	0.057	0.06	/
	1752.6	RMC	/	/	/	/	/	/
Head Right Cheek	1712.4	RMC	/	/	/	/	/	/
	1732.6	RMC	14.62	15	1.091	0.055	0.06	/
	1752.6	RMC	/	/	/	/	/	/
Head Right Tilt	1712.4	RMC	/	/	/	/	/	/
	1732.6	RMC	14.62	15	1.091	0.069	**0.08**	13#
	1752.6	RMC	/	/	/	/	/	/
Body Front (10mm)	1712.4	RMC	/	/	/	/	/	/
	1732.6	RMC	14.62	15	1.091	0.090	0.10	/
	1752.6	RMC	/	/	/	/	/	/
Body Back (10mm)	1712.4	RMC	/	/	/	/	/	/
	1732.6	RMC	14.62	15	1.091	0.422	**0.46**	14#
	1752.6	RMC	/	/	/	/	/	/
Body Left (10mm)	1712.4	RMC	/	/	/	/	/	/
	1732.6	RMC	14.62	15	1.091	0.053	0.06	/
	1752.6	RMC	/	/	/	/	/	/
Body Right (10mm)	1712.4	RMC	/	/	/	/	/	/
	1732.6	RMC	14.62	15	1.091	0.072	0.08	/
	1752.6	RMC	/	/	/	/	/	/
Body Bottom (10mm)	1712.4	RMC	/	/	/	/	/	/
	1732.6	RMC	14.62	15	1.091	0.202	0.22	/
	1752.6	RMC	/	/	/	/	/	/

Note: The test data above was performed on 2025/04/02.

WCDMA Band 4 (ANT1):

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
					Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	1712.4	RMC	/	/	/	/	/	/
	1732.6	RMC	14.62	15	1.091	0.545	0.59	/
	1752.6	RMC	/	/	/	/	/	/
Head Left Tilt	1712.4	RMC	/	/	/	/	/	/
	1732.6	RMC	14.62	15	1.091	0.416	0.45	/
	1752.6	RMC	/	/	/	/	/	/
Head Right Cheek	1712.4	RMC	14.26	14.5	1.057	0.868	0.92	/
	1732.6	RMC	14.62	15	1.091	0.731	0.80	/
	1752.6	RMC	14.24	14.5	1.062	0.804	0.85	/
Head Right Tilt	1712.4	RMC	14.26	14.5	1.057	1.07	1.13	/
	1732.6	RMC	14.62	15	1.091	0.910	0.99	/
	1752.6	RMC	14.24	14.5	1.062	1.07	**1.14**	15#
Body Front (10mm)	1712.4	RMC	/	/	/	/	/	/
	1732.6	RMC	14.62	15	1.091	0.173	0.19	/
	1752.6	RMC	/	/	/	/	/	/
Body Back (10mm)	1712.4	RMC	/	/	/	/	/	/
	1732.6	RMC	14.62	15	1.091	0.258	0.28	/
	1752.6	RMC	/	/	/	/	/	/
Body Left (10mm)	1712.4	RMC	/	/	/	/	/	/
	1732.6	RMC	14.62	15	1.091	0.073	0.08	/
	1752.6	RMC	/	/	/	/	/	/
Body Top (10mm)	1712.4	RMC	/	/	/	/	/	/
	1732.6	RMC	14.62	15	1.091	0.353	**0.39**	16#
	1752.6	RMC	/	/	/	/	/	/

Note: The test data above was performed on 2025/04/02.

WCDMA Band 5 (ANT0):

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
					Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.36	23.5	1.033	0.090	0.09	/
	846.6	RMC	/	/	/	/	/	/
Head Left Tilt	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.36	23.5	1.033	0.059	0.06	/
	846.6	RMC	/	/	/	/	/	/
Head Right Cheek	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.36	23.5	1.033	0.102	**0.11**	17#
	846.6	RMC	/	/	/	/	/	/
Head Right Tilt	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.36	23.5	1.033	0.043	0.05	/
	846.6	RMC	/	/	/	/	/	/
Body Front (10mm)	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.36	23.5	1.033	0.230	**0.24**	18#
	846.6	RMC	/	/	/	/	/	/
Body Back (10mm)	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.36	23.5	1.033	0.199	0.21	/
	846.6	RMC	/	/	/	/	/	/
Body Left (10mm)	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.36	23.5	1.033	0.096	0.10	/
	846.6	RMC	/	/	/	/	/	/
Body Right (10mm)	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.36	23.5	1.033	0.149	0.15	/
	846.6	RMC	/	/	/	/	/	/
Body Bottom (10mm)	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.36	23.5	1.033	0.147	0.15	/
	846.6	RMC	/	/	/	/	/	/

Note: The test data above was performed on 2025/03/31.

WCDMA Band 5 (ANT1):

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
					Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.36	23.5	1.033	0.631	0.65	/
	846.6	RMC	/	/	/	/	/	/
Head Left Tilt	826.4	RMC	23.31	23.5	1.045	0.722	0.75	/
	836.6	RMC	23.36	23.5	1.033	0.783	**0.81**	19#
	846.6	RMC	23.47	23.5	1.007	0.761	0.77	/
Head Right Cheek	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.36	23.5	1.033	0.646	0.67	/
	846.6	RMC	/	/	/	/	/	/
Head Right Tilt	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.36	23.5	1.033	0.757	0.78	/
	846.6	RMC	/	/	/	/	/	/
Body Front (10mm)	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.36	23.5	1.033	0.539	**0.56**	20#
	846.6	RMC	/	/	/	/	/	/
Body Back (10mm)	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.36	23.5	1.033	0.474	0.49	/
	846.6	RMC	/	/	/	/	/	/
Body Left (10mm)	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.36	23.5	1.033	0.225	0.23	/
	846.6	RMC	/	/	/	/	/	/
Body Top (10mm)	826.4	RMC	/	/	/	/	/	/
	836.6	RMC	23.36	23.5	1.033	0.510	0.53	/
	846.6	RMC	/	/	/	/	/	/

Note: The test data above was performed on 2025/04/01.

Note:
1. When the 1-g SAR is≤ 0.8W/Kg, testing for other channels are optional.
2. The EUT transmit and receive through the same antenna while testing SAR.
3. The default test configuration is to measure SAR with an established radio link between the EUT and a communication test set using a 12.2 kbps RMC(reference measurement Channel) Configured in All 1.
4. KDB 941225 D01-Body SAR is not required for HSDPA/HSUPA/DC-HSDPA/HSPA+ when the maximum average output of each RF channel is less than ¼ dB higher than measured 12.2kbps RMC or the maximum SAR for 12.2kbps RMC is < 75% of SAR limit.
5. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.

LTE Band 2 (ANT0):

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	16.08	16.5	1.102	0.063	0.07	/
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	14.72	15.0	1.067	0.047	0.05	/
Head Left Tilt	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	16.08	16.5	1.102	0.052	0.06	/
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	14.72	15.0	1.067	0.042	0.04	/
Head Right Cheek	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	16.08	16.5	1.102	0.066	**0.07**	21#
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	14.72	15.0	1.067	0.047	0.05	/
Head Right Tilt	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	16.08	16.5	1.102	0.062	0.07	/
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	14.72	15.0	1.067	0.047	0.05	/
Body Front (10mm)	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	16.08	16.5	1.102	0.084	0.09	/
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	14.72	15.0	1.067	0.058	0.06	/
Body Back (10mm)	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	16.08	16.5	1.102	0.570	**0.63**	22#
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	14.72	15.0	1.067	0.373	0.40	/
Body Left (10mm)	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	16.08	16.5	1.102	0.097	0.11	/
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	14.72	15.0	1.067	0.071	0.08	/
Body Right (10mm)	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	16.08	16.5	1.102	0.068	0.07	/
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	14.72	15.0	1.067	0.051	0.05	/
Body Bottom (10mm)	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	16.08	16.5	1.102	0.266	0.29	/
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	14.72	15.0	1.067	0.206	0.22	/

Note: The test data above was performed on 2025/04/05.

LTE Band 2 (ANT1):

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	16.08	16.5	1.102	0.281	0.31	/
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	14.72	15.0	1.067	0.201	0.21	/
Head Left Tilt	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	16.08	16.5	1.102	0.448	0.49	/
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	14.72	15.0	1.067	0.297	0.32	/
Head Right Cheek	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	16.08	16.5	1.102	0.705	**0.78**	23#
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	14.72	15.0	1.067	0.441	0.47	/
Head Right Tilt	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	16.08	16.5	1.102	0.690	0.76	/
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	14.72	15.0	1.067	0.553	0.59	/
Body Front (10mm)	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	16.08	16.5	1.102	0.171	0.19	/
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	14.72	15.0	1.067	0.107	0.11	/
Body Back (10mm)	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	16.08	16.5	1.102	0.300	0.33	/
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	14.72	15.0	1.067	0.184	0.20	/
Body Left (10mm)	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	16.08	16.5	1.102	0.077	0.08	/
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	14.72	15.0	1.067	0.065	0.07	/
Body Top (10mm)	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	16.08	16.5	1.102	0.420	**0.46**	24#
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	14.72	15.0	1.067	0.330	0.35	/

Note: The test data above was performed on 2025/04/05.

LTE Band 5 (ANT0):

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	829	10	1RB	/	/	/	/	/	/
	836.5	10	1RB	24.11	24.5	1.094	0.103	**0.11**	25#
	844	10	1RB	/	/	/	/	/	/
	836.5	10	50%RB	22.53	23.0	1.114	0.079	0.09	/
Head Left Tilt	829	10	1RB	/	/	/	/	/	/
	836.5	10	1RB	24.11	24.5	1.094	0.086	0.09	/
	844	10	1RB	/	/	/	/	/	/
	836.5	10	50%RB	22.53	23.0	1.114	0.076	0.08	/
Head Right Cheek	829	10	1RB	/	/	/	/	/	/
	836.5	10	1RB	24.11	24.5	1.094	0.094	0.10	/
	844	10	1RB	/	/	/	/	/	/
	836.5	10	50%RB	22.53	23.0	1.114	0.074	0.08	/
Head Right Tilt	829	10	1RB	/	/	/	/	/	/
	836.5	10	1RB	24.11	24.5	1.094	0.050	0.05	/
	844	10	1RB	/	/	/	/	/	/
	836.5	10	50%RB	22.53	23.0	1.114	0.041	0.05	/
Body Front (10mm)	829	10	1RB	/	/	/	/	/	/
	836.5	10	1RB	24.11	24.5	1.094	0.187	0.20	/
	844	10	1RB	/	/	/	/	/	/
	836.5	10	50%RB	22.53	23.0	1.114	0.143	0.16	/
Body Back (10mm)	829	10	1RB	/	/	/	/	/	/
	836.5	10	1RB	24.11	24.5	1.094	0.310	**0.34**	26#
	844	10	1RB	/	/	/	/	/	/
	836.5	10	50%RB	22.53	23.0	1.114	0.242	0.27	/
Body Left (10mm)	829	10	1RB	/	/	/	/	/	/
	836.5	10	1RB	24.11	24.5	1.094	0.184	0.20	/
	844	10	1RB	/	/	/	/	/	/
	836.5	10	50%RB	22.53	23.0	1.114	0.140	0.16	/
Body Right (10mm)	829	10	1RB	/	/	/	/	/	/
	836.5	10	1RB	24.11	24.5	1.094	0.171	0.19	/
	844	10	1RB	/	/	/	/	/	/
	836.5	10	50%RB	22.53	23.0	1.114	0.134	0.15	/
Body Bottom (10mm)	829	10	1RB	/	/	/	/	/	/
	836.5	10	1RB	24.11	24.5	1.094	0.142	0.16	/
	844	10	1RB	/	/	/	/	/	/
	836.5	10	50%RB	22.53	23.0	1.114	0.112	0.12	/

Note: The test data above was performed on 2025/04/02.

LTE Band 5 (ANT1):

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	829	10	1RB	24.30	24.5	1.047	0.913	0.96	/
	836.5	10	1RB	24.11	24.5	1.094	0.934	1.02	/
	844	10	1RB	24.27	24.5	1.054	0.974	1.03	/
	836.5	10	50%RB	22.53	23.0	1.114	0.659	0.73	/
	844	10	100%RB	22.61	23.0	1.094	0.681	0.75	/
Head Left Tilt	829	10	1RB	24.30	24.5	1.047	0.996	1.04	/
	836.5	10	1RB	24.11	24.5	1.094	1.04	1.14	/
	844	10	1RB	24.27	24.5	1.054	1.09	**1.15**	27#
	829	10	50%RB	22.45	23.0	1.135	0.758	0.86	/
	836.5	10	50%RB	22.53	23.0	1.114	0.742	0.83	/
	844	10	50%RB	22.44	23.0	1.138	0.778	0.89	/
	844	10	100%RB	22.61	23.0	1.094	0.594	0.65	/
Head Right Cheek	829	10	1RB	24.30	24.5	1.047	0.763	0.80	/
	836.5	10	1RB	24.11	24.5	1.094	0.803	0.88	/
	844	10	1RB	24.27	24.5	1.054	0.857	0.90	/
	836.5	10	50%RB	22.53	23.0	1.114	0.598	0.67	/
	844	10	100%RB	22.61	23.0	1.094	0.614	0.67	/
Head Right Tilt	829	10	1RB	24.30	24.5	1.047	0.767	0.80	/
	836.5	10	1RB	24.11	24.5	1.094	0.775	0.85	/
	844	10	1RB	24.27	24.5	1.054	0.792	0.84	/
	836.5	10	50%RB	22.53	23.0	1.114	0.574	0.64	/
	844	10	100%RB	22.61	23.0	1.094	0.573	0.63	/
Body Front (10mm)	829	10	1RB	/	/	/	/	/	/
	836.5	10	1RB	24.11	24.5	1.094	0.456	**0.50**	28#
	844	10	1RB	/	/	/	/	/	/
	836.5	10	50%RB	22.53	23.0	1.114	0.343	0.38	/
Body Back (10mm)	829	10	1RB	/	/	/	/	/	/
	836.5	10	1RB	24.11	24.5	1.094	0.415	0.45	/
	844	10	1RB	/	/	/	/	/	/
	836.5	10	50%RB	22.53	23.0	1.114	0.324	0.36	/
Body Left (10mm)	829	10	1RB	/	/	/	/	/	/
	836.5	10	1RB	24.11	24.5	1.094	0.285	0.31	/
	844	10	1RB	/	/	/	/	/	/
	836.5	10	50%RB	22.53	23.0	1.114	0.209	0.23	/
Body Top (10mm)	829	10	1RB	/	/	/	/	/	/
	836.5	10	1RB	24.11	24.5	1.094	0.363	0.40	/
	844	10	1RB	/	/	/	/	/	/
	836.5	10	50%RB	22.53	23.0	1.114	0.266	0.30	/

Note: The test data above was performed on 2025/03/31.

LTE Band 7 (ANT0):

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	2510	20	1RB	/	/	/	/	/	/
	2535	20	1RB	15.82	16.0	1.042	0.537	**0.56**	29#
	2560	20	1RB	/	/	/	/	/	/
	2535	20	50%RB	14.39	14.5	1.025	0.445	0.46	/
Head Left Tilt	2510	20	1RB	/	/	/	/	/	/
	2535	20	1RB	15.82	16.0	1.042	0.215	0.22	/
	2560	20	1RB	/	/	/	/	/	/
	2535	20	50%RB	14.39	14.5	1.025	0.180	0.18	/
Head Right Cheek	2510	20	1RB	/	/	/	/	/	/
	2535	20	1RB	15.82	16.0	1.042	0.254	0.26	/
	2560	20	1RB	/	/	/	/	/	/
	2535	20	50%RB	14.39	14.5	1.025	0.222	0.23	/
Head Right Tilt	2510	20	1RB	/	/	/	/	/	/
	2535	20	1RB	15.82	16.0	1.042	0.235	0.24	/
	2560	20	1RB	/	/	/	/	/	/
	2535	20	50%RB	14.39	14.5	1.025	0.207	0.21	/
Body Front (10mm)	2510	20	1RB	/	/	/	/	/	/
	2535	20	1RB	15.82	16.0	1.042	0.221	0.23	/
	2560	20	1RB	/	/	/	/	/	/
	2535	20	50%RB	14.39	14.5	1.025	0.184	0.19	/
Body Back (10mm)	2510	20	1RB	14.28	14.5	1.052	0.860	0.90	/
	2535	20	1RB	15.82	16.0	1.042	0.975	1.02	/
	2560	20	1RB	14.26	14.5	1.057	0.855	0.90	/
	2510	20	50%RB	13.28	13.5	1.052	0.746	0.78	/
	2535	20	50%RB	14.39	14.5	1.025	0.773	0.79	/
	2560	20	50%RB	14.00	14.5	1.122	0.703	0.79	/
	2535	20	100%RB	14.20	14.5	1.071	0.797	0.85	/
Body Left (10mm)	2510	20	1RB	/	/	/	/	/	/
	2535	20	1RB	15.82	16.0	1.042	0.326	0.34	/
	2560	20	1RB	/	/	/	/	/	/
	2535	20	50%RB	14.39	14.5	1.025	0.232	0.24	/
Body Right (10mm)	2510	20	1RB	/	/	/	/	/	/
	2535	20	1RB	15.82	16.0	1.042	0.252	0.26	/
	2560	20	1RB	/	/	/	/	/	/
	2535	20	50%RB	14.39	14.5	1.025	0.207	0.21	/
Body Bottom (10mm)	2510	20	1RB	14.28	14.5	1.052	1.06	**1.12**	30#
	2535	20	1RB	15.82	16.0	1.042	1.03	1.07	/
	2560	20	1RB	14.26	14.5	1.057	1.01	1.07	/
	2510	20	50%RB	13.28	13.5	1.052	0.936	0.98	/
	2535	20	50%RB	14.39	14.5	1.026	0.873	0.90	/
	2560	20	50%RB	14.00	14.5	1.122	0.820	0.92	/
	2510	20	100%RB	13.23	13.5	1.064	0.884	0.94	/

Note: The test data of 2510/2535MHz was performed on 2025/04/06, The test data of 2560MHz was performed on 2025/04/07.

LTE Band 7 (ANT1):

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	2510	20	1RB	/	/	/	/	/	/
	2535	20	1RB	15.82	16.0	1.042	0.126	0.13	/
	2560	20	1RB	/	/	/	/	/	/
	2535	20	50%RB	14.39	14.5	1.025	0.111	0.11	/
Head Left Tilt	2510	20	1RB	/	/	/	/	/	/
	2535	20	1RB	15.82	16.0	1.042	0.158	0.16	/
	2560	20	1RB	/	/	/	/	/	/
	2535	20	50%RB	14.39	14.5	1.025	0.145	0.15	/
Head Right Cheek	2510	20	1RB	/	/	/	/	/	/
	2535	20	1RB	15.82	16.0	1.042	0.563	0.59	/
	2560	20	1RB	/	/	/	/	/	/
	2535	20	50%RB	14.39	14.5	1.025	0.480	0.49	/
Head Right Tilt	2510	20	1RB	/	/	/	/	/	/
	2535	20	1RB	15.82	16.0	1.042	0.768	**0.80**	31#
	2560	20	1RB	/	/	/	/	/	/
	2535	20	50%RB	14.39	14.5	1.025	0.664	0.68	/
Body Front (10mm)	2510	20	1RB	/	/	/	/	/	/
	2535	20	1RB	15.82	16.0	1.042	0.114	0.12	/
	2560	20	1RB	/	/	/	/	/	/
	2535	20	50%RB	14.39	14.5	1.025	0.105	0.11	/
Body Back (10mm)	2510	20	1RB	/	/	/	/	/	/
	2535	20	1RB	15.82	16.0	1.042	0.375	**0.39**	32#
	2560	20	1RB	/	/	/	/	/	/
	2535	20	50%RB	14.39	14.5	1.025	0.314	0.32	/
Body Left (10mm)	2510	20	1RB	/	/	/	/	/	/
	2535	20	1RB	15.82	16.0	1.042	0.075	0.08	/
	2560	20	1RB	/	/	/	/	/	/
	2535	20	50%RB	14.39	14.5	1.025	0.070	0.07	/
Body Top (10mm)	2510	20	1RB	/	/	/	/	/	/
	2535	20	1RB	15.82	16.0	1.042	0.302	0.31	/
	2560	20	1RB	/	/	/	/	/	/
	2535	20	50%RB	14.39	14.5	1.025	0.261	0.27	/

Note: The test data above was performed on 2025/04/06.

LTE Band 12&17 (ANT0):

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	24.39	25.0	1.151	0.076	0.09	/
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	22.75	23.0	1.059	0.056	0.06	/
Head Left Tilt	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	24.39	25.0	1.151	0.067	0.08	/
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	22.75	23.0	1.059	0.053	0.06	/
Head Right Cheek	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	24.39	25.0	1.151	0.079	**0.09**	33#
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	22.75	23.0	1.059	0.066	0.07	/
Head Right Tilt	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	24.39	25.0	1.151	0.045	0.05	/
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	22.75	23.0	1.059	0.038	0.04	/
Body Front (10mm)	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	24.39	25.0	1.151	0.297	**0.34**	34#
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	22.75	23.0	1.059	0.217	0.23	/
Body Back (10mm)	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	24.39	25.0	1.151	0.114	0.13	/
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	22.75	23.0	1.059	0.096	0.10	/
Body Left (10mm)	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	24.39	25.0	1.151	0.272	0.31	/
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	22.75	23.0	1.059	0.201	0.21	/
Body Right (10mm)	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	24.39	25.0	1.151	0.169	0.19	/
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	22.75	23.0	1.059	0.120	0.13	/
Body Bottom (10mm)	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	24.39	25.0	1.151	0.072	0.08	/
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	22.75	23.0	1.059	0.057	0.06	/

Note: The test data above was performed on 2025/03/29.

Note:

1.The E-UTRA Operating Band 17 is a subset of band 12, and they are same in modulation type and rated output power, therefore, they were considered as one frequency band during SAR measurement,
LTE Band 12 (the wide frequency range) was selected to test.

LTE Band 12&17 (ANT1):

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	24.39	25.0	1.151	0.642	0.74	/
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	22.75	23.0	1.059	0.485	0.51	/
Head Left Tilt	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	24.39	25.0	1.151	0.654	0.75	/
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	22.75	23.0	1.059	0.516	0.55	/
Head Right Cheek	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	24.39	25.0	1.151	0.666	**0.77**	35#
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	22.75	23.0	1.059	0.481	0.51	/
Head Right Tilt	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	24.39	25.0	1.151	0.601	0.69	/
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	22.75	23.0	1.059	0.451	0.48	/
Body Front (10mm)	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	24.39	25.0	1.151	0.249	0.29	/
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	22.75	23.0	1.059	0.193	0.20	/
Body Back (10mm)	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	24.39	25.0	1.151	0.314	**0.36**	36#
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	22.75	23.0	1.059	0.234	0.25	/
Body Left (10mm)	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	24.39	25.0	1.151	0.294	0.34	/
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	22.75	23.0	1.059	0.217	0.23	/
Body Top (10mm)	704	10	1RB	/	/	/	/	/	/
	707.5	10	1RB	24.39	25.0	1.151	0.181	0.21	/
	711	10	1RB	/	/	/	/	/	/
	707.5	10	50%RB	22.75	23.0	1.059	0.142	0.15	/

Note: The test data above was performed on 2025/03/29.

Note:

1.The E-UTRA Operating Band 17 is a subset of band 12, and they are same in modulation type and rated output power, therefore, they were considered as one frequency band during SAR measurement,
LTE Band 12 (the wide frequency range) was selected to test.

LTE Band 13 (ANT0):

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	782	10	1RB	23.68	24.0	1.076	0.070	**0.08**	37#
	782	10	50%RB	23.07	23.5	1.104	0.062	0.07	/
Head Left Tilt	782	10	1RB	23.68	24.0	1.076	0.052	0.06	/
	782	10	50%RB	23.07	23.5	1.104	0.051	0.06	/
Head Right Cheek	782	10	1RB	23.68	24.0	1.076	0.044	0.05	/
	782	10	50%RB	23.07	23.5	1.104	0.041	0.05	/
Head Right Tilt	782	10	1RB	23.68	24.0	1.076	0.034	0.04	/
	782	10	50%RB	23.07	23.5	1.104	0.031	0.04	/
Body Front (10mm)	782	10	1RB	23.68	24.0	1.076	0.256	**0.28**	38#
	782	10	50%RB	23.07	23.5	1.104	0.249	0.28	/
Body Back (10mm)	782	10	1RB	23.68	24.0	1.076	0.198	0.21	/
	782	10	50%RB	23.07	23.5	1.104	0.182	0.20	/
Body Left (10mm)	782	10	1RB	23.68	24.0	1.076	0.174	0.19	/
	782	10	50%RB	23.07	23.5	1.104	0.117	0.13	/
Body Right (10mm)	782	10	1RB	23.68	24.0	1.076	0.134	0.14	/
	782	10	50%RB	23.07	23.5	1.104	0.121	0.13	/
Body Bottom (10mm)	782	10	1RB	23.68	24.0	1.076	0.111	0.12	/
	782	10	50%RB	23.07	23.5	1.104	0.102	0.11	/

Note: The test data above was performed on 2025/03/30.

LTE Band 13 (ANT1):

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	782	10	1RB	23.68	24.0	1.076	0.437	0.47	/
	782	10	50%RB	23.07	23.5	1.104	0.384	0.42	/
Head Left Tilt	782	10	1RB	23.68	24.0	1.076	0.488	**0.53**	39#
	782	10	50%RB	23.07	23.5	1.104	0.408	0.45	/
Head Right Cheek	782	10	1RB	23.68	24.0	1.076	0.431	0.46	/
	782	10	50%RB	23.07	23.5	1.104	0.388	0.43	/
Head Right Tilt	782	10	1RB	23.68	24.0	1.076	0.472	0.51	/
	782	10	50%RB	23.07	23.5	1.104	0.412	0.45	/
Body Front (10mm)	782	10	1RB	23.68	24.0	1.076	0.278	**0.30**	40#
	782	10	50%RB	23.07	23.5	1.104	0.238	0.26	/
Body Back (10mm)	782	10	1RB	23.68	24.0	1.076	0.243	0.26	/
	782	10	50%RB	23.07	23.5	1.104	0.205	0.23	/
Body Left (10mm)	782	10	1RB	23.68	24.0	1.076	0.216	0.23	/
	782	10	50%RB	23.07	23.5	1.104	0.192	0.21	/
Body Top (10mm)	782	10	1RB	23.68	24.0	1.076	0.187	0.20	/
	782	10	50%RB	23.07	23.5	1.104	0.166	0.18	/

Note: The test data above was performed on 2025/03/30.

LTE Band 38 (ANT0):

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	2580	20	1RB	/	/	/	/	/	/
	2595	20	1RB	19.25	19.6	1.084	0.434	**0.47**	41#
	2610	20	1RB	/	/	/	/	/	/
	2595	20	50%RB	18.4	18.5	1.023	0.394	0.40	/
Head Left Tilt	2580	20	1RB	/	/	/	/	/	/
	2595	20	1RB	19.25	19.6	1.084	0.184	0.20	/
	2610	20	1RB	/	/	/	/	/	/
	2595	20	50%RB	18.4	18.5	1.023	0.163	0.17	/
Head Right Cheek	2580	20	1RB	/	/	/	/	/	/
	2595	20	1RB	19.25	19.6	1.084	0.240	0.26	/
	2610	20	1RB	/	/	/	/	/	/
	2595	20	50%RB	18.4	18.5	1.023	0.230	0.24	/
Head Right Tilt	2580	20	1RB	/	/	/	/	/	/
	2595	20	1RB	19.25	19.6	1.084	0.179	0.19	/
	2610	20	1RB	/	/	/	/	/	/
	2595	20	50%RB	18.4	18.5	1.023	0.170	0.17	/
Body Front (10mm)	2580	20	1RB	/	/	/	/	/	/
	2595	20	1RB	19.25	19.6	1.084	0.150	0.16	/
	2610	20	1RB	/	/	/	/	/	/
	2595	20	50%RB	18.4	18.5	1.023	0.141	0.14	/
Body Back (10mm)	2580	20	1RB	/	/	/	/	/	/
	2595	20	1RB	19.25	19.6	1.084	0.727	0.79	/
	2610	20	1RB	/	/	/	/	/	/
	2595	20	50%RB	18.4	18.5	1.023	0.670	0.69	/
Body Left (10mm)	2580	20	1RB	/	/	/	/	/	/
	2595	20	1RB	19.25	19.6	1.084	0.239	0.26	/
	2610	20	1RB	/	/	/	/	/	/
	2595	20	50%RB	18.4	18.5	1.023	0.221	0.23	/
Body Right (10mm)	2580	20	1RB	/	/	/	/	/	/
	2595	20	1RB	19.25	19.6	1.084	0.116	0.13	/
	2610	20	1RB	/	/	/	/	/	/
	2595	20	50%RB	18.4	18.5	1.023	0.107	0.11	/
Body Bottom (10mm)	2580	20	1RB	19.13	19.6	1.114	0.775	0.86	/
	2595	20	1RB	19.25	19.6	1.084	0.859	**0.93**	42#
	2610	20	1RB	17.11	17.5	1.094	0.793	0.87	/
	2595	20	50%RB	18.4	18.5	1.023	0.600	0.61	/
	2595	20	100%RB	18.17	18.5	1.079	0.687	0.74	/

Note: The test data above was performed on 2025/04/08.

LTE Band 38 (ANT1):

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	2580	20	1RB	/	/	/	/	/	/
	2595	20	1RB	19.25	19.6	1.084	0.118	0.13	/
	2610	20	1RB	/	/	/	/	/	/
	2595	20	50%RB	18.4	18.5	1.023	0.102	0.10	/
Head Left Tilt	2580	20	1RB	/	/	/	/	/	/
	2595	20	1RB	19.25	19.6	1.084	0.152	0.16	/
	2610	20	1RB	/	/	/	/	/	/
	2595	20	50%RB	18.4	18.5	1.023	0.119	0.12	/
Head Right Cheek	2580	20	1RB	/	/	/	/	/	/
	2595	20	1RB	19.25	19.6	1.084	0.487	0.53	/
	2610	20	1RB	/	/	/	/	/	/
	2595	20	50%RB	18.4	18.5	1.023	0.359	0.37	/
Head Right Tilt	2580	20	1RB	/	/	/	/	/	/
	2595	20	1RB	19.25	19.6	1.084	0.619	**0.67**	43#
	2610	20	1RB	/	/	/	/	/	/
	2595	20	50%RB	18.4	18.5	1.023	0.454	0.46	/
Body Front (10mm)	2580	20	1RB	/	/	/	/	/	/
	2595	20	1RB	19.25	19.6	1.084	0.106	0.11	/
	2610	20	1RB	/	/	/	/	/	/
	2595	20	50%RB	18.4	18.5	1.023	0.086	0.09	/
Body Back (10mm)	2580	20	1RB	/	/	/	/	/	/
	2595	20	1RB	19.25	19.6	1.084	0.414	**0.45**	44#
	2610	20	1RB	/	/	/	/	/	/
	2595	20	50%RB	18.4	18.5	1.023	0.359	0.37	/
Body Left (10mm)	2580	20	1RB	/	/	/	/	/	/
	2595	20	1RB	19.25	19.6	1.084	0.077	0.08	/
	2610	20	1RB	/	/	/	/	/	/
	2595	20	50%RB	18.4	18.5	1.023	0.069	0.07	/
Body Top (10mm)	2580	20	1RB	/	/	/	/	/	/
	2595	20	1RB	19.25	19.6	1.084	0.258	0.28	/
	2610	20	1RB	/	/	/	/	/	/
	2595	20	50%RB	18.4	18.5	1.023	0.197	0.20	/

Note: The test data above was performed on 2025/04/08.

LTE Band 41 (ANT0):

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	2506	20	1RB	/	/	/	/	/	/
	2549.5	20	1RB	/	/	/	/	/	/
	2593	20	1RB	19.76	20.0	1.052	0.488	**0.51**	45#
	2636.5	20	1RB	/	/	/	/	/	/
	2680	20	1RB	/	/	/	/	/	/
	2593	20	50%RB	18.31	18.5	1.045	0.453	0.47	/
Head Left Tilt	2506	20	1RB	/	/	/	/	/	/
	2549.5	20	1RB	/	/	/	/	/	/
	2593	20	1RB	19.76	20.0	1.052	0.183	0.19	/
	2636.5	20	1RB	/	/	/	/	/	/
	2680	20	1RB	/	/	/	/	/	/
	2593	20	50%RB	18.31	18.5	1.045	0.174	0.18	/
Head Right Cheek	2506	20	1RB	/	/	/	/	/	/
	2549.5	20	1RB	/	/	/	/	/	/
	2593	20	1RB	19.76	20.0	1.052	0.219	0.23	/
	2636.5	20	1RB	/	/	/	/	/	/
	2680	20	1RB	/	/	/	/	/	/
	2593	20	50%RB	18.31	18.5	1.045	0.213	0.22	/
Head Right Tilt	2506	20	1RB	/	/	/	/	/	/
	2549.5	20	1RB	/	/	/	/	/	/
	2593	20	1RB	19.76	20.0	1.052	0.208	0.22	/
	2636.5	20	1RB	/	/	/	/	/	/
	2680	20	1RB	/	/	/	/	/	/
	2593	20	50%RB	18.31	18.5	1.045	0.165	0.17	/
Body Front (10mm)	2506	20	1RB	/	/	/	/	/	/
	2549.5	20	1RB	/	/	/	/	/	/
	2593	20	1RB	19.76	20.0	1.052	0.175	0.18	/
	2636.5	20	1RB	/	/	/	/	/	/
	2680	20	1RB	/	/	/	/	/	/
	2593	20	50%RB	18.31	18.5	1.045	0.166	0.17	/
Body Back (10mm)	2506	20	1RB	/	/	/	/	/	/
	2549.5	20	1RB	/	/	/	/	/	/
	2593	20	1RB	19.76	20.0	1.052	0.755	**0.79**	46#
	2636.5	20	1RB	/	/	/	/	/	/
	2680	20	1RB	/	/	/	/	/	/
	2593	20	50%RB	18.31	18.5	1.045	0.706	0.74	/
Body Left (10mm)	2506	20	1RB	/	/	/	/	/	/
	2549.5	20	1RB	/	/	/	/	/	/
	2593	20	1RB	19.76	20.0	1.052	0.254	0.27	/
	2636.5	20	1RB	/	/	/	/	/	/
	2680	20	1RB	/	/	/	/	/	/
	2593	20	50%RB	18.31	18.5	1.045	0.236	0.25	/

Note: The test data above was performed on 2025/04/07.

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Right (10mm)	2506	20	1RB	/	/	/	/	/	/
	2549.5	20	1RB	/	/	/	/	/	/
	2593	20	1RB	19.76	20.0	1.052	0.111	0.12	/
	2636.5	20	1RB	/	/	/	/	/	/
	2680	20	1RB	/	/	/	/	/	/
	2593	20	50%RB	18.31	18.5	1.045	0.105	0.11	/
Body Bottom (10mm)	2506	20	1RB	/	/	/	/	/	/
	2549.5	20	1RB	/	/	/	/	/	/
	2593	20	1RB	19.76	20.0	1.052	0.668	0.70	/
	2636.5	20	1RB	/	/	/	/	/	/
	2680	20	1RB	/	/	/	/	/	/
	2593	20	50%RB	18.31	18.5	1.045	0.619	0.65	/

Note: The test data above was performed on 2025/04/07.

Note:

1.The frequency range of LTE Band 41 is 2496~ 2690MHz. Per KDB 447498 D01, according to the following formula Calculate Nc is 5.

2.KDB procedures *the following should be applied to determine the number of required test channels. The test channels should be evenly spread across the transmission frequency band of each wireless mode.*

$$N_c = Round\{[100(f_{high} - f_{low})/f_c]^{0.5} \times (f_c/100)^{0.2}\},$$

where

- N_c is the number of test channels,rounded to nearest integer,
- f_{high} and f_{low} are the highest and lowest channel frequencies within the transmission band,
- f_c is the mid-band channel frequency,
- all frequencies are in MHz.

3. The power class 3 used for LTE Band 41 SAR testing.

LTE Band 41 (ANT1):

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	2506	20	1RB	/	/	/	/	/	/
	2549.5	20	1RB	/	/	/	/	/	/
	2593	20	1RB	19.76	20.0	1.052	0.087	0.09	/
	2636.5	20	1RB	/	/	/	/	/	/
	2680	20	1RB	/	/	/	/	/	/
	2593	20	50%RB	18.31	18.5	1.045	0.074	0.08	/
Head Left Tilt	2506	20	1RB	/	/	/	/	/	/
	2549.5	20	1RB	/	/	/	/	/	/
	2593	20	1RB	19.76	20.0	1.052	0.104	0.11	/
	2636.5	20	1RB	/	/	/	/	/	/
	2680	20	1RB	/	/	/	/	/	/
	2593	20	50%RB	18.31	18.5	1.045	0.088	0.09	/
Head Right Cheek	2506	20	1RB	/	/	/	/	/	/
	2549.5	20	1RB	/	/	/	/	/	/
	2593	20	1RB	19.76	20.0	1.052	0.358	0.38	/
	2636.5	20	1RB	/	/	/	/	/	/
	2680	20	1RB	/	/	/	/	/	/
	2593	20	50%RB	18.31	18.5	1.045	0.297	0.31	/
Head Right Tilt	2506	20	1RB	/	/	/	/	/	/
	2549.5	20	1RB	/	/	/	/	/	/
	2593	20	1RB	19.76	20.0	1.052	0.529	**0.56**	47#
	2636.5	20	1RB	/	/	/	/	/	/
	2680	20	1RB	/	/	/	/	/	/
	2593	20	50%RB	18.31	18.5	1.045	0.423	0.44	/
Body Front (10mm)	2506	20	1RB	/	/	/	/	/	/
	2549.5	20	1RB	/	/	/	/	/	/
	2593	20	1RB	19.76	20.0	1.052	0.103	0.11	/
	2636.5	20	1RB	/	/	/	/	/	/
	2680	20	1RB	/	/	/	/	/	/
	2593	20	50%RB	18.31	18.5	1.045	0.084	0.09	/
Body Back (10mm)	2506	20	1RB	/	/	/	/	/	/
	2549.5	20	1RB	/	/	/	/	/	/
	2593	20	1RB	19.76	20.0	1.052	0.456	**0.48**	48#
	2636.5	20	1RB	/	/	/	/	/	/
	2680	20	1RB	/	/	/	/	/	/
	2593	20	50%RB	18.31	18.5	1.045	0.364	0.38	/
Body Left (10mm)	2506	20	1RB	/	/	/	/	/	/
	2549.5	20	1RB	/	/	/	/	/	/
	2593	20	1RB	19.76	20.0	1.052	0.078	0.08	/
	2636.5	20	1RB	/	/	/	/	/	/
	2680	20	1RB	/	/	/	/	/	/
	2593	20	50%RB	18.31	18.5	1.045	0.069	0.07	/

Note: The test data above was performed on 2025/04/07.

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Body Top (10mm)	2506	20	1RB	/	/	/	/	/	/
	2549.5	20	1RB	/	/	/	/	/	/
	2593	20	1RB	19.76	20.0	1.052	0.252	0.27	/
	2636.5	20	1RB	/	/	/	/	/	/
	2680	20	1RB	/	/	/	/	/	/
	2593	20	50%RB	18.31	18.5	1.045	0.199	0.21	/

Note: The test data above was performed on 2025/04/07.

Note:

1.The frequency range of LTE Band 41 is 2496~ 2690MHz. Per KDB 447498 D01, according to the following formula Calculate Nc is 5.

2.KDB procedures *the following should be applied to determine the number of required test channels. The test channels should be evenly spread across the transmission frequency band of each wireless mode.*

$$N_c = Round\{[100(f_{high} - f_{low})/f_c]^{0.5} \times (f_c/100)^{0.2}\},$$

where

- N_c is the number of test channels, rounded to nearest integer,
- f_{high} and f_{low} are the highest and lowest channel frequencies within the transmission band,
- f_c is the mid-band channel frequency,
- all frequencies are in MHz.

3. The power class 3 used for LTE Band 41 SAR testing.

LTE Band 66&4 (ANT0):

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	16.65	17.5	1.216	0.041	0.05	/
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	16.01	16.5	1.119	0.040	0.04	/
Head Left Tilt	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	16.65	17.5	1.216	0.035	0.04	/
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	16.01	16.5	1.119	0.033	0.04	/
Head Right Cheek	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	16.65	17.5	1.216	0.079	**0.10**	49#
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	16.01	16.5	1.119	0.066	0.07	/
Head Right Tilt	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	16.65	17.5	1.216	0.052	0.06	/
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	16.01	16.5	1.119	0.045	0.05	/
Body Front (10mm)	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	16.65	17.5	1.216	0.072	0.09	/
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	16.01	16.5	1.119	0.062	0.07	/
Body Back (10mm)	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	16.65	17.5	1.216	0.286	**0.35**	50#
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	16.01	16.5	1.119	0.225	0.25	/
Body Left (10mm)	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	16.65	17.5	1.216	0.044	0.05	/
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	16.01	16.5	1.119	0.039	0.04	/
Body Right (10mm)	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	16.65	17.5	1.216	0.065	0.08	/
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	16.01	16.5	1.119	0.056	0.06	/
Body Bottom (10mm)	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	16.65	17.5	1.216	0.106	0.13	/
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	16.01	16.5	1.119	0.086	0.10	/

Note: The test data above was performed on 2025/04/03.

Note:
1.The E-UTRA Operating Band 4 is a subset of band 66, and they are same in modulation type and rated output power, therefore, they were considered as one frequency band during SAR measurement, LTE Band 66 (the wide frequency range) was selected to test.

LTE Band 66&4 (ANT1):

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	16.65	17.5	1.216	0.310	0.38	/
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	16.01	16.5	1.119	0.251	0.28	/
Head Left Tilt	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	16.65	17.5	1.216	0.311	0.38	/
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	16.01	16.5	1.119	0.279	0.31	/
Head Right Cheek	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	16.65	17.5	1.216	0.612	0.74	/
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	16.01	16.5	1.119	0.504	0.56	/
Head Right Tilt	1720	20	1RB	17.27	17.5	1.054	0.816	0.86	/
	1745	20	1RB	16.65	17.5	1.216	0.825	**1.00**	51#
	1770	20	1RB	17.24	17.5	1.062	0.785	0.83	/
	1745	20	50%RB	16.01	16.5	1.119	0.669	0.75	/
	1745	20	100%RB	15.74	16.0	1.062	0.705	0.75	/
Body Front (10mm)	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	16.65	17.5	1.216	0.178	0.22	/
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	16.01	16.5	1.119	0.148	0.17	/
Body Back (10mm)	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	16.65	17.5	1.216	0.263	0.32	/
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	16.01	16.5	1.119	0.214	0.24	/
Body Left (10mm)	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	16.65	17.5	1.216	0.082	0.10	/
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	16.01	16.5	1.119	0.068	0.08	/
Body Top (10mm)	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	16.65	17.5	1.216	0.323	**0.39**	52#
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	16.01	16.5	1.119	0.254	0.28	/

Note: The test data above was performed on 2025/04/03.

Note:

1.The E-UTRA Operating Band 4 is a subset of band 66, and they are same in modulation type and rated output power, therefore, they were considered as one frequency band during SAR measurement, LTE Band 66 (the wide frequency range) was selected to test.

Note:

1. When the 1-g SAR is ≤ 0.8W/Kg, testing for other channels are optional.
2. SAR for LTE band exposure configurations is measured according to the procedures of KDB 941225 D05 SAR for LTE Devices v02.
3. KDB941225D05-SAR for higher order modulation is required only when the highest maximum output power for the configuration in the higher order modulation is > 0.5 dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg

4. KDB941225D05-For QPSK with 100% RB allocation, when the reported SAR measured for the Highest output power channel is <1.45 W/kg, tests for the remaining required test channels are optional.
5.KDB941225D05- For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg.
6. KDB941225D05- Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offset the upper edge, middle and lower edge of each required test channel.
7. KDB941225D05- other channel bandwidths SAR test is required when the highest maximum output power of a configuration requiring testing in the smaller channel bandwidth is > 0.5 dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is > 1.45 W/kg.

WLAN 2.4G (ANT12):

EUT Position	Frequency (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)				
					Scaled Factor	Duty cycle Factor	Meas. SAR	Scaled SAR	Plot
Head Left Cheek	2412	802.11b	/	/	/	/	/	/	/
	2437	802.11b	/	/	/	/	/	/	/
	2462	802.11b	16.73	17.0	1.064	1.020	0.208	0.23	/
Head Left Tilt	2412	802.11b	/	/	/	/	/	/	/
	2437	802.11b	/	/	/	/	/	/	/
	2462	802.11b	16.73	17.0	1.064	1.020	0.249	**0.27**	53#
Head Right Cheek	2412	802.11b	/	/	/	/	/	/	/
	2437	802.11b	/	/	/	/	/	/	/
	2462	802.11b	16.73	17.0	1.064	1.020	0.143	0.16	/
Head Right Tilt	2412	802.11b	/	/	/	/	/	/	/
	2437	802.11b	/	/	/	/	/	/	/
	2462	802.11b	16.73	17.0	1.064	1.020	0.186	0.20	/
Body Front (10mm)	2412	802.11b	/	/	/	/	/	/	/
	2437	802.11b	/	/	/	/	/	/	/
	2462	802.11b	16.73	17.0	1.064	1.020	0.101	0.11	/
Body Back (10mm)	2412	802.11b	/	/	/	/	/	/	/
	2437	802.11b	/	/	/	/	/	/	/
	2462	802.11b	16.73	17.0	1.064	1.020	0.147	0.16	/
Body Right (10mm)	2412	802.11b	/	/	/	/	/	/	/
	2437	802.11b	/	/	/	/	/	/	/
	2462	802.11b	16.73	17.0	1.064	1.020	0.145	0.16	/
Body Top (10mm)	2412	802.11b	/	/	/	/	/	/	/
	2437	802.11b	/	/	/	/	/	/	/
	2462	802.11b	16.73	17.0	1.064	1.020	0.171	**0.19**	54#

Note: The test data above was performed on 2025/04/09.

Note:

1. When the 1-g SAR is≤ 0.8W/kg, testing for other channels are optional.
2.When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
3.KDB 248227 D01-SAR measurement is not required for 2.4 GHz OFDM(802.11g/n)when the highest reported SAR for DSSS(802.11b) is ≤ 1.2 W/kg, and the output power for DSSS is not less than that for OFDM.
4. According KDB 248227 D01, for SAR testing of WLAN with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to “1/(duty cycle)”.

10. MEASUREMENT VARIABILITY

In accordance with published RF Exposure KDB procedure 865664 D01 SAR measurement 100 MHz to 6 GHz v01. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results

1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20.

Note: The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.

The Highest Measured SAR Configuration in Each Frequency Band

Head

SAR probe calibration point	Frequency Band	Freq.(MHz)	EUT Position	1g Meas. SAR (W/kg)		Largest to Smallest SAR Ratio
				Original	Repeated	
750MHz	LTE B5	844	Head Left Tilt	1.09	0.991	1.10
1750MHz	WCDMA B4	1752.6	Head Right Tilt	1.07	0.987	1.08
1900MHz	PCS 1900	1909.8	Head Right Tilt	0.890	0.862	1.03

Body

SAR probe calibration point	Frequency Band	Freq.(MHz)	EUT Position	1g Meas. SAR (W/kg)		Largest to Smallest SAR Ratio
				Original	Repeated	
2450MHz	LTE B7	2510	Body Bottom (10mm)	1.06	1.01	1.05
2600MHz	LTE B7	2560	Body Bottom (10mm)	1.01	0.929	1.09

Note:

1. Second Repeated Measurement is not required since the ratio of the largest to smallest SAR for the original and first repeated measurement is not > 1.20.
2. The measured SAR results **do not** have to be scaled to the maximum tune-up tolerance to determine if repeated measurements are required.
3. SAR measurement variability must be assessed for each frequency band, which is determined by the **SAR probe calibration point and tissue-equivalent medium** used for the device measurements.

11. SAR SIMULTANEOUS TRANSMISSION DESCRIPTION

11.1 Simultaneous Transmission:

Description of Simultaneous Transmit Capabilities		
Transmitter Combination	**Simultaneous?**	**Hotspot?**
WWAN(GSM/WCDMA/LTE) + WLAN 2.4G	√	√
WWAN(GSM/WCDMA/LTE) + WLAN 5.2/5.8G	√	√
WWAN(GSM/WCDMA/LTE) + WLAN 5.3/5.6G	√	×
WLAN 2.4G + WLAN 5G	×	×
WLAN 2.4G + Bluetooth	×	×
WLAN 5G + Bluetooth	×	×

Note: In a WWAN antenna, only a single antenna in one band operates at a time.

11.2 Simultaneous SAR test exclusion considerations:

Mode(SAR1+SAR2)	Position	Reported SAR(W/kg)		ΣSAR < 1.6W/kg
		SAR1	SAR2	
WWAN(GSM/WCDMA/LTE) + Bluetooth	Head	1.15	0.08	1.23
	Body	1.12	0.04	1.16
WWAN(GSM/WCDMA/LTE) + WLAN 2.4G	Head	1.15	0.27	1.42
	Body	1.12	0.19	1.31
	Body (Hotspot)	1.12	0.19	1.31
WWAN(GSM/WCDMA/LTE) + WLAN 5G	Head	1.15	0.40	**1.55**
	Body	1.12	0.20	1.32
	Body (Hotspot)	1.12	0.20	1.32

Conclusion:
Sum of SAR:**ΣSAR ≤1.6 W/kg** therefore simultaneous transmission SAR with Volume Scans is **not required.**

APPENDIX A - MEASUREMENT UNCERTAINTY

The uncertainty budget has been determined for the measurement system and is given in the following Table.

Measurement uncertainty evaluation for IEEE1528-2013 SAR test

Uncertainty component	Tolerance/ uncertainty ± %	Probability distribution	Divisor	ci (1 g)	ci (10 g)	Standard uncertainty ± %, (1 g)	Standard uncertainty ± %, (10 g)
Measurement system							
Probe calibration(k=1)	6.55	N	1	1	1	6.6	6.6
Axial isotropy	4.7	R	√3	√0.5	√0.5	1.9	1.9
Hemispherical isotropy	9.6	R	√3	√0.5	√0.5	3.9	3.9
Boundary effect	1.0	R	√3	1	1	0.6	0.6
Linearity	4.7	R	√3	1	1	2.7	2.7
System detection limits	1.0	R	√3	1	1	0.6	0.6
Modulation response	0.0	R	√3	1	1	0.0	0.0
Readout electronics	0.3	N	1	1	1	0.3	0.3
Response time	0.0	R	√3	1	1	0.0	0.0
Integration time	0.0	R	√3	1	1	0.0	0.0
RF ambient conditions-noise	1.0	R	√3	1	1	0.6	0.6
RF ambient conditions-reflections	1.0	R	√3	1	1	0.6	0.6
Probe positioner mech. tolerance	0.8	R	√3	1	1	0.5	0.5
Probe positioning with respect to phantom shell	6.7	R	√3	1	1	3.9	3.9
Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation	2.0	R	√3	1	1	1.2	1.2
Test sample related							
Test sample positioning	3.3	N	1	1	1	3.3	3.3
Device holder uncertainty	4.7	N	1	1	1	4.7	4.7
Output power variation –SAR draft measurement	5.0	R	√3	1	1	2.9	2.9
SAR scaling	2.8	R	√3	1	1	1.6	1.6
Phantom and tissue parameters							
Phantom shell uncertainty– shape, thickness and permittivity	4.0	R	√3	1	1	2.3	2.3
Uncertainty in SAR correction for deviations in permittivity and conductivity	1.9	N	1	1	0.84	1.9	1.6
Liquid conductivity meas.	2.5	N	1	0.78	0.71	2.0	1.8
Liquid permittivity meas.	2.5	N	1	0.23	0.26	0.6	0.7
Liquid conductivity – temperature uncertainty	1.7	R	√3	0.78	0.71	0.8	0.7
Liquid permittivity – temperature uncertainty	0.3	R	√3	0.23	0.26	0.0	0.0
Combined standard uncertainty		RSS				12.1	12.0
Expanded uncertainty (95 % confidence interval)		k=2				24.2	24.0

APPENDIX B - SAR PLOTS

Please refer to the attachment.

APPENDIX C - EUT TEST POSITION PHOTOS

Please refer to the attachment.

APPENDIX D - PROBE CALIBRATION CERTIFICATES

Please refer to the attachment.

APPENDIX E - DIPOLE CALIBRATION CERTIFICATES

Please refer to the attachment.

******* END OF REPORT *******