TEST REPORT

Applicant:	INFINIX MOBILITY LIMITED
Address:	FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI STREET FOTAN NT HONGKONG
Equipment Type:	Mobile Phone
Model Name:	X6840
Brand Name:	Infinix
FCC ID:	2AIZN-YYS-X6840
Test Standard:	47 CFR Part 15 Subpart B ANSI C63.4-2014
Sample Arrival Date:	Nov. 26, 2025
Test Date:	Nov. 28, 2025
Date of Issue:	Jan. 04, 2026

ISSUED BY:

Shanghai Tejet Communications Technology Co., Ltd. Testing Center

Prepared by: Hao Longda

Hao Long da

Reviewed by: Huang Chengkun

Huang Chengkun

Approved by: Zhang Yanqing

(Laboratory Manager)

Zhang Yanqing

Revision History

Version	Issue Date	Revisions Content
Rev. 01	Jan. 04, 2026	Initial Issue

TABLE OF CONTENTS

1 GENERAL INFORMATION 4
1.1 Test Laboratory 4
1.2 Test Location 4
2 PRODUCT INFORMATION 5
2.1 Applicant Information 5
2.2 Manufacturer Information 5
2.3 General Description for Equipment under Test (EUT) 5
2.4 Ancillary Equipment 6
2.5 Technical Information 7
3 SUMMARY OF TEST RESULTS 8
3.1 Test Standards 8
3.2 Verdict 8
3.3 Decision Rule 8
3.4 Test Uncertainty 8
4 GENERAL TEST CONFIGURATIONS 9
4.1 Test Enclosure List 9
4.2 Test Configurations 9
4.3 Test Setups 10
5 TEST ITEMS 12
5.1 Emission Tests 12
5.1.1 Radiated emission 12
5.1.2 Conducted emission 14
ANNEX A TEST RESULTS AND TEST EQUIPMENT LIST 15
A.1 Radiated emission 15
A.2 Conducted emission 25

ANNEX B TEST SETUP PHOTOS 29
ANNEX C EUT EXTERNAL PHOTOS 29
ANNEX D EUT INTERNAL PHOTOS 29

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shanghai Tejet Communications Technology Co., Ltd. Testing Center
Address	1-2/F., Building 1, No.222, Xuanlan Road, Xuanqiao, Pudong New District, Shanghai, China

1.2 Test Location

Name	Shanghai Tejet Communications Technology Co., Ltd. Testing Center
Location	1-2/F., Building 1, No.222, Xuanlan Road, Xuanqiao, Pudong New District, Shanghai, China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1352.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	INFINIX MOBILITY LIMITED
Address	FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI STREET FOTAN NT HONGKONG

2.2 Manufacturer Information

Manufacturer	INFINIX MOBILITY LIMITED
Address	FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI STREET FOTAN NT HONGKONG

2.3 General Description for Equipment under Test (EUT)

Equipment Type	Mobile Phone
Model Name Under Test	X6840
Series Model Name	N/A
Description of Model Name Differentiation	N/A
Hardware Version	N/A
Software Version	N/A
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Ancillary Equipment

Ancillary Equipment 1	Battery	
	Brand Name	Infinix
	Model No.	BL-51EX
	Serial No.	N/A
	Capacity	5200 mAh
	Rated Voltage	3.85 V
	Limit Charge Voltage	4.45 V
Ancillary Equipment 2	Adapter 1	
	Brand Name	Infinix
	Model No.	U100XSA
	Serial No.	N/A
	Rated Input	100-240 V~, 0.15 A, 50/60 Hz 0.3A
	Rated Output	5 V⎓ 2 A
Ancillary Equipment 3	Adapter 2	
	Brand Name	Infinix
	Model No.	U100XSC
	Serial No.	N/A
	Rated Input	100-240 V~, 0.15 A, 50/60 Hz 0.3A
	Rated Output	5 V⎓ 2 A 10.0W
Ancillary Equipment 4	USB Cable	
	Model No.	N/A
	Length (Approx.)	1.0 m
Ancillary Equipment 5	Earphone 1	
	Length (Approx.)	1.15 m
Ancillary Equipment 6	Earphone 2	
	Length (Approx.)	1.15 m
Note 1: All Earphones are tested, only the worst data of Earphone 1 shown in this report. Note 2: All Adapters are tested, only the worst data of Adapter 1 shown in this report.		

2.5 Technical Information

Network and wireless connectivity	2G Network GSM/GPRS/EDGE 850/1900 MHz 3G Network WCDMA/HSDPA/HSUPA Band 2/4/5 4G Network LTE FDD Band 2/4/5/7/12/13/17/25/26/66 LTE TDD Band 38/41 Bluetooth, 2.4G WIFI, 5G WIFI BDS, Galileo, Glonass, GPS, SBAS, FM
Classification of equipment	Class B
Highest frequency generated or used in the device or on which the device operates or tunes(MHz)	5850 MHz

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15 Subpart B	Unintentional Radiators
2	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

3.2 Verdict

No.	Description	FCC Rule	Test Verdict	Remark
1	Radiated Emission	15.109	Pass	--
2	Conducted Emission, AC Ports	15.107	Pass	--

3.3 Decision Rule

☐ No Need

☒ Use General conformity decision rule (Consider uncertainty or not ☒ No ☐ Yes)

☐ Use Special Conformity Decision Rule (Consider uncertainty or not ☐ No ☐ Yes)

3.4 Test Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Conducted emissions (150 kHz-30 MHz)-AMN	2.6 dB
Radiated emissions (30 MHz-1 GHz)-966#1	4.2 dB
Radiated emissions (1 GHz-18 GHz) -966#1	5.3 dB
Radiated emissions (18 GHz-40 GHz) -966#1	5.6 dB

4 GENERAL TEST CONFIGURATIONS

4.1 Test Enclosure List

Description	Manufacturer	Model	Serial No.	Length	Description	Use
TF Card	N/A	N/A	N/A	N/A	N/A	☒
Laptop	DELL	N/A	N/A	N/A	N/A	☒

4.2 Test Configurations

All test modes of EUT are listed in the table below.

Test Mode Configuration	Description
Mode 1	The Rear Camera Test Mode EUT + Adapter + USB Cable + Battery + earphone + TF Card
Mode 2	The Front Camera Test Mode EUT + Adapter + USB Cable + Battery + earphone + TF Card
Mode 3	The Video Play Test Mode EUT + Adapter + USB Cable + Battery + earphone + TF Card
Mode 4	The USB Test Mode EUT + USB Cable + Battery + Laptop+ earphone + TF Card

Test Case	Test Mode Configuration	Worst Mode
Radiated emission	Mode 1~Mode 4	1, 4
Conducted emission	Mode 1~Mode 3	1
Note: Based on client request, all normal using modes of the normal function were tested, but only data of the worst mode (if test case has) was reported in this report.		

4.3 Test Setups

Test Setup 1



Radiated Emission (30 MHz-1 GHz)



Radiated Emission (above 1 GHz)

Test Setup 2



Conducted emission, AC ports

5 TEST ITEMS

5.1 Emission Tests

5.1.1 Radiated emission

5.1.1.1 Limit

Frequency range (MHz)	Class B (at 3 m)		Class A (at 3 m)
	Field Strength (μV/m)	Field Strength (dBμV/m)	Field Strength (dBμV/m)
30 - 88	100	40	49.5
88 - 216	150	43.5	54
216 - 960	200	46	56.9
Above 960	500	54	60
Note: 1) Field Strength (dBμV/m) = 20*log [Field Strength (μV/m)]. 2) In the emission tables above, the tighter limit applies at the band edges. 3) The limits using ANSI C63.4-2014. 4) For 30-1000 MHz, the CISPR quasi-peak is employed.			

For above 1000 MHz, according to the requirements of FCC 15.35, unless otherwise specified, the limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.

Frequency range (GHz)	Class B (at 3 m)			Class A (at 3 m)	
	Field Strength (μV/m)	Field Strength Average (dBμV/m)	Field Strength Peak (dBμV/m)	Field Strength Average (dBμV/m)	Field Strength Peak (dBμV/m)
1 - F_M	500	54	74	60	80
Note 1: The highest measurement frequency, F_M, in GHz, shall be determined as next Table. Note 2: Average Class A limit at 3m L_{3m} is determined by the following conversion formula: $L_{3m} = L_{10m} + 20*\log(d_{10m}/d_{3m})$ Where: L_{3m} is Average Class A limit at 3m; L_{10m} is Average Class A limit at 10m; d_{10m} is Measurement distance in 10m; d_{3m} is Measurement distance in 3m. For this case: L_{3m} = 49.5 + 20*log(10/3)=60 (dBμV/m).					

Highest internal frequency (F_X)	Highest measurement frequency (F_M)
$F_X \leq 108$ MHz	1 GHz
108 MHz $\leq F_X \leq$ 500 MHz	2 GHz
500 MHz $\leq F_X \leq$ 1 GHz	5 GHz
$F_X \geq$ 1 GHz	5 *F_X or 40 GHz, whichever is lower.
Note: F_X is Highest frequency generated or used in the device or on which the device operates or tunes.	

5.1.1.2 Test setup

Please refer to 4.2 section description of test setup of test setup 1. The photo of test setup please refer to ANNEX B.

5.1.1.3 Test procedure

1. The test employing the methods of measurement described in the publication referenced in Section 3(b) (ANSI C63.4);
2. All Radiated Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.
3. An initial pre-scan was performed in the chamber using the EMI Receiver in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by Bi-Log antenna with 2 orthogonal polarities.
4. The measurement frequency range is from 30 MHz to the 5th harmonic of the maximum frequency of the EUT internal source. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.
5. Use the following spectrum analyzer settings:
   Span = wide enough to fully capture the emission being measured
   RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz
   VBW ≥ RBW
   Sweep = auto
   Detector function = peak for f <1 GHz, peak & RMS Average for f ≥ 1 GHz
   Trace = max hold

5.1.1.4 Test result and test equipment list

Please refer to ANNEX A.1.

Note:

1. Results (dBμV/m) = Reading (dBμV/m) + Factor (dB/m)

The reading level is calculated by software which is not shown in the sheet

2. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain (dB)
3. Margin = Limit – Results

5.1.2 Conducted emission

5.1.2.1 Limit

Frequency range (MHz)	Class A		Class B	
	Quasi-peak (dBμV)	Average (dBμV)	Quasi-peak (dBμV)	Average (dBμV)
0.15 - 0.50	79	66	66 to 56	56 to 46
0.50 - 5	73	60	56	46
5 - 30	73	60	60	50

Note:

1) The lower limit shall apply at the band edges.
2) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50 MHz.
3) The limit using ANSI C63.4.

5.1.2.2 Test setup

Please refer to 4.2 section description of test setup of test setup 2. The photo of test setup please refer to ANNEX B.

5.1.2.3 Test procedure

1. The test employing the methods of measurement described in the publication referenced in Section 3(b) (ANSI C63.4);
2. The EUT is connected to the power mains through a LISN which provides 50 Ω/50 μH of coupling impedance for the measuring instrument. The test frequency range is from 150 kHz to 30 MHz. The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels that are more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed.
3. Use the following spectrum analyzer settings:
   RBW = 9 kHz
   VBW ≥ RBW
   Sweep = 10ms
   Detector function = Peak & Average
   Trace = max hold

5.1.2.4 Test result and test equipment list

Please refer to ANNEX A.2.

Note:

1. Results (dBμV) = Reading (dBμV) + Factor (dB)

The reading level is calculated by software which is not shown in the sheet

2. Factor = Insertion loss + Cable loss

3. Margin = Limit – Results

ANNEX A TEST RESULTS AND TEST EQUIPMENT LIST

A.1 Radiated emission

Note 1: Measurements shall be made with a quasi-peak measuring receiver in the frequency range 30 MHz to 1000 MHz. To reduce the testing time, a peak measuring receiver may be used instead of a quasi-peak measuring receiver. In case of dispute, measurement with a quasi-peak measuring receiver will take precedence.

Note 2: The Radiated Emission is required to be investigated to the upper frequency of 5th harmonic of the highest internal frequency of EUT or 40 GHz, whichever is lower. The test results above 18GHz are only noise and are not recorded in the report.

Sample No.	SC-SH25B0138-S04	Temperature	22.2°C
Humidity	48%RH	Test Voltage	AC 120V/60Hz
Test Engineer	Hao Longda	Test Date	2025.11.28

Test Mode 1

A.1.1 Test Antenna Vertical, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	51.873	18.29	-25.73	40.0	21.71	Peak	238.00	100	Vertical	Pass
2	100.664	26.95	-26.80	43.5	16.55	Peak	330.00	200	Vertical	Pass
3	176.664	13.00	-28.89	43.5	30.50	Peak	336.00	100	Vertical	Pass
4	260.569	17.03	-24.89	46.0	28.97	Peak	41.00	200	Vertical	Pass
5	361.158	23.00	-22.47	46.0	23.00	Peak	81.00	100	Vertical	Pass
6	784.514	28.22	-12.00	46.0	17.78	Peak	336.00	100	Vertical	Pass

A.1.2 Test Antenna Horizontal, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	45.714	14.66	-25.94	40.0	25.34	Peak	41.00	100	Horizontal	Pass
2	95.329	26.82	-27.55	43.5	16.68	Peak	244.00	200	Horizontal	Pass
3	237.774	24.60	-25.47	46.0	21.40	Peak	105.00	100	Horizontal	Pass
4	359.994	23.59	-22.52	46.0	22.41	Peak	132.00	100	Horizontal	Pass
5	570.338	22.80	-17.02	46.0	23.20	Peak	296.00	100	Horizontal	Pass
6	919.830	31.27	-9.21	46.0	14.73	Peak	65.00	100	Horizontal	Pass

Sample No.	SC-SH25B0138-S04	Temperature	22.2°C
Humidity	48%RH	Test Voltage	DC 5V From PC
Test Engineer	Hao Longda	Test Date	2025.11.28

Test Mode 4

A.1.3 Test Antenna Vertical, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	47.363	14.95	-25.78	40.0	25.05	Peak	41.00	100	Vertical	Pass
2	86.066	22.17	-30.37	40.0	17.83	Peak	325.00	100	Vertical	Pass
3	189.856	24.39	-27.23	43.5	19.11	Peak	357.00	100	Vertical	Pass
4	248.347	26.63	-24.86	46.0	19.37	Peak	204.00	200	Vertical	Pass
5	498.558	29.19	-18.23	46.0	16.81	Peak	360.00	100	Vertical	Pass
6	940.102	30.95	-9.26	46.0	15.05	Peak	141.00	200	Vertical	Pass

A.1.4 Test Antenna Horizontal, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	47.848	15.09	-25.75	40.0	24.91	Peak	335.00	100	Horizontal	Pass
2	90.431	24.20	-28.84	43.5	19.30	Peak	291.00	200	Horizontal	Pass
3	189.565	27.90	-27.29	43.5	15.60	Peak	319.00	100	Horizontal	Pass
4	256.446	29.39	-24.79	46.0	16.61	Peak	303.00	100	Horizontal	Pass
5	360.818	29.52	-22.49	46.0	16.48	Peak	6.00	100	Horizontal	Pass
6	654.825	29.01	-14.75	46.0	16.99	Peak	255.00	100	Horizontal	Pass

Equipment Information						
Equipment Name	Manufacturer	Model	Equipment No.	Cal. Date	Cal. Due	Use
EMI Receiver	KEYSIGHT	N9038A	BH-EMC-L127	2025.02.12	2026.02.11	☒
Test Antenna-Bi-Log	SCHWARZBECK	VULB 9163	BH-EMC-L132	2024.03.11	2027.03.10	☒
Anechoic Chamber	YiHeng	9m*6m*6m	BH-EMC-L001	2024.04.18	2027.04.17	☒
Description	Manufacturer	Name	Version	/		Use
Test Software	BALUN	BL410-E	V21.919	/		☒

Sample No.	SC-SH25B0138-S04	Temperature	22.2°C
Humidity	48%RH	Test Voltage	AC 120V/60Hz
Test Engineer	Hao Longda	Test Date	2025.11.28

Test Mode 1

A.1.5 Test Antenna Vertical, 1 GHz – 18 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1096.500	39.11	-15.84	74.0	34.89	Peak	256.00	100	Vertical	Pass
1**	1096.500	28.31	-15.84	54.0	25.69	AV	256.00	100	Vertical	Pass
2	2446.000	45.18	-11.78	74.0	28.82	Peak	122.00	100	Vertical	Pass
2**	2446.000	40.91	-11.78	54.0	13.09	AV	122.00	100	Vertical	Pass
3	5199.000	53.50	-0.19	74.0	20.50	Peak	165.00	100	Vertical	Pass
3**	5199.000	42.46	-0.19	54.0	11.54	AV	165.00	100	Vertical	Pass
4	7891.750	59.19	6.58	74.0	14.81	Peak	292.00	100	Vertical	Pass
4**	7891.750	47.73	6.58	54.0	6.27	AV	292.00	100	Vertical	Pass
5	9594.500	54.82	2.95	74.0	19.18	Peak	329.00	100	Vertical	Pass
5**	9594.500	45.08	2.95	54.0	8.92	AV	329.00	100	Vertical	Pass
6	16192.500	57.38	6.32	74.0	16.62	Peak	111.00	100	Vertical	Pass
6**	16192.500	47.16	6.32	54.0	6.84	AV	111.00	100	Vertical	Pass

A.1.6 Test Antenna Horizontal, 1 GHz – 18 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1179.800	39.45	-15.90	74.0	34.55	Peak	207.00	100	Horizontal	Pass
1**	1179.800	27.97	-15.90	54.0	26.03	AV	207.00	100	Horizontal	Pass
2	2426.100	43.60	-11.59	74.0	30.40	Peak	98.00	100	Horizontal	Pass
2**	2426.100	38.19	-11.59	54.0	15.81	AV	98.00	100	Horizontal	Pass
3	4782.000	51.18	-1.24	74.0	22.82	Peak	199.00	100	Horizontal	Pass
3**	4782.000	40.22	-1.24	54.0	13.78	AV	199.00	100	Horizontal	Pass
4	7323.500	58.92	5.74	74.0	15.08	Peak	266.00	100	Horizontal	Pass
4**	7323.500	47.87	5.74	54.0	6.13	AV	266.00	100	Horizontal	Pass
5	9737.000	55.80	2.15	74.0	18.20	Peak	186.00	100	Horizontal	Pass
5**	9737.000	45.69	2.15	54.0	8.31	AV	186.00	100	Horizontal	Pass
6	15533.500	58.62	6.20	74.0	15.38	Peak	316.00	100	Horizontal	Pass
6**	15533.500	47.78	6.20	54.0	6.22	AV	316.00	100	Horizontal	Pass

Sample No.	SC-SH25B0138-S04	Temperature	22.2°C
Humidity	48%RH	Test Voltage	DC 5V From PC
Test Engineer	Hao Longda	Test Date	2025.11.28

Test Mode 4

A.1.7 Test Antenna Vertical, 1 GHz – 18 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1499.500	53.17	-16.24	74.0	20.83	Peak	174.00	100	Vertical	Pass
1**	1499.500	36.44	-16.24	54.0	17.56	AV	174.00	100	Vertical	Pass
2	2371.400	53.25	-12.73	74.0	20.75	Peak	167.00	100	Vertical	Pass
2**	2371.400	37.78	-12.73	54.0	16.22	AV	167.00	100	Vertical	Pass
3	3991.250	55.26	-3.48	74.0	18.74	Peak	160.00	100	Vertical	Pass
3**	3991.250	43.04	-3.48	54.0	10.96	AV	160.00	100	Vertical	Pass
4	7473.750	58.97	5.43	74.0	15.03	Peak	271.00	100	Vertical	Pass
4**	7473.750	46.88	5.43	54.0	7.12	AV	271.00	100	Vertical	Pass
5	10582.000	57.48	4.74	74.0	16.52	Peak	293.00	100	Vertical	Pass
5**	10582.000	47.81	4.74	54.0	6.19	AV	293.00	100	Vertical	Pass
6	15955.500	58.63	5.50	74.0	15.37	Peak	0.00	100	Vertical	Pass
6**	15955.500	46.93	5.50	54.0	7.07	AV	0.00	100	Vertical	Pass

A.1.8 Test Antenna Horizontal, 1 GHz – 18 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1599.600	44.54	-16.21	74.0	29.46	Peak	276.00	100	Horizontal	Pass
1**	1599.600	28.83	-16.21	54.0	25.17	AV	276.00	100	Horizontal	Pass
2	2590.400	44.30	-10.88	74.0	29.70	Peak	274.00	100	Horizontal	Pass
2**	2590.400	33.14	-10.88	54.0	20.86	AV	274.00	100	Horizontal	Pass
3	5074.250	53.01	-0.36	74.0	20.99	Peak	188.00	100	Horizontal	Pass
3**	5074.250	41.94	-0.36	54.0	12.06	AV	188.00	100	Horizontal	Pass
4	7347.250	58.97	5.48	74.0	15.03	Peak	312.00	100	Horizontal	Pass
4**	7347.250	47.70	5.48	54.0	6.30	AV	312.00	100	Horizontal	Pass
5	9582.000	54.93	3.09	74.0	19.07	Peak	161.00	100	Horizontal	Pass
5**	9582.000	45.58	3.09	54.0	8.42	AV	161.00	100	Horizontal	Pass
6	16170.000	57.85	6.10	74.0	16.15	Peak	5.00	100	Horizontal	Pass
6**	16170.000	47.19	6.10	54.0	6.81	AV	5.00	100	Horizontal	Pass

Equipment Information						
Equipment Name	Manufacturer	Model	Equipment No.	Cal. Date	Cal. Due	Use
EMI Receiver	KEYSIGHT	N9038A	BH-EMC-L127	2025.02.12	2026.02.11	☒
EMI Receiver	KEYSIGHT	N9010B	BH-EMC-L099	2025.02.12	2026.02.11	☒
Test Antenna-Horn	SCHWARZBECK	BBHA 9120D	BH-EMC-L111	2024.03.11	2027.03.10	☒
Test Antenna-Horn	A-INFO	LB-180400-KF	BH-EMC-L061	2024.03.11	2027.03.10	☒
Anechoic Chamber	YiHeng	9m*6m*6m	BH-EMC-L001	2024.04.18	2027.04.17	☒
Description	Manufacturer	Name	Version	/		Use
Test Software	BALUN	BL410-E	V19.618	/		☒

A.2 Conducted emission

Note: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

Sample No.	SC-SH25B0138-S04	Temperature	22.5°C
Humidity	41%RH	Test Voltage	AC 120V/60Hz
Test Engineer	Hao Longda	Test Date	2025.11.28

Test Mode 1

A.2.1 AC ports - L Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.154	46.49	10.06	65.78	19.29	Peak	L	Pass
1**	0.154	28.35	10.06	55.78	27.43	AV	L	Pass
2	0.284	37.31	10.12	60.70	23.39	Peak	L	Pass
2**	0.284	22.23	10.12	50.70	28.47	AV	L	Pass
3	0.570	42.71	10.18	56.00	13.29	Peak	L	Pass
3**	0.570	26.82	10.18	46.00	19.18	AV	L	Pass
4	1.250	35.61	10.23	56.00	20.39	Peak	L	Pass
4**	1.250	21.46	10.23	46.00	24.54	AV	L	Pass
5	4.600	33.70	10.43	56.00	22.30	Peak	L	Pass
5**	4.600	19.63	10.43	46.00	26.37	AV	L	Pass
6	13.834	34.68	11.13	60.00	25.32	Peak	L	Pass
6**	13.834	22.98	11.13	50.00	27.02	AV	L	Pass

A.2.2 AC ports - N Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.158	52.52	10.15	65.57	13.05	Peak	N	Pass
1**	0.158	32.98	10.15	55.57	22.59	AV	N	Pass
2	0.238	46.79	10.15	62.17	15.38	Peak	N	Pass
2**	0.238	27.77	10.15	52.17	24.40	AV	N	Pass
3	0.572	46.61	10.19	56.00	9.39	Peak	N	Pass
3**	0.572	35.42	10.19	46.00	10.58	AV	N	Pass
4	2.336	39.63	10.26	56.00	16.37	Peak	N	Pass
4**	2.336	24.99	10.26	46.00	21.01	AV	N	Pass
5	4.696	37.29	10.42	56.00	18.71	Peak	N	Pass
5**	4.696	24.46	10.42	46.00	21.54	AV	N	Pass
6	9.574	35.92	10.89	60.00	24.08	Peak	N	Pass
6**	9.574	23.54	10.89	50.00	26.46	AV	N	Pass

Equipment Information						
Equipment Name	Manufacturer	Model	Equipment No.	Cal. Date	Cal. Due	Use
EMI Receiver	KEYSIGHT	N9038A	TJEMC144	2025.02.11	2026.02.10	☒
LISN	SCHWARZBECK	NSLK 8127	BH-EMC-L011	2025.02.11	2026.02.10	☒
10dB Limiter	SCHWARZBECK	VTSD 9561-F	BH-EMC-L014	2025.02.11	2026.02.10	☒
Shielded Room	YiHeng	4.1m*4.0m *3.2m	BH-EMC-L006	2024.02.22	2027.02.21	☒
Description	Manufacturer	Name	Version	/		Use
Test Software	BALUN	BL410-E	V21.919	/		☒

ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SH25B1334-AE.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SH25B1334-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SH25B1334-AI.PDF”.

Statement

1. The Testing Center guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.

2. For the report with Accreditation Symbol, the items marked with "☆" are not within the accredited scope.

3. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the test report stamp.

4. The test data and results are only valid for the tested samples provided by the customer.

5. This report shall not be partially reproduced without the written permission of the Testing Center.

6. Any objection shall be raised to the Testing Center within 30 days after receiving the report.

--END OF REPORT--