



FCC RADIO TEST REPORT

FCC ID: 2AIZZKY-T600PDA

Product : mobile communication terminal

Trade Name : Konying

Model Name : KY-T600PDA

Serial Model : N/A

Prepared for

Shenzhen Kang Ying Technology Co., Ltd.

Units 608, Saiba Electronic tower, No.6, Langshan 2Rd., Hi-Tech Industrial
Park North, Nanshan, Shenzhen China

Prepared by

Dongguan Yaxu(AiT) Technology Limited

No. 22, Jin QianLing Street 3, JiTiGang Village, HuangJiang
Town, DongGuan, GuangDong, China.



TEST RESULT CERTIFICATION

Applicant's name Shenzhen Kang Ying Technology Co., Ltd.
Address Units 608, Saiba Electronic tower, No.6, Langshan 2Rd., Hi-Tech
Industrial Park North, Nanshan, Shenzhen China
Manufacture's Name Shenzhen Kang Ying Technology Co., Ltd.
Address Units 608, Saiba Electronic tower, No.6, Langshan 2Rd., Hi-Tech
Industrial Park North, Nanshan, Shenzhen China

Product description

Product name mobile communication terminal
Model and/or type KY-T600PDA
reference
Serial Model N/A

Standards FCC Part15.247

Test procedure ANSI C63.10-2013

This device described above has been tested by AiT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of AiT, this document may be altered or revised by AiT, personal only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests Jun. 12 2016 ~Jun. 26 2016

Date of Issue Jun. 26 2016

Test Result **Pass**

Testing Engineer :

(Seal Chen)

Technical Manager :

(Jackie Deng)

Table of Contents	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	8
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	9
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	10
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	11
3 . EMC EMISSION TEST	13
3.1 CONDUCTED EMISSION MEASUREMENT	13
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	13
3.1.2 TEST PROCEDURE	14
3.1.3 DEVIATION FROM TEST STANDARD	14
3.1.4 TEST SETUP	14
3.1.5 EUT OPERATING CONDITIONS	14
3.1.6 TEST RESULTS	15
3.2 RADIATED EMISSION MEASUREMENT	17
3.2.1 RADIATED EMISSION LIMITS	17
3.2.2 TEST PROCEDURE	18
3.2.3 DEVIATION FROM TEST STANDARD	18
3.2.4 TEST SETUP	19
3.2.5 EUT OPERATING CONDITIONS	20
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	21
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	22
3.2.8 TEST RESULTS (1GHZ~ 10TH HARMONIC)	23
4 . POWER SPECTRAL DENSITY TEST	35
4.1 APPLIED PROCEDURES / LIMIT	35
4.1.1 TEST PROCEDURE	35
4.1.2 DEVIATION FROM STANDARD	35
4.1.3 TEST SETUP	35
4.1.4 EUT OPERATION CONDITIONS	35
4.1.5 TEST RESULTS	36



Table of Contents

Page

5 . BANDWIDTH TEST	38
5.1 APPLIED PROCEDURES / LIMIT	38
5.1.1 TEST PROCEDURE	38
5.1.2 EUT OPERATION CONDITIONS	38
5.1.3 TEST RESULTS	39
6 . PEAK OUTPUT POWER TEST	41
6.1 APPLIED PROCEDURES / LIMIT	41
6.1.1 TEST PROCEDURE	41
6.1.2 DEVIATION FROM STANDARD	41
6.1.3 TEST SETUP	41
6.1.4 EUT OPERATION CONDITIONS	41
6.1.5 TEST RESULTS	42
7 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	43
7.1 DEVIATION FROM STANDARD	43
7.2 TEST SETUP	43
7.3 EUT OPERATION CONDITIONS	44
7.4 TEST RESULTS	45
8 . ANTENNA REQUIREMENT	47
8.1 STANDARD REQUIREMENT	47
8.2 EUT ANTENNA	47
9 . EUT TEST PHOTO	48
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Peak Output Power	PASS	
15.247 (c)	Radiated Spurious Emission	PASS	
15.247 (d)	Power Spectral Density	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

1.1 TEST FACILITY

DongGuan Yaxu(AiT) Technology Limited

No. 22,JinQianLing Street 3, JiTiGang Village, Huang-Jiang Town, DongGuan, Guangdong, 523757 China.

FCC Registration No.: 248337

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95** %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	mobile communication terminal	
Model Name	KY-T600PDA	
Serial Model	N/A	
Model Difference	N/A	
Product Description	The EUT is a mobile communication terminal	
	Operation Frequency:	2402~2480MHz
	Modulation Type:	GFSK
	Bluetooth version:	4.0 BLE
	Bit Rate of Transmitter	1 Mbps
	Number Of Channel	40CH
	Antenna Designation:	Please see Note 3.
	Output Power(Conducted):	5.62dBm(PK)
	Antenna Gain (dBi)	0dbi
Channel List	Please refer to the Note 2.	
Ratings	DC 3.8V	
Adapter	M/N:MX520U,Input:100-240V, 50/60Hz, 0.35A, Output:DC 5V, 2A	
Battery	DC 3.8V, 5200mAh	
BT versions	V4.0 BLE because the firmware limitation, this product only supports BT4.0 BLE. And users can not enable other RF function by themselves.	
HW	V1.0	
SW	V1.1	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel	Frequency (MHz)
00	2402
01	2404
.....	
38	2478
39	2480

3.

Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
-----	-------	------------	--------------	-----------	------------	------

A	N/A	N/A	Internal antenna	Pogo pin connector	0	BT Antenna
---	-----	-----	------------------	--------------------	---	------------

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH00
Mode 2	CH19
Mode 3	CH39
Mode 4	BT link

For Conducted Emission	
Final Test Mode	Description
Mode 4	BT link


For Radiated Emission	
Final Test Mode	Description
Mode 1	CH00
Mode 2	CH19
Mode 3	CH39

Note:


- (1) The measurements are performed at the highest, middle, lowest available channels. Test performed by fully-charged battery.
- (2) The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Conducted Emission Test



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
E-1	mobile communication terminal	N/A	KY-T600PDA	N/A	EUT
E-2	Adapter	N/A	MX520U	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	0.8m	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

AC power line conducted test

No	Test Equipment	Manufacturer	Model No	Serial No	Cal. Date	Cal. Due Date
1	EMI Test Receiver	R&S	ESCI	100124	2015.06.29	2016.06.28
2	LISN	Kyoritsu	KNW-242	8-837-4	2015.06.29	2016.06.28
3	LISN	Kyoritsu	KNW-407	8-1789-3	2015.06.29	2016.06.28
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2015.06.29	2016.06.28

Radiation Test equipment

No	Test Equipment	Manufacturer	Model No	Serial No	Cal. Date	Cal. Due Date
1	Spectrum Analyzer	ADVANTEST	R3182	150900201	2015.06.29	2016.06.28
2	EMI Measuring Receiver	R&S	ESR	101660	2015.12.12	2016.12.11
3	Low Noise Pre Amplifier	Tsj	MLA-10K01-B01-27	1205323	2015.06.29	2016.06.28
4	Low Noise Pre Amplifier	Tsj	MLA-0120-A02-34	2648A04738	2015.12.02	2016.12.01
5	TRILOG Super Broadband test Antenna	SCHWARZBEC K	VULB9160	9160-3206	2015.12.03	2016.12.02
6	Broadband Horn Antenna	SCHWARZBEC K	BBHA9120D	452	2015.12.03	2016.12.02
7	SHF-EHF Horn	SCHWARZBEC K	BBHA9170	BBHA9170367	2015.12.03	2016.12.02
8	Loop Antenna	ARA	PLA-1030/B	1029	2015.03.20	2016.03.19
9	Radiated Cable 1# (30MHz-1GHz)	FUJIKURA	5D-2W	01	2016.01.04	2017.01.03
10	Radiated Cable 2# (1GHz -25GHz)	FUJIKURA	10D2W	02	2015.12.25	2016.12.24
11	Conducted Cable 1#(9KHz-30MHz)	FUJIKURA	1D-2W	01	2016.01.04	2017.01.03
12	SMA Antenna connector	Dosin	Dosin-SMA	N/A	N/A	N/A
13	Power Mete	Anritsu	ML2487B	110553	2015.07.10	2016.07.09



14	Power Sensor	Anritsu	MA2411B	100345	2015.07.10	2016.07.09
Note: The SMA antenna connector is soldered on the PCB board in order to perform conducted tests and this SMA antenna connector is listed in the equipment list. Low Noise Pre Amplifier : MLA-10K01-B01-27: gain :27db, frequency range:9kHz~1000MHz MLA-0120-A02-34: gain :34db, frequency range:1GHz~26.5GHz						

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes


3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

3.1.6 TEST RESULTS


EUT:	mobile communication terminal	Model Name. :	KY-T600PDA
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 5V by adapter AC120V/60Hz
Test Mode :	4	Phase:	L

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.9740	31.95	10.18	42.13	56.00	-13.87	QP	
2	0.9740	30.12	10.18	40.30	46.00	-5.70	AVG	
3	17.3980	37.69	10.42	48.11	60.00	-11.89	QP	
4 *	17.9460	34.08	10.43	44.51	50.00	-5.49	AVG	
5	25.0459	33.80	10.58	44.38	50.00	-5.62	AVG	
6	26.0220	40.11	10.61	50.72	60.00	-9.28	QP	



EUT:	mobile communication terminal	Model Name. :	KY-T600PDA
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 5V by adapter AC120V/60Hz
Test Mode :	4	Phase:	N

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.5580	23.99	10.32	34.31	56.00	-21.69	QP	
2		0.5580	22.84	10.32	33.16	46.00	-12.84	AVG	
3		2.7860	23.02	10.18	33.20	46.00	-12.80	AVG	
4		3.2060	26.65	10.18	36.83	56.00	-19.17	QP	
5		25.4700	38.60	10.59	49.19	60.00	-10.81	QP	
6		25.4700	30.20	10.59	40.79	50.00	-9.21	AVG	
7	*	25.6299	40.91	10.60	51.51	60.00	-8.49	QP	



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a)&A8.5, then the 15.209(a) limit in the table below has to be followed.

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section A8.4 (4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class A (dBuV/m) (at 3M)		Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80	60	74	54

Notes:

(1) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto

Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8m(1.5m above 1G) above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note: For radiated emission test above 1GHz:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.


Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)

EUT:	mobile communication terminal	Model Name. :	KY-T600PDA
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 3.8V by battery
Test Mode :	TX	Polarization :	--

Freq. (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	State P/F
--	--	--	--	P
--	--	--	--	P

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.


3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

EUT :	mobile communication terminal	Model Name :	KY-T600PDA
Temperature :	20 °C	Relative Humidity :	48%
Pressure:	1010 hPa	Test Voltage :	DC 3.8V by battery
Test Mode :	TX 2440(worse-case)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	42.15	21.34	6.24	27.58	40	-12.42	QP
V	95.27	25.76	11.95	37.71	43.5	-5.79	QP
V	188.64	24.22	10.36	34.58	43.5	-8.92	QP
V	581.23	17.35	14.58	31.93	46	-14.07	QP
H	98.75	25.74	5.66	31.4	43.5	-12.1	QP
H	205.44	26.88	8.86	35.74	43.5	-7.76	QP
H	337.47	25.12	10.36	35.48	46	-10.52	QP
H	584.15	23.95	14.58	38.53	46	-7.47	QP
Remark: Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit							

3.2.8 TEST RESULTS (1GHZ~ 10TH HARMONIC)


Test mode:	TX 2402 MHz	Polarization:	Horizontal
Frequency range:	1-26.5GHz		



Freq. (MHz)	Reading (dBμV)	Factor (dB)	Corrected Amplitude (dBμV/m)	Calbe Lost (dB)	Ant. Factor (dB/m)	Pr- Amp. Gain (dB)	Limit (dBμV/m)	Margin (dB)	Detector (PK/QP/AV)	Polar (H/V)
2750.08	38.13	-3.22	34.91	2.35	28.78	34.35	74	-39.09	peak	H
4804.00	43.54	5.06	48.6	3.57	36	34.51	74	-25.4	peak	H
4804.00	37.42	5.06	42.48	3.57	36	34.51	54	-11.52	AVG	H
7206.00	40.97	7.03	48	4.92	36.62	34.51	74	-26	peak	H
7206.00	29.46	7.03	36.49	4.92	36.62	34.51	54	-17.51	AVG	H
9608.00	39.07	10.63	49.7	6.15	38.81	34.33	74	-24.3	peak	H
9608.00	27.16	10.63	37.79	6.15	38.81	34.33	54	-16.21	AVG	H
12009.76	26.01	17.35	43.36	8.69	43.28	34.62	74	-30.64	peak	H
14575.98	26.13	17.63	43.76	9.69	43.2	35.26	74	-30.24	peak	H
17896.25	19.81	24.75	44.56	11.33	48.84	35.42	74	-29.44	peak	H

NOTE: No detected above 18GHz


Test mode:	TX 2402 MHz	Polarization:	Vertical
Frequency range:	1-26.5GHz		



Freq. (MHz)	Reading (dBμV)	Factor (dB)	Corrected Amplitude (dBμV/m)	Calbe Lost (dB)	Ant. Factor (dB/m)	Pr- Amp. Gain (dB)	Limit (dBμV/m)	Margin (dB)	Detector (PK/QP/AV)	Polar (H/V)
2750.08	38.13	-3.22	34.91	2.35	28.78	34.35	74	-39.09	peak	V
4804	40.04	5.06	45.1	3.57	36	34.51	74	-28.9	peak	V
4804	30.17	5.06	35.23	3.57	36	34.51	54	-18.77	AVG	V
7206	37.37	7.03	44.4	4.92	36.62	34.51	74	-29.6	peak	V
7206	28.69	7.03	35.72	4.92	36.62	34.51	54	-18.28	AVG	V
9608	33.57	10.63	44.2	6.15	38.81	34.33	74	-29.8	peak	V
9608	24.45	10.63	35.08	6.15	38.81	34.33	54	-18.92	AVG	V
16268.14	28.81	15.85	44.66	9.98	40.49	34.62	74	-29.34	peak	V
17711	19.92	24.88	44.8	11.42	48.72	35.26	74	-29.2	peak	V

NOTE: No detected above 18GHz


Test mode:	TX 2440 MHz	Polarization:	Horizontal
Frequency range:	1-26.5GHz		



Freq. (MHz)	Reading (dBμV)	Factor (dB)	Corrected Amplitude (dBμV/m)	Calbe Lost (dB)	Ant. Factor (dB/m)	Pr- Amp. Gain (dB)	Limit (dBμV/m)	Margin (dB)	Detector (PK/QP/AV)	Polar (H/V)
2750.08	38.13	-3.22	34.91	2.35	28.78	34.35	74	-39.09	peak	H
4880	41.56	5.14	46.7	3.84	35.91	34.61	74	-27.3	peak	H
4880	32.14	5.14	37.28	3.84	35.91	34.61	54	-16.72	AVG	H
7320	35.38	7.52	42.9	5.23	36.86	34.57	74	-31.1	peak	H
7320	24.16	7.52	31.68	5.23	36.86	34.57	54	-22.32	AVG	H
9760	33.24	11.36	44.6	6.45	39.6	34.69	74	-29.4	peak	H
9760	22.68	11.36	34.04	6.45	39.6	34.69	54	-19.96	AVG	H
14201.69	25.87	18.09	43.96	9.45	43.85	35.21	74	-30.04	peak	H
17038.15	24.1	20.8	44.9	11.37	45.1	35.67	74	-29.1	peak	H
2750.08	38.13	-3.22	34.91	2.35	28.78	34.35	74	-39.09	peak	H

NOTE: No detected above 18GHz


Test mode:	TX 2440 MHz	Polarization:	Vertical
Frequency range:	1-26.5GHz		



Freq. (MHz)	Reading (dBμV)	Factor (dB)	Corrected Amplitude (dBμV/m)	Calbe Lost (dB)	Ant. Factor (dB/m)	Pr- Amp. Gain (dB)	Limit (dBμV/m)	Margin (dB)	Detector (PK/QP/AV)	Polar (H/V)
1135.62	44.05	-10.75	33.3	2.14	21.57	34.46	74	-40.7	peak	V
4880.00	43.06	5.14	48.2	3.84	35.91	34.61	74	-25.8	peak	V
4880.00	31.15	5.14	36.29	3.84	35.91	34.61	54	-17.71	AVG	V
7320.00	35.48	7.52	43	5.23	36.86	34.57	74	-31	peak	V
7320.00	26.87	7.52	34.39	5.23	36.86	34.57	54	-19.61	AVG	V
9760.00	34.44	11.36	45.8	6.45	39.6	34.69	74	-28.2	peak	V
9760.00	24.33	11.36	35.69	6.45	39.6	34.69	54	-18.31	AVG	V
16268.14	28.81	15.85	44.66	9.68	41.38	35.21	74	-29.34	peak	V
17948.05	20.29	24.71	45	11.25	49.13	35.67	74	-29	peak	V

NOTE: No detected above 18GHz


Test mode:	TX 2480 MHz	Polarization:	Horizontal
Frequency range:	1-26.5GHz		



Freq. (MHz)	Reading (dBμV)	Factor (dB)	Corrected Amplitude (dBμV/m)	Calbe Lost (dB)	Ant. Factor (dB/m)	Pr- Amp. Gain (dB)	Limit (dBμV/m)	Margin (dB)	Detector (PK/QP/AV)	Polar (H/V)
2863.65	36.05	-2.55	33.5	2.41	29.61	34.57	74	-40.5	peak	H
4960.00	40.58	5.22	45.8	3.95	35.95	34.68	74	-28.2	peak	H
4960.00	29.76	5.22	34.98	3.95	35.95	34.68	54	-19.02	AVG	H
7440.00	36.54	8.06	44.6	5.64	37.14	34.72	74	-29.4	peak	H
7440.00	26.14	8.06	34.2	5.64	37.14	34.72	54	-19.8	AVG	H
9920.00	33.2	12.1	45.3	6.68	40.36	34.94	74	-28.7	peak	H
9920.00	22.36	12.1	34.46	6.68	40.36	34.94	54	-19.54	AVG	H
17507.00	19.67	25.03	44.7	11.42	49.07	35.46	74	-29.3	peak	H

NOTE: No detected above 18GHz

Test mode:	TX 2480 MHz	Polarization:	Vertical
Frequency range:	1-26.5GHz		




Freq. (MHz)	Reading (dBμV)	Factor (dB)	Corrected Amplitude (dBμV/m)	Calbe Lost (dB)	Ant. Factor (dB/m)	Pr- Amp. Gain (dB)	Limit (dBμV/m)	Margin (dB)	Detector (PK/QP/AV)	Polar (H/V)
2625.80	38.84	-4.04	34.8	2.41	28.07	34.52	74	-39.2	peak	V
4960.00	44.68	5.22	49.9	3.95	35.95	34.68	74	-24.1	peak	V
4960.00	34.32	5.22	39.54	3.95	35.95	34.68	54	-14.46	AVG	V
7440.00	36.34	8.06	44.4	5.64	37.14	34.72	74	-29.6	peak	V
7440.00	25.48	8.06	33.54	5.64	37.14	34.72	54	-20.46	AVG	V
9920.00	33.8	12.1	45.9	6.68	40.36	34.94	74	-28.1	peak	V
9920.00	23.59	12.1	35.69	6.68	40.36	34.94	54	-18.31	AVG	V
15773.00	28.04	16.56	44.6	11.24	40.8	35.48	74	-29.4	peak	V


NOTE: No detected above 18GHz

Conducted Spurious Emissions at Antenna Port:


Low Channel




Date: 13 JUN 2016 17:58:07



Date: 13 JUN 2016 17:57:42




Date: 13 JUN 2016 17:58:20




Date: 13 JUN 2016 17:58:31


Middle Channel




Date: 13 JUN 2016 17:59:14



Date: 13 JUN 2016 17:58:58






Date: 12 JUN 2016 17:59:21




Date: 12 JUN 2016 17:59:30

High Channel





Date: 12 JUN 2016 18:00:19



Date: 12 JUN 2016 18:00:29

4. POWER SPECTRAL DENSITY TEST

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C&A8.2				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS


4.1.1 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW ≥ 3 kHz.
4. Set the VBW $\geq 3 \times$ RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP



4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.


4.1.5 TEST RESULTS



EUT :	mobile communication terminal	Model Name :	KY-T600PDA
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1015 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX Mode /CH00, CH19, CH39		

Note: The relevant measured result has the offset with cable loss already.

Frequency	Power Density (dBm/100kHz)	Power Density (dBm/3kHz)	Limit (dBm/3 kHz)	Result
2402 MHz	-0.54	-14.66	8	PASS
2440 MHz	1.63	-13.57	8	PASS
2480 MHz	1.53	-13.67	8	PASS

BWCF = $10\log(3\text{ kHz}/100\text{ kHz}) = -15.2\text{ dB}$





5. BANDWIDTH TEST


5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C&A8.2				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2) &A8.2	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

5.1.1 TEST PROCEDURE

According to KDB 558074 D01 DTS Meas Guidance v03r04

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.




5.1.2 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


5.1.3 TEST RESULTS

EUT :	mobile communication terminal	Model Name :	KY-T600PDA
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX Mode /CH00, CH19, CH39		

Channel	Frequency (MHz)	6dB bandwidth (kHz)	99% bandwidth (MHz)	Limit (kHz)	Result
Low	2402	699.00	/	>500	Pass
Middle	2440	703.30	/	>500	Pass
High	2480	703.30	/	>500	Pass




TX CH 19



Date: 13 JUN 2016 17:52:21

TX CH 39



Date: 13 JUN 2016 17:52:34

6. PEAK OUTPUT POWER TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C &A8.4				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3) &A8.4	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

6.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the Power meter

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.1.5 TEST RESULTS

EUT :	mobile communication terminal	Model Name :	KY-T600PDA
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX Mode		

TX Mode			
Test Channel	Frequency	Maximum Conducted Output Power (PK)	LIMIT
	(MHz)	(dBm)	dBm
CH00	2402	4.57	30
CH19	2440	5.62	30
CH39	2480	5.55	30

7. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a)&A1.1 is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a)&A8.5, must also comply with the radiated emission limits specified in §15.209(a) &A1.1 (see §15.205(c)) &A8.5.


TEST PROCEDURE

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- Repeat above procedures until all measured frequencies were complete.

7.1 DEVIATION FROM STANDARD

No deviation.

7.2 TEST SETUP



7.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.4 TEST RESULTS


EUT :	mobile communication terminal	Model Name :	KY-T600PDA
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 3.8V

Frequency Band	Delta Peak to band emission (dBc)	> Limit (dBc)	Result
2390.00	48.7	20	Pass
2483.50	60.65	20	Pass

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
2390	48.75	1.05	49.8	74	-24.2	peak	Vertical
2390	45.16	1.05	46.21	74	-27.79	peak	Horizontal
2483.5	46.33	1.29	47.62	74	-26.38	peak	Vertical
2483.5	46.87	1.29	48.16	74	-25.84	peak	Horizontal


Note: Test method to see chapter 3.2 . When PK value is lower than the Average value limit, average not record.

Band Edge, Left Side



Date: 13 JUN 2016 17:57:19

Band Edge, Right Side



Date: 13 JUN 2016 17:56:43

8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT


15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2 EUT ANTENNA

The EUT antenna is Internal antenna with “pogo pin” antenna connector..

9. EUT TEST PHOTO

Radiated Measurement Photos



Conducted Measurement Photos

