



TEST REPORT

Applicant Name: Telpo Technology Co., Ltd.
Address: No.15, Juyuan South Road, Guicheng Street, Nanhai District,
Foshan City, Guangdong, China
Report Number: 2504A04025E-RF-00D
FCC ID: 2AJ2B-K1

Test Standard (s)

FCC PART 15.407

Sample Description

Product Name: Self-Service Kiosk
Model No.: K1, K1D, K1Q, K1P, K1DN
Trade Mark: Telpo
Received Date: 2025-12-12
Report Date: 2026-04-22

Test Result:	The EUT complied with the standards above.
--------------	--

Prepared and Checked By:

Jason Fan

Jason Fan
EMC Engineer

Approved By:

Bob. Liao

Bob.Liao
EMC Engineer

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA, or any agency of the Federal Government. The information marked “#” is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included but no need marked.
This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

Tel: +86 755-26503290

Web: www.atc-lab.com

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY..... 4

GENERAL INFORMATION..... 5

 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 5

 OBJECTIVE 6

 TEST METHODOLOGY 6

 TEST FACILITY 6

 MEASUREMENT UNCERTAINTY 6

SYSTEM TEST CONFIGURATION 7

 DESCRIPTION OF TEST CONFIGURATION..... 7

 EUT EXERCISE SOFTWARE AND POWER LEVEL # 7

 SPECIAL ACCESSORIES 8

 EQUIPMENT MODIFICATIONS..... 8

 SUPPORT EQUIPMENT LIST AND DETAILS 8

 EXTERNAL I/O CABLE..... 8

 BLOCK DIAGRAM OF TEST SETUP 8

SUMMARY OF TEST RESULTS 10

TEST EQUIPMENT LIST 11

ANTENNA REQUIREMENT 12

 APPLICABLE STANDARD..... 12

 ANTENNA CONNECTOR CONSTRUCTION 12

AC CONDUCTED EMISSIONS 13

 APPLICABLE STANDARD..... 13

 EUT SETUP..... 13

 EMI TEST RECEIVER SETUP..... 13

 TEST PROCEDURE 13

 CALCULATION 14

 TEST DATA 14

UNDESIRABLE EMISSION 17

 APPLICABLE STANDARD..... 17

 EUT SETUP..... 17

 EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP 19

 TEST PROCEDURE 19

 CALCULATION 20

 TEST DATA 20

EMISSION BANDWIDTH..... 82

 APPLICABLE STANDARD..... 82

 TEST PROCEDURE 82

 TEST DATA 83

CONDUCTED TRANSMITTER OUTPUT POWER 84

 APPLICABLE STANDARD..... 84

 TEST PROCEDURE 85

 TEST DATA 85

POWER SPECTRAL DENSITY 86

 APPLICABLE STANDARD..... 86

 TEST PROCEDURE 87

 TEST DATA 87

DUTY CYCLE..... 88

 TEST PROCEDURE 88

 TEST DATA 88

APPENDIX 89

EMISSION BANDWIDTH 90

99% OCCUPIED BANDWIDTH 94

MAXIMUM CONDUCTED OUTPUT POWER 98

POWER SPECTRAL DENSITY 99

DUTY CYCLE..... 103

EXHIBIT A-EUT PHOTOGRAPHS 106

EXHIBIT B-TEST SETUP PHOTOGRAPHS 107

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
Rev.00	2504A04025E-RF-00D	Original Report	2026-04-22

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product Name	Self-Service Kiosk
Tested Model	K1
Multiple Model	K1D, K1Q , K1P, K1DN
Model Difference [#]	The difference only lies in the model name and sales channels. Please refer to DOS letter for details. The applicant provided model "K1" for testing.
Voltage Range [#]	DC 24V from adapter
Adapter Information [#]	Model:GM130-2400500-F Input:100-240V~50/60Hz 2.5A Output:24.0V ---5.0A 120.0W
Note: There are three combinations for the same model. Combination1: Desk-Stand Appearance: master + Printer + Base plate Combination2: Floor-Stand Appearance: master + Printer + Lower Stand + Base plate Combination3: KDS Appearance: master + Interface box Note2: The worst mode after the BT pre-scan is Combination1, therefore, 5G WiFi only tests Combination1.	

Frequency Range	5G Wi-Fi: 5150-5250MHz;
Mode	802.11 a/n20/n40/ac20/ac40/ac80/ax20/ax40/ax80
Maximum Conducted Average Output Power (actual test result)	5150-5250MHz: 11.76dBm
Modulation Technique	OFDM, OFDMA
Antenna Specification [#]	Internal Antenna (It is provided by the applicant.)
	5150-5250MHz: 4.5 dBi
Sample Serial Number	For CE&RSE Test: 3ECH-1 For RF Conducted Test: 3ECH-2 (Assigned by ATC, Shenzhen)
Sample/EUT Status	Good condition
Note: The device is belong a client device.	

Objective

This type approval report is in accordance with Part 2-Subpart J, Part 15-Subparts A and E of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart E, section 15.203, 15.205, 15.207, 15.209 and 15.407 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices. And KDB789033D02 General U-NII Test Procedures New Rules v02r01.

Unless otherwise stated there are no any additions to, deviations, or exclusions from the method.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

Accredited by American Association for Laboratory Accreditation (A2LA).The Certificate Number is 4297.01.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5 %
RF Frequency		0.064×10^{-7}
RF output power, conducted		0.3 dB
Unwanted Emission, conducted		1.2 dB
AC Power Lines Conducted Emissions		2.7 dB
Emissions, Radiated	9kHz - 30MHz	2.1 dB
	30MHz - 1GHz	4.3 dB
	1GHz - 18GHz	4.9 dB
	18GHz - 26.5GHz	5.2 dB
	26.5GHz - 40GHz	4.6 dB
Temperature		1 °C
Humidity		2 %
Supply voltages		0.4 %

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The device supports 802.11a/n20/n40/ac20/ac40/ac80/ax20/ax40/ax80 mode, the n20/n40 mode was reduced test as identical parameter with ac20/ac40 mode.

For 5150-5250MHz, 7 channels are provided to testing:

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
36	5180	40	5200	44	5220	48	5240
38	5190	42	5210	46	5230	/	/

For 802.11a/ac20/ax20, Channel 36, 40 and 48 were tested.

For 802.11ac40/ax40, Channel 38, 46 were tested.

For 802.11ac80/ax80, Channel 42 was tested.

EUT Exercise Software and Power Level[#]

Exercise Software:	Engineering mode			
For 5150-5250MHz:				
Mode	Data Rate	Power Level		
		Lowest Channel	Middle Channel	Highest Channel
802.11 a	6Mbps	14	14	14
802.11 ac20	MCS0	13	13	13
802.11 ac40	MCS0	13	/	13
802.11 ac80	MCS0	/	13	/
802.11 ax20	MCS0	13	13	13
802.11 ax40	MCS0	13	/	13
802.11 ax80	MCS0	/	13	/

Note 1: The information in the above table is provided by the applicant.

Note 2: The worse-case data rates are determined to be as above for each mode based upon investigations by measuring the output power and PSD across all data rates, bandwidths and modulations.

Note 3: For 802.11 ax mode, the device not support partial RU mode.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Lenovo	Mouse	Unknown	Unknown
Lenovo	Keyboard	Unknown	Unknown
Kingston	USB disk*2	32G	Unknown

External I/O Cable


Cable Description	Shielding Type	Length (m)	From Port	To
RJ45 cable	No	5.0	EUT	LAN
USB cable	No	1.2	EUT	Mouse
USB cable	No	1.3	EUT	Keyboard
AC line	No	1.5	Adapter	AC mains
DC cable	No	1.5	Adapter	EUT

Block Diagram of Test Setup


For Conducted Emission:



For Radiated Emission Below 1GHz:



For Radiated Emission Above 1GHz:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.407(b)(9) & §15.207(a)	Conducted Emissions	Compliance
§15.205 & §15.209 & §15.407(b)	Undesirable Emission & Restricted Bands	Compliance
§15.407(a), (e)	Bandwidth	Compliance
§15.407(a)	Conducted Transmitter Output Power	Compliance
§15.407(a)	Power Spectral Density	Compliance
§15.407(h)(1)	Transmit Power Control (TPC)	Not Applicable*
§15.407(h)(2)	Dynamic Frequency Selection (DFS)	Not Applicable

Not Applicable: The EUT not operating within frequency range of 5250-5350MHz&5470-5725MHz.

Not Applicable*: The device does not support this function.

Note : The cable loss is 1dB, which was added into the all RF test results.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESCI	100784	2025/09/17	2026/09/16
Rohde & Schwarz	L.I.S.N.	ENV216	101314	2025/09/17	2026/09/16
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2025/09/18	2026/09/17
Rohde & Schwarz	Pulse Limiter	ESH3-Z2	100312	2025/05/30	2026/05/29
Unknown	RF Coaxial Cable	No.17	N0350	2025/05/30	2026/05/29
Test Software: e3 191218 (V9)					
Radiated Spurious Emission Test(Below 1GHz)					
Rohde & Schwarz	Test Receiver	ESR	102725	2025/09/18	2026/09/17
SONOMA INSTRUMENT	Amplifier	310N	186131	2026/01/20	2027/01/19
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2024/08/08	2027/08/07
Unknown	RF Coaxial Cable	No.12	N040	2025/05/30	2026/05/29
Unknown	RF Coaxial Cable	No.13	N300	2025/05/30	2026/05/29
Unknown	RF Coaxial Cable	No.14	N800	2025/05/30	2026/05/29
BACL	LOOP ANTENNA	1313-1A	3110711	2024/01/16	2027/01/15
Test Software: e3 191218 (V9)					
Radiated Spurious Emission Test(Above 1GHz)					
Rohde & Schwarz	Spectrum Analyzer	FSV40	101949	2025/09/17	2026/09/16
Decentest	Filter Switch Unit	DT7220FSU	DQ77927	2025/09/18	2026/09/17
Decentest	Multiplex Switch Test Control Set	DT7220CSU	DQ77924	2025/09/18	2026/09/17
COM-MW	Band Reject Filter	ZBSF8	12232062	2025/10/13	2026/10/12
A.H. Systems, inc.	Preamplifier	PAM-0118	226	2025/03/20	2026/03/19
Schwarzbeck	Horn Antenna	BBHA9120D	837	2023/02/22	2026/02/21
Unknown	RF Coaxial Cable	No.10	N050	2025/05/30	2026/05/29
Unknown	RF Coaxial Cable	No.11	N1000	2025/05/30	2026/05/29
Unknown	RF Coaxial Cable	No.19	N500	2025/05/30	2026/05/29
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2023/12/12	2026/12/11
BACL	Amplifier	BACL-1313-A1840	4012521	2025/05/30	2026/05/29
Unknown	RF Coaxial Cable	No.15	N600	2025/05/30	2026/05/29
Unknown	RF Coaxial Cable	No.16	N650	2025/05/30	2026/05/29
Test Software: e3 191218 (V9)					
RF Conducted test					
Rohde & Schwarz	Spectrum Analyzer	FSV-40	101590	2025/09/17	2026/09/16
Anritsu	Microwave Peak Power Sensor	MA24418A	12619	2025/03/26	2026/03/25
Anritsu	Microwave Peak Power Sensor	MA24418A	12619	2026/01/20	2027/01/19
WEINSCHL	10dB Attenuator	5324	AU 3842	2025/03/26	2026/03/25
WEINSCHL	10dB Attenuator	5324	AU 3842	2026/01/20	2027/01/19
Test Software: JDAutoTestSystem V1.0.0					

ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.407 (a), if the transmitting antennas of directional gain greater than 6dBi are used, the transmit power and power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one antenna arrangement for 5G Wi-Fi, which were permanently attached to the EUT, fulfill the requirement of this section. Please refer to the EUT photos.

Frequency Range	Antenna gain
5150-5250MHz	4.5 dBi


Result: Compliance.

AC CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207, §15.407(b) (9)

EUT Setup



- Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.
During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the LISN.
Maximizing procedure was performed on the six (6) highest emissions of the EUT.
All data was recorded in the Quasi-peak and average detection mode.

Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

Factor = LISN VDF + Cable Loss + 10dB Attenuation(Limiter)

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

Over Limit = Level - Limit

Level = Read Level + Factor

Test Data


Environmental Conditions

Temperature:	24.6℃
Relative Humidity:	42%
ATM Pressure:	100.9 kPa
TestEngineer:	Ronour Huang
TestDate:	2025-12-23
EUT Operation Mode:	5G WIFI Transmitting

Test Result: Compliance, please refer to the below data.

Note: The pre-scan maximum output power mode and channel: 5G WIFI 802.11a Low Channel was tested.


AC 120V/60Hz, Line:



Site : Shielding Room
 Condition : Line
 Job No. : 2504A04025E-RF
 Test Mode : 5G WIFI Transmitting
 Tester : Ronour Huang
 Receiver Setting: IF B/W 9kHz PK/AV

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.151	19.76	22.08	41.84	55.93	-14.09	Average
2	0.151	19.76	30.20	49.96	65.93	-15.97	QP
3	0.247	19.91	7.80	27.71	51.85	-24.14	Average
4	0.247	19.91	15.31	35.22	61.85	-26.63	QP
5	0.338	19.73	10.29	30.02	49.26	-19.24	Average
6	0.338	19.73	15.76	35.49	59.26	-23.77	QP
7	0.565	19.89	8.23	28.12	46.00	-17.88	Average
8	0.565	19.89	20.34	40.23	56.00	-15.77	QP
9	4.381	21.14	1.21	22.35	46.00	-23.65	Average
10	4.381	21.14	7.85	28.99	56.00	-27.01	QP
11	26.488	21.17	3.09	24.26	50.00	-25.74	Average
12	26.488	21.17	7.15	28.32	60.00	-31.68	QP

AC 120V/60Hz, Neutral:



Site : Shielding Room
Condition : Neutral
Job No. : 2504A04025E-RF
Test Mode : 5G WIFI Transmitting
Tester : Ronour Huang
Receiver Setting: IF B/W 9kHz PK/AV

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.162	19.86	19.89	39.75	55.37	-15.62	Average
2	0.162	19.86	28.16	48.02	65.37	-17.35	QP
3	0.213	19.93	10.57	30.50	53.11	-22.61	Average
4	0.213	19.93	20.71	40.64	63.11	-22.47	QP
5	0.314	19.87	9.47	29.34	49.86	-20.52	Average
6	0.314	19.87	15.81	35.68	59.86	-24.18	QP
7	0.579	19.95	6.66	26.61	46.00	-19.39	Average
8	0.579	19.95	17.39	37.34	56.00	-18.66	QP
9	2.354	20.52	2.10	22.62	46.00	-23.38	Average
10	2.354	20.52	8.24	28.76	56.00	-27.24	QP
11	23.140	20.89	1.62	22.51	50.00	-27.49	Average
12	23.140	20.89	6.04	26.93	60.00	-33.07	QP

UNDESIRABLE EMISSION

Applicable Standard

FCC §15.407 (b); §15.209; §15.205;


(b) Undesirable emission limits. Except as shown in paragraph (b) (7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:



- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209.

EUT Setup

9kHz - 30MHz:



30MHz - 1GHz:**Above 1GHz:**

The radiated emission performed in the 3 meters, using the setup accordance with the ANSI C63.10-2020. The specification used was the FCC 15.209, FCC 15.407 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9kHz to 40GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9kHz - 1000MHz:

Frequency Range	Measurement	RBW	Video B/W	IF B/W	Detector
9kHz - 150kHz	PK	0.3kHz	1kHz	/	PK
	QP/AV	/	/	200Hz	QP/AV
150kHz - 30MHz	PK	10kHz	30kHz	/	PK
	QP/AV	/	/	9kHz	QP/AV
30MHz - 1000MHz	PK	100kHz	300kHz	/	PK
	QP	/	/	120kHz	QP

1GHz -40GHz:

Pre-scan:

Measurement	Detector	Duty cycle	RBW	Video B/W
PK	Peak	Any	1MHz	3MHz
Ave.	Peak	>98%	1MHz	5kHz
		<98%	1MHz	≥1/T, no less than 5 kHz

Final measurement for emission identified during the pre-scan:

Measurement	Detector	Duty cycle	RBW	Video B/W
PK	Peak	Any	1MHz	3MHz
Ave.	Peak	>98%	1MHz	10Hz
		<98%	1MHz	≥1/T

Note 1: T is minimum transmission duration

Note 2: The 1GHz-18GHz testing use the notch filter.

Note 3: The band edge testing use 10dB attenuator.

Note 4: The filters and attenuators are all integrated within the filter switch unit.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

According to FCC §15.209(e), the provisions in §15.31, 15.33, and 15.35 for measuring emissions at distances other than the distances specified in the above table, determining the frequency range over which radiated emissions are to be measured, and limiting peak emissions apply to all devices operated under this part.

According to FCC§15.31 measurement standard (f)(2), at frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). This paragraph (f) shall not apply to Access BPL devices operating below 30 MHz.

For 9kHz-30MHz, test distance is 3m, extrapolation limit shall be calculated using Equation:

$$E_{\text{limit-measure}} = E_{\text{limit-Standard}} + 40 \times \log_{10}\left(\frac{d_{\text{Standard}}}{d_{\text{measure}}}\right)$$

Note 1: If the maximized peak measured value is under the QP/Average limit by more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Note 2: For above 1GHz, the test result of peak was 20dB below to the limit of peak, which can be compliant to the average limit, so just peak value was recorded.

Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\text{Over Limit/Margin} = \text{Level / Corrected Amplitude} - \text{Limit}$$

$$\text{Level / Corrected Amplitude} = \text{Read Level} + \text{Factor}$$

Test Data

For Radiated Spurious Emissions, this device is installed vertically in Y-axes orientation. It was provided by applicant. The Y-axes orientation was tested and recorded in the report.

9kHz-1GHz

Environmental Conditions


Temperature:	23.7℃
Relative Humidity:	55%
ATM Pressure:	100.7kPa
Test Engineer:	Jayden Luo
Test Date:	2026-4-15
EUT Operation Mode:	Transmitting

Test Result: Compliance, please refer to the below data.

Note 1: The Loop Antenna were tested in parallel, perpendicular, and ground-parallel. The worst orientation was parallel and the data was recorded in report.


Note 2: The maximum output power mode and channel: 5G WIFI 802.11a Low Channel was tested.

9kHz~30MHz:



Site : chamber
Condition : 3m
Job No. : 2504A04025E-RF
Polarization : Parallel Tester: Jayden Luo
Test Mode : 5G WIFI Transmitting
Receiver Setting: RBW:300Hz VBW:1kHz


	Freq	Read		Limit	Over	Remark	
		Factor	Level	Level	Line		Limit
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.015	33.49	30.33	63.82	123.93	-60.11	Peak
2	0.023	29.87	26.71	56.58	120.21	-63.63	Peak
3	0.047	23.39	27.40	50.79	114.13	-63.34	Peak
4	0.070	19.90	27.38	47.28	110.66	-63.38	Peak
5	0.094	17.04	25.07	42.11	108.11	-66.00	Peak
6	0.118	15.62	25.40	41.02	106.16	-65.14	Peak



Site : chamber
Condition : 3m
Job No. : 2504A04025E-RF
Polarization : Parallel Tester: Jayden Luo
Test Mode : 5G WIFI Transmitting
Receiver Setting: RBW:10kHz VBW:30kHz


	Freq		Read		Limit	Over	Remark
	Factor		Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.246	9.77	38.39	48.16	99.80	-51.64	Peak
2	0.464	4.02	43.56	47.58	94.28	-46.70	Peak
3	1.249	-2.72	61.37	58.65	65.50	-6.85	Peak
4	2.055	-5.41	61.86	56.45	69.54	-13.09	Peak
5	3.399	-6.02	61.77	55.75	69.54	-13.79	Peak
6	9.757	-5.39	40.93	35.54	69.54	-34.00	Peak

30MHz~1GHz:



Site : chamber
Condition: 3m HORIZONTAL
Job No. : 2504A04025E-RF Tester: Jayden Luo
Test Mode: 5G WIFI Transmitting
 : RBW:100kHz VBW:300kHz

	Freq	Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	115.169	-12.42	51.43	39.01	43.50	-4.49	QP
2	229.796	-10.51	53.43	42.92	46.00	-3.08	QP
3	344.537	-6.83	47.21	40.38	46.00	-5.62	QP
4	461.738	-4.72	45.89	41.17	46.00	-4.83	QP
5	600.110	-1.99	41.43	39.44	46.00	-6.56	QP
6	692.897	-1.12	40.94	39.82	46.00	-6.18	Peak



Site : chamber
Condition: 3m VERTICAL
Job No. : 2504A04025E-RF Tester: Jayden Luo
Test Mode: 5G WIFI Transmitting
 : RBW:100kHz VBW:300kHz

	Freq	Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	65.029	-12.40	46.31	33.91	40.00	-6.09	QP
2	115.220	-12.43	47.62	35.19	43.50	-8.31	Peak
3	230.603	-10.50	48.98	38.48	46.00	-7.52	Peak
4	345.292	-6.80	45.07	38.27	46.00	-7.73	Peak
5	445.632	-4.91	46.43	41.52	46.00	-4.48	QP
6	576.392	-2.97	40.56	37.59	46.00	-8.41	Peak

1GHz-40GHz

Environmental Conditions


Temperature:	21.4℃
Relative Humidity:	49%
ATM Pressure:	101.8 kPa
TestEngineer:	Colin Lin
TestDate:	2026-01-05
EUT Operation Mode:	Transmitting

Test Result: Compliance, please refer to the below data.

Note 1: For 1GHz-18GHz, the fundamental with band reject filter.

Note 2 : For 18GHz-40GHz, the pre-scan maximum output power mode and channel: 5G WIFI 802.11a Low Channel was tested..

5G WIFI 802.11a Low Channel 1GHz-18GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504A04025E-RF

Test Mode : Transmitting


Tester:Colin Lin

Note : 5G WIFI 802.11a Low Channel 5180MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read		Limit	Over	Remark
			Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1038.250	-14.41	67.57	53.16	74.00	-20.84	Peak
2	1558.875	-13.36	62.78	49.42	54.00	-4.58	Average
3	1558.875	-13.36	69.44	56.08	74.00	-17.92	Peak
4	4145.000	-8.15	46.16	38.01	54.00	-15.99	Average
5	4145.000	-8.15	63.03	54.88	74.00	-19.12	Peak
6	10360.000	3.99	51.04	55.03	68.20	-13.17	Peak
7	15540.000	4.85	40.37	45.22	54.00	-8.78	Average
8	15540.000	4.85	50.20	55.05	74.00	-18.95	Peak


5G WIFI 802.11a Low Channel 1GHz-18GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11a Low Channel 5180MHz 1GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1558.875	-13.36	63.44	50.08	54.00	-3.92	Average
2	1558.875	-13.36	68.51	55.15	74.00	-18.85	Peak
3	10360.000	3.99	50.69	54.68	68.20	-13.52	Peak
4	15540.000	4.85	40.20	45.05	54.00	-8.95	Average
5	15540.000	4.85	50.82	55.67	74.00	-18.33	Peak


5G WIFI 802.11a Low Channel 18GHz-40GHz_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11a Low Channel 5180MHz 18GHz-40GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq	Factor	Read		Limit	Over	Remark
		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 37918.250	7.68	50.91	58.59	68.20	-9.61	Peak
2 38949.500	6.28	39.06	45.34	54.00	-8.66	Average
3 38949.500	6.28	50.74	57.02	74.00	-16.98	Peak


5G WIFI 802.11a Low Channel 18GHz-40GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11a Low Channel 5180MHz 18GHz-40GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 38135.500	7.55	51.08	58.63	68.20	-9.57	Peak
2 38935.750	6.28	39.19	45.47	54.00	-8.53	Average
3 38935.750	6.28	51.18	57.46	74.00	-16.54	Peak

5G WIFI 802.11a Low Channel Bandedge_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504A04025E-RF

Test Mode : Transmitting


Tester:Colin Lin

Note : 5G WIFI 802.11a Low Channel 5180MHz Bandedge

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5149.475	-6.04	53.04	47.00	54.00	-7.00	Average
2	5149.475	-6.04	76.35	70.31	74.00	-3.69	Peak
3	5150.000	-6.04	53.13	47.09	54.00	-6.91	Average
4	5150.000	-6.04	76.35	70.31	74.00	-3.69	Peak


5G WIFI 802.11a Low Channel Bandedge_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11a Low Channel 5180MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5149.525	-6.04	53.01	46.97	54.00	-7.03	Average
2	5149.525	-6.04	74.20	68.16	74.00	-5.84	Peak
3	5150.000	-6.04	52.91	46.87	54.00	-7.13	Average
4	5150.000	-6.04	74.20	68.16	74.00	-5.84	Peak

5G WIFI 802.11a Middle Channel 1GHz-18GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504A04025E-RF

Test Mode : Transmitting


Tester:Colin Lin

Note : 5G WIFI 802.11a Middle Channel 5200MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1558.875	-13.36	63.17	49.81	54.00	-4.19	Average
2	1558.875	-13.36	68.99	55.63	74.00	-18.37	Peak
3	4159.875	-8.11	61.49	53.38	74.00	-20.62	Peak
4	10400.000	4.18	51.03	55.21	68.20	-12.99	Peak
5	15600.000	4.69	40.26	44.95	54.00	-9.05	Average
6	15600.000	4.69	51.48	56.17	74.00	-17.83	Peak


5G WIFI 802.11a Middle Channel 1GHz-18GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11a Middle Channel 5200MHz 1GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1558.875	-13.36	62.16	48.80	54.00	-5.20	Average
2	1558.875	-13.36	67.54	54.18	74.00	-19.82	Peak
3	10400.000	4.18	51.00	55.18	68.20	-13.02	Peak
4	15600.000	4.69	40.41	45.10	54.00	-8.90	Average
5	15600.000	4.69	50.83	55.52	74.00	-18.48	Peak


5G WIFI 802.11a High Channel 1GHz-18GHz_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11a High Channel 5240MHz 1GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1558.875	-13.36	63.65	50.29	54.00	-3.71	Average
2	1558.875	-13.36	69.27	55.91	74.00	-18.09	Peak
3	10480.000	4.01	50.99	55.00	68.20	-13.20	Peak
4	15720.000	4.85	41.43	46.28	54.00	-7.72	Average
5	15720.000	4.85	50.44	55.29	74.00	-18.71	Peak


5G WIFI 802.11a High Channel 1GHz-18GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11a High Channel 5240MHz 1GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1558.875	-13.36	62.99	49.63	54.00	-4.37	Average
2	1558.875	-13.36	67.65	54.29	74.00	-19.71	Peak
3	10480.000	4.01	51.11	55.12	68.20	-13.08	Peak
4	15720.000	4.85	41.41	46.26	54.00	-7.74	Average
5	15720.000	4.85	51.64	56.49	74.00	-17.51	Peak


5G WIFI 802.11a High Channel Bandedge_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11a High Channel 5240MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5350.000	-5.69	50.77	45.08	54.00	-8.92	Average
2	5350.000	-5.69	63.69	58.00	74.00	-16.00	Peak
3	5357.708	-5.64	50.80	45.16	54.00	-8.84	Average
4	5357.708	-5.64	63.52	57.88	74.00	-16.12	Peak


5G WIFI 802.11a High Channel Bandedge_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11a High Channel 5240MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5350.000	-5.69	50.96	45.27	54.00	-8.73	Average
2	5350.000	-5.69	63.48	57.79	74.00	-16.21	Peak
3	5352.580	-5.67	51.01	45.34	54.00	-8.66	Average
4	5352.580	-5.67	64.03	58.36	74.00	-15.64	Peak

5G WIFI 802.11ac20 Low Channel 1GHz-18GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504A04025E-RF

Test Mode : Transmitting


Tester:Colin Lin

Note : 5G WIFI 802.11ac20 Low Channel 5180MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1558.875	-13.36	62.55	49.19	54.00	-4.81	Average
2	1558.875	-13.36	68.65	55.29	74.00	-18.71	Peak
3	10360.000	3.99	50.34	54.33	68.20	-13.87	Peak
4	15540.000	4.85	40.44	45.29	54.00	-8.71	Average
5	15540.000	4.85	49.96	54.81	74.00	-19.19	Peak

5G WIFI 802.11ac20 Low Channel 1GHz-18GHz_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504A04025E-RF

Test Mode : Transmitting


Tester:Colin Lin

Note : 5G WIFI 802.11ac20 Low Channel 5180MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1558.875	-13.36	63.26	49.90	54.00	-4.10	Average
2	1558.875	-13.36	67.39	54.03	74.00	-19.97	Peak
3	10360.000	3.99	50.99	54.98	68.20	-13.22	Peak
4	15540.000	4.85	40.28	45.13	54.00	-8.87	Average
5	15540.000	4.85	50.10	54.95	74.00	-19.05	Peak


5G WIFI 802.11ac20 Low Channel Bandedge_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11ac20 Low Channel 5180MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5148.712	-6.04	52.71	46.67	54.00	-7.33	Average
2	5148.712	-6.04	73.90	67.86	74.00	-6.14	Peak
3	5150.000	-6.04	53.01	46.97	54.00	-7.03	Average
4	5150.000	-6.04	73.90	67.86	74.00	-6.14	Peak


5G WIFI 802.11ac20 Low Channel Bandedge_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11ac20 Low Channel 5180MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5148.375	-6.04	52.66	46.62	54.00	-7.38	Average
2	5148.375	-6.04	73.17	67.13	74.00	-6.87	Peak
3	5150.000	-6.04	52.96	46.92	54.00	-7.08	Average
4	5150.000	-6.04	73.17	67.13	74.00	-6.87	Peak


5G WIFI 802.11ac20 Middle Channel 1GHz-18GHz_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11ac20 Middle Channel 5200MHz 1GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1558.875	-13.36	63.04	49.68	54.00	-4.32	Average
2	1558.875	-13.36	69.05	55.69	74.00	-18.31	Peak
3	10400.000	4.18	51.11	55.29	68.20	-12.91	Peak
4	15600.000	4.69	40.10	44.79	54.00	-9.21	Average
5	15600.000	4.69	50.12	54.81	74.00	-19.19	Peak


5G WIFI 802.11ac20 Middle Channel 1GHz-18GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11ac20 Middle Channel 5200MHz 1GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1558.875	-13.36	63.21	49.85	54.00	-4.15	Average
2	1558.875	-13.36	68.79	55.43	74.00	-18.57	Peak
3	10400.000	4.18	51.18	55.36	68.20	-12.84	Peak
4	15600.000	4.69	41.15	45.84	54.00	-8.16	Average
5	15600.000	4.69	50.87	55.56	74.00	-18.44	Peak

5G WIFI 802.11ac20 High Channel 1GHz-18GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504A04025E-RF

Test Mode : Transmitting


Tester:Colin Lin

Note : 5G WIFI 802.11ac20 High Channel 5240MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1558.875	-13.36	64.55	51.19	54.00	-2.81	Average
2	1558.875	-13.36	69.59	56.23	74.00	-17.77	Peak
3	10480.000	4.01	49.90	53.91	68.20	-14.29	Peak
4	15720.000	4.85	41.79	46.64	54.00	-7.36	Average
5	15720.000	4.85	50.41	55.26	74.00	-18.74	Peak

5G WIFI 802.11ac20 High Channel 1GHz-18GHz_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504A04025E-RF

Test Mode : Transmitting


Tester:Colin Lin

Note : 5G WIFI 802.11ac20 High Channel 5240MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1558.875	-13.36	67.34	53.98	74.00	-20.02	Peak
2	10480.000	4.01	50.22	54.23	68.20	-13.97	Peak
3	15720.000	4.85	41.55	46.40	54.00	-7.60	Average
4	15720.000	4.85	50.57	55.42	74.00	-18.58	Peak

5G WIFI 802.11ac20 High Channel Bandedge_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504A04025E-RF

Test Mode : Transmitting


Tester:Colin Lin

Note : 5G WIFI 802.11ac20 High Channel 5240MHz Bandedge

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5350.000	-5.69	50.67	44.98	54.00	-9.02	Average
2	5350.000	-5.69	63.69	58.00	74.00	-16.00	Peak
3	5352.090	-5.69	51.03	45.34	54.00	-8.66	Average
4	5352.090	-5.69	63.64	57.95	74.00	-16.05	Peak


5G WIFI 802.11ac20 High Channel Bandedge_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11ac20 High Channel 5240MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5350.000	-5.69	50.94	45.25	54.00	-8.75	Average
2	5350.000	-5.69	63.45	57.76	74.00	-16.24	Peak
3	5355.748	-5.66	51.02	45.36	54.00	-8.64	Average
4	5355.748	-5.66	63.74	58.08	74.00	-15.92	Peak


5G WIFI 802.11ac40 Low Channel 1GHz-18GHz_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11ac40 Low Channel 5190MHz 1GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1558.875	-13.36	64.53	51.17	54.00	-2.83	Average
2	1558.875	-13.36	70.23	56.87	74.00	-17.13	Peak
3	10380.000	4.09	51.37	55.46	68.20	-12.74	Peak
4	15570.000	4.80	40.11	44.91	54.00	-9.09	Average
5	15570.000	4.80	49.83	54.63	74.00	-19.37	Peak


5G WIFI 802.11ac40 Low Channel 1GHz-18GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11ac40 Low Channel 5190MHz 1GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1558.875	-13.36	62.58	49.22	54.00	-4.78	Average
2	1558.875	-13.36	67.69	54.33	74.00	-19.67	Peak
3	10380.000	4.09	49.98	54.07	68.20	-14.13	Peak
4	15570.000	4.80	40.54	45.34	54.00	-8.66	Average
5	15570.000	4.80	50.16	54.96	74.00	-19.04	Peak


5G WIFI 802.11ac40 Low Channel Bandedge_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11ac40 Low Channel 5190MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5146.942	-6.03	53.21	47.18	54.00	-6.82	Average
2	5146.942	-6.03	76.85	70.82	74.00	-3.18	Peak
3	5150.000	-6.04	53.65	47.61	54.00	-6.39	Average
4	5150.000	-6.04	76.86	70.82	74.00	-3.18	Peak


5G WIFI 802.11ac40 Low Channel Bandedge_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11ac40 Low Channel 5190MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5148.015	-6.04	53.85	47.81	54.00	-6.19	Average
2	5148.015	-6.04	77.47	71.43	74.00	-2.57	Peak
3	5150.000	-6.04	54.02	47.98	54.00	-6.02	Average
4	5150.000	-6.04	77.47	71.43	74.00	-2.57	Peak

5G WIFI 802.11ac40 High Channel 1GHz-18GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504A04025E-RF

Test Mode : Transmitting


Tester:Colin Lin

Note : 5G WIFI 802.11ac40 High Channel 5230MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1558.875	-13.36	63.92	50.56	54.00	-3.44	Average
2	1558.875	-13.36	68.34	54.98	74.00	-19.02	Peak
3	10460.000	4.20	49.73	53.93	68.20	-14.27	Peak
4	15690.000	4.62	41.09	45.71	54.00	-8.29	Average
5	15690.000	4.62	51.61	56.23	74.00	-17.77	Peak


5G WIFI 802.11ac40 High Channel 1GHz-18GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11ac40 High Channel 5230MHz 1GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1558.875	-13.36	63.51	50.15	54.00	-3.85	Average
2	1558.875	-13.36	67.47	54.11	74.00	-19.89	Peak
3	10460.000	4.20	49.95	54.15	68.20	-14.05	Peak
4	15690.000	4.62	40.74	45.36	54.00	-8.64	Average
5	15690.000	4.62	50.56	55.18	74.00	-18.82	Peak


5G WIFI 802.11ac40 High Channel Bandedge_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11ac40 High Channel 5230MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5350.000	-5.69	51.55	45.86	54.00	-8.14	Average
2	5350.000	-5.69	64.06	58.37	74.00	-15.63	Peak
3	5356.319	-5.66	51.25	45.59	54.00	-8.41	Average
4	5356.319	-5.66	63.67	58.01	74.00	-15.99	Peak


5G WIFI 802.11ac40 High Channel Bandedge_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11ac40 High Channel 5230MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5350.000	-5.69	51.12	45.43	54.00	-8.57	Average
2	5350.000	-5.69	63.63	57.94	74.00	-16.06	Peak
3	5352.715	-5.67	51.31	45.64	54.00	-8.36	Average
4	5352.715	-5.67	63.43	57.76	74.00	-16.24	Peak

5G WIFI 802.11ac80 Middle Channel 1GHz-18GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504A04025E-RF


Test Mode : TransmittingTester:Colin Lin

Note : 5G WIFI 802.11ac80 Middle Channel 5210MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1038.250	-14.41	67.80	53.39	74.00	-20.61	Peak
2	1558.875	-13.36	62.92	49.56	54.00	-4.44	Average
3	1558.875	-13.36	68.71	55.35	74.00	-18.65	Peak
4	4168.375	-8.03	48.90	40.87	54.00	-13.13	Average
5	4168.375	-8.03	65.25	57.22	74.00	-16.78	Peak
6	10420.000	4.22	50.92	55.14	68.20	-13.06	Peak
7	15630.000	4.68	40.68	45.36	54.00	-8.64	Average
8	15630.000	4.68	50.89	55.57	74.00	-18.43	Peak

5G WIFI 802.11ac80 Middle Channel 1GHz-18GHz_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504A04025E-RF

Test Mode : Transmitting


Tester:Colin Lin

Note : 5G WIFI 802.11ac80 Middle Channel 5210MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1558.875	-13.36	63.65	50.29	54.00	-3.71	Average
2	1558.875	-13.36	68.38	55.02	74.00	-18.98	Peak
3	10420.000	4.22	50.63	54.85	68.20	-13.35	Peak
4	15630.000	4.68	41.04	45.72	54.00	-8.28	Average
5	15630.000	4.68	50.25	54.93	74.00	-19.07	Peak

5G WIFI 802.11ac80 Middle Channel Bandedge_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504A04025E-RF

Test Mode : Transmitting


Tester:Colin Lin

Note : 5G WIFI 802.11ac80 Middle Channel 5210MHz Bandedge

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5150.000	-6.04	53.11	47.07	54.00	-6.93	Average
2	5150.000	-6.04	75.80	69.76	74.00	-4.24	Peak
3	5350.000	-5.69	51.26	45.57	54.00	-8.43	Average
4	5350.000	-5.69	64.68	58.99	74.00	-15.01	Peak
5	5353.500	-5.67	51.30	45.63	54.00	-8.37	Average
6	5353.500	-5.67	63.91	58.24	74.00	-15.76	Peak


5G WIFI 802.11ac80 Middle Channel Bandedge_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11ac80 Middle Channel 5210MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5150.000	-6.04	53.92	47.88	54.00	-6.12	Average
2	5150.000	-6.04	76.24	70.20	74.00	-3.80	Peak
3	5350.000	-5.69	51.37	45.68	54.00	-8.32	Average
4	5350.000	-5.69	64.99	59.30	74.00	-14.70	Peak

5G WIFI 802.11ax20 Low Channel 1GHz-18GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504A04025E-RF

Test Mode : Transmitting


Tester:Colin Lin

Note : 5G WIFI 802.11ax20 Low Channel 5180MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1558.875	-13.36	64.48	51.12	54.00	-2.88	Average
2	1558.875	-13.36	69.30	55.94	74.00	-18.06	Peak
3	10360.000	3.99	51.40	55.39	68.20	-12.81	Peak
4	15540.000	4.85	40.14	44.99	54.00	-9.01	Average
5	15540.000	4.85	50.06	54.91	74.00	-19.09	Peak


5G WIFI 802.11ax20 Low Channel 1GHz-18GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11ax20 Low Channel 5180MHz 1GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1558.875	-13.36	67.12	53.76	74.00	-20.24	Peak
2	10360.000	3.99	51.39	55.38	68.20	-12.82	Peak
3	15540.000	4.85	40.58	45.43	54.00	-8.57	Average
4	15540.000	4.85	50.79	55.64	74.00	-18.36	Peak


5G WIFI 802.11ax20 Low Channel Bandedge_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11ax20 Low Channel 5180MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5148.550	-6.04	52.81	46.77	54.00	-7.23	Average
2	5148.550	-6.04	73.23	67.19	74.00	-6.81	Peak
3	5150.000	-6.04	53.01	46.97	54.00	-7.03	Average
4	5150.000	-6.04	73.23	67.19	74.00	-6.81	Peak


5G WIFI 802.11ax20 Low Channel Bandedge_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11ax20 Low Channel 5180MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5146.538	-6.03	53.01	46.98	54.00	-7.02	Average
2	5146.538	-6.03	74.70	68.67	74.00	-5.33	Peak
3	5150.000	-6.04	52.59	46.55	54.00	-7.45	Average
4	5150.000	-6.04	74.71	68.67	74.00	-5.33	Peak


5G WIFI 802.11ax20 Middle Channel 1GHz-18GHz_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11ax20 Middle Channel 5200MHz 1GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1558.875	-13.36	64.16	50.80	54.00	-3.20	Average
2	1558.875	-13.36	68.65	55.29	74.00	-18.71	Peak
3	10400.000	4.18	51.00	55.18	68.20	-13.02	Peak
4	15600.000	4.69	40.51	45.20	54.00	-8.80	Average
5	15600.000	4.69	50.30	54.99	74.00	-19.01	Peak


5G WIFI 802.11ax20 Middle Channel 1GHz-18GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11ax20 Middle Channel 5200MHz 1GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1558.875	-13.36	67.25	53.89	74.00	-20.11	Peak
2	10400.000	4.18	50.44	54.62	68.20	-13.58	Peak
3	15600.000	4.69	40.25	44.94	54.00	-9.06	Average
4	15600.000	4.69	50.47	55.16	74.00	-18.84	Peak

5G WIFI 802.11ax20 High Channel 1GHz-18GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504A04025E-RF


Test Mode : TransmittingTester:Colin Lin

Note : 5G WIFI 802.11ax20 High Channel 5240MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1558.875	-13.36	64.21	50.85	54.00	-3.15	Average
2	1558.875	-13.36	69.04	55.68	74.00	-18.32	Peak
3	10480.000	4.01	50.51	54.52	68.20	-13.68	Peak
4	15720.000	4.85	41.57	46.42	54.00	-7.58	Average
5	15720.000	4.85	51.19	56.04	74.00	-17.96	Peak

5G WIFI 802.11ax20 High Channel 1GHz-18GHz_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504A04025E-RF

Test Mode : Transmitting


Tester:Colin Lin

Note : 5G WIFI 802.11ax20 High Channel 5240MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1558.875	-13.36	61.56	48.20	54.00	-5.80	Average
2	1558.875	-13.36	67.79	54.43	74.00	-19.57	Peak
3	10480.000	4.01	50.03	54.04	68.20	-14.16	Peak
4	15720.000	4.85	41.77	46.62	54.00	-7.38	Average
5	15720.000	4.85	51.69	56.54	74.00	-17.46	Peak


5G WIFI 802.11ax20 High Channel Bandedge_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11ax20 High Channel 5240MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5350.000	-5.69	51.02	45.33	54.00	-8.67	Average
2	5350.000	-5.69	63.74	58.05	74.00	-15.95	Peak
3	5358.618	-5.64	50.79	45.15	54.00	-8.85	Average
4	5358.618	-5.64	64.01	58.37	74.00	-15.63	Peak


5G WIFI 802.11ax20 High Channel Bandedge_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11ax20 High Channel 5240MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5350.000	-5.69	50.66	44.97	54.00	-9.03	Average
2	5350.000	-5.69	63.57	57.88	74.00	-16.12	Peak

5G WIFI 802.11ax40 Low Channel 1GHz-18GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504A04025E-RF

Test Mode : Transmitting


Tester:Colin Lin

Note : 5G WIFI 802.11ax40 Low Channel 5190MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1558.875	-13.36	64.50	51.14	54.00	-2.86	Average
2	1558.875	-13.36	69.22	55.86	74.00	-18.14	Peak
3	10380.000	4.09	51.09	55.18	68.20	-13.02	Peak
4	15570.000	4.80	40.47	45.27	54.00	-8.73	Average
5	15570.000	4.80	50.49	55.29	74.00	-18.71	Peak
6	17887.380	8.28	39.66	47.94	54.00	-6.06	Average
7	17887.380	8.28	51.27	59.55	74.00	-14.45	Peak

5G WIFI 802.11ax40 Low Channel 1GHz-18GHz_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504A04025E-RF

Test Mode : Transmitting


Tester:Colin Lin

Note : 5G WIFI 802.11ax40 Low Channel 5190MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1558.875	-13.36	63.87	50.51	54.00	-3.49	Average
2	1558.875	-13.36	68.78	55.42	74.00	-18.58	Peak
3	10380.000	4.09	50.69	54.78	68.20	-13.42	Peak
4	15570.000	4.80	40.21	45.01	54.00	-8.99	Average
5	15570.000	4.80	50.51	55.31	74.00	-18.69	Peak
6	17895.880	8.27	39.64	47.91	54.00	-6.09	Average
7	17895.880	8.27	50.76	59.03	74.00	-14.97	Peak

5G WIFI 802.11ax40 Low Channel Bandedge_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504A04025E-RF

Test Mode : Transmitting


Tester:Colin Lin

Note : 5G WIFI 802.11ax40 Low Channel 5190MHz Bandedge

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5150.000	-6.04	53.43	47.39	54.00	-6.61	Average
2	5150.000	-6.04	78.35	72.31	74.00	-1.69	Peak


5G WIFI 802.11ax40 Low Channel Bandedge_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11ax40 Low Channel 5190MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5143.808	-6.03	52.90	46.87	54.00	-7.13	Average
2	5143.808	-6.03	74.41	68.38	74.00	-5.62	Peak
3	5150.000	-6.04	53.70	47.66	54.00	-6.34	Average
4	5150.000	-6.04	74.42	68.38	74.00	-5.62	Peak

5G WIFI 802.11ax40 High Channel 1GHz-18GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504A04025E-RF

Test Mode : Transmitting


Tester:Colin Lin

Note : 5G WIFI 802.11ax40 High Channel 5230MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1558.875	-13.36	62.77	49.41	54.00	-4.59	Average
2	1558.875	-13.36	68.38	55.02	74.00	-18.98	Peak
3	10460.000	4.20	49.92	54.12	68.20	-14.08	Peak
4	15690.000	4.62	41.42	46.04	54.00	-7.96	Average
5	15690.000	4.62	50.74	55.36	74.00	-18.64	Peak
6	17736.500	7.74	39.80	47.54	54.00	-6.46	Average
7	17736.500	7.74	50.92	58.66	74.00	-15.34	Peak


5G WIFI 802.11ax40 High Channel 1GHz-18GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11ax40 High Channel 5230MHz 1GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1558.875	-13.36	63.32	49.96	54.00	-4.04	Average
2	1558.875	-13.36	68.39	55.03	74.00	-18.97	Peak
3	10460.000	4.20	49.96	54.16	68.20	-14.04	Peak
4	15690.000	4.62	41.12	45.74	54.00	-8.26	Average
5	15690.000	4.62	51.14	55.76	74.00	-18.24	Peak
6	17719.500	7.69	40.24	47.93	54.00	-6.07	Average
7	17719.500	7.69	51.46	59.15	74.00	-14.85	Peak


5G WIFI 802.11ax40 High Channel Bandedge_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11ax40 High Channel 5230MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5350.000	-5.69	51.16	45.47	54.00	-8.53	Average
2	5350.000	-5.69	63.57	57.88	74.00	-16.12	Peak
3	5356.551	-5.66	51.30	45.64	54.00	-8.36	Average
4	5356.551	-5.66	65.11	59.45	74.00	-14.55	Peak


5G WIFI 802.11ax40 High Channel Bandedge_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504A04025E-RF
Test Mode : Transmitting Tester:Colin Lin
Note : 5G WIFI 802.11ax40 High Channel 5230MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5350.000	-5.69	51.46	45.77	54.00	-8.23	Average
2	5350.000	-5.69	63.77	58.08	74.00	-15.92	Peak
3	5352.018	-5.69	51.35	45.66	54.00	-8.34	Average
4	5352.018	-5.69	64.16	58.47	74.00	-15.53	Peak

5G WIFI 802.11ax80 Middle Channel 1GHz-18GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504A04025E-RF

Test Mode : Transmitting


Tester:Colin Lin

Note : 5G WIFI 802.11ax80 Middle Channel 5210MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1038.250	-14.41	67.97	53.56	74.00	-20.44	Peak
2	1558.875	-13.36	63.73	50.37	54.00	-3.63	Average
3	1558.875	-13.36	68.55	55.19	74.00	-18.81	Peak
4	10420.000	4.22	50.38	54.60	68.20	-13.60	Peak
5	15630.000	4.68	39.98	44.66	54.00	-9.34	Average
6	15630.000	4.68	50.38	55.06	74.00	-18.94	Peak
7	17968.130	8.27	40.31	48.58	54.00	-5.42	Average
8	17968.130	8.27	50.92	59.19	74.00	-14.81	Peak

5G WIFI 802.11ax80 Middle Channel 1GHz-18GHz_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504A04025E-RF

Test Mode : Transmitting


Tester:Colin Lin

Note : 5G WIFI 802.11ax80 Middle Channel 5210MHz 1GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1558.875	-13.36	63.90	50.54	54.00	-3.46	Average
2	1558.875	-13.36	67.82	54.46	74.00	-19.54	Peak
3	10420.000	4.22	50.83	55.05	68.20	-13.15	Peak
4	15630.000	4.68	41.41	46.09	54.00	-7.91	Average
5	15630.000	4.68	50.91	55.59	74.00	-18.41	Peak
6	17953.250	8.18	40.08	48.26	54.00	-5.74	Average
7	17953.250	8.18	50.99	59.17	74.00	-14.83	Peak

5G WIFI 802.11ax80 Middle Channel Bandedge_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504A04025E-RF


Test Mode : TransmittingTester:Colin Lin

Note : 5G WIFI 802.11ax80 Middle Channel 5210MHz Bandedge

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5150.000	-6.04	52.71	46.67	54.00	-7.33	Average
2	5150.000	-6.04	73.03	66.99	74.00	-7.01	Peak
3	5350.000	-5.69	51.18	45.49	54.00	-8.51	Average
4	5350.000	-5.69	64.70	59.01	74.00	-14.99	Peak

5G WIFI 802.11ax80 Middle Channel Bandedge_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504A04025E-RF

Test Mode : TransmittingTester:Colin Lin

Note : 5G WIFI 802.11ax80 Middle Channel 5210MHz Bandedge

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	5126.455	-5.99	53.74	47.75	54.00	-6.25	Average
2	5126.455	-5.99	74.45	68.46	74.00	-5.54	Peak
3	5150.000	-6.04	53.00	46.96	54.00	-7.04	Average
4	5150.000	-6.04	74.31	68.27	74.00	-5.73	Peak
5	5350.000	-5.69	51.16	45.47	54.00	-8.53	Average
6	5350.000	-5.69	66.08	60.39	74.00	-13.61	Peak

EMISSION BANDWIDTH

Applicable Standard

According to FCC §15.407(a), the maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

According to FCC §15.407(e), Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure

According to KDB789033 D02 section II.C. and section II.D.

1. Emission Bandwidth (EBW)

- a) Set RBW = approximately 1% of the emission bandwidth.
- b) Set the VBW > RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

2. Minimum Emission Bandwidth for the band 5.725-5.85 GHz

Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.725-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


3. 99% Occupied Bandwidth

The 99% occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. Measurement of the 99% occupied bandwidth is *required* only as a condition for using the optional bandedge measurement techniques described in II.G.3.d). Measurements of 99% occupied bandwidth may also optionally be used in lieu of the EBW to define the minimum frequency range over which the spectrum is integrated when measuring maximum conducted output power as described in II.E. However, the EBW must be measured to determine bandwidth dependent limits on maximum conducted output power in accordance with Section 15.407(a).

The following procedure shall be used for measuring (99%) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1% to 5% of the OBW
4. Set VBW $\geq 3 \times$ RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99% power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99% power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

Note: For devices that use channel aggregation refer to III.A and III.C for determining 99% bandwidth.



Note: Offset = RF cable loss(1.0dB[#]) + Attenuator(10dB)

Test Data

Test Result: Compliance. Please refer to the Appendix.

CONDUCTED TRANSMITTER OUTPUT POWER

Applicable Standard

According to FCC §15.407(a)

For an indoor access point operating in the band 5.15–5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For client devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For an outdoor access point operating in the band 5.15–5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).


For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

According to KDB789033 D02 section II.E.3.a).

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Note: Offset = RF cable loss(1.0dB[#]) + Attenuator(10dB)

Test Data

Test Result: Compliance. Please refer to the Appendix.

POWER SPECTRAL DENSITY

Applicable Standard

According to FCC §15.407(a)

For an indoor access point operating in the band 5.15–5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For an outdoor access point operating in the band 5.15–5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

For client devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01

Duty cycle $\geq 98\%$


KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-1 should be applied.

Duty cycle $< 98\%$, duty cycle variations are less than $\pm 2\%$

KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-2 should be applied.

Duty cycle $< 98\%$, duty cycle variations exceed $\pm 2\%$

KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-3 should be applied.



Note: Offset = RF cable loss(1.0dB[#]) + Attenuator(10dB)

Test Data

Test Result: Compliance. Please refer to the Appendix.


DUTY CYCLE

Test Procedure

According to ANSI C63.10-2020 Section 11.6

Measurements of duty cycle and transmission duration shall be performed using one of the following techniques:

- a) A diode detector and an oscilloscope that together have a sufficiently short response time to permit accurate measurements of the ON and OFF times of the transmitted signal.
- b) The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:
 - 1) Set the center frequency of the instrument to the center frequency of the transmission.
 - 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
 - 3) Set $VBW \geq RBW$. Set detector = peak or average.
 - 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)



Note: Offset = RF cable loss(1.0dB[#]) + Attenuator(10dB)

Test Data

Test Result: Compliance. Please refer to the Appendix.

APPENDIX

Test Information:

Sample No.:	3ECH-2	Test Date:	2026/01/13~2026/04/22
Test Site:	RF	Test Mode:	Transmitting
Tester:	Benny Li	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	19.6~24.8	Relative Humidity: (%)	46~51	ATM Pressure: (kPa)	100.7~101.8
----------------------	-----------	------------------------------	-------	------------------------	-------------

Emission Bandwidth


26dB Emission Bandwidth

5150-5250MHz

Mode	Test Frequency (MHz)	Result (MHz)
802.11a	5180	25.610
	5200	25.139
	5240	25.551
802.11ac20	5180	27.294
	5200	27.297
	5240	27.169
802.11ac40	5190	46.927
	5230	46.927
802.11ac80	5210	88.088
802.11ax20_RU_Full	5180	26.114
	5200	26.217
	5240	26.021
802.11ax40_RU_Full	5190	45.486
	5230	45.646
802.11ax80_RU_Full	5210	88.408


5150-5250MHz

802.11a_5180MHz




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 22.APR.2026 11:14:01

802.11a_5200MHz




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 22.APR.2026 11:14:38

802.11a_5240MHz




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 22.APR.2026 11:15:27

802.11ac20_5180MHz




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 22.APR.2026 11:19:36

802.11ac20_5200MHz




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 22.APR.2026 11:22:05

802.11ac20_5240MHz




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 22.APR.2026 11:22:47

802.11ac40_5190MHz




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 22.APR.2026 11:42:32

802.11ac40_5230MHz




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 22.APR.2026 11:42:57

802.11ac80_5210MHz




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 22.APR.2026 11:43:24

802.11ax20_5180MHz_RU_Full




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 22.APR.2026 11:34:08

802.11ax20_5200MHz_RU_Full




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 22.APR.2026 11:34:50

802.11ax20_5240MHz_RU_Full




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 22.APR.2026 11:35:19

802.11ax40_5190MHz_RU_Full




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 22.APR.2026 11:35:45

802.11ax40_5230MHz_RU_Full



ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 22.APR.2026 11:36:23

802.11ax80_5210MHz_RU_Full



ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 22.APR.2026 11:40:50

99% Occupied Bandwidth


5150-5250MHz

Mode	Test Frequency (MHz)	99% OBW (MHz)
802.11a	5180	16.700
	5200	16.650
	5240	16.750
802.11ac20	5180	17.950
	5200	17.950
	5240	18
802.11ac40	5190	36.700
	5230	36.800
802.11ac80	5210	76.200
802.11ax20_RU_Full	5180	19.100
	5200	19.100
	5240	19.200
802.11ax40_RU_FULL	5190	38
	5230	38
802.11ax80_RU_Full	5210	77.600

Note:
The 99% Occupied Bandwidth have not fall into the band 5250-5350MHz, please refer to the test plots of 99% Occupied Bandwidth.


5150-5250MHz

802.11a_5180MHz




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 16:34:54

802.11a_5200MHz




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 16:36:02

802.11a_5240MHz




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 16:37:06

802.11ac20_5180MHz




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 16:57:29

802.11ac20_5200MHz




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 16:58:36

802.11ac20_5240MHz




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 16:59:42

802.11ac40_5190MHz




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 17:01:02

802.11ac40_5230MHz




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 17:02:01

802.11ac80_5210MHz




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 17:03:05

802.11ax20_5180MHz_RU_Full




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 16:40:46

802.11ax20_5200MHz_RU_Full




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 16:43:25

802.11ax20_5240MHz_RU_Full




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 16:44:40

802.11ax40_5190MHz_RU_FULL




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 16:54:13

802.11ax40_5230MHz_RU_FULL



ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 16:55:17

802.11ax80_5210MHz_RU_Full



ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 16:51:09

Maximum Conducted Output Power

5150-5250MHz

Mode	Test Frequency (MHz)	Average Output Power(dBm)	Limit (dBm)	Verdict
802.11a	5180	11.76	24	Pass
	5200	11.19	24	Pass
	5240	11.23	24	Pass
802.11ac20	5180	10.22	24	Pass
	5200	10.73	24	Pass
	5240	9.99	24	Pass
802.11ac40	5190	10.43	24	Pass
	5230	10.25	24	Pass
802.11ac80	5210	10.32	24	Pass
802.11ax20_RU_Full	5180	10.25	24	Pass
	5200	10.21	24	Pass
	5240	9.89	24	Pass
802.11ax40_RU_FULL	5190	10.35	24	Pass
	5230	10.26	24	Pass
802.11ax80_RU_Full	5210	10.11	24	Pass

Power Spectral Density


5150-5250MHz

Mode	Test Frequency (MHz)	Reading (dBm/MHz)	Duty Cycle Factor(dB)	Result (dBm/MHz)	Limit (dBm/MHz)	Verdict
802.11a	5180	-7.73	9.17	1.44	11	Pass
	5200	-7.25	9.17	1.92	11	Pass
	5240	-7.13	9.17	2.04	11	Pass
802.11ac20	5180	-4.83	4.73	-0.10	11	Pass
	5200	-4.94	4.73	-0.21	11	Pass
	5240	-5.21	4.73	-0.48	11	Pass
802.11ac40	5190	-8.12	4.84	-3.28	11	Pass
	5230	-8.38	4.84	-3.54	11	Pass
802.11ac80	5210	-11.68	5.08	-6.60	11	Pass
802.11ax20_RU_Full	5180	-5.79	5.57	-0.22	11	Pass
	5200	-6.01	5.57	-0.44	11	Pass
	5240	-6.00	5.57	-0.43	11	Pass
802.11ax40_RU_FULL	5190	-8.77	5.56	-3.21	11	Pass
	5230	-8.45	5.56	-2.89	11	Pass
802.11ax80_RU_Full	5210	-11.82	5.71	-6.11	11	Pass

Result = Reading + Duty Cycle Factor


5150-5250MHz

802.11a_5180MHz




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 16:35:27

802.11a_5200MHz




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 16:36:32

802.11a_5240MHz




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 16:37:35

802.11ac20_5180MHz




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 16:58:06

802.11ac20_5200MHz




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 16:59:11

802.11ac20_5240MHz




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 17:00:17

802.11ac40_5190MHz




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 17:01:25

802.11ac40_5230MHz




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 17:02:24

802.11ac80_5210MHz




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 17:03:32

802.11ax20_5180MHz_RU_Full




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 16:41:22

802.11ax20_5200MHz_RU_Full




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 16:43:59

802.11ax20_5240MHz_RU_Full




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 16:45:13

802.11ax40_5190MHz_RU_FULL




ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 16:54:41

802.11ax40_5230MHz_RU_FULL



ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 16:55:49

802.11ax80_5210MHz_RU_Full



ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 16:51:36

Duty Cycle


5150-5250MHz

Mode	Test Frequency (MHz)	Ton (ms)	Ton+Toff (ms)	Duty Cycle (%)	Duty Cycle Factor(dB)	1/Ton (Hz)	VBW Setting (kHz)
802.11a	5200	1.381	11.407	12.11	9.17	724	1
802.11ac20	5200	5.078	15.105	33.62	4.73	197	0.200
802.11ac40	5190	4.891	14.920	32.78	4.84	204	0.300
802.11ac80	5210	4.505	14.526	31.01	5.08	222	0.300
802.11ax20_RU_FULL	5200	3.855	13.886	27.76	5.57	259	0.300
802.11ax40_RU_FULL	5190	3.859	13.890	27.78	5.56	259	0.300
802.11ax80_RU_FULL	5210	3.682	13.713	26.85	5.71	272	0.300

Duty Cycle = Ton/(Ton+Toff)*100%


5150-5250MHz

802.11a_5200MHz




ProjectNo.:2504A04025E-RF Tester:Benny LI
Date: 13.JAN.2026 16:12:20

802.11ac20_5200MHz




ProjectNo.:2504A04025E-RF Tester:Benny LI
Date: 13.JAN.2026 16:31:37

802.11ac40_5190MHz




ProjectNo.:2504A04025E-RF Tester:Benny LI
Date: 13.JAN.2026 16:32:22

802.11ac80_5210MHz




ProjectNo.:2504A04025E-RF Tester:Benny LI
Date: 13.JAN.2026 16:33:03

802.11ax20_5200MHz_RU_FULL




ProjectNo.:2504A04025E-RF Tester:Benny LI
Date: 13.JAN.2026 16:14:30

802.11ax40_5190MHz_RU_FULL



ProjectNo.:2504A04025E-RF Tester:Benny LI
Date: 13.JAN.2026 16:16:06

802.11ax80_5210MHz_RU_FULL



ProjectNo.:2504A04025E-RF Tester:Benny Li
Date: 13.JAN.2026 16:25:56

EXHIBIT A-EUT PHOTOGRAPHS

Please refer to the Attachment No.1 2504A04025E-RF EUT External Photos and Attachment No.2 2504A04025E-RF EUT Internal Photos.

EXHIBIT B-TEST SETUP PHOTOGRAPHS

Please refer to the Attachment No.4 2504A04025E-RF-00B Test Photos.

******* END OF REPORT *******