

TEST REPORT

Applicant Name: Telepower Communication Co., Ltd.
Address: 5 Bld, Zone A, Hantian Technology Town No.17 ShenHai RD,
Nanhai District Foshan China
Report Number: 2401S54552E-RF-00A
FCC ID: 2AJ2B-M8

Test Standard (s)

FCC PART 15.247

Sample Description

Product Type: POS Terminal
Model No.: M8
Multiple Model(s) No.: N/A
Trade Mark: Telpo
Date Received: 2024/04/25
Issue Date: 2024/07/12

Test Result:	Pass▲
--------------	-------

▲ In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Gala Liu

Gala Liu
RF Engineer

Approved By:

Nancy Wang

Nancy Wang
RF Supervisor

Note: The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.

This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

Bay Area Compliance Laboratories Corp. (Shenzhen)

5F(B-West), 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China

Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	6
TEST FACILITY	6
SYSTEM TEST CONFIGURATION	7
DESCRIPTION OF TEST CONFIGURATION	7
EUT EXERCISE SOFTWARE	7
SPECIAL ACCESSORIES	7
EQUIPMENT MODIFICATIONS	7
SUPPORT EQUIPMENT LIST AND DETAILS	8
EXTERNAL I/O CABLE	8
BLOCK DIAGRAM OF TEST SETUP	9
SUMMARY OF TEST RESULTS	10
TEST EQUIPMENT LIST	11
FCC §15.247 (I), §1.1307 (B) (1) & §2.1093 - RF EXPOSURE	12
APPLICABLE STANDARD	12
MEASUREMENT RESULT	12
FCC §15.203 - ANTENNA REQUIREMENT	13
APPLICABLE STANDARD	13
ANTENNA CONNECTOR CONSTRUCTION	13
FCC §15.207 (A) - AC LINE CONDUCTED EMISSIONS	14
APPLICABLE STANDARD	14
EUT SETUP	14
EMI TEST RECEIVER SETUP	14
TEST PROCEDURE	14
FACTOR & OVER LIMIT CALCULATION	15
TEST DATA	15
FCC §15.205, §15.209 & §15.247(D) - RADIATED EMISSIONS	18
APPLICABLE STANDARD	18
EUT SETUP	18
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	19
TEST PROCEDURE	20
FACTOR & OVER LIMIT/MARGIN CALCULATION	20
TEST DATA	20
FCC §15.247(A) (1) - CHANNEL SEPARATION TEST	35
APPLICABLE STANDARD	35
TEST PROCEDURE	35
TEST DATA	35

FCC §15.247(A) (1) - 20 DB EMISSION BANDWIDTH.....	40
APPLICABLE STANDARD	40
TEST PROCEDURE	40
TEST DATA	40
FCC §15.247(A) (1) (III) - QUANTITY OF HOPPING CHANNEL TEST.....	45
APPLICABLE STANDARD	45
TEST PROCEDURE	45
TEST DATA	45
FCC §15.247(A) (1) (III) - TIME OF OCCUPANCY (DWELL TIME).....	47
APPLICABLE STANDARD	47
TEST PROCEDURE	47
TEST DATA	47
FCC §15.247(B) (1) - PEAK OUTPUT POWER MEASUREMENT	52
APPLICABLE STANDARD	52
TEST PROCEDURE	52
TEST DATA	52
FCC §15.247(D) § 5.5 - BAND EDGES TESTING.....	57
APPLICABLE STANDARD	57
TEST PROCEDURE	57
TEST DATA	57
EUT PHOTOGRAPHS.....	64
TEST SETUP PHOTOGRAPHS	65

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	2401S54552E-RF-00A	Original Report	2024/07/12

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	POS Terminal
Tested Model	M8
Multiple Model(s)	N/A
Frequency Range	Bluetooth: 2402~2480MHz
Transmit Peak Power	7.56dBm
Modulation Technique	Bluetooth: GFSK, $\pi/4$ -DQPSK, 8DPSK
Antenna Specification [#]	-1.2dBi (provided by the applicant)
Voltage Range	DC 7.60V from Li-ion battery or DC 12V from adapter
Sample serial number	2KLY-2 for Conducted and Radiated Emissions Test 2KLY-3 for RF Conducted Test (Assigned by BACL, Shenzhen)
Sample/EUT Status	Good condition
Adapter Information	Model: GMB36-120300-F Input: AC 100-240V, 50/60Hz, 1.5A Output: DC 12.0V, 3.0A, 36.0W

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.207, 15.205, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF output power, conducted		0.72 dB(k=2, 95% level of confidence)
AC Power Lines Conducted Emissions	9kHz-150kHz	3.94dB(k=2, 95% level of confidence)
	150kHz-30MHz	3.84dB(k=2, 95% level of confidence)
Radiated Emissions	9kHz - 30MHz	3.30dB(k=2, 95% level of confidence)
	30MHz~200MHz (Horizontal)	4.48dB(k=2, 95% level of confidence)
	30MHz~200MHz (Vertical)	4.55dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Horizontal)	4.85dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Vertical)	5.05dB(k=2, 95% level of confidence)
	1GHz - 6GHz	5.35dB(k=2, 95% level of confidence)
	6GHz - 18GHz	5.44dB(k=2, 95% level of confidence)
	18GHz - 40GHz	5.16dB(k=2, 95% level of confidence)
Temperature		±1°C
Humidity		±1%
Supply voltages		±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 715558, the FCC Designation No. : CN5045.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	40	2442
1	2403	41	2443
2	2404	42	2444
...	...	...	...
...	...	...	...
36	2438	75	2477
37	2439	76	2478
38	2440	77	2479
39	2441	78	2480

EUT was tested with Channel 0, 39 and 78.

EUT Exercise Software

“QRCT3;cmd.exe”[#] exercise software was used and the power level is 9[#]. The software and power level was provided by the applicant.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Unknown	Socket	Unknown	Unknown
Telepower	Router	Unknown	Unknown
Telepower	Serial device	Unknown	Unknown
Telepower	Money case	Unknown	Unknown
Unknown	U disk*4	Unknown	Unknown

External I/O Cable


Cable Description	Length (m)	From Port	To
Un-shielding Un-Detachable DC Cable	1.5	EUT	Adapter
Un-shielded Detachable AC Cable	1.5	Adapter	LISN/Socket
Un-shielded detachable RJ45 cable	3.0	EUT	Router
Un-shielded detachable RS232 cable	3.0	EUT	Serial device
Un-shielded detachable RJ12 cable	3.0	EUT	Money case

Block Diagram of Test Setup

For Conducted Emissions:



For Radiated Emissions:



SUMMARY OF TEST RESULTS

Rules	Description of Test	Result
FCC 15.247 (i), §1.1307 (b) (1) & §2.1093	RF Exposure	Compliant
FCC §15.203	Antenna Requirement	Compliant
FCC §15.207(a)	AC Line Conducted Emissions	Compliant
FCC §15.205, §15.209, §15.247(d)	Radiated Emissions	Compliant
FCC §15.247(a)(1)	20 dB Emission Bandwidth & 99% Occupied Bandwidth	Compliant
FCC §15.247(a)(1)	Channel Separation Test	Compliant
FCC §15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliant
FCC §15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliant
FCC §15.247(b)(1)	Peak Output Power Measurement	Compliant
FCC §15.247(d)	Band edges	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2024/01/16	2025/01/15
Rohde & Schwarz	LISN	ENV216	101613	2024/01/16	2025/01/15
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2023/08/03	2024/08/02
Unknown	CE Cable	CE Cable	UF A210B-1-0720-504504	2023/08/03	2024/08/02
Audix	EMI Test software	E3	191218(V9)	NCR	NCR
Radiated Emission Test					
R&S	EMI Test Receiver	ESR3	102455	2024/01/16	2025/01/15
Sonoma instrument	Pre-amplifier	310 N	186238	2023/06/08	2024/06/07
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2023/07/20	2026/07/19
BACL	Active Loop Antenna	1313-1A	4031911	2024/03/21	2025/03/20
Unknown	Cable	Chamber Cable 1	F-03-EM236	2023/08/03	2024/08/02
Unknown	Cable	Chamber Cable 4	EC-007	2023/08/03	2024/08/02
Audix	EMI Test software	E3	19821b(V9)	NCR	NCR
Rohde & Schwarz	Spectrum Analyzer	FSV40	101605	2024/03/27	2025/03/26
COM-POWER	Pre-amplifier	PA-122	181919	2023/06/29	2024/06/28
Schwarzbeck	Horn Antenna	BBHA9120D(1201)	1143	2023/07/26	2026/07/25
Unknown	RF Cable	KMSE	0735	2023/10/08	2024/10/07
Unknown	RF Cable	UFA147	219661	2023/10/08	2024/10/07
SNSD	2.4G Band Reject filter	BSF2402-2480MN-0898-001	2.4G filter	2023/08/03	2024/08/02
A.H.System	Pre-amplifier	PAM-1840VH	190	2023/08/02	2024/08/01
Electro-Mechanics Co	Horn Antenna	3116	2026	2023/09/18	2026/09/17
UTIFLEX	RF Cable	NO. 13	232308-001	2023/08/03	2024/08/02
Audix	EMI Test software	E3	191218(V9)	NCR	NCR
RF Conducted Test					
R&S	spectrum analyzer	FSV40	101942	2023/12/18	2024/12/17
MARCONI	10dB Attenuator	6534/3	2942	2023/07/04	2024/07/03

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 - RF EXPOSURE**Applicable Standard**

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Measurement Result

For worst case:

Mode	Frequency (MHz)	Max tune-up conducted power [#] (dBm)	Max tune-up conducted power [#] (mW)	Distance (mm)	Calculated value	Threshold (1-g SAR)	SAR Test Exclusion
BT	2402-2480	8.0	6.31	5	2.0	3.0	Yes

Result: Compliant

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna arrangement, which was permanently attached, the antenna gain[#] is -1.2dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant

FCC §15.207 (a) - AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Note: The term "cable loss" refers to the combination of a cable and a 10dB transient limiter (attenuator).

Test Data


Environmental Conditions

Temperature:	24 °C
Relative Humidity:	55 %
ATM Pressure:	101 kPa

The testing was performed by Macy Shi on 2024-05-17.

EUT operation mode: Transmitting (Maximum output power mode, EDR (8DPSK) High Channel)

AC 120V/60 Hz, Line



Condition: Line


Project : 2401S54552E-RF

Tester : Macy shi

Note : BT

	Freq	Read Level	LISN Level	LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.15	8.52	29.07	10.40	10.15	55.74	-26.67	Average
2	0.15	25.07	45.62	10.40	10.15	65.74	-20.12	QP
3	0.21	2.10	22.59	10.39	10.10	53.36	-30.77	Average
4	0.21	15.98	36.47	10.39	10.10	63.36	-26.89	QP
5	0.36	-2.80	17.64	10.27	10.17	48.69	-31.05	Average
6	0.36	1.39	21.83	10.27	10.17	58.69	-36.86	QP
7	0.58	1.11	21.61	10.29	10.21	46.00	-24.39	Average
8	0.58	5.74	26.24	10.29	10.21	56.00	-29.76	QP
9	3.72	-4.55	16.10	10.39	10.26	46.00	-29.90	Average
10	3.72	-0.18	20.47	10.39	10.26	56.00	-35.53	QP
11	23.26	2.47	23.32	10.66	10.19	50.00	-26.68	Average
12	23.26	8.21	29.06	10.66	10.19	60.00	-30.94	QP

AC 120V/60 Hz, Neutral



Condition: Neutral

Project : 2401S54552E-RF

Tester : Macy shi

Note : BT

	Freq	Read Level	Level	LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.15	9.02	29.40	10.23	10.15	55.82	-26.42	Average
2	0.15	25.34	45.72	10.23	10.15	65.82	-20.10	QP
3	0.20	2.64	23.34	10.60	10.10	53.45	-30.11	Average
4	0.20	15.89	36.59	10.60	10.10	63.45	-26.86	QP
5	0.37	-1.98	18.95	10.74	10.19	48.43	-29.48	Average
6	0.37	3.04	23.97	10.74	10.19	58.43	-34.46	QP
7	0.58	5.19	26.06	10.66	10.21	46.00	-19.94	Average
8	0.58	10.38	31.25	10.66	10.21	56.00	-24.75	QP
9	4.45	-4.39	16.25	10.40	10.24	46.00	-29.75	Average
10	4.45	-0.05	20.59	10.40	10.24	56.00	-35.41	QP
11	23.26	2.99	23.42	10.24	10.19	50.00	-26.58	Average
12	23.26	8.96	29.39	10.24	10.19	60.00	-30.61	QP


FCC §15.205, §15.209 & §15.247(d) - RADIATED EMISSIONS

Applicable Standard


FCC §15.205; §15.209; §15.247(d)


EUT Setup

9 kHz-30MHz:



30MHz-1GHz:



Above 1GHz:

The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
9 kHz – 150 kHz	/	/	200 Hz	QP
	300 Hz	1 kHz	/	PK
150 kHz – 30 MHz	/	/	9 kHz	QP
	10 kHz	30 kHz	/	PK
30 MHz – 1000 MHz	/	/	120 kHz	QP
	100 kHz	300 kHz	/	PK
Above 1 GHz	Harmonics & Band Edge			
	1MHz	3 MHz	/	PK
	Average Emission Level=Peak Emission Level+20*log(Duty cycle)			
	Other Emissions			
	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Average

For Duty cycle measurement:

Use the duty cycle factor correction factor method per 15.35(c).

Duty cycle=On time/100milliseconds, On time= $N_1 \cdot L_1 + N_2 \cdot L_2 + \dots + N_{n-1} \cdot L_{n-1} + N_n \cdot L_n$,

Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulse, etc.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

All emissions under the average limit and under the noise floor have not recorded in the report.

Factor & Over Limit/Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit/Margin} &= \text{Level/Corrected Amplitude} - \text{Limit} \\ \text{Level / Corrected Amplitude} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Test Data

Environmental Conditions

Temperature:	22~25 °C
Relative Humidity:	50~54 %
ATM Pressure:	101 kPa

The testing was performed by Anson Su on 2024-05-28 for below 1GHz and Zenos Qiao on 2024-05-18 for above 1GHz.

Test mode: Transmitting


Note: After pre-scan in the X, Y and Z axes of orientation, the worst case z-axis of orientation were recorded.

9 kHz-30MHz: *(Maximum output power mode, EDR (8DPSK) High Channel)*

The amplitude of spurious emissions attenuated more than 20 dB below the limit was not recorded.

30MHz-1GHz: (Maximum output power mode, EDR (8DPSK) High Channel)


Horizontal



Site : Chamber A
Condition : 3m Horizontal
Project Number: 2401S54552E-RF
Note : BT
Tester : Anson Su

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	40.52	-11.85	24.82	12.97	40.00	-27.03 QP
2	83.05	-18.20	38.90	20.70	40.00	-19.30 QP
3	123.00	-12.28	48.60	36.32	43.50	-7.18 QP
4	222.95	-13.96	43.86	29.90	46.00	-16.10 QP
5	406.44	-10.47	34.49	24.02	46.00	-21.98 QP
6	802.49	-5.28	26.57	21.29	46.00	-24.71 QP

Vertical



Site : Chamber A
Condition : 3m Vertical
Project Number: 2401S54552E-RF
Note : BT
Tester : Anson Su

	Freq Factor		Read Level	Level	Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	44.04	-15.30	33.06	17.76	40.00	-22.24	QP
2	82.58	-18.79	47.27	28.48	40.00	-11.52	QP
3	119.38	-12.86	40.08	27.22	43.50	-16.28	QP
4	222.66	-14.79	31.81	17.02	46.00	-28.98	QP
5	668.73	-6.88	27.15	20.27	46.00	-25.73	QP
6	879.48	-4.95	26.04	21.09	46.00	-24.91	QP

Above 1GHz:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/AV					
8DPSK							
Low Channel 2402MHz							
2378.54	55.60	PK	H	-2.93	52.67	74	-21.33
2379.75	55.77	PK	V	-2.93	52.84	74	-21.16
4804.00	47.18	PK	H	2.42	49.60	74	-24.40
4804.00	47.45	PK	V	2.42	49.87	74	-24.13
Middle Channel 2441MHz							
4882.00	46.96	PK	H	2.58	49.54	74	-24.46
4882.00	47.18	PK	V	2.58	49.76	74	-24.24
High Channel 2480MHz							
2483.50	60.33	PK	H	-3.17	57.16	74	-16.84
2483.50	60.90	PK	V	-3.17	57.73	74	-16.27
4960.00	46.64	PK	H	2.68	49.32	74	-24.68
4960.00	46.87	PK	V	2.68	49.55	74	-24.45

Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Factor + Reading

Margin = Corrected. Amplitude - Limit

The other spurious emission which is in the noise floor level was not recorded.

Field Strength of Average							
Frequency (MHz)	Peak Measurement @3m (dBμV/m)	Polar (H/V)	Duty Cycle Corrected Factor (dB)	Average Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Comment
Low Channel 2402MHz							
2378.54	52.67	H	-24.73	27.94	54	-26.06	Bandedge
2379.75	52.84	V	-24.73	28.11	54	-25.89	Bandedge
4804.00	49.60	H	-24.73	24.87	54	-29.13	Harmonic
4804.00	49.87	V	-24.73	25.14	54	-28.86	Harmonic
Middle Channel 2441MHz							
4882.00	49.54	H	-24.73	24.81	54	-29.19	Harmonic
4882.00	49.76	V	-24.73	25.03	54	-28.97	Harmonic
High Channel 2480MHz							
2483.50	57.16	H	-24.73	32.43	54	-21.57	Bandedge
2483.50	57.73	V	-24.73	33.00	54	-21.00	Bandedge
4960.00	49.32	H	-24.73	24.59	54	-29.41	Harmonic
4960.00	49.55	V	-24.73	24.82	54	-29.18	Harmonic

Note: Average level= Peak level+ Duty Cycle Corrected Factor


Worst case duty cycle:


Duty Cycle = Ton/100ms = 2.899*2/100=0.05798

Duty Cycle Corrected Factor = 20lg (Duty Cycle) = 20lg0.05798 = -24.73





Band Edge Measurements (Radiated):








Harmonic and Emissions Measurements:














FCC §15.247(a) (1) - CHANNEL SEPARATION TEST


Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.2

1. Set the EUT in transmitting mode, maxhold the channel.
2. Set the adjacent channel of the EUT and maxhold another trace.
3. Measure the channel separation.



Test Data

Environmental Conditions

Temperature:	25.7~26.6 °C
Relative Humidity:	45~48 %
ATM Pressure:	101 kPa


The testing was performed by Kungfumaster Liang on 2024-05-20.

EUT operation mode: Transmitting

Test Result: Compliant.

Test Modes	Test Frequency (MHz)	Channel Separation (MHz)	Limits (MHz)
BDR Mode (GFSK)	2402	1.000	0.627
	2441	1.000	0.632
	2480	1.000	0.629
EDR Mode ($\pi/4$ -DQPSK)	2402	1.006	0.859
	2441	1.000	0.859
	2480	1.000	0.859
EDR Mode (8DPSK)	2402	1.006	0.861
	2441	1.000	0.864
	2480	1.000	0.864







FCC §15.247(a) (1) - 20 dB EMISSION BANDWIDTH

Applicable Standard


Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.7 & Clause 6.9.2

The following conditions shall be observed for measuring the occupied bandwidth and 20 dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / 20 dB bandwidth if the device is not transmitting continuously.
- The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW/ 20dB bandwidth and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.



Test Data

Environmental Conditions

Temperature:	25.7~26.6 °C
Relative Humidity:	45~48 %
ATM Pressure:	101 kPa

The testing was performed by Kungfumaster Liang on 2024-05-20.

EUT operation mode: Transmitting

Test Result: Compliant.

Test Modes	Test Channel	Test Frequency (MHz)	20 dB Bandwidth (MHz)
BDR Mode (GFSK)	Lowest	2402	0.940
	Middle	2441	0.948
	Highest	2480	0.944
EDR Mode ($\pi/4$ -DQPSK)	Lowest	2402	1.288
	Middle	2441	1.288
	Highest	2480	1.288
EDR Mode (8DPSK)	Lowest	2402	1.292
	Middle	2441	1.296
	Highest	2480	1.296

20 dB Bandwidth

BDR Mode (GFSK)	
Low Channel	Spectrum Ref Level 30.00 dBm Offset 10.50 dB RBW 30 kHz Att 30 dB SWT 1 ms VBW 100 kHz Mode Sweep 1Pk Max CF 2.402 GHz 501 pts Span 2.0 MHz ProjectNo.:2401S54552E-RF Tester:Kungfumaater Liang Date: 20.MAY.2024 19:19:52
Middle Channel	Spectrum Ref Level 30.00 dBm Offset 10.50 dB RBW 30 kHz Att 30 dB SWT 1 ms VBW 100 kHz Mode Sweep 1Pk Max CF 2.441 GHz 501 pts Span 2.0 MHz ProjectNo.:2401S54552E-RF Tester:Kungfumaater Liang Date: 20.MAY.2024 19:21:24
High Channel	Spectrum Ref Level 30.00 dBm Offset 10.50 dB RBW 30 kHz Att 30 dB SWT 1 ms VBW 100 kHz Mode Sweep 1Pk Max CF 2.48 GHz 501 pts Span 2.0 MHz ProjectNo.:2401S54552E-RF Tester:Kungfumaater Liang Date: 20.MAY.2024 19:22:21

TR-EM-RF001 Page 43 of 65 Version 1.0 (2023/10/07)

EDR Mode (8DPSK)

Low Channel

ProjectNo.:24013545528-RF Tester:Rungfunaster Liang
Date: 20.MAY.2024 19:26:42

Middle Channel

ProjectNo.:24013545528-RF Tester:Rungfunaster Liang
Date: 20.MAY.2024 19:27:51

High Channel

ProjectNo.:24013545528-RF Tester:Rungfunaster Liang
Date: 20.MAY.2024 19:28:25


FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST**Applicable Standard**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.3

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the max-hold function record the quantity of the channel.

**Test Data****Environmental Conditions**

Temperature:	25.7~26.6 °C
Relative Humidity:	45~48 %
ATM Pressure:	101 kPa

The testing was performed by Kungfumaster Liang on 2024-05-20.

EUT operation mode: Transmitting

Test Result: Compliant.

Test Modes	Frequency Range (MHz)	Number of Hopping Channel	Limits
GFSK	2400-2483.5	79	≥15
$\pi/4$ -DQPSK	2400-2483.5	79	≥15
8DPSK	2400-2483.5	79	≥15

Hopping Channel	
GFSK	Spectrum Ref Level 30.00 dBm Offset 10.50 dB RBW 100 kHz Att 30 dB SWT 1 ms VBW 300 kHz Mode Sweep 1Pk Max M1[1] 3.89 dBm D1[1] 2.402080 GHz 1.91 dB 78.000 MHz P1 Start 2.4 GHz 501 pts Stop 2.4835 GHz ProjectNo.:2401S54552E-RF Tester:Kungfumaster Liang Date: 20.MAY.2024 20:12:51
$\pi/4$ -DQPSK	Spectrum Ref Level 30.00 dBm Offset 10.50 dB RBW 100 kHz Att 30 dB SWT 1 ms VBW 300 kHz Mode Sweep 1Pk Max M1[1] 2.65 dBm D1[1] 2.401920 GHz 2.00 dB 78.160 MHz P1 Start 2.4 GHz 501 pts Stop 2.4835 GHz ProjectNo.:2401S54552E-RF Tester:Kungfumaster Liang Date: 20.MAY.2024 20:17:20
8DPSK	Spectrum Ref Level 30.00 dBm Offset 10.50 dB RBW 100 kHz Att 30 dB SWT 1 ms VBW 300 kHz Mode Sweep 1Pk Max M1[1] 2.70 dBm D1[1] 2.402080 GHz 2.29 dB 78.000 MHz P1 Start 2.4 GHz 501 pts Stop 2.4835 GHz ProjectNo.:2401S54552E-RF Tester:Kungfumaster Liang Date: 20.MAY.2024 20:20:45


FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.4

1. The EUT was worked in channel hopping.
2. Set the RBW to: 1MHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Set the span to 0Hz.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Recorded the time of single pulses

**Test Data****Environmental Conditions**

Temperature:	25.7~26.6 °C
Relative Humidity:	45~48 %
ATM Pressure:	101 kPa

The testing was performed by Kungfumaster Liang on 2024-05-20.

EUT operation mode: Transmitting

Test Result: Compliant.

Test Modes	Packet Type	Test Frequency (MHz)	Pulse width (ms)	Result (s)	Limit (s)
BDR Mode (GFSK)	DH1	2441	0.384	0.123	0.400
	DH3	2441	1.638	0.262	0.400
	DH5	2441	2.890	0.308	0.400
EDR Mode ($\pi/4$ -DQPSK)	2DH1	2441	0.390	0.125	0.400
	2DH3	2441	1.644	0.263	0.400
	2DH5	2441	2.900	0.309	0.400
EDR Mode (8DPSK)	3DH1	2441	0.390	0.125	0.400
	3DH3	2441	1.638	0.262	0.400
	3DH5	2441	2.900	0.309	0.400

Note:

DH1/2DH1/3DH1:Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s

DH3/2DH3/3DH3:Dwell time=Pulse time (ms) $\times$ (1600/4/79) $\times$ 31.6 s

DH5/2DH5/3DH5:Dwell time=Pulse time (ms) $\times$ (1600/6/79) $\times$ 31.6 s

DH1	BDR Mode (GFSK) Spectrum Ref Level 25.00 dBm Offset 10.50 dB RBW 1 MHz Att 30 dB SWT 1 ms VBW 3 MHz SGL TRG:VID IPk Clr M1[1] D2[1] -6.09 dBm -2.00 μs 7.62 dB 384.00 μs TRG 2.200 dBm M1 D2 CF 2.443 GHz 501 pts 100.0 μs/ ProjectNo.:2401S54552E-RF Tester:Kungfumaster Liang Date: 20.MAY.2024 20:39:17
DH3	Spectrum Ref Level 25.00 dBm Offset 10.50 dB RBW 1 MHz Att 30 dB SWT 2 ms VBW 3 MHz SGL TRG:VID IPk Clr M1[1] D2[1] 5.09 dBm 0.00000000 s 0.19 dB 1.63800 ms TRG 2.100 dBm M1 D2 CF 2.443 GHz 501 pts 300.0 μs/ ProjectNo.:2401S54552E-RF Tester:Kungfumaster Liang Date: 20.MAY.2024 20:40:30
DH5	Spectrum Ref Level 25.00 dBm Offset 10.50 dB RBW 1 MHz Att 30 dB SWT 5 ms VBW 3 MHz SGL TRG:VID IPk Clr M1[1] D2[1] 2.83 dBm 0.00000000 s 3.34 dB 2.89000 ms TRG 2.200 dBm M1 D2 CF 2.443 GHz 501 pts 500.0 μs/ ProjectNo.:2401S54552E-RF Tester:Kungfumaster Liang Date: 20.MAY.2024 20:41:06

2DH1	EDR Mode ($\pi/4$-DQPSK) Spectrum Ref Level 25.00 dBm Offset 10.50 dB RBW 1 MHz Att 30 dB SWT 1 ms VBW 3 MHz SGL TRG:VID IPk Clk M1[1] D2[1] -2.47 dBm -2.00 ps -0.63 dB 390.00 ps TRG 2.300 dBm CF 2.443 GHz 501 pts 100.0 ps/ ProjectNo.:2401S54552E-RF Tester:Kungfumaster Liang Date: 20.MAY.2024 20:42:06
2DH3	Spectrum Ref Level 25.00 dBm Offset 10.50 dB RBW 1 MHz Att 30 dB SWT 2 ms VBW 3 MHz SGL TRG:VID IPk Clk M1[1] D2[1] 1.42 dBm -6.00 ps 3.99 dB 1.64400 ms TRG 2.300 dBm CF 2.443 GHz 501 pts 300.0 ps/ ProjectNo.:2401S54552E-RF Tester:Kungfumaster Liang Date: 20.MAY.2024 20:43:03
2DH5	Spectrum Ref Level 25.00 dBm Offset 10.50 dB RBW 1 MHz Att 30 dB SWT 5 ms VBW 3 MHz SGL TRG:VID IPk Clk M1[1] D2[1] -6.96 dBm -10.00 ps 11.44 dB 2.93000 ms TRG 2.300 dBm CF 2.443 GHz 501 pts 500.0 ps/ ProjectNo.:2401S54552E-RF Tester:Kungfumaster Liang Date: 20.MAY.2024 20:43:41

3DH1	EDR Mode (8DPSK) Spectrum Ref Level 25.00 dBm Offset 10.50 dB RBW 1 MHz Att 30 dB SWT 1 ms VBW 3 MHz SGL TRG:VID 1Pk Clk M1[1] D2[1] -0.59 dBm -2.00 μs -4.58 dB 390.00 μs TRG 2.800 dBm CF 2.443 GHz 501 pts 100.0 μs/ ProjectNo.:2401S54552E-RF Tester:Kungfumaster Liang Date: 20.MAY.2024 20:44:25
3DH3	Spectrum Ref Level 25.00 dBm Offset 10.50 dB RBW 1 MHz Att 30 dB SWT 2 ms VBW 3 MHz SGL TRG:VID 1Pk Clk M1[1] D2[1] 4.70 dBm 0.00000000 s 1.13 dB 1.63000 ms TRG 2.800 dBm CF 2.443 GHz 501 pts 300.0 μs/ ProjectNo.:2401S54552E-RF Tester:Kungfumaster Liang Date: 20.MAY.2024 20:45:21
3DH5	Spectrum Ref Level 25.00 dBm Offset 10.50 dB RBW 1 MHz Att 30 dB SWT 5 ms VBW 3 MHz SGL TRG:VID 1Pk Clk M1[1] D2[1] 4.58 dBm 0.00000000 s -0.27 dB 2.90000 ms TRG 2.700 dBm CF 2.443 GHz 501 pts 500.0 μs/ ProjectNo.:2401S54552E-RF Tester:Kungfumaster Liang Date: 20.MAY.2024 20:46:13

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT


Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.5

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions




Temperature:	25.7~26.6 °C
Relative Humidity:	45~48 %
ATM Pressure:	101 kPa




The testing was performed by Kungfumaster Liang on 2024-05-20.




EUT operation mode: Transmitting

Test Result: Compliant.

Test Modes	Test Frequency (MHz)	Peak Conducted Output Power (dBm)	Limits (dBm)
BDR Mode (GFSK)	2402	4.44	21
	2441	6.17	21
	2480	6.32	21
EDR Mode ($\pi/4$ -DQPSK)	2402	5.17	21
	2441	6.89	21
	2480	7.15	21
EDR Mode (8DPSK)	2402	5.58	21
	2441	7.23	21
	2480	7.56	21

BDR Mode (GFSK)	
Low Channel	Spectrum Ref Level 30.00 dBm Offset 10.50 dB RBW 3 MHz Att 30 dB SWT 1 ms VBW 10 MHz Mode Sweep 1Pk Max M1[1] 4.44 dBm 2.40201880 GHz  CF 2.402 GHz 501 pts Span 4.7 MHz ProjectNo.:2401S54552E-RF Tester:Kungfumaster Liang Date: 20.MAY.2024 19:45:11
Middle Channel	Spectrum Ref Level 30.00 dBm Offset 10.50 dB RBW 3 MHz Att 30 dB SWT 1 ms VBW 10 MHz Mode Sweep 1Pk Max M1[1] 6.17 dBm 2.44100950 GHz  CF 2.441 GHz 501 pts Span 4.74 MHz ProjectNo.:2401S54552E-RF Tester:Kungfumaster Liang Date: 20.MAY.2024 19:46:41
High Channel	Spectrum Ref Level 30.00 dBm Offset 10.50 dB RBW 3 MHz Att 30 dB SWT 1 ms VBW 10 MHz Mode Sweep 1Pk Max M1[1] 6.32 dBm 2.47991520 GHz  CF 2.48 GHz 501 pts Span 4.72 MHz ProjectNo.:2401S54552E-RF Tester:Kungfumaster Liang Date: 20.MAY.2024 19:48:09

EDR Mode ($\pi/4$ -DQPSK)	
Low Channel	Spectrum Ref Level 30.00 dBm Offset 10.50 dB RBW 3 MHz Att 30 dB SWT 1 ms VBW 10 MHz Mode Sweep 1Pk Max M1[1] 5.17 dBm 2.4018330 GHz  CF 2.402 GHz 501 pts Span 6.44 MHz ProjectNo.:2401S54552E-RF Tester:Kungfumaster Liang Date: 20.MAY.2024 19:48:48
Middle Channel	Spectrum Ref Level 30.00 dBm Offset 10.50 dB RBW 3 MHz Att 30 dB SWT 1 ms VBW 10 MHz Mode Sweep 1Pk Max M1[1] 6.09 dBm 2.4411930 GHz  CF 2.441 GHz 501 pts Span 6.44 MHz ProjectNo.:2401S54552E-RF Tester:Kungfumaster Liang Date: 20.MAY.2024 19:49:26
High Channel	Spectrum Ref Level 30.00 dBm Offset 10.50 dB RBW 3 MHz Att 30 dB SWT 1 ms VBW 10 MHz Mode Sweep 1Pk Max M1[1] 7.15 dBm 2.4801670 GHz  CF 2.48 GHz 501 pts Span 6.44 MHz ProjectNo.:2401S54552E-RF Tester:Kungfumaster Liang Date: 20.MAY.2024 19:50:00

EDR Mode (8DPSK)	
Low Channel	Spectrum Ref Level 30.00 dBm Offset 10.50 dB RBW 3 MHz Att 30 dB SWT 1 ms VBW 10 MHz Mode Sweep 1Pk Max M1[1] 5.59 dBm 2.4019480 GHz  CF 2.402 GHz 501 pts Span 6.46 MHz ProjectNo.:2401S54552E-RF Tester:Kungfumaster Liang Date: 20.MAY.2024 19:50:43
Middle Channel	Spectrum Ref Level 30.00 dBm Offset 10.50 dB RBW 3 MHz Att 30 dB SWT 1 ms VBW 10 MHz Mode Sweep 1Pk Max M1[1] 7.23 dBm 2.4409480 GHz  CF 2.441 GHz 501 pts Span 6.48 MHz ProjectNo.:2401S54552E-RF Tester:Kungfumaster Liang Date: 20.MAY.2024 19:51:20
High Channel	Spectrum Ref Level 30.00 dBm Offset 10.50 dB RBW 3 MHz Att 30 dB SWT 1 ms VBW 10 MHz Mode Sweep 1Pk Max M1[1] 7.56 dBm 2.4800520 GHz  CF 2.48 GHz 501 pts Span 6.48 MHz ProjectNo.:2401S54552E-RF Tester:Kungfumaster Liang Date: 20.MAY.2024 19:51:54

FCC §15.247(d) § 5.5 - BAND EDGES TESTING


Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.6 & Clause 6.10

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data


Environmental Conditions


Temperature:	25.7~26.6 °C
Relative Humidity:	45~48 %
ATM Pressure:	101 kPa


The testing was performed by Kungfumaster Liang on 2024-05-20.


EUT operation mode: Transmitting


Test Result: Compliant.














EUT PHOTOGRAPHS

Please refer to the attachment 2401S54552E-RF External photo and 2401S54552E-RF Internal photo.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2401S54552E-RFA Test Setup photo.

******* END OF REPORT *******