

TEST REPORT

Applicant Name: Telepower Communication Co., Ltd.
Address: 5 Bld, Zone A, Hantian Technology Town No.17 ShenHai RD,
Nanhai District Foshan China
Report Number: SZ1240308-11508E-RF-00C
FCC ID: 2AJ2B-T20C

Test Standard (s)
FCC PART 15.407

Sample Description

Product Type: Ticket Validator
Model No.: T20
Multiple Model(s) No.: T20B,T20C,T20D,T20P
Trade Mark: Telpo
Date Received: 2024/03/08
Issue Date: 2024/05/28

Test Result:	Pass▲
--------------	-------

▲ In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Gala Liu

Gala Liu
RF Engineer

Approved By:

Nancy Wang

Nancy Wang
RF Supervisor

Note: The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.

This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

Bay Area Compliance Laboratories Corp. (Shenzhen)

5F(B-West), 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China

Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	6
TEST FACILITY	6
SYSTEM TEST CONFIGURATION	7
DESCRIPTION OF TEST CONFIGURATION	7
EUT EXERCISE SOFTWARE	7
DUTY CYCLE	8
EQUIPMENT MODIFICATIONS	10
SUPPORT EQUIPMENT LIST AND DETAILS	10
EXTERNAL I/O CABLE.....	10
BLOCK DIAGRAM OF TEST SETUP	11
SUMMARY OF TEST RESULTS	12
TEST EQUIPMENT LIST	13
FCC §1.1307 (B) & §2.1091- MPE-BASED EXEMPTION	14
APPLICABLE STANDARD	14
RESULT	15
FCC §15.203 – ANTENNA REQUIREMENT.....	17
APPLICABLE STANDARD	17
ANTENNA CONNECTOR CONSTRUCTION	17
FCC §15.407 (B) (6) §15.207 (A) – CONDUCTED EMISSIONS	18
APPLICABLE STANDARD	18
EUT SETUP	18
EMI TEST RECEIVER SETUP.....	18
TEST PROCEDURE	18
FACTOR & OVER LIMIT CALCULATION.....	19
TEST DATA	19
§15.205 & §15.209 & §15.407(B)– UNDESIRABLE EMISSION	22
APPLICABLE STANDARD	22
EUT SETUP	22
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	24
TEST PROCEDURE	24
FACTOR & OVER LIMIT/MARGIN CALCULATION	25
TEST DATA	25
FCC §15.407(A), (E) – 26 DB & 6DB EMISSION BANDWIDTH.....	39
APPLICABLE STANDARD	39
TEST PROCEDURE	39
TEST DATA	40

FCC §15.407(A) – CONDUCTED TRANSMITTER OUTPUT POWER.....	48
APPLICABLE STANDARD	48
TEST PROCEDURE	48
TEST DATA	49
FCC §15.407(A) - POWER SPECTRAL DENSITY	50
TEST PROCEDURE	50
TEST DATA	51
EUT PHOTOGRAPHS.....	55
TEST SETUP PHOTOGRAPHS	56

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	SZ1240308-11508E-RF-00C	Original Report	2024/05/28

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Ticket Validator
Tested Model	T20
Multiple Model(s)	T20B,T20C,T20D,T20P
Frequency Range	5G Wi-Fi: 5150-5250MHz
Mode	802.11a/n20/n40/ac20/ac40/ac80
Maximum Conducted Average Output Power	5150-5250MHz: 14.63dBm
Modulation Technique	OFDM
Antenna Specification [#]	0dBi (provided by the applicant)
Voltage Range	DC 9V-40V
Sample serial number	2LGK-4 for Conducted and Radiated Emissions Test 2LGK-3 for RF Conducted Test (Assigned by BACL, Shenzhen)
Sample/EUT Status	Good condition
Adapter Information	N/A
Note: The Multiple models are electrically identical with the test model except for model name. Please refer to the declaration letter [#] for more detail, which was provided by manufacturer.	

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and E of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart E, section 15.203, 15.205, 15.207, 15.209 and 15.407 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices. And KDB789033 D02 General U-NII Test Procedures New Rules v02r01.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF Frequency		213.55 Hz(k=2, 95% level of confidence)
RF output power, conducted		0.72 dB(k=2, 95% level of confidence)
Unwanted Emission, conducted		1.75 dB(k=2, 95% level of confidence)
AC Power Lines Conducted Emissions	9kHz-150kHz	3.94dB(k=2, 95% level of confidence)
	150kHz-30MHz	3.84dB(k=2, 95% level of confidence)
Radiated Emissions	9kHz - 30MHz	3.30dB(k=2, 95% level of confidence)
	30MHz~200MHz (Horizontal)	4.48dB(k=2, 95% level of confidence)
	30MHz~200MHz (Vertical)	4.55dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Horizontal)	4.85dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Vertical)	5.05dB(k=2, 95% level of confidence)
	1GHz - 6GHz	5.35dB(k=2, 95% level of confidence)
	6GHz - 18GHz	5.44dB(k=2, 95% level of confidence)
	18GHz - 40GHz	5.16dB(k=2, 95% level of confidence)
Temperature		±1°C
Humidity		±1%
Supply voltages		±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 715558, the FCC Designation No. : CN5045.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode, which was provided by manufacturer.

The system support 802.11a/n ht20/n ht40/ac vht20/ac vht40/ac vht80, the 802.11 n ht20/n ht40 were reduced since the identical parameters with 802.11n-HT20 and vht40.

For 5150-5250MHz Band, 7 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220
38	5190	46	5230
40	5200	48	5240
42	5210	/	/

For 802.11a/ac20 mode: channel 36, 40, 48 were tested;

For 802.11ac40 mode: channel 38, 46 were tested;

For 802.11ac80 mode, channel 42 was tested.

EUT Exercise Software


“QRCT4”[#] software was used and power level as below. The software and power level was provided by the applicant. The device was tested with the worst case was performed as below:

5150-5250 MHz Band:				
Test Modes	Test Channels	Test Frequency (MHz)	Data rate	Power Level Setting [#]
802.11a	Lowest	5180	6Mbps	18
	Middle	5200	6Mbps	18
	Highest	5240	6Mbps	18
802.11n-HT20	Lowest	5180	MCS0	18
	Middle	5200	MCS0	18
	Highest	5240	MCS0	18
802.11n-HT40	Lowest	5190	MCS0	14
	Highest	5230	MCS0	14
802.11ac-VHT80	Middle	5210	MCS0	12

Duty cycle


Test Modes	Ton (ms)	Ton+off (ms)	Duty cycle (%)	Duty Cycle Factor (dB)	1/T (Hz)	VBW Setting (Hz)
802.11a	2.025	2.066	98.02	/	/	10
802.11n-HT20	1.703	1.743	97.71	0.10	587	1000
802.11n-HT40	0.839	0.876	95.78	0.19	1192	2000
802.11ac-VHT80	0.414	0.451	91.80	0.37	2415	3000

802.11a




ProjectNo.:SZ1240308-11508E-RF Tester:Bamboo Zhan
Date: 22.APR.2024 21:03:39

802.11ac 20




ProjectNo.:SZ1240308-11508E-RF Tester:Bamboo Zhan
Date: 22.APR.2024 22:03:00

802.11ac 40



ProjectNo.:SZ1240308-11508E-RF Tester:Bamboo Zhan
Date: 22.APR.2024 22:09:30



ProjectNo.:SZ1240308-11508E-RF Tester:Bamboo Zhan
Date: 22.APR.2024 21:55:11

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Unknown	Socket	Unknown	Unknown
Unknown	Adapter	Unknown	Unknown

External I/O Cable


Cable Description	Length (m)	From Port	To
Un-shielding Un-Detachable DC Cable	1.0	EUT	Adapter
Un-shielded Detachable AC Cable	1.5	Adapter	LISN/Socket
Un-shielding Un-Detachable AC Cable	1.5	Socket	AC Mains

Block Diagram of Test Setup

For Conducted Emissions:



For Radiated Emissions:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307 (b) & §2.1091	MPE-Based Exemption	Compliant
§15.203	Antenna Requirement	Compliant
§15.407(b)(9)& §15.207(a)	Conducted Emissions	Compliant
§15.205& §15.209 &§15.407(b)	Undesirable Emission& Restricted Bands	Compliant
§15.407(a) (e)	26 dB Emission Bandwidth & 6dB Bandwidth	Compliant
§15.407(a)	Conducted Transmitter Output Power	Compliant
§15.407 (a)	Power Spectral Density	Compliant
§15.407 (h)	Transmit Power Control (TPC)	Not Applicable
§15.407 (h)	Dynamic Frequency Selection (DFS)	Not Applicable

Not Applicable: The supplier declared that the equipment has no this function.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2024/01/16	2025/01/15
Rohde & Schwarz	LISN	ENV216	101613	2024/01/16	2025/01/15
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2023/08/03	2024/08/02
Unknown	CE Cable	CE Cable	UF A210B-1-0720-504504	2023/08/03	2024/08/02
Audix	EMI Test software	E3	191218(V9)	NCR	NCR
Radiated Emission Test					
R&S	EMI Test Receiver	ESR3	102455	2024/01/16	2025/01/15
Sonoma instrument	Pre-amplifier	310 N	186238	2023/06/08	2024/06/07
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2023/07/20	2024/07/19
ETS	Passive Loop Antenna	6512	29604	2023/07/07	2024/07/06
Unknown	Cable	Chamber Cable 1	F-03-EM236	2023/08/03	2024/08/02
Unknown	Cable	Chamber Cable 4	EC-007	2023/08/03	2024/08/02
Audix	EMI Test software	E3	19821b(V9)	NCR	NCR
Rohde & Schwarz	Spectrum Analyzer	FSV40	101605	2024/03/27	2025/03/26
COM-POWER	Pre-amplifier	PA-122	181919	2023/06/29	2024/06/28
Schwarzbeck	Horn Antenna	BBHA9120D(1201)	1143	2023/07/26	2024/07/25
Unknown	RF Cable	KMSE	0735	2023/10/08	2024/10/07
Unknown	RF Cable	UFA147	219661	2023/10/08	2024/10/07
SNSD	5G Band Reject filter	BSF5150-5850MN-0899-004	5G filter	2023/08/03	2024/08/02
A.H.System	Pre-amplifier	PAM-1840VH	190	2023/08/03	2024/08/02
Electro-Mechanics Co	Horn Antenna	3116	2026	2023/09/18	2026/09/17
UTIFLEX	RF Cable	NO. 13	232308-001	2023/08/03	2024/08/02
Audix	EMI Test software	E3	191218(V9)	NCR	NCR
RF Conducted Test					
R&S	SPECTRUM ANALYZER	FSU26	200120	2024/01/08	2025/01/07
ANRITSU	Microwave peak power sensor	MA24418A	12622	2023/08/08	2024/08/07
Unknown	10dB Attenuator	Unknown	F-03-EM122	2023/07/04	2024/07/03

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307 (B) & §2.1091- MPE-BASED EXEMPTION

Applicable Standard

According to subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 Interim General RF Exposure Guidance

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation:

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Result

Mode	Frequency (MHz)	Tune up conducted power [#]	Antenna Gain [#]		ERP		Evaluation Distance (m)	ERP Limit (mW)
		(dBm)	(dBi)	(dBd)	(dBm)	(mW)		
BT	2402-2480	10.0	2.16	0.01	10.01	10.02	0.2	768
BLE	2402-2480	-2.5	2.16	0.01	-2.49	0.56	0.2	768
2.4G Wi-Fi	2412-2462	23.5	2.16	0.01	23.51	224.39	0.2	768
5.2G Wi-Fi	5180-5240	15.0	0	-2.15	12.85	19.28	0.2	768
GSM850*	824-849	25.98	-4.91	-7.06	18.92	77.98	0.2	422
PCS1900*	1850-1910	20.48	2.30	0.15	20.63	115.61	0.2	768
WCDMA B2	1850-1910	22.0	2.30	0.15	22.15	164.06	0.2	768
WCDMA B5	824-849	23.0	-4.91	-7.06	15.94	39.26	0.2	422
LTE B2	1850-1910	23.0	2.30	0.15	23.15	206.54	0.2	768
LTE B4	1710-1755	23.0	1.88	-0.27	22.73	187.50	0.2	768
LTE B7	2500-2570	22.0	2.95	0.8	22.8	190.55	0.2	768
LTE B38	2570-2620	22.5	3.34	1.19	23.69	233.88	0.2	768

Note: 1. The tune up conducted power and antenna gain was declared by the applicant.

2. The BT, 2.4G Wi-Fi and 5G Wi-Fi cannot transmit at same time.

3. 0dBd=2.15dBi

Note*: It was the time average power according to the duty cycle.

Mode		Tune-up Peak Output Power (dBm)			Tune-up Average Output Power (dBm)		
		Low	Middle	High	Low	Middle	High
GPRS850	1 slot	33.5	33.5	33.5	24.47	24.47	24.47
	2 slots	32.0	32.0	32.0	25.98	25.98	25.98
	3 slots	30.0	30.0	30.0	25.74	25.74	25.74
	4 slots	28.5	28.5	28.5	25.49	25.49	25.49
GPRS1900	1 slot	27.5	27.5	27.5	18.47	18.47	18.47
	2 slots	26.5	26.5	26.5	20.48	20.48	20.48
	3 slots	24.0	24.0	24.0	19.74	19.74	19.74
	4 slots	23.0	23.0	23.0	19.99	19.99	19.99

Note: the duty cycle for 1 slot is 1/8, 2 slots is 1/4, 3 slots is 3/8, 4 slots is 1/2

The average power=Peak power+ duty cycle factor

Duty cycle factor=10*log (duty cycle)

NFC:

Mode	Frequency (MHz)	Maximum E-Field (dBuV/m@3m)	Maximum EIRP (dBm)	ERP		Evaluation Distance (m)	ERP Limit (mW)
				(dBm)	(mW)		
NFC	13.56	69.98	-25.22	-27.37	0.002	0.2	751

Note: EIRP = E-Field – 95.2 @3m, ERP = EIRP-2.15

Simultaneous transmitting consideration (worst case):

The ratio= $ERP_{2.4G\ Wi-Fi}/limit + ERP_{LTE\ B38}/limit + ERP_{NFC}/limit = 224.39/768 + 233.88/768 + 0.002/751 = 0.597 < 1.0$

So simultaneous exposure is compliant.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.407 (a), if the transmitting antennas of directional gain greater than 6dBi are used, the transmit power and power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one internal antenna which was permanently attached, and the maximum antenna gain[#] is 0dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant

FCC §15.407 (b) (6) §15.207 (a) – CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207, §15.407(b) (6)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and Average detection mode.

Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Note: The term "cable loss" refers to the combination of a cable and a 10dB transient limiter (attenuator).

Test Data


Environmental Conditions

Temperature:	26 °C
Relative Humidity:	54 %
ATM Pressure:	101 kPa

The testing was performed by Macy Shi on 2024-04-07.

EUT operation mode: Transmitting (Maximum output power mode, 802.11 ac 20, 5200MHz)

AC 120V/60 Hz, Line



Condition: Line


Project : SZ1240308-11508E-RF

Tester : Macy shi

Note : 5G WIFI

	Freq	Read Level	LISN Level	LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.15	13.89	34.44	10.40	10.15	55.91	-21.47	Average
2	0.15	26.64	47.19	10.40	10.15	65.91	-18.72	QP
3	0.21	5.07	25.56	10.39	10.10	53.36	-27.80	Average
4	0.21	15.65	36.14	10.39	10.10	63.36	-27.22	QP
5	0.33	0.65	21.09	10.29	10.15	49.40	-28.31	Average
6	0.33	6.35	26.79	10.29	10.15	59.40	-32.61	QP
7	0.58	9.97	30.45	10.28	10.20	46.00	-15.55	Average
8	0.58	12.76	33.24	10.28	10.20	56.00	-22.76	QP
9	3.68	-3.25	17.40	10.39	10.26	46.00	-28.60	Average
10	3.68	1.54	22.19	10.39	10.26	56.00	-33.81	QP
11	25.05	4.39	25.27	10.64	10.24	50.00	-24.73	Average
12	25.05	9.13	30.01	10.64	10.24	60.00	-29.99	QP

AC 120V/60 Hz, Neutral



Condition: Neutral

Project : SZ1240308-11508E-RF

Tester : Macy shi

Note : 5G WIFI

	Freq	Read Level	LISN Level	LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.15	11.19	31.58	10.24	10.15	55.74	-24.16	Average
2	0.15	24.88	45.27	10.24	10.15	65.74	-20.47	QP
3	0.20	5.23	25.92	10.60	10.09	53.62	-27.70	Average
4	0.20	16.96	37.65	10.60	10.09	63.62	-25.97	QP
5	0.44	-2.38	18.58	10.77	10.19	47.11	-28.53	Average
6	0.44	1.25	22.21	10.77	10.19	57.11	-34.90	QP
7	0.59	1.04	21.90	10.65	10.21	46.00	-24.10	Average
8	0.59	3.78	24.64	10.65	10.21	56.00	-31.36	QP
9	3.53	-4.44	16.17	10.35	10.26	46.00	-29.83	Average
10	3.53	0.38	20.99	10.35	10.26	56.00	-35.01	QP
11	25.05	2.76	23.26	10.26	10.24	50.00	-26.74	Average
12	25.05	7.25	27.75	10.26	10.24	60.00	-32.25	QP

§15.205 & §15.209 & §15.407(B)– UNDESIRABLE EMISSION

Applicable Standard

FCC §15.407 (b); §15.209; §15.205;


(b) Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:



- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209.

EUT Setup

9 kHz-30MHz:



30MHz-1GHz:**Above 1 GHz:**

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC 15.209 and FCC 15.407 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9 kHz-1GHz:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
9 kHz – 150 kHz	/	/	200 Hz	QP
	300 Hz	1 kHz	/	PK
150 kHz – 30 MHz	/	/	9 kHz	QP
	10 kHz	30 kHz	/	PK
30 MHz – 1000 MHz	/	/	120 kHz	QP
	100 kHz	300 kHz	/	PK

1-40GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	10 Hz
	<98%	1MHz	≥1/Ton

Note: Ton is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

Radiated Spurious Emission

During the radiated emission test, the adapter was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all the installation combinations.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

All emissions under the average limit and under the noise floor have not recorded in the report.

According to ANSI C63.10-2013,9.4: For field strength measurements made at other than the distance at which the applicable limit is specified, extrapolate the measured field strength to the field strength at the distance specified by the limit using an inverse distance correction factor (20 dB/decade of distance). In some cases, a different distance correction factor may be required;

$$E_{\text{SpecLimit}} = E_{\text{Meas}} + 20 \log \left(\frac{d_{\text{Meas}}}{d_{\text{SpecLimit}}} \right)$$

where

$E_{\text{SpecLimit}}$	is the field strength of the emission at the distance specified by the limit, in dB μ V/m
E_{Meas}	is the field strength of the emission at the measurement distance, in dB μ V/m
d_{Meas}	is the measurement distance, in m
$d_{\text{SpecLimit}}$	is the distance specified by the limit, in m

So the extrapolation factor of 1m is $20 \cdot \log(1/3) = -9.5$ dB, for 18-40GHz range, the limit of 1m distance was added by 9.5dB from limit of 3m to compared with the result measurement at 1m distance.

Factor & Over Limit/Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit} &= \text{Level} - \text{Limit}; \text{Margin} = \text{Limit} - \text{Corrected Amplitude} \\ \text{Level / Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

Test Data

Environmental Conditions

Temperature:	22~25.5 °C
Relative Humidity:	50~54 %
ATM Pressure:	101 kPa

The testing was performed by Anson Su from 2024-04-01 to 2024-04-02 for below 1GHz and Zenos Qiao on 2024-04-16 for above 1GHz.

EUT operation mode: Transmitting


Note: After pre-scan in the X, Y and Z axes of orientation, the worst case z-axis of orientation were recorded.

9 kHz-30MHz: (Maximum output power mode, 802.11 ac 20, 5200MHz)

The amplitude of spurious emissions attenuated more than 20 dB below the limit was not recorded.

30 MHz–1 GHz: (Maximum output power mode, 802.11 ac 20, 5200MHz)


Horizontal



Site : Chamber A
Condition : 3m Horizontal
Project Number: SZ1240308-11508E-RF
Note : 5G WIFI
Tester : Anson Su

	Freq Factor		Read Level		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	Line	Limit	
1	189.74	-12.30	49.99	37.69	43.50	-5.81	QP
2	192.00	-12.05	53.30	41.25	43.50	-2.25	QP
3	195.14	-11.65	52.10	40.45	43.50	-3.05	QP
4	206.58	-11.14	51.60	40.46	43.50	-3.04	QP
5	211.34	-11.22	53.30	42.08	43.50	-1.42	QP
6	215.46	-11.28	54.50	43.22	43.50	-0.28	QP
7	239.99	-11.69	50.00	38.31	46.00	-7.69	QP
8	248.44	-11.83	55.11	43.28	46.00	-2.72	QP
9	252.84	-11.74	55.10	43.36	46.00	-2.64	QP
10	273.11	-10.98	53.50	42.52	46.00	-3.48	QP
11	280.02	-10.72	53.30	42.58	46.00	-3.42	QP
12	283.36	-10.59	52.70	42.11	46.00	-3.89	QP
13	294.76	-10.16	50.90	40.74	46.00	-5.26	QP
14	333.69	-9.89	47.30	37.41	46.00	-8.59	QP
15	347.11	-9.86	46.60	36.74	46.00	-9.26	QP
16	357.93	-9.45	48.19	38.74	46.00	-7.26	QP

Vertical



Site : Chamber A
Condition : 3m Vertical
Project Number: SZ1240308-11508E-RF
Note : 5G WIFI
Tester : Anson Su

		Read		Limit	Over	Remark
Freq Factor		Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	49.40	-17.15	38.58	21.43	40.00	-18.57 QP
2	58.23	-17.56	41.88	24.32	40.00	-15.68 QP
3	92.26	-16.88	40.20	23.32	43.50	-20.18 QP
4	191.33	-12.82	44.10	31.28	43.50	-12.22 QP
5	219.56	-12.24	46.79	34.55	46.00	-11.45 QP
6	606.19	-4.26	39.22	34.96	46.00	-11.04 QP

Above 1GHz:**5150-5250 MHz:**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/AV					
802.11a							
5180MHz							
5147.72	55.60	PK	H	2.70	58.30	74	-15.70
5147.72	47.71	AV	H	2.70	50.41	54	-3.59
5149.19	55.25	PK	V	2.71	57.96	74	-16.04
5149.19	46.97	AV	V	2.71	49.68	54	-4.32
10360.00	45.46	PK	H	13.07	58.53	68.2	-9.67
10360.00	45.23	PK	V	13.07	58.30	68.2	-9.90
5200MHz							
10400.00	45.75	PK	H	13.12	58.87	68.2	-9.33
10400.00	45.54	PK	V	13.12	58.66	68.2	-9.54
5240MHz							
5353.24	55.27	PK	H	3.07	58.34	74	-15.66
5353.24	41.75	AV	H	3.07	44.82	54	-9.18
5354.63	55.12	PK	V	3.07	58.19	74	-15.81
5354.63	41.63	AV	V	3.07	44.70	54	-9.30
10480.00	46.11	PK	H	13.07	59.18	68.2	-9.02
10480.00	45.87	PK	V	13.07	58.94	68.2	-9.26

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/AV					
802.11n20							
5180MHz							
5149.53	57.58	PK	H	2.71	60.29	74	-13.71
5149.53	46.77	AV	H	2.71	49.48	54	-4.52
5149.16	56.94	PK	V	2.71	59.65	74	-14.35
5149.16	46.19	AV	V	2.71	48.90	54	-5.10
10360.00	45.64	PK	H	13.07	58.71	68.2	-9.49
10360.00	45.43	PK	V	13.07	58.50	68.2	-9.70
5200MHz							
10400.00	45.97	PK	H	13.12	59.09	68.2	-9.11
10400.00	45.72	PK	V	13.12	58.84	68.2	-9.36
5240MHz							
5350.78	55.48	PK	H	3.07	58.55	74	-15.45
5350.78	41.87	AV	H	3.07	44.94	54	-9.06
5351.35	44.31	PK	V	3.07	47.38	74	-26.62
5351.35	41.73	AV	V	3.07	44.80	54	-9.20
10480.00	46.29	PK	H	13.07	59.36	68.2	-8.84
10480.00	46.06	PK	V	13.07	59.13	68.2	-9.07

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/AV					
802.11n40							
5190MHz							
5149.53	56.37	PK	H	2.71	59.08	74	-14.92
5149.53	46.54	AV	H	2.71	49.25	54	-4.75
5149.24	56.05	PK	V	2.71	58.76	74	-15.24
5149.24	45.98	AV	V	2.71	48.69	54	-5.31
10380.00	45.37	PK	H	13.09	58.46	68.2	-9.74
10380.00	45.18	PK	V	13.09	58.27	68.2	-9.93
5230MHz							
5350.88	54.87	PK	H	3.07	57.94	74	-16.06
5350.88	42.48	AV	H	3.07	45.55	54	-8.45
5351.39	54.69	PK	V	3.07	57.76	74	-16.24
5351.39	42.26	AV	V	3.07	45.33	54	-8.67
10460.00	45.89	PK	H	13.09	58.98	68.2	-9.22
10460.00	45.71	PK	V	13.09	58.80	68.2	-9.40
802.11ac80							
5210MHz							
5149.84	60.55	PK	H	2.71	63.26	74	-10.74
5149.84	47.87	AV	H	2.71	50.58	54	-3.42
5149.37	59.72	PK	V	2.71	62.43	74	-11.57
5149.37	46.94	AV	V	2.71	49.65	54	-4.35
5355.52	55.19	PK	H	3.07	58.26	74	-15.74
5355.52	42.72	AV	H	3.07	45.79	54	-8.21
5354.85	55.03	PK	V	3.07	58.10	74	-15.90
5354.85	42.57	AV	V	3.07	45.64	54	-8.36
10420.00	45.24	PK	H	13.12	58.36	68.2	-9.84
10420.00	45.05	PK	V	13.12	58.17	68.2	-10.03

Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor


Corrected Amplitude = Factor + Reading


Margin = Corrected. Amplitude - Limit

The other spurious emission which is in the noise floor level was not recorded.


Test plots for Band Edge Measurements (Radiated)


5150-5250MHz:








Test plots for Harmonic Measurements (802.11a, 5180MHz)














FCC §15.407(a), (e) – 26 dB & 6dB EMISSION BANDWIDTH

Applicable Standard

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure

According to KDB789033 D02 section II.C and section II.D

1. Emission Bandwidth (EBW)

- a) Set RBW = approximately 1% of the emission bandwidth.
- b) Set the VBW > RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

2. Minimum Emission Bandwidth for the band 5.725-5.85 GHz

Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.725-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


3. 99% Occupied Bandwidth:

According to ANSI C63.10-2013 Section 12.4.2&6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.

- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW/RBW})]$ below the reference level. Specific guidance is given in 4.1.5.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	48 %
ATM Pressure:	101 kPa

The testing was performed by Bamboo Zhan from 2024-04-22 to 2024-04-26.


EUT operation mode: Transmitting




Test Result: Compliant.

5150-5250MHz:

Test Modes	Test Frequency (MHz)	26 dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
802.11a	5180	28.20	17.40
	5200	30.30	17.80
	5240	30.12	18.12
802.11n-HT20	5180	34.00	18.36
	5200	34.20	18.56
	5240	31.52	18.80
802.11n-HT40	5190	54.24	26.40
	5230	50.56	36.40
802.11ac-VHT80	5210	94.56	76.00
Note: The 99% Occupied Bandwidth have not fall into the band 5250-5350MHz, please refer to the test plots of 99% Occupied Bandwidth			

5150-5250MHz:



802.11a Lowest Channel	99% Emission Bandwidth  Ref: 25 dBm *Att: 30 dB *RBW: 300 kHz Marker 1 [T1]: 5.178520000 GHz, 7.90 dBm *VSW: 1 MHz *SWT: 1 s OSW: 7.400000000 MHz, Temp: 2.144 dBm, LVL: -1.00 dBm 5.171480000 GHz, Temp: 2.191 dBm, LVL: -6.60 dBm 5.188880000 GHz, LVL: -1.09 dBm Center: 5.18 GHz 4 MHz/ Span: 40 MHz ProjectNo.:SZ1240308-11508E-RF Tester:Bamboo Zhan Date: 22.APR.2024 21:07:03
802.11a Middle Channel	99% Emission Bandwidth  Ref: 25 dBm *Att: 30 dB *RBW: 300 kHz Marker 1 [T1]: 5.201280000 GHz, 7.76 dBm *VSW: 1 MHz *SWT: 1 s OSW: 7.800000000 MHz, Temp: 2.177 dBm, LVL: -1.88 dBm 5.191400000 GHz, Temp: 2.191 dBm, LVL: -6.60 dBm 5.209200000 GHz, LVL: -1.09 dBm Center: 5.2 GHz 4 MHz/ Span: 40 MHz ProjectNo.:SZ1240308-11508E-RF Tester:Bamboo Zhan Date: 22.APR.2024 21:04:31
802.11a Highest Channel	99% Emission Bandwidth  Ref: 25 dBm *Att: 30 dB *RBW: 300 kHz Marker 1 [T1]: 5.237880000 GHz, 7.95 dBm *VSW: 1 MHz *SWT: 1 s OSW: 8.120000000 MHz, Temp: 2.144 dBm, LVL: -1.38 dBm 5.231320000 GHz, Temp: 2.171 dBm, LVL: -6.97 dBm 5.249440000 GHz, LVL: -1.09 dBm Center: 5.24 GHz 4 MHz/ Span: 40 MHz ProjectNo.:SZ1240308-11508E-RF Tester:Bamboo Zhan Date: 22.APR.2024 21:00:32

FCC §15.407(a) – CONDUCTED TRANSMITTER OUTPUT POWER

Applicable Standard

For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method PM-G should be applied

- Place the EUT on a bench and set it in transmitting mode.
- Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	48 %
ATM Pressure:	101 kPa

The testing was performed by Bamboo Zhan on 2024-04-22.

EUT operation mode: Transmitting

Test Result: Compliant.

5150-5250 MHz:

Test Modes	Test Frequency (MHz)	Max. Conducted Average Output Power (dBm)	
		Result	Limit
802.11a	5180	14.61	24
	5200	14.61	24
	5240	14.57	24
802.11n-HT20	5180	14.57	24
	5200	14.63	24
	5240	14.61	24
802.11n-HT40	5190	11.94	24
	5230	11.97	24
802.11ac-VHT80	5210	10.07	24
Note: The EUT is a client device.			

FCC §15.407(a) - POWER SPECTRAL DENSITY

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01

Duty cycle $\geq 98\%$


KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-1 should be applied.

Duty cycle $< 98\%$, duty cycle variations are less than $\pm 2\%$

KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-2 should be applied.

Duty cycle $< 98\%$, duty cycle variations exceed $\pm 2\%$

KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-3 should be applied.



Test Data

Environmental Conditions

Temperature:	25°C
Relative Humidity:	48%
ATM Pressure:	101 kPa

The testing was performed by Bamboo Zhan on 2024-04-22.

EUT operation mode: Transmitting

Test Result: Compliant.

5150-5250 MHz:

Test Modes	Test Frequency (MHz)	Reading (dBm/MHz)	Duty Cycle Factor (dB)	Maximum Power Spectral Density (dBm/MHz)	
				Result	Limit
802.11a	5180	4.02	/	4.02	11
	5200	4.10	/	4.10	11
	5240	4.07	/	4.07	11
802.11n-HT20	5180	3.71	0.10	3.81	11
	5200	3.76	0.10	3.86	11
	5240	3.73	0.10	3.83	11
802.11n-HT40	5190	-1.94	0.19	-1.75	11
	5230	-1.89	0.19	-1.70	11
802.11ac-VHT80	5210	-7.14	0.37	-6.77	11
Note: The EUT is a client device.					

Maximum power spectral density

Ref 25 dBm *Att 30 dB RBW 1 MHz Marker 1 [73.1] 4.03 dBm
 VMW 3 MHz SWF 2 s 5.181240900 GHz

Offset 10.5 dB

Center 5.18 GHz 4 MHz/ Span 40 MHz

Ref 25 dBm *Att 30 dB

RBW 1 MHz VBW 3 MHz SWF 2 a

Marker 1 [5.198840000 GHz] 4.10 dBm

dBm

Center 5.2 GHz 4 MHz/ Span 40 MHz

Ref: 25. dBm
 Att: 30. dB
 RBW: 1 MHz
 VBW: 3 MHz
 BW: 2 s
 Marker: 1 [93.1]
 4.07 dBm
 3.241320000 GHz

1.00m
 20dB

Center: 3.24 GHz
 4 MHz/
 Span: 40 MHz

Version 1.0 (2023/10/07)

EUT PHOTOGRAPHS

Please refer to the attachment SZ1240308-11508E-RF External photo and SZ1240308-11508E-RF Internal photo.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment SZ1240308-11508E-RFB Test Setup photo.

******* END OF REPORT *******