FCC TEST REPORT

Test report
On Behalf of
PINGHU WELLYE ELECTRICAL CO.,LTD
For
REMOTE CONTROL
Model No.: TX19, RX74, RX71, RX42, RX65, RX19, RX57, RX75, RX18, RX20, RX25, RX88, RX30, RX12, RX89, RX90, RX91, RX92, RX93, RX94, RX95, RX23, RX41, TX3, TX7, TX9, TX23, TX10, TX20, TX4

FCC ID: 2AJ2H-WYTX19

Prepared for :	**PINGHU WELLYE ELECTRICAL CO.,LTD** **NO.8 Jinhui Road, Xingcang Town Pinghu, China**
Prepared By :	**Shenzhen HUAK Testing Technology Co., Ltd.** **1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street, Bao'an District, Shenzhen, China**

Date of Test:	**Apr. 07, 2021 ~Apr. 15, 2021**
Date of Report:	**Apr. 15, 2021**
Report Number:	**HK2104071042-E**

TEST RESULT CERTIFICATION

Applicant's name ..... : PINGHU WELLYE ELECTRICAL CO.,LTD

Address ..... : NO.8 Jinhui Road, Xingcang Town Pinghu, China

Manufacture's Name..... : PINGHU WELLYE ELECTRICAL CO.,LTD

Address ..... : NO.8 Jinhui Road, Xingcang Town Pinghu, China

Product description

Trade Mark: N/A

Product name ..... : REMOTE CONTROL

Model and/or type reference : TX19, RX74, RX71, RX42, RX65, RX19, RX57, RX75, RX18, RX20, RX25, RX88, RX30, RX12, RX89, RX90, RX91, RX92, RX93, RX94, RX95, RX23, RX41, TX3, TX7, TX9, TX23, TX10, TX20, TX4

Standards ..... : FCC Rules and Regulations Part 15 Subpart C Section 15.249
ANSI C63.10: 2013

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAK Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAK Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Date of Test.....:

Date (s) of performance of tests .....: **Apr. 07, 2021 ~Apr. 15, 2021**

Date of Issue.....: **Apr. 15, 2021**

Test Result .....: **Pass**

Testing Engineer : Gary Qian

(Gary Qian)

Technical Manager : Eden Hu

(Eden Hu)

Authorized Signatory : Jason Zhou

(Jason Zhou)

Table of Contents **Page**

1 . TEST SUMMARY 5
1.1 . Test Procedures And Results 5
1.2 . Test Facility 5
1.3 . Measurement Uncertainty 5
2 . GENERAL INFORMATION 6
2.1 . General Description Of EUT 6
2.2 . Operation of EUT during testing 7
2.3 . Description Of Test Setup 8
2.4 . Measurement Instruments List 9
3 . CONDUCTED EMISSIONS TEST 10
3.1. Conducted Power Line Emission Limit 10
3.2. Test Setup 10
3.3. Test Procedure 10
3.4. Test Result 11
4. RADIATED EMISSION TEST 12
4.1. Radiation Limit 12
4.2. Test Setup 12
4.3. Test Procedure 13
4.4. Test Result 13
5. BAND EDGE 19
5.1. Limits 19
5.2. Test Procedure 19
5.3. Test Result 20
6. OCCUPIED BANDWIDTH MEASUREMENT 22
6.1. Test Setup 22
6.2. Test Procedure 22
6.3. Measurement Equipment Used 22
6.4. Test Result 22
7. ANTENNA REQUIREMENT 24
8. PHOTOGRAPH OF TEST 25
9. PHOTOS OF THE EUT 26

**** Modifited History ****

Revison	Description	Issued Data	Remark
Revsion 1.0	Initial Test Report Release	Apr. 15, 2021	Jason Zhou

1. TEST SUMMARY

1.1. Test Procedures And Results

DESCRIPTION OF TEST	SECTION NUMBER	RESULT
CONDUCTED EMISSIONS TEST	15.207	N/A
RADIATED EMISSION TEST	15.249(a) /15.209	COMPLIANT
BAND EDGE	15.249(d)/15.205	COMPLIANT
OCCUPIED BANDWIDTH MEASUREMENT	15.215（c）	COMPLIANT
ANTENNA REQUIREMENT	15.203	COMPLIANT

1.2. Test Facility

Test Firm : Shenzhen HUAK Testing Technology Co., Ltd.

Address : 1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street, Bao'an District, Shenzhen, China

1.3. Measurement Uncertainty

Measurement Uncertainty

Conducted Emission Expanded Uncertainty	=	2.71dB, k=2
Radiated emission expanded uncertainty(9kHz-30MHz)	=	4.26dB, k=2
Radiated emission expanded uncertainty(30MHz-1000MHz)	=	3.90dB, k=2
Radiated emission expanded uncertainty(Above 1GHz)	=	4.28dB, k=2

2. GENERAL INFORMATION

2.1. General Description Of EUT

Equipment	REMOTE CONTROL
Model Name	TX19
Serial Model	RX74, RX71, RX42, RX65, RX19, RX57, RX75, RX18, RX20, RX25, RX88, RX30, RX12, RX89, RX90, RX91, RX92, RX93, RX94, RX95, RX23, RX41, TX3, TX7, TX9, TX23, TX10, TX20, TX4
Model Difference	All model's the function, software and electric circuit are the same, only with a product color, appearance and model named different. Test sample model: TX19.
FCC ID	2AJ2H-WYTX19
Antenna Type	PCB Antenna
Antenna Gain	0dBi
Operation frequency	2405-2479MHz
Number of Channels	75CH
Modulation Type	GFSK
Power Source	DC 3V from battery
Power Rating	DC 3V from battery

2.1.1. Carrier Frequency of Channels

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2405	**27**	2431	**53**	2457
2	2406	**28**	2432	**54**	2458
3	2407	**29**	2433	**55**	2459
4	2408	**30**	2434	**56**	2460
5	2409	**31**	2435	**57**	2461
6	2410	**32**	2436	**58**	2462
7	2411	**33**	2437	**59**	2463
8	2412	**34**	2438	**60**	2464
9	2413	**35**	2439	**61**	2465
10	2414	**36**	2440	**62**	2466
11	2415	**37**	2440	**63**	2467
12	2416	**38**	2442	**64**	2468
13	2417	**39**	2443	**65**	2469
14	2418	**40**	2444	**66**	2470
15	2419	**41**	2445	**67**	2471
16	2420	**42**	2446	**68**	2472
17	2421	**43**	2447	**69**	2473
18	2422	**44**	2448	**70**	2474
19	2423	**45**	2449	**71**	2475
20	2424	**46**	2450	**72**	2476
21	2425	**47**	2451	**73**	2477
22	2426	**48**	2452	**74**	2478
23	2427	**49**	2453	**75**	2479
24	2428	**50**	2454		
25	2429	**51**	2455		
26	2430	**52**	2456		

2.2. Operation of EUT during testing

Operating Mode
The mode is used: **Transmitting mode**
Low Channel: 2405MHz
Middle Channel: 2440MHz
High Channel: 2479MHz

2.3. Description Of Test Setup

Operation of EUT during testing:

EUT

The sample was placed (0.8m below 1GHz, 1.5m above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages. The worst case is X position.

2.4. Measurement Instruments List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	R&S	ENV216	HKE-002	Jun. 18, 2020	1 Year
2.	Receiver	R&S	ESCI 7	HKE-010	Jun. 18, 2020	1 Year
3.	RF automatic control unit	Tonscend	JS0806-2	HKE-060	Jun. 18, 2020	1 Year
4.	Spectrum analyzer	R&S	FSP40	HKE-025	Jun. 18, 2020	1 Year
5.	Spectrum analyzer	Agilent	N9020A	HKE-048	Jun. 18, 2020	1 Year
6.	Preamplifier	Schwarzbeck	BBV 9743	HKE-006	Jun. 18, 2020	1 Year
7.	EMI Test Receiver	Rohde & Schwarz	ESCI 7	HKE-010	Jun. 18, 2020	1 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	HKE-012	Jun. 18, 2020	1 Year
9.	Loop Antenna	Schwarzbeck	FMZB 1519 B	HKE-014	Jun. 18, 2020	1 Year
10.	Horn Antenna	Schewarzbeck	9120D	HKE-013	Jun. 18, 2020	1 Year
11.	Pre-amplifier	EMCI	EMC051845SE	HKE-015	Jun. 18, 2020	1 Year
12.	Pre-amplifier	Agilent	83051A	HKE-016	Jun. 18, 2020	1 Year
13.	EMI Test Software EZ-EMC	Tonscend	JY3120-B Version	HKE-083	Jun. 18, 2020	N/A
14.	Power Sensor	Agilent	E9300A	HKE-086	Jun. 18, 2020	1 Year
15.	Spectrum analyzer	Agilent	N9020A	HKE-048	Jun. 18, 2020	1 Year
16.	Signal generator	Agilent	N5182A	HKE-029	Jun. 18, 2020	1 Year
17.	Signal Generator	Agilent	83630A	HKE-028	Jun. 18, 2020	1 Year
18.	Shielded room	Shiel Hong	4*3*3	HKE-039	Dec. 17, 2020	3 Year
19.	Hight gain antenna	Schwarzbeck	LB-180400KF	HKE-054	Jun. 18, 2020	1 Year

3. CONDUCTED EMISSIONS TEST

3.1. Conducted Power Line Emission Limit

For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following.

Frequency (MHz)	Maximum RF Line Voltage (dBμV)			
	CLASS A		CLASS B	
	Q.P.	Ave.	Q.P.	Ave.
0.15 - 0.50	79	66	66-56*	56-46*
0.50 - 5.00	73	60	56	46
5.00 - 30.0	73	60	60	50

* Decreasing linearly with the logarithm of the frequency

For intentional device, according to §15.207(a) Line Conducted Emission Limit is same as above table.

3.2. Test Setup



3.3. Test Procedure

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10.
2. Support equipment, if needed, was placed as per ANSI C63.10.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
4. If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.

3.4. Test Result

Not applicable.
Note: EUT power supply by DC Power, so this test item not applicable.

4. RADIATED EMISSION TEST

4.1. Radiation Limit

For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values：

Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.490	300	20log 2400/F (kHz)	2400/F (kHz)
0.490-1.705	30	20log 24000/F (kHz)	24000/F (kHz)
1.705-30	30	20log 30	30
30-88	3	40	100
88-216	3	43.5	150
216-960	3	46	200
Above 960	3	54	500

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

4.2. Test Setup

（1）Radiated Emission Test-Up Frequency Below 30MHz



（2）Radiated Emission Test-Up Frequency 30MHz~1GHz



（3）Radiated Emission Test-Up Frequency Above 1GHz



4.3. Test Procedure

1. Below 1GHz measurement the EUT is placed on turntable which is 0.8m above ground plane. And above 1GHz measurement EUT was placed on low permittivity and low tangent turn table which is 1.5m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The test frequency range from 9KHz to 25GHz per FCC PART 15.33(a).

Note:
For battery operated equipment, the equipment tests shall be performed using a new battery.

4.4. Test Result

PASS
All the test modes completed for test. The worst case of Radiated Emission is CH 01; the test data of this mode was reported.

Below 1GHz Test Results:

Antenna polarity: H



Suspected List									
NO.	Freq. [MHz]	Factor [dB]	Reading [dBμV/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	70.7808	-17.81	27.74	9.93	40.00	30.07	100	254	Horizontal
2	138.7487	-19.10	28.50	9.40	43.50	34.10	100	293	Horizontal
3	261.0911	-13.54	29.04	15.50	46.00	30.50	100	51	Horizontal
4	388.2883	-10.68	27.30	16.62	46.00	29.38	100	48	Horizontal
5	566.9469	-6.49	26.70	20.21	46.00	25.79	100	86	Horizontal
6	666.9570	-4.75	26.56	21.81	46.00	24.19	100	254	Horizontal

Remark: Factor = Cable loss + Antenna factor – Preamplifier; Level = Reading + Factor; Margin = Limit – Level

Antenna polarity: V



Suspected List									
NO.	Freq. [MHz]	Factor [dB]	Reading [dBμV/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	46.5065	-13.65	28.53	14.88	40.00	25.12	100	165	Vertical
2	74.6647	-18.51	33.58	15.07	40.00	24.93	100	306	Vertical
3	119.3293	-16.99	28.00	11.01	43.50	32.49	100	348	Vertical
4	219.3393	-14.58	28.73	14.15	46.00	31.85	100	290	Vertical
5	407.7077	-10.26	27.59	17.33	46.00	28.67	100	236	Vertical
6	665.0150	-4.87	26.86	21.99	46.00	24.01	100	348	Vertical

Remark: Factor = Cable loss + Antenna factor – Preamplifier; Level = Reading + Factor; Margin = Limit – Level

Harmonics and Spurious Emissions

Frequency Range (9 kHz-30MHz)

Frequency (MHz)	Level@3m (dBμV/m)	Limit@3m (dBμV/m)
--	--	--
--	--	--
--	--	--
--	--	--

Note: *1. Emission Level=Reading+ Cable loss+ Antenna factor-Amp factor.*

2. The emission levels are 20 dB below the limit value, which are not reported. It is deemed to comply with the requirement.

Above 1 GHz Test Results:
CH Low (2405MHz)

Horizontal:

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2405	104.94	-5.84	99.1	114	-14.9	peak
2405	83.57	-5.84	77.73	94	-16.27	AVG
4810	54.27	-3.64	50.63	74	-23.37	peak
4810	42.52	-3.64	38.88	54	-15.12	AVG
7215	50.13	-0.95	49.18	74	-24.82	peak
7215	40.65	-0.95	39.7	54	-14.3	AVG
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Vertical:

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2405	110.29	-5.84	104.45	114	-9.55	peak
2405	82.73	-5.84	76.89	94	-17.11	AVG
4810	55.74	-3.64	52.1	74	-21.9	peak
4810	44.16	-3.64	40.52	54	-13.48	AVG
7215	52.22	-0.95	51.27	74	-22.73	peak
7215	40.31	-0.95	39.36	54	-14.64	AVG
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

CH Middle (2440MHz)

Horizontal:

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2440	106.43	-5.71	100.72	114	-13.28	peak
2440	73.83	-5.71	68.12	94	-25.88	AVG
4880	56.33	-3.51	52.82	74	-21.18	peak
4880	43.17	-3.51	39.66	54	-14.34	AVG
7320	53.78	-0.82	52.96	74	-21.04	peak
7320	42.05	-0.82	41.23	54	-12.77	AVG
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Vertical:

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2440	101.61	-5.71	95.9	114	-18.1	peak
2440	80.59	-5.71	74.88	94	-19.12	AVG
4880	52.78	-3.51	49.27	74	-24.73	peak
4880	41.56	-3.51	38.05	54	-15.95	AVG
7320	54.15	-0.82	53.33	74	-20.67	peak
7320	41.73	-0.82	40.91	54	-13.09	AVG
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

CH High (2479MHz)

Horizontal:

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2479	101.36	-5.65	95.71	114	-18.29	peak
2479	81.79	-5.65	76.14	94	-17.86	AVG
4958	52.65	-3.43	49.22	74	-24.78	peak
4958	41.17	-3.43	37.74	54	-16.26	AVG
7437	53.68	-0.75	52.93	74	-21.07	peak
7437	39.71	-0.75	38.96	54	-15.04	AVG
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Vertical:

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2479	102.81	-5.65	97.16	114	-16.84	peak
2479	82.04	-5.65	76.39	94	-17.61	AVG
4958	53.85	-3.43	50.42	74	-23.58	peak
4958	42.34	-3.43	38.91	54	-15.09	AVG
7437	52.17	-0.75	51.42	74	-22.58	peak
7437	37.63	-0.75	36.88	54	-17.12	AVG
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Remark：
(1) Measuring frequencies from 1 GHz to the 25 GHz.
(2) “F” denotes fundamental frequency; “H” denotes spurious frequency. “E” denotes band edge frequency.
(3) * denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
(4)The emissions are attenuated more than 20dB below the permissible limits are not record in the report.
(5) The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120KHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10KHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for peak measurement with peak detector at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average measurement with peak detection at frequency above 1GHz.
(6) When the test results of Peak Detected below the limits of Average Detected, the Average Detected is not need completed. For example: Top Channel at Fundamental 73.16dBuV/m(PK Value) <93.98(AV Limit), at harmonic 53.20 dBuV/m(PK Value) <54 dBuV/m(AV Limit), the Average Detected not need to completed.
(7)All modes of operation were investigated and the worst-case emissions are reported.

5. BAND EDGE

5.1. Limits

FCC PART 15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

5.2. Test Procedure

The band edge compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW to 1MHz and VBM to 3MHz to measure the peak field strength and set RBW to 1MHz and VBW to 10Hz to measure the average radiated field strength.The conducted RF band edge was measured by using a spectrum analyzer. Set span wide enough to capture the highest in-band emission and the emission at the band edge. Set RBW to 1MHz and VBW to 3MHz, to measure the conducted peak band edge.

5.3. Test Result

PASS

Radiated Band Edge Test:

Operation Mode: TX CH Low (2405MHz)

Horizontal (Worst case)

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2310	54.72	-5.81	48.91	74	-25.09	peak
2310	/	-5.81	/	54	/	AVG
2390	55.19	-5.84	49.35	74	-24.65	peak
2390	/	-5.84	/	54	/	AVG
2400	55.69	-5.84	49.85	74	-24.15	peak
2400	/	-5.84	/	54	/	AVG
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Vertical:

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2310	56.74	-5.81	50.93	74	-23.07	peak
2310	/	-5.81	/	54	/	AVG
2390	54.18	-5.84	48.34	74	-25.66	peak
2390	/	-5.84	/	54	/	AVG
2400	56.77	-5.84	50.93	74	-23.07	peak
2400	/	-5.84	/	54	/	AVG
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Operation Mode: TX CH High (2479MHz)

Horizontal (Worst case)

Frequency (MHz)	Reading Result (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2483.50	56.23	-5.65	50.58	74	-23.42	peak
2483.50	/	-5.65	/	54	/	AVG
2500.00	56.74	-5.65	51.09	74	-22.91	peak
2500.00	/	-5.65	/	54	/	AVG
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Vertical:

Frequency (MHz)	Reading Result (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2483.50	57.19	-5.65	51.54	74	-22.46	peak
2483.50	/	-5.65	/	54	/	AVG
2500.00	56.94	-5.65	51.29	74	-22.71	peak
2500.00	/	-5.65	/	54	/	AVG
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.						
Remark: All the other emissions not reported were too low to read and deemed to comply with FCC limit.						

6. OCCUPIED BANDWIDTH MEASUREMENT

6.1. Test Setup

Same as Radiated Emission Measurement

6.2. Test Procedure

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Set EUT as normal operation.
3. Based on ANSI C63.10 section 6.9.2: RBW= 10KHz. VBW= 30 KHz, Span=1MHz.
4. The useful radiated emission from the EUT was detected by the spectrum analyser with peak detector.

6.3. Measurement Equipment Used

Same as Radiated Emission Measurement

6.4. Test Result

PASS

Frequency	20dB Bandwidth (MHz)	Result
2405 MHz	0.4918	**PASS**
2440 MHz	0.4571	**PASS**
2479 MHz	0.4817	**PASS**

CH: 2405MHz



CH: 2440MHz



CH: 2479MHz



7. ANTENNA REQUIREMENT

Standard Applicable
For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna Connected Construction
The antenna used in this product is a PCB Antenna which permanently attached. It conforms to the standard requirements. The directional gains of antenna used for transmitting is 0dBi.

ANTENNA



8. PHOTOGRAPH OF TEST

Radiated Emission





9. PHOTOS OF THE EUT

Reference to the reporter : ANNEX A of external photos and ANNEX B of internal photos.

---------End of test report---------