

RF Exposure Evaluation

FCC ID: 2AJ2I-S888

1. Client Information

Applicant : Fugle Products (HK)Company Limited
Address : ROOM 1103, HANG SENG MONGKOK BUILDING 677 NATHAN ROAD
MONGKOK, KOWLOON HONG KONG
Manufacturer : Shenzhen Shengxingwang Precision Technology Co., Ltd.
Address : No.4 Long Jing Road, YangMei Village, Bantian Street, Longgang
District, Shenzhen, China

2. General Description of EUT

EUT Name	:	True wireless earbuds	
Models No.	:	S888	
Model Difference	:	N/A	
Product Description	:	Operation Frequency:	Bluetooth 4.1: 2402~2480 MHz
		Number of Channel:	Bluetooth: 79 Channels See Note 2
		Max Peak Output Power:	Bluetooth: 0.203 dBm(GFSK)
		Antenna Gain:	-4.65 dBi TDA Antenna
		Modulation Type:	GFSK 1Mbps(1 Mbps) π /4-DQPSK(2 Mbps) 8-DPSK(3 Mbps)
Power Supply	:	DC power by USB cable. DC power by Li-ion battery.	
Power Rating	:	EUT-1: DC 5V by USB Cable. DC 3.7V by 2000mAh Li-ion Battery. EUT-2: DC 3.7V by 35mAh Li-ion Battery.	
Connecting I/O Port(S)	:	Please refer to the User's Manual	
Note: EUT-1: Charging Box EUT-2: Headsets			

Note:

More test information about the EUT please refer to the RF Test Report.

SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

- (1) Clause 4.3: General SAR test reduction and exclusion guidance

- Sub clause 4.31: Standalone SAR test exclusion considerations

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance ≤ 5 mm are determined by:

- [(max. power of channel, including tune-up tolerance, mW)/(min. test separation, mm)] * $[\sqrt{f_{\text{GHz}}}] \leq 3.0$ for 1-g SAR

- [(max. power of channel, including tune-up tolerance, mW)/(min. test separation, mm)] * $[\sqrt{f_{\text{GHz}}}] \leq 7.5.0$ for 10-g SAR

2.

Calculation:

Test separation: 5mm					
Bluetooth Mode (GFSK)					
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	-0.985	±0.5	0.894	0.277	3.0
2.441	-0.704	±0.5	0.954	0.298	3.0
2.480	0.203	±0.5	1.176	0.370	3.0
Bluetooth Mode (π /4-DQPSK)					
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	-0.100	±0.5	1.096	0.340	3.0
2.441	-0.700	±0.5	0.955	0.298	3.0
2.480	-0.814	±0.5	0.930	0.293	3.0
Bluetooth Mode (8-DPSK)					
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	0.114	±0.5	1.152	0.357	3.0
2.441	-0.453	±0.5	1.011	0.316	3.0
2.480	-0.610	±0.5	0.975	0.307	3.0

So standalone SAR measurements are not required.

-----END OF REPORT-----