


	 MARKING ELECTROMAGNETIC COMPATIBILITY ELECTRICAL SAFETY LASER SPECTROSCOPY ENVIRONMENTAL PHYSICS	G.S.D. S.r.l. Certified in accordance with UNI EN ISO 9001:2008 by TÜV Rheinland Italia S.r.l. Certificate N. 39 00 1850509
G.S.D. S.r.l PISA - Italy	Test Report n. 16767mpe	Rev. 01
Manufacturer	MOTION S.P.A.	
Address	Via Biondini 27 47121 Forlì (FC) Italy	
Test Family Name	PTR6100M -- nRF24L01+	
FCC ID	2AJ5S0001	
IC ID	22061-0001	
Testing Laboratory Name	G.S.D. S.r.l.	
Address	Via Marmiceto, 8 56121 Ospedaletto Pisa (PI) Italy	
Tel/Fax	+39 050 984254 / +39 050 984262	
P.IVA/VAT	01343950505	
http – e-mail	www.gsd.it - info@gsd.it	
FCC Listed: Registration Number: 424037		
IC Listed: Registration Number: 9353A		
Location and Date of Issue	Pisa, 2016 December 02	
G.S.D. s.r.l. Via Marmiceto, 8 56121 OSPEDALETTO - PISA Tel. 050.984254 - Fax 050.984262 P. IVA 01343950505 SENIOR EMC TEST MANAGER <i>Dr. Gian Luca Genovesi</i>  QUALITY MANAGER <i>Dr. David Pelliccia</i> 		

INDEX	
1.MAXIMUM PERMISSIBLE EXPOSURE.....	3

1. MAXIMUM PERMISSIBLE EXPOSURE
Prediction of RF Exposure were calculated accordingly to KDB 447498 D01v06
Result
Per KDB 447498 D01 v06
For 100 MHz to 6 GHz and <i>test separation distances</i> ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following: $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where: • $f(\text{GHz})$ is the RF channel transmit frequency in GHz • Power and distance are rounded to the nearest mW and mm before calculation • The result is rounded to one decimal place for comparison. • The values 3.0 and 7.5 are referred to as <i>numeric thresholds</i> in step b) The test exclusions are applicable only when the minimum <i>test separation distance</i> is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum <i>test separation distance</i> is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion. d (distance) = 5 mm f = 2.4 GHz $\sqrt{f(\text{GHz})} = 1.55$ $P_{\text{max}} = 2.512$ mW
Conclusion: accordingly to KDB 447498 D01v06 exclusion threshold is $0.77 < 3$, RF exposure evaluation is not required.