

Maximum Permissible Exposure Report

1. Product Information

FCC ID	: 2AJ6DTODAAIR4G
EUT	: 4G Router/4G LTE/Wireless Router
Test Model	: TD954G2
Additional Model No.	TD4G38, TD954G, TD-GPRS-1MW, TD4GAC2, TD-RW3F-AM, TD-RW3G-AM, TD-RW3G-AMZ, TD-RW5G-AM, TD-RW5G-AMZ, TD4G32
Model declaration	PCB board, structure and internal of these model(s) are the same, So no additional models were tested.
Power Supply	: Adapter parameter: Input: AC 100-240V, 50/60Hz, 0.5A Output: DC 24V, 0.5A
Hardware Version	: TD-95
Software Version	: TD-95
2G	:
Support Band	: ☐ GSM 900 (EU-Band) ☐ DCS 1800 (EU-Band) ☒ GSM 850 (U.S.-Band) ☒ PCS 1900 (U.S.-Band)
Release Version	: R99
GPRS Class	: Class 12
EGPRS Class	: Class 12
Type Of Modulation	: GMSK for GSM/GPRS; 8PSK for EGPRS
Antenna Description	: PIFA Antenna; -1.43dBi (max.) For GSM 850; 1.75dBi (max.) For PCS 1900.
3G	:
Support Band	: ☒ WCDMA Band II (U.S.-Band) ☒ WCDMA Band V (U.S.-Band) ☒ WCDMA Band IV (U.S.-Band) ☐ WCDMA Band I (EU-Band) ☐ WCDMA Band VIII (EU-Band)
Release Version	: R8
Type Of Modulation	: WCDMA: QPSK; HSDPA/HSUPA: QPSK
Antenna Description	: PIFA Antenna; 1.75dBi (max.) For WCDMA Band II; 1.46dBi (max.) For WCDMA Band IV; -1.43dBi (max.) For WCDMA Band V.
LTE	:
Support Band	: ☒ E-UTRA Band 2(U.S.-Band) ☒ E-UTRA Band 4(U.S.-Band) ☒ E-UTRA Band 5(U.S.-Band) ☒ E-UTRA Band 12(U.S.-Band) ☒ E-UTRA Band 13(U.S.-Band) ☒ E-UTRA Band 14(U.S.-Band)

☒ E-UTRA Band 66(U.S.-Band)
☒ E-UTRA Band 71(U.S.-Band)

LTE Release Version : R13

Type Of Modulation : QPSK/16QAM

Antenna Description : PIFA Antenna;
1.75dBi (max.) For E-UTRA Band 2;
1.46dBi (max.) For E-UTRA Band 4;
-1.43dBi (max.) For E-UTRA Band 5;
-1.73dBi (max.) For E-UTRA Band 12;
-0.35dBi (max.) For E-UTRA Band 13;
0.60dBi (max.) For E-UTRA Band 14;
1.46dBi (max.) For E-UTRA Band 66;
-1.73dBi (max.) For E-UTRA Band 71.

Power Class : Class 3

WIFI(2.4G Band) :

Frequency Range : 2412MHz ~ 2462MHz

Channel Spacing : 5MHz

Channel Number : 11 Channel for 20MHz bandwidth(2412~2462MHz)
9 channels for 40MHz bandwidth(2422~2452MHz)

Modulation Type : 802.11b: DSSS; 802.11g/n: OFDM

Antenna Description : PIFA Antenna, 5.0dBi(Max.)

Exposure category : General population/uncontrolled environment

EUT Type : Production Unit

Device Type : Mobile Device

2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer Evaluation Method

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Antenna Information

Jiangmen Todaair Electronics Co., Ltd can only use antennas certificated as follows provided by manufacturer;

Antenna type and antenna number	Operate frequency band	Maximum antenna gain	Notes
PIFA Antenna	2400 MHz – 2500 MHz	5.0 dBi	WLAN ANT
PIFA Antenna	1850~1910 MHz	1.75 dBi	GSM/WCDMA/LTE Main ANT
PIFA Antenna	1710~1755 MHz	1.46dBi	WCDMA/LTE Main ANT
PIFA Antenna	824~849 MHz	-1.43dBi	GSM/WCDMA/LTE Main ANT
PIFA Antenna	669~716 MHz	-1.73dBi	LTE Main ANT
PIFA Antenna	777~787 MHz	-0.35dBi	LTE Main ANT
PIFA Antenna	788~798 MHz	0.60dBi	LTE Main ANT
PIFA Antenna	1710~1780 MHz	1.46dBi	LTE Main ANT
PIFA Antenna	663~698 MHz	-1.73dBi	LTE Main ANT

6. Conducted Power

[WIFI Max Peak Conducted Power]

Mode	Channel	Peak Power [dBm]			Limit [dBm]	Verdict
		Ant 0	Ant 1	Sum		
11B	LCH	14.63	14.27	/	30	PASS
	MCH	14.39	14.89	/	30	PASS
	HCH	13.69	14.76	/	30	PASS
11G	LCH	13.70	13.71	/	30	PASS
	MCH	14.91	14.36	/	30	PASS
	HCH	14.39	14.25	/	30	PASS
11N20	LCH	13.96	13.87	16.93	27.99	PASS
	MCH	14.58	14.58	17.59	27.99	PASS
	HCH	14.03	14.52	17.29	27.99	PASS
11N40	LCH	12.54	13.55	16.08	27.99	PASS
	MCH	13.74	13.81	16.79	27.99	PASS
	HCH	13.79	13.75	16.78	27.99	PASS

[GSM Max Average Power]

Test Mode	Channel	Frequency (MHz)	Max Average Power (dBm)
PCS 1900	Low	1850.2	29.69
	Middle	1880.0	29.73
	High	1909.8	29.67

GSM 850	Low	824.2	32.65
	Middle	836.6	32.70
	High	848.8	32.68

[WCDMA Max Average Power]

Test Mode	Channel	Frequency (MHz)	Max Average Power (dBm)
WCDMA Band II	Low	1852.4	23.59
	Middle	1880.0	23.65
	High	1907.6	23.53
WCDMA Band V	Low	826.4	23.54
	Middle	836.4	23.53
	High	846.6	23.43

WCDMA Band IV	Low	1712.4	23.16
	Middle	1732.6	23.32
	High	1752.6	23.45

[LTE Max Average Power]

Test Mode		Channel	Max Average Power (dBm)
LTE	Band 2	LCH	23.25
		MCH	23.81
		HCH	23.23
	Band 4	LCH	23.69
		MCH	23.81
		HCH	23.91
	Band 5	LCH	23.92
		MCH	24.20
		HCH	24.39
	Band 12	LCH	22.71
		MCH	24.10
		HCH	25.04
	Band 13	LCH	24.44
		MCH	24.91
		HCH	25.03
	Band 14	LCH	23.52
		MCH	23.93
		HCH	23.74
	Band 66	LCH	23.97
		MCH	23.97
		HCH	24.00
	Band 71	LCH	23.98
		MCH	24.00
		HCH	23.99

7. Manufacturing Tolerance

[WIFI Max Conducted Power]

Test Mode	Channel	Max Conducted Power (dBm)	ANT Max. Tune Up Power (dBm)
WIFI	B	14.89	14.0±1.0
	G	14.36	14.0±1.0
	N 20	17.59	17.0±1.0
	N 40	16.79	16.0±1.0

[GSMMax Average Power]

Test Mode	Channel	Max Average Power (dBm)	ANT Max. Tune Up Power (dBm)
PCS1900	LCH	29.69	29.0±1.0
	MCH	29.73	29.0±1.0
	HCH	29.67	29.0±1.0
GSM850	LCH	32.65	32.0±1.0
	MCH	32.70	32.0±1.0
	HCH	32.68	32.0±1.0

[WCDMA Max Average Power]

Test Mode	Channel	Max Average Power (dBm)	ANT Max. Tune Up Power (dBm)
WCDMA	Band II	LCH	23.59
		MCH	23.65
		HCH	23.53
	Band V	LCH	23.54
		MCH	23.53
		HCH	23.43
	Band IV	LCH	23.16
		MCH	23.32
		HCH	23.45
			23.0±1.0

<LTE Max Average Power>

Test Mode	Channel	Max Average Power (dBm)	ANT Max. Tune Up Power (dBm)
LTE	Band 2	LCH	23.25
		MCH	23.81
		HCH	23.23
	Band 4	LCH	23.69
		MCH	23.81
		HCH	23.91
	Band 5	LCH	23.92
		MCH	24.20
		HCH	24.39
	Band 12	LCH	22.71
		MCH	24.10
		HCH	25.04
	Band 13	LCH	24.44
		MCH	24.91
		HCH	25.03
	Band 14	LCH	23.52
		MCH	23.93
		HCH	23.74
	Band 66	LCH	23.97
		MCH	23.97
		HCH	24.00
	Band 71	LCH	23.98

		MCH	24.00	23.0±1.0
		HCH	23.99	23.0±1.0

8. Measurement Results

8.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
WLAN	18.0	63.0957	8.01	6.3241	0.0794	1.0

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
GSM 850	33.0	1995.2623	-1.43	0.7194	0.2856	0.55
PCS1900	30.0	1000.0000	1.75	1.4962	0.2977	1.0
WCDMA Band II	24.0	251.1886	1.75	1.4962	0.0748	1.0
WCDMA Band IV	24.0	251.1886	1.46	1.3996	0.0699	1.0
WCDMA Band V	24.0	251.1886	-1.43	0.7194	0.0360	0.55
LTE Band 2	24.0	251.1886	1.75	1.4962	0.0748	1.0
LTE Band 4	24.0	251.1886	1.46	1.3996	0.0699	1.0
LTE Band 5	25.0	316.2278	-1.43	0.7194	0.0453	0.55
LTE Band 12	25.5	354.8134	-1.73	0.6714	0.0474	0.47
LTE Band 13	26.0	398.1072	-0.35	0.9226	0.0731	0.52
LTE Band 14	24.0	251.1886	0.60	1.1482	0.0574	0.53
LTE Band 66	24.0	251.1886	1.46	1.3996	0.0699	1.0
LTE Band 71	24.0	251.1886	-1.73	0.6714	0.0336	0.44

Remark:

1. Output power including turn-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer;
3. We choose the lowest frequency operate to calculate MPE limit as higher frequency will have higher MPE limits;
4. $MPE\ values = PG/4\pi R^2$.

8.2 Simultaneous Transmission MPE

The sample support two WIFI Antenna and another one GSM&&WCDMA& LTE transmit antenna, so need consider simultaneous transmission;

Simultaneous transmission MPE

According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

$\sum$ of MPE ratios ≤ 1.0

Mode	$\sum$ MPE max ratios	Limit	Results
WIFI + GSM	0.599	1.0	Pass
WIFI + WCDMA	0.154	1.0	Pass
WIFI + LTE	0.220	1.0	Pass

9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----