

RF Exposure Compliance Requirement

1. Standard requirement

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	F/300	6
1500-100000	--	--	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	F/1500	30
1500-100000	--	--	1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

2. MPE Calculation Method

$$E (V/m) = (30 \cdot P \cdot G)^{0.5} / d \quad \text{Power Density: } P_d (W/m^2) = E^2 / 377$$

E=Electric Field (V/m)

P=Peak RF output Power (W)

G=EUT Antenna numeric gain (numeric)

d= Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

3. Calculated Result and Limit

For BT FHSS Type only:

Normal mode-GFSK modulation type with DH5 data packet:

Frequency (MHz)	Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2402	2.239	4.36	2.729	0.00122	1	Complies
2441	2.239	5.98	3.963	0.00176	1	Complies
2480	2.239	6.10	4.074	0.00181	1	Complies

EDR mode only-8DPSK modulation type with 3DH5 data packet::

Frequency (MHz)	Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2402	2.239	2.49	1.774	0.00079	1	Complies
2441	2.239	4.67	2.931	0.00131	1	Complies
2480	2.239	4.98	3.148	0.00140	1	Complies

For DSSS Type only::

Frequency (MHz)	Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2404	2.239	7.22	5.272	0.00235	1	Complies
2444	2.239	6.93	4.932	0.00220	1	Complies
2479	2.239	5.73	3.741	0.00167	1	Complies



SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch

Application No.: GZEM1610006811AV

Page: 3 of 3

FCC ID: 2AJ8KB0029RA

The device is a synchronous transmitter with two wireless modules for emission signal at same time. Below worst case was recorded.

The max peak output power from the device should be 9.346mw.

Power density is 0.00416(mW/cm²) < Limit 1 (mW/cm²).

Conclusion:

The device meets the maximum permissible exposure requirement.