

























8.5 RADIATED SPURIOUS EMISSION

8.5.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 D01 15.247 Meas Guidance v05r02

8.5.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (uV/m)	300
0.490-1.705	2400/F(KHz)	20 log (uV/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

8.5.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

8.5.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz(1GHz to 25GHz), 100 kHz for $f < 1$ GHz(30MHz to 1GHz), 200Hz for $f < 150$ KHz(9KHz to 150KHz), 9KHz for $f < 30$ MHz(150KHz to 30KHz)

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2020 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

8.5.5 Test Results

Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

■ Spurious Emission below 30MHz(9KHz to 30MHz)

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance}/\text{test distance})$ (dB);

Limit line = Specific limits(dBuV) + distance extrapolation factor

- Spurious Emission Above 1GHz(1GHz to 25GHz)
- All modes 2.4G 802.11b/g/n have been tested, and the worst result of 802.11b recorded was report as below:

Test mode: 802.11 b Frequency: Channel 1: 2412MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
4822.5	V	50.02	48.69	74	54	23.98	5.31
8467.5	V	58.62	38.00	74	54	15.38	16.00
17979.375	V	67.79	50.78	74	54	6.21	3.22
4882.5	H	49.96	32.03	74	54	24.04	21.97
9905.625	H	60.34	41.60	74	54	13.66	12.40
17531.25	H	67.58	50.88	74	54	6.42	3.12

Test mode: 802.11 b Frequency: Channel 6: 2437MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
4873.125	V	49.48	48.49	74	54	24.52	5.51
9898.125	V	59.60	41.75	74	54	14.40	12.25
17705.625	V	67.43	47.77	74	54	6.57	6.23
4873.125	H	49.65	48.12	74	54	24.35	5.88
8334.375	H	58.66	38.26	74	54	15.34	15.74
16987.5	H	67.75	49.77	74	54	6.25	4.23

Test mode: 802.11 b Frequency: Channel 11: 2462MHz


Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
4923.75	V	50.47	48.33	74	54	23.53	5.67
11298.75	V	62.92	44.94	74	54	11.08	9.06
17490	V	67.81	50.74	74	54	6.19	3.26
4923.75	H	50.28	48.14	74	54	23.72	5.86
11291.25	H	64.18	44.98	74	54	9.82	9.02
16745.625	H	67.65	46.88	74	54	6.35	7.12

- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).
 - (2) Emission Level= Reading Level+Correct Factor +Cable Loss.
 - (3) Correct Factor= Ant_F + Cab_L - Preamp
 - (4)The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.


■ Spurious Emission above 1GHz (1GHz to 18GHz)

All modes have been tested, and the worst result recorded was report as below:


Test mode: 802.11 b Frequency: Channel 1: 2412MHz V




Test mode: 802.11 b Frequency: Channel 1: 2412MHz H




Test mode: 802.11 b Frequency: Channel 6: 2437MHz V




Test mode: 802.11 b Frequency: Channel 6: 2437MHz H



Test mode: 802.11 b Frequency: Channel 11: 2462MHz V



Test mode: 802.11 b Frequency: Channel 11: 2462MHz H



■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz
All modes 2.4G 802.11b/g/n have been tested, and the worst result of 802.11b recorded was report as below:

Test mode: 802.11 n20 Frequency: Channel 1: 2412MHz

Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2389.75	H	63.79	74.00	39.38	54.00
2388.93	V	58.27	74.00	39.33	54.00

Test mode: 802.11 n20 Frequency: Channel 11: 2462MHz

Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2484.01	H	65.55	74.00	39.51	54.00
2483.67	V	60.12	74.00	39.43	54.00


Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).
(2) Emission Level= Reading Level+Correct Factor +Cable Loss.
(3) Correct Factor= Ant_F + Cab_L - Preamp
(4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Spurious Emission in Restricted Band 2310-2390MHz

Test Model ☐ 802.11b ☐ 802.11g ☒ 802.11n(HT20) ☐ 802.11n(HT40)

☒ Channel 1: 2412MHz ☐ Channel 3: 2422MHz Polarity: H

VBW=3MHz




Spurious Emission in Restricted Band 2310-2390MHz

Test Model ☐ 802.11b ☐ 802.11g ☒ 802.11n(HT20) ☐ 802.11n(HT40)


☒ Channel 1: 2412MHz ☐ Channel 3: 2422MHz Polarity: V

VBW=3MHz




Spurious Emission in Restricted Band 2483.5-2500MHz

Test Model	☐ 802.11b	☐ 802.11g	☒ 802.11n(HT20)	☐ 802.11n(HT40)
	☒ Channel 11: 2462MHz		☐ Channel 9: 2452MHz	
	VBW=3MHz		Polarity: H	




Spurious Emission in Restricted Band 2483.5-2500MHz

Test Model	☐ 802.11b	☐ 802.11g	☒ 802.11n(HT20)	☐ 802.11n(HT40)
	☒ Channel 11: 2462MHz		☐ Channel 9: 2452MHz	
	VBW=3MHz		Polarity: V	




- Spurious Emission below 1GHz (30MHz to 1GHz)
- All modes 2.4G 802.11b/g/n have been tested, and the worst result of 802.11b recorded was report as below:

2412



Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	31.9419	23.20	8.09	31.29	PK	40.00	8.71	Vertical
2	36.7968	26.08	8.87	34.95	PK	40.00	5.05	Vertical
3	51.3614	23.92	10.89	34.81	PK	40.00	5.19	Vertical
4	91.1712	28.27	9.05	37.32	PK	43.50	6.18	Vertical
5	349.4494	20.89	14.68	35.57	PK	46.00	10.43	Vertical
6	599.96	19.67	19.80	39.47	PK	46.00	6.53	Vertical

Final Data List					
NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	31.9419	8.09	30.99	40.00	9.01
2	36.7968	8.87	34.65	40.00	5.35
3	51.3614	10.89	33.87	40.00	6.13
4	91.1712	9.05	36.74	43.50	6.76
5	349.4494	14.68	34.99	46.00	11.01
6	599.96	19.80	38.89	46.00	7.11




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	249.4394	27.53	11.71	39.24	PK	46.00	6.76	Horizontal
2	299.9299	26.28	13.36	39.64	PK	46.00	6.36	Horizontal
3	349.4494	25.52	14.68	40.20	PK	46.00	5.80	Horizontal
4	399.9399	24.77	15.46	40.23	PK	46.00	5.77	Horizontal
5	650.4504	20.37	18.70	39.07	PK	46.00	6.93	Horizontal
6	950.4805	17.78	21.68	39.46	PK	46.00	6.54	Horizontal

Final Data List


NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	249.4394	11.71	38.50	46.00	7.50
2	299.9299	13.36	39.26	46.00	6.74
3	349.4494	14.68	39.82	46.00	6.18
4	399.9399	15.46	39.69	46.00	6.31
5	650.4504	18.70	38.89	46.00	7.11
6	950.4805	21.68	39.28	46.00	6.72

2437



Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	31.9419	23.49	8.09	31.58	PK	40.00	8.42	Vertical
2	36.7968	24.98	8.87	33.85	PK	40.00	6.15	Vertical
3	51.3614	23.49	10.89	34.38	PK	40.00	5.62	Vertical
4	97.968	25.31	10.06	35.37	PK	43.50	8.13	Vertical
5	349.4494	21.71	14.68	36.39	PK	46.00	9.61	Vertical
6	599.96	19.62	19.80	39.42	PK	46.00	6.58	Vertical

Final Data List					
NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	31.9419	8.09	30.99	40.00	9.01
2	36.7968	8.87	33.62	40.00	6.38
3	51.3614	10.89	34.15	40.00	5.85
4	97.968	10.06	34.97	43.50	8.53
5	349.4494	14.68	35.99	46.00	10.01
6	599.96	19.80	39.02	46.00	6.98




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	249.4394	27.40	11.71	39.11	PK	46.00	6.89	Horizontal
2	299.9299	27.32	13.36	40.68	PK	46.00	5.32	Horizontal
3	349.4494	25.75	14.68	40.43	PK	46.00	5.57	Horizontal
4	384.4044	24.44	15.12	39.56	PK	46.00	6.44	Horizontal
5	650.4504	20.14	18.70	38.84	PK	46.00	7.16	Horizontal
6	950.4805	17.09	21.68	38.77	PK	46.00	7.23	Horizontal

Final Data List


NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	249.4394	11.71	38.48	46.00	7.52
2	299.9299	13.36	40.41	46.00	5.59
3	349.4494	14.68	40.16	46.00	5.84
4	384.4044	15.12	39.12	46.00	6.88
5	650.4504	18.70	38.76	46.00	7.24
6	950.4805	21.68	38.69	46.00	7.31

2462



Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	30.971	23.86	7.93	31.79	PK	40.00	8.21	Vertical
2	36.7968	25.36	8.87	34.23	PK	40.00	5.77	Vertical
3	51.3614	23.62	10.89	34.51	PK	40.00	5.49	Vertical
4	68.8388	25.72	8.75	34.47	PK	40.00	5.53	Vertical
5	349.4494	21.28	14.68	35.96	PK	46.00	10.04	Vertical
6	599.96	18.57	19.80	38.37	PK	46.00	7.63	Vertical

Final Data List					
NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	30.971	7.93	30.80	40.00	9.20
2	36.7968	8.87	34.08	40.00	5.92
3	51.3614	10.89	34.36	40.00	5.64
4	68.8388	8.75	33.68	40.00	6.32
5	349.4494	14.68	35.17	46.00	10.83
6	599.96	19.80	37.94	46.00	8.06



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	249.4394	27.38	11.71	39.09	PK	46.00	6.91	Horizontal
2	299.9299	26.24	13.36	39.60	PK	46.00	6.40	Horizontal
3	349.4494	24.90	14.68	39.58	PK	46.00	6.42	Horizontal
4	399.9399	24.86	15.46	40.32	PK	46.00	5.68	Horizontal
5	650.4504	21.06	18.70	39.76	PK	46.00	6.24	Horizontal
6	950.4805	17.42	21.68	39.10	PK	46.00	6.90	Horizontal

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	249.4394	11.71	38.10	46.00	7.90
2	299.9299	13.36	38.61	46.00	7.39
3	349.4494	14.68	38.95	46.00	7.05
4	399.9399	15.46	39.53	46.00	6.47
5	650.4504	18.70	38.97	46.00	7.03
6	950.4805	21.68	38.67	46.00	7.33

8.6 CONDUCTED EMISSIONS TEST

8.6.1 Applicable Standard

According to FCC Part 15.207(a)

8.6.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

8.6.3 Test Configuration

Test according to clause 7.3conducted emission test setup


8.6.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.
Maximum procedure was performed on the highest emissions to ensure EUT compliance.
Repeat above procedures until all frequency measured were complete.

8.6.5 Test Results

Pass

The 120V &240V voltagehave been tested, and the worst result recorded was report as below:



Site Conduction #1

Phase: **L1**

Temperature: 24.2


Limit: (CE)FCC PART 15 class B_QP

Power: AC 120V/60Hz

Humidity: 51 %

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1500	42.61	10.06	52.67	66.00	-13.33	QP	
2		0.1500	23.64	10.06	33.70	56.00	-22.30	AVG	
3		0.4340	31.06	10.12	41.18	57.18	-16.00	QP	
4		0.4340	14.05	10.12	24.17	47.18	-23.01	AVG	
5		1.0900	19.21	10.17	29.38	56.00	-26.62	QP	
6		1.0900	14.51	10.17	24.68	46.00	-21.32	AVG	
7		6.9060	20.28	10.93	31.21	60.00	-28.79	QP	
8		6.9060	11.64	10.93	22.57	50.00	-27.43	AVG	
9		13.5620	26.52	12.73	39.25	60.00	-20.75	QP	
10		13.5620	22.43	12.73	35.16	50.00	-14.84	AVG	
11		17.8300	20.49	14.08	34.57	60.00	-25.43	QP	
12		17.8300	13.22	14.08	27.30	50.00	-22.70	AVG	



Site Conduction #1

Phase: **N**

Temperature: 24.2

Limit: (CE)FCC PART 15 class B_QP

Power: AC 120V/60Hz

Humidity: 51 %

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1540	41.53	10.07	51.60	65.78	-14.18	QP	
2		0.1540	20.66	10.07	30.73	55.78	-25.05	AVG	
3		0.4500	30.26	10.12	40.38	56.88	-16.50	QP	
4		0.4500	20.01	10.12	30.13	46.88	-16.75	AVG	
5		1.8220	18.47	10.26	28.73	56.00	-27.27	QP	
6		1.8220	14.32	10.26	24.58	46.00	-21.42	AVG	
7		6.1900	20.99	10.82	31.81	60.00	-28.19	QP	
8		6.1900	14.86	10.82	25.68	50.00	-24.32	AVG	
9		13.5660	25.60	12.73	38.33	60.00	-21.67	QP	
10		13.5660	20.10	12.73	32.83	50.00	-17.17	AVG	
11		17.8540	18.43	14.09	32.52	60.00	-27.48	QP	
12		17.8540	9.69	14.09	23.78	50.00	-26.22	AVG	

8.7 ANTENNA APPLICATION

8.7.1 Antenna Requirement

Standard	Requirement
FCC CRF Part15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

8.7.2 Result

PASS.

- The EUT has a PCB Antenna for WIFI 2.4G, the antenna gain is 2.20 dBi.

Note: ☒ Antenna uses a permanently attached antenna which is not replaceable.
☐ Not using a standard antenna jack or electrical connector for antenna replacement
☐ The antenna has to be professionally installed (please provide method of installation)

Which in accordance to section 15.203, please refer to the internal photos.

Detail of factor for radiated emission

Frequency(MHz)	Ant_F(dB)	Cab_L(dB)	Preamp(dB)	Correct Factor(dB)
0.009	20.6	0.03	\	20.63
0.15	20.7	0.1	\	20.8
1	20.9	0.15	\	21.05
10	20.1	0.28	\	20.38
30	18.8	0.45	\	19.25
30	11.7	0.62	27.9	-15.58
100	12.5	1.02	27.8	-14.28
300	12.9	1.91	27.5	-12.69
600	19.2	2.92	27	-4.88
800	21.1	3.54	26.6	-1.96
1000	22.3	4.17	26.2	0.27
1000	25.6	1.76	41.4	-14.04
3000	28.9	3.27	43.2	-11.03
5000	31.1	4.2	44.6	-9.3
8000	36.2	5.95	44.7	-2.55
10000	38.4	6.3	43.9	0.8
12000	38.5	7.14	42.3	3.34
15000	40.2	8.15	41.4	6.95
18000	45.4	9.02	41.3	13.12
18000	37.9	1.81	47.9	-8.19
21000	37.9	1.95	48.7	-8.85
25000	39.3	2.01	42.8	-1.49
28000	39.6	2.16	46.0	-4.24
31000	41.2	2.24	44.5	-1.06
34000	41.5	2.29	46.6	-2.81
37000	43.8	2.30	46.4	-0.3
40000	43.2	2.50	42.2	3.5

*** End of Report ***