

11B_Ant1_2412




11B_Ant1_2437




11B_Ant1_2462




11G_Ant1_2412




11G_Ant1_2437




11G_Ant1_2462




11N20SISO_Ant1_2412




11N20SISO_Ant1_2437




11N20SISO_Ant1_2462




11N40SISO_Ant1_2422



11N40SISO_Ant1_2437



11N40SISO_Ant1_2452



8.5 UNWANTED EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS

8.5.1 Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 D01 15.247 Meas Guidance v05r02

According to RSS-247, 5.5

8.5.2 Conformance Limit

According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

8.5.3 Test Configuration

Test according to clause 6.1 radio frequency test setup

8.5.4 Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

■ Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to ≥ 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

■ Band-edge measurement

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the emission operating on the channel closest to the band-edge, as well as any modulation products which fall outside of the authorized band of operation

Set RBW $\geq 1\%$ of the span=100kHz Set VBW $\geq 3 \times$ RBW

Set Sweep = auto Set Detector function = peak Set Trace = max hold

Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. The marker-delta value now displayed must comply with the limit specified in this Section.

■ Emission level measurement

Set the center frequency and span to encompass frequency range to be measured.

Set the RBW = 100 kHz.

Set the VBW = 300 kHz.

Set Detector = peak

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements. Report the three highest emissions relative to the limit.

8.5.5 Test Results

Temperature:	25 °C
Relative Humidity:	45%
ATM Pressure:	1011 mbar

Note: N/A

All the antenna (Antenna 1) and modes (802.11b/g/n) have been tested and the worst (Antenna 1, 802.11b) result recorded was reported as below:




TestMode	Antenna	Frequency[MHz]	FreqRange [Mhz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
11B	Ant1	2412	Reference	5.19	5.19	---	PASS
			30~1000	5.19	-45.73	≤-24.81	PASS
			1000~26500	5.19	-31.33	≤-24.81	PASS
		2437	Reference	3.35	3.35	---	PASS
			30~1000	3.35	-45.91	≤-26.65	PASS
			1000~26500	3.35	-30.26	≤-26.65	PASS
		2462	Reference	6.35	6.35	---	PASS
			30~1000	6.35	-45.89	≤-23.65	PASS
			1000~26500	6.35	-30.86	≤-23.65	PASS



11B Ant1 2412 0~Reference




11B Ant1 2412 30~1000






11B_Ant1_2437_30~1000




11B_Ant1_2437_1000~26500



11B Ant1_2462 0~Reference




11B Ant1_2462 30~1000





TestMode	Antenna	ChName	Frequency[MHz]	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	Low	2412	5.38	-35.98	≤-24.62	PASS
		High	2462	6.38	-36.69	≤-23.62	PASS



8.6 RADIATED SPURIOUS EMISSION

8.6.1 Applicable Standard

According to FCC Part 15.247(d), 15.205, 15.209 and KDB 558074 D01 15.247 Meas Guidance v05r02
According to IC RSS-Gen and RSS-247

8.6.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.205 the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Field Strength ($\text{dB}\mu\text{V/m}$)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log ($\mu\text{V/m}$)	300
0.490-1.705	24000/F(KHz)	20 log ($\mu\text{V/m}$)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

8.6.3 Test Configuration

Test according to clause 6.2 radio frequency test setup

8.6.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

For Above 1GHz:

The EUT was placed on a turn table which is 1.5m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 1GHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 100 kHz for

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 30MHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 9kHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 150KHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 200Hz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit. Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

8.6.5 Test Results

Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

■ Spurious Emission below 30MHz(9KHz to 30MHz)

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance}/ \text{test distance})$ (dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor

■ Spurious Emission Above 1GHz(1GHz to 25GHz)

All the antenna(Antenna 1)and modes(802.11b/g/n)have been tested and the worst(Antenna 1,802.11b) result recorded was report as below:

Test mode:		802.11b		Frequency:		Channel 1: 2412MHz	
Freq. (MHz)	Ant.Pol.	Reading Level (dBuV/m)	Correct Factor (dB/m)	Corrected Reading (dBuV/m)	Limit 3m (dBuV/m)	Margin (dB)	Remark
5320.153	V	50.14	-5.66	44.48	74.00	-29.52	Peak
5320.153	V	32.12	-5.66	26.46	54.00	-27.54	Avg
10113.66	V	49.22	5.36	54.58	74.00	-19.42	Peak
10113.66	V	31.02	5.36	36.38	54.00	-17.62	Avg
17860.07	V	50.48	13.80	64.28	74.00	-9.72	Peak
17860.07	V	32.44	13.80	46.24	54.00	-7.76	Avg
	V						Peak
	V						Avg
	V						Peak
	V						Avg
	V						Peak
	V						Avg
4604.267	H	48.85	-7.51	41.34	74.00	-32.66	Peak
4604.267	H	30.84	-7.51	23.33	54.00	-30.67	Avg
14611.82	H	49.80	8.19	57.99	74.00	-16.01	Peak
14611.82	H	31.69	8.19	39.88	54.00	-14.12	Avg
17997.39	H	50.06	14.51	64.57	74.00	-9.43	Peak
17997.39	H	31.86	14.51	46.37	54.00	-7.63	Avg
	H						Peak
	H						Avg
	H						Peak
	H						Avg
	H						Peak
	H						Avg
Note: (1) Peak RBW=1 MHz, VBW ≥3×RBW, Detector=Peak; (2) Avg RBW=1 MHz, VBW=1/T _{on} , Detector=Peak, where: T _{on} is transmit duration; (3) Corrected Reading= Reading Level+Correct Factor; (4) Correct Factor= Ant_F + Cab_L- Preamp; (5) Margin = Limit - Corrected Reading;							

Test mode: 802.11b Frequency: Channel 6: 2437MHz

Freq. (MHz)	Ant.Pol.	Reading Level (dBuV/m)	Correct Factor (dB/m)	Corrected Reading (dBuV/m)	Limit 3m (dBuV/m)	Margin (dB)	Remark
5424.968	V	49.59	-5.50	44.09	74.00	-29.91	Peak
5424.968	V	31.57	-5.50	26.07	54.00	-27.93	Avg
12596.39	V	50.32	6.24	56.56	74.00	-17.44	Peak
12596.39	V	32.30	6.24	38.54	54.00	-15.46	Avg
17839.43	V	49.74	13.68	63.42	74.00	-10.58	Peak
17839.43	V	31.72	13.68	45.40	54.00	-8.60	Avg
	V						Peak
	V						Avg
	V						Peak
	V						Avg
	V						Peak
	V						Avg
4376.535	H	48.67	-8.17	40.50	74.00	-33.50	Peak
4376.535	H	30.57	-8.17	22.40	54.00	-31.60	Avg
12574.57	H	48.94	6.24	55.18	74.00	-18.82	Peak
12574.57	H	31.93	6.24	38.17	54.00	-15.83	Avg
17885.90	H	50.12	13.93	64.05	74.00	-9.95	Peak
17885.90	H	32.10	13.93	46.03	54.00	-7.97	Avg
	H						Peak
	H						Avg
	H						Peak
	H						Avg
	H						Peak
	H						Avg
Note: (1) PeakRBW=1 MHz, VBW $\geq 3 \times$ RBW, Detector=Peak; (2) Avg RBW=1 MHz, VBW=1/T _{on} , Detector=Peak, where: T _{on} is transmit duration; (3) Corrected Reading= Reading Level+Correct Factor; (4) Correct Factor= Ant_F + Cab_L- Preamp; (5) Margin = Limit - Corrected Reading;							

Test mode: 802.11b Frequency: Channel 11: 2462MHz

Freq. (MHz)	Ant.Pol.	Reading Level (dBuV/m)	Correct Factor (dB/m)	Corrected Reading (dBuV/m)	Limit 3m (dBuV/m)	Margin (dB)	Remark
4415.926	V	48.40	-8.03	40.37	74.00	-33.63	Peak
4415.926	V	30.33	-8.03	22.30	54.00	-31.70	Avg
9784.430	V	49.83	4.64	54.47	74.00	-19.53	Peak
9784.430	V	31.76	4.64	36.40	54.00	-17.60	Avg
17916.94	V	50.21	14.09	64.30	74.00	-9.70	Peak
17916.94	V	32.11	14.09	46.20	54.00	-7.80	Avg
	V						Peak
	V						Avg
	V						Peak
	V						Avg
	V						Peak
	V						Avg
6933.776	H	48.71	-0.69	48.02	74.00	-25.98	Peak
6933.776	H	30.70	-0.69	30.01	54.00	-23.99	Avg
10485.74	H	52.97	5.62	58.59	74.00	-15.41	Peak
10485.74	H	34.72	5.62	40.34	54.00	-13.66	Avg
17916.94	H	49.56	14.09	63.65	74.00	-10.35	Peak
17916.94	H	31.51	14.09	45.60	54.00	-8.40	Avg
	H						Peak
	H						Avg
	H						Peak
	H						Avg
	H						Peak
	H						Avg
Note: (1) PeakRBW=1 MHz, VBW ≥3×RBW, Detector=Peak; (2) Avg RBW=1 MHz, VBW=1/T _{on} , Detector=Peak, where: T _{on} is transmit duration; (3) Corrected Reading= Reading Level+Correct Factor; (4) Correct Factor= Ant_F + Cab_L- Preamp; (5)Margin = Limit - Corrected Reading;							

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

All the antenna(Antenna 1) and modes(802.11b/g/n) have been tested and the worst(Antenna 1,802.11b) result recorded was report as below:

Test mode: 802.11b Frequency: Channel 1: 2412MHz


Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2387.456	H	50.20	74.00	32.26	54.00
2388.532	V	50.01	74.00	32.03	54.00

Test mode: 802.11b Frequency: Channel 11: 2462MHz


Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2483.535	H	51.61	74.00	33.78	54.00
2483.643	V	53.05	74.00	35.11	54.00

- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
 - (2) Emission Level= Reading Level+Correct Factor.
 - (3) Correct Factor= Ant_F + Cab_L - Preamp
 - (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.


Test Model	802.11b	Spurious Emission in Restricted Band 2310-2390MHz	Channel 1: 2412MHz	VBW=3MHz	Polarity: H
------------	---------	---	--------------------	----------	-------------




Test Model	802.11b	Spurious Emission in Restricted Band 2310-2390MHz	Channel 1: 2412MHz	VBW=3MHz	Polarity: V
------------	---------	---	--------------------	----------	-------------



Test Model	802.11b	Spurious Emission in Restricted Band 2483.5-2500MHz	Channel 11: 2462MHz	VBW=3MHz	Polarity: H
------------	---------	---	---------------------	----------	-------------




Test Model	802.11b	Spurious Emission in Restricted Band 2483.5-2500MHz	Channel 11: 2462MHz	VBW=3MHz	Polarity: V
------------	---------	---	---------------------	----------	-------------




■ Spurious Emission below 1GHz (30MHz to 1GHz)


All the antenna(Antenna 1) and modes(802.11b/g/n) have been tested and the worst(Antenna 1,802.11b) result recorded was report as below:




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		895.0328	29.75	5.63	35.38	46.00	-10.62	QP		
2		560.2015	33.74	0.05	33.79	46.00	-12.21	QP		
3		276.6081	30.94	-5.83	25.11	46.00	-20.89	QP		
4		115.5230	30.70	-9.84	20.86	43.50	-22.64	QP		
5	*	52.2995	41.90	-7.39	34.51	40.00	-5.49	QP		
6		47.2840	41.18	-7.90	33.28	40.00	-6.72	QP		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		51.5033	31.75	-7.41	24.34	40.00	-15.66	QP		
2		162.7532	33.49	-9.86	23.63	43.50	-19.87	QP		
3		257.7610	38.16	-6.86	31.30	46.00	-14.70	QP		
4	*	379.7477	35.94	-3.24	32.70	46.00	-13.30	QP		
5		480.1065	33.09	-1.79	31.30	46.00	-14.70	QP		
6		963.0061	33.50	4.06	37.56	54.00	-16.44	QP		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree degree	Comment
1		77.1180	34.96	-10.00	24.96	40.00	-15.04	QP			
2		162.7532	33.49	-9.86	23.63	43.50	-19.87	QP			
3		257.7610	38.16	-6.86	31.30	46.00	-14.70	QP			
4		379.7477	35.94	-3.24	32.70	46.00	-13.30	QP			
5	*	560.2015	34.80	0.05	34.85	46.00	-11.15	QP			
6		963.0061	33.50	4.06	37.56	54.00	-16.44	QP			



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	51.6390	42.26	-7.41	34.85	40.00	-5.15	QP		
2		66.1501	36.76	-7.84	28.92	40.00	-11.08	QP		
3		83.9627	40.03	-10.90	29.13	40.00	-10.87	QP		
4		276.0026	31.95	-5.84	26.11	46.00	-19.89	QP		
5		560.2015	35.14	0.05	35.19	46.00	-10.81	QP		
6		847.3132	28.65	6.67	35.32	46.00	-10.68	QP		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	51.6390	42.26	-7.41	34.85	40.00	-5.15	QP		
2		83.9627	40.03	-10.90	29.13	40.00	-10.87	QP		
3		261.4018	37.56	-6.68	30.88	46.00	-15.12	QP		
4		560.2015	35.78	0.05	35.83	46.00	-10.17	QP		
5		800.3817	30.57	5.62	36.19	46.00	-9.81	QP		
6		976.6087	32.56	4.49	37.05	54.00	-16.95	QP		



Site 3m Chamber #1

Polarization: **Vertical**

Temperature: 28.1 C

Limit: (RE)FCC PART 15 CLASS B

Power: AC 120V/60Hz

Humidity: 43 %

Mode: WIFI2.4G 2462

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		47.6168	41.66	-7.95	33.71	40.00	-6.29	QP		
2	*	51.9795	41.86	-7.39	34.47	40.00	-5.53	QP		
3		83.9995	40.58	-10.90	29.68	40.00	-10.32	QP		
4		259.0067	32.20	-6.79	25.41	46.00	-20.59	QP		
5		559.9560	33.33	0.05	33.38	46.00	-12.62	QP		
6		881.7932	29.27	5.57	34.84	46.00	-11.16	QP		

8.7 CONDUCTED EMISSION TEST

8.7.1 Applicable Standard

According to FCC Part 15.207(a)

According to IC RSS-Gen 8.8

8.7.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

8.7.3 Test Configuration

Test according to clause 6.3conducted emission test setup

8.7.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.


Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Repeat above procedures until all frequency measured were complete.

8.7.5 Test Results

Pass

The AC120V &240V voltage have been tested, and the worst result recorded was report as below:



Site Conduction #1

Phase: **L1**

Temperature: 21.9

Limit: (CE)FCC PART 15 class B_QP


Power: AC 120V/60Hz

Humidity: 58 %

Mode: WIFI 2.4G mode

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1500	36.23	9.53	45.76	66.00	-20.24	QP	
2		0.1500	14.63	9.53	24.16	56.00	-31.84	AVG	
3		0.3150	26.18	9.53	35.71	59.84	-24.13	QP	
4		0.3150	18.58	9.53	28.11	49.84	-21.73	AVG	
5		0.5450	11.40	9.53	20.93	56.00	-35.07	QP	
6		0.5450	3.01	9.53	12.54	46.00	-33.46	AVG	
7		3.4500	22.90	9.56	32.46	56.00	-23.54	QP	
8		3.4500	7.93	9.56	17.49	46.00	-28.51	AVG	
9	*	8.9800	33.50	9.67	43.17	60.00	-16.83	QP	
10		8.9800	23.00	9.67	32.67	50.00	-17.33	AVG	
11		17.0550	29.94	9.87	39.81	60.00	-20.19	QP	
12		17.0550	19.70	9.87	29.57	50.00	-20.43	AVG	



Site Conduction #1

Phase: **N**

Temperature: 21.9

Limit: (CE)FCC PART 15 class B_QP

Power: AC 120V/60Hz

Humidity: 58 %

Mode: WIFI 2.4G mode

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1500	35.99	9.53	45.52	66.00	-20.48	QP	
2		0.1500	17.18	9.53	26.71	56.00	-29.29	AVG	
3		0.2700	24.67	9.53	34.20	61.12	-26.92	QP	
4		0.2700	14.68	9.53	24.21	51.12	-26.91	AVG	
5		0.3200	24.17	9.53	33.70	59.71	-26.01	QP	
6		0.3200	17.17	9.53	26.70	49.71	-23.01	AVG	
7		3.6050	21.73	9.56	31.29	56.00	-24.71	QP	
8		3.6050	8.31	9.56	17.87	46.00	-28.13	AVG	
9		9.0300	33.03	9.67	42.70	60.00	-17.30	QP	
10		9.0300	22.17	9.67	31.84	50.00	-18.16	AVG	
11	*	13.5300	34.37	9.78	44.15	60.00	-15.85	QP	
12		13.5300	19.41	9.78	29.19	50.00	-20.81	AVG	

8.8 ANTENNA APPLICATION

8.8.1 Antenna Requirement

Standard	Requirement
FCC CRF Part15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
FCC 47 CFR Part 15.247 (b)	If transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.
RSS-Gen Section 6.8	The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.
RSS-247 Section 5.4	If the transmitter employs an antenna system that emits multiple directional beams, but does not emit multiple directional beams simultaneously, the total output power conducted to the array or arrays that comprise the device (i.e. the sum of the power supplied to all antennas, antenna elements, staves, etc., and summed across all carriers or frequency channels) shall not exceed the applicable output power limit. However, the total conducted output power shall be reduced by 1 dB below the specified limits for each 3 dB that the directional gain of the antenna/antenna array exceeds 6 dBi. The directional antenna gain shall be computed as the sum of 10 log (number of array elements or staves) plus the directional gain of the element or stave having the highest gain.

8.8.2 Result

PASS.

- Note:
- ☒ Antenna use a permanently attached antenna which is not replaceable.
 - ☐ Not using a standard antenna jack or electrical connector for antenna replacement
 - ☐ The antenna has to be professionally installed (please provide method of installation)

Please refer to the attached document Internal Photos to show the antenna connector.

*** End of Report ***