

TEST REPORT

Product Name : Smart Reader
Model Number : KR901, KR901S, KR902, KR902S, KR903,
KR904, AC03-KR91H-01, AC03-KR92H-01,
AC03-KR93H-01, AC03-KR94H-01
FCC ID : 2AJ9T-21207

Prepared for : ZKTECO CO., LTD.
Address : No.32, Pingshan Industrial Avenue, Tangxia Town,
Dongguan City, Guangdong Province, China 523728

Prepared by : EMTEK (SHENZHEN) CO., LTD.
Address : Building 69, Majialong Industry Zone, Nanshan District,
Shenzhen, Guangdong, China

Tel: (0755) 26954280
Fax: (0755) 26954282

Report Number : ENS2508120052W00401R
Date(s) of Tests : August 13, 2025 to September 9, 2025
Date of issue : September 10, 2025

TABLE OF CONTENTS

1 EUT TECHNICAL DESCRIPTION	5
2 SUMMARY OF TEST RESULT	6
3 TEST METHODOLOGY	7
3.1 GENERAL DESCRIPTION OF APPLIED STANDARDS	7
3.2 MEASUREMENT EQUIPMENT USED	7
3.3 DESCRIPTION OF TEST MODES	7
4 FACILITIES AND ACCREDITATIONS	9
4.1 FACILITIES	9
4.2 LABORATORY ACCREDITATIONS AND LISTINGS	9
5 TEST SYSTEM UNCERTAINTY	10
6 SETUP OF EQUIPMENT UNDER TEST	11
6.1 RADIO FREQUENCY TEST SETUP 1	11
6.2 RADIO FREQUENCY TEST SETUP 2	11
6.3 CONDUCTED EMISSION TEST SETUP	12
6.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM	13
6.5 SUPPORT EQUIPMENT	13
7 TEST REQUIREMENTS	14
7.1 OCCUPIED BANDWIDTH	14
7.2 RADIATED SPURIOUS EMISSION	16
7.3 CONDUCTED EMISSION TEST	26
8 ANTENNA APPLICATION	29

TEST RESULT CERTIFICATION

Applicant : ZKTECO CO., LTD.
Address : No.32, Pingshan Industrial Avenue, Tangxia Town, Dongguan City, Guangdong Province, China 523728
Manufacturer : ZKTECO CO., LTD.
Address : No.32, Pingshan Industrial Avenue, Tangxia Town, Dongguan City, Guangdong Province, China 523728
EUT : Smart Reader
Model Name : KR901, KR901S, KR902, KR902S, KR903, KR904, AC03-KR91H-01, AC03-KR92H-01, AC03-KR93H-01, AC03-KR94H-01
Trademark : N/A

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C	PASS

The above equipment was tested by EMTEK(SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207&15.209.

The test results of this report relate only to the tested sample identified in this report.

Date of Test : August 13, 2025 to September 9, 2025

Prepared by : 
Una Yu/Editor

Reviewer : 
Joe Xia/Supervisor

Approved & Authorized Signer : 
Lisa Wang/Manager

Modified Information

Version	Report No.	Revision Date	Summary
Ver1.0	ENS2508120052W00401R	/	Original Report



1 EUT TECHNICAL DESCRIPTION

Product:	Smart Reader
Model Number:	KR901, KR901S, KR902, KR902S, KR903, KR904, AC03-KR91H-01, AC03-KR92H-01, AC03-KR93H-01, AC03-KR94H-01 (Note: The models are identical on circuitry design, PCB layout, electrical components used, internal wiring and functions; only different mold colors, We chose KR904 as the final test prototype)
Test Voltage:	AC 120V/60Hz
Power Supply:	DC 9-12V input
Adapter:	MODEL:ADS-40SI-12-3 12036E INPUT: AC100-240V~50Hz/60Hz,Max.1.0A OUTPUT:12.0V,3.0A
Test Voltage:	AC 120V/60Hz
Modulation:	ASK
Frequency Range:	125KHz
Antenna Type:	Induction coil antenna
Antenna Gain:	0 dBi
Temperature Range:	-20°C~+60°C

Note: For more details, please refer to the user's manual of the EUT.

2 SUMMARY OF TEST RESULT

FCC Part Clause	Test Parameter	Verdict	Remark
2.1049	Occupied Bandwidth	PASS	
15.209	Radiated Spurious Emissions	PASS	
15.207	Conducted Emission	PASS	
NOTE1: N/A (Not Applicable)			

RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for **FCC ID:2AJ9T-21207** filing to comply with Section 15.225 of the FCC Part 15, Subpart C Rules.



3 TEST METHODOLOGY

3.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:
FCC 47 CFR Part 2, Subpart J
FCC 47 CFR Part 15, Subpart C

3.2 MEASUREMENT EQUIPMENT USED

Conducted Emission Test Equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
EMI Test Receiver	Rohde & Schwarz	ESCI	101384	2025/5/13	1Year
AMN	Rohde & Schwarz	ENV216	101161	2025/5/13	1Year
AMN	Kyoritsu	KNW-407	8-1492-9	2025/5/11	1Year

For Spurious Emissions Test:

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
Pre-Amplifier	Bonn	BLMA 011001N	2213967A	2024/10/18	1Year
EMI Test Receiver	Rohde & Schwarz	ESR7	102551	2024/10/18	1Year
Bilog Antenna	Schwarzbeck	VULB9163	9163142	2024/7/8	2Year
Horn antenna	Schwarzbeck	BBHA9120D	9120D-1198	2025/5/13	2Year
Pre-Amplifier	Bonn	BLMA 0118-5G	2213967B-01	2024/10/18	1Year
Spectrum Analyzer	Rohde & Schwarz	FSV3044	101290	2024/10/18	1Year
Horn antenna	Schwarzbeck	BBHA9170	9170-399	2025/5/13	2Year
Pre-Amplifier	Lunar EM	LNA18G26-40	J1012131010001	2025/5/9	1Year
Pre-Amplifier	Lunar EM	LNA26G40-40	J1013131028001	2025/5/9	1Year
Loop Antenna	Schwarzbeck	FMZB1519	1519-012	2025/5/13	2Year
Coaxial Cable	TIMES	NmNm-7-C15702	N/A	2025/5/9	1Year
Coaxial Cable	TIMES	HF290-NMSM-6.5M	N/A	2025/5/9	1Year
Coaxial Cable	TIMES	LMR-240 N-N	N/A	2025/5/9	1Year

For Other Test Items:

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
Wideband Radio Communication Tester	R&S	CMW500	171168	2024/9/18	1Year
Frequency Extender	R&S	CMW-Z800A	100430	2024/9/18	1Year
Spectrum Analyzer	R&S	FSV3044	101289	2024/12/17	1Year
Analog Signal Generator	R&S	SMB100A	183237	2024/9/18	1Year
Vector Signal Generator	R&S	SMM100A	101808	2024/9/18	1Year
RF Control Unit(Power Meter)	Tonscend	JS0806-2	22C8060567	2024/9/18	1Year
Temperature&Humidity Chamber	ESPEC	EL-02KA	12107166	2025/5/10	1 Year
DC Power Supply	KEYSIGHT	E3642A	MY53030016	2024/9/18	1 Year

3.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting mode is programmed.



4 FACILITIES AND ACCREDITATIONS

4.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

Building 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

4.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab.

: **Accredited by CNAS**

The Certificate Registration Number is L2291

The Laboratory has been assessed and proved to be in compliance with CNAS-CL01 (identical to ISO/IEC 17025:2017)

Accredited by FCC

Designation Number: CN1204

Test Firm Registration Number: 882943

Accredited by A2LA

The Certificate Number is 4321.01

Accredited by Industry Canada

The Conformity Assessment Body Identifier is CN0008

Name of Firm

: EMTEK (SHENZHEN) CO., LTD.

Site Location

: Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China

5 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Conducted Emissions Test	$\pm 2.0\text{dB}$
Radiated Emission Test	$\pm 2.0\text{dB}$
Occupied Bandwidth Test	$\pm 1.0\text{dB}$
All emission, radiated	$\pm 3\text{dB}$
Temperature	$\pm 0.5^\circ\text{C}$
Humidity	$\pm 3\%$


Measurement Uncertainty for a level of Confidence of 95%



6 SETUP OF EQUIPMENT UNDER TEST

6.1 RADIO FREQUENCY TEST SETUP 1

The component's antenna port(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



6.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.


Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.


Above 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

(a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz




6.3 CONDUCTED EMISSION TEST SETUP


The mains cable of the EUT (maybe per AC/DC Adapter) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.

According to the requirements in ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



6.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM



6.5 SUPPORT EQUIPMENT

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite

Auxiliary Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. Unless otherwise denoted as EUT in 『Remark』 column , device(s) used in tested system is a support equipment

7 TEST REQUIREMENTS

7.1 OCCUPIED BANDWIDTH

7.1.1 Applicable Standard

According to FCC Part 2.1049

7.1.2 Conformance Limit

No limit requirement.

7.1.3 Test Configuration

Test according to clause 6.1 radio frequency test setup 1

7.1.4 Test Procedure

The EUT was operating in transmit mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 1% occupied bandwidth (30Hz).

Set the video bandwidth (VBW) = 3 times RBW .

Set Span= approximately 2 to 3 times the occupied bandwidth

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 99% down one side of the emission. Reset the markerdelta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 99% bandwidth of the emission.

If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

Measure and record the results in the test report.

7.1.5 Test Results


Temperature :	23.4℃	Test Date :	August 14, 2025
Humidity :	42 %	Test By:	HYD

Modulation Mode	Channel Number	Channel Frequency (KHz)	-20dB Measurement Bandwidth (kHz)	Limit (kHz)	Verdict
ASK	0	125	0.02517	N/A	PASS
Note: N/A (Not Applicable)					

Test Model

20dB Bandwidth
Channel 0: 125KHz

ASK Modulation



7.2 RADIATED SPURIOUS EMISSION

7.2.1 Applicable Standard

According to FCC Part 15.209

7.2.2 Conformance Limit

FCC Part 15.209				
Frequency (MHz)	Field Strength Limitation		Field Strength Limitation Frequency tion at 3m Measurement Dist	
	(uV/m)	Dist	(uV/m)	(dBuV/m)
0.009 – 0.490	2400 / F(KHz)	300m	10000 * 2400/F(KHz)	20log 2400/F(KHz) + 80
0.490 – 1.705	24000 / F(KHz)	30m	100 * 24000/F(KHz)	20log 24000/F(KHz) + 40
1.705 – 30.00	30	30m	100* 30	20log 30 + 40
30.0 – 88.0	100	3m	100	20log 100
88.0 – 216.0	150	3m	150	20log 150
216.0 – 960.0	200	3m	200	20log 200
Above 960.0	500	3m	500	20log 500

According to FCC Part15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

- Remark:
1. Emission level in dBuV/m=20 log (uV/m)
 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
 3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of § 15.205, and the emissions located in restricted bands also comply with 15.209 limit.

7.2.3 Test Configuration

Test according to clause 6.2 radio frequency test setup 2

7.2.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 100 kHz for $f < 1$ GHz(30MHz to 1GHz), 200Hz for $f < 150$ KHz(9KHz to 150KHz), 9KHz for $f < 30$ MHz(150KHz to 30KHz)

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold


Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.


Repeat above procedures until all frequency measured was complete.

7.2.5 Test Results


■ Spurious Emission below 30MHz (9KHz to 30MHz)




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		0.0111	26.83	20.29	47.12	126.68	-79.56	peak		
2		0.0170	24.20	20.23	44.43	122.98	-78.55	peak		
3		0.0326	19.59	20.17	39.76	117.33	-77.57	peak		
4		0.0634	13.83	20.67	34.50	111.55	-77.05	peak		
5		0.0884	11.38	20.42	31.80	108.67	-76.87	peak		
6	*	0.1253	36.16	20.55	56.71	105.64	-48.93	peak		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		0.0130	24.46	20.27	44.73	125.31	-80.58	peak		
2		0.0221	23.58	20.18	43.76	120.70	-76.94	peak		
3		0.0372	18.56	20.28	38.84	116.18	-77.34	peak		
4		0.0625	13.89	20.66	34.55	111.68	-77.13	peak		
5		0.0831	13.99	20.50	34.49	109.20	-74.71	peak		
6	*	0.1253	36.17	20.55	56.72	105.64	-48.92	peak		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		0.0120	24.73	20.28	45.01	126.00	-80.99	peak		
2		0.0221	23.58	20.18	43.76	120.70	-76.94	peak		
3		0.0372	18.56	20.28	38.84	116.18	-77.34	peak		
4		0.0468	15.98	20.52	36.50	114.19	-77.69	peak		
5		0.0831	13.99	20.50	34.49	109.20	-74.71	peak		
6	*	0.1253	36.17	20.55	56.72	105.64	-48.92	peak		



Site 3m Chamber #2

Polarization: X

Temperature: 22.4 C

Limit: (RE)FCC PART 15.209(9K-30M)


Power: DC 12V

Humidity: 52 %


Mode: 125K

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		0.1862	22.43	20.45	42.88	102.20	-59.32	peak		
2		0.4786	15.34	20.87	36.21	94.00	-57.79	peak		
3	*	2.1552	13.01	20.48	33.49	69.50	-36.01	peak		
4		4.6714	11.72	20.57	32.29	69.50	-37.21	peak		
5		10.3422	11.89	19.87	31.76	69.50	-37.74	peak		
6		23.8877	12.44	20.16	32.60	69.50	-36.90	peak		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		0.2173	21.44	20.50	41.94	100.86	-58.92	peak		
2	*	0.5980	15.83	20.84	36.67	72.07	-35.40	peak		
3		2.3584	12.58	20.46	33.04	69.50	-36.46	peak		
4		4.7970	11.63	20.58	32.21	69.50	-37.29	peak		
5		8.5916	11.47	19.88	31.35	69.50	-38.15	peak		
6		22.6551	11.87	20.15	32.02	69.50	-37.48	peak		



Site 3m Chamber #2

Polarization: Z

Temperature: 22.4 C

Limit: (RE)FCC PART 15.209(9K-30M)

Power: DC 12V

Humidity: 52 %


Mode:125K

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		0.2172	21.44	20.50	41.94	100.86	-58.92	peak		
2	*	1.4874	13.85	20.55	34.40	64.18	-29.78	peak		
3		2.3584	12.58	20.46	33.04	69.50	-36.46	peak		
4		4.7970	11.63	20.58	32.21	69.50	-37.29	peak		
5		8.8223	10.92	19.84	30.76	69.50	-38.74	peak		
6		22.6551	11.87	20.15	32.02	69.50	-37.48	peak		

■ Spurious Emission Above 30MHz (30MHz to 1GHz)

Mode:	125KHz
-------	--------




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	54.2743	48.27	-16.60	31.67	PK	40.00	8.33	Vertical
2	67.8679	42.90	-18.48	24.42	PK	40.00	15.58	Vertical
3	121.271	42.78	-18.67	24.11	PK	43.50	19.39	Vertical
4	175.645	41.86	-18.77	23.09	PK	43.50	20.41	Vertical
5	704.824	30.88	-5.83	25.05	PK	46.00	20.95	Vertical
6	739.779	31.40	-5.25	26.15	PK	46.00	19.85	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	54.2743	-16.60	31.52	40.00	8.48
2	67.8679	-18.48	24.27	40.00	15.73
3	121.2713	-18.67	23.96	43.50	19.54
4	175.6456	-18.77	22.94	43.50	20.56
5	704.8248	-5.83	24.90	46.00	21.10
6	739.7798	-5.25	26.00	46.00	20.00

Mode:	125KHz
-------	--------



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	40.6807	39.71	-17.36	22.35	PK	40.00	17.65	Horizontal
2	54.2743	37.79	-16.60	21.19	PK	40.00	18.81	Horizontal
3	587.337	31.04	-6.81	24.23	PK	46.00	21.77	Horizontal
4	709.679	30.98	-5.79	25.19	PK	46.00	20.81	Horizontal
5	840.760	31.20	-4.33	26.87	PK	46.00	19.13	Horizontal
6	923.293	31.52	-2.66	28.86	PK	46.00	17.14	Horizontal

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	40.6807	-17.36	21.95	40.00	18.05
2	54.2743	-16.60	20.63	40.00	19.37
3	587.3373	-6.81	23.67	46.00	22.33
4	709.6797	-5.79	24.99	46.00	21.01
5	840.7608	-4.33	26.50	46.00	19.50
6	923.2933	-2.66	28.49	46.00	17.51

7.3 CONDUCTED EMISSION TEST

7.3.1 Applicable Standard

According to FCC Part 15.207(a)

7.3.2 Conformance Limit

Conducted Emission Limit		
Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50
Note: 1. The lower limit shall apply at the transition frequencies 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.		

7.3.3 Test Configuration

Test according to clause 7.3 conducted emission test setup


7.3.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.
Maximum procedure was performed on the highest emissions to ensure EUT compliance.
Repeat above procedures until all frequency measured were complete.

7.3.5 Test Results

Pass

The 120V & 240V voltage have been tested, and the worst result recorded was report as below:



Site Conduction 2#

Phase: **N**

Temperature: 27.6

Limit: (CE)FCC PART 15 class B_QP


Power: DC 12V from adapter

Humidity: 52 %

Mode: 125kHz mode

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1540	28.44	10.51	38.95	65.78	-26.83	QP	
2		0.1540	7.63	10.51	18.14	55.78	-37.64	AVG	
3		0.2860	23.75	10.57	34.32	60.64	-26.32	QP	
4		0.2860	8.52	10.57	19.09	50.64	-31.55	AVG	
5		0.3380	23.44	10.59	34.03	59.25	-25.22	QP	
6		0.3380	10.95	10.59	21.54	49.25	-27.71	AVG	
7		3.9620	20.44	10.72	31.16	56.00	-24.84	QP	
8		3.9620	3.35	10.72	14.07	46.00	-31.93	AVG	
9		9.0220	17.16	10.94	28.10	60.00	-31.90	QP	
10		9.0220	2.08	10.94	13.02	50.00	-36.98	AVG	
11		13.5620	38.23	11.28	49.51	60.00	-10.49	peak	
12		27.1260	31.39	11.50	42.89	60.00	-17.11	QP	
13	*	27.1260	29.86	11.50	41.36	50.00	-8.64	AVG	



Site Conduction 2#

Phase: **L1**

Temperature: 27.6

Limit: (CE)FCC PART 15 class B QP

Power: DC 12V from adapter

Humidity: 52 %

Mode: 125kHz mode

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1620	26.46	10.53	36.99	65.36	-28.37	QP	
2		0.1620	4.03	10.53	14.56	55.36	-40.80	AVG	
3		0.3100	22.66	10.58	33.24	59.97	-26.73	QP	
4		0.3100	9.33	10.58	19.91	49.97	-30.06	AVG	
5		0.3420	23.50	10.59	34.09	59.15	-25.06	QP	
6		0.3420	11.21	10.59	21.80	49.15	-27.35	AVG	
7		1.2860	17.53	10.59	28.12	56.00	-27.88	QP	
8		1.2860	4.56	10.59	15.15	46.00	-30.85	AVG	
9		3.9460	20.49	10.71	31.20	56.00	-24.80	QP	
10		3.9460	2.16	10.71	12.87	46.00	-33.13	AVG	
11		13.5620	38.83	11.31	50.14	60.00	-9.86	peak	
12		27.1260	31.44	11.54	42.98	60.00	-17.02	QP	
13	*	27.1260	30.03	11.54	41.57	50.00	-8.43	AVG	

8 ANTENNA APPLICATION

8.1.1 Antenna Requirement

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

8.1.2 Result

The EUT'S antenna is induction coil antenna, the antenna's gain is 0 dBi and meets the requirement. and the antenna can't be replaced by the user, which in accordance to section 15.203.

--- End of Report ---