

RF Exposure Evaluation declaration

Product Name	SOUND BAR + WIRELESS SUBWOOFER
Model No.	STUDIO SB 40
FCC ID	2AJAA-STUDIOSB40

Applicant	Dongguan Meiloon Acoustic Equipments Co., Ltd.
Address	77, Yuanlin Road Fenghuanggang Ind Estate, Tangxia Town, 523727 Dongguan City, Guangdong Province, China.

Date of Receipt	Jun. 27, 2016
Date of Declaration	Aug. 26, 2016
Report No.	1680525R-RFUSP23V00

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product : SOUND BAR + WIRELESS SUBWOOFER
Test Item : RF Exposure Evaluation
Test Site : No.3 OATS

For BT:

Operation Frequency	2402 – 2480MHz
Maximum Conducted output power	7.66dBm
Antenna gain	6.2dBi

Output Power Into Antenna & RF Exposure Evaluation Distance:

Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
5.834451043	0.0048

Power density is lower than the limit (1 mW/cm²).

For BLE:

Operation Frequency	2402 – 2480MHz
Maximum Conducted output power	0.53dBm
Antenna gain	6.2dBi

Output Power Into Antenna & RF Exposure Evaluation Distance:

Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1.129795915	0.0009

Power density is lower than the limit (1 mW/cm²).