



RF Exposure Evaluation Report

Equipment : WGSocAiP
Brand Name : MRLOOP
Model No. : ML60EF1
FCC ID : 2AJAS60EFA100201606
Standard : 47 CFR Part 2.1091
Applicant : MR.Loop
7F.-6,NO.237,Sec.1,Datong Rd. Xizhi Dist., New
Taipei City, Taiwan
Manufacturer : Siliconware Precision Industries Co., Ltd
No. 123, Sec.3,Da Fong Rd., Tantz, Taichung 427,
Taiwan, R.O.C

The product sample received on May 20, 2016 and completely tested on Jul. 14, 2016. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with 47 CFR Part 2.1091, and pass the limit.

Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Sam Chen
SPORTON INTERNATIONAL INC.





TABLE OF CONTENTS

1	GENERAL DESCRIPTION	4
1.1	EUT General Information	4
1.2	Testing Location	4
2	MAXIMUM PERMISSIBLE EXPOSURE	5
2.1	Limit of Maximum Permissible Exposure	5
2.2	MPE Calculation Method	5
2.3	Calculated Result and Limit.....	6

REVISION HISTORY

[illegible]

1 General Description

1.1 EUT General Information

The Channel Plan(s)		
Evaluation Mode	Operating Frequency (GHz)	Modulation Type
High-rate PHY (HRP) Band	Channel 2 HRP: 60.48 Channel 3 HRP: 62.64	QPSK, 16-QAM

1.2 Testing Location

Testing Location		
☐	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-327-0973
☒	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



2.3 Calculated Result and Limit

Exposure Environment	General Population / Uncontrolled Exposure					
Temp	23℃			Humidity	61%	
Test Engineer	Peter Wu			Test Date	Jul. 06, 2016 ~ Jul. 14, 2016	
Test results						
Maximum EIPR Power of Test Frequency (GHz)	Average EIRP Power (dBm)	Average EIRP Power (mW)	Power Density (S) (mW/cm²)	Separation Distance (cm)	Limit of Power Density (S) (mW/cm²)	
HRP 62.64 GHz	12.11	16.25	0.003	20	1.00	