

FCC RF Exposure

EUT Description: iSeemini

Model No.: BPHW01S

FCC ID: 2AJFA-XSQ01S

1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1 - g and 10 - g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
$$[(\text{max power of channel, including tune - up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
 for 1 - g SAR and ≤ 7.5 for 10 - g extremity SAR,

Where:

Result = $P \sqrt{F/D}$

F = the RF channel transmit frequency in GHz

P = Maximum turn - up power in mw

D = Min. test separation distance in mm

2. Test Result of RF Exposure Evaluation

	Output power (dBm)	Tune Up Power (dBm)	Max Tune Up power dBm/mW	Min test separation distance mm	Result	Limit (mW/cm ²)	SAR Test Exclusion
802.11b	8.46	8 ± 1	9/7.94	5	2.479	3.0	Pass
802.11g	7.93	7 ± 1	8/6.31	5	1.970	3.0	Pass
802.11n(HT20)	7.26	7 ± 1	8/6.31	5	1.970	3.0	Pass
802.11n(HT40)	6.54	7 ± 1	8/6.31	5	1.970	3.0	Pass

Note: Exclusion Thresholds Results = $[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

f(GHz) is the RF channel transmit frequency in GHz

Distance = 5mm