

TEST REPORT

Product Name : Dash Cam
Brand Mark : DDPAI
Model No. : mini Pro
FCC ID : 2AJFX-MINIPRO
Report Number : BLA-EMC-202302-A4403
Date of Sample Receipt : 2023/2/23
Date of Test : 2023/2/24 to 2023/3/9
Date of Issue : 2023/3/10
Test Standard : KDB447498D04 General RF Exposure
Guidance v01
Test Result : Pass

Prepared for:

Heath Co LLC

2445 Nashville Road, Bowling Green, KY. 42101 USA

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.

**Building C, No. 107, Shihuan Road, Shiyao Sub-District, Baoan District,
Shenzhen, Guangdong Province, China**

TEL: +86-755-23059481

Compiled by:

Review by:

Approved by:

Date: 2023/3/10



REPORT REVISE RECORD

Version No.	Date	Description
00	2023/3/10	Original

TABLE OF CONTENTS

1 GENERAL INFORMATION	4
2 GENERAL DESCRIPTION OF E.U.T.....	4
3 LABORATORY LOCATION	5
4 RF EXPOSURE COMPLIANCE REQUIREMENT	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
<i>Standard Requirement</i>	6
<i>Limits</i>	6

1 GENERAL INFORMATION

Applicant	DDPAI Technology Co., Ltd
Address	Floor 12,Yihua finance building,Nanshan software industry park,Xuefu Rd,Nanshan district,Shenzhen
Manufacturer	DDPAI Technology Co., Ltd
Address	Floor 12,Yihua finance building,Nanshan software industry park,Xuefu Rd,Nanshan district,Shenzhen
Factory	DDPAI Technology Co., Ltd
Address	Building A, Futai Industrial Park, Qingfeng south Road, Keyuancheng, Tangxia Town, Dongguan city, Guangdong province, China
Product Name	Dash Cam
Test Model No.	mini Pro

2 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	V00
Software Version	V00
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Channel Spacing:	5MHz
Number of Channels:	802.11b/g/n(HT20):11
Antenna Type:	PCB Antenna
Antenna gain:	Antenna:2dBi
Remark:The Antenna Gain is supplied by the customer.BlueAsia is not responsible for this data	

3 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co., Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province,
China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673
No tests were sub-contracted.

4 RF EXPOSURE COMPLIANCE REQUIREMENT

4.1 RF EXPOSURE COMPLIANCE REQUIREMENT

Standard Requirement

According to 447498 D04 Interim General RF Exposure Guidance v01

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

Limits

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)										
		5	10	15	20	25	30	35	40	45	50
	300	39	65	88	110	129	148	166	184	201	217
	450	22	44	67	89	112	135	158	180	203	226
	835	9	25	44	66	90	116	145	175	207	240
	1900	3	12	26	44	66	92	122	157	195	236
	2450	3	10	22	38	59	83	111	143	179	219
	3600	2	8	18	32	49	71	96	125	158	195
	5800	1	6	14	25	40	58	80	106	136	169

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

$$EIRP = p_t \times g_t = (EXd)^{2/30}$$

where:

p_t = transmitter output power in watts,

g_t = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, --- $10((dBuV/m)/20)/106$

d = measurement distance in meters (m)---3m

$$S_{opt} = (EXd)^{2/30} \times g_t$$

Ant gain = 2 dBi

Max Output power = 20.481dBm @ 2437MHz

$$ERP = 20.481dBm + 2dBi - 2.15 = 20.331dBm$$

So

ERP is worse case

$$10^{2.0331} = 107.92 \text{ mW} < 3060 \text{ mW}$$

Comply with RF exposure exemption limit.

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.