

Maximum Permissible Exposure (MPE)

Standard Applicable

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to §1.1310 and §2.1091 RF exposure is calculated.

Limits for Maximum Permissive Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-15000	/	/	1.0	30

F = frequency in MHz

* = Plane-wave equipment power density

FCC

Maximum Permissible Exposure (MPE) Evaluation: The worst case of Average power

Power measurement: refer to Part15.247 report for details.

Wi-Fi	Frequency Range (MHz)	Channels	Peak / Average Power	Modulation Technology
802.11b	2412 – 2462(DTS)	11	18.89dBm (PK)	DSSS
802.11g	2412 – 2462(DTS)	11	23.40dBm (PK)	OFDM
802.11n	HT20 2412 – 2462(DTS)	11	23.18dBm (PK)	

Maximum output power at antenna input terminal:	23.4	(dBm)
Maximum output power at antenna input terminal:	218.7761624	(mW)
Tune-Up power Tolerance:	0.5	dB
Duty cycle:	100	(%)
Maximum Pav :	245.4708916	(mW)
Antenna gain (typical):	3	(dBi)
Maximum antenna gain:	1.995262315	(numeric)
Prediction distance:	20	(cm)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.0974878	(mW/cm ²)

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4 \pi R^2$$

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

Measurement Result:

The predicted power density level at 20 cm is 0.0974878 mW/cm². This is below the uncontrolled exposure limit of 1 mW/cm².

BT mode:

Maximum Permissible Exposure (MPE) Evaluation: The worst case of Average power

Power measurement: refer to Part15.247 report for details.

BDR Mode

Frequency (MHz)	Peak Reading Power (dBm)	Cable Loss	Output Power (dBm)	Output Power (W)	Limit (W)
Low	-1.33	2.50	1.17	0.00131	1
Mid	-1.00	2.50	1.50	0.00141	1
High	-1.41	2.50	1.09	0.00128	1

Maximum output power at antenna input terminal:	1.5	(dBm)
Maximum output power at antenna input terminal:	1.412537545	(mW)
Tune-Up power Tolerance:	1	dB
Duty cycle:	100	(%)
Maximum Pav :	1.77827941	(mW)
Antenna gain (typical):	3	(dBi)
Maximum antenna gain:	1.995262315	(numeric)
Prediction distance:	20	(cm)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.0007062	(mW/cm ²)

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4 \pi R^2$$

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

Measurement Result:

The worst power density is 0.0007062 mW/cm² which is less than 1 mW/cm².

~ end ~