



Appendix Test Data for SRD (Conducted Measurement)

Product Name: R/C car

Trade Mark: /

Test Model: LH-C064

FCC ID: 2AJGI-LH-C064

Environmental Conditions

Temperature:	23.5°C
Relative Humidity:	58%
ATM Pressure:	100.0 kPa
Test Engineer:	Allen Lai
Supervised by:	Max Zhang
NOTE	N/A

Appendix A: DTS Bandwidth

Test Result

Test Mode	Antenna	Frequency [MHz]	DTS BW [MHz]	FL [MHz]	FH [MHz]	Limit [MHz]	Verdict
SRD	Ant1	2405	0.672	2404.936	2405.608	0.5	PASS
SRD	Ant1	2445	0.688	2444.940	2445.628	0.5	PASS
SRD	Ant1	2475	0.744	2474.932	2475.676	0.5	PASS

Note: offset(dB) = cable loss(dB) + attenuator factor(dB)





Test Graphs







Appendix B: Occupied Channel Bandwidth

Test Result

Test Mode	Antenna	Frequency [MHz]	OCB [MHz]	FL [MHz]	FH [MHz]	Limit [MHz]	Verdict
SRD	Ant1	2405	1.1576	2404.7033	2405.8609	---	---
SRD	Ant1	2445	1.1755	2444.6992	2445.8747	---	---
SRD	Ant1	2475	1.1883	2474.6978	2475.8861	---	---

Note: offset(dB) = cable loss(dB) + attenuator factor(dB)





Test Graphs







Appendix C: Maximum peak conducted output power

Test Result Peak


Test Mode	Antenna	Frequency [MHz]	Conducted Peak Power [dBm]	Conducted Limit [dBm]	Verdict
SRD	Ant1	2405	-2.88	≤30	PASS
SRD	Ant1	2445	-3.45	≤30	PASS
SRD	Ant1	2475	-3.16	≤30	PASS


Note: offset(dB) = cable loss(dB) + attenuator factor(dB)





Test Graphs Peak







Appendix D: Maximum peak power spectral density

Test Result


Test Mode	Antenna	Frequency [MHz]	Result [dBm/3kHz]	Limit [dBm/3kHz]	Verdict
SRD	Ant1	2405	-17.19	≤8.00	PASS
SRD	Ant1	2445	-18.66	≤8.00	PASS
SRD	Ant1	2475	-17.59	≤8.00	PASS


Note: offset(dB) = cable loss(dB) + attenuator factor(dB)





Test Graphs







Appendix E: Band edge measurements

Test Result


Test Mode	Antenna	Ch. Name	Frequency [MHz]	Ref. Level [dBm]	Result [dBm]	Limit [dBm]	Verdict
SRD	Ant1	Low	2405	-3.37	-46.01	≤ -23.37	PASS
SRD	Ant1	High	2475	-4.36	-48.87	≤ -24.36	PASS

Note: offset(dB) = cable loss(dB) + attenuator factor(dB)





Test Graphs





Appendix F: Conducted Spurious Emission

Test Result


Test Mode	Antenna	Frequency [MHz]	Freq. Range [MHz]	Ref. Level [dBm]	Result [dBm]	Limit [dBm]	Verdict
SRD	Ant1	2405	0~Reference	-3.34	-3.34	---	PASS
SRD	Ant1	2405	30~1000	-3.34	-52.72	≤ -23.34	PASS
SRD	Ant1	2405	1000~26500	-3.34	-27.68	≤ -23.34	PASS
SRD	Ant1	2445	0~Reference	-4.73	-4.73	---	PASS
SRD	Ant1	2445	30~1000	-4.73	-52.99	≤ -24.73	PASS
SRD	Ant1	2445	1000~26500	-4.73	-27.8	≤ -24.73	PASS
SRD	Ant1	2475	0~Reference	-4.44	-4.44	---	PASS
SRD	Ant1	2475	30~1000	-4.44	-51.88	≤ -24.44	PASS
SRD	Ant1	2475	1000~26500	-4.44	-27.1	≤ -24.44	PASS


Note: offset(dB) in Reference test plots = cable loss(dB) + attenuator factor(dB); For spurious emissions plots from 30MHz to 26.5GHz, the cable loss and attenuator factors have been set in the 'Input Correction' of the Spectrum Analyzer during the test.






Test Graphs






SRD-Ant1-2405-1000~26500-PASS




SRD-Ant1-2445-0~Reference-PASS





SRD-Ant1-2445-30~1000-PASS




SRD-Ant1-2445-1000~26500-PASS






SRD-Ant1-2475-0~Reference-PASS



SRD-Ant1-2475-30~1000-PASS





SRD-Ant1-2475-1000~26500-PASS





Appendix G: Duty Cycle

Test Result

Test Mode	Antenna	Frequency [MHz]	ON Time [ms]	Period [ms]	Duty Cycle [%]	Duty Cycle Factor [dB]
SRD	Ant1	2405	0.17	0.30	56.67	2.47
SRD	Ant1	2445	0.17	0.30	56.67	2.47
SRD	Ant1	2475	0.17	0.30	56.67	2.47

Note: offset(dB) = cable loss(dB) + attenuator factor(dB)





Test Graphs



