



FCC TEST REPORT

Test report
On Behalf of
**PO FUNG ELECTRONIC(HK) INTERNATIOANL GROUP
COMPANY**
For
TWO WAY RADIO

Model No.: UV-5RIII, UV-5RX3

FCC ID: 2AJGM-UV5R

Prepared for : **PO FUNG ELECTRONIC(HK) INTERNATIOANL GROUP COMPANY**
3/F FULOK BLDG 131-133 WING LOK ST SHEUNG WAN, Hong Kong

Prepared By : **Shenzhen HUAKE Testing Technology Co., Ltd.**
**1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street, Bao'an
District, Shenzhen City, China**

Date of Test: **Sep. 03, 2018~Sep. 28, 2018**

Date of Report: **Sep. 28, 2018**

Report Number: **HK1809111047E**



TEST RESULT CERTIFICATION

Applicant's name : PO FUNG ELECTRONIC(HK) INTERNATIOANL GROUP COMPANY
Address : 3/F FULOK BLDG 131-133 WING LOK ST SHEUNG WAN, Hong Kong
Manufacture's Name : PO FUNG ELECTRONIC(HK) INTERNATIOANL GROUP COMPANY
Address : 3/F FULOK BLDG 131-133 WING LOK ST SHEUNG WAN, Hong Kong

Product description TWO WAY RADIO
Brand Name BAOFENG ,Pofung
Mode Name UV-5RIII
Serial Name UV-5RX3
Difference Description All tlhe same except the model name.
Standards : FCC Rules and Regulations Part 15B

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAKE Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAKE Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Date of Test :
Date (s) of performance of tests : **Sep. 03, 2018~Sep. 28, 2018**
Date of Issue : **Sep. 28, 2018**
Test Result : **Pass**

Testing Engineer :

(Gary Qian)

Technical Manager :

(Eden Hu)

Authorized Signatory :

(Jason Zhou)



Revision	Issue Date	Revisions	Revised By
V1.0	Sep. 28, 2018	Class II Permissive Change	Jason Zhou

Note: The original report Ref. No.(AGC02294180603FE08)(2018-06-26), was modified on 2018-09-28 to include the following changes and additions for:

- Updated the product designation , model name and software.
- The product increases the supported frequency band by 200 - 260 MHz.

Based on the above changes, the Conduction Emission and Radiation Emission test are updated into this report, the test setup photos and EUT photos are updated.



TABLE OF CONTENTS

1. VERIFICATION OF COMPLIANCE	5
2. PRODUCT INFORMATION	6
3. MEASUREMENT UNCERTAINTY	7
4. IDENTIFICATION OF THE RESPONSIBLE TESTING LOCATION	8
5. SUPPORT EQUIPMENT LIST	9
6. SYSTEM DESCRIPTION	9
7. SUMMARY OF TEST RESULTS	10
8. FCC RADIATED EMISSION TEST	11
8.1. TEST EQUIPMENT OF RADIATED EMISSION	11
8.2. LIMITS OF RADIATED EMISSION TEST	11
8.3 BLOCK DIAGRAM OF RADIATED EMISSION TEST	11
8.4 PROCEDURE OF RADIATED EMISSION TEST	13
8.5 TEST RESULT OF RADIATED EMISSION TEST	14
9. CONDUCTED EMISSION TEST	16
9.1 PROVISIONS APPLICABLE	16
9.2 MEASUREMENT PROCEDURE	16
9.3 TEST SETUP BLOCK DIAGRAM	17
9.4 TEST RESULT	18
APPENDIX 1 PHOTOGRAPHS OF TEST SETUP	20
APPENDIX 2 PHOTOGRAPHS OF EUT	21



1. VERIFICATION OF COMPLIANCE

Hardware Version	5R-VER22
Software Version	UV-5RX3
Measurement Procedure	ANSI C63.4: 2014
Deviation:	None
Condition of Test Sample	Normal

The test results of this report relate only to the tested sample identified in this report.



2. PRODUCT INFORMATION

The EUT is a Analog Transceiver designed for voice communication. It is designed by way of utilizing the F3E modulation achieves the system operating.

A major technical description of EUT is described as following:

Communication Type	Voice / Tone only
Modulation	FM
RX Frequency Range	Rx:136 MHz -174 MHz, 400MHz -480MHz, 200MHz-260MHz
Emission Type	F3E
Antenna Designation	Detachable
Antenna Gain	2.15dBi
Power Supply	DC 7.4V 1800mAh, charging with DC 8.4V.
Adapter Parameter	INPUT:AC 100-240V~ 50/60Hz ,0.4A OUTPUT:DC 10V 0.5A
Charger Parameter	INPUT: DC 10V 0.5A OUTPUT:DC 8.4V 0.4A

I/O Port Information (☒Applicable ☐Not Applicable)

I/O Port of EUT			
I/O Port Type	Q'TY	Cable	Tested with
DC Input Port	1	1.14m, Unshielded	1
Antenna Connect Port	1	0	1



3. MEASUREMENT UNCERTAINTY

- Uncertainty of Conducted Emission, $U_c = \pm 3.2\text{dB}$
- Uncertainty of Radiated Emission below 1GHz, $U_c = \pm 3.9\text{dB}$
- Uncertainty of Radiated Emission above 1GHz, $U_c = \pm 4.8\text{dB}$

**4. IDENTIFICATION OF THE RESPONSIBLE TESTING LOCATION**

Site	Shenzhen HUAKE Testing Technology Co., Ltd.
Location	1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street, Bao'an District, Shenzhen City, China
Designation Number	CN1229
Test Firm Registration Number : 616276	

List Of Test Equipment:

Conducted Emission Shielding Room Test Site (744)					
Equipment	Manufacturer	Model	Serial Number	Cal. Date	Cal. Due
Receiver	R&S	ESCI 7	HKE-010	Dec. 29, 2017	Dec. 28, 2018
LISN	R&S	ENV216	HKE-002	Dec. 29, 2017	Dec. 28, 2018
Conducted test software	Tonscend	TS+ Rev 2.5.0.0	HKE-081	N/A	N/A

TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Broadband antenna	Schwarzbeck	VULB 9163	HKE-012	Dec. 29, 2017	Dec. 28, 2018
Receiver	R&S	ESCI 7	HKE-010	Dec. 29, 2017	Dec. 28, 2018
Preamplifier	Schwarzbeck	BBV 9743	HKE-006	Dec. 29, 2017	Dec. 28, 2018
Position controller	Taiwan MF	MF7802	HKE-011	Dec. 29, 2017	Dec. 28, 2018
Horn antenna	Schwarzbeck	9120D	HKE-013	Dec. 29, 2017	Dec. 28, 2018



5. SUPPORT EQUIPMENT LIST

Device Type	Manufacturer	Model Name	Serial No.	Data Cable	Power Cable
-	--	-	--	--	-

6. SYSTEM DESCRIPTION

EUT test procedure:

1. Connect EUT and peripheral devices.
2. Power on the EUT, the EUT begins to work.
3. Make sure the EUT normal working.

EMC TEST MODES

No.	TEST MODES
1	Scanning mode
2	Scanning stopped/Receiving

Note: Only the result of the worst case was recorded in the report.

**7. SUMMARY OF TEST RESULTS**

FCC Rules	Description Of Test	Result
§15.107	Conduction Emission	Compliant
§15.109	Radiated Emission	Compliant



8. FCC RADIATED EMISSION TEST

8.1. TEST EQUIPMENT OF RADIATED EMISSION


8.2. LIMITS OF RADIATED EMISSION TEST

Frequency (MHz)	Distance (m)	Maximum Field Strength Limit (dBuV/m/ Q.P.)
30~88	3	41.0
88~216	3	45.0
216~960	3	48.0
960~2000	3	53.5

**Note: The lower limit shall apply at the transition frequency. Because the EUT RX frequency range up to 480 MHz, so the upper the frequency range up to 2 GHz.


8.3 BLOCK DIAGRAM OF RADIATED EMISSION TEST

RADIATED EMISSION TEST SETUP 30MHz-1000MHz





RADIATED EMISSION TEST SETUP ABOVE 1000MHz





8.4 PROCEDURE OF RADIATED EMISSION TEST


- 1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2) Support equipment, if needed, was placed as per ANSI C63.4.
- 3) All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4) The EUT received power by AC 120V/60Hz adapter.
- 5) The antenna was placed at 3 meter away from the EUT as stated in FCC Part 15. The antenna connected to the Analyzer via a cable and at times a pre-amplifier would be used.
- 6) The Analyzer / Receiver quickly scanned from 30MHz to 1000MHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- 7) The test mode(s) were scanned during the test:
- 8) Recorded at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and Q.P./Peak reading is presented. For emissions below 1GHz, use 120KHz RBW and VBW $\geq$ 3RBW for QP reading.
- 9) For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
- 10) When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 11) If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 12) For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 13) In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.
- 14) The test data of the worst case condition (mode 1) was reported on the following Data page



8.5 TEST RESULT OF RADIATED EMISSION TEST

Radiated Emission Test –Horizontal -3m Below 1G

66.9 dBuV/m




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	46.1667	25.09	11.49	36.58	40.00	-3.42	peak			
2		99.5167	21.10	10.00	31.10	43.50	-12.40	peak			
3		125.3833	14.10	8.37	22.47	43.50	-21.03	peak			
4		214.3000	9.80	10.54	20.34	43.50	-23.16	peak			
5		359.8000	0.57	18.80	19.37	46.00	-26.63	peak			
6		511.7667	1.28	21.45	22.73	46.00	-23.27	peak			

RESULT: PASS



Radiated Emission Test –Vertical -3m Below 1G

66.9 dBuV/m



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	!	47.7832	26.35	8.39	34.74	40.00	-5.26	peak			
2	*	73.6500	33.33	3.36	36.69	40.00	-3.31	peak			
3		131.8500	23.52	11.80	35.32	43.50	-8.18	peak			
4		220.7667	6.55	11.04	17.59	46.00	-28.41	peak			
5		490.7500	0.13	21.03	21.16	46.00	-24.84	peak			
6		573.2000	0.15	22.60	22.75	46.00	-23.25	peak			

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

3. Emissions range from 1GHz to 2GHz have 20dB margin. No recording in the test report.

4. Only the data of the worst case would be record in this test report.



9. CONDUCTED EMISSION TEST

9.1 PROVISIONS APPLICABLE

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the, the radio frequency voltage that is conducted back onto the AC power line on any frequencies within the band 150 KHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50uH/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequencies ranges.

Frequency of Emission (MHz)	Conducted Limit(dBuV)	
	Quasi-Peak	Average
0.15 – 0.5	66 to 56 *	56 to 46 *
0.5 – 5	56	46
5 – 30	60	50


* Decreases with the logarithm of the frequency.

9.2 MEASUREMENT PROCEDURE

- (1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- (2) Support equipment, if needed, was placed as per ANSI C63.4.
- (3) All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- (4) All support equipments received AC120V/60Hz power from a LISN, if any.
- (5) The EUT received DC charging voltage by adapter which received 120V/60Hz power by a LISN.
- (6) The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- (7) Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes. During the above scans, the emissions were maximized by cable manipulation.




9.3 TEST SETUP BLOCK DIAGRAM





9.4 TEST RESULT

CONDUCTED EMISSION TEST – LINE L



Suspected List

NO.	Freq. [MHz]	Level [dBμV]	Factor [dB]	Limit [dBμV]	Margin [dB]	Detector
1	0.1500	49.95	10.03	66.00	16.05	PK
2	0.2895	53.03	10.03	60.54	7.51	PK
3	0.4110	46.16	10.03	57.63	11.47	PK
4	1.4100	44.19	10.11	56.00	11.81	PK
5	3.6420	41.99	10.25	56.00	14.01	PK
6	11.9895	49.73	9.99	60.00	10.27	PK

Final Data List


NO.	Freq. [MHz]	Factor [dB]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]
1	0.1511	10.03	48.74	65.94	17.20	29.07	55.94	26.87
2	0.2886	10.03	49.90	60.56	10.66	30.52	50.56	20.04
3	0.4151	10.03	41.66	57.55	15.89	26.35	47.55	21.20
4	1.4075	10.11	37.93	56.00	18.07	23.95	46.00	22.05
5	3.6744	10.25	34.86	56.00	21.14	24.29	46.00	21.71
6	12.0752	9.99	44.20	60.00	15.80	36.36	50.00	13.64

RESULT: PASS



CONDUCTED EMISSION TEST – LINE N

FCC PART 15 B CLASS B(N)



Suspected List

NO.	Freq. [MHz]	Level [dBμV]	Factor [dB]	Limit [dBμV]	Margin [dB]	Detector
1	0.1500	53.40	10.03	66.00	12.60	PK
2	0.2850	51.58	10.04	60.67	9.09	PK
3	0.4110	48.57	10.03	57.63	9.06	PK
4	1.7250	41.56	10.13	56.00	14.44	PK
5	3.9525	39.41	10.25	56.00	16.59	PK
6	15.6750	47.40	9.97	60.00	12.60	PK

Final Data List


NO.	Freq. [MHz]	Factor [dB]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]
1	0.1500	10.03	48.48	66.00	17.52	28.97	56.00	27.03
2	0.2822	10.04	47.33	60.75	13.42	28.27	50.75	22.48
3	0.4090	10.03	37.77	57.67	19.90	22.53	47.67	25.14
4	1.7400	10.14	36.03	56.00	19.97	22.03	46.00	23.97
5	3.9339	10.25	30.57	56.00	25.43	20.98	46.00	25.02
6	15.5248	9.97	39.37	60.00	20.63	28.34	50.00	21.66

RESULT: PASS




APPENDIX 1 PHOTOGRAPHS OF TEST SETUP

CONDUCTED EMISSION TEST SETUP



RADIATED EMISSION TEST SETUP





APPENDIX 2 PHOTOGRAPHS OF EUT

TOTAL VIEW OF EUT



TOP VIEW OF EUT





BOTTOM VIEW OF EUT



FRONT VIEW OF EUT





BACK VIEW OF EUT



LEFT VIEW OF EUT





RIGHT VIEW OF EUT




OPEN VIEW-1 OF EUT






OPEN VIEW-2 OF EUT




OPEN VIEW-3 OF EUT






INTERNAL VIEW-1 OF EUT




INTERNAL VIEW-2 OF EUT






INTERNAL VIEW-4 OF EUT




INTERNAL VIEW-5 OF EUT






INTERNAL VIEW-6 OF EUT



INTERNAL VIEW-7 OF EUT



----END OF REPORT----