



Shenzhen BST Technology Co., Ltd.

Report No.: BST1706794950002Y-ER-2

RADIO TEST REPORT

For

Shenzhen Petwant Pet Products Co.,Ltd.

Product Name:	5 meals Smart pet feeder
Model :	F2 Wi-Fi
Series Model:	F2 Wi-Fi, F2 Camera
FCC ID:	2AJGV-F2
Prepared By :	Shenzhen BST Technology Co., Ltd. Building No.23-24, Zhiheng Industrial Park, Guankouer Road, Nantou,Nanshan District,Shenzhen,Guangdong,China
Test Date:	June 10-27, 2017
Date of Report :	June 27, 2017
Test Result	pass
Report No.:	BST1706794950002Y-ER-2



RADIO TEST REPORT.....	1
1. GENERAL INFORMATION.....	4
1.1 Product Description for Equipment Under Test (EUT).....	4
1.2 Test Standards.....	5
1.3 Test Methodology.....	5
1.4 Test Facility.....	5
1.5 EUT Setup and Test Mode.....	5
1.6 Measurement Uncertainty.....	6
2. SUMMARY OF TEST RESULTS.....	7
3. RF Exposure.....	8
3.1 Standard Applicable.....	8
3.2 Test Result.....	8
4. Antenna Requirement.....	9
4.1 Standard Applicable.....	9
4.2 Evaluation Information.....	9
5. Power Spectral Density.....	10
5.1 Standard Applicable.....	10
5.2 Test Procedure.....	10
5.3 Environmental Conditions.....	10
5.4 Summary of Test Results/Plots.....	11
6. 6dB Bandwidth.....	16
6.1 Standard Applicable.....	16
6.2 Test Procedure.....	16
6.3 Environmental Conditions.....	16
6.4 Summary of Test Results/Plots.....	16
7. RF Output Power.....	22
7.1 Standard Applicable.....	22
7.2 Test Procedure.....	22
7.3 Environmental Conditions.....	22
7.4 Summary of Test Results/Plot.....	23
8. Field Strength of Spurious Emissions.....	24
8.1 Standard Applicable.....	24
8.2 Test Procedure.....	24
8.3 Corrected Amplitude & Margin Calculation.....	25
8.4 Environmental Conditions.....	26
8.5 Summary of Test Results/Plots.....	26
9. Out of Band Emissions.....	48
9.1 Standard Applicable.....	48



9.2 Test Procedure.....	48
9.3 Environmental Conditions.....	49
9.4 Summary of Test Results/Plots.....	49
10. Conducted Emissions.....	52
10.1 Test Procedure.....	53
10.2 Basic Test Setup Block Diagram.....	53
10.3 Environmental Conditions.....	53
10.4 Test Receiver Setup.....	54
10.5 Summary of Test Results/Plots.....	54
10.6 Conducted Emissions Test Data.....	54
11. Test Photo.....	57



1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Shenzhen Petwant Pet Products Co.,Ltd.
Address of applicant: 2/F,No. 64 Wugang Road, Xikeng Community,
Henggang Street,Longgang District, Shenzhen

Manufacturer: Shenzhen Petwant Pet Products Co.,Ltd.
Address of manufacturer: 2/F,No. 64 Wugang Road, Xikeng Community,
Henggang Street,Longgang District, Shenzhen

General Description of EUT	
Product Name:	5 meals Smart pet feeder
Trade Name:	N/A
Model No.:	F2 Wi-Fi
Adding Model(s):	F2 Camera
Rated Voltage:	DC 5V From Adapter
Battery Capacity:	4800mah
Power Adapter Model:	Ak06WG-0500100uW
Software Version:	V3.0
Hardware Version:	V1.0
<i>Note: The test data is gathered from a production sample provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 802.11b/g/n(HT20)
RF Output Power:	15.07dBm (Conducted)
Type of Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Data Rate:	1-11Mbps, 6-54Mbps, up to 150Mbps
Quantity of Channels:	11 for 802.11b/g/n(HT20)
Channel Separation:	5MHz
Type of Antenna:	FPCB
Antenna Gain:	1dBi
Lowest Internal Frequency	32.768kHz



1.2 Test Standards

The following report is prepared on behalf of the **Smart Pet Feeder** in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard for Testing Unlicensed Wireless Devices, and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. The measurement guide KDB 558074 D01 v03r05 for digital transmission systems shall be performed also.

1.4 Test Facility

Shenzhen Asia Test Technology Co.,Ltd.

7 / F, Xinwei Building, Gushu Village, Xixiang Town, Baoan District, Shenzhen, China

FCC Registration No.: 348715; IC Registration No.: 12198A

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:



Test Mode List		
Test Mode	Description	Remark
TM1	802.11b	2412MHz, 2437MHz, 2462MHz
TM2	802.11g	2412MHz, 2437MHz, 2462MHz
TM3	802.11n-HT20	2412MHz, 2437MHz, 2462MHz
Note: All test modes (different data rate and different modulation) are performed, but only the worst case is recorded in this report.		

Accessories Equipment List and Details			
Description	Manufacturer	Model No.	Serial Number
/	/	/	/
Accessories Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With Core/Without Core
/	/	/	/
EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	$\pm 2.88\text{dB}$
Transmitter Spurious Emissions	Radiated	$\pm 5.1\text{dB}$



Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
Spectrum Analyzer	Agilent	E4407B	MY41440400	2017-06-04	2018-06-03
Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2017-06-04	2018-06-03
EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2017-06-04	2018-06-03
Amplifier	Agilent	8447F	3113A06717	2017-06-04	2018-06-03
Amplifier	C&D	PAP-1G18	2002	2017-06-04	2018-06-03
Broadband Antenna	Schwarz beck	VULB9163	9163-333	2017-06-04	2018-06-03
Horn Antenna	ETS	3117	00086197	2017-06-04	2018-06-03
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2017-06-04	2018-06-03
Loop Antenna	Schwarz beck	FMZB 1516	9773	2017-06-04	2018-06-03
EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2017-06-04	2018-06-03
L.I.S.N	Schwarz beck	NSLK8126	8126-224	2017-06-04	2018-06-03
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2017-06-04	2018-06-03

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 2.1093	RF Exposure	Compliant
§ 15.203; § 15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§ 15.207(a)	Conducted Emission	Compliant
§ 15.247(e)	Power Spectral Density	Compliant
§ 15.247(a)(2)	6 dB Bandwidth	Compliant
§ 15.247(b)(3)	RF Output Power	Compliant
§ 15.209(a)	Radiated Emission	Compliant
§ 15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: not applicable



3. RF Exposure

3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.



4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information

This product has a FPCB antenna, fulfill the requirement of this section.



5. Power Spectral Density

5.1 Standard Applicable

According to 15.247(a)(1)(iii), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.2 Test Procedure

According to the KDB 558074 D01 v03r05, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:

- (g) Set instrument center frequency to DTS channel center frequency.
- (h) Set span to at least 1.5 times the OBW.
- (i) Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- (j) Set VBW $\geq 3 \times \text{RBW}$.
- (k) Detector = power averaging (RMS) or sample detector (when RMS not available).
- (l) Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$.
- (m) Sweep time = auto couple.
- (n) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- (o) Use the peak marker function to determine the maximum amplitude level.
- (p) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

5.3 Environmental Conditions


Temperature:	21°C
Relative Humidity:	50%
ATM Pressure:	101.2



5.4 Summary of Test Results/Plots


Test Mode	Test Channel MHz	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
802.11b	2412	-20.25	8
	2437	-193-.66	8
	2462	-19.22	8
802.11g	2412	-22.44	8
	2437	-21.92	8
	2462	-21.38	8
802.11n HT20	2412	-21.87	8
	2437	-21.25	8
	2462	-20.76	8

Please refer to the following test plots:






802.11b-Middle Channel



Date: 24 JUN 2017 16:50:28


802.11b-High Channel



Date: 24 JUN 2017 16:50:49




802.11g-Low Channel



Date: 24 JUN 2017 16:49:27


802.11g-Middle Channel



Date: 24 JUN 2017 16:49:03




802.11g-High Channel



Date: 24 JUN 2017 16:48:43


802.11n-HT20-Low Channel



Date: 24 JUN 2017 16:47:40




802.11n-HT20-Middle Channel



Date: 24 JUN 2017 16:47:57

802.11n-HT20-High Channel



Date: 24 JUN 2017 16:48:14



6. 6dB Bandwidth

6.1 Standard Applicable

According to 15.247(a)(2). Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

6.2 Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3 Environmental Conditions

Temperature:	21°C
Relative Humidity:	50%
ATM Pressure:	101.2


6.4 Summary of Test Results/Plots

Test Mode	Test Channel MHz	6 dB Bandwidth MHz	Limit kHz
802.11b	2412	10.0578	≥ 500
	2437	10.0563	≥ 500
	2462	10.0594	≥ 500
802.11g	2412	16.5469	≥ 500
	2437	16.5563	≥ 500
	2462	16.5344	≥ 500
802.11n-HT20	2412	17.8016	≥ 500
	2437	17.8016	≥ 500
	2462	17.8016	≥ 500




Please refer to the following test plots:

802.11b-Low Channel




802.11b-Middle Channel






802.11b-High Channel



Date: 24 JUN 2017 15:33:44


802.11g-Low Channel



Date: 24 JUN 2017 15:31:16




802.11g-Middle Channel



Date: 24 JUN 2017 15:30:36


802.11g-High Channel



Date: 24 JUN 2017 15:29:44




802.11n-HT20-Low Channel



Date: 24 JUN 2017 15:27:34


802.11n-HT20-Middle Channel



Date: 24 JUN 2017 15:28:14



802.11n-HT20-High Channel



Date: 24 JUN 2017 15:29:00



7. RF Output Power

7.1 Standard Applicable

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

7.2 Test Procedure

According to the KDB-558074 D01 v03r05, 9.2.2.2, when this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth

- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW $\geq 3 \times$ RBW.
- d) Number of points in sweep $\geq 2 \times$ span / RBW. (This gives bin-to-bin spacing $\leq$ RBW/2, so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- g) If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run”.
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

7.3 Environmental Conditions

Temperature:	21°C
Relative Humidity:	50%
ATM Pressure:	101.2



7.4 Summary of Test Results/Plots

Test Mode	Frequency MHz	Reading dBm	Output Power mW	Limit mW
802.11b_11Mbps	2412	14.86	30.619	1000
	2437	11.54	14.256	1000
	2462	13.24	21.086	1000
802.11g_54Mbps	2412	14.42	27.669	1000
	2437	13.54	22.594	1000
	2462	15.67	36.898	1000
802.11n HT20_MCS7	2412	14.62	28.973	1000
	2437	13.28	21.281	1000
	2462	12.86	19.320	1000



8. Field Strength of Spurious Emissions

8.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).



The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

8.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



Frequency :9kHz-30MHz

RBW=10KHz,

VBW =30KHz

Sweep time= Auto

Trace = max hold

Detector function = peak

Frequency :30MHz-1GHz

RBW=120KHz,

VBW=300KHz

Sweep time= Auto

Trace = max hold

Detector function = peak, QP

Frequency :Above 1GHz

RBW=1MHz,

VBW=3MHz(Peak), 10Hz(AV)

Sweep time= Auto

Trace = max hold

Detector function = peak, AV

8.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$



The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

8.4 Environmental Conditions

Temperature:	21°C
Relative Humidity:	50%
ATM Pressure:	101.2


8.5 Summary of Test Results/Plots

According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst cases:




Plot of Radiated Emissions Test Data (30MHz to 1GHz)

Vertical





Horizontal




*Spurious Emissions Above 1GHz**Test Mode: 802.11b (worst case)*

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2412MHz							
4824.000	60.21	-3.77	56.44	74	17.56	H	PK
4824.000	40.45	-3.77	36.68	54	17.32	H	AV
7236.000	59.32	1.19	60.51	74	13.49	H	PK
7236.000	47.28	1.19	48.47	54	5.53	H	AV
4824.000	59.82	-3.77	56.05	74	17.95	V	PK
4824.000	45.01	-3.77	41.24	54	12.76	V	AV
7236.000	60.25	1.19	61.44	74	12.56	V	PK
7236.000	47.14	1.19	48.33	54	5.67	V	AV
Middle Channel-2437MHz							
4874.000	56.15	-3.65	52.5	74	21.5	H	PK
4874.000	48.45	-3.65	44.8	54	9.2	H	AV
7311.000	56.47	1.56	58.03	74	15.97	H	PK
7311.000	41.16	1.56	42.72	54	11.28	H	AV
4874.000	57.36	-3.65	53.71	74	20.29	V	PK
4874.000	47.42	-3.65	43.77	54	10.23	V	AV
7311.000	46.25	-3.63	42.62	74	31.38	V	PK
7311.000	46.63	1.56	48.19	54	5.81	V	AV
High Channel-2462MHz							
4924.000	52.25	-3.54	48.71	74	25.29	H	PK
4924.000	45.67	-3.54	42.13	54	11.87	H	AV
7386.000	51.58	1.67	53.25	74	20.75	H	PK
7386.000	43.68	1.67	45.35	54	8.65	H	AV
4924.000	64.58	-3.58	61	74	13	V	PK
4924.000	45.99	-3.58	42.41	54	11.59	V	AV
7386.000	56.35	1.67	58.02	74	15.98	V	PK
7386.000	42.56	1.67	44.23	54	9.77	V	AV


Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength istoo small to be measured.




(conducted)
802.11b-Lowest




Date: 24 JUN 2017 15:43:54



Date: 24 JUN 2017 15:43:28




Date: 24 JUN 2017 15:43:41




Date: 24 JUN 2017 15:44:05


802.11b-Middle




Date: 24 JUN 2017 15:45:45



Date: 24 JUN 2017 15:45:21




Date: 24 JUN 2017 15:45:32




Date: 24 JUN 2017 15:45:55


802.11b-High




Date: 24.JUN.2017 15:46:44



Date: 24.JUN.2017 15:46:22




Date: 24 JUN 2017 15:46:32




Date: 24 JUN 2017 15:46:53


802.11g-Lowest




Date: 24 JUN 2017 15:49:58



Date: 24 JUN 2017 15:49:30




Date: 24 JUN 2017 15:49:47




Date: 24 JUN 2017 15:50:10


802.11g-Middle




Date: 24 JUN 2017 15:48:50



Date: 24 JUN 2017 15:48:30




Date: 24 JUN 2017 15:48:41




Date: 24 JUN 2017 15:49:05


802.11g-High




Date: 24 JUN 2017 15:47:40



Date: 24 JUN 2017 15:47:19




Date: 24 JUN 2017 15:47:31




Date: 24 JUN 2017 15:47:51


802.11n-HT20-Lowest




Date: 24 JUN 2017 15:51:03



Date: 24 JUN 2017 15:50:44




Date: 24 JUN 2017 15:50:53




Date: 24 JUN 2017 15:51:15


802.11n-HT20-Middle




Date: 24 JUN 2017 15:52:05



Date: 24 JUN 2017 15:51:37




Date: 24 JUN 2017 15:51:52




Date: 24 JUN 2017 15:52:19


802.11n-HT20-Highest




Date: 24 JUN 2017 15:53:31



Date: 24 JUN 2017 15:53:10



Date: 24 JUN 2017 15:53:22



Date: 24 JUN 2017 15:53:39



9. Out of Band Emissions

9.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

9.2 Test Procedure

According to the KDB 558074D01 v03r05, the band-edge radiated test method as follows:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

According to the KDB 558074 D01 v03r05, the conducted spurious emissions test method as follows:

1. Set start frequency to DTS channel edge frequency.
2. Set stop frequency so as to encompass the spectrum to be examined.
3. Set RBW = 100 kHz.
4. Set VBW $\geq$ 300 kHz.
5. Detector = peak.
6. Trace Mode = max hold.
7. Sweep = auto couple.
8. Allow the trace to stabilize (this may take some time, depending on the extent of the span).
9. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding




restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

9.3 Environmental Conditions


Temperature:	21℃
Relative Humidity:	50%
ATM Pressure:	101.2

9.4 Summary of Test Results/Plots


802.11 b




Date: 24 JUN 2017 15:35:14





802.11g





802.11n





Date: 24 JUN 2017 15:41:52

10. Conducted Emissions


10.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

10.2 Basic Test Setup Block Diagram



10.3 Environmental Conditions

Temperature:	22°C
Relative Humidity:	53%
ATM Pressure:	101.1 mbar



10.4 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency	150 kHz
Stop Frequency.....	30 MHz
Sweep Speed	Auto
IF Bandwidth	10 kHz
Quasi-Peak Adapter Bandwidth	9 kHz
Quasi-Peak Adapter Mode	Normal

10.5 Summary of Test Results/Plots


According to the data in section 12.6, the EUT complied with the FCC Part 15.207 Conducted margin for this device, with the *worst* margin reading of:

-5.05 dB at 0.6419 MHz in the **Neutral** mode, **peak** detector, **0.15-30MHz**

10.6 Conducted Emissions Test Data




L





N





10. Test Photo





Test report