Report No.: DDT-R18042408-1E1

Issued Date: Sep. 20, 2018

FCC CERTIFICATION TEST REPORT

FOR

Applicant	:	Walnut Technology (Dongguan) Limited
Address	:	B502, Unit 1, Building 17, Xinzhuyuan, No. 4 Xinzhu Road, Songshan Lake High-tech District, Dongguan
Equipment under Test	:	SPECTRA
Model No.	:	Silver
Trade Mark	:	SPECTRA, WALNUTT
FCC ID	:	2AJJR-SILVER
Manufacturer	:	Walnut Technology (Dongguan) Limited
Address	:	B502, Unit 1, Building 17, Xinzhuyuan, No. 4 Xinzhu Road, Songshan Lake High-tech District, Dongguan

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, **E-mail:** ddt@dgddt.com, http://www.dgddt.com

REPORT

TABLE OF CONTENTS

Test report declares....4
1. Summary of test results 6
2. General test information.... 7
2.1. Description of EUT 7
2.2. Accessories of EUT 7
2.3. Assistant equipment used for test.... 7
2.4. Block diagram of EUT configuration for test.... 8
2.5. Test environment conditions.... 8
2.6. Deviations of test standard 8
2.7. Test laboratory 8
2.8. Measurement uncertainty 9
3. Equipment used during test 10
4. 6dB Bandwidth 11
4.1. Block diagram of test setup 11
4.2. Limits 11
4.3. Test Procedure.... 11
4.4. Test Result 11
4.5. Original test data 12
5. Maximum Peak Output Power 14
5.1. Block diagram of test setup 14
5.2. Limits 14
5.3. Test Procedure.... 14
5.4. Test Result 14
5.5. Original test data 15
6. Power Spectral Density.... 17
6.1. Block diagram of test setup 17
6.2. Limits 17
6.3. Test Procedure.... 17
6.4. Test Result 17
6.5. Original test data 18
7. Band Edge Compliance (conducted method) 20
7.1. Block diagram of test setup 20
7.2. Limits 20
7.3. Test Procedure.... 20
7.4. Test Result 21
7.5. Original test data 21

8. Radiated emission 23
8.1. Block diagram of test setup 23
8.2. Limit 24
8.3. Test Procedure 25
8.4. Test result 27
9. RF Conducted Spurious Emissions 31
9.1. Block diagram of test setup 31
9.2. Limits 31
9.3. Test Procedure 31
9.4. Test Result 32
9.5. Original test data 32
10. Emissions in restricted frequency bands 37
10.1. Block diagram of test setup 37
10.2. Limit 37
10.3. Test Procedure 37
10.4. Test result 37
11. Power Line Conducted Emission 42
11.1. Block diagram of test setup 42
11.2. Power Line Conducted Emission Limits 42
11.3. Test Procedure 42
11.4. Test Result 43
12. Antenna Requirements 46
12.1. Limit 46
12.2. Result 46

TEST REPORT DECLARE

Applicant	:	Walnut Technology (Dongguan) Limited
Address	:	B502, Unit 1, Building 17, Xinzhuyuan, No. 4 Xinzhu Road, Songshan Lake High-tech District, Dongguan
Equipment under Test	:	SPECTRA
Model No.	:	Silver
Trade mark	:	SPECTRA, WALNUTT
Manufacturer	:	Walnut Technology (Dongguan) Limited
Address	:	B502, Unit 1, Building 17, Xinzhuyuan, No. 4 Xinzhu Road, Songshan Lake High-tech District, Dongguan

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C

Test procedure used:

ANSI C63.10:2013

We Declare:

The equipment described above is tested by Dongguan Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Dongguan Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC standards.

Report No:	DDT-R18042408-1E1		
Date of Receipt:	Apr. 26, 2018	**Date of Test:**	Apr. 26, 2018 ~ Sep. 20, 2018

Prepared By:

Ella Gong

Ella Gong/Engineer

Approved By:

DONGGUAN DONGDIAN TESTING SERVICE CO., LTD. DONG DIAN TESTING DDT APPROVED

Damon Hu

Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision history

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Sep. 20, 2018	

1. Summary of test results

The EUT have been tested according to the applicable standards as referenced below.		
Description of Test Item	**Standard**	**Results**
6dB Bandwidth	FCC Part 15: 15.247 ANSI C63.10:2013	PASS
Peak Output Power	FCC Part 15: 15.247 ANSI C63.10:2013	PASS
Power Spectral Density	FCC Part 15: 15.247 ANSI C63.10:2013	PASS
Band Edge Compliance (conducted method)	FCC Part 15: 15.209 FCC Part 15: 15.247 ANSI C63.10:2013	PASS
Radiation Emission	FCC Part 15: 15.247 ANSI C63.10:2013	PASS
RF Conducted Spurious Emissions	FCC Part 15: 15.209 FCC Part 15: 15.247 ANSI C63.10:2013	PASS
Emission in restricted frequency bands	FCC Part 15: 15.209 FCC Part 15: 15.247 ANSI C63.10:2013	PASS
Power Line Conducted Emission	FCC Part 15: 15.207 ANSI C63.10:2013	PASS
Antenna requirement	FCC Part 15: 15.203	PASS

2. General test information

2.1. Description of EUT

EUT* Name	:	SPECTRA
Model Number	:	Silver
EUT function description	:	Please reference user manual of this device
Power supply	:	DC 42V from external AC Adapter DC 36V 5000mAh Polymer Li-ion built-in battery
Radio Specification	:	Bluetooth V5.0
Operation frequency	:	2402MHz-2480MHz
Modulation	:	GFSK
Data rate	:	1Mbps
Antenna Type	:	Integral antenna, maximum PK gain: 0dBi
Sample Type	:	Series production

Note: EUT is the ab. of equipment under test.

Channel information					
Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	14	2430MHz	28	2458MHz
1	2404MHz	15	2432MHz	29	2460MHz
2	2406MHz	16	2434MHz	30	2462MHz
3	2408MHz	17	2436MHz	31	2464MHz
4	2410MHz	18	2438MHz	32	2466MHz
5	2412MHz	19	2440MHz	33	2468MHz
6	2414MHz	20	2442MHz	34	2470MHz
7	2416MHz	21	2444MHz	35	2472MHz
8	2418MHz	22	2446MHz	36	2474MHz
9	2420MHz	23	2448MHz	37	2476MHz
10	2422MHz	24	2450MHz	38	2478MHz
11	2424MHz	25	2452MHz	39	2480MHz
12	2426MHz	26	2454MHz		
13	2428MHz	27	2456MHz		

2.2. Accessories of EUT

Description of Accessories	Manufacturer	Model number	Serial No.	Other
N/A	N/A	N/A	N/A	N/A

2.3. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	EMC Compliance	SN
Notebook	DELL	Latitude D610	FCC DOC	00045-534-136-300
AC Adapter	HUAWEI	HW-050450C00	N/A	Input: 100-240V~ 50/60Hz, Output: 5V/2A or 4.5V/5A or 5V/4.5A

2.4. Block diagram of EUT configuration for test



Test software: SmartRF Flash Programmer.EXE
The test software was used to control EUT work in Continuous Tx mode, and select test channel, wireless mode as below table:

Tested mode, channel, information		
Mode	Channel	Frequency (MHz)
GFSK	CH0	2402
	CH19	2440
	CH39	2480

2.5. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	21-25℃
Humidity range:	40-75%
Pressure range:	86-106kPa

2.6. Deviations of test standard

No Deviation.

2.7. Test laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, http://www.dgddt.com, Email: ddt@dgddt.com

CNAS Accreditation No. L6451; A2LA Accreditation No. 3870.01

Designation Number: CN1182; Test Firm Registration Number: 540522

Industry Canada site registration number: 10288A-1

2.8. Measurement uncertainty

Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power (Conducted) (Spectrum analyzer)	0.86dB (10MHz ≤ f < 3.6GHz);
	1.38dB (3.6GHz ≤ f < 8GHz)
Peak Output Power (Conducted) (Power Sensor)	0.74dB
Power Spectral Density	0.74dB (10MHz ≤ f < 3.6GHz);
	1.38dB (3.6GHz ≤ f < 8GHz)
Frequencies Stability	6.7 x 10^{-8} (Antenna couple method)
	5.5 x 10^{-8} (Conducted method)
Conducted spurious emissions	0.86dB (10MHz ≤ f < 3.6GHz);
	1.40dB (3.6GHz ≤ f < 8GHz)
	1.66dB (8GHz ≤ f < 22GHz)
Uncertainty for radio frequency (RBW<20kHz)	3×10^{-8}
Temperature	0.4℃
Humidity	2%
Uncertainty for Radiation Emission test (30MHz-1GHz)	4.70dB (Antenna Polarize: V)
	4.84dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1GHz-40GHz)	4.10dB (1-6GHz)
	4.40dB (6GHz-18GHz)
	3.54dB (18GHz-26GHz)
	4.30dB (26GHz-40GHz)
Uncertainty for Power line conduction emission test	3.32dB (150kHz-30MHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. Equipment used during test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
RF Connected Test (Tonscend RF Measurement System)					
Spectrum analyzer	R&S	FSU26	200071	Oct. 23, 2017	1 Year
Spectrum analyzer	R&S	FSU26	201124	Dec. 11, 2017	1 Year
Wideband Radio Communication tester	R&S	CMW500	117491	Jun. 29, 2018	1 Year
Vector Signal Generator	Agilent	E8267D	US49060192	Oct. 23, 2017	1 Year
Vector Signal Generator	Agilent	N5182A	MY48180737	Jun. 29, 2018	1 Year
Power Sensor	Agilent	U2021XA	MY55150010	Oct. 21, 2017	1 Year
Power Sensor	Agilent	U2021XA	MY55150011	Oct. 23, 2017	1 Year
DC Power Source	MATRIS	MPS-3005L-3	D813058W	Aug. 18, 2018	1 Year
Attenuator	Mini-Circuits	BW-S10W2	101109	Aug. 18, 2018	1 Year
RF Cable	Micable	C10-01-01-1	100309	Oct. 21, 2017	1 Year
Temp&Humi Programmable	ZHIXIANG	ZXGDJS-150L	ZX170110-A	Oct. 21, 2017	1 Year
Test Software	JS Tonscend	JS1120-3	Ver.2.7	N/A	N/A
Radiated Emission Test Chamber 1#					
EMI Test Receiver	R&S	ESU8	100316	Oct. 21, 2017	1 Year
Spectrum analyzer	Agilent	E4447A	MY50180031	Jun. 29, 2018	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB9163	9163-462	Nov. 09, 2017	1 Year
Active Loop antenna	Schwarzbeck	FMZB-1519	1519-038	Oct. 17, 2017	1 Year
Double Ridged Horn Antenna	R&S	HF907	100276	Oct. 17, 2017	1 Year
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	790	Nov. 09, 2017	1 Year
Pre-amplifier	A.H.	PAM-0118	360	Oct. 21, 2017	1 Year
Pre-amplifier	TERA-MW	TRLA-0040 G35	101303	Oct. 21, 2017	1 Year
RF Cable	HUBSER	CP-X2+ CP-X1	W11.03+ W12.02	Oct. 21, 2017	1 Year
RF Cable	N/A	SMAJ-SMA J-1M+ 11M	17070133+17070131	Nov. 08, 2017	1 Year
MI Cable	HUBSER	C10-01-01-1 M	1091629	Oct. 21, 2017	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A
Power Line Conducted Emissions Test					
Test Receiver	R&S	ESU8	100316	Oct. 21, 2017	1 Year
LISN 1	R&S	ENV216	101109	Oct. 21, 2017	1 Year
LISN 2	R&S	ESH2-Z5	100309	Oct. 21, 2017	1 Year
Pulse Limiter	R&S	ESH3-Z2	101242	Oct. 21, 2017	1 Year
CE Cable 1	HUBSER	N/A	W10.01	Oct. 21, 2017	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A

4. 6dB Bandwidth

4.1. Block diagram of test setup



4.2. Limits

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500 kHz

4.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows:

RBW:	100kHz
VBW:	300kHz
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, measure the 6dB bandwidth of signal.

4.4. Test Result

Mode	Channel	6dB bandwidth Result (MHz)	6 dB width Limit (MHz)	Conclusion
GFSK	CH0	0.696	>0.5	PASS
	CH19	0.688	>0.5	PASS
	CH39	0.688	>0.5	PASS

4.5. Original test data

BLE_ANT1_2402



Date: 4.MAY.2018 15:30:11

BLE_ANT1_2440



Date: 4.MAY.2018 15:34:59

BLE_ANT1_2480


RBW 100 kHz
VBW 300 kHz
SWT 5 ms
Delta 3 [T1]
0.23 dB
688.000000000 kHz
Ref 20 dBm
Att 20 dB
20 Offset 1.2 dB
OBW 1.164000000 MHz
Marker 1 [T1]
-5.03 dBm
2.479664000 GHz
Marker 2 [T1]
1.27 dBm
2.480256000 GHz
Temp 1 [T1 OBW]
-10.02 dBm
2.479424000 GHz
Temp 2 [T1 OBW]
-15.59 dBm
2.480588000 GHz
D1 -4.732 dBm
1 PK VIEW
A
LVL
3DB
Center 2.48 GHz
400 kHz/
Span 4 MHz
Date: 4.MAY.2018 15:37:00

5. Maximum Peak Output Power

5.1. Block diagram of test setup

Same with 4.1

5.2. Limits

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows:

RBW:	≥DTS bandwidth
VBW:	≥3 x RBW
Span	≥3 x RBW
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges measure out the PK output power.

5.4. Test Result

Mode	Freq (MHz)	Peak Output Power (dBm)	Limit (dBm)	Conclusion
GFSK	2402	2.21	30	PASS
	2440	2.31	30	PASS
	2480	1.82	30	PASS

5.5. Original test data

BLE_ANT1_2402



Date: 4.MAY.2018 15:30:35

BLE_ANT1_2440



Date: 4.MAY.2018 15:35:22

BLE_ANT1_2480


RBW 3 MHz
VBW 10 MHz
SWT 2.5 ms
Marker 1 [T1]
1.82 dBm
2.479532051 GHz
Ref 20 dBm
Att 20 dB
20 Offset 1.2 dB
10
0
-10
-20
-30
-40
-50
-60
-70
-80
1 PK
VIEW
A
LVL
3DB
Center 2.48 GHz
400 kHz/
Span 4 MHz
Date: 4.MAY.2018 15:37:23

6. Power Spectral Density

6.1. Block diagram of test setup

Same with 4.1

6.2. Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

6.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows:

Center frequency	DTS Channel center frequency
RBW:	3 kHz ≤ RBW ≤ 100 kHz
VBW:	≥ 3RBW
Span	1.5 times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.

(4) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.4. Test Result

EUT Set Mode	Channel	Result (dBm/30kHz)	Result (dBm/3kHz)
GFSK	CH0	-1.03	-11.03
	CH19	-1.32	-11.32
	CH39	-1.87	-11.87
Limit: <8dBm/3kHz			Conclusion: PASS

6.5. Original test data

BLE_ANT1_2402



Date: 4.MAY.2018 15:30:46

BLE_ANT1_2440



Date: 4.MAY.2018 15:35:33

BLE_ANT1_2480


RBW 30 kHz
VBW 100 kHz
SWT 10 ms
Marker 1 [T1]
-1.87 dBm
2.480010000 GHz
Ref 20 dBm
Att 20 dB
20 Offset 1.2 dB
1 PK
MAXH
A
LVL
3DB
10
0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.48 GHz
200 kHz/
Span 2 MHz
Date: 4.MAY.2018 15:37:34

7. Band Edge Compliance (conducted method)

7.1. Block diagram of test setup

Same with 4.1

7.2. Limits

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

7.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	DTS Channel center frequency
RBW:	100kHz
VBW:	300kHz
Span	1.5times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:

RBW:	100kHz
VBW:	300kHz
Span	Encompass frequency range to be measured
Number of measurement points	≥ span/RBW
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band

7.4. Test Result

EUT Set Mode	CH or Frequency	Measured Range	Result (dBm)
GFSK	CH0	2.31GHz-2.41GHz	PASS
	CH39	2.47GHz-2.57GHz	PASS

7.5. Original test data

BLE_ANT1_Low



BLE_ANT1_High


RBW 100 kHz
VBW 300 kHz
SWT 10 ms
Ref 20 dBm
Att 20 dB
Offset 1.2 dB
Marker 4 [T1]
-51.44 dBm
2.483600000 GHz
Marker 1 [T1]
1.06 dBm
2.479700000 GHz
Marker 2 [T1]
-47.92 dBm
2.483500000 GHz
Marker 3 [T1]
-58.18 dBm
2.500000000 GHz
D1 -18.94 dBm
1 PK
MAXH
A
LVL
3DB
Start 2.47 GHz
10 MHz/
Stop 2.57 GHz
Date: 4.MAY.2018 15:37:46

8. Radiated emission

8.1. Block diagram of test setup

In 3m Anechoic Chamber Test Setup Diagram for 9kHz-30MHz



In 3m Anechoic Chamber Test Setup Diagram for 30MHz-1GHz



In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test an appropriate high pass filter was inserted in the input port of AMP.

8.2. Limit

8.2.1 FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	([2])
13.36-13.41			

8.2.2 FCC 15.209 Limit.

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Note: (1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30MHz, measurement may be performed at a distance closer then that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$Limit_{3m}(dBuV/m) = Limit_{30m}(dBuV/m) + 40Log(30m/3m)$$

8.2.3 Limit for this EUT

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

8.3. Test Procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a semi-anechoic chamber for above 1G.

(2) Test antenna was located 3m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9kHz-30MHz	Active Loop antenna	3m
30MHz-1GHz	Trilog Broadband Antenna	3m
1GHz-18GHz	Double Ridged Horn Antenna(1GHz-18GHz)	3m
18GHz-40GHz	Horn Antenna(18GHz-40GHz)	1m

According ANSI C63.10:2013 clause 6.4.4.2 and 6,5.3, for measurements below 30 MHz, the loop antenna was positioned with its plane vertical from the EUT and rotated about its vertical axis for maximum response at each azimuth position around the EUT. And the loop antenna also

be positioned with its plane horizontal at the specified distance from the EUT. The center of the loop is 1 m above the ground. for measurement above 30MHz, the Trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9kHz to 25GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1m to 4m (Except loop antenna, it's fixed 1m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9kHz to 25GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 9kHz to 30MHz and 18GHz to 25GHz, so below final test was performed with frequency range from 30MHz to 18GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2013 on Radiated Emission test.

(5) The emissions from 9kHz to 1GHz were measured based on CISPR QP detector except for the frequency bands 9-90kHz, 110-490kHz, for emissions from 9kHz-90kHz,110kHz-490kHz and above 1GHz were measured based on average detector, for emissions above 1GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9kHz to 1GHz, QP or average values were measured with EMI receiver with below RBW

Frequency band	RBW
9kHz-150kHz	200Hz
150kHz-30MHz	9kHz
30MHz-1GHz	120kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure (according ANSI C63.10:2013 clause 4.1.4.2.2 procedure for average measure).

(8) X axis, Y axis, Z axis are tested, and worse setup X axis is reported.

8.4. Test result

PASS. (See below detailed test result)

All the emissions except fundamental emission from 9kHz to 25GHz were comply with 15.209 limit.

Note1: According exploratory test no any obvious emission was detected from 9kHz to 30MHz and 18GHz to 25GHz, so the final test was performed with frequency range from 30MHz to 18GHz and recorded in below.

Note2: For emissions below 1GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1GHz, the final test was only performed with EUT working in GFSK, Tx 2440MHz mode.

Note3: For emissions above 1GHz. If peak results comply with AV limit, AV Result is deemed to comply with AV limit.

Radiated Emission test (below 1GHz)

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber 1#	D:\2018 RE1# Report Data\Q18042408-1E SILVER\FCC BELOW1G - 0918.EM6	
Test Date	: 2018-09-18	**Tested By**	: TALENT
EUT	: SPECTRA	**Model Number**	: Silver
Power Supply	: AC 120V/60Hz	**Test Mode**	: Tx mode
Condition	: Temp:24.5'C, Humi:55.5%, Press:100.1kPa	**Antenna/Distance**	: 2017 VULB 9163 1#/3m/HORIZONTAL
Memo	:		

Data: 34



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	143.83	21.25	7.64	4.73	33.62	43.50	-9.88	QP	HORIZONTAL
2	159.78	19.31	8.59	4.82	32.72	43.50	-10.78	QP	HORIZONTAL
3	191.75	14.41	10.78	4.98	30.17	43.50	-13.33	QP	HORIZONTAL
4	287.99	7.67	13.12	5.47	26.26	46.00	-19.74	QP	HORIZONTAL
5	431.03	6.92	15.97	5.74	28.63	46.00	-17.37	QP	HORIZONTAL
6	774.16	4.19	20.91	7.24	32.34	46.00	-13.66	QP	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber 1#	D:\2018 RE1# Report Data\Q18042408-1E SILVER\FCC BELOW1G - 0917.EM6	
Test Date	: 2018-09-18	**Tested By**	: TALENT
EUT	: SPECTRA	**Model Number**	: Silver
Power Supply	: AC 120V/60Hz	**Test Mode**	: Tx mode
Condition	: Temp:24.5'C, Humi:55.5%, Press:100.1kPa	**Antenna/Distance**	: 2017 VULB 9163 1#/3m/VERTICAL
Memo	:		

Data: 35



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	52.21	5.64	13.23	4.02	22.89	40.00	-17.11	QP	VERTICAL
2	98.14	3.40	11.13	4.40	18.93	43.50	-24.57	QP	VERTICAL
3	143.83	14.42	7.64	4.73	26.79	43.50	-16.71	QP	VERTICAL
4	287.99	4.67	13.12	5.47	23.26	46.00	-22.74	QP	VERTICAL
5	432.55	11.21	16.01	5.73	32.95	46.00	-13.05	QP	VERTICAL
6	906.48	4.74	22.59	7.62	34.95	46.00	-11.05	QP	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

Radiated Emission test (above 1GHz)

Freq. (MHz)	Read level (dBμV)	Antenna Factor (dB/m)	PRM Factor(dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector type	Polarization
GFSK Tx mode 2402MHz									
3346.00	32.19	31.13	23.35	6.06	46.03	74.00	-27.97	Peak	HORIZONTAL
4502.00	30.57	34.20	22.63	7.08	49.22	74.00	-24.78	Peak	HORIZONTAL
5114.00	30.42	35.11	22.47	7.65	50.71	74.00	-23.29	Peak	HORIZONTAL
5947.00	30.73	35.68	22.07	8.18	52.52	74.00	-21.48	Peak	HORIZONTAL
6593.00	29.88	35.90	22.69	8.28	51.37	74.00	-22.63	Peak	HORIZONTAL
7035.00	29.73	36.81	23.08	8.36	51.82	74.00	-22.18	Peak	HORIZONTAL
3601.00	32.34	32.02	23.21	6.26	47.41	74.00	-26.59	Peak	VERTICAL
4553.00	32.45	34.28	22.65	7.13	51.21	74.00	-22.79	Peak	VERTICAL
5216.00	30.78	35.22	22.12	7.72	51.60	74.00	-22.40	Peak	VERTICAL
5675.00	29.50	35.57	21.51	8.01	51.57	74.00	-22.43	Peak	VERTICAL
5947.00	30.73	35.68	22.07	8.18	52.52	74.00	-21.48	Peak	VERTICAL
6882.00	30.23	36.54	22.95	8.32	52.14	74.00	-21.86	Peak	VERTICAL
GFSK Tx mode 2440MHz									
3431.00	31.59	31.56	23.25	6.12	46.02	74.00	-27.98	Peak	HORIZONTAL
4604.00	31.34	34.37	22.68	7.18	50.21	74.00	-23.79	Peak	HORIZONTAL
5403.00	29.73	35.40	21.48	7.83	51.48	74.00	-22.52	Peak	HORIZONTAL
5998.00	28.56	35.70	22.18	8.21	50.29	74.00	-23.71	Peak	HORIZONTAL
6593.00	31.07	35.90	22.69	8.28	52.56	74.00	-21.44	Peak	HORIZONTAL
7052.00	30.38	36.82	23.09	8.38	52.49	74.00	-21.51	Peak	HORIZONTAL
3822.00	31.90	32.29	23.30	6.44	47.33	74.00	-26.67	Peak	VERTICAL
4655.00	31.77	34.45	22.70	7.23	50.75	74.00	-23.25	Peak	VERTICAL
5233.00	30.09	35.23	22.06	7.73	50.99	74.00	-23.01	Peak	VERTICAL
5947.00	29.88	35.68	22.07	8.18	51.67	74.00	-22.33	Peak	VERTICAL
6355.00	30.14	35.70	22.49	8.25	51.60	74.00	-22.40	Peak	VERTICAL
6984.00	31.58	36.76	23.05	8.33	53.62	74.00	-20.38	Peak	VERTICAL
GFSK Tx mode 2480MHz									
3516.00	31.24	31.92	23.18	6.19	46.17	74.00	-27.83	Peak	HORIZONTAL
4553.00	30.97	34.28	22.65	7.13	49.73	74.00	-24.27	Peak	HORIZONTAL
5131.00	30.38	35.13	22.41	7.66	50.76	74.00	-23.24	Peak	HORIZONTAL
5335.00	29.92	35.33	21.71	7.79	51.33	74.00	-22.67	Peak	HORIZONTAL
5981.00	30.07	35.69	22.14	8.20	51.82	74.00	-22.18	Peak	HORIZONTAL
6525.00	30.82	35.76	22.63	8.27	52.22	74.00	-21.78	Peak	HORIZONTAL
3550.00	30.93	31.96	23.19	6.22	45.92	74.00	-28.08	Peak	VERTICAL
4553.00	31.59	34.28	22.65	7.13	50.35	74.00	-23.65	Peak	VERTICAL
5352.00	29.58	35.35	21.66	7.80	51.07	74.00	-22.93	Peak	VERTICAL
5947.00	29.53	35.68	22.07	8.18	51.32	74.00	-22.68	Peak	VERTICAL
6406.00	30.52	35.70	22.53	8.26	51.95	74.00	-22.05	Peak	VERTICAL
7171.00	29.81	36.87	23.17	8.48	51.99	74.00	-22.01	Peak	VERTICAL
Result: Pass									

Note:1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. For emissions above 1GHz. If peak results comply with AV limit, AV Result is deemed to comply with AV limit.

9. RF Conducted Spurious Emissions

9.1. Block diagram of test setup

Same as section 4.1

9.2. Limits

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

9.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	Test frequency
RBW:	100kHz
VBW:	300kHz
Span	Wide enough to capture the peak level of the in-band emission
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:

RBW:	100kHz
VBW:	300kHz
Span	Encompass frequency range to be measured
Number of measurement points	≥span/RBW
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band

9.4. Test Result

Mode	Freq. (MHz)	Conclusion
GFSK	2402	PASS
	2440	PASS
	2480	PASS

9.5. Original test data

BLE_ANT1_2402_Ref



BLE_ANT1_2402_30~1000



Date: 4.MAY.2018 15:31:13

BLE_ANT1_2402_1000~26500



Date: 4.MAY.2018 15:31:55

BLE_ANT1_2440_Ref



Date: 4.MAY.2018 15:35:39

BLE_ANT1_2440_30~1000



Date: 4.MAY.2018 15:35:47

BLE_ANT1_2440_1000~26500



BLE_ANT1_2480_Ref



BLE_ANT1_2480_30~1000



Date: 4.MAY.2018 15:38:01

BLE_ANT1_2480_1000~26500



Date: 4.MAY.2018 15:38:43

10. Emissions in restricted frequency bands

10.1. Block diagram of test setup



10.2. Limit

All restriction band should comply with 15.209, other emission should be at least 20dB below the fundamental.

10.3. Test Procedure

Same with clause 8.3 except change investigated frequency range from 2310MHz to 2410MHz and 2470MHz to 2500MHz.

Remark: All restriction band have been tested, and only the worst case is shown in report.

10.4. Test result

PASS. (See below detailed test result)

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber 1#	D:\2018 RE1# Report Data\Q18042408-1E SILVER\FCC ABOVE1G.EM6	
Test Date	: 2018-05-07	**Tested By**	: Talent
EUT	: SPECTRA	**Model Number**	: Silver
Power Supply	: Battery	**Test Mode**	: Tx mode
Condition	: Temp:24.5'C, Humi:55.5%, Press:100.1kPa	**Antenna/Distance**	: 2017 HF907/3m/HORIZONTAL
Memo	: 2402		

Data: 2



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2361.10	38.47	26.90	23.16	5.08	47.29	74.00	-26.71	Peak	HORIZONTAL
2	2390.00	36.44	27.00	23.21	5.11	45.34	74.00	-28.66	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber 1#	D:\2018 RE1# Report Data\Q18042408-1E SILVER\FCC ABOVE1G.EM6	
Test Date	: 2018-05-07	**Tested By**	: Talent
EUT	: SPECTRA	**Model Number**	: Silver
Power Supply	: Battery	**Test Mode**	: Tx mode
Condition	: Temp:24.5'C, Humi:55.5%, Press:100.1kPa	**Antenna/Distance**	: 2017 HF907/3m/VERTICAL
Memo	: 2402		

Data: 1



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2378.50	37.98	26.96	23.19	5.10	46.85	74.00	-27.15	Peak	VERTICAL
2	2390.00	37.23	27.00	23.21	5.11	46.13	74.00	-27.87	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber 1#	D:\2018 RE1# Report Data\Q18042408-1E SILVER\FCC ABOVE1G.EM6	
Test Date	: 2018-05-07	**Tested By**	: Talent
EUT	: SPECTRA	**Model Number**	: Silver
Power Supply	: Battery	**Test Mode**	: Tx mode
Condition	: Temp:24.5'C, Humi:55.5%, Press:100.1kPa	**Antenna/Distance**	: 2017 HF907/3m/HORIZONTAL
Memo	: 2480		

Data: 10



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	36.62	27.34	23.38	5.21	45.79	74.00	-28.21	Peak	HORIZONTAL
2	2485.96	39.07	27.35	23.38	5.21	48.25	74.00	-25.75	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber 1#	D:\2018 RE1# Report Data\Q18042408-1E SILVER\FCC ABOVE1G.EM6	
Test Date	: 2018-05-07	**Tested By**	: Talent
EUT	: SPECTRA	**Model Number**	: Silver
Power Supply	: Battery	**Test Mode**	: Tx mode
Condition	: Temp:24.5'C, Humi:55.5%, Press:100.1kPa	**Antenna/Distance**	: 2017 HF907/3m/VERTICAL
Memo	: 2480		

Data: 9



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	39.25	27.34	23.38	5.21	48.42	74.00	-25.58	Peak	VERTICAL
2	2487.55	39.51	27.36	23.39	5.22	48.70	74.00	-25.30	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

11. Power Line Conducted Emission

11.1. Block diagram of test setup



11.2. Power Line Conducted Emission Limits

Frequency	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

11.3. Test Procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

Configuration EUT to simulate typical usage as described in clause 2.4 and test equipment as described in clause 10.2 of this report.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

11.4. Test Result

PASS. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.
Note2: "-----" means Peak detection; "-----" means Average detection
Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/60Hz, recorded worse case (AC 120V/60Hz).

TR-4-E-010 Conducted Emission Test Result

Test Site	: DDT 1# Shield Room	D:\2018 CE report data\Q18042408-1E\CE.EM6	
Test Date	: 2018-09-17	**Tested By**	: Aaron
EUT	: SPECTRA	**Model Number**	: Silver
Power Supply	: AC 120V/60Hz	**Test Mode**	: Tx mode
Condition	: Temp:24.5'C, Humi:55.5%, Press:100.1kPa	**LISN**	: 2017 ENV216/NEUTRAL
Memo	:		

Data: 2



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBµV)	Limit Line (dBµV)	Over Limit (dB)	Detector	Phase
1	0.19	29.25	9.45	0.04	9.86	48.60	63.89	-15.29	QP	NEUTRAL
2	0.19	19.26	9.45	0.04	9.86	38.61	53.89	-15.28	Average	NEUTRAL
3	0.25	26.06	9.42	0.04	9.86	45.38	61.82	-16.44	QP	NEUTRAL
4	0.25	17.18	9.42	0.04	9.86	36.50	51.82	-15.32	Average	NEUTRAL
5	1.09	18.73	9.30	0.14	9.86	38.03	56.00	-17.97	QP	NEUTRAL
6	1.09	9.10	9.30	0.14	9.86	28.40	46.00	-17.60	Average	NEUTRAL
7	3.68	19.17	9.27	0.11	9.87	38.42	56.00	-17.58	QP	NEUTRAL
8	3.68	8.02	9.27	0.11	9.87	27.27	46.00	-18.73	Average	NEUTRAL
9	7.18	15.34	9.33	0.11	9.88	34.66	60.00	-25.34	QP	NEUTRAL
10	7.18	10.16	9.33	0.11	9.88	29.48	50.00	-20.52	Average	NEUTRAL
11	12.52	13.45	9.45	0.12	9.91	32.93	60.00	-27.07	QP	NEUTRAL
12	12.52	6.80	9.45	0.12	9.91	26.28	50.00	-23.72	Average	NEUTRAL

Note: 1. Result Level = Read Level +LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site	: DDT 1# Shield Room	D:\2018 CE report data\Q18042408-1E\CE.EM6	
Test Date	: 2018-09-17	**Tested By**	: Aaron
EUT	: SPECTRA	**Model Number**	: Silver
Power Supply	: AC 120V/60Hz	**Test Mode**	: Tx mode
Condition	: Temp:24.5'C, Humi:55.5%, Press:100.1kPa	**LISN**	: 2017 ENV216/LINE
Memo	:		

Data: 4



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBµV)	Limit Line (dBµV)	Over Limit (dB)	Detector	Phase
1	0.19	26.81	9.51	0.04	9.86	46.22	63.89	-17.67	QP	LINE
2	0.19	18.25	9.51	0.04	9.86	37.66	53.89	-16.23	Average	LINE
3	0.26	22.40	9.52	0.04	9.86	41.82	61.47	-19.65	QP	LINE
4	0.26	14.39	9.52	0.04	9.86	33.81	51.47	-17.66	Average	LINE
5	0.38	16.39	9.53	0.04	9.83	35.79	58.34	-22.55	QP	LINE
6	0.38	7.30	9.53	0.04	9.83	26.70	48.34	-21.64	Average	LINE
7	0.82	16.43	9.56	0.11	9.86	35.96	56.00	-20.04	QP	LINE
8	0.82	6.33	9.56	0.11	9.86	25.86	46.00	-20.14	Average	LINE
9	3.64	19.08	9.63	0.11	9.87	38.69	56.00	-17.31	QP	LINE
10	3.64	9.79	9.63	0.11	9.87	29.40	46.00	-16.60	Average	LINE
11	7.81	16.21	9.74	0.11	9.88	35.94	60.00	-24.06	QP	LINE
12	7.81	9.09	9.74	0.11	9.88	28.82	50.00	-21.18	Average	LINE

Note: 1. Result Level = Read Level +LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

12. Antenna Requirements

12.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

12.2. Result

The antennas used for this product is integrated antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 0dBi.

END OF REPORT