



FCC CFR47 PART 15 SUBPART C

Bluetooth Low Energy

CERTIFICATION TEST REPORT

FOR

AIRWAY CLEARANCE SYSTEM

PRODUCT NAME: PMACS1WI

FCC ID: 2AJKO-PMACS1WI

REPORT NUMBER: 4787592605-E2V2

ISSUE DATE: DEC 26, 2016

Prepared for

**Hill-Rom Services Private Limited
1 Yishun Avenue 7, 768923, Singapore**

Prepared by

**UL Korea, Ltd. Suwon Laboratory
218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16675, Korea
TEL: (031) 337-9902
FAX: (031) 213-5433**



Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V1	12/21/16	Initial issue	Junwhan Lee
V2	12/26/16	Addressed TCB's questions	Junwhan Lee

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS.....	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION.....	6
4. CALIBRATION AND UNCERTAINTY	6
4.1. MEASURING INSTRUMENT CALIBRATION	6
4.2. SAMPLE CALCULATION	6
4.3. MEASUREMENT UNCERTAINTY	6
5. EQUIPMENT UNDER TEST	7
5.1. DESCRIPTION OF EUT	7
5.2. MAXIMUM OUTPUT POWER.....	7
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	7
5.4. WORST-CASE CONFIGURATION AND MODE.....	7
5.5. DESCRIPTION OF TEST SETUP.....	8
6. TEST AND MEASUREMENT EQUIPMENT	10
7. MEASUREMENT METHODS.....	11
8. ON TIME, DUTY CYCLE AND MEASUREMENT METHODS	11
8.1. ON TIME AND DUTY CYCLE RESULTS.....	11
9. SUMMARY TABLE	12
10. ANTENNA PORT TEST RESULTS.....	13
10.1. 6 dB BANDWIDTH.....	13
10.2. 99% BANDWIDTH	15
10.3. OUTPUT POWER.....	17
10.4. AVERAGE POWER	19
10.5. PSD.....	20
10.6. CONDUCTED SPURIOUS EMISSIONS	22
11. RADIATED TEST RESULTS.....	26
11.1. LIMITS AND PROCEDURE.....	26
11.2. TRANSMITTER ABOVE 1 GHz.....	28
11.3. WORST-CASE BELOW 1 GHz	38

12.	AC POWER LINE CONDUCTED EMISSIONS	40
13.	SETUP PHOTOS	45

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: Hill-Rom Services Private Limited
EUT DESCRIPTION: Airway Clearance System
PRODUCT NAME: PMACS1WI
SERIAL NUMBER: PREDVM0036 (RADIATED & CONDUCTED)
DATE TESTED: OCT 07, 2016 - DEC 21, 2016

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Korea, Ltd. By:



CY Choi
Suwon Lab Engineer
UL Korea, Ltd.

Tested By:



Junwhan Lee
Suwon Lab Engineer
UL Korea, Ltd.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2013, FCC CFR 47 Part 2, FCC CFR 47 Part 15.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro	
☒	Chamber 1
☐	Chamber 2

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <http://www.iasonline.org/PDF/TL/TL-637.pdf>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamplifier Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	2.32 dB
Radiated Disturbance, Below 1GHz	4.14 dB
Radiated Disturbance, Above 1 GHz	5.97 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a Airway Clearance System with DTS/UNII a/b/g/n and BT/BLE features.
This test report addresses the DTS (BLE) operational mode.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum total conducted output power as follows:

Frequency Range [MHz]	Mode	Power Mode	Output Power [dBm]	Output Power [mW]
2402 - 2480	BLE	Peak	4.54	2.85
		Average	4.03	2.53

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an Chip antenna, with a maximum gain of 0.5 dBi

5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission below 1GHz and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

Radiated emission above 1GHz was performed with the EUT set to transmit low/mid/high channels.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that X orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in X orientation.

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Adapter	SHENZHEN MEGMEET ELECTRICAL CO., LTD	MANGO120-24CK	8801631000045	N/A


I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-DIN	Shielded	1.2m	N/A

TEST SETUP

The EUT is a stand-alone unit during the tests.
Test software exercised the EUT to enable BLE mode.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	Cal Due
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	749	04-25-17
Antenna, Horn, 18 GHz	ETS	3115	00161451	05-17-17
Antenna, Horn, 18 GHz	ETS	3117	00168724	06-17-17
Antenna, Horn, 18 GHz	ETS	3117	00168717	06-17-17
Antenna, Horn, 40 GHz	ETS	3116C	00166155	11-30-17
Antenna, Horn, 40 GHz	ETS	3116C-PA	00168841	12-15-17
Preamplifier, 1000 MHz	Sonoma	310N	341282	08-17-17
Preamplifier, 1000 MHz	Sonoma	310N	351741	08-16-17
Preamplifier	ETS	3115-PA	00167475	08-17-17
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1896138	08-16-17
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	08-17-17
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54490312	08-16-17
Bluetooth Tester	TESCOM	TC-3000C	3000C000546	08-18-17
Average Power Sensor	R&S	NRZ-Z91	102681	08-16-17
Average Power Sensor	Agilent / HP	U2000	MY54270007	08-17-17
EMI Test Receive, 40 GHz	R&S	ESU40	100439	08-17-17
EMI Test Receive, 40 GHz	R&S	ESU40	100457	08-16-17
EMI Test Receive, 3 GHz	R&S	ESR3	101832	08-16-17
Attenuator / Switch driver	HP	11713A	3748A04272	N/A
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	009	08-17-17
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	015	08-16-17
High Pass Filter 3GHz	Micro-Tronics	HPM17543	010	08-17-17
High Pass Filter 3GHz	Micro-Tronics	HPM17543	015	08-16-17
High Pass Filter 6GHz	Micro-Tronics	HPM17542	009	08-17-17
High Pass Filter 6GHz	Micro-Tronics	HPM17542	016	08-16-17
LISN	R&S	ENV-216	101836	08-16-17
LISN	R&S	ENV-216	101837	08-16-17
Attenuator	PASTERNAK	PE7087-10	A009	08-16-17
Antenna, Loop, 9kHz-30MHz	R&S	HFH2-Z2	100418	11-25-17

7. MEASUREMENT METHODS

KDB 558074 D01 DTS Meas Guidance v03r05: Measurement Procedure §9.1.1 is used for peak power and §10.2 PKPSD is used for power spectral density.

Unwanted emissions within Restricted Bands are measured using traditional radiated procedures.

Band edge emissions within Restricted Bands are measured using RMS with duty cycle factor offset method.


8. ON TIME, DUTY CYCLE AND MEASUREMENT METHODS

LIMITS

None: for reporting purposes only.

8.1. ON TIME AND DUTY CYCLE RESULTS

Mode	ON Time B [msec]	Period [msec]	Duty Cycle x [linear]	Duty Cycle [%]	Duty Cycle Correction Factor [dB]	1/T Minimum VBW [kHz]
2400MHz Bands						
BLE	0.386	0.647	0.598	59.8%	2.24	2.589



9. SUMMARY TABLE

FCC Part Section	Test Description	Test Limit	Test Condition	Test Result	Worst Case
15.247 (a)(2)	Occupied Band width (6dB)	>500KHz	Conducted	Pass	687.7 kHz
2.1051, 15.247 (d)	Band Edge / Conducted Spurious Emission	-20dBc		Pass	-51.7 dBm
15.247	TX conducted output power	<30dBm		Pass	4.542 dBm (Peak)
15.247	PSD	<8dBm		Pass	-11.44 dBm (Peak)
15.207 (a)	AC Power Line conducted emissions	Section 10	Power Line conducted	Pass	48.55 dBuV (Qp)
15.205, 15.209	Radiated Spurious Emission	< 54dBuV/m	Radiated	Pass	50.14 dBuV/m (Av)

10. ANTENNA PORT TEST RESULTS

10.1. 6 dB BANDWIDTH

LIMITS

FCC §15.247 (a) (2)

The minimum 6 dB bandwidth shall be at least 500 kHz.


TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The RBW is set to 100 kHz and the VBW is set to 300 kHz. The sweep time is coupled.

RESULTS

Channel	Frequency [MHz]	6 dB Bandwidth [kHz]	Minimum Limit [kHz]
Low	2402	689.5	500.0
Mid	2440	687.7	500.0
High	2480	690.9	500.0
Worst		687.7	500.0

6 dB BANDWIDTH PLOTS



10.2. 99% BANDWIDTH

LIMITS

None; for reporting purposes only.




TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99 % bandwidth and to 1% of the span. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

RESULTS

Channel	Frequency [MHz]	99% Bandwidth [MHz]
Low	2402	1.043
Mid	2440	1.033
High	2480	1.032
Worst		1.043

99% BANDWIDTH PLOTS

Low CH	 Center Freq: 2.40200000 GHz Radio Std: None Trig: Free Run #Atten: 30 dB Radio Device: BTS 10 dB/div Ref 20.00 dBm Center 2.402 GHz Span 3 MHz #Res BW 30 kHz VBW 300 kHz #Sweep 100 ms Occupied Bandwidth 1.0425 MHz Total Power -2.85 dBm Transmit Freq Error 4.399 kHz OBW Power 99.00 % x dB Bandwidth 1.234 MHz x dB -26.00 dB
Middle CH	 Center Freq: 2.44000000 GHz Radio Std: None Trig: Free Run #Atten: 30 dB Radio Device: BTS 10 dB/div Ref 20.00 dBm Center 2.44 GHz Span 3 MHz #Res BW 30 kHz VBW 300 kHz #Sweep 100 ms Occupied Bandwidth 1.0331 MHz Total Power 0.13 dBm Transmit Freq Error -8.423 kHz OBW Power 99.00 % x dB Bandwidth 1.215 MHz x dB -26.00 dB
High CH	 Center Freq: 2.48000000 GHz Radio Std: None Trig: Free Run #Atten: 30 dB Radio Device: BTS 10 dB/div Ref 20.00 dBm Center 2.48 GHz Span 3 MHz #Res BW 30 kHz VBW 300 kHz #Sweep 100 ms Occupied Bandwidth 1.0316 MHz Total Power 2.03 dBm Transmit Freq Error -4.869 kHz OBW Power 99.00 % x dB Bandwidth 1.234 MHz x dB -26.00 dB

10.3. OUTPUT POWER

LIMITS

FCC §15.247 (b)

The maximum antenna gain is less than or equal to 6 dBi, therefore the limit is 30 dBm.


TEST PROCEDURE

Peak power is measured using KDB558074 D01 DTS Meas Guidance v03r05 under section 9.1.1 utilizing spectrum analyzer.

RESULTS

Channel	Frequency [MHz]	Peak Power Reading [dBm]	Limit [dBm]	Margin [dB]
Low	2402	-0.286	30.000	-30.286
Mid	2440	2.647	30.000	-27.353
High	2480	4.542	30.000	-25.458
Worst		4.542		-25.458

OUTPUT POWER PLOTS



10.4. AVERAGE POWER

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter.

RESULTS

The cable assembly insertion loss of 10.1 dB (including 10 dB pad and 0.1 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

Channel	Frequency [MHz]	AV power [dBm]	AV power [mW]
Low	2402	-0.86	0.82
Middle	2440	2.13	1.63
High	2480	4.03	2.53

10.5. PSD

LIMITS

FCC §15.247

The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST PROCEDURE

Power Spectral Density was performed utilizing the "Method PKPSD (Peak PSD)" under KDB558074 D01 DTS Meas Guidance v03r05

RESULTS

Channel	Frequency [MHz]	PSD [dBm]	Limit [dBm]	Margin [dB]
Low	2402	-16.32	8.00	-24.32
Mid	2440	-13.32	8.00	-21.32
High	2480	-11.44	8.00	-19.44

Low CH

Middle CH

High CH

Keysight Spectrum Analyzer - Swept SA

RL RF 50 Ω DC CORREC SENSE INT ALIGN AUTO 07:14:16 PM Nov 22, 2016

PN0: Wide Trg: Free Run #Avg Type: RMS
IF Gain: Low Atten: 20 dB AvgHold: 100/100

Ref 10.00 dBm

10 dB/div Log

Mkr1 2.401 967 71 GHz
-16.318 dBm

Center 2.4020000 GHz Span 1.564 MHz
#Res BW 3.0 kHz #VBW 10 kHz Sweep 50.67 ms (20001 pts)

Middle CH

Keysight Spectrum Analyzer - Swept SA

RL RF 50 Ω DC CORREC SENSE INT ALIGN AUTO 07:13:45 PM Nov 22, 2016

PN0: Wide Trg: Free Run #Avg Type: RMS
IF Gain: Low Atten: 20 dB AvgHold: 100/100

Ref 10.00 dBm

10 dB/div Log

Mkr1 2.439 966 76 GHz
-13.318 dBm

Center 2.4400000 GHz Span 1.550 MHz
#Res BW 3.0 kHz #VBW 10 kHz Sweep 49.33 ms (20001 pts)

High CH

Keysight Spectrum Analyzer - Swept SA

RL RF 50 Ω DC CORREC SENSE INT ALIGN AUTO 07:13:01 PM Nov 22, 2016

PN0: Wide Trg: Free Run #Avg Type: RMS
IF Gain: Low Atten: 20 dB AvgHold: 100/100

Ref 10.00 dBm

10 dB/div Log

Mkr1 2.479 966 19 GHz
-11.440 dBm

Center 2.4800000 GHz Span 1.547 MHz
#Res BW 3.0 kHz #VBW 10 kHz Sweep 49.33 ms (20001 pts)

10.6. CONDUCTED SPURIOUS EMISSIONS

LIMITS

FCC §15.247 (d)

Output power was measured based on the use of a peak measurement, therefore the required attenuation is 20 dB.


TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

RESULTS


BANDEDGE & SPURIOUS EMISSIONS, LOW CHANNEL



SPURIOUS EMISSIONS, MID CHANNEL



SPURIOUS EMISSIONS, HIGH CHANNEL



11. RADIATED TEST RESULTS

11.1. LIMITS AND PROCEDURE

LIMITS

FCC §15.205 and §15.209

Limits for radiated disturbance of an intentional radiator		
Frequency range (MHz)	Limits (μV/m)	Measurement Distance (m)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 – 88	100**	3
88 - 216	150**	3
216 – 960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g. §§ 15.231 and 15.241.

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane for below 1GHz and 150 cm for above 1GHz. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and add duty cycle factor for average measurements. (Restricted bandedge, Final detection of spurious harmonic emissions)
Duty cycle factor = $10 \log(1/x)$. For this sample: $DCF = 10 \log(1/0.598) = 2.24 \text{ dB}$
(Spectrum Analyzer round it up to 2.24dB)

Pre-scans to detect harmonic and spurious emissions, the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 30 KHz for peak measurements.

The spectrum from 1 GHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.
(From 30MHz to 1GHz, test was performed with the EUT set to transmit at the channel with highest output power)


The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

Note : Emission was pre-scanned from 9KHz to 30MHz; No emissions were detected which was at least 20dB below the specification limit (consider distance correction factor).
Per FCC part 15.31(o), test results were not reported.

Formula for converting the field strength from uV/m to dBuV/m is:
Limit (dBuV/m) = $20 \log \text{limit (uV/m)}$

11.2. TRANSMITTER ABOVE 1 GHz RESTRICTED BANDEDGE (LOW CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 17)_150619	Path_2	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	46.25	Pk		-29	0	49.05	-	-	74	-24.95	129	149	H
2	* 2.375	49.81	Pk		-29	0	52.61	-	-	74	-21.39	129	149	H
3	* 2.39	35.92	RMS		-29	2.24	40.96	54	-13.04	-	-	129	149	H
4	* 2.354	36.93	RMS		-29	2.24	41.87	54	-12.13	-	-	129	149	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

RMS - RMS detection

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 17)_150619	Path_2	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	45.74	Pk	31.8	-29	0	48.54	-	-	74	-25.46	162	136	V
2	* 2.33	49.34	Pk	31.7	-29	0	52.04	-	-	74	-21.96	162	136	V
3	* 2.39	36.02	RMS	31.8	-29	2.24	41.06	54	-12.94	-	-	162	136	V
4	* 2.347	36.86	RMS	31.7	-29	2.24	41.8	54	-12.2	-	-	162	136	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

RMS - RMS detection

AUTHORIZED BANDEDGE (HIGH CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117/001687 171_150619	Path_2	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	47.07	Pk	32	-28.3	0	50.77	-	-	74	-23.23	98	169	H
2	* 2.49	48.68	Pk	32	-28.3	0	52.38	-	-	74	-21.62	98	169	H
3	* 2.484	37.22	RMS	32	-28.3	2.24	43.16	54	-10.84	-	-	98	169	H
4	* 2.484	37.07	RMS	32	-28.3	2.24	43.01	54	-10.99	-	-	98	169	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

RMS - RMS detection

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117/001687 171_150619	Path_2	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	48.33	Pk	32	-28.3	0	52.03	-	-	74	-21.97	163	146	V
2	* 2.484	49.53	Pk	32	-28.3	0	53.23	-	-	74	-20.77	163	146	V
3	* 2.484	37.59	RMS	32	-28.3	2.24	43.53	54	-10.47	-	-	163	146	V
4	* 2.484	37.63	RMS	32	-28.3	2.24	43.57	54	-10.43	-	-	163	146	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector


RMS - RMS detection

HARMONICS AND SPURIOUS EMISSIONS

LOW CHANNEL HORIZONTAL



LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 17)_150619	Path_3	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.804	42.43	PK	34	-33.8	0	42.63	-	-	74	-31.37	0-360	250	H
3	7.205	36.14	PK	35.7	-30.8	0	41.04	-	-	74	-32.96	0-360	250	H
5	9.608	31.55	PK	37	-27.3	0	41.25	-	-	74	-32.75	0-360	250	H
2	* 4.805	44.17	PK	34	-33.8	0	44.37	-	-	74	-29.63	0-360	150	V
4	7.206	33.98	PK	35.7	-30.8	0	38.88	-	-	74	-35.12	0-360	250	V
6	9.604	30.75	PK	37	-27.3	0	40.45	-	-	74	-33.55	0-360	250	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_3	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.804	51.43	PK2	34	-33.8	0	51.63	-	-	74	-22.37	183	113	H
* 4.804	43.78	MAv1	34	-33.8	2.24	46.22	54	-7.78	-	-	183	113	H
7.206	46.08	PK2	35.7	-30.8	0	50.98	-	-	74	-23.02	130	153	H
* 4.804	53.31	PK2	34	-33.8	0	53.51	-	-	74	-20.49	170	105	V
* 4.804	47.51	MAv1	34	-33.8	2.24	49.95	54	-4.05	-	-	170	105	V
7.206	44.98	PK2	35.7	-30.8	0	49.88	-	-	74	-24.12	207	100	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK2 - KDB558074 Method: Maximum Peak

MAv1 - KDB558074 Option 1 Maximum RMS Average

MID CHANNEL HORIZONTAL



MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 17)_150619	Path_3	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.88	43.9	PK	34	-34	0	43.9	-	-	74	-30.1	0-360	150	H
3	* 7.32	41.52	PK	35.8	-30.9	0	46.42	-	-	74	-27.58	0-360	250	H
5	9.764	31.23	PK	37.2	-26.6	0	41.83	-	-	74	-32.17	0-360	150	H
2	* 4.88	46.61	PK	34	-34	0	46.61	-	-	74	-27.39	0-360	150	V
4	* 7.319	35.47	PK	35.8	-30.9	0	40.37	-	-	74	-33.63	0-360	150	V
6	9.764	31.71	PK	37.2	-26.6	0	42.31	-	-	74	-31.69	0-360	150	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak detector

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_3	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.88	52.52	PK-U	34	-34	0	52.52	-	-	74	-21.48	188	158	H
* 4.88	45.49	MAV1	34	-34	2.24	47.73	54	-6.27	-	-	188	158	H
* 7.319	48.7	PK-U	35.8	-30.9	0	53.6	-	-	74	-20.4	128	141	H
* 7.319	40.8	MAV1	35.8	-30.9	2.24	47.94	54	-6.06	-	-	128	141	H
* 4.879	53.34	PK-U	34	-34	0	53.34	-	-	74	-20.66	83	170	V
* 4.88	47.9	MAV1	34	-34	2.24	50.14	54	-3.86	-	-	83	170	V
* 7.319	46.53	PK-U	35.8	-30.9	0	51.43	-	-	74	-22.57	109	227	V
* 7.319	36.78	MAV1	35.8	-30.9	2.24	43.92	54	-10.08	-	-	109	227	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK2 - KDB558074 Method: Maximum Peak

MAV1 - KDB558074 Option 1 Maximum RMS Average

HIGH CHANNEL HORIZONTAL



HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 17)_150619	Path_3	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.959	47.48	PK	34	-34	0	47.48	-	-	74	-26.52	0-360	150	H
3	* 7.44	42.79	PK	35.8	-30.7	0	47.89	-	-	74	-26.11	0-360	250	H
5	9.92	30.23	PK	37.4	-27.2	0	40.43	-	-	74	-33.57	0-360	150	H
2	* 4.959	47.47	PK	34	-34	0	47.47	-	-	74	-26.53	0-360	150	V
4	* 7.441	37.14	PK	35.8	-30.7	0	42.24	-	-	74	-31.76	0-360	150	V
6	9.918	30.71	PK	37.4	-27.3	0	40.81	-	-	74	-33.19	0-360	150	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak detector

Radiated Emissions

Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016 8717)_150 619	Path_3	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.959	53.77	PK-U	34	-34	0	53.77	-	-	74	-20.23	175	159	H
* 4.96	46.94	MAV1	34	-34	2.24	49.18	54	-4.82	-	-	175	159	H
* 7.439	49.93	PK-U	35.8	-30.7	0	55.03	-	-	74	-18.97	128	232	H
* 7.44	41.67	MAV1	35.8	-30.7	2.24	49.01	54	-4.99	-	-	128	232	H
* 4.96	53	PK-U	34	-34	0	53	-	-	74	-21	80	174	V
* 4.96	47.49	MAV1	34	-34	2.24	49.73	54	-4.27	-	-	80	174	V
* 7.439	47.36	PK-U	35.8	-30.7	0	52.46	-	-	74	-21.54	60	167	V
* 7.439	38.41	MAV1	35.8	-30.7	2.24	45.75	54	-8.25	-	-	60	167	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


PK2 - KDB558074 Method: Maximum Peak

MAV1 - KDB558074 Option 1 Maximum RMS Average


11.3. WORST-CASE BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION)

HORIZONTAL PLOT



VERTICAL PLOT



BELOW 1 GHz TABLE

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	VULB9163-750	Bi-Log	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	44.5775	39.64	Pk	13.5	-30.2	22.94	40	-17.06	0-360	400	H
2	65.2325	42.92	Pk	11.1	-29.9	24.12	40	-15.88	0-360	200	H
4	44.2375	48.36	Pk	13.4	-30.2	31.56	40	-8.44	0-360	100	V
5	* 164.385	48.65	Pk	8.7	-28.5	28.85	43.52	-14.67	0-360	200	V
6	179.26	48.33	Pk	9.4	-28.3	29.43	43.52	-14.09	0-360	200	V
3	205.1	46.75	Pk	11.4	-28.1	30.05	43.52	-13.47	0-360	100	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

12. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.10.


The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS

6 WORST EMISSIONS

LINE 1 PLOT



LINE 1 RESULTS

Trace Markers

Phase L1 .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101837_w ith ex- cord_L1	CE Shield Room	Corrected Reading (dB(uVolts)	CISPR 22 Class B ITE QP	Margin (dB)	CISPR 22 Class B ITE AV	Margin (dB)
1	.366	41.42	Pk	9.9	0	51.32	58.59	-7.27	-	-
2	.375	29.51	Av	9.9	0	39.41	-	-	48.39	-8.98
3	.735	37.4	Pk	9.9	0	47.3	56	-8.7	-	-
4	.735	24.7	Av	9.9	0	34.6	-	-	46	-11.4
5	1.329	34.96	Pk	9.8	.1	44.86	56	-11.14	-	-
6	1.329	21.26	Av	9.8	.1	31.16	-	-	46	-14.84
7	1.473	33.42	Pk	9.8	.1	43.32	56	-12.68	-	-
8	1.482	13.48	Av	9.8	.1	23.38	-	-	46	-22.62
9	1.608	38.05	Pk	9.7	.1	47.85	56	-8.15	-	-
10	1.608	19.84	Av	9.7	.1	29.64	-	-	46	-16.36
11	1.752	36.8	Pk	9.7	.1	46.6	56	-9.4	-	-
12	1.752	17.12	Av	9.7	.1	26.92	-	-	46	-19.08

Pk - Peak detector

Av - Average detection


Quasi-Peak Emissions

Phase L1 .15 - 30MHz

Frequency (MHz)	Meter Reading (dBuV)	Det	101837_wit h ex-cord_L1	CE Shield Room	Corrected Reading (dB(uVolts))	CISPR 22 Class B ITE QP	Margin (dB)	CISPR 22 Class B ITE AV	Margin (dB)
.3669	38.65	Qp	9.9	0	48.55	58.57	-10.02	-	-
.7386	32.76	Qp	9.9	0	42.66	56	-13.34	-	-
1.6044	32.76	Qp	9.7	.1	42.56	56	-13.44	-	-
1.7484	31.15	Qp	9.7	.1	40.95	56	-15.05	-	-

Qp - Quasi-Peak detector

LINE 2 PLOT



LINE 2 RESULTS

Trace Markers

Phase N .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101837_w ith ex- cord_N	CE Shield Room	Corrected Reading (dB(uVolts)	CISPR 22 Class B ITE QP	Margin (dB)	CISPR 22 Class B ITE AV	Margin (dB)
13	.339	39.01	Pk	9.8	0	48.81	59.23	-10.42	-	-
14	.375	26.57	Av	9.9	0	36.47	-	-	48.39	-11.92
15	.735	37.47	Pk	9.9	0	47.37	56	-8.63	-	-
16	.735	24.71	Av	9.9	0	34.61	-	-	46	-11.39
17	1.338	34.24	Pk	9.8	.1	44.14	56	-11.86	-	-
18	1.329	21.53	Av	9.8	.1	31.43	-	-	46	-14.57
19	1.482	34.22	Pk	9.8	.1	44.12	56	-11.88	-	-
20	1.482	13.39	Av	9.8	.1	23.29	-	-	46	-22.71
21	1.608	36.73	Pk	9.7	.1	46.53	56	-9.47	-	-
22	1.626	19.97	Av	9.7	.1	29.77	-	-	46	-16.23
23	1.761	35.68	Pk	9.7	.1	45.48	56	-10.52	-	-
24	1.752	16.72	Av	9.7	.1	26.52	-	-	46	-19.48

Pk - Peak detector

Av - Average detection

Quasi-Peak Emissions

Phase N .15 - 30MHz

Frequency (MHz)	Meter Reading (dBuV)	Det	101837_wit h ex-cord_N	CE Shield Room	Corrected Reading (dB(uVolts))	CISPR 22 Class B ITE QP	Margin (dB)	CISPR 22 Class B ITE AV	Margin (dB)
.7305	32.62	Qp	9.9	0	42.52	56	-13.48	-	-
1.6044	31.69	Qp	9.7	.1	41.49	56	-14.51	-	-

Qp - Quasi-Peak detector