



FCC Part 15C Test Report

FCC ID:2AJKQSY-5D

Product Name:	5D four wheel alignment
Trademark:	SUCVARY
Model Name :	SY-5D
Prepared For : Address :	Shenzhen Fiengle Tech Co.,Ltd 21F A Building, No, 5 Exchange Square South China city Long Gang District, Shenzhen, P.R.C
Prepared By : Address :	Shenzhen BCTC Technology Co., Ltd. No.101,Yousong Road,Longhua New District, Shenzhen,China
Test Date:	Aug. 15 – Aug. 22, 2016
Date of Report :	Aug. 22, 2016
Report No.:	BCTC-160506602E



TEST RESULT CERTIFICATION

Applicant's name..... : Shenzhen Fiengle Tech Co.,Ltd
Address..... : 21F A Building, No, 5 Exchange Square South China city Long
Gang District, Shenzhen, P.R.C
Manufacture's Name..... : Shenzhen Fiengle Tech Co.,Ltd
Address..... : 21F A Building, No, 5 Exchange Square South China city Long
Gang District, Shenzhen, P.R.C
Product description
Product name..... : 5D four wheel alignment
Model and/or type reference : SY-5D
Standards..... : FCC Part15.247
ANSI C63.10:2013
KDB 558074 D01 DTS Meas Guidance v03r03

This device described above has been tested by BCTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of BCTC, this document may be altered or revised by BCTC, personal only, and shall be noted in the revision of the document.

Testing Engineer : _____

Eric Yang

Eric Yang

Reviewer
(Supervisor) : _____

Jade Yang

Jade Yang

Approved &
Authorized
Signer(Manager) : _____



Carson Zhang

**Table of Contents**

	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	8
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	10
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	11
3 . EMC EMISSION TEST	12
3.1 CONDUCTED EMISSION MEASUREMENT	12
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	12
3.1.2 TEST PROCEDURE	12
3.1.3 DEVIATION FROM TEST STANDARD	12
3.1.4 TEST SETUP	13
3.1.5 EUT OPERATING CONDITIONS	13
3.1.6 TEST RESULTS	14
3.2 RADIATED EMISSION MEASUREMENT	16
3.2.1 RADIATED EMISSION LIMITS	16
3.2.2 TEST PROCEDURE	17
3.2.3 DEVIATION FROM TEST STANDARD	17
3.2.4 TEST SETUP	17
3.2.5 EUT OPERATING CONDITIONS	18
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	19
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	20
3.2.8 TEST RESULTS (1GHZ~25GHZ)	22
3.3 RADIATED BAND EMISSION MEASUREMENT	30
3.3.1 TEST REQUIREMENT:	30
3.3.2 TEST PROCEDURE	30
3.3.3 DEVIATION FROM TEST STANDARD	31
3.3.4 TEST SETUP	31
3.3.5 EUT OPERATING CONDITIONS	31
4 . POWER SPECTRAL DENSITY TEST	40



Table of Contents	Page
4.1 APPLIED PROCEDURES / LIMIT	40
4.1.1 TEST PROCEDURE	40
4.1.2 DEVIATION FROM STANDARD	40
4.1.3 TEST SETUP	40
4.1.4 EUT OPERATION CONDITIONS	40
4.1.5 TEST RESULTS	41
5 . BANDWIDTH TEST	65
5.1 APPLIED PROCEDURES / LIMIT	65
5.1.1 TEST PROCEDURE	65
5.1.2 DEVIATION FROM STANDARD	65
5.1.3 TEST SETUP	65
5.1.4 EUT OPERATION CONDITIONS	65
5.1.5 TEST RESULTS	66
6 . PEAK OUTPUT POWER TEST	90
6.1 APPLIED PROCEDURES / LIMIT	90
6.1.1 TEST PROCEDURE	90
6.1.2 DEVIATION FROM STANDARD	90
6.1.3 TEST SETUP	90
6.1.4 EUT OPERATION CONDITIONS	90
6.1.5 TEST RESULTS	91
7 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	93
7.1 APPLICABLE STANDARD	93
7.2 TEST PROCEDURE	93
7.3 DEVIATION FROM STANDARD	93
7.4 TEST SETUP	93
7.5 EUT OPERATION CONDITIONS	94
7.1 TEST RESULTS	94
8 . ANTENNA REQUIREMENT	107
8.1 STANDARD REQUIREMENT	107
8.2 EUT ANTENNA	107
9 . EUT TEST PHOTO	108
10 . EUT PHOTO	110
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Peak Output Power	PASS	
15.247 (c)	Radiated Spurious Emission	PASS	
15.247 (d)	Power Spectral Density	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report



1.1 TEST FACILITY

Shenzhen BCTC Technology Co., Ltd.

Add. : No.101,Yousong Road,Longhua New District, Shenzhen,China

FCC Registered No.: 187086

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	5D four wheel alignment	
Trade Name	SUCVARY	
Model Name	SY-5D	
Serial Model	N/A	
Model Difference	N/A	
Product Description	The EUT is a 5D four wheel alignment	
	Operation Frequency:	802.11b/g/n20MHz:2412~2462 MHz 802.11n40MHz:2422~2452 MHz
	Modulation Type:	WIFI: OFDM/DSSS
	Bit Rate of Transmitter	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6Mbps 802.11n Up to 150Mbps
	Number Of Channel	802.11b/g/n20MHz:11 CH 802.11n40MHz: 7 CH
	Antenna Designation:	Please see Note 3.
Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.		
Channel List	Please refer to the Note 2.	
Power	AC120-240V 50/60Hz	
hardware version	--	
Software version	--	
Serial number	--	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2.

Channel List for 802.11b/g/n(20)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

Channel List for 802.11n(40)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
03	2422	05	2432	07	2442	09	2452
04	2427	06	2437	08	2447		

3.

Table for Filed Antenna

Module 1

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	PCB Antenna	N/A	1.0	

Module 2

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	PCB Antenna	N/A	1.0	
2	N/A	N/A	PCB Antenna	N/A	1.0	

Note1: Directional Gain=1.0dBi+10log(1)=1.0dBi

Note2: The EUT incorporates a mimo funtion. Physically, the EUT provide two completed transmitter and two receivers.

2.2 DESCRIPTION OF TEST MODES

Pretest Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n20 CH1/ CH6/ CH11
Mode 4	802.11n40 CH3/ CH6/ CH9
Mode 5	Link Mode

Conducted Emission	
Final Test Mode	Description
Mode 5	Link Mode



For Radiated Emission	
Final Test Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n20 CH1/ CH6/ CH11
Mode 4	802.11n40 CH3/ CH6/ CH9


Note:

(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.



2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission/Radiated Spurious Emission Test



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	5D four wheel alignment	SUCVARY	SY-5D	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	1.5M	AC cable unshielded

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer	Agilent	E4407B	MY45109572	2015.08.25	2016.08.24
2	Test Receiver	R&S	ESPI	101396	2015.08.25	2016.08.24
3	Bilog Antenna	SCHWARZBECK	VULB9160	VULB9160-3369	2015.08.25	2016.08.24
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2016.07.06	2017.07.05
5	Spectrum Analyzer	Agilent	N9020A	MY5051041	2016.07.06	2017.07.05
6	Horn Antenna	SCHWARZBECK	9120D	9120D-1275	2015.08.25	2016.08.24
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2016.07.06	2017.07.05
8	Amplifier	SCHWARZBECK	BBV9718	9718-270	2015.08.25	2016.08.24
9	Amplifier	SCHWARZBECK	BBV9743	9743-119	2015.08.25	2016.08.24
10	Loop Antenna	ARA	PLSY-5D30/B	1029	2016.07.06	2017.07.05
11	Power Meter	R&S	NRVS	100696	2016.07.06	2017.07.05
12	Power Sensor	R&S	NRV-Z55	161905	2016.07.06	2017.07.05
13	RF cables	R&S	N/A	N/A	2016.07.06	2017.07.05

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Test Receiver	R&S	ESCI	1166.5950K03-101165-ha	2016.06.06	2017.06.05
2	LISN	R&S	NSLK8126	8126466	2015.08.24	2016.08.23
3	LISN	R&S	NSLK8126	8126487	2015.08.24	2016.08.23
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2016.06.07	2017.06.06
5	RF cables	R&S	R204	R20X	2016.07.06	2017.07.05



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 240V, the worst voltage was AC 120V and the data recording in the report.



3.1.6 TEST RESULTS

Temperature :	26°C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	L
Test Voltage :	AC120V 60Hz	Test Mode :	Mode 5




Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1980	39.45	10.06	49.51	63.69	-14.18	QP	
2	*	0.1980	36.19	10.06	46.25	53.69	-7.44	AVG	
3		0.2620	32.34	10.08	42.42	61.36	-18.94	QP	
4		0.2620	27.33	10.08	37.41	51.36	-13.95	AVG	
5		0.3860	30.01	10.10	40.11	58.15	-18.04	QP	
6		0.3860	26.91	10.10	37.01	48.15	-11.14	AVG	
7		1.1580	30.67	10.17	40.84	56.00	-15.16	QP	
8		1.1580	25.29	10.17	35.46	46.00	-10.54	AVG	
9		1.9260	28.54	10.18	38.72	56.00	-17.28	QP	
10		1.9260	22.84	10.18	33.02	46.00	-12.98	AVG	
11		6.9380	34.32	10.10	44.42	60.00	-15.58	QP	
12		6.9380	28.64	10.10	38.74	50.00	-11.26	AVG	



Temperature :	26°C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	AC120V 60Hz	Test Mode :	Mode 5



Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1980	39.15	10.06	49.21	63.69	-14.48	QP	
2 *	0.1980	36.36	10.06	46.42	53.69	-7.27	AVG	
3	0.2620	31.72	10.08	41.80	61.36	-19.56	QP	
4	0.2620	26.89	10.08	36.97	51.36	-14.39	AVG	
5	0.3860	29.99	10.10	40.09	58.15	-18.06	QP	
6	0.3860	26.86	10.10	36.96	48.15	-11.19	AVG	
7	1.1580	29.82	10.17	39.99	56.00	-16.01	QP	
8	1.1580	22.93	10.17	33.10	46.00	-12.90	AVG	
9	1.9300	28.22	10.18	38.40	56.00	-17.60	QP	
10	1.9300	22.29	10.18	32.47	46.00	-13.53	AVG	
11	5.4020	30.27	10.13	40.40	60.00	-19.60	QP	
12	5.4020	23.32	10.13	33.45	50.00	-16.55	AVG	



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	25GHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
- Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)**

Temperature:	20℃	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	AC120V 60Hz
Test Mode :	Mode 5	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.

**3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)**

Temperature :	26℃	Relative Humidity :	54%
Pressure :	1010 hPa	Polarization :	Horizontal
Test Voltage :	AC120V 60Hz		
Test Mode :	Mode 5		




Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1	!	150.0107	50.48	-12.86	37.62	43.50	-5.88	QP
2	*	210.0482	57.18	-15.91	41.27	43.50	-2.23	QP
3	!	330.1949	54.34	-11.81	42.53	46.00	-3.47	QP
4	!	510.0436	50.92	-8.02	42.90	46.00	-3.10	QP
5	!	631.6884	48.60	-5.41	43.19	46.00	-2.81	QP
6	!	932.2713	43.87	-0.85	43.02	46.00	-2.98	QP



Temperature :	26℃	Relative Humidity :	54%
Pressure :	1010 hPa	Polarization :	Vertical
Test Voltage :	AC120V 60Hz		
Test Mode :	Mode 5		



Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1	!	89.9047	56.75	-17.51	39.24	43.50	-4.26	QP
2	!	270.3747	56.09	-13.50	42.59	46.00	-3.41	QP
3	*	330.1949	55.19	-11.81	43.38	46.00	-2.62	QP
4	!	570.6100	49.69	-6.54	43.15	46.00	-2.85	QP
5	!	691.9867	47.73	-4.52	43.21	46.00	-2.79	QP
6	!	752.7432	46.41	-3.03	43.38	46.00	-2.62	QP



3.2.8 TEST RESULTS (1GHZ~25GHZ)

Module1

802.11b									
Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		operation frequency:2412							
V	4824.00	67.47	39.55	7.85	25.66	61.43	74	-12.57	PK
V	4824.00	48.62	39.55	7.85	25.66	42.58	54	-11.42	AV
V	7236.00	66.87	38.33	7.52	24.55	60.61	74	-13.39	PK
V	7236.00	48.78	38.33	7.52	24.55	42.52	54	-11.48	AV
V	15450.00	51.44	35.23	6.75	26.59	49.55	74	-24.45	PK
H	4824.00	68.36	39.55	7.85	25.66	62.32	74	-11.68	PK
H	4824.00	49.76	39.55	7.85	25.66	43.72	54	-10.28	AV
H	7236.00	69.31	38.33	7.52	23.55	62.05	74	-11.95	PK
H	7236.00	52.05	38.33	7.52	23.22	44.46	54	-9.54	AV
H	15450.00	47.52	35.45	6.75	27.88	46.70	74	-27.30	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		operation frequency:2437							
V	4874.00	66.49	38.89	7.57	25.45	60.62	74	-13.38	PK
V	4874.00	49.61	38.89	7.57	25.45	43.74	54	-10.26	AV
V	7311.00	67.39	38.78	7.35	24.78	60.74	74	-13.26	PK
V	7311.00	47.27	38.78	7.35	24.78	40.62	54	-13.38	AV
V	15450.00	52.35	35.89	6.42	26.47	49.35	74	-24.65	PK
H	4874.00	65.75	38.89	7.57	25.45	59.88	74	-14.12	PK
H	4874.00	49.28	38.89	7.57	25.45	43.41	54	-10.59	AV
H	7311.00	69.64	38.78	7.35	24.78	62.99	74	-11.01	PK
H	7311.00	48.43	38.78	7.35	24.78	41.78	54	-12.22	AV
H	15450.00	49.65	36.68	6.42	26.65	46.04	74	-27.96	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		operation frequency:2462							
V	4924.00	68.65	38.75	7.46	25.45	62.81	74	-11.19	PK
V	4924.00	50.54	38.75	7.46	25.45	44.70	54	-9.30	AV
V	7386.00	67.62	38.65	7.22	24.78	60.97	74	-13.03	PK
V	7386.00	49.54	38.65	7.22	24.78	42.89	54	-11.11	AV
V	15450.00	53.63	35.58	6.35	26.47	50.87	74	-23.13	PK
H	4924.00	66.42	38.75	7.46	25.45	60.58	74	-13.42	PK
H	4924.00	50.54	38.75	7.46	25.45	44.70	54	-9.30	AV
H	7386.00	69.83	38.65	7.22	24.78	63.18	74	-10.82	PK
H	7386.00	48.67	38.65	7.22	24.78	42.02	54	-11.98	AV
H	15450.00	50.12	36.42	6.32	26.65	46.67	74	-27.33	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11g									
Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2412									
V	4824.00	66.67	39.55	7.85	25.66	60.63	74	-13.37	PK
V	4824.00	49.87	39.55	7.85	25.66	43.83	54	-10.17	AV
V	7236.00	66.25	38.33	7.52	24.55	59.99	74	-14.01	PK
V	7236.00	47.79	38.33	7.52	24.55	41.53	54	-12.47	AV
V	15450.00	50.68	35.23	6.75	26.59	48.79	74	-25.21	PK
H	4824.00	63.74	39.55	7.85	25.66	57.70	74	-16.30	PK
H	4824.00	49.66	39.55	7.85	25.66	43.62	54	-10.38	AV
H	7236.00	69.52	38.33	7.52	23.55	62.26	74	-11.74	PK
H	7236.00	50.64	38.33	7.52	23.22	43.05	54	-10.95	AV
H	15450.00	45.92	35.45	6.75	27.88	45.10	74	-28.90	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2437									
V	4874.00	65.78	38.89	7.57	25.45	59.91	74	-14.09	PK
V	4874.00	48.96	38.89	7.57	25.45	43.09	54	-10.91	AV
V	7311.00	66.45	38.78	7.35	24.78	59.80	74	-14.20	PK
V	7311.00	48.78	38.78	7.35	24.78	42.13	54	-11.87	AV
V	15450.00	52.59	35.89	6.42	26.47	49.59	74	-24.41	PK
H	4874.00	64.23	38.89	7.57	25.45	58.36	74	-15.64	PK
H	4874.00	49.75	38.89	7.57	25.45	43.88	54	-10.12	AV
H	7311.00	70.89	38.78	7.35	24.78	64.24	74	-9.76	PK
H	7311.00	48.78	38.78	7.35	24.78	42.13	54	-11.87	AV
H	15450.00	48.75	36.68	6.45	26.65	45.17	74	-28.83	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2462									
V	4924.00	67.85	38.75	7.46	25.45	62.01	74	-11.99	PK
V	4924.00	48.34	38.75	7.46	25.45	42.50	54	-11.50	AV
V	7386.00	68.75	38.65	7.22	24.78	62.10	74	-11.90	PK
V	7386.00	49.35	38.65	7.22	24.78	42.70	54	-11.30	AV
V	15450.00	53.76	35.58	6.35	26.47	51.00	74	-23.00	PK
H	4924.00	66.45	38.75	7.46	25.45	60.61	74	-13.39	PK
H	4924.00	50.12	38.75	7.46	25.45	44.28	54	-9.72	AV
H	7386.00	69.29	38.65	7.22	24.78	62.64	74	-11.36	PK
H	7386.00	48.75	38.65	7.22	24.78	42.10	54	-11.90	AV
H	15450.00	49.25	36.42	6.32	26.65	45.80	74	-28.20	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n(20MHz)

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		operation frequency:2412							
V	4824.00	67.76	39.55	7.85	25.66	61.72	74	-12.28	PK
V	4824.00	48.58	39.55	7.85	25.66	42.54	54	-11.46	AV
V	7236.00	66.65	38.33	7.52	24.55	60.39	74	-13.61	PK
V	7236.00	48.47	38.33	7.52	24.55	42.21	54	-11.79	AV
V	15450.00	51.46	35.23	6.75	26.59	49.57	74	-24.43	PK
H	4824.00	68.72	39.55	7.85	25.66	62.68	74	-11.32	PK
H	4824.00	49.39	39.55	7.85	25.66	43.35	54	-10.65	AV
H	7236.00	69.58	38.33	7.52	23.55	62.32	74	-11.68	PK
H	7236.00	52.66	38.33	7.52	23.22	45.07	54	-8.93	AV
H	15450.00	47.78	35.45	6.75	27.88	46.96	74	-27.04	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		operation frequency:2437							
V	4874.00	66.55	38.89	7.57	25.45	60.68	74	-13.32	PK
V	4874.00	49.69	38.89	7.57	25.45	43.82	54	-10.18	AV
V	7311.00	67.47	38.78	7.35	24.78	60.82	74	-13.18	PK
V	7311.00	47.58	38.78	7.35	24.78	40.93	54	-13.07	AV
V	15450.00	52.23	35.89	6.42	26.47	49.23	74	-24.77	PK
H	4874.00	65.58	38.89	7.57	25.45	59.71	74	-14.29	PK
H	4874.00	49.79	38.89	7.57	25.45	43.92	54	-10.08	AV
H	7311.00	69.58	38.78	7.35	24.78	62.93	74	-11.07	PK
H	7311.00	48.72	38.78	7.35	24.78	42.07	54	-11.93	AV
H	15450.00	49.44	36.68	6.42	26.65	45.83	74	-28.17	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		operation frequency:2462							
V	4924.00	68.64	38.75	7.46	25.45	62.80	74	-11.20	PK
V	4924.00	50.72	38.75	7.46	25.45	44.88	54	-9.12	AV
V	7386.00	67.65	38.65	7.22	24.78	61.00	74	-13.00	PK
V	7386.00	49.52	38.65	7.22	24.78	42.87	54	-11.13	AV
V	15450.00	53.29	35.58	6.35	26.47	50.53	74	-23.47	PK
H	4924.00	66.36	38.75	7.46	25.45	60.52	74	-13.48	PK
H	4924.00	50.58	38.75	7.46	25.45	44.74	54	-9.26	AV
H	7386.00	69.79	38.65	7.22	24.78	63.14	74	-10.86	PK
H	7386.00	48.67	38.65	7.22	24.78	42.02	54	-11.98	AV
H	15450.00	50.56	36.42	6.32	26.65	47.11	74	-26.89	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n(40MHz)

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		operation frequency:2422							
V	4844.000	68.59	39.55	7.77	25.66	62.47	74	-11.53	PK
V	4844.000	48.68	39.55	7.77	25.66	42.56	54	-11.44	AV
V	7266.000	67.56	38.33	7.30	24.55	61.08	74	-12.92	PK
V	7266.000	48.39	38.33	7.30	24.55	41.91	54	-12.09	AV
V	15450.00	51.74	35.23	6.60	26.59	49.70	74	-24.30	PK
H	4844.000	68.69	39.55	7.77	25.66	62.57	74	-11.43	PK
H	4844.000	49.45	39.55	7.77	25.66	43.33	54	-10.67	AV
H	7266.000	69.58	38.33	7.30	23.55	62.10	74	-11.90	PK
H	7266.000	52.66	38.33	7.30	23.22	44.85	54	-9.15	AV
H	15450.00	48.37	35.45	6.60	27.88	47.40	74	-26.60	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		operation frequency:2437							
V	4874.00	66.48	38.89	7.57	25.45	60.61	74	-13.39	PK
V	4874.00	49.57	38.89	7.57	25.45	43.70	54	-10.30	AV
V	7311.00	67.65	38.78	7.35	24.78	61.00	74	-13.00	PK
V	7311.00	47.82	38.78	7.35	24.78	41.17	54	-12.83	AV
V	15450.00	52.32	35.89	6.42	26.47	49.32	74	-24.68	PK
H	4874.00	65.87	38.89	7.57	25.45	60.00	74	-14.00	PK
H	4874.00	49.95	38.89	7.57	25.45	44.08	54	-9.92	AV
H	7311.00	69.84	38.78	7.35	24.78	63.19	74	-10.81	PK
H	7311.00	48.27	38.78	7.35	24.78	41.62	54	-12.38	AV
H	15450.00	49.63	36.68	6.42	26.65	46.02	74	-27.98	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		operation frequency:2452							
V	4904.00	68.47	38.75	7.38	25.45	62.55	74	-11.45	PK
V	4904.00	50.35	38.75	7.38	25.45	44.43	54	-9.57	AV
V	7356.00	67.64	38.65	7.15	24.78	60.92	74	-13.08	PK
V	7356.00	49.95	38.65	7.15	24.78	43.23	54	-10.77	AV
V	15450.00	53.45	35.58	6.25	26.47	50.59	74	-23.41	PK
H	4904.00	66.72	38.75	7.38	25.45	60.80	74	-13.20	PK
H	4904.00	50.94	38.75	7.38	25.45	45.02	54	-8.98	AV
H	7356.00	69.76	38.65	7.15	24.78	63.04	74	-10.96	PK
H	7356.00	48.57	38.65	7.15	24.78	41.85	54	-12.15	AV
H	15450.00	50.37	36.42	6.25	26.65	46.85	74	-27.15	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



Module2

802.11b									
Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		operation frequency:2412							
V	4824.00	66.45	39.55	7.85	25.66	60.41	74	-13.59	PK
V	4824.00	49.74	39.55	7.85	25.66	43.70	54	-10.30	AV
V	7236.00	66.52	38.33	7.52	24.55	60.26	74	-13.74	PK
V	7236.00	47.62	38.33	7.52	24.55	41.36	54	-12.64	AV
V	15450.00	50.37	35.23	6.75	26.59	48.48	74	-25.52	PK
H	4824.00	63.15	39.55	7.85	25.66	57.11	74	-16.89	PK
H	4824.00	49.38	39.55	7.85	25.66	43.34	54	-10.66	AV
H	7236.00	69.24	38.33	7.52	23.55	61.98	74	-12.02	PK
H	7236.00	50.18	38.33	7.52	23.22	42.59	54	-11.41	AV
H	15450.00	45.96	35.45	6.75	27.88	45.14	74	-28.86	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		operation frequency:2437							
V	4874.00	65.56	38.89	7.57	25.45	59.69	74	-14.31	PK
V	4874.00	48.65	38.89	7.57	25.45	42.78	54	-11.22	AV
V	7311.00	66.68	38.78	7.35	24.78	60.03	74	-13.97	PK
V	7311.00	48.25	38.78	7.35	24.78	41.60	54	-12.40	AV
V	15450.00	52.36	35.89	6.42	26.47	49.36	74	-24.64	PK
H	4874.00	64.89	38.89	7.57	25.45	59.02	74	-14.98	PK
H	4874.00	49.55	38.89	7.57	25.45	43.68	54	-10.32	AV
H	7311.00	70.35	38.78	7.35	24.78	63.70	74	-10.30	PK
H	7311.00	48.81	38.78	7.35	24.78	42.16	54	-11.84	AV
H	15450.00	48.69	36.68	6.45	26.65	45.11	74	-28.89	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		operation frequency:2462							
V	4924.00	67.28	38.75	7.46	25.45	61.44	74	-12.56	PK
V	4924.00	48.33	38.75	7.46	25.45	42.49	54	-11.51	AV
V	7386.00	68.84	38.65	7.22	24.78	62.19	74	-11.81	PK
V	7386.00	49.56	38.65	7.22	24.78	42.91	54	-11.09	AV
V	15450.00	53.65	35.58	6.35	26.47	50.89	74	-23.11	PK
H	4924.00	66.97	38.75	7.46	25.45	61.13	74	-12.87	PK
H	4924.00	50.95	38.75	7.46	25.45	45.11	54	-8.89	AV
H	7386.00	69.53	38.65	7.22	24.78	62.88	74	-11.12	PK
H	7386.00	48.67	38.65	7.22	24.78	42.02	54	-11.98	AV
H	15450.00	49.82	36.42	6.32	26.65	46.37	74	-27.63	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11g									
Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2412									
V	4824.00	66.23	39.55	7.85	25.66	60.19	74	-13.81	PK
V	4824.00	49.58	39.55	7.85	25.66	43.54	54	-10.46	AV
V	7236.00	66.39	38.33	7.52	24.55	60.13	74	-13.87	PK
V	7236.00	47.67	38.33	7.52	24.55	41.41	54	-12.59	AV
V	15450.00	50.95	35.23	6.75	26.59	49.06	74	-24.94	PK
H	4824.00	63.25	39.55	7.85	25.66	57.21	74	-16.79	PK
H	4824.00	49.49	39.55	7.85	25.66	43.45	54	-10.55	AV
H	7236.00	69.35	38.33	7.52	23.55	62.09	74	-11.91	PK
H	7236.00	50.47	38.33	7.52	23.22	42.88	54	-11.12	AV
H	15450.00	45.78	35.45	6.75	27.88	44.96	74	-29.04	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2437									
V	4874.00	65.96	38.89	7.57	25.45	60.09	74	-13.91	PK
V	4874.00	48.58	38.89	7.57	25.45	42.71	54	-11.29	AV
V	7311.00	66.57	38.78	7.35	24.78	59.92	74	-14.08	PK
V	7311.00	48.87	38.78	7.35	24.78	42.22	54	-11.78	AV
V	15450.00	52.68	35.89	6.42	26.47	49.68	74	-24.32	PK
H	4874.00	64.35	38.89	7.57	25.45	58.48	74	-15.52	PK
H	4874.00	49.57	38.89	7.57	25.45	43.70	54	-10.30	AV
H	7311.00	70.68	38.78	7.35	24.78	64.03	74	-9.97	PK
H	7311.00	48.55	38.78	7.35	24.78	41.90	54	-12.10	AV
H	15450.00	48.45	36.68	6.42	26.65	44.84	74	-29.16	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2462									
V	4924.00	67.43	38.75	7.46	25.45	61.59	74	-12.41	PK
V	4924.00	48.74	38.75	7.46	25.45	42.90	54	-11.10	AV
V	7386.00	68.22	38.65	7.22	24.78	61.57	74	-12.43	PK
V	7386.00	49.78	38.65	7.22	24.78	43.13	54	-10.87	AV
V	15450.00	53.75	35.58	6.35	26.47	50.99	74	-23.01	PK
H	4924.00	66.68	38.75	7.46	25.45	60.84	74	-13.16	PK
H	4924.00	50.24	38.75	7.46	25.45	44.40	54	-9.60	AV
H	7386.00	69.73	38.65	7.22	24.78	63.08	74	-10.92	PK
H	7386.00	48.47	38.65	7.22	24.78	41.82	54	-12.18	AV
H	15450.00	49.66	36.42	6.32	26.65	46.21	74	-27.79	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n(20MHz)

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		operation frequency:2412							
V	4824.00	67.25	39.55	7.85	25.66	61.21	74	-12.79	PK
V	4824.00	48.63	39.55	7.85	25.66	42.59	54	-11.41	AV
V	7236.00	66.47	38.33	7.52	24.55	60.21	74	-13.79	PK
V	7236.00	48.62	38.33	7.52	24.55	42.36	54	-11.64	AV
V	15450.00	51.49	35.23	6.75	26.59	49.60	74	-24.40	PK
H	4824.00	68.53	39.55	7.85	25.66	62.49	74	-11.51	PK
H	4824.00	49.34	39.55	7.85	25.66	43.30	54	-10.70	AV
H	7236.00	69.42	38.33	7.52	23.55	62.16	74	-11.84	PK
H	7236.00	52.25	38.33	7.52	23.22	44.66	54	-9.34	AV
H	15450.00	47.18	35.45	6.75	27.88	46.36	74	-27.64	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		operation frequency:2437							
V	4874.00	66.49	38.89	7.57	25.45	60.62	74	-13.38	PK
V	4874.00	49.72	38.89	7.57	25.45	43.85	54	-10.15	AV
V	7311.00	67.19	38.78	7.35	24.78	60.54	74	-13.46	PK
V	7311.00	47.27	38.78	7.35	24.78	40.62	54	-13.38	AV
V	15450.00	52.38	35.89	6.42	26.47	49.38	74	-24.62	PK
H	4874.00	65.26	38.89	7.57	25.45	59.39	74	-14.61	PK
H	4874.00	49.17	38.89	7.57	25.45	43.30	54	-10.70	AV
H	7311.00	69.22	38.78	7.35	24.78	62.57	74	-11.43	PK
H	7311.00	48.45	38.78	7.35	24.78	41.80	54	-12.20	AV
H	15450.00	49.56	36.68	6.42	26.65	45.95	74	-28.05	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		operation frequency:2462							
V	4924.00	68.62	38.75	7.46	25.45	62.78	74	-11.22	PK
V	4924.00	50.74	38.75	7.46	25.45	44.90	54	-9.10	AV
V	7386.00	67.53	38.65	7.22	24.78	60.88	74	-13.12	PK
V	7386.00	49.15	38.65	7.22	24.78	42.50	54	-11.50	AV
V	15450.00	53.22	35.58	6.35	26.47	50.46	74	-23.54	PK
H	4924.00	66.46	38.75	7.46	25.45	60.62	74	-13.38	PK
H	4924.00	50.75	38.75	7.46	25.45	44.91	54	-9.09	AV
H	7386.00	69.39	38.65	7.22	24.78	62.74	74	-11.26	PK
H	7386.00	48.82	38.65	7.22	24.78	42.17	54	-11.83	AV
H	15450.00	50.74	36.42	6.32	26.65	47.29	74	-26.71	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n(40MHz)

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		operation frequency:2422							
V	4844.000	68.81	39.55	7.77	25.66	62.69	74	-11.31	PK
V	4844.000	48.34	39.55	7.77	25.66	42.22	54	-11.78	AV
V	7266.000	67.63	38.33	7.30	24.55	61.15	74	-12.85	PK
V	7266.000	48.72	38.33	7.30	24.55	42.24	54	-11.76	AV
V	15450.00	51.85	35.23	6.60	26.59	49.81	74	-24.19	PK
H	4844.000	68.69	39.55	7.77	25.66	62.57	74	-11.43	PK
H	4844.000	49.88	39.55	7.77	25.66	43.76	54	-10.24	AV
H	7266.000	69.47	38.33	7.30	23.55	61.99	74	-12.01	PK
H	7266.000	52.23	38.33	7.30	23.22	44.42	54	-9.58	AV
H	15450.00	48.41	35.45	6.60	27.88	47.44	74	-26.56	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		operation frequency:2437							
V	4874.00	66.74	38.89	7.57	25.45	60.87	74	-13.13	PK
V	4874.00	49.35	38.89	7.57	25.45	43.48	54	-10.52	AV
V	7311.00	67.35	38.78	7.35	24.78	60.70	74	-13.30	PK
V	7311.00	47.57	38.78	7.35	24.78	40.92	54	-13.08	AV
V	15450.00	52.48	35.89	6.42	26.47	49.48	74	-24.52	PK
H	4874.00	65.68	38.89	7.57	25.45	59.81	74	-14.19	PK
H	4874.00	49.25	38.89	7.57	25.45	43.38	54	-10.62	AV
H	7311.00	69.23	38.78	7.35	24.78	62.58	74	-11.42	PK
H	7311.00	48.71	38.78	7.35	24.78	42.06	54	-11.94	AV
H	15450.00	49.63	36.68	6.42	26.65	46.02	74	-27.98	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		operation frequency:2452							
V	4904.00	68.24	38.75	7.38	25.45	62.32	74	-11.68	PK
V	4904.00	50.43	38.75	7.38	25.45	44.51	54	-9.49	AV
V	7356.00	67.54	38.65	7.15	24.78	60.82	74	-13.18	PK
V	7356.00	49.69	38.65	7.15	24.78	42.97	54	-11.03	AV
V	15450.00	53.91	35.58	6.25	26.47	51.05	74	-22.95	PK
H	4904.00	66.58	38.75	7.38	25.45	60.66	74	-13.34	PK
H	4904.00	50.69	38.75	7.38	25.45	44.77	54	-9.23	AV
H	7356.00	69.57	38.65	7.15	24.78	62.85	74	-11.15	PK
H	7356.00	48.97	38.65	7.15	24.78	42.25	54	-11.75	AV
H	15450.00	50.43	36.42	6.25	26.65	46.91	74	-27.09	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



3.3 RADIATED BAND EMISSION MEASUREMENT

3.3.1 TEST REQUIREMENT:

FCC Part15 C Section 15.209 and 15.205

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

3.3.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



3.3.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

**3.3.6 TEST RESULT****Module1****802.11b**

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2412							
V	2390.00	38.28	13.83	52.11	74.00	-21.89	PK
V	2390.00	26.45	13.83	40.28	54.00	-13.72	AV
V	2400.00	38.29	13.85	52.14	74.00	-21.86	PK
V	2400.00	25.87	13.85	39.72	54.00	-14.28	AV
H	2390.00	38.53	13.83	52.36	74.00	-21.64	PK
H	2390.00	26.64	13.83	40.47	54.00	-13.53	AV
V	2400.00	38.34	13.85	52.19	74.00	-21.81	PK
V	2400.00	26.48	13.85	40.33	54.00	-13.67	AV

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2462							
V	2483.50	38.67	14.02	52.69	74.00	-21.31	PK
V	2483.50	26.85	14.02	40.87	54.00	-13.13	AV
V	2500.00	38.26	14.06	52.32	74.00	-21.68	PK
V	2500.00	26.14	14.06	40.2	54.00	-13.80	AV
H	2483.50	38.33	14.02	52.35	74.00	-21.65	PK
H	2483.50	26.72	14.02	40.74	54.00	-13.26	AV
H	2500.00	38.37	14.06	52.43	74.00	-21.57	PK
H	2500.00	26.86	14.06	40.92	54.00	-13.08	AV

Remark:

1. Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11g

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2412							
V	2390.00	37.61	13.83	51.44	74.00	-22.76	PK
V	2390.00	26.27	13.83	40.1	54.00	-14.18	AV
V	2400.00	38.35	13.85	52.2	74.00	-22.54	PK
V	2400.00	25.87	13.85	39.72	54.00	-14.59	AV
H	2390.00	38.59	13.83	52.42	74.00	-22.47	PK
H	2390.00	26.32	13.83	40.15	54.00	-14.15	AV
V	2400.00	38.44	13.85	52.29	74.00	-22.59	PK
V	2400.00	26.38	13.85	40.23	54.00	-14.19	AV

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2462							
V	2483.50	38.23	14.02	52.25	74.00	-21.75	PK
V	2483.50	26.47	14.02	40.49	54.00	-13.51	AV
V	2500.00	38.21	14.06	52.27	74.00	-21.73	PK
V	2500.00	25.97	14.06	40.03	54.00	-13.97	AV
H	2483.50	38.35	14.02	52.37	74.00	-21.63	PK
H	2483.50	26.55	14.02	40.57	54.00	-13.43	AV
H	2500.00	37.79	14.06	51.85	74.00	-22.15	PK
H	2500.00	26.34	14.06	40.4	54.00	-13.60	AV

Remark:

1. Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n(20MHz)

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2412							
V	2390.00	37.86	13.83	51.69	74.00	-22.31	PK
V	2390.00	26.35	13.83	40.18	54.00	-13.82	AV
V	2400.00	38.12	13.85	51.97	74.00	-22.03	PK
V	2400.00	25.77	13.85	39.62	54.00	-14.38	AV
H	2390.00	38.19	13.83	52.02	74.00	-21.98	PK
H	2390.00	26.32	13.83	40.15	54.00	-13.85	AV
V	2400.00	38.05	13.85	51.9	74.00	-22.10	PK
V	2400.00	26.33	13.85	40.18	54.00	-13.82	AV

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2462							
V	2483.50	38.11	14.02	52.13	74.00	-21.87	PK
V	2483.50	26.54	14.02	40.56	54.00	-13.44	AV
V	2500.00	37.64	14.06	51.7	74.00	-22.30	PK
V	2500.00	25.98	14.06	40.04	54.00	-13.96	AV
H	2483.50	38.22	14.02	52.24	74.00	-21.76	PK
H	2483.50	26.58	14.02	40.6	54.00	-13.40	AV
H	2500.00	37.84	14.06	51.9	74.00	-22.10	PK
H	2500.00	26.39	14.06	40.45	54.00	-13.55	AV

Remark:

1. Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


802.11n(40MHz)

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2422							
V	2390.00	38.17	13.83	52.00	74.00	-22.00	PK
V	2390.00	26.51	13.83	40.34	54.00	-13.66	AV
V	2400.00	38.38	13.85	52.23	74.00	-21.77	PK
V	2400.00	26.07	13.85	39.92	54.00	-14.08	AV
H	2390.00	38.46	13.83	52.29	74.00	-21.71	PK
H	2390.00	26.54	13.83	40.37	54.00	-13.63	AV
V	2400.00	38.33	13.85	52.18	74.00	-21.82	PK
V	2400.00	26.48	13.85	40.33	54.00	-13.67	AV

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2452							
V	2483.50	38.38	13.83	52.21	74.00	-21.79	PK
V	2483.50	26.76	13.83	40.59	54.00	-13.41	AV
V	2500.00	38.32	13.85	52.17	74.00	-21.83	PK
V	2500.00	26.18	13.85	40.03	54.00	-13.97	AV
H	2483.50	38.5	13.83	52.33	74.00	-21.67	PK
H	2483.50	26.8	13.83	40.63	54.00	-13.37	AV
H	2500.00	38.12	13.85	51.97	74.00	-22.03	PK
H	2500.00	27.06	13.85	40.91	54.00	-13.09	AV

Remark:

1. Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



Module2

802.11b

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2412							
V	2390.00	38.56	13.83	52.39	74.00	-21.61	PK
V	2390.00	26.45	13.83	40.28	54.00	-13.72	AV
V	2400.00	38.26	13.85	52.11	74.00	-21.89	PK
V	2400.00	25.99	13.85	39.84	54.00	-14.16	AV
H	2390.00	38.35	13.83	52.18	74.00	-21.82	PK
H	2390.00	26.46	13.83	40.29	54.00	-13.71	AV
V	2400.00	38.29	13.85	52.14	74.00	-21.86	PK
V	2400.00	26.34	13.85	40.19	54.00	-13.81	AV

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2462							
V	2483.50	38.39	14.02	52.41	74.00	-21.59	PK
V	2483.50	26.47	14.02	40.49	54.00	-13.51	AV
V	2500.00	38.25	14.06	52.31	74.00	-21.69	PK
V	2500.00	26.32	14.06	40.38	54.00	-13.62	AV
H	2483.50	38.37	14.02	52.39	74.00	-21.61	PK
H	2483.50	26.72	14.02	40.74	54.00	-13.26	AV
H	2500.00	37.92	14.06	51.98	74.00	-22.02	PK
H	2500.00	26.87	14.06	40.93	54.00	-13.07	AV

Remark:

1. Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11g

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:2412							
V	2390.00	37.63	13.83	51.46	74.00	-22.54	PK
V	2390.00	26.13	13.83	39.96	54.00	-14.04	AV
V	2400.00	37.84	13.85	51.69	74.00	-22.31	PK
V	2400.00	25.68	13.85	39.53	54.00	-14.47	AV
H	2390.00	38.03	13.83	51.86	74.00	-22.14	PK
H	2390.00	26.15	13.83	39.98	54.00	-14.02	AV
V	2400.00	37.89	13.85	51.74	74.00	-22.26	PK
V	2400.00	26.17	13.85	40.02	54.00	-13.98	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
operation frequency:2462							
V	2483.50	37.82	14.02	51.84	74.00	-22.16	PK
V	2483.50	26.37	14.02	40.39	54.00	-13.61	AV
V	2500.00	37.77	14.06	51.83	74.00	-22.17	PK
V	2500.00	25.56	14.06	39.62	54.00	-14.38	AV
H	2483.50	38.07	14.02	52.09	74.00	-21.91	PK
H	2483.50	26.54	14.02	40.56	54.00	-13.44	AV
H	2500.00	37.71	14.06	51.77	74.00	-22.23	PK
H	2500.00	26.67	14.06	40.73	54.00	-13.27	AV

Remark:

1. Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n(20MHz)

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2412							
V	2390.00	37.83	13.83	51.66	74.00	-22.34	PK
V	2390.00	26.22	13.83	40.05	54.00	-13.95	AV
V	2400.00	38.05	13.85	51.9	74.00	-22.10	PK
V	2400.00	25.86	13.85	39.71	54.00	-14.29	AV
H	2390.00	38.15	13.83	51.98	74.00	-22.02	PK
H	2390.00	26.32	13.83	40.15	54.00	-13.85	AV
V	2400.00	38.01	13.85	51.86	74.00	-22.14	PK
V	2400.00	26.26	13.85	40.11	54.00	-13.89	AV

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2462							
V	2483.50	38.04	14.02	52.06	74.00	-21.94	PK
V	2483.50	26.52	14.02	40.54	54.00	-13.46	AV
V	2500.00	38.44	14.06	52.5	74.00	-21.50	PK
V	2500.00	25.27	14.06	39.33	54.00	-14.67	AV
H	2483.50	38.19	14.02	52.21	74.00	-21.79	PK
H	2483.50	26.58	14.02	40.6	54.00	-13.40	AV
H	2500.00	37.84	14.06	51.9	74.00	-22.10	PK
H	2500.00	26.39	14.06	40.45	54.00	-13.55	AV

Remark:

1. Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n(40MHz)

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2422							
V	2390.00	38.27	13.83	52.1	74.00	-21.90	PK
V	2390.00	26.36	13.83	40.19	54.00	-13.81	AV
V	2400.00	38.47	13.85	52.32	74.00	-21.68	PK
V	2400.00	26.25	13.85	40.1	54.00	-13.90	AV
H	2390.00	38.46	13.83	52.29	74.00	-21.71	PK
H	2390.00	26.54	13.83	40.37	54.00	-13.63	AV
V	2400.00	38.33	13.85	52.18	74.00	-21.82	PK
V	2400.00	26.49	13.85	40.34	54.00	-13.66	AV

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:2452							
V	2483.50	38.52	14.02	52.54	74.00	-21.46	PK
V	2483.50	26.39	14.02	40.41	54.00	-13.59	AV
V	2500.00	38.32	14.06	52.38	74.00	-21.62	PK
V	2500.00	26.18	14.06	40.24	54.00	-13.76	AV
H	2483.50	38.53	14.02	52.52	74.00	-21.48	PK
H	2483.50	26.47	14.02	40.49	54.00	-13.51	AV
H	2500.00	38.12	14.06	52.18	74.00	-21.82	PK
H	2500.00	27.05	14.06	41.11	54.00	-12.89	AV

Remark:

1. Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



4. POWER SPECTRAL DENSITY TEST

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS


4.1.1 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP



4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.




4.1.5 TEST RESULTS

Module1


Temperature :	25℃	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	AC120V 60Hz
Test Mode :	TX b Mode		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-4.52	8	PASS
2437 MHz	-4.64	8	PASS
2462 MHz	-4.16	8	PASS






TX CH06




TX CH11






Temperature :	25°C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	AC120V 60Hz
Test Mode :	TX g Mode		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-9.55	8	PASS
2437 MHz	-10.74	8	PASS
2462 MHz	-11.76	8	PASS






TX CH06




TX CH11






Temperature :	25°C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	AC120V 60Hz
Test Mode :	TX n Mode(20M)		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-12.84	8	PASS
2437 MHz	-12.91	8	PASS
2462 MHz	-12.64	8	PASS






TX CH06




TX CH11






Temperature :	25°C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	AC120V 60Hz
Test Mode :	TX n Mode(40M)		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2422 MHz	-14.84	8	PASS
2437 MHz	-14.19	8	PASS
2452 MHz	-15.06	8	PASS






TX CH06



TX CH09






Module2

Temperature :	25°C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	AC120V 60Hz
Test Mode :	TX b Mode		


Frequency	Power Density (dBm)		Limit (dBm)	Result
2412 MHz	Ant.1	-3.24	8	PASS
	Ant.2	-3.93		
2437 MHz	Ant.1	-2.18	8	PASS
	Ant.2	-3.96		
2462 MHz	Ant.1	-1.83	8	PASS
	Ant.2	-2.70		

Ant.1






TX CH06






TX CH11





Ant. 2










Temperature :	25°C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	AC120V 60Hz
Test Mode :	TX g Mode		

Frequency	Power Density (dBm)		Limit (dBm)	Result
2412 MHz	Ant.1	-6.39	8	PASS
	Ant.2	-5.85		
2437 MHz	Ant.1	-4.70	8	PASS
	Ant.2	-4.11		
2462 MHz	Ant.1	-4.70	8	PASS
	Ant.2	-5.14		



Ant.1








Ant.2








Temperature :	25°C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	AC120V 60Hz
Test Mode :	TX n Mode(20M)		


Frequency	Read Level (dBm)		Total Power Spectral Density(dBm)	Limit (dBm)	Result
2412 MHz	Ant.1	-4.07	-3.28	8	PASS
	Ant.2	-10.76			
2437 MHz	Ant.1	-6.53	-4.77	8	PASS
	Ant.2	-11.19			
2462 MHz	Ant.1	-4.87	-3.87	8	PASS
	Ant.2	-11.15			

Ant.1






TX CH06






TX CH11





Ant.2








Temperature :	25°C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	AC120V 60Hz
Test Mode :	TX n Mode(40M)		


Frequency	Read Level (dBm)		Total Power Spectral Density(dBm)	Limit (dBm)	Result
2422 MHz	Ant.1	-9.29	-7.21	8	PASS
	Ant.2	-11.39			
2437 MHz	Ant.1	-8.43	-6.78	8	PASS
	Ant.2	-11.56			
2452 MHz	Ant.1	-7.83	-6.38	8	PASS
	Ant.2	-11.71			

Ant.1






TX CH06






TX CH09





Ant.2







5. BANDWIDTH TEST

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

5.1.1 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




5.1.5 TEST RESULTS

Module1


Temperature :	25°C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC120V 60Hz
Test Mode :	TX b Mode		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2412	10.10	500	Pass
Middle	2437	10.10	500	Pass
High	2462	10.07	500	Pass






TX CH 06




TX CH 11






Temperature :	25°C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC120V 60Hz
Test Mode :	TX g Mode		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2412	16.50	500	Pass
Middle	2437	16.51	500	Pass
High	2462	16.50	500	Pass






TX CH 06




TX CH 11




Temperature :	25°C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC120V 60Hz
Test Mode :	TX n Mode(20M)		



Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2412	17.78	500	Pass
Middle	2437	17.75	500	Pass
High	2462	17.80	500	Pass







Temperature :	25°C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC120V 60Hz
Test Mode :	TX n Mode(40M)		



Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2422	36.40	500	Pass
Middle	2437	36.39	500	Pass
High	2452	36.39	500	Pass



**Module2**


Temperature :	25°C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC120V 60Hz



Test Mode : TX b Mode


Channel	Frequency (MHz)	6dB bandwidth (MHz)		Limit (kHz)	Result
Low	2412	Ant.1	10.086	500	Pass
		Ant.2	10.112	500	Pass
Middle	2437	Ant.1	10.082	500	Pass
		Ant.2	10.134	500	Pass
High	2462	Ant.1	10.086	500	Pass
		Ant.2	10.146	500	Pass

Ant.1






TX CH 06





TX CH 11






Ant.2





TX CH 11






Temperature :	25°C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC120V 60Hz
Test Mode :	TX g Mode		


Channel	Frequency (MHz)	6dB bandwidth (MHz)		Limit (kHz)	Result
Low	2412	Ant.1	16.579	500	Pass
		Ant.2	16.438	500	Pass
Middle	2437	Ant.1	16.551	500	Pass
		Ant.2	15.142	500	Pass
High	2462	Ant.1	16.574	500	Pass
		Ant.2	15.155	500	Pass

Ant.1








TX CH 06



TX CH 11



Ant.2








Temperature :	25°C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC120V 60Hz
Test Mode :	TX n Mode(20M)		


Channel	Frequency (MHz)	6dB bandwidth (MHz)		Limit (kHz)	Result
Low	2412	Ant.1	17.765	500	Pass
		Ant.2	16.101	500	Pass
Middle	2437	Ant.1	17.761	500	Pass
		Ant.2	15.188	500	Pass
High	2462	Ant.1	17.760	500	Pass
		Ant.2	15.119	500	Pass

Ant.1






TX CH 06






TX CH 11





Ant.2








Temperature :	25°C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC120V 60Hz
Test Mode :	TX n Mode(40M)		


Channel	Frequency (MHz)	6dB bandwidth (MHz)		Limit (kHz)	Result
Low	2422	Ant.1	36.168	500	Pass
		Ant.2	36.352	500	Pass
Middle	2437	Ant.1	36.177	500	Pass
		Ant.2	35.235	500	Pass
High	2452	Ant.1	36.199	500	Pass
		Ant.2	35.325	500	Pass

Ant.1






TX CH 06






TX CH 09





Ant.2







6. PEAK OUTPUT POWER TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

6.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the Power meter

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



6.1.5 TEST RESULTS

Temperature :	25°C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC120V 60Hz

Module1

TX 802.11b Mode				
Test Channe	Frequency	Maximum Conducted Output Power(PK)	Maximum Conducted Output Power(AV)	LIMIT
	(MHz)	(dBm)	(dBm)	dBm
CH01	2412	16.22	14.43	30
CH06	2437	16.11	14.27	30
CH11	2462	16.31	14.21	30
TX 802.11g Mode				
CH01	2412	14.79	12.05	30
CH06	2437	14.65	12.76	30
CH11	2462	14.70	12.81	30
TX 802.11n-HT20 Mode				
CH01	2412	13.77	11.12	30
CH06	2437	13.72	11.01	30
CH11	2462	13.64	11.94	30
TX 802.11n-HT40 Mode				
CH03	2422	12.53	10.82	30
CH06	2437	12.71	10.04	30
CH09	2452	12.49	10.79	30



Module2

	Frequency	Antenna port	Maximum Conducted Output Power(PK)	Maximum Conducted Output Power(PK)	Total Conducted Output Power(PK)	Total Conducted Output Power(PK)	LIMIT
	(MHz)		(dBm)	(mW)	(mW)	(dBm)	dBm
802.11b	2412	Ant.1	12.82	19.14	N/A	N/A	30
		Ant.2	12.55	17.99			
	2437	Ant.1	12.61	18.24	N/A	N/A	30
		Ant.2	12.46	17.62			
	2462	Ant.1	12.40	17.38	N/A	N/A	30
		Ant.2	12.52	17.86			
802.11g	2412	Ant.1	11.97	15.74	N/A	N/A	30
		Ant.2	11.49	14.09			
	2437	Ant.1	11.79	15.10	N/A	N/A	30
		Ant.2	11.21	13.21			
	2462	Ant.1	11.33	13.58	N/A	N/A	30
		Ant.2	11.00	12.59			
802.11n20	2412	Ant.1	10.61	11.51	22.20	13.46	30
		Ant.2	10.29	10.69			
	2437	Ant.1	10.00	10.00	20.99	13.22	30
		Ant.2	10.41	10.99			
	2462	Ant.1	10.41	10.99	22.98	13.61	30
		Ant.2	10.79	11.99			
802.11n40	2422	Ant.1	9.36	8.63	17.46	12.42	30
		Ant.2	9.46	8.83			
	2437	Ant.1	9.56	9.04	17.87	12.52	30
		Ant.2	9.46	8.83			
	2452	Ant.1	9.71	9.35	19.29	12.85	30
		Ant.2	9.97	9.93			



7. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

7.1 APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


7.2 TEST PROCEDURE

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP





7.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.1 TEST RESULTS




Module1

802.11b: Band Edge, Left Side




802.11b: Band Edge, Right Side






802.11g: Band Edge, Left Side




802.11g: Band Edge, Right Side






802.11n-HT20: Band Edge, Left Side




802.11n-HT20: Band Edge, Right Side






802.11n-HT40: Band Edge, Left Side



802.11n-HT40: Band Edge, Right Side







Module2

Ant.1

802.11b: Band Edge, Left Side




802.11b: Band Edge, Right Side






802.11g: Band Edge, Left Side




802.11g: Band Edge, Right Side






802.11n-HT20: Band Edge, Left Side




802.11n-HT20: Band Edge, Right Side






802.11n-HT40: Band Edge, Left Side




802.11n-HT40: Band Edge, Right Side






Ant.2

802.11b: Band Edge, Left Side




802.11b: Band Edge, Right Side






802.11g: Band Edge, Left Side




802.11g: Band Edge, Right Side






802.11n-HT20: Band Edge, Left Side




802.11n-HT20: Band Edge, Right Side






802.11n-HT40: Band Edge, Left Side



802.11n-HT40: Band Edge, Right Side





8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2 EUT ANTENNA


The EUT antenna is Module 1 and Module 2 PCB antenna. It complies with the standard requirement.

9. EUT TEST PHOTO

Conducted Measurement Photos



Radiated Measurement Photos




Radiated Measurement Photos





10. EUT PHOTO



***** END OF REPORT *****