ACCREDITED
Certificate # 3939.01

FCC TEST REPORT

(PART 22)

Applicant:	DataRemote Incorporated
Address:	18001 Old Cutler Rd. Suite 600, Miami, FL 33157

Manufacturer or Supplier:	DataRemote Incorporated
Address:	18001 Old Cutler Rd. Suite 600, Miami, FL 33157
Product:	LTE Cellular Router
Brand Name:	DataRemote
Model Name:	CDS-9090
FCC ID:	2AJLF-CDS-9090
Date of tests:	Feb. 15, 2019 ~ Mar. 11, 2019

The tests have been carried out according to the requirements of the following standard:

☒ **FCC PART 22, Subpart H**
☒ **ANSI/TIA/EIA-603-D**
☒ **ANSI/TIA/EIA-603-E**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Roger Li Engineer / Mobile Department	Approved by Sam Tung Manager / Mobile Department
Roger Date: Mar. 15, 2019	Date: Mar. 15, 2019

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

RELEASE CONTROL RECORD **4**

1 SUMMARY OF TEST RESULTS **5**

1.1 MEASUREMENT UNCERTAINTY 5

1.2 TEST SITE AND INSTRUMENTS 6

2 GENERAL INFORMATION **7**

2.1 GENERAL DESCRIPTION OF EUT 7

2.2 CONFIGURATION OF SYSTEM UNDER TEST 9

2.3 DESCRIPTION OF SUPPORT UNITS 10

2.4 TEST ITEM AND TEST CONFIGURATION 10

2.5 EUT OPERATING CONDITIONS 13

2.6 GENERAL DESCRIPTION OF APPLIED STANDARDS 13

3 TEST TYPES AND RESULTS **14**

3.1 OUTPUT POWER MEASUREMENT 14

3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT 14

3.1.2 TEST PROCEDURES 14

3.1.3 TEST SETUP 15

3.1.4 TEST RESULTS 16

3.2 FREQUENCY STABILITY MEASUREMENT 23

3.2.1 LIMITS OF FREQUENCY STABILIITY MEASUREMENT 23

3.2.2 TEST PROCEDURE 23

3.2.3 TEST SETUP 23

3.2.4 TEST RESULTS 24

3.3 OCCUPIED BANDWIDTH MEASUREMENT 29

3.3.1 TEST PROCEDURES 29

3.3.2 TEST SETUP 29

3.3.3 TEST RESULTS 30

3.4 BAND EDGE MEASUREMENT 35

3.4.1 LIMITS OF BAND EDGE MEASUREMENT 35

3.4.2 TEST SETUP 35

3.4.3 TEST PROCEDURES 36

3.4.4 TEST RESULTS 37

3.5 CONDUCTED SPURIOUS EMISSIONS 46

3.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT 46

3.5.2 TEST PROCEDURE 46

3.5.3 TEST SETUP 46

3.5.4 TEST RESULTS 47

3.6 RADIATED EMISSION MEASUREMENT 52

3.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT 52

3.6.2 TEST PROCEDURES 52

3.6.3 DEVIATION FROM TEST STANDARD 52

3.6.4 TEST SETUP 53

3.6.5 TEST RESULTS 55

3.7 PEAK TO AVERAGE RATIO 75
3.7.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT 75
3.7.2 TEST SETUP 75
3.7.3 TEST PROCEDURES 75
3.7.4 TEST RESULTS 76

4 PHOTOGRAPHS OF THE TEST CONFIGURATION 81

5 INFORMATION ON THE TESTING LABORATORIES 82

6 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB 83

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF190128W002-1	Original release	Mar. 15, 2019

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 22 & Part 2			
STANDARD SECTION	**TEST TYPE**	**RESULT**	**REMARK**
2.1046 22.913 (a)	Effective Radiated Power	PASS	Meet the requirement of limit.
2.1055 22.355	Frequency Stability	PASS	Meet the requirement of limit.
2.1049 22.917b	Occupied Bandwidth	PASS	Meet the requirement of limit.
--	Peak to average ratio*	PASS	Meet the requirement of limit.
22.917	Band Edge Measurements	PASS	Meet the requirement of limit.
2.1051 22.917	Conducted Spurious Emissions	PASS	Meet the requirement of limit.
2.1053 22.917	Radiated Spurious Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -26.07dB at 52.33MHz.

* Refer to KDB 971168 D01 Power Meas License Digital Systems v03r01.

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
Effective Radiated Power	±4.48dB
Frequency Stability	±39.27Hz
Radiated emissions	±4.48dB
Conducted emissions	±2 dB
Occupied Channel Bandwidth	±21.7KHz
Band Edge Measurements	±4.48dB
Peak to average ratio	±0.76dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.2 TEST SITE AND INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 16,18	Mar. 15,19
EXA Signal Analyzer	KEYSIGHT	N9010A-526	MY54510322	Mar. 16,18	Mar. 15,19
Bilog Antenna 1	ETS-LINDGREN	3143B	00161964	Mar. 15,18	Mar. 14,19
Bilog Antenna 2	ETS-LINDGREN	3143B	00161965	Mar. 15,18	Mar. 14,19
Horn Antenna 1	ETS-LINDGREN	3117	00168728	Mar. 15,18	Mar. 14,19
Horn Antenna 2	ETS-LINDGREN	3117	00168692	Nov. 30, 18	Nov. 29, 19
Loop antenna	Daze	ZN30900A	0708	Oct. 23,18	Oct. 22, 19
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K-SG/QMS-00361	15433	Nov. 21, 18	Nov. 20, 19
Radio Communication Analyzer	ANRITSU	MT8820C	6201465426	Feb. 26,19	Feb. 25,20
Signal Pre-Amplifier	EMSI	EMC 9135	980249	Jul. 09,18	Jul. 08,19
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	Jul. 09,18	Jul. 08,19
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Jul. 09,18	Jul. 08,19
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	Apr. 21,18	Apr. 20,19
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SMA	1505	Jul. 09,18	Jul. 08,19
Power Meter	Anritsu	ML2495A	1506002	Feb. 26,19	Feb. 25,20
Power Sensor	Anritsu	MA2411B	1339352	Mar. 16,18	Mar. 15,19
Humid & Temp Programmable Tester	Juyi	ITH-120-45-CP-AR	IAA1504-001	Jul. 09,18	Jul. 08,19
MXG Analog Microvave Signal Generator	KEYSIGHT	N5183A	MY50143024	Mar. 13,18	Mar. 12,19

NOTE: 1. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

2. The test was performed in 3m Semi-anechoic Chamber and RF Oven Room.

3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.

4. The FCC Site Registration No. is 525120; The Designation No. is CN1171.

2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

EUT	LTE Cellular Router	
MODEL NAME	CDS-9090	
POWER SUPPLY	15.0Vdc (adapter or host equipment) 7.4Vdc (Li-ion, battery)	
MODULATION TYPE	**WCDMA**	BPSK,QPSK
	LTE	QPSK, 16QAM
FREQUENCY RANGE	**WCDMA**	826.4MHz ~ 846.6MHz
	LTE Band 5 (Channel Bandwidth: 1.4MHz)	824.7MHz ~ 848.3MHz
	LTE Band 5 (Channel Bandwidth: 3MHz)	825.5MHz ~ 847.5MHz
	LTE Band 5 (Channel Bandwidth: 5MHz)	826.5MHz ~ 846.5MHz
	LTE Band 5 (Channel Bandwidth: 10MHz)	829MHz ~ 844MHz
MAX. ERP POWER	**WCDMA**	205mW
	LTE Band 5 (Channel Bandwidth: 1.4MHz)	242mW
	LTE Band 5 (Channel Bandwidth: 3MHz)	246mW
	LTE Band 5 (Channel Bandwidth: 5MHz)	263mW
	LTE Band 5 (Channel Bandwidth: 10MHz)	215mW
EMISSION DESIGNATOR	**WCDMA**	4M16F9W
	LTE Band 5 (Channel Bandwidth: 1.4MHz)	QPSK: 1M09G7D
		16QAM: 1M09W7D
	LTE Band 5 (Channel Bandwidth: 3MHz)	QPSK: 2M69G7D
		16QAM: 2M68W7D
	LTE Band 5 (Channel Bandwidth: 5MHz)	QPSK: 4M48G7D
		16QAM: 4M47W7D
	LTE Band 5 (Channel Bandwidth: 10MHz)	QPSK: 8M93G7D
		16QAM: 8M93W7D
ANTENNA TYPE	Fixed External antenna with -0.5dBi gain	
HW VERSION	V1.2	
SW VERSION	V0.5.5	
I/O PORTS	Refer to user's manual	
DATA CABLE	N/A	

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's

manual.

2. The EUT was powered by the following adapter:

ADAPTER	
BRAND:	Shenzhen Mass Power Electronic Limited
MODEL:	NBS40C150200B3
INPUT:	AC 100-240V, 1A
OUTPUT:	DC 15V, 2A

3. The EUT matched the following Ethernet Cable and Telephone Cables:

ETHERNET CABLE	
BRAND:	Shenzhen Eternity Ju Electronic Co., Ltd
MODEL:	RJ45-8P8C
SIGNAL LINE:	1500±20mm

TELEPHONE CABLE 1	
BRAND:	Shenzhen Eternity Ju Electronic Co., Ltd
MODEL:	RJ11-6P2C
SIGNAL LINE:	1500±20mm

TELEPHONE CABLE 2	
BRAND:	Shenzhen Eternity Ju Electronic Co., Ltd
MODEL:	RJ11-6P2C
SIGNAL LINE:	1500±20mm

4. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

2.2 CONFIGURATION OF SYSTEM UNDER TEST

FOR RADIATION EMISSION



FOR CONDUCTED & E.R.P. TEST



2.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	DC source	LONG WEI	PS-6403D	010934269	N/A
2	PC	HP	A6608CN	3CR83825X3	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	DC Line: Unshielded, Detachable 1.0m
2	AC Line: Unshielded, Detachable 1.5m

NOTE:

1. All power cords of the above support units are non shielded (1.8m).

2.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports The worst case in ERP and radiated emission was found when positioned on X-plane for WCDMA/LTE. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION
A	**EUT + Adapter with WCDMA or LTE link**
B	EUT + Battery with **WCDMA or LTE link**

WCDMA MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
B	ERP	4132 to 4233	4132, 4182, 4233	WCDMA
B	FREQUENCY STABILITY	4132 to 4233	4132, 4233	WCDMA
B	OCCUPIED BANDWIDTH	4132 to 4233	4132, 4182, 4233	WCDMA
B	BAND EDGE	4132 to 4233	4132, 4233	WCDMA
B	CONDCUDETED EMISSION	4132 to 4233	4132, 4182, 4233	WCDMA
A	RADIATED EMISSION	4132 to 4233	4132, 4182, 4233	WCDMA

LTE BAND 5 MODE

TEST ITEM	Available Channel	Tested Channel	Channel bandwidth	modulation	mode
ERP	20407 to 20643	20407, 20525, 20643	1.4MHz	QPSK,16QAM	1 RB / 0 RB Offset
	20415 to 20635	20415, 20525, 20635	3MHz	QPSK,16QAM	1 RB / 0 RB Offset
	20425 to 20625	20425, 20525, 20625	5MHz	QPSK,16QAM	1 RB / 0 RB Offset
	20450 to 20600	20450, 20525, 20600	10MHz	QPSK,16QAM	1 RB / 0 RB Offset
FREQUENCY STABILITY	20407 to 20643	20407, 20643	1.4MHz	QPSK,16QAM	1 RB / 0 RB Offset
	20415 to 20635	20415, 20635	3MHz	QPSK,16QAM	1 RB / 0 RB Offset
	20425 to 20625	20425, 20625	5MHz	QPSK,16QAM	1 RB / 0 RB Offset
	20450 to 20600	20450, 20600	10MHz	QPSK,16QAM	1 RB / 0 RB Offset
OCCUPIED BANDWIDTH	20407 to 20643	20407, 20525, 20643	1.4MHz	QPSK	6 RB / 0 RB Offset
				16QAM	6 RB / 0 RB Offset
	20415 to 20635	20415, 20525, 20635	3MHz	QPSK	15 RB / 0 RB Offset
				16QAM	15 RB / 0 RB Offset
	20425 to 20625	20425, 20525, 20625	5MHz	QPSK	25 RB / 0 RB Offset
				16QAM	25 RB / 0 RB Offset
	20450 to 20600	20450, 20525, 20600	10MHz	QPSK	50 RB / 0 RB Offset
				16QAM	50 RB / 0 RB Offset

BAND EDGE	20407 to 20643	20407	1.4 MHz	QPSK,16QAM	1 RB / 0 RB Offset
					6 RB / 0 RB Offset
	20407 to 20643	20643	1.4 MHz	QPSK,16QAM	1 RB / 5 RB Offset
					6 RB / 0 RB Offset
	20415 to 20635	20415	3 MHz	QPSK,16QAM	1 RB / 0 RB Offset
					15 RB / 0 RB Offset
	20415 to 20635	20635	3 MHz	QPSK,16QAM	1 RB / 14 RB Offset
					15 RB / 0 RB Offset
	20425 to 20625	20425	5MHz	QPSK,16QAM	1 RB / 0 RB Offset
					25 RB / 0 RB Offset
	20425 to 20625	20625	5MHz	QPSK,16QAM	1 RB / 24 RB Offset
					25 RB / 0 RB Offset
	20450 to 20600	20450	10MHz	QPSK,16QAM	1 RB / 0 RB Offset
					50 RB / 0 RB Offset
	20450 to 20600	20600	10MHz	QPSK,16QAM	1 RB / 49 RB Offset
					50 RB / 0 RB Offset
CONDCUDETED EMISSION	20407 to 20643	20407, 20525, 20643	1.4MHz	QPSK	1 RB / 0 RB Offset
	20415 to 20635	20415, 20525, 20635	3MHz	QPSK	1 RB / 0 RB Offset
	20425 to 20625	20425, 20525, 20625	5MHz	QPSK	1 RB / 0 RB Offset
	20450 to 20600	20450, 20525, 20600	10MHz	QPSK	1 RB / 0 RB Offset
RADIATED EMISSION	20407 to 20643	20525	1.4MHz	QPSK	1 RB / 0 RB Offset
	20415 to 20635	20525	3MHz	QPSK	1 RB / 0 RB Offset
	20425 to 20625	20425, 20525, 20625	5MHz	QPSK	1 RB / 0 RB Offset
	20450 to 20600	20525	10MHz	QPSK	1 RB / 0 RB Offset

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
ERP	23deg. C, 62%RH	7.4Vdc from Battery	Rose Ma
FREQUENCY STABILITY	23deg. C, 62%RH	DC 7V/15V/16V	Rain Wang
OCCUPIED BANDWIDTH	23deg. C, 62%RH	7.4Vdc from Battery	Rain Wang
BAND EDGE	23deg. C, 62%RH	7.4Vdc from Battery	Rain Wang
CONDCUDETED EMISSION	23deg. C, 62%RH	7.4Vdc from Battery	Rain Wang
RADIATED EMISSION	25deg. C, 63.6%RH	15Vdc from adapter	Rose Ma

2.5 EUT OPERATING CONDITIONS

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

2.6 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 22

KDB 971168 D01 Power Meas License Digital Systems v03r01

ANSI/TIA/EIA-603-D

ANSI/TIA/EIA-603-E

ANSI C63.26-2015

NOTE: All test items have been performed and recorded as per the above standards.

3 TEST TYPES AND RESULTS

3.1 OUTPUT POWER MEASUREMENT

3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Mobile / Portable station are limited to 7 watts e.r.p.

3.1.2 TEST PROCEDURES

EIRP / ERP MEASUREMENT:

a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 5MHz for WCDMA mode and 10MHz for LTE mode.

b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.

c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value“ of step b. Record the power level of S.G

d. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.P.R power - 2.15dBi.

CONDUCTED POWER MEASUREMENT:

The EUT was set up for the maximum power with WCDMA link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

3.1.3 TEST SETUP

EIRP / ERP Measurement:
<Radiated Emission below or equal 1 GHz>



<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

CONDUCTED POWER MEASUREMENT:



3.1.4 TEST RESULTS

CONDUCTED OUTPUT POWER (dBm)

Band	WCDMA V		
Channel	4132	4182	4233
Frequency (MHz)	826.4	836.4	846.6
RMC 12.2K	22.59	22.44	22.41
HSPA			
HSDPA Subtest-1	21.75	21.60	21.57
HSDPA Subtest-2	21.67	21.52	21.49
HSDPA Subtest-3	21.25	21.10	21.07
HSDPA Subtest-4	21.18	21.03	21.00
HSUPA Subtest-1	21.72	21.57	21.54
HSUPA Subtest-2	19.82	19.67	19.64
HSUPA Subtest-3	20.65	20.50	20.47
HSUPA Subtest-4	19.63	19.48	19.45
HSUPA Subtest-5	21.58	21.43	21.40

LTE Band 5

Band/BW	Modulation	RB Size	RB Offset	Low CH 20407 Frequency 824.7 MHz	Mid CH 20525 Frequency 836.5 MHz	High CH 20643 Frequency 848.3 MHz	3GPP MPR (dB)
5/1.4	QPSK	1	0	22.00	22.14	22.21	0
		1	2	22.17	22.31	22.38	0
		1	5	22.07	22.21	22.28	0
		3	0	21.98	22.12	22.19	0
		3	1	22.15	22.29	22.36	0
		3	3	22.05	22.19	22.26	0
		6	0	21.10	21.24	21.31	1
	16QAM	1	0	20.78	20.92	20.99	1
		1	2	20.50	20.64	20.71	1
		1	5	20.34	20.48	20.55	1
		3	0	20.77	20.91	20.98	1
		3	1	20.49	20.63	20.70	1
		3	3	20.33	20.47	20.54	1
		6	0	20.24	20.38	20.45	2

Band/BW	Modulation	RB Size	RB Offset	Low CH 20415 Frequency 825.5 MHz	Mid CH 20525 Frequency 836.5 MHz	High CH 20635 Frequency 847.5 MHz	3GPP MPR (dB)
5/3	QPSK	1	0	22.04	22.18	22.25	0
		1	7	22.21	22.35	22.42	0
		1	14	22.11	22.25	22.32	0
		8	0	21.21	21.35	21.42	1
		8	3	21.11	21.25	21.32	1
		8	7	21.19	21.33	21.40	1
		15	0	21.14	21.28	21.35	1
	16QAM	1	0	20.82	20.96	21.03	1
		1	7	20.54	20.68	20.75	1
		1	14	20.38	20.52	20.59	1
		8	0	20.21	20.35	20.42	2
		8	3	20.25	20.39	20.46	2
		8	7	20.26	20.40	20.47	2
		15	0	20.28	20.42	20.49	2

Band/BW	Modulation	RB Size	RB Offset	Low CH 20425	Mid CH 20525	High CH 20625	3GPP MPR (dB)
				Frequency 826.5 MHz	Frequency 836.5 MHz	Frequency 846.5 MHz	
5/5	QPSK	1	0	22.10	22.24	22.31	0
		1	12	22.27	22.41	22.48	0
		1	24	22.17	22.31	22.38	0
		12	0	21.27	21.41	21.48	1
		12	6	21.17	21.31	21.38	1
		12	13	21.25	21.39	21.46	1
		25	0	21.20	21.34	21.41	1
	16QAM	1	0	20.88	21.02	21.09	1
		1	12	20.60	20.74	20.81	1
		1	24	20.44	20.58	20.65	1
		12	0	20.27	20.41	20.48	2
		12	6	20.31	20.45	20.52	2
		12	13	20.32	20.46	20.53	2
		25	0	20.34	20.48	20.55	2

Band/BW	Modulation	RB Size	RB Offset	Low CH 20450	Mid CH 20525	High CH 20600	3GPP MPR (dB)
				Frequency 829 MHz	Frequency 836.5 MHz	Frequency 844 MHz	
5/10	QPSK	1	0	22.13	22.27	22.34	0
		1	24	22.30	22.44	**22.51**	0
		1	49	22.20	22.34	22.41	0
		25	0	21.30	21.44	21.51	1
		25	12	21.20	21.34	21.41	1
		25	25	21.28	21.42	21.49	1
		50	0	21.23	21.37	21.44	1
	16QAM	1	0	20.91	21.05	21.12	1
		1	24	20.63	20.77	20.84	1
		1	49	20.47	20.61	20.68	1
		25	0	20.30	20.44	20.51	2
		25	12	20.34	20.48	20.55	2
		25	25	20.35	20.49	20.56	2
		50	0	20.37	20.51	20.58	2

d

ERP POWER (dBm)

WCDMA

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
4132	826.4	-19.93	33.56	11.48	14.06	H
4182	836.4	-19.97	33.63	11.51	14.15	H
4233	846.6	-20.05	33.57	11.37	13.70	H
4132	826.4	-9.25	34.24	22.84	192.13	V
4182	836.4	-9.31	34.59	23.13	**205.40**	V
4233	846.6	-9.38	34.62	23.09	203.84	V

REMARKS: 1. ERP Output Power (dBm) = SPA LVL (dBm) + Correction Factor (dB) -2.15(dB).
2. Correction factor (dB) = Free Space Loss + Antenna Factor + Cable Loss

LTE BAND 5

CHANNEL BANDWIDTH: 1.4MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
20407	824.7	-13.89	33.67	17.63	57.98	H	7
20525	836.5	-16.88	33.62	14.59	28.80	H	7
20643	848.3	-16.86	33.65	14.64	29.07	H	7
20407	824.7	-8.68	34.25	23.42	219.68	V	7
20525	836.5	-8.66	34.60	23.79	239.22	V	7
20643	848.3	-8.65	34.63	23.83	**241.55**	V	7

CHANNEL BANDWIDTH: 1.4MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
20407	824.7	-14.72	33.67	16.80	47.90	H	7
20525	836.5	-17.90	33.62	13.57	22.77	H	7
20643	848.3	-17.96	33.65	13.54	22.57	H	7
20407	824.7	-9.51	34.25	22.59	181.47	V	7
20525	836.5	-9.68	34.60	22.77	189.15	V	7
20643	848.3	-9.75	34.63	22.73	187.50	V	7

CHANNEL BANDWIDTH: 3MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
20415	825.5	-13.70	33.72	17.87	61.25	H	7
20525	836.5	-16.82	33.62	14.65	29.20	H	7
20635	847.5	-16.73	33.65	14.77	29.98	H	7
20415	825.5	-8.49	34.30	23.66	232.33	V	7
20525	836.5	-8.60	34.60	23.85	242.55	V	7
20635	847.5	-8.52	34.57	23.90	**245.53**	V	7

CHANNEL BANDWIDTH: 3MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
20415	825.5	-14.85	33.72	16.72	47.00	H	7
20525	836.5	-17.92	33.62	13.55	22.67	H	7
20635	847.5	-17.89	33.65	13.61	22.96	H	7
20415	825.5	-9.64	34.30	22.51	178.28	V	7
20525	836.5	-9.70	34.60	22.75	188.28	V	7
20635	847.5	-9.68	34.57	22.74	187.97	V	7

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
20425	826.5	-13.71	33.69	17.83	60.73	H	7
20525	836.5	-16.89	33.62	14.58	28.73	H	7
20625	846.5	-16.80	33.66	14.71	29.59	H	7
20425	826.5	-8.50	34.85	24.20	**262.97**	V	7
20525	836.5	-8.67	34.60	23.78	238.67	V	7
20625	846.5	-8.59	34.59	23.85	242.88	V	7

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
20425	826.5	-14.57	33.69	16.97	49.82	H	7
20525	836.5	-17.76	33.62	13.71	23.52	H	7
20625	846.5	-17.65	33.66	13.86	24.33	H	7
20425	826.5	-9.36	34.85	23.34	215.72	V	7
20525	836.5	-9.54	34.60	22.91	195.34	V	7
20625	846.5	-9.44	34.59	23.00	199.71	V	7

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
20450	829	-14.29	33.73	17.29	53.52	H	7
20525	836.5	-17.34	33.62	14.13	25.91	H	7
20600	844	-17.38	33.51	13.98	25.02	H	7
20450	829	-9.08	34.54	23.31	214.09	V	7
20525	836.5	-9.12	34.60	23.33	**215.18**	V	7
20600	844	-9.17	34.46	23.14	205.83	V	7

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)	LIMIT (W)
20450	829	-15.22	33.73	16.36	43.20	H	7
20525	836.5	-18.41	33.62	13.06	20.25	H	7
20600	844	-18.21	33.51	13.15	20.67	H	7
20450	829	-10.01	34.54	22.38	172.82	V	7
20525	836.5	-10.19	34.60	22.26	168.19	V	7
20600	844	-10.00	34.46	22.31	170.02	V	7

REMARKS: 1. ERP Output Power (dBm) = SPA LVL (dBm) + Correction Factor (dB) -2.15(dB).
2. Correction factor (dB) = Free Space Loss + Antenna Factor + Cable Loss

3.2 FREQUENCY STABILITY MEASUREMENT

3.2.1 LIMITS OF FREQUENCY STABILIITY MEASUREMENT

1.5 ppm is for base and fixed station. 2.5 ppm is for mobile station.

3.2.2 TEST PROCEDURE

a. Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.

b. EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.

c. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the ±0.5℃ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

3.2.3 TEST SETUP



3.2.4 TEST RESULTS

WCDMA Band V

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	Low Channel	High Channel	
15	0.0018	0.0017	2.5
7	-0.0021	-0.0020	2.5
16	0.0018	0.0016	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 7Vdc to 16Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (℃)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	Low Channel	High Channel	
-30	-0.0122	-0.0109	2.5
-20	-0.0112	-0.0099	2.5
-10	-0.0095	-0.0085	2.5
0	-0.0086	-0.0076	2.5
10	-0.0065	-0.0058	2.5
20	-0.0052	-0.0046	2.5
30	-0.0042	-0.0037	2.5
40	-0.0027	-0.0024	2.5
50	-0.0014	-0.0012	2.5

LTE Band 5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	1.4MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
15	0.0021	0.0019	2.5
7	-0.0029	-0.0029	2.5
16	0.0021	0.0021	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 7Vdc to 16Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (℃)	1.4MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0141	-0.0131	2.5
-20	-0.0124	-0.0115	2.5
-10	-0.0111	-0.0101	2.5
0	-0.0097	-0.0088	2.5
10	-0.0088	-0.0091	2.5
20	-0.0065	-0.0068	2.5
30	-0.0033	-0.0034	2.5
40	-0.0020	-0.0020	2.5
50	-0.0005	-0.0005	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	3MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
15	0.0016	0.0019	2.5
7	-0.0019	-0.0022	2.5
16	0.0016	0.0020	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 7Vdc to 16Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (℃)	3MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0125	-0.0118	2.5
-20	-0.0114	-0.0108	2.5
-10	-0.0095	-0.0090	2.5
0	-0.0078	-0.0074	2.5
10	-0.0065	-0.0062	2.5
20	-0.0051	-0.0048	2.5
30	-0.0030	-0.0028	2.5
40	-0.0018	-0.0016	2.5
50	-0.0004	-0.0003	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	5MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
15	0.0016	0.0019	2.5
7	-0.0018	-0.0022	2.5
16	0.0016	0.0016	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 7Vdc to 16Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (℃)	5MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0102	-0.0076	2.5
-20	-0.0085	-0.0063	2.5
-10	-0.0076	-0.0056	2.5
0	-0.0064	-0.0047	2.5
10	-0.0047	-0.0034	2.5
20	-0.0033	-0.0024	2.5
30	-0.0026	-0.0019	2.5
40	-0.0016	-0.0011	2.5
50	-0.0004	-0.0002	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	10MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
15	0.0021	0.0024	2.5
7	-0.0025	-0.0024	2.5
16	0.0020	0.0021	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 7Vdc to 16Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (℃)	10MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0112	-0.0099	2.5
-20	-0.0098	-0.0086	2.5
-10	-0.0084	-0.0074	2.5
0	-0.0062	-0.0055	2.5
10	-0.0049	-0.0043	2.5
20	-0.0039	-0.0033	2.5
30	-0.0025	-0.0021	2.5
40	-0.0013	-0.0010	2.5
50	0.0002	0.0003	2.5

3.3 OCCUPIED BANDWIDTH MEASUREMENT

3.3.1 TEST PROCEDURES

The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

3.3.2 TEST SETUP



3.3.3 TEST RESULTS

CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)	CHANNEL	Frequency (MHz)	26dB Bandwidth (MHz)
		WCDMA			WCDMA
4132	826.4	4.16	4132	826.4	4.75
4182	836.4	4.16	4182	836.4	4.73
4233	846.6	4.14	4233	846.6	4.73

SPECTRUM PLOT OF WORST VALUE

99% Occupied Bandwidth



26dB Occupied Bandwidth



LTE band 5							
Channel Bandwidth : 1.4MHz							
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)		Channel	Frequency (MHz)	26 dB bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
20407	824.7	1.09	1.09	20407	824.7	1.26	1.27
20525	836.5	1.08	1.09	20525	836.5	1.26	1.28
20643	848.3	1.09	1.08	20643	848.3	1.28	1.26

SPECTRUM PLOT OF WORST VALUE of 99% Occupied Bandwidth

1.4MHz/QPSK



1.4MHz/16QAM



SPECTRUM PLOT OF WORST VALUE of 26dB Occupied Bandwidth

1.4MHz/QPSK



1.4MHz/16QAM



LTE band 5							
Channel Bandwidth : 3MHz							
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)		Channel	Frequency (MHz)	26 dB bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
20415	825.5	2.69	2.68	20415	825.5	2.93	2.93
20525	836.5	2.68	2.68	20525	836.5	2.91	2.94
20635	847.5	2.68	2.68	20635	847.5	2.93	2.93

SPECTRUM PLOT OF WORST VALUE of 99% Occupied Bandwidth

3MHz/QPSK

3MHz/16QAM



SPECTRUM PLOT OF WORST VALUE of 26dB Occupied Bandwidth

3MHz/QPSK



3MHz/16QAM



LTE band 5							
Channel Bandwidth : 5 MHz							
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)		Channel	Frequency (MHz)	26 dB bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
20425	826.5	4.48	4.47	20425	826.5	4.90	4.92
20525	836.5	4.47	4.46	20525	836.5	4.91	4.87
20625	846.5	4.46	4.47	20625	846.5	4.91	4.95

SPECTRUM PLOT OF WORST VALUE of 99% Occupied Bandwidth

5MHz/QPSK

5MHz/16QAM



SPECTRUM PLOT OF WORST VALUE of 26dB Occupied Bandwidth

5MHz/QPSK

5MHz/16QAM



LTE band 5							
Channel Bandwidth : 10 MHz							
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)		Channel	Frequency (MHz)	26 dB bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
20450	829	8.93	8.93	20450	829	9.70	9.66
20525	836.5	8.93	8.92	20525	836.5	9.76	9.60
20600	844	8.93	8.93	20600	844	9.70	9.65

SPECTRUM PLOT OF WORST VALUE of 99% Occupied Bandwidth

10MHz/QPSK

10MHz/16QAM



SPECTRUM PLOT OF WORST VALUE of 26dB Occupied Bandwidth

10MHz/QPSK

10MHz/16QAM



3.4 BAND EDGE MEASUREMENT

3.4.1 LIMITS OF BAND EDGE MEASUREMENT

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

3.4.2 TEST SETUP



3.4.3 TEST PROCEDURES

a. All measurements were done at low and high operational frequency range.

b. The center frequency of spectrum is the band edge frequency and span is 10MHz. RBW of the spectrum is 100kHz and VBW of the spectrum is 300kHz (WCDMA).

c. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 20kHz and VBW of the spectrum is 100 kHz. (LTE bandwidth 1.4MHz).

d. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 30kHz and VBW of the spectrum is 100kHz. (LTE bandwidth 3MHz)

e. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 50kHz and VBW of the spectrum is 200kHz. (LTE bandwidth 5MHz)

f. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 100kHz and VBW of the spectrum is 300kHz. (LTE bandwidth 10MHz)

g. Record the max trace plot into the test report.

3.4.4 TEST RESULTS

WCDMA			
CHANNEL	4132	CHANNEL	4233
			

LTE Band5					
Channel Bandwidth: 1.4MHz QPSK					
CHANNEL	20407	1 RB	CHANNEL	20643	1 RB

LTE Band5					
Channel Bandwidth: 1.4MHz QPSK					
CHANNEL	20407	Full RB	CHANNEL	20643	Full RB

LTE Band5					
Channel Bandwidth: 1.4MHz 16QAM					
CHANNEL	20407	1 RB	CHANNEL	20643	1 RB

LTE Band5					
Channel Bandwidth: 1.4MHz 16QAM					
CHANNEL	20407	Full RB	CHANNEL	20643	Full RB

LTE Band5					
Channel Bandwidth: 3MHz QPSK					
CHANNEL	20415	1 RB	CHANNEL	20635	1 RB

LTE Band5					
Channel Bandwidth: 3MHz QPSK					
CHANNEL	20415	Full RB	CHANNEL	20635	Full RB

LTE Band5					
Channel Bandwidth: 3MHz 16QAM					
CHANNEL	20415	1 RB	CHANNEL	20635	1 RB

LTE Band5					
Channel Bandwidth: 3MHz 16QAM					
CHANNEL	20415	Full RB	CHANNEL	20635	Full RB

LTE Band5					
Channel Bandwidth: 5MHz QPSK					
CHANNEL	20425	1 RB	CHANNEL	20625	1 RB

LTE Band5					
Channel Bandwidth: 5MHz QPSK					
CHANNEL	20425	Full RB	CHANNEL	20625	Full RB

LTE Band5					
Channel Bandwidth: 5MHz 16QAM					
CHANNEL	20425	1 RB	CHANNEL	20625	1 RB

LTE Band5					
Channel Bandwidth: 5MHz 16QAM					
CHANNEL	20425	Full RB	CHANNEL	20625	Full RB

LTE Band5					
Channel Bandwidth: 10MHz QPSK					
CHANNEL	20450	1 RB	CHANNEL	20600	1 RB

LTE Band5					
Channel Bandwidth: 10MHz QPSK					
CHANNEL	20450	Full RB	CHANNEL	20600	Full RB

LTE Band5					
Channel Bandwidth: 10MHz 16QAM					
CHANNEL	20450	1 RB	CHANNEL	20600	1 RB

LTE Band5					
Channel Bandwidth: 10MHz 16QAM					
CHANNEL	20450	Full RB	CHANNEL	20600	Full RB
					

3.5 CONDUCTED SPURIOUS EMISSIONS

3.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. The emission limit equal to –13dBm.

3.5.2 TEST PROCEDURE

a. The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.

b. Measuring frequency range is from 9 kHz to 9GHz. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.

3.5.3 TEST SETUP



3.5.4 TEST RESULTS

WCDMA	
CHANNEL 4132	CHANNEL 4182
FREQUENCY RANGE : 30MHz~9.0GHz	FREQUENCY RANGE : 30MHz~9.0GHz
	
CHANNEL 4233	
FREQUENCY RANGE : 30MHz~9.0GHz	
	

LTE Band 5 (Channel Bandwidth: 1.4MHz)	
CHANNEL 20407	CHANNEL 20525
FREQUENCY RANGE : 30MHz~9.0GHz	FREQUENCY RANGE : 30MHz~9.0GHz
	

LTE Band 5 (Channel Bandwidth: 1.4MHz)	
CHANNEL 20643	
FREQUENCY RANGE : 30MHz~9.0GHz	

LTE Band 5 (Channel Bandwidth: 3MHz)	
CHANNEL 20415	CHANNEL 20525
FREQUENCY RANGE : 30MHz~9.0GHz	FREQUENCY RANGE : 30MHz~9.0GHz
CHANNEL 20635	
FREQUENCY RANGE : 30MHz~9.0GHz	
	

LTE Band 5 (Channel Bandwidth: 5MHz)	
CHANNEL 20425	CHANNEL 20525
FREQUENCY RANGE : 30MHz~9.0GHz	FREQUENCY RANGE : 30MHz~9.0GHz
	
CHANNEL 20625	
FREQUENCY RANGE : 30MHz~9.0GHz	
	

LTE Band 5 (Channel Bandwidth: 10MHz)	
CHANNEL 20450	CHANNEL 20525
FREQUENCY RANGE : 30MHz~9.0GHz	FREQUENCY RANGE : 30MHz~9.0GHz
	
CHANNEL 20600	
FREQUENCY RANGE : 30MHz~9.0GHz	
	

3.6 RADIATED EMISSION MEASUREMENT

3.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. The emission limit equal to –13dBm.

3.6.2 TEST PROCEDURES

a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.

b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value “ of step a. Record the power level of S.G

c. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn.

d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.P.R power - 2.15dBi.

NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

3.6.3 DEVIATION FROM TEST STANDARD

No deviation

3.6.4 TEST SETUP

<Below 30MHz>



< Frequency Range 30MHz~1GHz >



< Frequency Range above 1GHz >



For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.6.5 TEST RESULTS

BELOW 1GHz WORST-CASE DATA

9 KHz – 30 MHz data: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

30 MHz – 1GHz data:

WCDMA Band V:

MODE	TX channel 4182	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 15V from adapter
TESTED BY	Rose Ma		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	52.330	-39.07	-39.79	-13.00	-26.07	0.72	Peak	Horizontal
2		74.680	-50.83	-40.68	-13.00	-37.83	-10.15	Peak	Horizontal
3		156.490	-58.47	-39.77	-13.00	-45.47	-18.70	Peak	Horizontal
4		236.790	-61.10	-44.57	-13.00	-48.10	-16.53	Peak	Horizontal
5		279.860	-63.47	-48.67	-13.00	-50.47	-14.80	Peak	Horizontal
6		345.870	-54.66	-42.39	-13.00	-41.66	-12.27	Peak	Horizontal



MODE	TX channel 4182	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 15V from adapter
TESTED BY	Rose Ma		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	45.720	-42.36	-38.95	-13.00	-29.36	-3.41	Peak	Vertical
2		96.780	-54.52	-43.89	-13.00	-41.52	-10.63	Peak	Vertical
3		124.670	-53.50	-41.21	-13.00	-40.50	-12.29	Peak	Vertical
4		221.870	-58.88	-47.86	-13.00	-45.88	-11.02	Peak	Vertical
5		301.530	-52.56	-41.27	-13.00	-39.56	-11.29	Peak	Vertical
6		375.460	-55.34	-44.32	-13.00	-42.34	-11.02	Peak	Vertical



ABOVE 1GHz DATA

Note: For higher frequency, the emission is too low to be detected.

WCDMA Band V:

CH 4132:

MODE	TX channel 4132	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 15V from adapter
TESTED BY	Rose Ma		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	1648.000	-47.96	-42.99	-13.00	-34.96	-4.97	Peak	Horizontal
2	2479.200	-52.66	-51.01	-13.00	-39.66	-1.65	Peak	Horizontal



MODE	TX channel 4132	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 15V from adapter
TESTED BY	Rose Ma		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	1648.000	-48.38	-44.83	-13.00	-35.38	-3.55	Peak	Vertical
2		2479.200	-49.11	-48.94	-13.00	-36.11	-0.17	Peak	Vertical



CH 4182:

MODE	TX channel 4182	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 15V from adapter
TESTED BY	Rose Ma		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	1666.000	-45.34	-40.52	-13.00	-32.34	-4.82	Peak	Horizontal
2	2509.200	-55.49	-53.89	-13.00	-42.49	-1.60	Peak	Horizontal



MODE	TX channel 4182	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 15V from adapter
TESTED BY	Rose Ma		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	1666.000	-49.90	-46.52	-13.00	-36.90	-3.38	Peak	Vertical
2		2509.200	-56.30	-56.17	-13.00	-43.30	-0.13	Peak	Vertical



CH 4233:

MODE	TX channel 4233	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 15V from adapter
TESTED BY	Rose Ma		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1702.000	-44.70	-40.18	-13.00	-31.70	-4.52	Peak	Horizontal
2 PP	2539.800	-39.73	-38.24	-13.00	-26.73	-1.49	Peak	Horizontal



MODE	TX channel 4233	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 15V from adapter
TESTED BY	Rose Ma		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	1702.000	-50.22	-47.17	-13.00	-37.22	-3.05	Peak	Vertical
2		2539.830	-53.79	-53.79	-13.00	-40.79	0.00	Peak	Vertical



LTE Band 5

CHANNEL BANDWIDTH: 1.4MHz / QPSK

MODE	TX channel 20525	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 15V from adapter
TESTED BY	Rose Ma		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	1666.000	-47.96	-43.14	-13.00	-34.96	-4.82	Peak	Horizontal
2		2509.500	-61.03	-59.43	-13.00	-48.03	-1.60	Peak	Horizontal



MODE	TX channel 20525	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 15V from adapter
TESTED BY	Rose Ma		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	1666.000	-49.96	-46.58	-13.00	-36.96	-3.38	Peak	Vertical
2	2509.500	-53.75	-53.62	-13.00	-40.75	-0.13	Peak	Vertical



CHANNEL BANDWIDTH: 3MHz / QPSK

MODE	TX channel 20525	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 15V from adapter
TESTED BY	Rose Ma		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1666.000	-56.83	-52.01	-13.00	-43.83	-4.82	Peak	Horizontal
2 PP	2509.500	-55.29	-53.69	-13.00	-42.29	-1.60	Peak	Horizontal



MODE	TX channel 20525	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 15V from adapter
TESTED BY	Rose Ma		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	1666.000	-49.16	-45.78	-13.00	-36.16	-3.38	Peak	Vertical
2		2509.500	-55.85	-55.72	-13.00	-42.85	-0.13	Peak	Vertical



CHANNEL BANDWIDTH: 5MHz / QPSK

CH 20425

MODE	TX channel 20425	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 15V from adapter
TESTED BY	Rose Ma		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		1653.000	-48.15	-43.23	-13.00	-35.15	-4.92	Peak	Horizontal
2	PP	2479.500	-44.81	-43.16	-13.00	-31.81	-1.65	Peak	Horizontal



MODE	TX channel 20425	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 15V from adapter
TESTED BY	Rose Ma		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	1653.000	-51.94	-48.44	-13.00	-38.94	-3.50	Peak	Vertical
2		2479.500	-52.30	-52.13	-13.00	-39.30	-0.17	Peak	Vertical



CH 20525

MODE	TX channel 20525	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 15V from adapter
TESTED BY	Rose Ma		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1666.000	-51.11	-46.29	-13.00	-38.11	-4.82	Peak	Horizontal
2 PP	2509.500	-42.98	-41.38	-13.00	-29.98	-1.60	Peak	Horizontal



MODE	TX channel 20525	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 15V from adapter
TESTED BY	Rose Ma		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	1666.000	-48.72	-45.34	-13.00	-35.72	-3.38	Peak	Vertical
2		2509.500	-51.40	-51.27	-13.00	-38.40	-0.13	Peak	Vertical



CH 20625

MODE	TX channel 20625	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 15V from adapter
TESTED BY	Rose Ma		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	1693.000	-48.88	-44.29	-13.00	-35.88	-4.59	Peak	Horizontal
2		2539.500	-53.05	-51.56	-13.00	-40.05	-1.49	Peak	Horizontal



MODE	TX channel 20625	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 15V from adapter
TESTED BY	Rose Ma		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	1693.000	-48.92	-45.79	-13.00	-35.92	-3.13	Peak	Vertical
2		2539.500	-51.64	-51.64	-13.00	-38.64	0.00	Peak	Vertical



CHANNEL BANDWIDTH: 10MHz / QPSK

MODE	TX channel 20525	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 15V from adapter
TESTED BY	Rose Ma		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	1666.000	-53.54	-48.72	-13.00	-40.54	-4.82	Peak	Horizontal
2	2509.500	-60.24	-58.64	-13.00	-47.24	-1.60	Peak	Horizontal



MODE	TX channel 20525	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	26deg. C, 56%RH	INPUT POWER	DC 15V from adapter
TESTED BY	Rose Ma		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	1666.000	-45.50	-42.12	-13.00	-32.50	-3.38	Peak	Vertical
2	2509.500	-62.98	-62.85	-13.00	-49.98	-0.13	Peak	Vertical



3.7 PEAK TO AVERAGE RATIO

3.7.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

3.7.2 TEST SETUP



3.7.3 TEST PROCEDURES

1. Set resolution/measurement bandwidth ≥ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.

3.7.4 TEST RESULTS

WCDMA

CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
4132	826.4	2.80

SPECTRUM PLOT OF WORST VALUE



CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
4182	836.4	2.90

SPECTRUM PLOT OF WORST VALUE



CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
4233	846.6	2.92

SPECTRUM PLOT OF WORST VALUE



LTE BAND 5

CHANNEL BANDWIDTH: 1.4MHz				CHANNEL BANDWIDTH: 3MHz			
CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM			QPSK	16QAM
20407	824.7	4.62	5.51	20415	825.5	4.86	5.72
20525	836.5	5.15	5.99	20525	836.5	5.26	6.13
20643	848.3	5.05	5.89	20635	847.5	5.17	5.99

SPECTRUM PLOT OF WORST VALUE

1.4MHz/QPSK



1.4MHz/16QAM



3MHz/QPSK

3MHz/16QAM



CHANNEL BANDWIDTH: 5MHz				CHANNEL BANDWIDTH: 10MHz			
CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM			QPSK	16QAM
20425	826.5	5.01	5.69	20450	829	5.11	5.93
20525	836.5	5.23	6.00	20525	836.5	5.06	5.93
20625	846.5	5.11	5.93	20600	844	4.93	5.74

SPECTRUM PLOT OF WORST VALUE

5MHz/QPSK

5MHz/16QAM



10MHz/QPSK



10MHz/16QAM

4 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

5 INFORMATION ON THE TESTING LABORATORIES

We, BV 7LAYERS COMMUNICATIONS TECHNOLOGY (SHENZHEN) CO. LTD., were founded in 2015 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Shenzhen EMC/RF Lab:
Tel: +86-755-88696566
Fax: +86-755-88696577

Email: customerservice.dg@cn.bureauveritas.com
Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.

6 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---