

(User Manual-REP TWVSC REMOTE

Specifications:

Model No. :	REP TWVSC REMOTE
Battery :	3V
Dimensions :	115.7*37.5*11mm
Transmit frequency	2440MHz
Data Transmit mode	ASK Transmit
Ambient Temperature :	0~40°C

Applications :

- Chairs and beds Remote controls.
- Other electric furniture controls.

FCC ID: 2AJLRREMOTE

THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS: (1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE, AND (2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRE OPERATION.

NOTE: THE GRANTEE IS NOT RESPONSIBLE FOR ANY CHANGES OR MODIFICATIONS NOT EXPRESSLY APPROVED BY THE PARTY RESPONSIBLE FOR COMPLIANCE. SUCH MODIFICATIONS COULD VOID THE USER'S AUTHORITY TO OPERATE THE EQUIPMENT.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

(User Manual-REP TWVSC REMOTE

Use:

Button function, see the attached diagram

Electrical performance:

1. 3V use alkaline battery-powered, Operating Current $\leq 18\text{mA}$
2. Wireless remote control distance of $\geq 30\text{meters}$
3. Standby operating current $\leq 10\text{uA}$

Size and Funtion Diagram :

