

RF TEST REPORT for Intentional Radiator

No. 161001034SHA-001

Applicant : Ningbo UTEC Electric Co., Ltd
CN8, Far-East Industry Park, YUYAO CITY,
Zhejiang Province

Manufacturer : Ningbo UTEC Electric Co., Ltd
CN8, Far-East Industry Park, YUYAO CITY,
Zhejiang Province

Product Name : Surface-mounted luminaire with LED

Type/Model : 6324-CAM

SUMMARY

The equipment complies with the requirements according to the following standard(s):

47CFR Part 15 (2016): Radio Frequency Devices

ANSI C63.10 (2013): American National Standard for Testing Unlicensed Wireless Devices


Date of issue: December 16, 2016

Prepared by:



Wade Zhang (Project Engineer)

Reviewed by:



Daniel Zhao (Reviewer)

Description of Test Facility

Name: Intertek Testing Services Limited Shanghai
Address: Building No.86, 1198 Qinzhou Road(North), Shanghai 200233, P.R.
China
FCC Registration Number: 236597
IC Assigned Code: 2042B-1
Name of contact: Jonny Jing
Tel: +86 21 61278271
Fax: +86 21 54262353

Content

SUMMARY	1
DESCRIPTION OF TEST FACILITY	2
1. TEST SUMMARY	4
2. GENERAL INFORMATION.....	5
2.1 Applicant Information	5
2.2 Identification of the EUT.....	5
2.3 Technical specification	6
3. TEST SPECIFICATION	7
3.1 Instrument list.....	7
3.2 Test Standard	7
3.3 Mode of operation during the test / Test peripherals used	8
4. MINIMUM 6dB BANDWIDTH	10
4.1 Limit	10
4.2 Test Configuration.....	10
4.3 Test Procedure and test setup	10
4.4 Test Protocol.....	11
5. MAXIMUM CONDUCTED OUTPUT POWER	18
5.1 Test limit.....	18
5.2 Test Configuration.....	18
5.3 Test procedure and test setup	18
5.4 Test protocol.....	19
6. POWER SPECTRUM DENSITY.....	20
6.1 Test limit.....	20
6.2 Test Configuration.....	20
6.3 Test procedure and test setup	21
6.4 Test Protocol.....	21
7. EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS.....	28
7.1 Test limit.....	28
7.2 Test Configuration.....	28
7.3 Test procedure and test setup	28
7.4 Test Protocol.....	29
8. RADIATED EMISSIONS IN RESTRICTED FREQUENCY BANDS	54
8.1 Test limit.....	54
8.2 Test Configuration.....	54
8.3 Test procedure and test setup	55
8.4 Test Protocol.....	56
9. POWER LINE CONDUCTED EMISSION.....	62
9.1 Limit	62
9.2 Test configuration.....	62
9.3 Test procedure and test set up	63
9.4 Test protocol.....	64

1. Test Summary

This report applies to tested sample only. This report shall not be reproduced in part without written approval of Intertek Testing Service Shanghai Limited.

Test Items	FCC Reference	Result
Minimum 6dB Bandwidth	15.247(a)(2)	Pass
Output power	15.247(b)	Pass
Power spectrum density	15.247(e)	Pass
Emissions in non-restricted frequency bands	15.247(d)	Pass
Emissions in restricted frequency bands	15.247(d) & 15.205 & 15.209	Pass
Power line conducted emission	15.207	NA

Note: NA =Not Applicable

2. General Information

2.1 Applicant Information

Applicant : Ningbo UTEC Electric Co., Ltd
CN8, Far-East Industry Park, YUYAO CITY,
Zhejiang Province

Name of contact : WANG DITING

Tel : 0086-574-62760549

Fax : /

Manufacturer : Ningbo UTEC Electric Co., Ltd
CN8, Far-East Industry Park, YUYAO CITY,
Zhejiang Province

2.2 Identification of the EUT

Equipment : Surface-mounted luminaire with LED

Type/model : 6324-CAM

FCC ID : 2AJM2UTEC2017

2.3 Technical specification

Operation Frequency : 2412~2462 MHz
 Band
 Type of Modulation : CCK,BPSK,QPSK,DSSS,OFDM
 OFDM(BPSK,QPSK,16QAM,64QAM)
 EUT Modes of : 802.11b/g;
 Modulation 802.11n HT20,HT40;
 Channel Number : 11Channel for 2412MHz~2462MHz for 11b,11g,11n(H20);
 7 Channel for 2422MHz~2452MHz for 11n HT40;
 Description of EUT : The EUT is a Wi-Fi luminaire with LED, it support 2.4G band,
 and there have only one model. We tested it and listed the 2.4G
 band results in this report.
 Port identification : /
 Rating : 120Vac, 60Hz, 38W
 Antenna : 1.8dBi Integral PCB Antenna
 Declared Temperature : 0°C ~ 50°C
 range
 Category of EUT : Class B
 EUT type : ☒ Table top ☐ Floor standing
 Sample received date : November 18, 2016
 Sample Identification : *0161118-01-001*
 No
 Date of test : November 18, 2016 ~ December 5, 2016

3. Test Specification

3.1 Instrument list

Selected	Equipment	Type	Manu.	Internal no.	Cal. Date	Due date
☒	PXA Analyzer	N9030A	Agilent	EC5338	2016/3/4	2017/3/3
☒	Vector SG	N5182B	Agilent	EC5175	2016/3/4	2017/3/3
☒	Power sensor	U2021XA	Agilent	EC5338-1	2016/3/4	2017/3/3
☒	MXG Analog SG	N5181A	Agilent	EC5338-2	2016/3/4	2017/3/3
☒	Power meter	N1911A/N1921A	Agilent	EC4318	2016/4/10	2017/4/9
☒	EMI Receiver	ESCS 30	R&S	EC 2107	2016/10/19	2017/10/18
☒	A.M.N.	ESH2-Z5	R&S	EC 3119	2015/12/16	2017/12/15
☒	I.S.N.	FCC-TLISN-T8-02	FCC	EC3756	2016/2/16	2017/2/15
☒	EMI chamber	3m	Albatross	EC 3048	2016/5/5	2017/5/4
☒	Test Receiver	ESIB 26	R&S	EC 3045	2016/10/19	2017/10/18
☒	Test Receiver	ESCI 7	R&S	EC4501	2016/2/24	2017/2/23
☒	Bilog Antenna	CBL 6112D	TESEQ	EC 4206	2016/5/30	2017/5/29
☒	Horn antenna	HF 906	R&S	EC 3049	2016/9/11	2017/9/10
☒	Horn antenna	HAP18-26W	TOYO	EC 4792-3	2014/6/12	2017/6/11
☒	Pre-amplifier	Pre-amp 18	R&S	EC 5262	2016/5/24	2017/5/23
☒	Pre-amplifier	Tpa0118-40	R&S	EC 4792-2	2016/4/11	2017/4/10
☒	Shielded room	-	Zhongyu	EC 2838	2016/1/9	2017/1/8

3.2 Test Standard

47CFR Part 15 (2016): Radio Frequency Devices

ANSI C63.10 (2013): American National Standard for Testing Unlicensed Wireless Devices

3.3 Mode of operation during the test / Test peripherals used

Operation Frequency each of channel For 802.11b/g/n20/n40							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz	/	

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test as representatives, and the selected channel see below:

Modulation	Lowest(MHz)	Middle(MHz)	Highest(MHz)
802.11b	2412	2437	2462
802.11g	2412	2437	2462
802.11n20	2412	2437	2462
802.11n(HT40)	2422	2437	2452

While testing transmitting mode of EUT, the internal modulation and continuously transmission was applied.

The test setting software and command is offered by the manufactory.

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, the pre-scan for all data rates in each modulation and bands was tested, and the worst case was found and used in all test cases.

After this pre-scan, we choose the following table of the data rata as the final test mode.

Modulation	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
Duty cycle setting during the transmission is 100% with maximum power setting for all modulations.	

Test Mode description:**Radiated test construction:**

Mode 1: EUT with antenna;

Conducted test construction:

Mode 2: EUT RF port connected to SPA directly;

Test peripherals used:

Item No	Description	Band and Model	S/No
1	Laptop computer	HP ProBook 6470b	NA
2	USB RF Engineering Board	/	NA
Note: The accessories are used for configuration only and not used during test.			


4. Minimum 6dB Bandwidth

Test result: Pass

4.1 Limit

For systems using digital modulation techniques that may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz and 5725 - 5850 MHz bands, the minimum 6 dB bandwidth shall be at least 500 kHz.

4.2 Test Configuration



4.3 Test Procedure and test setup

The minimum 6dB bandwidth per FCC §15.247(a)(2) is measured using the Spectrum Analyzer according to DTS test procedure of “KDB558074 D01 DTS Meas Guidance v03r05” for compliance to FCC 47CFR 15.247 requirements (clause 8.1).

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) ≥ 3 RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

4.4 Test Protocol

Temperature: 22°C


Relative Humidity: 53%

Mode	CH	6dB Emission Bandwidth (MHz)	Limit (MHz)
802.11b	L	10.05	≥ 0.5
	M	10.06	
	H	10.07	
802.11g	L	16.57	
	M	16.57	
	H	16.55	
802.11n20	L	17.79	
	M	17.79	
	H	17.80	
802.11n40	L	36.37	
	M	36.37	
	H	36.37	

Mode	CH	99% Occupy Bandwidth (MHz)	Limit (MHz)
802.11b	L	14.862	NA
	M	14.930	
	H	14.942	
802.11g	L	16.494	
	M	16.495	
	H	16.748	
802.11n20	L	17.712	
	M	17.709	
	H	17.824	
802.11n40	L	35.906	
	M	35.920	
	H	35.917	

Test plot as follows:


802.11b Frequency L




Frequency M




Frequency H




802.11g Frequency L




Frequency M




Frequency H




802.11n20 Frequency L




Frequency M




Frequency H




802.11n40 Frequency L



Frequency M



Frequency H



5. Maximum Conducted Output power


Test result: Pass

5.1 Test limit

- ☐ For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt
- ☐ For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts
- ☒ For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.

If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. If there have a beam forming type, the limit should be the minimum of 30dBm and 30+ (6 –antenna gain-beam forming gain).

5.2 Test Configuration



5.3 Test procedure and test setup

The EUT was tested according to DTS test procedure of “KDB558074 D01 DTS Meas Guidance v03r05” for compliance to FCC 47CFR 15.247 requirements (clause 9.1.2).

5.4 Test protocol

Temperature: 22 °C

Relative Humidity: 53 %

Mode	Frequency (MHz)	Reading (dBm)	Limit (dBm)	Margin (dB)
802.11b	2412	16.95	30.00	13.05
	2437	16.70	30.00	13.30
	2462	16.55	30.00	13.45
802.11g	2412	20.23	30.00	9.77
	2437	20.23	30.00	9.77
	2462	20.06	30.00	9.94
802.11n20	2412	23.95	30.00	6.05
	2437	24.70	30.00	5.30
	2462	24.55	30.00	5.45
802.11n40	2422	20.35	30.00	9.65
	2437	20.33	30.00	9.67
	2452	20.86	30.00	9.14

6. Power spectrum density


Test result: Pass

6.1 Test limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. If there have a beam forming type, the limit should be the minimum of 8dBm/MHz and $8 + (6 - \text{antenna gain} - \text{beam forming gain})$.

6.2 Test Configuration



6.3 Test procedure and test setup

The power output per FCC §15.247(e) was tested according to DTS test procedure of “KDB558074 D01 DTS Meas Guidance v03r05” (clause 10.2 Method PKPSD) for compliance to FCC 47CFR 15.247 requirements.

- 1) Set analyzer center frequency to DTS channel center frequency.
- 2) Set the span to 1.5 times the DTS bandwidth.
- 3) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- 4) Set the VBW $\geq 3 \times \text{RBW}$.
- 5) Detector = peak.
- 6) Sweep time = auto couple.
- 7) Trace mode = max hold.
- 8) Allow trace to fully stabilize.
- 9) Use the peak marker function to determine the maximum amplitude level within the RBW.
- 10) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.4 Test Protocol


Temperature: 22 °C

Relative Humidity: 53 %


Mode	Frequency (MHz)	Max PSD (dBm/100KHz)	Limit (dBm/3KHz)	Margin (dB)
802.11b	2412	6.132	8.00	1.868
	2437	5.089	8.00	2.911
	2462	5.043	8.00	2.957
802.11g	2412	1.225	8.00	6.775
	2437	0.971	8.00	7.029
	2462	0.545	8.00	7.455
802.11 n20	2412	1.692	8.00	6.308
	2437	1.894	8.00	6.106
	2462	1.448	8.00	6.552
802.11 n40	2422	-1.558	8.00	9.558
	2437	-2.383	8.00	10.383
	2452	-2.280	8.00	10.280

Test plot as follows:


802.11b Frequency L




Frequency M




Frequency H




802.11g Frequency L




Frequency M




Frequency H




802.11n20 Frequency L




Frequency M




Frequency H



802.11n40 Frequency L



Frequency M



Frequency H




7. Emissions in non-restricted frequency bands

Test result: Pass

7.1 Test limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

7.2 Test Configuration



7.3 Test procedure and test setup

The Emission outside the frequency Band per FCC § 15.247(d) is measured using the Spectrum Analyzer with the resolutions bandwidth set at 100kHz, the video bandwidth set at 300kHz, and the SPAN>>RBW.

The EUT was tested according to DTS test procedure of “KDB558074 D01 DTS Meas Guidance v03r05” (clause 11.0) for compliance to FCC 47CFR 15.247 requirements.

7.4 Test Protocol



Temperature: 22 °C



Relative Humidity: 53 %

Test Mode	Frequency (MHz)	Results		Limit
		Port 1	Port 2	
802.11b	2412	Pass	Pass	>20dB
	2437	Pass	Pass	
	2462	Pass	Pass	
802.11g	2412	Pass	Pass	
	2437	Pass	Pass	
	2462	Pass	Pass	
802.11n20	2412	Pass	Pass	
	2437	Pass	Pass	
	2462	Pass	Pass	
802.11n40	2422	Pass	Pass	
	2437	Pass	Pass	
	2452	Pass	Pass	



Test plot as follows:



802.11b Frequency L









Frequency M









Frequency H









802.11g Frequency L









Frequency M









Frequency H









802.11n20 Frequency L









Frequency M









Frequency H









802.11n40 Frequency L









Frequency M





Frequency H





8. Radiated Emissions in restricted frequency bands


Test result: Pass

8.1 Test limit

The radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) showed as below:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

8.2 Test Configuration



8.3 Test procedure and test setup

The measurement was applied in a semi-anechoic chamber. While testing for spurious emission higher than 1GHz, if applied, the pre-amplifier would be equipped just at the output terminal of the antenna.

Tabletop devices shall be placed on a non-conducting platform with nominal top surface dimensions 1 m by 1.5 m. For emissions testing at or below 1 GHz, the table height shall be 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height shall be 1.5 m.

The turntable rotated 360 degrees to determine the position of the maximum emission level. The EUT was set 3 meters away from the receiving antenna which was mounted on an antenna mast. The antenna moved up and down between from 1 meter to 4 meters to find out the maximum emission level.

The EUT was tested according to DTS test procedure of KDB558074 D01 DTS “Meas Guidance v03r05” for compliance to FCC 47CFR 15.247 requirements.

The radiated emission was measured using the Spectrum Analyzer with the resolutions bandwidth set as:

RBW = 100 kHz, VBW = 300 kHz (30MHz-1GHz)

RBW = 1MHz, VBW = 3MHz (>1GHz for PK);

Remark:

1. Factor= Antenna Factor + Cable Loss (-Amplifier, is employed)
2. Measured level= Original Receiver Reading + Factor
3. Margin = limit – Measured level
4. If the PK measured level is lower than AV limit, the AV test can be elided.

Example:

Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,

Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10dBuV.

Then Factor = 30.20 + 2.00 – 32.00 = 0.20dB/m;

Measured level = 10dBuV + 0.20dB/m = 10.20dBuV/m

Assuming limit = 54dBuV/m,

Measured level = 10.20dBuV/m, then Margin = 54 -10.20 = 43.80dBuV/m.

8.4 Test Protocol


Temperature: 25 °C

Relative Humidity: 55 %


The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

30MHz~1GHz, 802.11n20 mode,

Horizontal



Vertical



30MHz~1GHz, Test data:

Polarization	Frequency (MHz)	Measured level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector
H	30.00	24.1	40.0	15.9	PK
	63.05	22.8	40.0	17.2	PK
	105.81	31.0	43.5	12.5	PK
	169.96	29.7	43.5	13.8	PK
	212.73	35.8	43.5	7.7	PK
	346.85	31.6	46.0	14.4	PK
	360.46	38.3	46.0	7.7	PK
	601.50	36.5	46.0	9.5	PK
	900.86	41.6	46.0	4.4	PK
V	41.66	37.5	40.0	2.5	QP
	43.61	38.0	40.0	2.0	QP
	63.05	35.4	40.0	4.6	PK
	105.81	36.1	43.5	7.4	PK
	134.97	30.6	43.5	12.9	PK
	201.06	38.1	43.5	5.4	PK
	346.85	34.3	46.0	11.7	PK
	449.88	38.0	46.0	8.0	PK
	601.50	37.6	46.0	8.4	PK
	900.86	43.3	46.0	2.7	PK

Note: The worst test result (30MHz to 1GHz) of channel M (2437MHz) was chosen to list in the report as representative.

Test result above 1GHz:

The emission was conducted from 1GHz to 25GHz.

1: 802.11b

Polarity	Frequency (MHz)	Measured level (dBuV/m)	Limit (dBuV/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
Ver/Hor	2390	50.12	74	-7.80	100	190	23.88	PK
		41.33	54	-7.80	100	190	12.67	AV
	2412	105.33	-	-7.80	100	190	-	PK
		97.42	-	-7.80	100	190	-	AV
	4824	48.55	74	-2.10	100	190	25.45	PK
		40.25	54	-2.10	100	190	13.75	AV
Note:	2412MHz is fundamental signal.							

Polarity	Frequency (MHz)	Measured level (dBuV/m)	Limit (dBuV/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
Ver/Hor	2437	105.37	-	-7.80	100	190	-	PK
		96.24	-	-7.80	100	190	-	AV
	4874	49.43	74	-2.10	100	190	24.57	PK
		41.22	54	-2.10	100	190	12.78	AV
	7311	48.32	74	6.50	100	190	25.68	PK
		39.02	54	6.50	100	190	14.98	AV
Note:	2437MHz is fundamental signal.							

Polarity	Frequency (MHz)	Measured level (dBuV/m)	Limit (dBuV/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
Ver/Hor	2462	106.14	-	-7.80	100	190	-	PK
		95.64	-	-7.80	100	190	-	AV
	2483.5	50.22	74	-7.50	100	190	23.78	PK
		42.33	54	-7.50	100	190	11.67	AV
	4924	49.98	74	-2.10	100	190	24.02	PK
		38.92	54	-2.10	100	190	15.08	AV
	7386	48.26	74	6.50	100	190	25.74	PK
		39.45	54	6.50	100	190	14.55	AV
Note:	2462MHz is fundamental signal.							

2: 2.4G band 802.11g

Polarity	Frequency (MHz)	Measured level (dBuV/m)	Limit (dBuV/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
Ver/Hor	2390	50.44	74	-7.80	100	190	23.56	PK
		41.32	54	-7.80	100	190	12.68	AV
	2412	108.63	-	-7.80	100	190	-	PK
		95.35	-	-7.80	100	190	-	AV
	4824	49.47	74	-2.10	100	190	24.53	PK
		36.45	54	-2.10	100	190	17.55	AV
Note:	2412MHz is fundamental signal.							

Polarity	Frequency (MHz)	Measured level (dBuV/m)	Limit (dBuV/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
Ver/Hor	2437	108.76	-	-7.80	100	190	-	PK
		95.84	-	-7.80	100	190	-	AV
	4874	51.44	74	-2.10	100	190	22.56	PK
		41.36	54	-2.10	100	190	12.64	AV
	7311	46.46	74	6.50	100	190	27.54	PK
		39.33	54	6.50	100	190	14.67	AV
Note:	2437MHz is fundamental signal.							

Polarity	Frequency (MHz)	Measured level (dBuV/m)	Limit (dBuV/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
Ver/Hor	2462	109.35	-	-7.80	100	190	-	PK
		96.44	-	-7.80	100	190	-	AV
	2483.5	50.48	74	-7.50	100	190	23.52	PK
		42.22	54	-7.50	100	190	11.78	AV
	4924	51.43	74	-2.10	100	190	22.57	PK
		40.47	54	-2.10	100	190	13.53	AV
	7386	45.57	74	6.50	100	190	28.43	PK
		36.46	54	6.50	100	190	17.54	AV
Note:	2462MHz is fundamental signal.							

3: 802.11n20

Polarity	Frequency (MHz)	Measured level (dBuV/m)	Limit (dBuV/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
Ver/Hor	2390	51.44	74	-7.80	100	190	22.56	PK
		42.46	54	-7.80	100	190	11.54	AV
	2412	109.47	-	-7.80	100	190	-	PK
		92.88	-	-7.80	100	190	-	AV
	4824	49.65	74	-2.10	100	190	24.35	PK
		38.48	54	-2.10	100	190	15.52	AV
Note:	2412MHz is fundamental signal.							

Polarity	Frequency (MHz)	Measured level (dBuV/m)	Limit (dBuV/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
Ver/Hor	2437	109.84	-	-7.80	100	190	-	PK
		92.44	-	-7.80	100	190	-	AV
	4874	47.85	74	-2.10	100	190	26.15	PK
		39.57	54	-2.10	100	190	14.43	AV
	7311	45.58	74	6.50	100	190	28.42	PK
		38.42	54	6.50	100	190	15.58	AV
Note:	2437MHz is fundamental signal.							

Polarity	Frequency (MHz)	Measured level (dBuV/m)	Limit (dBuV/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
Ver/Hor	2462	109.44	-	-7.80	100	190	-	PK
		92.54	-	-7.80	100	190	-	AV
	2483.5	50.37	74	-7.50	100	190	23.63	PK
		40.45	54	-7.50	100	190	13.55	AV
	4924	48.46	74	-2.10	100	190	25.54	PK
		37.68	54	-2.10	100	190	16.32	AV
	7386	45.26	74	6.50	100	190	28.74	PK
		38.64	54	6.50	100	190	15.36	AV
Note:	2462MHz is fundamental signal.							

4: 2.4G band 802.11n HT40

Polarity	Frequency (MHz)	Measured level (dBuV/m)	Limit (dBuV/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
Ver/Hor	2390	50.32	74	-7.80	100	190	23.68	PK
		41.63	54	-7.80	100	190	12.37	AV
	2422	106.33	-	-7.80	100	190	-	PK
		91.25	-	-7.80	100	190	-	AV
	4844	48.53	74	-2.10	100	190	25.47	PK
		39.58	54	-2.10	100	190	14.42	AV
Note:	2422MHz is fundamental signal.							

Polarity	Frequency (MHz)	Measured level (dBuV/m)	Limit (dBuV/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
Ver/Hor	2437	106.44	-	-7.80	100	190	-	PK
		92.34	-	-7.80	100	190	-	AV
	4874	48.43	74	-2.10	100	190	25.57	PK
		38.66	54	-2.10	100	190	15.34	AV
	7311	45.63	74	6.50	100	190	28.37	PK
		38.35	54	6.50	100	190	15.65	AV
Note:	2437MHz is fundamental signal.							

Polarity	Frequency (MHz)	Measured level (dBuV/m)	Limit (dBuV/m)	Factor (dB)	Antenna (cm)	Turn table (deg)	Margin (dB)	Remark
Ver/Hor	2452	107.44	-	-7.80	100	190	-	PK
		90.35	-	-7.80	100	190	-	AV
	2483.5	47.44	74	-7.50	100	190	26.56	PK
		38.43	54	-7.50	100	190	15.57	AV
	4904	47.58	74	-2.10	100	190	26.42	PK
		36.58	54	-2.10	100	190	17.42	AV
	7356	43.17	74	6.50	100	190	30.83	PK
		36.48	54	6.50	100	190	17.52	AV
Note:	2452MHz is fundamental signal.							


9. Power line conducted emission

Test result: **Pass**

9.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dBUV)	
	QP	AV
0.15-0.5	66 to 56*	56 to 46 *
0.5-5	56	46
5-30	60	50
* Decreases with the logarithm of the frequency.		

9.2 Test configuration



☒ For table top equipment, wooden support is 0.8m height table

☐ For floor standing equipment, wooden support is 0.1m height rack.

9.3 Test procedure and test set up


The EUT are connected to the main power through a line impedance stabilization network (LISN). This provides a $50\Omega/50\mu\text{H}$ coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a $50\Omega/50\mu\text{H}$ coupling impedance with 50Ω termination.

Both sides (Line and Neutral) of AC line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4 on conducted measurement. The bandwidth of the test receiver is set at 9 kHz.

9.4 Test protocol

Temperature : 22°C
Relative Humidity : 52%


L line



Test Data:

Frequency (MHz)	Quasi-peak			Average		
	level dB(μV)	Limit dB(μV)	Margin (dB)	level dB(μV)	limit dB(μV)	Margin (dB)
0.152	53.31	65.90	12.59	37.15	55.90	18.75
0.352	42.19	58.90	16.71	28.34	48.90	20.56
0.485	41.20	56.25	15.05	34.36	46.25	11.89
0.588	33.47	56.00	22.53	18.71	46.00	27.29
0.964	34.26	56.00	21.74	26.18	46.00	19.82
1.754	33.59	56.00	22.41	22.42	46.00	23.58
18.639	32.96	60.00	27.04	23.19	50.00	26.81

N line



Test Data:

Frequency (MHz)	Quasi-peak			Average		
	level dB(μV)	Limit dB(μV)	Margin (dB)	level dB(μV)	limit dB(μV)	Margin (dB)
0.152	52.67	65.90	13.23	38.24	55.90	17.66
0.352	46.48	58.90	12.42	31.57	48.90	17.33
0.470	47.73	56.52	8.79	42.53	46.52	3.99
0.649	41.43	56.00	14.57	26.72	46.00	19.28
0.937	39.50	56.00	16.50	32.91	46.00	13.09
1.639	39.93	56.00	16.07	27.39	46.00	18.61

Note: The worst test results of channel M (2437MHz, 802.11n20) was chosen to list in the report as representative.