

# TEST REPORT

**Product Name** : Mobile Phone  
**Brand Name** : itel  
**Model** : C681L  
**Series Model** : N/A  
**FCC ID** : 2AJMN-C681L  
**Applicant** : **ITEL MOBILE LIMITED**  
**Address** : FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI STREET FOTAN NT HONGKONG  
**Manufacturer** : **ITEL MOBILE LIMITED**  
**Address** : FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI STREET FOTAN NT HONGKONG  
**Factory** : **SHENZHEN TECNO TECHNOLOGY CO., LTD.**  
**Address** : 101, Building 24, Waijing Industrial Park, Fumin Community, Fucheng Street, Longhua District, Shenzhen City, P.R.China  
**Standard(s)** : FCC CFR Title 47 Part 15 Subpart C Section 15.247  
**Date of Receipt** : Oct. 10, 2025  
**Date of Test** : Oct. 11, 2025~ Nov. 03, 2025  
**Issued Date** : Nov. 04, 2025


**Issued By:** **Guangdong Asia Hongke Test Technology Limited**

B1/F, Building 11, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street,  
Bao'an District, Shenzhen, Guangdong, China

Tel.: +86 0755-230967639

Fax.: +86 0755-230967639

**Reviewed by:**



Aalen.Ye

**Approved by:**



Allen Wang



Note: This device has been tested and found to comply with the standard(s) listed, this test report merely corresponds to the test sample. It is not permitted to copy extracts of these test result without the written permission of the test laboratory. This report shall not be reproduced except in full, without the written approval of Guangdong Asia Hongke Test Technology Limited. If there is a need to alter or revise this document, the right belongs to Guangdong Asia Hongke Test Technology Limited, and it should give a prior written notice of the revision document. This test report must not be used by the client to claim product endorsement.

**Guangdong Asia Hongke Test Technology Limited**

B1/F, Building 11, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China.



**Report Revise Record**

| Report Version | Issued Date   | Notes           |
|----------------|---------------|-----------------|
| M0             | Nov. 24, 2025 | Initial Release |

# Contents

|          |                                                    |           |
|----------|----------------------------------------------------|-----------|
| <b>1</b> | <b>TEST SUMMARY.....</b>                           | <b>4</b>  |
| 1.1      | TEST STANDARDS .....                               | 4         |
| 1.2      | TEST SUMMARY .....                                 | 4         |
| 1.3      | TEST FACILITY .....                                | 5         |
| 1.4      | MEASUREMENT UNCERTAINTY .....                      | 5         |
| <b>2</b> | <b>GENERAL INFORMATION .....</b>                   | <b>6</b>  |
| 2.1      | ENVIRONMENTAL CONDITIONS.....                      | 6         |
| 2.2      | GENERAL DESCRIPTION OF EUT .....                   | 6         |
| 2.3      | DESCRIPTION OF TEST MODES AND TEST FREQUENCY ..... | 7         |
| 2.4      | SPECIAL ACCESSORIES .....                          | 8         |
| 2.5      | EQUIPMENT LIST FOR THE TEST.....                   | 8         |
| <b>3</b> | <b>TEST CONDITIONS AND RESULTS.....</b>            | <b>10</b> |
| 3.1      | CONDUCTED EMISSIONS TEST .....                     | 10        |
| 3.2      | RADIATED EMISSIONS AND BAND EDGE .....             | 13        |
| 3.3      | MAXIMUM PEAK OUTPUT POWER .....                    | 30        |
| 3.4      | 20dB BANDWIDTH .....                               | 31        |
| 3.5      | OCCUPIED BANDWIDTH.....                            | 32        |
| 3.6      | FREQUENCY SEPARATION .....                         | 33        |
| 3.7      | NUMBER OF HOPPING FREQUENCY .....                  | 34        |
| 3.8      | TIME OF OCCUPANCY (DWEIL TIME) .....               | 35        |
| 3.9      | OUT-OF-BAND EMISSIONS .....                        | 36        |
| 3.10     | PSEUDORANDOM FREQUENCY HOPPING SEQUENCE.....       | 38        |
| 3.11     | ANTENNA REQUIREMENT.....                           | 39        |

# 1 TEST SUMMARY

## 1.1 Test Standards

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

[ANSI C63.10: 2020](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB558074 D01 15.247 Meas Guidance v05r02](#): Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating Under Section 15.247 of the FCC Rules

## 1.2 Test Summary

| Test Item                                             | Section in 47 CFR   | Result |
|-------------------------------------------------------|---------------------|--------|
| Maximum Conducted Output Power                        | §15.247(b)          | Pass   |
| 20dB Bandwidth                                        | §15.247(a)          | Pass   |
| Frequency Separation                                  | §15.247(a)          | Pass   |
| Number Of Hopping Frequency                           | §15.247(a)          | Pass   |
| Time Of Occupancy (Dwell Time)                        | §15.247(a)          | Pass   |
| Conducted Spurious Emissions and Band Edges Emissions | §15.205, §15.247(d) | Pass   |
| Radiated Spurious Emissions                           | §15.209, §15.247(d) | Pass   |
| Emissions at Restricted Band                          | §15.205             | Pass   |
| AC Mains Conducted Emissions                          | §15.207(a)          | Pass   |
| Antenna Requirements                                  | §15.203             | Pass   |

## 1.3 Test Facility

### Test Laboratory:

#### Guangdong Asia Hongke Test Technology Limited

B1/F, Building 11, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

The test facility is recognized, certified or accredited by the following organizations:

#### FCC-Registration No.: 251906 Designation Number: CN1376

Guangdong Asia Hongke Test Technology Limited has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

#### IC —Registration No.: 31737 CAB identifier: CN0165

The 3m Semi-anechoic chamber of Guangdong Asia Hongke Test Technology Limited has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 31737

#### A2LA-Lab Cert. No.: 7133.01

Guangdong Asia Hongke Test Technology Limited has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

## 1.4 Measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Guangdong Asia Hongke Test Technology Limited's quality system according to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Asia Hongke laboratory is reported:

| Test                          | Measurement Uncertainty   | Notes |
|-------------------------------|---------------------------|-------|
| Power Line Conducted Emission | 9KHz~30MHz $\pm 1.20$ dB  | (1)   |
| Radiated Emission             | 9KHz~30MHz $\pm 3.10$ dB  | (1)   |
| Radiated Emission             | 30MHz~1GHz $\pm 3.75$ dB  | (1)   |
| Radiated Emission             | 1GHz~18GHz $\pm 3.88$ dB  | (1)   |
| Radiated Emission             | 18GHz~40GHz $\pm 3.88$ dB | (1)   |
| RF power, conducted           | 30MHz~6GHz $\pm 0.16$ dB  | (1)   |
| RF power density, conducted   | $\pm 0.24$ dB             | (1)   |
| Spurious emissions, conducted | $\pm 0.21$ dB             | (1)   |
| Temperature                   | $\pm 1^{\circ}\text{C}$   | (1)   |
| Humidity                      | $\pm 3\%$                 | (1)   |
| DC and low frequency voltages | $\pm 1.5\%$               | (1)   |
| Time                          | $\pm 2\%$                 | (1)   |
| Duty cycle                    | $\pm 2\%$                 | (1)   |
| Bandwidth                     | $\pm 1.5 \times 10^{-6}$  | (1)   |

The report uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty Multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95%.

## 2 GENERAL INFORMATION

### 2.1 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

|                     |         |
|---------------------|---------|
| Normal Temperature: | 25°C    |
| Relative Humidity:  | 55 %    |
| Air Pressure:       | 101 kPa |

### 2.2 General Description of EUT

|                                                                                                                                                                                             |                                                                                                     |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Product Name:                                                                                                                                                                               | Mobile Phone                                                                                        |
| Model/Type reference:                                                                                                                                                                       | C681L                                                                                               |
| Serial Model:                                                                                                                                                                               | N/A                                                                                                 |
| Power Supply:                                                                                                                                                                               | DC 3.91V from battery 5100mAh                                                                       |
| Adapter Information:                                                                                                                                                                        | Model: U180ISA<br>Input: AC100-240V, 50/60Hz, 0.6A<br>Output: DC 5.0V, 2.4A or 7.5V, 2.4A 18.0W Max |
| Hardware Version:                                                                                                                                                                           | /                                                                                                   |
| Software Version:                                                                                                                                                                           | /                                                                                                   |
| Sample(s) Status:                                                                                                                                                                           | AiTSZ-251127006-1(Normal sample)<br>AiTSZ-251127006-3(Engineer sample)                              |
| <b>Bluetooth:</b>                                                                                                                                                                           |                                                                                                     |
| Supported type:                                                                                                                                                                             | Bluetooth BR/EDR                                                                                    |
| Modulation:                                                                                                                                                                                 | GFSK, $\pi/4$ DQPSK, 8DPSK                                                                          |
| Operation frequency:                                                                                                                                                                        | 2402MHz~2480MHz                                                                                     |
| Channel number:                                                                                                                                                                             | 79                                                                                                  |
| Channel separation:                                                                                                                                                                         | 1MHz                                                                                                |
| Antenna type:                                                                                                                                                                               | Internal antenna                                                                                    |
| Antenna gain:                                                                                                                                                                               | -1.55dBi (declare by applicant)                                                                     |
| <b>Remark:</b><br>The above DUT's information was declared by manufacturer. For more detailed features description, please refer to the manufacturer's specifications or the User's Manual. |                                                                                                     |

## 2.3 Description of Test Modes and Test Frequency

There are 79 channels provided to the EUT and Channel 00/39/78 were selected to test.

### Operation Frequency List:

| Channel | Frequency (MHz) |
|---------|-----------------|
| 00      | 2402            |
| 01      | 2403            |
| ⋮       | ⋮               |
| 38      | 2440            |
| 39      | 2441            |
| 40      | 2442            |
| ⋮       | ⋮               |
| 77      | 2479            |
| 78      | 2480            |

Note: The line display in grey were the channel selected for testing

Exploratory testing was performed under each mode combination test channel; only the final measurement of the worst combination was made and recorded in this report.

| Test case                              | Exploratory measurement                           |                                                 |                                                                                                                                         | Final measurement<br>Recorded<br>In Report        |                                                 |                                                                                                                                         |
|----------------------------------------|---------------------------------------------------|-------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------|-------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
|                                        | Mode                                              | Date rate                                       | Channel                                                                                                                                 | Mode                                              | Date rate                                       | Channel                                                                                                                                 |
| Frequency Separation                   | GFSK Hopping<br>Π/4DQPSK Hopping<br>8DPSK Hopping | DH1/DH3/DH5<br>2DH1/2DH3/2DH5<br>3DH1/3DH3/3DH5 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | GFSK Hopping<br>Π/4DQPSK Hopping<br>8DPSK Hopping | DH5<br>2DH5<br>3DH5                             | <input checked="" type="checkbox"/> Middle                                                                                              |
| Number Of Hopping Frequency            | GFSK Hopping<br>Π/4DQPSK Hopping<br>8DPSK Hopping | DH1/DH3/DH5<br>2DH1/2DH3/2DH5<br>3DH1/3DH3/3DH5 | <input checked="" type="checkbox"/> Full                                                                                                | GFSK Hopping<br>Π/4DQPSK Hopping<br>8DPSK Hopping | DH5<br>2DH5<br>3DH5                             | <input checked="" type="checkbox"/> middle                                                                                              |
| Time of Occupancy (dwell time)         | GFSK Hopping<br>Π/4DQPSK Hopping<br>8DPSK Hopping | DH1/DH3/DH5<br>2DH1/2DH3/2DH5<br>3DH1/3DH3/3DH5 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | GFSK Hopping<br>Π/4DQPSK Hopping<br>8DPSK Hopping | DH1/DH3/DH5<br>2DH1/2DH3/2DH5<br>3DH1/3DH3/3DH5 | <input checked="" type="checkbox"/> Middle                                                                                              |
| 20dB bandwidth                         | GFSK<br>Π/4DQPSK<br>8DPSK                         | DH1/DH3/DH5<br>2DH1/2DH3/2DH5<br>3DH1/3DH3/3DH5 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | GFSK<br>Π/4DQPSK<br>8DPSK                         | DH5<br>2DH5<br>3DH5                             | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest |
| Maximum Conducted Output Power         | GFSK<br>Π/4DQPSK<br>8DPSK                         | DH1/DH3/DH5<br>2DH1/2DH3/2DH5<br>3DH1/3DH3/3DH5 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | GFSK<br>Π/4DQPSK<br>8DPSK                         | DH5<br>2DH5<br>3DH5                             | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest |
| Conducted Band edge                    | GFSK<br>Π/4DQPSK<br>8DPSK                         | DH1/DH3/DH5<br>2DH1/2DH3/2DH5<br>3DH1/3DH3/3DH5 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Highest                                               | GFSK<br>Π/4DQPSK<br>8DPSK                         | DH5<br>2DH5<br>3DH5                             | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Highest                                               |
| Radiated Band edge                     | GFSK<br>Π/4DQPSK<br>8DPSK                         | DH1/DH3/DH5<br>2DH1/2DH3/2DH5<br>3DH1/3DH3/3DH5 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Highest                                               | GFSK                                              | DH5                                             | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Highest                                               |
| Conducted Spurious Emissions           | GFSK<br>Π/4DQPSK<br>8DPSK                         | DH1/DH3/DH5<br>2DH1/2DH3/2DH5<br>3DH1/3DH3/3DH5 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | GFSK<br>Π/4DQPSK<br>8DPSK                         | DH5<br>2DH5<br>3DH5                             | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest |
| Radiated Spurious Emissions Above 1GHz | GFSK<br>Π/4DQPSK<br>8DPSK                         | DH1/DH3/DH5<br>2DH1/2DH3/2DH5<br>3DH1/3DH3/3DH5 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | GFSK                                              | DH5                                             | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest |
| Radiated Spurious Emissions Below 1GHz | GFSK<br>Π/4DQPSK<br>8DPSK                         | DH1/DH3/DH5<br>2DH1/2DH3/2DH5<br>3DH1/3DH3/3DH5 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | GFSK                                              | DH5                                             | <input checked="" type="checkbox"/> Middle                                                                                              |
| Conducted Emissions 0.15-30 MHz        | GFSK<br>Π/4DQPSK<br>8DPSK                         | DH1/DH3/DH5<br>2DH1/2DH3/2DH5<br>3DH1/3DH3/3DH5 | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | GFSK                                              | DH5                                             | <input checked="" type="checkbox"/> Middle                                                                                              |

## Power setting during the test:

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters:

| Test Software Version | Engineering Mode |         |         |
|-----------------------|------------------|---------|---------|
| Frequency             | 2402MHz          | 2441MHz | 2480MHz |
| BR/EDR                | Default          | Default | Default |

## 2.4 Special Accessories

Follow auxiliary equipment(s) test with EUT that provided by the manufacturer or laboratory is listed as follow:

| Description | Manufacturer | Model | Serial No. | Provided by | Other |
|-------------|--------------|-------|------------|-------------|-------|
| /           | /            | /     | /          | /           | /     |
| /           | /            | /     | /          | /           | /     |

## 2.5 Equipment List for the Test

| Conducted Emission measurement        |                   |              |           |             |            |            |
|---------------------------------------|-------------------|--------------|-----------|-------------|------------|------------|
| Item                                  | Test Equipment    | Manufacturer | Model No. | Serial No.  | Last Cal.  | Cal.Due    |
| <input checked="" type="checkbox"/> 1 | EMI Test Receiver | R&S          | ESPI      | 100771      | 2025.09.23 | 2026.09.22 |
| <input checked="" type="checkbox"/> 2 | LISN              | R&S          | NNLK 8129 | 8130179     | 2025.09.23 | 2026.09.22 |
| <input checked="" type="checkbox"/> 3 | ISN               | TESEQ        | T800      | 29429       | 2025.09.23 | 2026.09.22 |
| <input checked="" type="checkbox"/> 4 | Pulse Limiter     | R&S          | ESH3-Z2   | 102789      | 2025.09.23 | 2026.09.22 |
| <input checked="" type="checkbox"/> 5 | CE Software       | EZ           | EZ-EMC_CE | Ver.AIT-03A | N/A        | N/A        |

| Radiation Emission measurement         |                                     |              |                 |                 |            |            |
|----------------------------------------|-------------------------------------|--------------|-----------------|-----------------|------------|------------|
| Item                                   | Test Equipment                      | Manufacturer | Model No.       | Serial No.      | Last Cal.  | Cal.Due    |
| <input checked="" type="checkbox"/> 1  | EMI Measuring Receiver              | R&S          | ESR             | 101160          | 2025.09.23 | 2026.09.22 |
| <input checked="" type="checkbox"/> 2  | Low Noise Pre Amplifier             | SCHWARZBECK  | BBV 9745        | 00282           | 2025.09.23 | 2026.09.22 |
| <input checked="" type="checkbox"/> 3  | Low Noise Pre Amplifier             | CESHENG      | CSKJLNA231 016A | CSKJLNA23 1016A | 2025.09.23 | 2026.09.22 |
| <input checked="" type="checkbox"/> 4  | Spectrum Analyzer                   | R&S          | FSV40           | 101470          | 2025.09.23 | 2026.09.22 |
| <input checked="" type="checkbox"/> 5  | Passive Loop                        | ETS          | 6512            | 00165355        | 2024.08.29 | 2026.08.28 |
| <input checked="" type="checkbox"/> 6  | TRILOG Super Broadband test Antenna | SCHWARZBECK  | VULB9168        | 01434           | 2024.08.29 | 2027.08.28 |
| <input checked="" type="checkbox"/> 7  | Broadband Horn Antenna              | Schwarzbeck  | BBHA 9120D      | 452             | 2024.08.29 | 2027.08.28 |
| <input checked="" type="checkbox"/> 8  | Horn Antenna 15-40GHz               | SCHWARZBECK  | BBHA9170        | BBHA91703 67    | 2024.08.28 | 2027.08.27 |
| <input checked="" type="checkbox"/> 9  | 6dB Attenuator                      | JFW          | 50FPE-006       | 4360846-949-1   | 2025.09.23 | 2026.09.22 |
| <input checked="" type="checkbox"/> 10 | RE Software                         | EZ           | EZ-EMC_RE       | Ver.AIT-03A     | N/A        | N/A        |

| RF Conducted measurement              |                                     |              |              |                |            |            |
|---------------------------------------|-------------------------------------|--------------|--------------|----------------|------------|------------|
| Item                                  | Test Equipment                      | Manufacturer | Model No.    | Serial No.     | Last Cal.  | Cal.Due    |
| <input checked="" type="checkbox"/> 1 | Spectrum Analyzer                   | Agilent      | N9020A       | MY53421570     | 2025.09.23 | 2026.09.22 |
| <input type="checkbox"/> 2            | Power Sensor                        | Agilent      | 8481A        | MY41097697     | 2025.09.23 | 2026.09.22 |
| <input type="checkbox"/> 3            | Vector Signal Generator             | Agilent      | N5182A       | MY50143009     | 2025.09.23 | 2026.09.22 |
| <input type="checkbox"/> 4            | Analog signal generator             | Agilent      | E8257        | MY51554256     | 2025.09.23 | 2026.09.22 |
| <input type="checkbox"/> 5            | Const Temp. & Humidity Chamber      | Eastlab      | YH-HW-408L   | 23051109       | 2025.09.23 | 2026.09.22 |
| <input type="checkbox"/> 6            | Wideband Radio communication tester | R&S          | CMW500       | 1201.0002K50   | 2025.09.23 | 2026.09.22 |
| <input checked="" type="checkbox"/> 7 | DC power supply                     | ZHAOXIN      | RXN-305D-2   | 28070002559    | 2025.09.23 | 2026.09.22 |
| <input type="checkbox"/> 8            | RF Test box                         | TST          | TSTPASS      | 21033016       | 2025.09.23 | 2026.09.22 |
| <input checked="" type="checkbox"/> 9 | RF Software                         | TST          | TSTPASS      | Version 2.0    | N/A        | N/A        |
| <input type="checkbox"/> 10           | RF Software                         | Cesheng      | WCN Regulary | Ver 25.03.2901 | N/A        | N/A        |

Note: ☐ is not applicable in this Test Report. ☒ is applicable in this Test Report.

### 3 TEST CONDITIONS AND RESULTS


#### 3.1 Conducted Emissions Test

##### LIMIT

| Frequency range (MHz) | Limit (dBuV) |           |
|-----------------------|--------------|-----------|
|                       | Quasi-peak   | Average   |
| 0.15-0.5              | 66 to 56*    | 56 to 46* |
| 0.5-5                 | 56           | 46        |
| 5-30                  | 60           | 50        |

\* Decreases with the logarithm of the frequency.

##### TEST CONFIGURATION




##### TEST PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10:2020.
2. Support equipment, if needed, was placed as per ANSI C63.10:2020.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10:2020.
4. The adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.


## TEST RESULTS

Remark: Both 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz power supply have been tested, only the worst result of 120 VAC, 60 Hz was reported as below:



Remark: Correct Factor = Insertion loss of LISN + Cable loss + Insertion loss of Pulse Limiter;  
Measurement Result = Reading Level + Correct Factor;  
Margin = Measurement Result - Limit

| No. | Frequency (MHz) | Reading (dBuV) | Correct (dB) | Result (dBuV) | Limit (dBuV) | Margin (dB) | Remark |
|-----|-----------------|----------------|--------------|---------------|--------------|-------------|--------|
| 1   | 0.4874          | 42.11          | 10.26        | 52.37         | 56.21        | -3.84       | QP     |
| 2   | 0.5100          | 30.08          | 10.26        | 40.34         | 46.00        | -5.66       | AVG    |
| 3   | 0.7890          | 35.06          | 10.24        | 45.30         | 56.00        | -10.70      | QP     |
| 4   | 0.8924          | 17.84          | 10.26        | 28.10         | 46.00        | -17.90      | AVG    |
| 5   | 1.1490          | 32.26          | 10.27        | 42.53         | 56.00        | -13.47      | QP     |
| 6   | 1.2210          | 16.81          | 10.26        | 27.07         | 46.00        | -18.93      | AVG    |
| 7   | 1.5404          | 32.65          | 10.25        | 42.90         | 56.00        | -13.10      | QP     |
| 8   | 1.5404          | 22.45          | 10.25        | 32.70         | 46.00        | -13.30      | AVG    |
| 9   | 1.8554          | 31.81          | 10.24        | 42.05         | 56.00        | -13.95      | QP     |
| 10  | 2.3280          | 31.06          | 10.22        | 41.28         | 56.00        | -14.72      | QP     |
| 11  | 3.0794          | 17.57          | 10.20        | 27.77         | 46.00        | -18.23      | AVG    |
| 12  | 4.5734          | 16.16          | 10.14        | 26.30         | 46.00        | -19.70      | AVG    |



## 3.2 Radiated Emissions and Band Edge

### Limit

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission out of authorized band shall not exceed the following table at a 3 meters measurement distance.


In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits


| Frequency (MHz) | Distance (Meters) | Radiated (dBμV/m)                          | Radiated (μV/m)       |
|-----------------|-------------------|--------------------------------------------|-----------------------|
| 0.009-0.49      | 3                 | $20\log(2400/F(\text{KHz}))+40\log(300/3)$ | $2400/F(\text{KHz})$  |
| 0.49-1.705      | 3                 | $20\log(24000/F(\text{KHz}))+40\log(30/3)$ | $24000/F(\text{KHz})$ |
| 1.705-30        | 3                 | $20\log(30)+40\log(30/3)$                  | 30                    |
| 30-88           | 3                 | 40.0                                       | 100                   |
| 88-216          | 3                 | 43.5                                       | 150                   |
| 216-960         | 3                 | 46.0                                       | 200                   |
| Above 960       | 3                 | 54.0                                       | 500                   |

### TEST CONFIGURATION


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



### (C) Radiated Emission Test Set-Up, Frequency above 1000MHz



### Test Procedure

- Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
- Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT
- And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- Repeat above procedures until all frequency measurements have been completed.
- Radiated emission test frequency band from 9KHz to 25GHz.
- The distance between test antenna and EUT as following table states:

| Test Frequency range | Test Antenna Type   | Test Distance |
|----------------------|---------------------|---------------|
| 9KHz-30MHz           | Active Loop Antenna | 3             |
| 30MHz-1GHz           | Bilog Antenna       | 3             |
| 1GHz-18GHz           | Horn Antenna        | 3             |
| 18GHz-25GHz          | Horn Antenna        | 1             |

- Setting test receiver/spectrum as following table states:


| Test Frequency range | Test Receiver/Spectrum Setting                                                                      | Detector |
|----------------------|-----------------------------------------------------------------------------------------------------|----------|
| 9KHz-150KHz          | RBW=200Hz/VBW=3KHz, Sweep time=Auto                                                                 | QP       |
| 150KHz-30MHz         | RBW=9KHz/VBW=100KHz, Sweep time=Auto                                                                | QP       |
| 30MHz-1GHz           | RBW=120KHz/VBW=1000KHz, Sweep time=Auto                                                             | QP       |
| 1GHz-40GHz           | Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto<br>Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto | Peak     |

### TEST RESULTS

Remark:

- All GFSK,  $\pi/4$  DQPSK and 8DPSK mode were measured from 9 KHz to 25GHz and recorded worst case at GFSK DH5 mode.
- For below 1GHz testing recorded worst at GFSK DH5 middle channel.
- Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and The emission levels from 9kHz to 30MHz are attenuated 20dB below the limit and not recorded in report.

### For 30MHz-1GHz




Remark:

Emission Level = Reading + Factor;

Factor = Antenna Factor + Cable Loss – Pre-amplifier;

Margin= Emission Level - Limit.

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Det. | Height (cm) |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|------|-------------|
| 1   | 60.9175         | 29.28          | -10.42        | 18.86          | 40.00          | -21.14      | peak | 100         |
| 2   | 78.4133         | 32.36          | -13.02        | 19.34          | 40.00          | -20.66      | peak | 100         |
| 3   | 136.4598        | 29.39          | -9.35         | 20.04          | 43.50          | -23.46      | peak | 100         |
| 4   | 214.5142        | 32.18          | -11.59        | 20.59          | 43.50          | -22.91      | peak | 100         |
| 5 * | 297.2240        | 41.50          | -7.94         | 33.56          | 46.00          | -12.44      | peak | 100         |
| 6   | 731.9202        | 30.36          | 2.25          | 32.61          | 46.00          | -13.39      | peak | 100         |



### For 1GHz to 25GHz

Note:GFSK, Pi/4 DQPSK and 8DPSK all have been tested, only worse case GFSK is reported as bellow:


| Test channel: Lowest channel  |                   |            |                |                |             |              |
|-------------------------------|-------------------|------------|----------------|----------------|-------------|--------------|
| Detector: Peak Value          |                   |            |                |                |             |              |
| Frequency (MHz)               | Read Level (dBuV) | Factor(dB) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Polarization |
| 4804.00                       | 49.60             | -7.98      | 41.62          | 74.00          | 32.38       | Vertical     |
| 4804.00                       | 49.39             | -7.98      | 41.41          | 74.00          | 32.59       | Horizontal   |
| Detector: Average Value       |                   |            |                |                |             |              |
| Frequency (MHz)               | Read Level (dBuV) | Factor(dB) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Polarization |
| 4804.00                       | 40.42             | -7.98      | 32.44          | 54.00          | 21.56       | Vertical     |
| 4804.00                       | 40.08             | -7.98      | 32.10          | 54.00          | 21.90       | Horizontal   |
| Test channel: Middle channel  |                   |            |                |                |             |              |
| Detector: Peak Value          |                   |            |                |                |             |              |
| Frequency (MHz)               | Read Level (dBuV) | Factor(dB) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Polarization |
| 4882.00                       | 50.08             | -7.47      | 42.61          | 74.00          | 31.39       | Vertical     |
| 4882.00                       | 49.78             | -7.47      | 42.31          | 74.00          | 31.69       | Horizontal   |
| Detector: Average Value       |                   |            |                |                |             |              |
| Frequency (MHz)               | Read Level (dBuV) | Factor(dB) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Polarization |
| 4882.00                       | 40.22             | -7.47      | 32.75          | 54.00          | 21.25       | Vertical     |
| 4882.00                       | 40.26             | -7.47      | 32.79          | 54.00          | 21.21       | Horizontal   |
| Test channel: Highest channel |                   |            |                |                |             |              |
| Detector: Peak Value          |                   |            |                |                |             |              |
| Frequency (MHz)               | Read Level (dBuV) | Factor(dB) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Polarization |
| 4960.00                       | 50.23             | -7.00      | 43.23          | 74.00          | 30.77       | Vertical     |
| 4960.00                       | 49.76             | -7.00      | 42.76          | 74.00          | 31.24       | Horizontal   |
| Detector: Average Value       |                   |            |                |                |             |              |
| Frequency (MHz)               | Read Level (dBuV) | Factor(dB) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Polarization |
| 4960.00                       | 39.94             | -7.00      | 32.94          | 54.00          | 21.06       | Vertical     |
| 4960.00                       | 40.36             | -7.00      | 33.36          | 54.00          | 20.64       | Horizontal   |

### REMARKS:

1. Emission level (dBuV/m) = Reading (dBuV)+ Factor (dB/m)
2. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Emission level- Limit value.
4. -- Mean the PK detector measured value is below average limit.
5. Other emission levels are attenuated 20dB below the limit and not recorded in report.
6. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.

### Radiation Restricted band

|               |                |                |             |
|---------------|----------------|----------------|-------------|
| Product Name: | Mobile Phone   | Product Model: | C681L       |
| Test By:      | Vic Duan       | Test mode:     | DH1 Tx mode |
| Test Channel: | Lowest channel | Polarization:  | Vertical    |
| Test Voltage: | DC 3.91V       |                |             |




| Suspected Data List |             |                |               |                |                |             |           |          |         |          |
|---------------------|-------------|----------------|---------------|----------------|----------------|-------------|-----------|----------|---------|----------|
| NO.                 | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Verdict | Polarity |
| 1                   | 2329.93     | 23.66          | 36.01         | 59.67          | 74.00          | 14.33       | 239       | PK       | PASS    | Vertical |
| 2                   | 2329.93     | 11.31          | 36.01         | 47.32          | 54.00          | 6.68        | 49        | AV       | PASS    | Vertical |
| 3                   | 2361.70     | 23.78          | 36.11         | 59.89          | 74.00          | 14.11       | 16        | PK       | PASS    | Vertical |
| 4                   | 2361.70     | 11.09          | 36.11         | 47.20          | 54.00          | 6.80        | 16        | AV       | PASS    | Vertical |
| 5                   | 2390.00     | 21.89          | 36.19         | 58.08          | 74.00          | 15.92       | 34        | PK       | PASS    | Vertical |
| 6                   | 2390.00     | 11.06          | 36.19         | 47.25          | 54.00          | 6.75        | 209       | AV       | PASS    | Vertical |

#### Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

|                      |                |                       |             |
|----------------------|----------------|-----------------------|-------------|
| <b>Product Name:</b> | Mobile Phone   | <b>Product Model:</b> | C681L       |
| <b>Test By:</b>      | Vic Duan       | <b>Test mode:</b>     | DH1 Tx mode |
| <b>Test Channel:</b> | Lowest channel | <b>Polarization:</b>  | Horizontal  |
| <b>Test Voltage:</b> | DC 3.91V       |                       |             |




#### Suspected Data List

| NO. | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Verdict | Polarity   |
|-----|-------------|----------------|---------------|----------------|----------------|-------------|-----------|----------|---------|------------|
| 1   | 2336.32     | 23.92          | 36.03         | 59.95          | 74.00          | 14.05       | 80        | PK       | PASS    | Horizontal |
| 2   | 2336.32     | 11.41          | 36.03         | 47.44          | 54.00          | 6.56        | 110       | AV       | PASS    | Horizontal |
| 3   | 2365.18     | 11.15          | 36.12         | 47.27          | 54.00          | 6.73        | 292       | AV       | PASS    | Horizontal |
| 4   | 2365.18     | 24.24          | 36.12         | 60.36          | 74.00          | 13.64       | 38        | PK       | PASS    | Horizontal |
| 5   | 2390.00     | 22.35          | 36.19         | 58.54          | 74.00          | 15.46       | 349       | PK       | PASS    | Horizontal |
| 6   | 2390.00     | 11.09          | 36.19         | 47.28          | 54.00          | 6.72        | 250       | AV       | PASS    | Horizontal |

#### Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

|                      |                 |                       |             |
|----------------------|-----------------|-----------------------|-------------|
| <b>Product Name:</b> | Mobile Phone    | <b>Product Model:</b> | C681L       |
| <b>Test By:</b>      | Vic Duan        | <b>Test mode:</b>     | DH1 Tx mode |
| <b>Test Channel:</b> | Highest channel | <b>Polarization:</b>  | Vertical    |
| <b>Test Voltage:</b> | DC 3.91V        |                       |             |




#### Suspected Data List

| NO. | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Verdict | Polarity |
|-----|-------------|----------------|---------------|----------------|----------------|-------------|-----------|----------|---------|----------|
| 1   | 2483.50     | 22.09          | 36.24         | 58.33          | 74.00          | 15.67       | 0         | PK       | PASS    | Vertical |
| 2   | 2483.50     | 11.16          | 36.24         | 47.40          | 54.00          | 6.60        | 51        | AV       | PASS    | Vertical |
| 3   | 2491.64     | 23.31          | 36.31         | 59.62          | 74.00          | 14.38       | 318       | PK       | PASS    | Vertical |
| 4   | 2491.64     | 11.07          | 36.31         | 47.38          | 54.00          | 6.62        | 288       | AV       | PASS    | Vertical |
| 5   | 2497.71     | 23.24          | 36.36         | 59.60          | 74.00          | 14.40       | 315       | PK       | PASS    | Vertical |
| 6   | 2497.71     | 11.02          | 36.36         | 47.38          | 54.00          | 6.62        | 288       | AV       | PASS    | Vertical |

#### Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

|                      |                 |                       |             |
|----------------------|-----------------|-----------------------|-------------|
| <b>Product Name:</b> | Mobile Phone    | <b>Product Model:</b> | C681L       |
| <b>Test By:</b>      | Vic Duan        | <b>Test mode:</b>     | DH1 Tx mode |
| <b>Test Channel:</b> | Highest channel | <b>Polarization:</b>  | Horizontal  |
| <b>Test Voltage:</b> | DC 3.91V        |                       |             |



#### Suspected Data List


| NO. | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Verdict | Polarity   |
|-----|-------------|----------------|---------------|----------------|----------------|-------------|-----------|----------|---------|------------|
| 1   | 2483.50     | 22.08          | 36.24         | 58.32          | 74.00          | 15.68       | 252       | PK       | PASS    | Horizontal |
| 2   | 2483.50     | 11.06          | 36.24         | 47.30          | 54.00          | 6.70        | 38        | AV       | PASS    | Horizontal |
| 3   | 2491.62     | 11.05          | 36.31         | 47.36          | 54.00          | 6.64        | 46        | AV       | PASS    | Horizontal |
| 4   | 2491.62     | 23.64          | 36.31         | 59.95          | 74.00          | 14.05       | 357       | PK       | PASS    | Horizontal |
| 5   | 2497.21     | 24.04          | 36.36         | 60.40          | 74.00          | 13.60       | 226       | PK       | PASS    | Horizontal |
| 6   | 2497.21     | 11.03          | 36.36         | 47.39          | 54.00          | 6.61        | 305       | AV       | PASS    | Horizontal |

#### Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

### π/4-DQPSK mode

|               |                |                |              |
|---------------|----------------|----------------|--------------|
| Product Name: | Mobile Phone   | Product Model: | C681L        |
| Test By:      | Vic Duan       | Test mode:     | 2DH1 Tx mode |
| Test Channel: | Lowest channel | Polarization:  | Vertical     |
| Test Voltage: | DC 3.91V       |                |              |




### Suspected Data List

| NO. | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Verdict | Polarity |
|-----|-------------|----------------|---------------|----------------|----------------|-------------|-----------|----------|---------|----------|
| 1   | 2328.14     | 24.19          | 36.01         | 60.20          | 74.00          | 13.80       | 146       | PK       | PASS    | Vertical |
| 2   | 2328.14     | 11.38          | 36.01         | 47.39          | 54.00          | 6.61        | 349       | AV       | PASS    | Vertical |
| 3   | 2358.60     | 23.63          | 36.10         | 59.73          | 74.00          | 14.27       | 245       | PK       | PASS    | Vertical |
| 4   | 2358.60     | 11.17          | 36.10         | 47.27          | 54.00          | 6.73        | 275       | AV       | PASS    | Vertical |
| 5   | 2390.00     | 23.36          | 36.19         | 59.55          | 74.00          | 14.45       | 98        | PK       | PASS    | Vertical |
| 6   | 2390.00     | 10.96          | 36.19         | 47.15          | 54.00          | 6.85        | 18        | AV       | PASS    | Vertical |

### Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

|                      |                |                       |              |
|----------------------|----------------|-----------------------|--------------|
| <b>Product Name:</b> | Mobile Phone   | <b>Product Model:</b> | C681L        |
| <b>Test By:</b>      | Vic Duan       | <b>Test mode:</b>     | 2DH1 Tx mode |
| <b>Test Channel:</b> | Lowest channel | <b>Polarization:</b>  | Horizontal   |
| <b>Test Voltage:</b> | DC 3.91V       |                       |              |




| Suspected Data List |             |                |               |                |                |             |           |          |         |            |
|---------------------|-------------|----------------|---------------|----------------|----------------|-------------|-----------|----------|---------|------------|
| NO.                 | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Verdict | Polarity   |
| 1                   | 2335.00     | 23.69          | 36.03         | 59.72          | 74.00          | 14.28       | 266       | PK       | PASS    | Horizontal |
| 2                   | 2335.00     | 11.38          | 36.03         | 47.41          | 54.00          | 6.59        | 130       | AV       | PASS    | Horizontal |
| 3                   | 2368.37     | 11.14          | 36.13         | 47.27          | 54.00          | 6.73        | 307       | AV       | PASS    | Horizontal |
| 4                   | 2368.37     | 23.42          | 36.13         | 59.55          | 74.00          | 14.45       | 326       | PK       | PASS    | Horizontal |
| 5                   | 2390.00     | 22.12          | 36.19         | 58.31          | 74.00          | 15.69       | 262       | PK       | PASS    | Horizontal |
| 6                   | 2390.00     | 11.08          | 36.19         | 47.27          | 54.00          | 6.73        | 292       | AV       | PASS    | Horizontal |

**Remark:**

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

|                      |                 |                       |              |
|----------------------|-----------------|-----------------------|--------------|
| <b>Product Name:</b> | Mobile Phone    | <b>Product Model:</b> | C681L        |
| <b>Test By:</b>      | Vic Duan        | <b>Test mode:</b>     | 2DH1 Tx mode |
| <b>Test Channel:</b> | Highest channel | <b>Polarization:</b>  | Vertical     |
| <b>Test Voltage:</b> | DC 3.91V        |                       |              |




#### Suspected Data List

| NO. | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Verdict | Polarity |
|-----|-------------|----------------|---------------|----------------|----------------|-------------|-----------|----------|---------|----------|
| 1   | 2483.50     | 22.07          | 36.24         | 58.31          | 74.00          | 15.69       | 103       | PK       | PASS    | Vertical |
| 2   | 2483.50     | 11.05          | 36.24         | 47.29          | 54.00          | 6.71        | 111       | AV       | PASS    | Vertical |
| 3   | 2491.68     | 23.20          | 36.31         | 59.51          | 74.00          | 14.49       | 132       | PK       | PASS    | Vertical |
| 4   | 2491.68     | 11.03          | 36.31         | 47.34          | 54.00          | 6.66        | 319       | AV       | PASS    | Vertical |
| 5   | 2497.58     | 23.24          | 36.36         | 59.60          | 74.00          | 14.40       | 6         | PK       | PASS    | Vertical |
| 6   | 2497.58     | 10.94          | 36.36         | 47.30          | 54.00          | 6.70        | 120       | AV       | PASS    | Vertical |

#### Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

|                      |                 |                       |              |
|----------------------|-----------------|-----------------------|--------------|
| <b>Product Name:</b> | Mobile Phone    | <b>Product Model:</b> | C681L        |
| <b>Test By:</b>      | Vic Duan        | <b>Test mode:</b>     | 2DH1 Tx mode |
| <b>Test Channel:</b> | Highest channel | <b>Polarization:</b>  | Horizontal   |
| <b>Test Voltage:</b> | DC 3.91V        |                       |              |



#### Suspected Data List


| NO. | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Verdict | Polarity   |
|-----|-------------|----------------|---------------|----------------|----------------|-------------|-----------|----------|---------|------------|
| 1   | 2483.50     | 21.80          | 36.24         | 58.04          | 74.00          | 15.96       | 274       | PK       | PASS    | Horizontal |
| 2   | 2483.50     | 10.98          | 36.24         | 47.22          | 54.00          | 6.78        | 126       | AV       | PASS    | Horizontal |
| 3   | 2492.39     | 23.47          | 36.32         | 59.79          | 74.00          | 14.21       | 346       | PK       | PASS    | Horizontal |
| 4   | 2492.39     | 11.00          | 36.32         | 47.32          | 54.00          | 6.68        | 89        | AV       | PASS    | Horizontal |
| 5   | 2497.21     | 23.58          | 36.36         | 59.94          | 74.00          | 14.06       | 126       | PK       | PASS    | Horizontal |
| 6   | 2497.21     | 11.09          | 36.36         | 47.45          | 54.00          | 6.55        | 130       | AV       | PASS    | Horizontal |

#### Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

### 8DPSK mode

|                      |                |                       |              |
|----------------------|----------------|-----------------------|--------------|
| <b>Product Name:</b> | Mobile Phone   | <b>Product Model:</b> | C681L        |
| <b>Test By:</b>      | Vic Duan       | <b>Test mode:</b>     | 3DH1 Tx mode |
| <b>Test Channel:</b> | Lowest channel | <b>Polarization:</b>  | Vertical     |
| <b>Test Voltage:</b> | DC 3.91V       |                       |              |




### Suspected Data List

| NO. | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Verdict | Polarity |
|-----|-------------|----------------|---------------|----------------|----------------|-------------|-----------|----------|---------|----------|
| 1   | 2332.56     | 24.09          | 36.02         | 60.11          | 74.00          | 13.89       | 259       | PK       | PASS    | Vertical |
| 2   | 2332.56     | 11.50          | 36.02         | 47.52          | 54.00          | 6.48        | 26        | AV       | PASS    | Vertical |
| 3   | 2357.19     | 24.03          | 36.09         | 60.12          | 74.00          | 13.88       | 251       | PK       | PASS    | Vertical |
| 4   | 2357.19     | 11.25          | 36.09         | 47.34          | 54.00          | 6.66        | 217       | AV       | PASS    | Vertical |
| 5   | 2390.00     | 22.13          | 36.19         | 58.32          | 74.00          | 15.68       | 75        | PK       | PASS    | Vertical |
| 6   | 2390.00     | 11.03          | 36.19         | 47.22          | 54.00          | 6.78        | 105       | AV       | PASS    | Vertical |

### Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

|                      |                |                       |              |
|----------------------|----------------|-----------------------|--------------|
| <b>Product Name:</b> | Mobile Phone   | <b>Product Model:</b> | C681L        |
| <b>Test By:</b>      | Vic Duan       | <b>Test mode:</b>     | 3DH1 Tx mode |
| <b>Test Channel:</b> | Lowest channel | <b>Polarization:</b>  | Horizontal   |
| <b>Test Voltage:</b> | DC 3.91V       |                       |              |




#### Suspected Data List

| NO. | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Verdict | Polarity   |
|-----|-------------|----------------|---------------|----------------|----------------|-------------|-----------|----------|---------|------------|
| 1   | 2333.41     | 24.21          | 36.02         | 60.23          | 74.00          | 13.77       | 177       | PK       | PASS    | Horizontal |
| 2   | 2333.41     | 11.38          | 36.02         | 47.40          | 54.00          | 6.60        | 88        | AV       | PASS    | Horizontal |
| 3   | 2363.39     | 24.70          | 36.11         | 60.81          | 74.00          | 13.19       | 219       | PK       | PASS    | Horizontal |
| 4   | 2363.39     | 11.16          | 36.11         | 47.27          | 54.00          | 6.73        | 309       | AV       | PASS    | Horizontal |
| 5   | 2390.00     | 22.75          | 36.19         | 58.94          | 74.00          | 15.06       | 234       | PK       | PASS    | Horizontal |
| 6   | 2390.00     | 11.04          | 36.19         | 47.23          | 54.00          | 6.77        | 88        | AV       | PASS    | Horizontal |

#### Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

|               |                 |                |              |
|---------------|-----------------|----------------|--------------|
| Product Name: | Mobile Phone    | Product Model: | C681L        |
| Test By:      | Vic Duan        | Test mode:     | 3DH1 Tx mode |
| Test Channel: | Highest channel | Polarization:  | Vertical     |
| Test Voltage: | DC 3.91V        |                |              |




#### Suspected Data List

| NO. | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Verdict | Polarity |
|-----|-------------|----------------|---------------|----------------|----------------|-------------|-----------|----------|---------|----------|
| 1   | 2483.50     | 22.90          | 36.24         | 59.14          | 74.00          | 14.86       | 344       | PK       | PASS    | Vertical |
| 2   | 2483.50     | 11.26          | 36.24         | 47.50          | 54.00          | 6.50        | 118       | AV       | PASS    | Vertical |
| 3   | 2491.53     | 10.93          | 36.31         | 47.24          | 54.00          | 6.76        | 330       | AV       | PASS    | Vertical |
| 4   | 2491.53     | 23.37          | 36.31         | 59.68          | 74.00          | 14.32       | 299       | PK       | PASS    | Vertical |
| 5   | 2497.43     | 24.36          | 36.36         | 60.72          | 74.00          | 13.28       | 142       | PK       | PASS    | Vertical |
| 6   | 2497.43     | 10.95          | 36.36         | 47.31          | 54.00          | 6.69        | 306       | AV       | PASS    | Vertical |

#### Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

|                      |                 |                       |              |
|----------------------|-----------------|-----------------------|--------------|
| <b>Product Name:</b> | Mobile Phone    | <b>Product Model:</b> | C681L        |
| <b>Test By:</b>      | Vic Duan        | <b>Test mode:</b>     | 3DH1 Tx mode |
| <b>Test Channel:</b> | Highest channel | <b>Polarization:</b>  | Horizontal   |
| <b>Test Voltage:</b> | DC 3.91V        |                       |              |



#### Suspected Data List

| NO. | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Verdict | Polarity   |
|-----|-------------|----------------|---------------|----------------|----------------|-------------|-----------|----------|---------|------------|
| 1   | 2483.50     | 22.11          | 36.24         | 58.35          | 74.00          | 15.65       | 292       | PK       | PASS    | Horizontal |
| 2   | 2483.50     | 11.01          | 36.24         | 47.25          | 54.00          | 6.75        | 2         | AV       | PASS    | Horizontal |
| 3   | 2490.65     | 10.95          | 36.30         | 47.25          | 54.00          | 6.75        | 277       | AV       | PASS    | Horizontal |
| 4   | 2490.65     | 24.02          | 36.30         | 60.32          | 74.00          | 13.68       | 292       | PK       | PASS    | Horizontal |
| 5   | 2497.89     | 24.02          | 36.36         | 60.38          | 74.00          | 13.62       | 322       | PK       | PASS    | Horizontal |
| 6   | 2497.89     | 10.97          | 36.36         | 47.33          | 54.00          | 6.67        | 266       | AV       | PASS    | Horizontal |

#### Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

#### REMARKS:

- Emission level (dBμV/m) = Reading (dBμV)+ Factor (dB/m)
- Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
- Margin value = Emission level- Limit value.
- Mean the PK detector measured value is below average limit.
- Other emission levels are attenuated 20dB below the limit and not recorded in report.
- RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.

### 3.3 Maximum Peak Output Power

#### Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels: 1 watt.


For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

#### Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer. According to ANSI C63.10:2020 Output power test procedure for frequency-hopping spread-spectrum (FHSS) devices; this is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. The hopping shall be disabled for this test:

- a) Use the following spectrum analyzer settings:
  - 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
  - 2) RBW > 20 dB bandwidth of the emission being measured.
  - 3) VBW  $\geq$  RBW.
  - 4) Sweep: Auto.
  - 5) Detector function: Peak.
  - 6) Trace: Max hold.
- b) Allow trace to stabilize.
- c) Use the marker-to-peak function to set the marker to the peak of the emission.
- d) The indicated level is the peak output power, after any corrections for external attenuators and cables.

#### Test Configuration



#### Test Results

☒ Pass ☐ Not Applicable

Note:

For test data, please refer to Appendix RF test data for BT.

### 3.4 20dB Bandwidth

#### Limit

For frequency hopping systems operating in the 2400MHz-2483.5MHz no limit for 20dB bandwidth.

#### Test Procedure


Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer. Place the EUT on the table and set it in transmitting mode.

Use the following spectrum analyzer settings:

- 1) Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel.
- 2) RBW  $\geq 1\%$  of the 20 dB bandwidth, VBW  $\geq$  RBW.
- 3) Detector function = peak.
- 4) Trace = max hold.

The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

#### Test Configuration



#### Test Results

☒ Pass ☐ Not Applicable

Note:

For test data, please refer to Appendix RF test data for BT.

### 3.5 Occupied Bandwidth

#### Limit

N/A

#### Test Procedure

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

RBW=1% to 5% of the OBW


VBW=approximately 3 X RBW

Detector=Peak

Trace Mode: Max Hold

Use the 99% power bandwidth function of the instrument to measure the Occupied Bandwidth and recorded.

#### Test Configuration



#### Test Results

☒ Pass ☐ Not Applicable

Note:  
For test data, please refer to Appendix RF test data for BT.

### 3.6 Frequency Separation

#### LIMIT

Frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25KHz or the  $2/3 \times 20\text{dB}$  bandwidth of the hopping channel, whichever is greater.


#### Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer. Place the EUT on the table and set it in hopping mode.

- Span: Wide enough to capture the peaks of two adjacent channels.
- RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- $\text{VBW} \geq \text{RBW}$ .
- Sweep: Auto.
- Detector function: Peak.
- Trace: Max hold.
- Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

#### TEST CONFIGURATION



#### TEST RESULTS

Passed

☒ Pass ☐ Not Applicable

Note:

For test data, please refer to Appendix RF test data for BT.

### 3.7 Number of hopping frequency

#### Limit

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.


#### Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer. Place the EUT on the table and set it in hopping mode.

Use the following spectrum analyzer settings:

- Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- VBW  $\geq$  RBW.
- Sweep: Auto.
- Detector function: Peak.
- Trace: Max hold.
- Allow the trace to stabilize.
- Count how many channel in the band.

#### Test Configuration



#### Test Results

Passed

☒ Pass ☐ Not Applicable

Note:

For test data, please refer to Appendix RF test data for BT.

### 3.8 Time of Occupancy (Dwell Time)

#### Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

#### Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer. Place the EUT on the table and set it in hopping mode.

Use the following spectrum analyzer settings:


- Set center frequency of Spectrum Analyzer = operating frequency.
- Span: Zero span.
- RBW shall be  $\leq$  channel spacing and where possible RBW should be set  $\gg 1 / T$ , where T is the expected dwell time per channel.
- $VBW \geq RBW$
- Sweep: Single Sweep
- Detector function: Peak.

Use the marker-delta function to determine the transmit time per hop.

Repeat the measurement using a longer sweep time(31.6s) to determine the number of hops over the period specified in the requirements.

The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements.

#### Test Configuration



#### Test Results

**Passed**

☒ **Pass**      ☐ **Not Applicable**

Note:

For test data, please refer to Appendix RF test data for BT.

### 3.9 Out-of-band Emissions

#### **Limit**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

#### **Test Procedure**

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer. Place the EUT on the table and set it in transmitting mode.

##### **Step 1: Reference level measurement using the following procedure:**

- a) Set instrument center frequency to channel center frequency.
- b) Set the span to  $\geq 1.5$  times the bandwidth.
- c) Set the RBW = 100 kHz.
- d) Set the VBW  $\geq [3 \times \text{RBW}]$ .
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum PSD level.


Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

##### **Step 2: Emission level measurement using the following procedure:**

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW  $\geq [3 \times \text{RBW}]$ .
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements of PSD level measured in step 1 Reference level measurement.

## Test Configuration



## Test Results

**Passed**

☒ **Pass**      ☐ **Not Applicable**

Note:

For test data, please refer to Appendix RF test data for BT.

### 3.10 Pseudorandom Frequency Hopping Sequence

#### TEST APPLICABLE


##### **For 47 CFR Part 15C section 15.247 (a) (1) RSS-247§5.1 requirement:**

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hop-ping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hop-ping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

#### **EUT Pseudorandom Frequency Hopping Sequence Requirement**


The pseudorandom frequency hopping sequence may be generated in a nine-stage shift register whose 5<sup>th</sup> and 9<sup>th</sup> stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones, for example: the shift register is initialized with nine ones.

- Number of shift register stages:9
- Length of pseudo-random sequence:29-1=511 bits
- Longest sequence of zeros:8(non-inverted signal)



*Linear Feedback Shift Register for Generation of the PRBS sequence*

An example of pseudorandom frequency hopping sequence as follows:



Each frequency used equally one the average by each transmitter.

The system receiver has input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shift frequencies in synchronization with the transmitted signals.

### 3.11 Antenna Requirement

#### Standard Applicable

**For intentional device, according to FCC 47 CFR Section 15.203:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited

**FCC CFR Title 47 Part 15 Subpart C Section 15.247(b) (4):**

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### Test Result

The maximum gain of antenna was -1.55dBi with impedance 50Ω.

\*\*\*\*\* End of Report \*\*\*\*\*