

Appendix A: Effective (Isotropic) Radiated Power Output Data

Test Result

Band	Channel	PCL	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
GSM850	128	5	32.16	23.01	38.45	PASS
GSM850	190	5	32.27	23.12	38.45	PASS
GSM850	251	5	33.29	24.14	38.45	PASS
GSM1900	512	0	29.01	27.01	33.00	PASS
GSM1900	661	0	28.75	26.75	33.00	PASS
GSM1900	810	0	28.47	26.47	33.00	PASS

Band	Channel	PCL	Slot	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
GPRS850	128	5	1	32.14	22.99	38.45	PASS
GPRS850	128	5	2	32.61	23.46	38.45	PASS
GPRS850	128	5	3	30.37	21.22	38.45	PASS
GPRS850	128	5	4	30.21	21.06	38.45	PASS
GPRS850	190	5	1	32.23	23.08	38.45	PASS
GPRS850	190	5	2	32.37	23.22	38.45	PASS
GPRS850	190	5	3	30.14	20.99	38.45	PASS
GPRS850	190	5	4	29.97	20.82	38.45	PASS
GPRS850	251	5	1	33.22	24.07	38.45	PASS
GPRS850	251	5	2	32.09	22.94	38.45	PASS
GPRS850	251	5	3	29.83	20.68	38.45	PASS
GPRS850	251	5	4	29.69	20.54	38.45	PASS
GPRS1900	512	0	1	29.08	27.08	33.00	PASS
GPRS1900	512	0	2	28.45	26.45	33.00	PASS
GPRS1900	512	0	3	26.84	24.84	33.00	PASS
GPRS1900	512	0	4	26.64	24.64	33.00	PASS
GPRS1900	661	0	1	28.78	26.78	33.00	PASS
GPRS1900	661	0	2	28.25	26.25	33.00	PASS
GPRS1900	661	0	3	26.74	24.74	33.00	PASS
GPRS1900	661	0	4	26.58	24.58	33.00	PASS
GPRS1900	810	0	1	28.47	26.47	33.00	PASS
GPRS1900	810	0	2	27.99	25.99	33.00	PASS
GPRS1900	810	0	3	26.58	24.58	33.00	PASS
GPRS1900	810	0	4	26.48	24.48	33.00	PASS

Band	Channel	PCL	Slot	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
EGPRS850	128	8	1	26.70	17.55	38.45	PASS
EGPRS850	128	8	2	25.54	16.39	38.45	PASS
EGPRS850	128	8	3	23.39	14.24	38.45	PASS
EGPRS850	128	8	4	22.00	12.85	38.45	PASS
EGPRS850	190	8	1	26.35	17.2	38.45	PASS
EGPRS850	190	8	2	25.30	16.15	38.45	PASS
EGPRS850	190	8	3	23.10	13.95	38.45	PASS
EGPRS850	190	8	4	21.74	12.59	38.45	PASS
EGPRS850	251	8	1	26.50	17.35	38.45	PASS
EGPRS850	251	8	2	25.33	16.18	38.45	PASS
EGPRS850	251	8	3	23.12	13.97	38.45	PASS
EGPRS850	251	8	4	21.66	12.51	38.45	PASS
EGPRS1900	512	2	1	24.70	22.7	33.00	PASS
EGPRS1900	512	2	2	23.56	21.56	33.00	PASS
EGPRS1900	512	2	3	21.46	19.46	33.00	PASS
EGPRS1900	512	2	4	20.06	18.06	33.00	PASS
EGPRS1900	661	2	1	24.92	22.92	33.00	PASS
EGPRS1900	661	2	2	23.80	21.8	33.00	PASS
EGPRS1900	661	2	3	21.68	19.68	33.00	PASS
EGPRS1900	661	2	4	20.26	18.26	33.00	PASS
EGPRS1900	810	2	1	25.59	23.59	33.00	PASS
EGPRS1900	810	2	2	24.52	22.52	33.00	PASS
EGPRS1900	810	2	3	22.37	20.37	33.00	PASS
EGPRS1900	810	2	4	20.94	18.94	33.00	PASS

Remark: EIRP (dBm) = Conducted power (dBm) + Antenna Gain (dBi). (For GSM1900)

ERP (dBm) = EIRP (dBm) - 2.15 (dB). (For GSM850)


Appendix B: Peak-to-Average Ratio(CCDF)

Test Result

Band	Channel	PCL	Result(dB)	Limit(dB)	Verdict
GSM850	190	5	3.86	13	PASS
EGPRS850	190	8	5.52	13	PASS
GSM1900	661	0	2.66	13	PASS
EGPRS1900	661	2	5.3	13	PASS

Remark: All channel and all modulation had been tested, but only the worst case data displayed in this report.

Test Graphs





Appendix C: 26dB Bandwidth and Occupied Bandwidth

Test Result

Band	Channel	PCL	Occupied Bandwidth (MHz)	26dB Bandwidth (MHz)	Limit (MHz)	Verdict
GSM850	128	5	0.24348	0.3104	---	PASS
GSM850	190	5	0.24720	0.3100	---	PASS
GSM850	251	5	0.24504	0.3123	---	PASS
EGPRS850	128	8	0.25093	0.3180	---	PASS
EGPRS850	190	8	0.25261	0.3203	---	PASS
EGPRS850	251	8	0.24986	0.3099	---	PASS
GSM1900	512	0	0.24562	0.3102	---	PASS
GSM1900	661	0	0.24464	0.3109	---	PASS
GSM1900	810	0	0.24534	0.3157	---	PASS
EGPRS1900	512	2	0.24928	0.3247	---	PASS
EGPRS1900	661	2	0.25385	0.3265	---	PASS
EGPRS1900	810	2	0.25403	0.3374	---	PASS

Test Graphs







Appendix D: Band Edge

Test Result

Band	Channel	PCL	Freq (MHz)	Result (dBm)	Limit(dBm)	Verdict
GSM850	128	5	824.00	-25.39	-13	PASS
GSM850	251	5	849.02	-23.30	-13	PASS
EGPRS850	128	8	824.00	-34.30	-13	PASS
EGPRS850	251	8	849.00	-32.86	-13	PASS
GSM1900	512	0	1849.98	-14.85	-13	PASS
GSM1900	810	0	1910.02	-14.61	-13	PASS
EGPRS1900	512	2	1849.99	-20.01	-13	PASS
EGPRS1900	810	2	1910.00	-18.32	-13	PASS

Test Graphs






Appendix E: Conducted Spurious Emission

Test Result

Band	Channel	PCL	Frequency Range(MHz)	Max.Freq. (MHz)	Result (dBm)	Limit (dBm)	Verdict
GSM850	128	5	0.009~0.15MHz	0.01	-55.13	-33	PASS
GSM850	128	5	0.15~30MHz	0.15	-44.42	-13	PASS
GSM850	128	5	30~1000MHz	940.54	-44.37	-13	PASS
GSM850	128	5	1000~10000MHz	1648	-30.67	-13	PASS
GSM850	190	5	0.009~0.15MHz	0.01	-56.07	-33	PASS
GSM850	190	5	0.15~30MHz	0.15	-42.73	-13	PASS
GSM850	190	5	30~1000MHz	947.62	-44.53	-13	PASS
GSM850	190	5	1000~10000MHz	1673.2	-30.81	-13	PASS
GSM850	251	5	0.009~0.15MHz	0.01	-54.88	-33	PASS
GSM850	251	5	0.15~30MHz	0.16	-44.56	-13	PASS
GSM850	251	5	30~1000MHz	960.94	-45.08	-13	PASS
GSM850	251	5	1000~10000MHz	2546.8	-29.79	-13	PASS
GSM1900	512	0	0.009~0.15MHz	0.01	-56.82	-43	PASS
GSM1900	512	0	0.15~30MHz	0.15	-42.91	-23	PASS
GSM1900	512	0	30~1000MHz	981.99	-45.4	-13	PASS
GSM1900	512	0	1000~18000MHz	16141.33	-22.05	-13	PASS
GSM1900	661	0	0.009~0.15MHz	0.01	-56.05	-43	PASS
GSM1900	661	0	0.15~30MHz	0.16	-42.36	-23	PASS
GSM1900	661	0	30~1000MHz	844.67	-46.2	-13	PASS
GSM1900	661	0	1000~18000MHz	16973.77	-22.29	-13	PASS
GSM1900	810	0	0.009~0.15MHz	0.01	-56.02	-43	PASS
GSM1900	810	0	0.15~30MHz	0.16	-45.3	-23	PASS
GSM1900	810	0	30~1000MHz	862.32	-45.22	-13	PASS
GSM1900	810	0	1000~18000MHz	16972.63	-22.42	-13	PASS

Remark: All channel and all modulation had been tested, but only the worst case data displayed in this report.

Test Graphs





JianYan Testing Group Shenzhen Co., Ltd.


No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Project No.: JYTSZR2312022







Appendix F: Frequency Stability

Test Result

Reference Frequency: GSM850 Middle channel=190 Frequency=836.6MHz					
Temperature					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.91	-30	2.62	0.003132	±2.5	Pass
	-20	4.26	0.005092		
	-10	1.13	0.001351		
	0	3.87	0.004626		
	10	1.45	0.001733		
	20	4.52	0.005403		
	30	4.49	0.005367		
	40	1.16	0.001387		
	50	0.45	0.000538		
Voltage					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.45	3.07	0.003670	±2.5	Pass
	3.91	2.78	0.003323		
	4.50	4.55	0.005439		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Reference Frequency: EGPRS850 Middle channel=190 Frequency=836.6MHz					
Temperature					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.91	-30	-5.71	-0.006825	±2.5	Pass
	-20	-4.91	-0.005869		
	-10	-2.03	-0.002426		
	0	-4.29	-0.005128		
	10	1.19	0.001422		
	20	1.16	0.001387		
	30	3.68	0.004399		
	40	0.58	0.000693		
	50	2.62	0.003132		
Voltage					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.45	-3.13	-0.003741	±2.5	Pass
	3.91	-2.65	-0.003168		
	4.50	-3.55	-0.004243		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Reference Frequency: PCS1900 Middle channel=661 Frequency=1880MHz					
Temperature					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.91	-30	-13.20	-0.007021	Within authorized band for PCS 1900	Pass
	-20	-15.34	-0.008160		
	-10	-16.85	-0.008963		
	0	-8.33	-0.004431		
	10	-19.08	-0.010149		
	20	-9.56	-0.005085		
	30	-9.69	-0.005154		
	40	-12.07	-0.006420		
	50	-21.28	-0.011319		
Voltage					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.45	-13.14	-0.006989	Within authorized band for PCS 1900	Pass
	3.91	-17.92	-0.009532		
	4.50	-14.66	-0.007798		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Reference Frequency: EGPRS1900 Middle channel=661 Frequency=1880MHz					
Temperature					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.91	-30	-29.22	-0.015543	Within authorized band for PCS 1900	Pass
	-20	-31.06	-0.016521		
	-10	-29.99	-0.015952		
	0	-30.35	-0.016144		
	10	-29.32	-0.015596		
	20	-26.99	-0.014356		
	30	-24.86	-0.013223		
	40	-32.74	-0.017415		
	50	-26.31	-0.013995		
Voltage					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.45	-24.50	-0.013032	Within authorized band for PCS 1900	Pass
	3.91	-29.90	-0.015904		
	4.50	-30.77	-0.016367		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Appendix G: Modulation Characteristics

Test Result

Band	Channel	Result	Verdict
GSM850	190	PASS	PASS
EGPRS850	190	PASS	PASS
GSM1900	661	PASS	PASS
EGPRS1900	661	PASS	PASS

Remark: All channel had been tested, but only the worst case data displayed in this report.

Test Graphs

