

| UID   | Rev | Communication System Name                                            | Group    | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|----------------------------------------------------------------------|----------|----------|------------------------|
| 10225 | CAC | UMTS-FDD (HSPA+)                                                     | WCDMA    | 5.97     | ±9.6                   |
| 10226 | CAC | LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)                             | LTE-TDD  | 9.49     | ±9.6                   |
| 10227 | CAC | LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)                             | LTE-TDD  | 10.26    | ±9.6                   |
| 10228 | CAC | LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)                               | LTE-TDD  | 9.22     | ±9.6                   |
| 10229 | CAE | LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)                               | LTE-TDD  | 9.48     | ±9.6                   |
| 10230 | CAE | LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)                               | LTE-TDD  | 10.25    | ±9.6                   |
| 10231 | CAE | LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK)                                 | LTE-TDD  | 9.19     | ±9.6                   |
| 10232 | CAH | LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)                               | LTE-TDD  | 9.48     | ±9.6                   |
| 10233 | CAH | LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)                               | LTE-TDD  | 10.25    | ±9.6                   |
| 10234 | CAH | LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK)                                 | LTE-TDD  | 9.21     | ±9.6                   |
| 10235 | CAH | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)                              | LTE-TDD  | 9.48     | ±9.6                   |
| 10236 | CAH | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)                              | LTE-TDD  | 10.25    | ±9.6                   |
| 10237 | CAH | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)                                | LTE-TDD  | 9.21     | ±9.6                   |
| 10238 | CAG | LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)                              | LTE-TDD  | 9.48     | ±9.6                   |
| 10239 | CAG | LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)                              | LTE-TDD  | 10.25    | ±9.6                   |
| 10240 | CAG | LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK)                                | LTE-TDD  | 9.21     | ±9.6                   |
| 10241 | CAC | LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)                           | LTE-TDD  | 9.82     | ±9.6                   |
| 10242 | CAC | LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)                           | LTE-TDD  | 9.86     | ±9.6                   |
| 10243 | CAC | LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)                             | LTE-TDD  | 9.46     | ±9.6                   |
| 10244 | CAE | LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)                             | LTE-TDD  | 10.06    | ±9.6                   |
| 10245 | CAE | LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)                             | LTE-TDD  | 10.06    | ±9.6                   |
| 10246 | CAE | LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK)                               | LTE-TDD  | 9.30     | ±9.6                   |
| 10247 | CAH | LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)                             | LTE-TDD  | 9.91     | ±9.6                   |
| 10248 | CAH | LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)                             | LTE-TDD  | 10.09    | ±9.6                   |
| 10249 | CAH | LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK)                               | LTE-TDD  | 9.29     | ±9.6                   |
| 10250 | CAH | LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)                            | LTE-TDD  | 9.81     | ±9.6                   |
| 10251 | CAH | LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)                            | LTE-TDD  | 10.17    | ±9.6                   |
| 10252 | CAH | LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)                              | LTE-TDD  | 9.24     | ±9.6                   |
| 10253 | CAG | LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)                            | LTE-TDD  | 9.90     | ±9.6                   |
| 10254 | CAG | LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)                            | LTE-TDD  | 10.14    | ±9.6                   |
| 10255 | CAG | LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK)                              | LTE-TDD  | 9.20     | ±9.6                   |
| 10256 | CAC | LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)                          | LTE-TDD  | 9.96     | ±9.6                   |
| 10257 | CAC | LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)                          | LTE-TDD  | 10.08    | ±9.6                   |
| 10258 | CAC | LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)                            | LTE-TDD  | 9.34     | ±9.6                   |
| 10259 | CAE | LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)                            | LTE-TDD  | 9.98     | ±9.6                   |
| 10260 | CAE | LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)                            | LTE-TDD  | 9.97     | ±9.6                   |
| 10261 | CAE | LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK)                              | LTE-TDD  | 9.24     | ±9.6                   |
| 10262 | CAH | LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)                            | LTE-TDD  | 9.83     | ±9.6                   |
| 10263 | CAH | LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)                            | LTE-TDD  | 10.16    | ±9.6                   |
| 10264 | CAH | LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK)                              | LTE-TDD  | 9.23     | ±9.6                   |
| 10265 | CAH | LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)                           | LTE-TDD  | 9.92     | ±9.6                   |
| 10266 | CAH | LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)                           | LTE-TDD  | 10.07    | ±9.6                   |
| 10267 | CAH | LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)                             | LTE-TDD  | 9.30     | ±9.6                   |
| 10268 | CAG | LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)                           | LTE-TDD  | 10.06    | ±9.6                   |
| 10269 | CAG | LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)                           | LTE-TDD  | 10.13    | ±9.6                   |
| 10270 | CAG | LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK)                             | LTE-TDD  | 9.58     | ±9.6                   |
| 10274 | CAC | UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.10)                            | WCDMA    | 4.87     | ±9.6                   |
| 10275 | CAC | UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.4)                             | WCDMA    | 3.95     | ±9.6                   |
| 10277 | CAA | PHS (QPSK)                                                           | PHS      | 11.81    | ±9.6                   |
| 10278 | CAA | PHS (QPSK, BW 884 MHz, Roll-off 0.5)                                 | PHS      | 11.81    | ±9.6                   |
| 10279 | CAA | PHS (QPSK, BW 884 MHz, Roll-off 0.38)                                | PHS      | 12.18    | ±9.6                   |
| 10290 | AAB | CDMA2000, RC1, SO55, Full Rate                                       | CDMA2000 | 3.91     | ±9.6                   |
| 10291 | AAB | CDMA2000, RC3, SO55, Full Rate                                       | CDMA2000 | 3.46     | ±9.6                   |
| 10292 | AAB | CDMA2000, RC3, SO32, Full Rate                                       | CDMA2000 | 3.39     | ±9.6                   |
| 10293 | AAB | CDMA2000, RC3, SO3, Full Rate                                        | CDMA2000 | 3.50     | ±9.6                   |
| 10295 | AAB | CDMA2000, RC1, SO3, 1/8th Rate 25 tr.                                | CDMA2000 | 12.49    | ±9.6                   |
| 10297 | AAE | LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)                              | LTE-FDD  | 5.81     | ±9.6                   |
| 10298 | AAE | LTE-FDD (SC-FDMA, 50% RB, 3 MHz, QPSK)                               | LTE-FDD  | 5.72     | ±9.6                   |
| 10299 | AAE | LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)                             | LTE-FDD  | 6.39     | ±9.6                   |
| 10300 | AAE | LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)                             | LTE-FDD  | 6.60     | ±9.6                   |
| 10301 | AAA | IEEE 802.16e WiMAX (29:18, 5 ms, 10 MHz, QPSK, PUSC)                 | WiMAX    | 12.03    | ±9.6                   |
| 10302 | AAA | IEEE 802.16e WiMAX (29:18, 5 ms, 10 MHz, QPSK, PUSC, 3 CTRL symbols) | WiMAX    | 12.57    | ±9.6                   |
| 10303 | AAA | IEEE 802.16e WiMAX (31:15, 5 ms, 10 MHz, 64QAM, PUSC)                | WiMAX    | 12.52    | ±9.6                   |
| 10304 | AAA | IEEE 802.16e WiMAX (29:18, 5 ms, 10 MHz, 64QAM, PUSC)                | WiMAX    | 11.86    | ±9.6                   |
| 10305 | AAA | IEEE 802.16e WiMAX (31:15, 10 ms, 10 MHz, 64QAM, PUSC, 15 symbols)   | WiMAX    | 15.24    | ±9.6                   |
| 10306 | AAA | IEEE 802.16e WiMAX (29:18, 10 ms, 10 MHz, 64QAM, PUSC, 18 symbols)   | WiMAX    | 14.67    | ±9.6                   |

| UID   | Rev | Communication System Name                                                       | Group    | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|---------------------------------------------------------------------------------|----------|----------|------------------------|
| 10307 | AAA | IEEE 802.16e WiMAX (29:18, 10 ms, 10 MHz, QPSK, PUSC, 18 symbols)               | WiMAX    | 14.49    | ±9.6                   |
| 10308 | AAA | IEEE 802.16e WiMAX (29:18, 10 ms, 10 MHz, 16QAM, PUSC)                          | WiMAX    | 14.46    | ±9.6                   |
| 10309 | AAA | IEEE 802.16e WiMAX (29:18, 10 ms, 10 MHz, 16QAM, AMC 2x3, 18 symbols)           | WiMAX    | 14.58    | ±9.6                   |
| 10310 | AAA | IEEE 802.16e WiMAX (29:18, 10 ms, 10 MHz, QPSK, AMC 2x3, 18 symbols)            | WiMAX    | 14.57    | ±9.6                   |
| 10311 | AAE | LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)                                        | LTE-FDD  | 6.06     | ±9.6                   |
| 10313 | AAA | IDEN 1.3                                                                        | IDEN     | 10.51    | ±9.6                   |
| 10314 | AAA | IDEN 1.6                                                                        | IDEN     | 13.48    | ±9.6                   |
| 10315 | AAB | IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 96pc duty cycle)                       | WLAN     | 1.71     | ±9.6                   |
| 10316 | AAB | IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 96pc duty cycle)                   | WLAN     | 8.36     | ±9.6                   |
| 10317 | AAE | IEEE 802.11a WiFi 5 GHz (OFDM, 6 Mbps, 96pc duty cycle)                         | WLAN     | 8.36     | ±9.6                   |
| 10352 | AAA | Pulse Waveform (200Hz, 10%)                                                     | Generic  | 10.00    | ±9.6                   |
| 10353 | AAA | Pulse Waveform (200Hz, 20%)                                                     | Generic  | 6.99     | ±9.6                   |
| 10354 | AAA | Pulse Waveform (200Hz, 40%)                                                     | Generic  | 3.98     | ±9.6                   |
| 10355 | AAA | Pulse Waveform (200Hz, 60%)                                                     | Generic  | 2.22     | ±9.6                   |
| 10356 | AAA | Pulse Waveform (200Hz, 80%)                                                     | Generic  | 0.97     | ±9.6                   |
| 10387 | AAA | QPSK Waveform, 1 MHz                                                            | Generic  | 5.10     | ±9.6                   |
| 10388 | AAA | QPSK Waveform, 10 MHz                                                           | Generic  | 5.22     | ±9.6                   |
| 10396 | AAA | 64-QAM Waveform, 100 kHz                                                        | Generic  | 6.27     | ±9.6                   |
| 10399 | AAA | 64-QAM Waveform, 40 MHz                                                         | Generic  | 6.27     | ±9.6                   |
| 10400 | AAF | IEEE 802.11ac WiFi (20 MHz, 64-QAM, 99pc duty cycle)                            | WLAN     | 8.37     | ±9.6                   |
| 10401 | AAF | IEEE 802.11ac WiFi (40 MHz, 64-QAM, 99pc duty cycle)                            | WLAN     | 8.60     | ±9.6                   |
| 10402 | AAF | IEEE 802.11ac WiFi (80 MHz, 64-QAM, 99pc duty cycle)                            | WLAN     | 8.53     | ±9.6                   |
| 10403 | AAB | CDMA2000 (1xEV-DO, Rev. 0)                                                      | CDMA2000 | 3.76     | ±9.6                   |
| 10404 | AAB | CDMA2000 (1xEV-DO, Rev. A)                                                      | CDMA2000 | 3.77     | ±9.6                   |
| 10406 | AAB | CDMA2000, RC3, SC32, SCH0, Full Rate                                            | CDMA2000 | 5.22     | ±9.6                   |
| 10410 | AAH | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9, Subframe Conf=4) | LTE-TDD  | 7.82     | ±9.6                   |
| 10414 | AAA | WLAN CCDF, 64-QAM, 40 MHz                                                       | Generic  | 8.54     | ±9.6                   |
| 10415 | AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 99pc duty cycle)                       | WLAN     | 1.54     | ±9.6                   |
| 10416 | AAA | IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 99pc duty cycle)                   | WLAN     | 8.23     | ±9.6                   |
| 10417 | AAD | IEEE 802.11a/n WiFi 5 GHz (OFDM, 6 Mbps, 99pc duty cycle)                       | WLAN     | 8.23     | ±9.6                   |
| 10418 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Long preamble)   | WLAN     | 8.14     | ±9.6                   |
| 10419 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Short preamble)  | WLAN     | 8.19     | ±9.6                   |
| 10422 | AAD | IEEE 802.11n (HT Greenfield, 7.2 Mbps, BPSK)                                    | WLAN     | 8.32     | ±9.6                   |
| 10423 | AAD | IEEE 802.11n (HT Greenfield, 43.3 Mbps, 16-QAM)                                 | WLAN     | 8.47     | ±9.6                   |
| 10424 | AAD | IEEE 802.11n (HT Greenfield, 72.2 Mbps, 64-QAM)                                 | WLAN     | 8.40     | ±9.6                   |
| 10425 | AAD | IEEE 802.11n (HT Greenfield, 15 Mbps, BPSK)                                     | WLAN     | 8.41     | ±9.6                   |
| 10426 | AAD | IEEE 802.11n (HT Greenfield, 90 Mbps, 16-QAM)                                   | WLAN     | 8.45     | ±9.6                   |
| 10427 | AAD | IEEE 802.11n (HT Greenfield, 150 Mbps, 64-QAM)                                  | WLAN     | 8.41     | ±9.6                   |
| 10430 | AAE | LTE-FDD (OFDMA, 5 MHz, E-TM 3.1)                                                | LTE-FDD  | 8.28     | ±9.6                   |
| 10431 | AAE | LTE-FDD (OFDMA, 10 MHz, E-TM 3.1)                                               | LTE-FDD  | 8.38     | ±9.6                   |
| 10432 | AAD | LTE-FDD (OFDMA, 15 MHz, E-TM 3.1)                                               | LTE-FDD  | 8.34     | ±9.6                   |
| 10433 | AAD | LTE-FDD (OFDMA, 20 MHz, E-TM 3.1)                                               | LTE-FDD  | 8.34     | ±9.6                   |
| 10434 | AAB | W-CDMA (BS Test Model 1, 64 DPCH)                                               | WCDMA    | 8.60     | ±9.6                   |
| 10435 | AAG | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)                  | LTE-TDD  | 7.82     | ±9.6                   |
| 10447 | AAE | LTE-FDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)                                  | LTE-FDD  | 7.56     | ±9.6                   |
| 10448 | AAE | LTE-FDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)                                 | LTE-FDD  | 7.53     | ±9.6                   |
| 10449 | AAD | LTE-FDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)                                 | LTE-FDD  | 7.51     | ±9.6                   |
| 10450 | AAD | LTE-FDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)                                 | LTE-FDD  | 7.48     | ±9.6                   |
| 10451 | AAB | W-CDMA (BS Test Model 1, 64 DPCH, Clipping 44%)                                 | WCDMA    | 7.59     | ±9.6                   |
| 10453 | AAE | Validation (Square, 10 ms, 1 ms)                                                | Test     | 10.00    | ±9.6                   |
| 10456 | AAD | IEEE 802.11ac WiFi (160 MHz, 64-QAM, 99pc duty cycle)                           | WLAN     | 8.63     | ±9.6                   |
| 10457 | AAB | UMTS-FDD (DC-HSDPA)                                                             | WCDMA    | 6.62     | ±9.6                   |
| 10458 | AAA | CDMA2000 (1xEV-DO, Rev. B, 2 carriers)                                          | CDMA2000 | 6.55     | ±9.6                   |
| 10459 | AAA | CDMA2000 (1xEV-DO, Rev. B, 3 carriers)                                          | CDMA2000 | 8.25     | ±9.6                   |
| 10460 | AAB | UMTS-FDD (WCDMA, AMR)                                                           | WCDMA    | 2.39     | ±9.6                   |
| 10461 | AAC | LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)                 | LTE-TDD  | 7.82     | ±9.6                   |
| 10462 | AAC | LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)               | LTE-TDD  | 8.30     | ±9.6                   |
| 10463 | AAC | LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)               | LTE-TDD  | 8.56     | ±9.6                   |
| 10464 | AAD | LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)                   | LTE-TDD  | 7.82     | ±9.6                   |
| 10465 | AAD | LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)                 | LTE-TDD  | 8.32     | ±9.6                   |
| 10466 | AAD | LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)                 | LTE-TDD  | 8.57     | ±9.6                   |
| 10467 | AAG | LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)                   | LTE-TDD  | 7.82     | ±9.6                   |
| 10468 | AAG | LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)                 | LTE-TDD  | 8.32     | ±9.6                   |
| 10469 | AAG | LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)                 | LTE-TDD  | 8.56     | ±9.6                   |
| 10470 | AAG | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)                  | LTE-TDD  | 7.82     | ±9.6                   |
| 10471 | AAG | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)                | LTE-TDD  | 8.32     | ±9.6                   |

| UID   | Rev | Communication System Name                                            | Group   | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|----------------------------------------------------------------------|---------|----------|------------------------|
| 10472 | AAG | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 8.57     | ±9.6                   |
| 10473 | AAF | LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)       | LTE-TDD | 7.82     | ±9.6                   |
| 10474 | AAF | LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 8.32     | ±9.6                   |
| 10475 | AAF | LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 8.57     | ±9.6                   |
| 10477 | AAG | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 8.32     | ±9.6                   |
| 10478 | AAG | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 8.57     | ±9.6                   |
| 10479 | AAC | LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)    | LTE-TDD | 7.74     | ±9.6                   |
| 10480 | AAC | LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)  | LTE-TDD | 8.18     | ±9.6                   |
| 10481 | AAC | LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)  | LTE-TDD | 8.45     | ±9.6                   |
| 10482 | AAD | LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)      | LTE-TDD | 7.71     | ±9.6                   |
| 10483 | AAD | LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)    | LTE-TDD | 8.39     | ±9.6                   |
| 10484 | AAD | LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)    | LTE-TDD | 8.47     | ±9.6                   |
| 10485 | AAG | LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)      | LTE-TDD | 7.59     | ±9.6                   |
| 10486 | AAG | LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)    | LTE-TDD | 8.38     | ±9.6                   |
| 10487 | AAG | LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)    | LTE-TDD | 8.60     | ±9.6                   |
| 10488 | AAG | LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 7.70     | ±9.6                   |
| 10489 | AAG | LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.31     | ±9.6                   |
| 10490 | AAG | LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.54     | ±9.6                   |
| 10491 | AAF | LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 7.74     | ±9.6                   |
| 10492 | AAF | LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.41     | ±9.6                   |
| 10493 | AAF | LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.55     | ±9.6                   |
| 10494 | AAG | LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 7.74     | ±9.6                   |
| 10495 | AAG | LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.37     | ±9.6                   |
| 10496 | AAG | LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.54     | ±9.6                   |
| 10497 | AAC | LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 7.67     | ±9.6                   |
| 10498 | AAC | LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9) | LTE-TDD | 8.40     | ±9.6                   |
| 10499 | AAC | LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9) | LTE-TDD | 8.68     | ±9.6                   |
| 10500 | AAD | LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 7.67     | ±9.6                   |
| 10501 | AAD | LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.44     | ±9.6                   |
| 10502 | AAD | LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.52     | ±9.6                   |
| 10503 | AAG | LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 7.72     | ±9.6                   |
| 10504 | AAG | LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.31     | ±9.6                   |
| 10505 | AAG | LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.54     | ±9.6                   |
| 10506 | AAG | LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)    | LTE-TDD | 7.74     | ±9.6                   |
| 10507 | AAG | LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)  | LTE-TDD | 8.36     | ±9.6                   |
| 10508 | AAG | LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)  | LTE-TDD | 8.55     | ±9.6                   |
| 10509 | AAF | LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)    | LTE-TDD | 7.99     | ±9.6                   |
| 10510 | AAF | LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)  | LTE-TDD | 8.49     | ±9.6                   |
| 10511 | AAF | LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)  | LTE-TDD | 8.51     | ±9.6                   |
| 10512 | AAG | LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)    | LTE-TDD | 7.74     | ±9.6                   |
| 10513 | AAG | LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)  | LTE-TDD | 8.42     | ±9.6                   |
| 10514 | AAG | LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)  | LTE-TDD | 8.45     | ±9.6                   |
| 10515 | AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 99pc duty cycle)            | WLAN    | 1.58     | ±9.6                   |
| 10516 | AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 99pc duty cycle)          | WLAN    | 1.57     | ±9.6                   |
| 10517 | AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 99pc duty cycle)           | WLAN    | 1.58     | ±9.6                   |
| 10518 | AAD | IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 99pc duty cycle)            | WLAN    | 8.23     | ±9.6                   |
| 10519 | AAD | IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 99pc duty cycle)           | WLAN    | 8.39     | ±9.6                   |
| 10520 | AAD | IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 99pc duty cycle)           | WLAN    | 8.12     | ±9.6                   |
| 10521 | AAD | IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 99pc duty cycle)           | WLAN    | 7.97     | ±9.6                   |
| 10522 | AAD | IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 99pc duty cycle)           | WLAN    | 8.45     | ±9.6                   |
| 10523 | AAD | IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 99pc duty cycle)           | WLAN    | 8.08     | ±9.6                   |
| 10524 | AAD | IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 99pc duty cycle)           | WLAN    | 8.27     | ±9.6                   |
| 10525 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS0, 99pc duty cycle)                   | WLAN    | 8.36     | ±9.6                   |
| 10526 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS1, 99pc duty cycle)                   | WLAN    | 8.42     | ±9.6                   |
| 10527 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS2, 99pc duty cycle)                   | WLAN    | 8.21     | ±9.6                   |
| 10528 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS3, 99pc duty cycle)                   | WLAN    | 8.36     | ±9.6                   |
| 10529 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS4, 99pc duty cycle)                   | WLAN    | 8.36     | ±9.6                   |
| 10530 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS6, 99pc duty cycle)                   | WLAN    | 8.43     | ±9.6                   |
| 10531 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS7, 99pc duty cycle)                   | WLAN    | 8.29     | ±9.6                   |
| 10532 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS8, 99pc duty cycle)                   | WLAN    | 8.38     | ±9.6                   |
| 10533 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS0, 99pc duty cycle)                   | WLAN    | 8.45     | ±9.6                   |
| 10534 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS1, 99pc duty cycle)                   | WLAN    | 8.45     | ±9.6                   |
| 10535 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS2, 99pc duty cycle)                   | WLAN    | 8.32     | ±9.6                   |
| 10536 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS3, 99pc duty cycle)                   | WLAN    | 8.44     | ±9.6                   |
| 10537 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS4, 99pc duty cycle)                   | WLAN    | 8.54     | ±9.6                   |
| 10538 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS5, 99pc duty cycle)                   | WLAN    | 8.39     | ±9.6                   |
| 10540 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS6, 99pc duty cycle)                   | WLAN    | 8.39     | ±9.6                   |

| UID   | Rev | Communication System Name                                       | Group | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|-----------------------------------------------------------------|-------|----------|------------------------|
| 10541 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS7, 99pc duty cycle)              | WLAN  | 8.46     | ±9.6                   |
| 10542 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS8, 99pc duty cycle)              | WLAN  | 8.65     | ±9.6                   |
| 10543 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS9, 99pc duty cycle)              | WLAN  | 8.65     | ±9.6                   |
| 10544 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS0, 99pc duty cycle)              | WLAN  | 8.47     | ±9.6                   |
| 10545 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS1, 99pc duty cycle)              | WLAN  | 8.55     | ±9.6                   |
| 10546 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS2, 99pc duty cycle)              | WLAN  | 8.35     | ±9.6                   |
| 10547 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS3, 99pc duty cycle)              | WLAN  | 8.49     | ±9.6                   |
| 10548 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS4, 99pc duty cycle)              | WLAN  | 8.37     | ±9.6                   |
| 10550 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS6, 99pc duty cycle)              | WLAN  | 8.38     | ±9.6                   |
| 10551 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS7, 99pc duty cycle)              | WLAN  | 8.50     | ±9.6                   |
| 10552 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS8, 99pc duty cycle)              | WLAN  | 8.42     | ±9.6                   |
| 10553 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS9, 99pc duty cycle)              | WLAN  | 8.45     | ±9.6                   |
| 10554 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS0, 99pc duty cycle)             | WLAN  | 8.48     | ±9.6                   |
| 10555 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS1, 99pc duty cycle)             | WLAN  | 8.47     | ±9.6                   |
| 10556 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS2, 99pc duty cycle)             | WLAN  | 8.50     | ±9.6                   |
| 10557 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS3, 99pc duty cycle)             | WLAN  | 8.52     | ±9.6                   |
| 10558 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS4, 99pc duty cycle)             | WLAN  | 8.61     | ±9.6                   |
| 10560 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS6, 99pc duty cycle)             | WLAN  | 8.73     | ±9.6                   |
| 10561 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS7, 99pc duty cycle)             | WLAN  | 8.56     | ±9.6                   |
| 10562 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS8, 99pc duty cycle)             | WLAN  | 8.69     | ±9.6                   |
| 10563 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS9, 99pc duty cycle)             | WLAN  | 8.77     | ±9.6                   |
| 10564 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 99pc duty cycle)  | WLAN  | 8.25     | ±9.6                   |
| 10565 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 99pc duty cycle) | WLAN  | 8.45     | ±9.6                   |
| 10566 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 99pc duty cycle) | WLAN  | 8.13     | ±9.6                   |
| 10567 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 99pc duty cycle) | WLAN  | 8.00     | ±9.6                   |
| 10568 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 99pc duty cycle) | WLAN  | 8.37     | ±9.6                   |
| 10569 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 99pc duty cycle) | WLAN  | 8.10     | ±9.6                   |
| 10570 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 99pc duty cycle) | WLAN  | 8.30     | ±9.6                   |
| 10571 | AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 90pc duty cycle)       | WLAN  | 1.99     | ±9.6                   |
| 10572 | AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 90pc duty cycle)       | WLAN  | 1.99     | ±9.6                   |
| 10573 | AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 90pc duty cycle)     | WLAN  | 1.98     | ±9.6                   |
| 10574 | AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 90pc duty cycle)      | WLAN  | 1.98     | ±9.6                   |
| 10575 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 90pc duty cycle)  | WLAN  | 8.59     | ±9.6                   |
| 10576 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 90pc duty cycle)  | WLAN  | 8.60     | ±9.6                   |
| 10577 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 90pc duty cycle) | WLAN  | 8.70     | ±9.6                   |
| 10578 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 90pc duty cycle) | WLAN  | 8.49     | ±9.6                   |
| 10579 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 90pc duty cycle) | WLAN  | 8.36     | ±9.6                   |
| 10580 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 90pc duty cycle) | WLAN  | 8.76     | ±9.6                   |
| 10581 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 90pc duty cycle) | WLAN  | 8.35     | ±9.6                   |
| 10582 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 90pc duty cycle) | WLAN  | 8.67     | ±9.6                   |
| 10583 | AAD | IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 90pc duty cycle)       | WLAN  | 8.59     | ±9.6                   |
| 10584 | AAD | IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 90pc duty cycle)       | WLAN  | 8.60     | ±9.6                   |
| 10585 | AAD | IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 90pc duty cycle)      | WLAN  | 8.70     | ±9.6                   |
| 10586 | AAD | IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 90pc duty cycle)      | WLAN  | 8.49     | ±9.6                   |
| 10587 | AAD | IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 90pc duty cycle)      | WLAN  | 8.36     | ±9.6                   |
| 10588 | AAD | IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 90pc duty cycle)      | WLAN  | 8.76     | ±9.6                   |
| 10589 | AAD | IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 90pc duty cycle)      | WLAN  | 8.35     | ±9.6                   |
| 10590 | AAD | IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 90pc duty cycle)      | WLAN  | 8.67     | ±9.6                   |
| 10591 | AAD | IEEE 802.11n (HT Mixed, 20 MHz, MCS0, 90pc duty cycle)          | WLAN  | 8.63     | ±9.6                   |
| 10592 | AAD | IEEE 802.11n (HT Mixed, 20 MHz, MCS1, 90pc duty cycle)          | WLAN  | 8.79     | ±9.6                   |
| 10593 | AAD | IEEE 802.11n (HT Mixed, 20 MHz, MCS2, 90pc duty cycle)          | WLAN  | 8.64     | ±9.6                   |
| 10594 | AAD | IEEE 802.11n (HT Mixed, 20 MHz, MCS3, 90pc duty cycle)          | WLAN  | 8.74     | ±9.6                   |
| 10595 | AAD | IEEE 802.11n (HT Mixed, 20 MHz, MCS4, 90pc duty cycle)          | WLAN  | 8.74     | ±9.6                   |
| 10596 | AAD | IEEE 802.11n (HT Mixed, 20 MHz, MCS5, 90pc duty cycle)          | WLAN  | 8.71     | ±9.6                   |
| 10597 | AAD | IEEE 802.11n (HT Mixed, 20 MHz, MCS6, 90pc duty cycle)          | WLAN  | 8.72     | ±9.6                   |
| 10598 | AAD | IEEE 802.11n (HT Mixed, 20 MHz, MCS7, 90pc duty cycle)          | WLAN  | 8.50     | ±9.6                   |
| 10599 | AAD | IEEE 802.11n (HT Mixed, 40 MHz, MCS0, 90pc duty cycle)          | WLAN  | 8.79     | ±9.6                   |
| 10600 | AAD | IEEE 802.11n (HT Mixed, 40 MHz, MCS1, 90pc duty cycle)          | WLAN  | 8.88     | ±9.6                   |
| 10601 | AAD | IEEE 802.11n (HT Mixed, 40 MHz, MCS2, 90pc duty cycle)          | WLAN  | 8.82     | ±9.6                   |
| 10602 | AAD | IEEE 802.11n (HT Mixed, 40 MHz, MCS3, 90pc duty cycle)          | WLAN  | 8.94     | ±9.6                   |
| 10603 | AAD | IEEE 802.11n (HT Mixed, 40 MHz, MCS4, 90pc duty cycle)          | WLAN  | 9.03     | ±9.6                   |
| 10604 | AAD | IEEE 802.11n (HT Mixed, 40 MHz, MCS5, 90pc duty cycle)          | WLAN  | 8.75     | ±9.6                   |
| 10605 | AAD | IEEE 802.11n (HT Mixed, 40 MHz, MCS6, 90pc duty cycle)          | WLAN  | 8.97     | ±9.6                   |
| 10606 | AAD | IEEE 802.11n (HT Mixed, 40 MHz, MCS7, 90pc duty cycle)          | WLAN  | 8.82     | ±9.6                   |
| 10607 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS0, 90pc duty cycle)              | WLAN  | 8.64     | ±9.6                   |
| 10608 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS1, 90pc duty cycle)              | WLAN  | 8.77     | ±9.6                   |

| UID   | Rev | Communication System Name                              | Group     | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|--------------------------------------------------------|-----------|----------|------------------------|
| 10609 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS2, 90pc duty cycle)     | WLAN      | 8.57     | ±9.6                   |
| 10610 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS3, 90pc duty cycle)     | WLAN      | 8.78     | ±9.6                   |
| 10611 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS4, 90pc duty cycle)     | WLAN      | 8.70     | ±9.6                   |
| 10612 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS5, 90pc duty cycle)     | WLAN      | 8.77     | ±9.6                   |
| 10613 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS6, 90pc duty cycle)     | WLAN      | 8.94     | ±9.6                   |
| 10614 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS7, 90pc duty cycle)     | WLAN      | 8.59     | ±9.6                   |
| 10615 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS8, 90pc duty cycle)     | WLAN      | 8.82     | ±9.6                   |
| 10616 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS0, 90pc duty cycle)     | WLAN      | 8.82     | ±9.6                   |
| 10617 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS1, 90pc duty cycle)     | WLAN      | 8.81     | ±9.6                   |
| 10618 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS2, 90pc duty cycle)     | WLAN      | 8.58     | ±9.6                   |
| 10619 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS3, 90pc duty cycle)     | WLAN      | 8.86     | ±9.6                   |
| 10620 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS4, 90pc duty cycle)     | WLAN      | 8.87     | ±9.6                   |
| 10621 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS5, 90pc duty cycle)     | WLAN      | 8.77     | ±9.6                   |
| 10622 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS6, 90pc duty cycle)     | WLAN      | 8.68     | ±9.6                   |
| 10623 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS7, 90pc duty cycle)     | WLAN      | 8.82     | ±9.6                   |
| 10624 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS8, 90pc duty cycle)     | WLAN      | 8.96     | ±9.6                   |
| 10625 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS9, 90pc duty cycle)     | WLAN      | 8.96     | ±9.6                   |
| 10626 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS0, 90pc duty cycle)     | WLAN      | 8.83     | ±9.6                   |
| 10627 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS1, 90pc duty cycle)     | WLAN      | 8.88     | ±9.6                   |
| 10628 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS2, 90pc duty cycle)     | WLAN      | 8.71     | ±9.6                   |
| 10629 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS3, 90pc duty cycle)     | WLAN      | 8.85     | ±9.6                   |
| 10630 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS4, 90pc duty cycle)     | WLAN      | 8.72     | ±9.6                   |
| 10631 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS5, 90pc duty cycle)     | WLAN      | 8.81     | ±9.6                   |
| 10632 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS6, 90pc duty cycle)     | WLAN      | 8.74     | ±9.6                   |
| 10633 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS7, 90pc duty cycle)     | WLAN      | 8.83     | ±9.6                   |
| 10634 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS8, 90pc duty cycle)     | WLAN      | 8.80     | ±9.6                   |
| 10635 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS9, 90pc duty cycle)     | WLAN      | 8.81     | ±9.6                   |
| 10636 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS0, 90pc duty cycle)    | WLAN      | 8.83     | ±9.6                   |
| 10637 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS1, 90pc duty cycle)    | WLAN      | 8.79     | ±9.6                   |
| 10638 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS2, 90pc duty cycle)    | WLAN      | 8.86     | ±9.6                   |
| 10639 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS3, 90pc duty cycle)    | WLAN      | 8.85     | ±9.6                   |
| 10640 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS4, 90pc duty cycle)    | WLAN      | 8.98     | ±9.6                   |
| 10641 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS5, 90pc duty cycle)    | WLAN      | 9.06     | ±9.6                   |
| 10642 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS6, 90pc duty cycle)    | WLAN      | 9.06     | ±9.6                   |
| 10643 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS7, 90pc duty cycle)    | WLAN      | 8.89     | ±9.6                   |
| 10644 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS8, 90pc duty cycle)    | WLAN      | 9.05     | ±9.6                   |
| 10645 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS9, 90pc duty cycle)    | WLAN      | 9.11     | ±9.6                   |
| 10646 | AAH | LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,7)  | LTE-TDD   | 11.96    | ±9.6                   |
| 10647 | AAG | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,7) | LTE-TDD   | 11.96    | ±9.6                   |
| 10648 | AAA | CDMA2000 (1x Advanced)                                 | CDMA2000  | 3.45     | ±9.6                   |
| 10652 | AAF | LTE-TDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)         | LTE-TDD   | 6.91     | ±9.6                   |
| 10653 | AAF | LTE-TDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)        | LTE-TDD   | 7.42     | ±9.6                   |
| 10654 | AAE | LTE-TDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)        | LTE-TDD   | 6.96     | ±9.6                   |
| 10655 | AAF | LTE-TDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)        | LTE-TDD   | 7.21     | ±9.6                   |
| 10658 | AAB | Pulse Waveform (200Hz, 10%)                            | Test      | 10.00    | ±9.6                   |
| 10659 | AAB | Pulse Waveform (200Hz, 20%)                            | Test      | 6.99     | ±9.6                   |
| 10660 | AAB | Pulse Waveform (200Hz, 40%)                            | Test      | 3.98     | ±9.6                   |
| 10661 | AAB | Pulse Waveform (200Hz, 60%)                            | Test      | 2.22     | ±9.6                   |
| 10662 | AAB | Pulse Waveform (200Hz, 80%)                            | Test      | 0.97     | ±9.6                   |
| 10670 | AAA | Bluetooth Low Energy                                   | Bluetooth | 2.19     | ±9.6                   |
| 10671 | AAC | IEEE 802.11ax (20 MHz, MCS0, 90pc duty cycle)          | WLAN      | 9.09     | ±9.6                   |
| 10672 | AAC | IEEE 802.11ax (20 MHz, MCS1, 90pc duty cycle)          | WLAN      | 8.57     | ±9.6                   |
| 10673 | AAC | IEEE 802.11ax (20 MHz, MCS2, 90pc duty cycle)          | WLAN      | 8.76     | ±9.6                   |
| 10674 | AAC | IEEE 802.11ax (20 MHz, MCS3, 90pc duty cycle)          | WLAN      | 8.74     | ±9.6                   |
| 10675 | AAC | IEEE 802.11ax (20 MHz, MCS4, 90pc duty cycle)          | WLAN      | 8.90     | ±9.6                   |
| 10676 | AAC | IEEE 802.11ax (20 MHz, MCS5, 90pc duty cycle)          | WLAN      | 8.77     | ±9.6                   |
| 10677 | AAC | IEEE 802.11ax (20 MHz, MCS6, 90pc duty cycle)          | WLAN      | 8.73     | ±9.6                   |
| 10678 | AAC | IEEE 802.11ax (20 MHz, MCS7, 90pc duty cycle)          | WLAN      | 8.78     | ±9.6                   |
| 10679 | AAC | IEEE 802.11ax (20 MHz, MCS8, 90pc duty cycle)          | WLAN      | 8.89     | ±9.6                   |
| 10680 | AAC | IEEE 802.11ax (20 MHz, MCS9, 90pc duty cycle)          | WLAN      | 8.80     | ±9.6                   |
| 10681 | AAC | IEEE 802.11ax (20 MHz, MCS10, 90pc duty cycle)         | WLAN      | 8.62     | ±9.6                   |
| 10682 | AAC | IEEE 802.11ax (20 MHz, MCS11, 90pc duty cycle)         | WLAN      | 8.83     | ±9.6                   |
| 10683 | AAC | IEEE 802.11ax (20 MHz, MCS0, 99pc duty cycle)          | WLAN      | 8.42     | ±9.6                   |
| 10684 | AAC | IEEE 802.11ax (20 MHz, MCS1, 99pc duty cycle)          | WLAN      | 8.26     | ±9.6                   |
| 10685 | AAC | IEEE 802.11ax (20 MHz, MCS2, 99pc duty cycle)          | WLAN      | 8.33     | ±9.6                   |
| 10686 | AAC | IEEE 802.11ax (20 MHz, MCS3, 99pc duty cycle)          | WLAN      | 8.25     | ±9.6                   |

| UID   | Rev | Communication System Name                      | Group | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|------------------------------------------------|-------|----------|------------------------|
| 10687 | AAC | IEEE 802.11ax (20 MHz, MCS4, 99pc duty cycle)  | WLAN  | 8.45     | ±9.6                   |
| 10688 | AAC | IEEE 802.11ax (20 MHz, MCS5, 99pc duty cycle)  | WLAN  | 8.29     | ±9.6                   |
| 10689 | AAC | IEEE 802.11ax (20 MHz, MCS6, 99pc duty cycle)  | WLAN  | 8.55     | ±9.6                   |
| 10690 | AAC | IEEE 802.11ax (20 MHz, MCS7, 99pc duty cycle)  | WLAN  | 8.29     | ±9.6                   |
| 10691 | AAC | IEEE 802.11ax (20 MHz, MCS8, 99pc duty cycle)  | WLAN  | 8.25     | ±9.6                   |
| 10692 | AAC | IEEE 802.11ax (20 MHz, MCS9, 99pc duty cycle)  | WLAN  | 8.29     | ±9.6                   |
| 10693 | AAC | IEEE 802.11ax (20 MHz, MCS10, 99pc duty cycle) | WLAN  | 8.25     | ±9.6                   |
| 10694 | AAC | IEEE 802.11ax (20 MHz, MCS11, 99pc duty cycle) | WLAN  | 8.57     | ±9.6                   |
| 10695 | AAC | IEEE 802.11ax (40 MHz, MCS0, 90pc duty cycle)  | WLAN  | 8.78     | ±9.6                   |
| 10696 | AAC | IEEE 802.11ax (40 MHz, MCS1, 90pc duty cycle)  | WLAN  | 8.91     | ±9.6                   |
| 10697 | AAC | IEEE 802.11ax (40 MHz, MCS2, 90pc duty cycle)  | WLAN  | 8.81     | ±9.6                   |
| 10698 | AAC | IEEE 802.11ax (40 MHz, MCS3, 90pc duty cycle)  | WLAN  | 8.89     | ±9.6                   |
| 10699 | AAC | IEEE 802.11ax (40 MHz, MCS4, 90pc duty cycle)  | WLAN  | 8.82     | ±9.6                   |
| 10700 | AAC | IEEE 802.11ax (40 MHz, MCS5, 90pc duty cycle)  | WLAN  | 8.73     | ±9.6                   |
| 10701 | AAC | IEEE 802.11ax (40 MHz, MCS6, 90pc duty cycle)  | WLAN  | 8.86     | ±9.6                   |
| 10702 | AAC | IEEE 802.11ax (40 MHz, MCS7, 90pc duty cycle)  | WLAN  | 8.70     | ±9.6                   |
| 10703 | AAC | IEEE 802.11ax (40 MHz, MCS8, 90pc duty cycle)  | WLAN  | 8.82     | ±9.6                   |
| 10704 | AAC | IEEE 802.11ax (40 MHz, MCS9, 90pc duty cycle)  | WLAN  | 8.56     | ±9.6                   |
| 10705 | AAC | IEEE 802.11ax (40 MHz, MCS10, 90pc duty cycle) | WLAN  | 8.69     | ±9.6                   |
| 10706 | AAC | IEEE 802.11ax (40 MHz, MCS11, 90pc duty cycle) | WLAN  | 8.66     | ±9.6                   |
| 10707 | AAC | IEEE 802.11ax (40 MHz, MCS0, 99pc duty cycle)  | WLAN  | 8.32     | ±9.6                   |
| 10708 | AAC | IEEE 802.11ax (40 MHz, MCS1, 99pc duty cycle)  | WLAN  | 8.55     | ±9.6                   |
| 10709 | AAC | IEEE 802.11ax (40 MHz, MCS2, 99pc duty cycle)  | WLAN  | 8.33     | ±9.6                   |
| 10710 | AAC | IEEE 802.11ax (40 MHz, MCS3, 99pc duty cycle)  | WLAN  | 8.29     | ±9.6                   |
| 10711 | AAC | IEEE 802.11ax (40 MHz, MCS4, 99pc duty cycle)  | WLAN  | 8.39     | ±9.6                   |
| 10712 | AAC | IEEE 802.11ax (40 MHz, MCS5, 99pc duty cycle)  | WLAN  | 8.67     | ±9.6                   |
| 10713 | AAC | IEEE 802.11ax (40 MHz, MCS6, 99pc duty cycle)  | WLAN  | 8.33     | ±9.6                   |
| 10714 | AAC | IEEE 802.11ax (40 MHz, MCS7, 99pc duty cycle)  | WLAN  | 8.26     | ±9.6                   |
| 10715 | AAC | IEEE 802.11ax (40 MHz, MCS8, 99pc duty cycle)  | WLAN  | 8.45     | ±9.6                   |
| 10716 | AAC | IEEE 802.11ax (40 MHz, MCS9, 99pc duty cycle)  | WLAN  | 8.30     | ±9.6                   |
| 10717 | AAC | IEEE 802.11ax (40 MHz, MCS10, 99pc duty cycle) | WLAN  | 8.48     | ±9.6                   |
| 10718 | AAC | IEEE 802.11ax (40 MHz, MCS11, 99pc duty cycle) | WLAN  | 8.24     | ±9.6                   |
| 10719 | AAC | IEEE 802.11ax (80 MHz, MCS0, 90pc duty cycle)  | WLAN  | 8.81     | ±9.6                   |
| 10720 | AAC | IEEE 802.11ax (80 MHz, MCS1, 90pc duty cycle)  | WLAN  | 8.87     | ±9.6                   |
| 10721 | AAC | IEEE 802.11ax (80 MHz, MCS2, 90pc duty cycle)  | WLAN  | 8.76     | ±9.6                   |
| 10722 | AAC | IEEE 802.11ax (80 MHz, MCS3, 90pc duty cycle)  | WLAN  | 8.55     | ±9.6                   |
| 10723 | AAC | IEEE 802.11ax (80 MHz, MCS4, 90pc duty cycle)  | WLAN  | 8.70     | ±9.6                   |
| 10724 | AAC | IEEE 802.11ax (80 MHz, MCS5, 90pc duty cycle)  | WLAN  | 8.90     | ±9.6                   |
| 10725 | AAC | IEEE 802.11ax (80 MHz, MCS6, 90pc duty cycle)  | WLAN  | 8.74     | ±9.6                   |
| 10726 | AAC | IEEE 802.11ax (80 MHz, MCS7, 90pc duty cycle)  | WLAN  | 8.72     | ±9.6                   |
| 10727 | AAC | IEEE 802.11ax (80 MHz, MCS8, 90pc duty cycle)  | WLAN  | 8.66     | ±9.6                   |
| 10728 | AAC | IEEE 802.11ax (80 MHz, MCS9, 90pc duty cycle)  | WLAN  | 8.65     | ±9.6                   |
| 10729 | AAC | IEEE 802.11ax (80 MHz, MCS10, 90pc duty cycle) | WLAN  | 8.64     | ±9.6                   |
| 10730 | AAC | IEEE 802.11ax (80 MHz, MCS11, 90pc duty cycle) | WLAN  | 8.67     | ±9.6                   |
| 10731 | AAC | IEEE 802.11ax (80 MHz, MCS0, 99pc duty cycle)  | WLAN  | 8.42     | ±9.6                   |
| 10732 | AAC | IEEE 802.11ax (80 MHz, MCS1, 99pc duty cycle)  | WLAN  | 8.48     | ±9.6                   |
| 10733 | AAC | IEEE 802.11ax (80 MHz, MCS2, 99pc duty cycle)  | WLAN  | 8.40     | ±9.6                   |
| 10734 | AAC | IEEE 802.11ax (80 MHz, MCS3, 99pc duty cycle)  | WLAN  | 8.25     | ±9.6                   |
| 10735 | AAC | IEEE 802.11ax (80 MHz, MCS4, 99pc duty cycle)  | WLAN  | 8.33     | ±9.6                   |
| 10736 | AAC | IEEE 802.11ax (80 MHz, MCS5, 99pc duty cycle)  | WLAN  | 8.27     | ±9.6                   |
| 10737 | AAC | IEEE 802.11ax (80 MHz, MCS6, 99pc duty cycle)  | WLAN  | 8.36     | ±9.6                   |
| 10738 | AAC | IEEE 802.11ax (80 MHz, MCS7, 99pc duty cycle)  | WLAN  | 8.42     | ±9.6                   |
| 10739 | AAC | IEEE 802.11ax (80 MHz, MCS8, 99pc duty cycle)  | WLAN  | 8.29     | ±9.6                   |
| 10740 | AAC | IEEE 802.11ax (80 MHz, MCS9, 99pc duty cycle)  | WLAN  | 8.48     | ±9.6                   |
| 10741 | AAC | IEEE 802.11ax (80 MHz, MCS10, 99pc duty cycle) | WLAN  | 8.40     | ±9.6                   |
| 10742 | AAC | IEEE 802.11ax (80 MHz, MCS11, 99pc duty cycle) | WLAN  | 8.43     | ±9.6                   |
| 10743 | AAC | IEEE 802.11ax (160 MHz, MCS0, 90pc duty cycle) | WLAN  | 8.94     | ±9.6                   |
| 10744 | AAC | IEEE 802.11ax (160 MHz, MCS1, 90pc duty cycle) | WLAN  | 9.16     | ±9.6                   |
| 10745 | AAC | IEEE 802.11ax (160 MHz, MCS2, 90pc duty cycle) | WLAN  | 8.93     | ±9.6                   |
| 10746 | AAC | IEEE 802.11ax (160 MHz, MCS3, 90pc duty cycle) | WLAN  | 9.11     | ±9.6                   |
| 10747 | AAC | IEEE 802.11ax (160 MHz, MCS4, 90pc duty cycle) | WLAN  | 9.04     | ±9.6                   |
| 10748 | AAC | IEEE 802.11ax (160 MHz, MCS5, 90pc duty cycle) | WLAN  | 8.93     | ±9.6                   |
| 10749 | AAC | IEEE 802.11ax (160 MHz, MCS6, 90pc duty cycle) | WLAN  | 8.90     | ±9.6                   |
| 10750 | AAC | IEEE 802.11ax (160 MHz, MCS7, 90pc duty cycle) | WLAN  | 8.79     | ±9.6                   |
| 10751 | AAC | IEEE 802.11ax (160 MHz, MCS8, 90pc duty cycle) | WLAN  | 8.82     | ±9.6                   |
| 10752 | AAC | IEEE 802.11ax (160 MHz, MCS9, 90pc duty cycle) | WLAN  | 8.81     | ±9.6                   |

| UID   | Rev | Communication System Name                       | Group         | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|-------------------------------------------------|---------------|----------|------------------------|
| 10753 | AAC | IEEE 802.11ax (160 MHz, MCS10, 90pc duty cycle) | WLAN          | 9.00     | ±9.6                   |
| 10754 | AAC | IEEE 802.11ax (160 MHz, MCS11, 90pc duty cycle) | WLAN          | 8.94     | ±9.6                   |
| 10755 | AAC | IEEE 802.11ax (160 MHz, MCS0, 99pc duty cycle)  | WLAN          | 8.64     | ±9.6                   |
| 10756 | AAC | IEEE 802.11ax (160 MHz, MCS1, 99pc duty cycle)  | WLAN          | 8.77     | ±9.6                   |
| 10757 | AAC | IEEE 802.11ax (160 MHz, MCS2, 99pc duty cycle)  | WLAN          | 8.77     | ±9.6                   |
| 10758 | AAC | IEEE 802.11ax (160 MHz, MCS3, 99pc duty cycle)  | WLAN          | 8.69     | ±9.6                   |
| 10759 | AAC | IEEE 802.11ax (160 MHz, MCS4, 99pc duty cycle)  | WLAN          | 8.58     | ±9.6                   |
| 10760 | AAC | IEEE 802.11ax (160 MHz, MCS5, 99pc duty cycle)  | WLAN          | 8.49     | ±9.6                   |
| 10761 | AAC | IEEE 802.11ax (160 MHz, MCS6, 99pc duty cycle)  | WLAN          | 8.58     | ±9.6                   |
| 10762 | AAC | IEEE 802.11ax (160 MHz, MCS7, 99pc duty cycle)  | WLAN          | 8.49     | ±9.6                   |
| 10763 | AAC | IEEE 802.11ax (160 MHz, MCS8, 99pc duty cycle)  | WLAN          | 8.53     | ±9.6                   |
| 10764 | AAC | IEEE 802.11ax (160 MHz, MCS9, 99pc duty cycle)  | WLAN          | 8.54     | ±9.6                   |
| 10765 | AAC | IEEE 802.11ax (160 MHz, MCS10, 99pc duty cycle) | WLAN          | 8.54     | ±9.6                   |
| 10766 | AAC | IEEE 802.11ax (160 MHz, MCS11, 99pc duty cycle) | WLAN          | 8.51     | ±9.6                   |
| 10767 | AAG | 5G NR (CP-OFDM, 1 RB, 5 MHz, QPSK, 15 kHz)      | 5G NR FR1 TDD | 7.99     | ±9.6                   |
| 10768 | AAE | 5G NR (CP-OFDM, 1 RB, 10 MHz, QPSK, 15 kHz)     | 5G NR FR1 TDD | 8.01     | ±9.6                   |
| 10769 | AAD | 5G NR (CP-OFDM, 1 RB, 15 MHz, QPSK, 15 kHz)     | 5G NR FR1 TDD | 8.01     | ±9.6                   |
| 10770 | AAE | 5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 15 kHz)     | 5G NR FR1 TDD | 8.02     | ±9.6                   |
| 10771 | AAD | 5G NR (CP-OFDM, 1 RB, 25 MHz, QPSK, 15 kHz)     | 5G NR FR1 TDD | 8.02     | ±9.6                   |
| 10772 | AAE | 5G NR (CP-OFDM, 1 RB, 30 MHz, QPSK, 15 kHz)     | 5G NR FR1 TDD | 8.23     | ±9.6                   |
| 10773 | AAF | 5G NR (CP-OFDM, 1 RB, 40 MHz, QPSK, 15 kHz)     | 5G NR FR1 TDD | 8.03     | ±9.6                   |
| 10774 | AAE | 5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 15 kHz)     | 5G NR FR1 TDD | 8.02     | ±9.6                   |
| 10775 | AAF | 5G NR (CP-OFDM, 50% RB, 5 MHz, QPSK, 15 kHz)    | 5G NR FR1 TDD | 8.31     | ±9.6                   |
| 10776 | AAE | 5G NR (CP-OFDM, 50% RB, 10 MHz, QPSK, 15 kHz)   | 5G NR FR1 TDD | 8.30     | ±9.6                   |
| 10777 | AAC | 5G NR (CP-OFDM, 50% RB, 15 MHz, QPSK, 15 kHz)   | 5G NR FR1 TDD | 8.30     | ±9.6                   |
| 10778 | AAE | 5G NR (CP-OFDM, 50% RB, 20 MHz, QPSK, 15 kHz)   | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10779 | AAC | 5G NR (CP-OFDM, 50% RB, 25 MHz, QPSK, 15 kHz)   | 5G NR FR1 TDD | 8.42     | ±9.6                   |
| 10780 | AAE | 5G NR (CP-OFDM, 50% RB, 30 MHz, QPSK, 15 kHz)   | 5G NR FR1 TDD | 8.38     | ±9.6                   |
| 10781 | AAF | 5G NR (CP-OFDM, 50% RB, 40 MHz, QPSK, 15 kHz)   | 5G NR FR1 TDD | 8.38     | ±9.6                   |
| 10782 | AAE | 5G NR (CP-OFDM, 50% RB, 50 MHz, QPSK, 15 kHz)   | 5G NR FR1 TDD | 8.43     | ±9.6                   |
| 10783 | AAG | 5G NR (CP-OFDM, 100% RB, 5 MHz, QPSK, 15 kHz)   | 5G NR FR1 TDD | 8.31     | ±9.6                   |
| 10784 | AAE | 5G NR (CP-OFDM, 100% RB, 10 MHz, QPSK, 15 kHz)  | 5G NR FR1 TDD | 8.29     | ±9.6                   |
| 10785 | AAD | 5G NR (CP-OFDM, 100% RB, 15 MHz, QPSK, 15 kHz)  | 5G NR FR1 TDD | 8.40     | ±9.6                   |
| 10786 | AAE | 5G NR (CP-OFDM, 100% RB, 20 MHz, QPSK, 15 kHz)  | 5G NR FR1 TDD | 8.35     | ±9.6                   |
| 10787 | AAD | 5G NR (CP-OFDM, 100% RB, 25 MHz, QPSK, 15 kHz)  | 5G NR FR1 TDD | 8.44     | ±9.6                   |
| 10788 | AAE | 5G NR (CP-OFDM, 100% RB, 30 MHz, QPSK, 15 kHz)  | 5G NR FR1 TDD | 8.39     | ±9.6                   |
| 10789 | AAF | 5G NR (CP-OFDM, 100% RB, 40 MHz, QPSK, 15 kHz)  | 5G NR FR1 TDD | 8.37     | ±9.6                   |
| 10790 | AAE | 5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 15 kHz)  | 5G NR FR1 TDD | 8.39     | ±9.6                   |
| 10791 | AAG | 5G NR (CP-OFDM, 1 RB, 5 MHz, QPSK, 30 kHz)      | 5G NR FR1 TDD | 7.83     | ±9.6                   |
| 10792 | AAE | 5G NR (CP-OFDM, 1 RB, 10 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.92     | ±9.6                   |
| 10793 | AAD | 5G NR (CP-OFDM, 1 RB, 15 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.95     | ±9.6                   |
| 10794 | AAE | 5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.82     | ±9.6                   |
| 10795 | AAD | 5G NR (CP-OFDM, 1 RB, 25 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.84     | ±9.6                   |
| 10796 | AAE | 5G NR (CP-OFDM, 1 RB, 30 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.82     | ±9.6                   |
| 10797 | AAF | 5G NR (CP-OFDM, 1 RB, 40 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 8.01     | ±9.6                   |
| 10798 | AAE | 5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.89     | ±9.6                   |
| 10799 | AAF | 5G NR (CP-OFDM, 1 RB, 60 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.93     | ±9.6                   |
| 10801 | AAF | 5G NR (CP-OFDM, 1 RB, 80 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.89     | ±9.6                   |
| 10802 | AAE | 5G NR (CP-OFDM, 1 RB, 90 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.87     | ±9.6                   |
| 10803 | AAF | 5G NR (CP-OFDM, 1 RB, 100 MHz, QPSK, 30 kHz)    | 5G NR FR1 TDD | 7.93     | ±9.6                   |
| 10805 | AAE | 5G NR (CP-OFDM, 50% RB, 10 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10806 | AAD | 5G NR (CP-OFDM, 50% RB, 15 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 8.37     | ±9.6                   |
| 10809 | AAE | 5G NR (CP-OFDM, 50% RB, 30 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10810 | AAF | 5G NR (CP-OFDM, 50% RB, 40 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10812 | AAF | 5G NR (CP-OFDM, 50% RB, 60 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 8.35     | ±9.6                   |
| 10817 | AAG | 5G NR (CP-OFDM, 100% RB, 5 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 8.35     | ±9.6                   |
| 10818 | AAE | 5G NR (CP-OFDM, 100% RB, 10 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10819 | AAD | 5G NR (CP-OFDM, 100% RB, 15 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.33     | ±9.6                   |
| 10820 | AAE | 5G NR (CP-OFDM, 100% RB, 20 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.30     | ±9.6                   |
| 10821 | AAD | 5G NR (CP-OFDM, 100% RB, 25 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.41     | ±9.6                   |
| 10822 | AAE | 5G NR (CP-OFDM, 100% RB, 30 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.41     | ±9.6                   |
| 10823 | AAF | 5G NR (CP-OFDM, 100% RB, 40 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.36     | ±9.6                   |
| 10824 | AAE | 5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.39     | ±9.6                   |
| 10825 | AAF | 5G NR (CP-OFDM, 100% RB, 60 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.41     | ±9.6                   |
| 10827 | AAF | 5G NR (CP-OFDM, 100% RB, 80 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.42     | ±9.6                   |
| 10828 | AAE | 5G NR (CP-OFDM, 100% RB, 90 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.43     | ±9.6                   |

| UID   | Rev | Communication System Name                            | Group         | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|------------------------------------------------------|---------------|----------|------------------------|
| 10829 | AAF | 5G NR (CP-OFDM, 100% RB, 100 MHz, QPSK, 30 kHz)      | 5G NR FR1 TDD | 8.40     | ±9.6                   |
| 10830 | AAE | 5G NR (CP-OFDM, 1 RB, 10 MHz, QPSK, 60 kHz)          | 5G NR FR1 TDD | 7.63     | ±9.6                   |
| 10831 | AAD | 5G NR (CP-OFDM, 1 RB, 15 MHz, QPSK, 60 kHz)          | 5G NR FR1 TDD | 7.73     | ±9.6                   |
| 10832 | AAE | 5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 60 kHz)          | 5G NR FR1 TDD | 7.74     | ±9.6                   |
| 10833 | AAD | 5G NR (CP-OFDM, 1 RB, 25 MHz, QPSK, 60 kHz)          | 5G NR FR1 TDD | 7.70     | ±9.6                   |
| 10834 | AAE | 5G NR (CP-OFDM, 1 RB, 30 MHz, QPSK, 60 kHz)          | 5G NR FR1 TDD | 7.75     | ±9.6                   |
| 10835 | AAF | 5G NR (CP-OFDM, 1 RB, 40 MHz, QPSK, 60 kHz)          | 5G NR FR1 TDD | 7.70     | ±9.6                   |
| 10836 | AAE | 5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 60 kHz)          | 5G NR FR1 TDD | 7.66     | ±9.6                   |
| 10837 | AAF | 5G NR (CP-OFDM, 1 RB, 60 MHz, QPSK, 60 kHz)          | 5G NR FR1 TDD | 7.68     | ±9.6                   |
| 10839 | AAF | 5G NR (CP-OFDM, 1 RB, 80 MHz, QPSK, 60 kHz)          | 5G NR FR1 TDD | 7.70     | ±9.6                   |
| 10840 | AAE | 5G NR (CP-OFDM, 1 RB, 90 MHz, QPSK, 60 kHz)          | 5G NR FR1 TDD | 7.67     | ±9.6                   |
| 10841 | AAF | 5G NR (CP-OFDM, 1 RB, 100 MHz, QPSK, 60 kHz)         | 5G NR FR1 TDD | 7.71     | ±9.6                   |
| 10843 | AAD | 5G NR (CP-OFDM, 50% RB, 15 MHz, QPSK, 60 kHz)        | 5G NR FR1 TDD | 8.49     | ±9.6                   |
| 10844 | AAE | 5G NR (CP-OFDM, 50% RB, 20 MHz, QPSK, 60 kHz)        | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10846 | AAE | 5G NR (CP-OFDM, 50% RB, 30 MHz, QPSK, 60 kHz)        | 5G NR FR1 TDD | 8.41     | ±9.6                   |
| 10854 | AAE | 5G NR (CP-OFDM, 100% RB, 10 MHz, QPSK, 60 kHz)       | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10855 | AAD | 5G NR (CP-OFDM, 100% RB, 15 MHz, QPSK, 60 kHz)       | 5G NR FR1 TDD | 8.36     | ±9.6                   |
| 10856 | AAE | 5G NR (CP-OFDM, 100% RB, 20 MHz, QPSK, 60 kHz)       | 5G NR FR1 TDD | 8.37     | ±9.6                   |
| 10857 | AAD | 5G NR (CP-OFDM, 100% RB, 25 MHz, QPSK, 60 kHz)       | 5G NR FR1 TDD | 8.35     | ±9.6                   |
| 10858 | AAE | 5G NR (CP-OFDM, 100% RB, 30 MHz, QPSK, 60 kHz)       | 5G NR FR1 TDD | 8.36     | ±9.6                   |
| 10859 | AAF | 5G NR (CP-OFDM, 100% RB, 40 MHz, QPSK, 60 kHz)       | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10860 | AAE | 5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 60 kHz)       | 5G NR FR1 TDD | 8.41     | ±9.6                   |
| 10861 | AAF | 5G NR (CP-OFDM, 100% RB, 60 MHz, QPSK, 60 kHz)       | 5G NR FR1 TDD | 8.40     | ±9.6                   |
| 10863 | AAF | 5G NR (CP-OFDM, 100% RB, 80 MHz, QPSK, 60 kHz)       | 5G NR FR1 TDD | 8.41     | ±9.6                   |
| 10864 | AAE | 5G NR (CP-OFDM, 100% RB, 90 MHz, QPSK, 60 kHz)       | 5G NR FR1 TDD | 8.37     | ±9.6                   |
| 10865 | AAF | 5G NR (CP-OFDM, 100% RB, 100 MHz, QPSK, 60 kHz)      | 5G NR FR1 TDD | 8.41     | ±9.6                   |
| 10866 | AAF | 5G NR (DFT-s-OFDM, 1 RB, 100 MHz, QPSK, 30 kHz)      | 5G NR FR1 TDD | 5.68     | ±9.6                   |
| 10868 | AAF | 5G NR (DFT-s-OFDM, 100% RB, 100 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 5.89     | ±9.6                   |
| 10869 | AAE | 5G NR (DFT-s-OFDM, 1 RB, 100 MHz, QPSK, 120 kHz)     | 5G NR FR2 TDD | 5.75     | ±9.6                   |
| 10870 | AAE | 5G NR (DFT-s-OFDM, 100% RB, 100 MHz, QPSK, 120 kHz)  | 5G NR FR2 TDD | 5.86     | ±9.6                   |
| 10871 | AAE | 5G NR (DFT-s-OFDM, 1 RB, 100 MHz, 16QAM, 120 kHz)    | 5G NR FR2 TDD | 5.75     | ±9.6                   |
| 10872 | AAE | 5G NR (DFT-s-OFDM, 100% RB, 100 MHz, 16QAM, 120 kHz) | 5G NR FR2 TDD | 6.52     | ±9.6                   |
| 10873 | AAE | 5G NR (DFT-s-OFDM, 1 RB, 100 MHz, 64QAM, 120 kHz)    | 5G NR FR2 TDD | 6.61     | ±9.6                   |
| 10874 | AAE | 5G NR (DFT-s-OFDM, 100% RB, 100 MHz, 64QAM, 120 kHz) | 5G NR FR2 TDD | 6.65     | ±9.6                   |
| 10875 | AAE | 5G NR (CP-OFDM, 1 RB, 100 MHz, QPSK, 120 kHz)        | 5G NR FR2 TDD | 7.78     | ±9.6                   |
| 10876 | AAE | 5G NR (CP-OFDM, 100% RB, 100 MHz, QPSK, 120 kHz)     | 5G NR FR2 TDD | 8.39     | ±9.6                   |
| 10877 | AAE | 5G NR (CP-OFDM, 1 RB, 100 MHz, 16QAM, 120 kHz)       | 5G NR FR2 TDD | 7.95     | ±9.6                   |
| 10878 | AAE | 5G NR (CP-OFDM, 100% RB, 100 MHz, 16QAM, 120 kHz)    | 5G NR FR2 TDD | 8.41     | ±9.6                   |
| 10879 | AAE | 5G NR (CP-OFDM, 1 RB, 100 MHz, 64QAM, 120 kHz)       | 5G NR FR2 TDD | 8.12     | ±9.6                   |
| 10880 | AAE | 5G NR (CP-OFDM, 100% RB, 100 MHz, 64QAM, 120 kHz)    | 5G NR FR2 TDD | 8.38     | ±9.6                   |
| 10881 | AAE | 5G NR (DFT-s-OFDM, 1 RB, 50 MHz, QPSK, 120 kHz)      | 5G NR FR2 TDD | 5.75     | ±9.6                   |
| 10882 | AAE | 5G NR (DFT-s-OFDM, 100% RB, 50 MHz, QPSK, 120 kHz)   | 5G NR FR2 TDD | 5.96     | ±9.6                   |
| 10883 | AAE | 5G NR (DFT-s-OFDM, 1 RB, 50 MHz, 16QAM, 120 kHz)     | 5G NR FR2 TDD | 6.57     | ±9.6                   |
| 10884 | AAE | 5G NR (DFT-s-OFDM, 100% RB, 50 MHz, 16QAM, 120 kHz)  | 5G NR FR2 TDD | 6.53     | ±9.6                   |
| 10885 | AAE | 5G NR (DFT-s-OFDM, 1 RB, 50 MHz, 64QAM, 120 kHz)     | 5G NR FR2 TDD | 6.61     | ±9.6                   |
| 10886 | AAE | 5G NR (DFT-s-OFDM, 100% RB, 50 MHz, 64QAM, 120 kHz)  | 5G NR FR2 TDD | 6.65     | ±9.6                   |
| 10887 | AAE | 5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 120 kHz)         | 5G NR FR2 TDD | 7.78     | ±9.6                   |
| 10888 | AAE | 5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 120 kHz)      | 5G NR FR2 TDD | 8.35     | ±9.6                   |
| 10889 | AAE | 5G NR (CP-OFDM, 1 RB, 50 MHz, 16QAM, 120 kHz)        | 5G NR FR2 TDD | 8.02     | ±9.6                   |
| 10890 | AAE | 5G NR (CP-OFDM, 100% RB, 50 MHz, 16QAM, 120 kHz)     | 5G NR FR2 TDD | 8.40     | ±9.6                   |
| 10891 | AAE | 5G NR (CP-OFDM, 1 RB, 50 MHz, 64QAM, 120 kHz)        | 5G NR FR2 TDD | 8.13     | ±9.6                   |
| 10892 | AAE | 5G NR (CP-OFDM, 100% RB, 50 MHz, 64QAM, 120 kHz)     | 5G NR FR2 TDD | 8.41     | ±9.6                   |
| 10897 | AAE | 5G NR (DFT-s-OFDM, 1 RB, 5 MHz, QPSK, 30 kHz)        | 5G NR FR1 TDD | 5.66     | ±9.6                   |
| 10898 | AAC | 5G NR (DFT-s-OFDM, 1 RB, 10 MHz, QPSK, 30 kHz)       | 5G NR FR1 TDD | 5.67     | ±9.6                   |
| 10899 | AAB | 5G NR (DFT-s-OFDM, 1 RB, 15 MHz, QPSK, 30 kHz)       | 5G NR FR1 TDD | 5.67     | ±9.6                   |
| 10900 | AAC | 5G NR (DFT-s-OFDM, 1 RB, 20 MHz, QPSK, 30 kHz)       | 5G NR FR1 TDD | 5.68     | ±9.6                   |
| 10901 | AAB | 5G NR (DFT-s-OFDM, 1 RB, 25 MHz, QPSK, 30 kHz)       | 5G NR FR1 TDD | 5.68     | ±9.6                   |
| 10902 | AAC | 5G NR (DFT-s-OFDM, 1 RB, 30 MHz, QPSK, 30 kHz)       | 5G NR FR1 TDD | 5.68     | ±9.6                   |
| 10903 | AAD | 5G NR (DFT-s-OFDM, 1 RB, 40 MHz, QPSK, 30 kHz)       | 5G NR FR1 TDD | 5.68     | ±9.6                   |
| 10904 | AAC | 5G NR (DFT-s-OFDM, 1 RB, 50 MHz, QPSK, 30 kHz)       | 5G NR FR1 TDD | 5.68     | ±9.6                   |
| 10905 | AAD | 5G NR (DFT-s-OFDM, 1 RB, 60 MHz, QPSK, 30 kHz)       | 5G NR FR1 TDD | 5.68     | ±9.6                   |
| 10906 | AAD | 5G NR (DFT-s-OFDM, 1 RB, 80 MHz, QPSK, 30 kHz)       | 5G NR FR1 TDD | 5.68     | ±9.6                   |
| 10907 | AAE | 5G NR (DFT-s-OFDM, 50% RB, 5 MHz, QPSK, 30 kHz)      | 5G NR FR1 TDD | 5.78     | ±9.6                   |
| 10908 | AAC | 5G NR (DFT-s-OFDM, 50% RB, 10 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 5.93     | ±9.6                   |
| 10909 | AAB | 5G NR (DFT-s-OFDM, 50% RB, 15 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 5.96     | ±9.6                   |
| 10910 | AAC | 5G NR (DFT-s-OFDM, 50% RB, 20 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 5.83     | ±9.6                   |

| UID   | Rev | Communication System Name                           | Group         | PAR (dB) | Unc <sup>E</sup> $k=2$ |
|-------|-----|-----------------------------------------------------|---------------|----------|------------------------|
| 10911 | AAB | 5G NR (DFT-s-OFDM, 50% RB, 25 MHz, QPSK, 30 kHz)    | 5G NR FR1 TDD | 5.93     | ±9.6                   |
| 10912 | AAC | 5G NR (DFT-s-OFDM, 50% RB, 30 MHz, QPSK, 30 kHz)    | 5G NR FR1 TDD | 5.84     | ±9.6                   |
| 10913 | AAD | 5G NR (DFT-s-OFDM, 50% RB, 40 MHz, QPSK, 30 kHz)    | 5G NR FR1 TDD | 5.84     | ±9.6                   |
| 10914 | AAC | 5G NR (DFT-s-OFDM, 50% RB, 50 MHz, QPSK, 30 kHz)    | 5G NR FR1 TDD | 5.85     | ±9.6                   |
| 10915 | AAD | 5G NR (DFT-s-OFDM, 50% RB, 60 MHz, QPSK, 30 kHz)    | 5G NR FR1 TDD | 5.83     | ±9.6                   |
| 10916 | AAD | 5G NR (DFT-s-OFDM, 50% RB, 80 MHz, QPSK, 30 kHz)    | 5G NR FR1 TDD | 5.87     | ±9.6                   |
| 10917 | AAD | 5G NR (DFT-s-OFDM, 50% RB, 100 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 5.94     | ±9.6                   |
| 10918 | AAE | 5G NR (DFT-s-OFDM, 100% RB, 5 MHz, QPSK, 30 kHz)    | 5G NR FR1 TDD | 5.86     | ±9.6                   |
| 10919 | AAC | 5G NR (DFT-s-OFDM, 100% RB, 10 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 5.86     | ±9.6                   |
| 10920 | AAB | 5G NR (DFT-s-OFDM, 100% RB, 15 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 5.87     | ±9.6                   |
| 10921 | AAC | 5G NR (DFT-s-OFDM, 100% RB, 20 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 5.84     | ±9.6                   |
| 10922 | AAB | 5G NR (DFT-s-OFDM, 100% RB, 25 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 5.82     | ±9.6                   |
| 10923 | AAC | 5G NR (DFT-s-OFDM, 100% RB, 30 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 5.84     | ±9.6                   |
| 10924 | AAD | 5G NR (DFT-s-OFDM, 100% RB, 40 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 5.84     | ±9.6                   |
| 10925 | AAC | 5G NR (DFT-s-OFDM, 100% RB, 50 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 5.95     | ±9.6                   |
| 10926 | AAD | 5G NR (DFT-s-OFDM, 100% RB, 60 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 5.84     | ±9.6                   |
| 10927 | AAD | 5G NR (DFT-s-OFDM, 100% RB, 80 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 5.94     | ±9.6                   |
| 10928 | AAD | 5G NR (DFT-s-OFDM, 1 RB, 5 MHz, QPSK, 15 kHz)       | 5G NR FR1 FDD | 5.52     | ±9.6                   |
| 10929 | AAD | 5G NR (DFT-s-OFDM, 1 RB, 10 MHz, QPSK, 15 kHz)      | 5G NR FR1 FDD | 5.52     | ±9.6                   |
| 10930 | AAC | 5G NR (DFT-s-OFDM, 1 RB, 15 MHz, QPSK, 15 kHz)      | 5G NR FR1 FDD | 5.52     | ±9.6                   |
| 10931 | AAC | 5G NR (DFT-s-OFDM, 1 RB, 20 MHz, QPSK, 15 kHz)      | 5G NR FR1 FDD | 5.51     | ±9.6                   |
| 10932 | AAC | 5G NR (DFT-s-OFDM, 1 RB, 25 MHz, QPSK, 15 kHz)      | 5G NR FR1 FDD | 5.51     | ±9.6                   |
| 10933 | AAC | 5G NR (DFT-s-OFDM, 1 RB, 30 MHz, QPSK, 15 kHz)      | 5G NR FR1 FDD | 5.51     | ±9.6                   |
| 10934 | AAC | 5G NR (DFT-s-OFDM, 1 RB, 40 MHz, QPSK, 15 kHz)      | 5G NR FR1 FDD | 5.51     | ±9.6                   |
| 10935 | AAD | 5G NR (DFT-s-OFDM, 1 RB, 50 MHz, QPSK, 15 kHz)      | 5G NR FR1 FDD | 5.51     | ±9.6                   |
| 10936 | AAD | 5G NR (DFT-s-OFDM, 50% RB, 5 MHz, QPSK, 15 kHz)     | 5G NR FR1 FDD | 5.90     | ±9.6                   |
| 10937 | AAD | 5G NR (DFT-s-OFDM, 50% RB, 10 MHz, QPSK, 15 kHz)    | 5G NR FR1 FDD | 5.77     | ±9.6                   |
| 10938 | AAC | 5G NR (DFT-s-OFDM, 50% RB, 15 MHz, QPSK, 15 kHz)    | 5G NR FR1 FDD | 5.90     | ±9.6                   |
| 10939 | AAC | 5G NR (DFT-s-OFDM, 50% RB, 20 MHz, QPSK, 15 kHz)    | 5G NR FR1 FDD | 5.82     | ±9.6                   |
| 10940 | AAC | 5G NR (DFT-s-OFDM, 50% RB, 25 MHz, QPSK, 15 kHz)    | 5G NR FR1 FDD | 5.89     | ±9.6                   |
| 10941 | AAC | 5G NR (DFT-s-OFDM, 50% RB, 30 MHz, QPSK, 15 kHz)    | 5G NR FR1 FDD | 5.83     | ±9.6                   |
| 10942 | AAC | 5G NR (DFT-s-OFDM, 50% RB, 40 MHz, QPSK, 15 kHz)    | 5G NR FR1 FDD | 5.85     | ±9.6                   |
| 10943 | AAD | 5G NR (DFT-s-OFDM, 50% RB, 50 MHz, QPSK, 15 kHz)    | 5G NR FR1 FDD | 5.95     | ±9.6                   |
| 10944 | AAD | 5G NR (DFT-s-OFDM, 100% RB, 5 MHz, QPSK, 15 kHz)    | 5G NR FR1 FDD | 5.81     | ±9.6                   |
| 10945 | AAD | 5G NR (DFT-s-OFDM, 100% RB, 10 MHz, QPSK, 15 kHz)   | 5G NR FR1 FDD | 5.85     | ±9.6                   |
| 10946 | AAC | 5G NR (DFT-s-OFDM, 100% RB, 15 MHz, QPSK, 15 kHz)   | 5G NR FR1 FDD | 5.83     | ±9.6                   |
| 10947 | AAC | 5G NR (DFT-s-OFDM, 100% RB, 20 MHz, QPSK, 15 kHz)   | 5G NR FR1 FDD | 5.87     | ±9.6                   |
| 10948 | AAC | 5G NR (DFT-s-OFDM, 100% RB, 25 MHz, QPSK, 15 kHz)   | 5G NR FR1 FDD | 5.94     | ±9.6                   |
| 10949 | AAC | 5G NR (DFT-s-OFDM, 100% RB, 30 MHz, QPSK, 15 kHz)   | 5G NR FR1 FDD | 5.87     | ±9.6                   |
| 10950 | AAC | 5G NR (DFT-s-OFDM, 100% RB, 40 MHz, QPSK, 15 kHz)   | 5G NR FR1 FDD | 5.94     | ±9.6                   |
| 10951 | AAD | 5G NR (DFT-s-OFDM, 100% RB, 50 MHz, QPSK, 15 kHz)   | 5G NR FR1 FDD | 5.92     | ±9.6                   |
| 10952 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 15 kHz)   | 5G NR FR1 FDD | 8.25     | ±9.6                   |
| 10953 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-QAM, 15 kHz)  | 5G NR FR1 FDD | 8.15     | ±9.6                   |
| 10954 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 15 kHz)  | 5G NR FR1 FDD | 8.23     | ±9.6                   |
| 10955 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 15 kHz)  | 5G NR FR1 FDD | 8.42     | ±9.6                   |
| 10956 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 30 kHz)   | 5G NR FR1 FDD | 8.14     | ±9.6                   |
| 10957 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-QAM, 30 kHz)  | 5G NR FR1 FDD | 8.31     | ±9.6                   |
| 10958 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 30 kHz)  | 5G NR FR1 FDD | 8.81     | ±9.6                   |
| 10959 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 30 kHz)  | 5G NR FR1 FDD | 8.33     | ±9.6                   |
| 10960 | AAE | 5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 15 kHz)   | 5G NR FR1 TDD | 9.32     | ±9.6                   |
| 10961 | AAC | 5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-QAM, 15 kHz)  | 5G NR FR1 TDD | 9.36     | ±9.6                   |
| 10962 | AAB | 5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 15 kHz)  | 5G NR FR1 TDD | 9.40     | ±9.6                   |
| 10963 | AAC | 5G NR DL (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 15 kHz)  | 5G NR FR1 TDD | 9.55     | ±9.6                   |
| 10964 | AAE | 5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 30 kHz)   | 5G NR FR1 TDD | 9.29     | ±9.6                   |
| 10965 | AAC | 5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-QAM, 30 kHz)  | 5G NR FR1 TDD | 9.37     | ±9.6                   |
| 10966 | AAB | 5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 30 kHz)  | 5G NR FR1 TDD | 9.55     | ±9.6                   |
| 10967 | AAC | 5G NR DL (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 30 kHz)  | 5G NR FR1 TDD | 9.42     | ±9.6                   |
| 10968 | AAD | 5G NR DL (CP-OFDM, TM 3.1, 100 MHz, 64-QAM, 30 kHz) | 5G NR FR1 TDD | 9.49     | ±9.6                   |
| 10972 | AAC | 5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 15 kHz)         | 5G NR FR1 TDD | 11.59    | ±9.6                   |
| 10973 | AAD | 5G NR (DFT-s-OFDM, 1 RB, 100 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 9.06     | ±9.6                   |
| 10974 | AAD | 5G NR (CP-OFDM, 100% RB, 100 MHz, 256-QAM, 30 kHz)  | 5G NR FR1 TDD | 10.28    | ±9.6                   |
| 10976 | AAA | ULLA BDR                                            | ULLA          | 1.16     | ±9.6                   |
| 10979 | AAA | ULLA HDR4                                           | ULLA          | 8.58     | ±9.6                   |
| 10980 | AAA | ULLA HDR8                                           | ULLA          | 10.32    | ±9.6                   |
| 10981 | AAA | ULLA HDRp4                                          | ULLA          | 3.19     | ±9.6                   |
| 10982 | AAA | ULLA HDRp8                                          | ULLA          | 3.43     | ±9.6                   |

| UID   | Rev | Communication System Name                          | Group         | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|----------------------------------------------------|---------------|----------|------------------------|
| 10983 | AAC | 5G NR DL (CP-OFDM, TM 3.1, 40 MHz, 64-QAM, 15 kHz) | 5G NR FR1 TDD | 9.31     | ±9.6                   |
| 10984 | AAB | 5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 15 kHz) | 5G NR FR1 TDD | 9.42     | ±9.6                   |
| 10985 | AAC | 5G NR DL (CP-OFDM, TM 3.1, 40 MHz, 64-QAM, 30 kHz) | 5G NR FR1 TDD | 9.54     | ±9.6                   |
| 10986 | AAB | 5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 30 kHz) | 5G NR FR1 TDD | 9.50     | ±9.6                   |
| 10987 | AAC | 5G NR DL (CP-OFDM, TM 3.1, 60 MHz, 64-QAM, 30 kHz) | 5G NR FR1 TDD | 9.53     | ±9.6                   |
| 10988 | AAB | 5G NR DL (CP-OFDM, TM 3.1, 70 MHz, 64-QAM, 30 kHz) | 5G NR FR1 TDD | 9.38     | ±9.6                   |
| 10989 | AAC | 5G NR DL (CP-OFDM, TM 3.1, 80 MHz, 64-QAM, 30 kHz) | 5G NR FR1 TDD | 9.33     | ±9.6                   |
| 10990 | AAB | 5G NR DL (CP-OFDM, TM 3.1, 90 MHz, 64-QAM, 30 kHz) | 5G NR FR1 TDD | 9.52     | ±9.6                   |
| 11003 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 15 kHz) | 5G NR FR1 TDD | 10.24    | ±9.6                   |
| 11004 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 30 kHz) | 5G NR FR1 TDD | 10.73    | ±9.6                   |
| 11005 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 25 MHz, 64-QAM, 15 kHz) | 5G NR FR1 FDD | 8.70     | ±9.6                   |
| 11006 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 15 kHz) | 5G NR FR1 FDD | 8.55     | ±9.6                   |
| 11007 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 40 MHz, 64-QAM, 15 kHz) | 5G NR FR1 FDD | 8.46     | ±9.6                   |
| 11008 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 15 kHz) | 5G NR FR1 FDD | 8.51     | ±9.6                   |
| 11009 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 25 MHz, 64-QAM, 30 kHz) | 5G NR FR1 FDD | 8.76     | ±9.6                   |
| 11010 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 30 kHz) | 5G NR FR1 FDD | 8.95     | ±9.6                   |
| 11011 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 40 MHz, 64-QAM, 30 kHz) | 5G NR FR1 FDD | 8.96     | ±9.6                   |
| 11012 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 30 kHz) | 5G NR FR1 FDD | 8.68     | ±9.6                   |
| 11013 | AAB | IEEE 802.11be (320 MHz, MCS1, 99pc duty cycle)     | WLAN          | 8.47     | ±9.6                   |
| 11014 | AAB | IEEE 802.11be (320 MHz, MCS2, 99pc duty cycle)     | WLAN          | 8.45     | ±9.6                   |
| 11015 | AAB | IEEE 802.11be (320 MHz, MCS3, 99pc duty cycle)     | WLAN          | 8.44     | ±9.6                   |
| 11016 | AAB | IEEE 802.11be (320 MHz, MCS4, 99pc duty cycle)     | WLAN          | 8.44     | ±9.6                   |
| 11017 | AAB | IEEE 802.11be (320 MHz, MCS5, 99pc duty cycle)     | WLAN          | 8.41     | ±9.6                   |
| 11018 | AAB | IEEE 802.11be (320 MHz, MCS6, 99pc duty cycle)     | WLAN          | 8.40     | ±9.6                   |
| 11019 | AAB | IEEE 802.11be (320 MHz, MCS7, 99pc duty cycle)     | WLAN          | 8.29     | ±9.6                   |
| 11020 | AAB | IEEE 802.11be (320 MHz, MCS8, 99pc duty cycle)     | WLAN          | 8.27     | ±9.6                   |
| 11021 | AAB | IEEE 802.11be (320 MHz, MCS9, 99pc duty cycle)     | WLAN          | 8.46     | ±9.6                   |
| 11022 | AAB | IEEE 802.11be (320 MHz, MCS10, 99pc duty cycle)    | WLAN          | 8.36     | ±9.6                   |
| 11023 | AAB | IEEE 802.11be (320 MHz, MCS11, 99pc duty cycle)    | WLAN          | 8.09     | ±9.6                   |
| 11024 | AAB | IEEE 802.11be (320 MHz, MCS12, 99pc duty cycle)    | WLAN          | 8.42     | ±9.6                   |
| 11025 | AAB | IEEE 802.11be (320 MHz, MCS13, 99pc duty cycle)    | WLAN          | 8.37     | ±9.6                   |
| 11026 | AAB | IEEE 802.11be (320 MHz, MCS0, 99pc duty cycle)     | WLAN          | 8.39     | ±9.6                   |

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.



Client

**Sporton**  
Taoyuan City

Certificate No.

**EX-7700\_Jan26**

## CALIBRATION CERTIFICATE

Object

**EX3DV4 - SN:7700**

Calibration procedure(s)

QA CAL-01.v10, QA CAL-12.v10, QA CAL-14.v7, QA CAL-23.v6,  
QA CAL-25.v8, QA CAL-48.v2  
Calibration procedure for dosimetric E-field probes

Calibration date

**January 26, 2026**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^\circ\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID         | Calibration Date (Certificate No.)     | Sched. Cal. |
|-----------------------------|------------|----------------------------------------|-------------|
| Power Sensor R&S NRP40T     | SN: 101861 | 29-Apr-25 (No. 2025-001450)            | Apr-26      |
| N-type mismatch combination | SN: L1119  | 26-Mar-25 (No. 217-04292)              | Mar-26      |
| OCP DAK-12                  | SN: 1016   | 16-Sept-25 (No. OCP-DAK12-1016_Sep25)  | Sep-26      |
| OCP DAK-3,5                 | SN: 1249   | 16-Sept-25 (No. OCP-DAK3.5-1249_Sep25) | Sep-26      |
| Reference Probe EX3DV4      | SN: 7349   | 10-Jan-25 (No. EX3-7349_Jan25)         | Jan-26      |
| DAE4                        | SN: 1301   | 22-Jan-26 (No. DAE4-1301_Jan26)        | Jan-27      |

| Secondary Standards | ID        | Check Date (in house)                 | Sched. Check |
|---------------------|-----------|---------------------------------------|--------------|
| ACAP 2020 Setup 1   | SN: L1404 | 01-Oct-25 (No. IHCK_ACAP2020-1_Oct25) | Oct-26       |
| OCP DAK-12          | SN: 1029  | 27-Feb-25 (No. OCP-DAK12-1029_Feb25)  | Feb-26       |
| OCP DAK-3,5         | SN: 1336  | 10-Dec-25 (No. OCP-DAK3.5-1336_Dec25) | Dec-26       |

|                                                                                                                 | Name           | Function              | Signature |
|-----------------------------------------------------------------------------------------------------------------|----------------|-----------------------|-----------|
| Calibrated by                                                                                                   | Joanna Lleshaj | Laboratory Technician |           |
| Approved by                                                                                                     | Sven Kühn      | Technical Manager     |           |
| Issued: January 27, 2026                                                                                        |                |                       |           |
| This calibration certificate shall not be reproduced except in full without written approval of the laboratory. |                |                       |           |

## Calibration Laboratory of

Schmid & Partner  
Engineering AG

Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
C Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

## Glossary

|                        |                                                                                                                                                |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| TSL                    | tissue simulating liquid                                                                                                                       |
| NORM <sub>x,y,z</sub>  | sensitivity in free space                                                                                                                      |
| ConvF                  | sensitivity in TSL / NORM <sub>x,y,z</sub>                                                                                                     |
| DCP                    | diode compression point                                                                                                                        |
| CF                     | crest factor (1/duty_cycle) of the RF signal                                                                                                   |
| A, B, C, D             | modulation dependent linearization parameters                                                                                                  |
| Polarization $\varphi$ | $\varphi$ rotation around probe axis                                                                                                           |
| Polarization $\theta$  | $\theta$ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\theta = 0$ is normal to probe axis |
| Connector Angle        | information used in DASY system to align probe sensor X to the robot coordinate system                                                         |

## Calibration is Performed According to the Following Standards:

- IEC/IEEE 62209-1528, "Measurement Procedure For The Assessment Of Specific Absorption Rate Of Human Exposure To Radio Frequency Fields From Hand-Held And Body-Worn Wireless Communication Devices – Part 1528: Human Models, Instrumentation And Procedures (Frequency Range of 4 MHz to 10 GHz)", October 2020.
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

## Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\theta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not affect the E<sup>2</sup>-field uncertainty inside TSL (see below ConvF).
- NORM(f)<sub>x,y,z</sub> = NORM<sub>x,y,z</sub> \* frequency\_response** (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal. DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; D<sub>x,y,z</sub>; VR<sub>x,y,z</sub>; A, B, C, D** are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM<sub>x</sub> (no uncertainty required).

## Parameters of Probe: EX3DV4 - SN:7700

## Basic Calibration Parameters

|                                                           | Sensor X | Sensor Y | Sensor Z | Unc (k = 2) |
|-----------------------------------------------------------|----------|----------|----------|-------------|
| Norm ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) <sup>A</sup> | 0.63     | 0.64     | 0.67     | ±10.1%      |
| DCP (mV) <sup>B</sup>                                     | 106.4    | 105.7    | 105.4    | ±4.7%       |

## Calibration Results for Modulation Response

| UID   | Communication System Name      |   | A<br>dB | B<br>dB $\sqrt{\mu\text{V}}$ | C     | D<br>dB | VR<br>mV | Max<br>dev. | Max<br>Unc <sup>E</sup><br>k = 2 |
|-------|--------------------------------|---|---------|------------------------------|-------|---------|----------|-------------|----------------------------------|
| 0     | Continuous Wave                | X | 0.00    | 0.00                         | 1.00  | 0.00    | 129.4    | ±2.0%       | ±4.7%                            |
|       |                                | Y | 0.00    | 0.00                         | 1.00  |         | 137.4    |             |                                  |
|       |                                | Z | 0.00    | 0.00                         | 1.00  |         | 135.4    |             |                                  |
| 10352 | Pulse (D=10%, T=5 ms)          | X | 0.81    | 69.92                        | 17.76 | 10.00   | 23.0     | ±1.7%       | ±9.6%                            |
|       |                                | Y | 0.28    | 60.15                        | 15.10 |         | 24.0     |             |                                  |
|       |                                | Z | 0.58    | 69.94                        | 18.35 |         | 24.0     |             |                                  |
| 10353 | Pulse (D=20%, T=5 ms)          | X | 0.76    | 72.93                        | 17.79 | 6.99    | 47.0     | ±1.3%       | ±9.6%                            |
|       |                                | Y | 0.26    | 63.16                        | 15.17 |         | 48.0     |             |                                  |
|       |                                | Z | 0.54    | 72.95                        | 18.40 |         | 48.0     |             |                                  |
| 10354 | Pulse (D=40%, T=5 ms)          | X | 0.71    | 75.94                        | 17.83 | 3.98    | 93.0     | ±1.2%       | ±9.6%                            |
|       |                                | Y | 0.23    | 66.17                        | 15.24 |         | 95.0     |             |                                  |
|       |                                | Z | 0.50    | 75.96                        | 18.46 |         | 97.0     |             |                                  |
| 10355 | Pulse (D=60%, T=5 ms)          | X | 0.68    | 77.71                        | 17.86 | 2.22    | 139.0    | ±1.2%       | ±9.6%                            |
|       |                                | Y | 0.22    | 67.93                        | 15.29 |         | 143.0    |             |                                  |
|       |                                | Z | 0.48    | 77.72                        | 18.50 |         | 145.0    |             |                                  |
| 10387 | Random (BW=1 MHz, MOD=QPSK)    | X | 0.01    | 74.83                        | 19.16 | 0.20    | 107.0    | ±1.4%       | ±9.6%                            |
|       |                                | Y | 0.00    | 65.05                        | 17.05 |         | 110.0    |             |                                  |
|       |                                | Z | 0.01    | 74.84                        | 19.91 |         | 112.0    |             |                                  |
| 10388 | Random (BW=10 MHz, MOD=QPSK)   | X | 1.59    | 74.71                        | 17.41 | 0.00    | 113.0    | ±2.4%       | ±9.6%                            |
|       |                                | Y | 0.56    | 64.93                        | 14.31 |         | 116.0    |             |                                  |
|       |                                | Z | 1.62    | 74.72                        | 17.53 |         | 118.0    |             |                                  |
| 10396 | Random (BW=100 kHz, MOD=64QAM) | X | 0.00    | 73.65                        | 20.01 | 1.52    | 80.0     | ±3.2%       | ±9.6%                            |
|       |                                | Y | 0.00    | 63.87                        | 18.49 |         | 82.0     |             |                                  |
|       |                                | Z | 0.02    | 73.67                        | 21.37 |         | 84.0     |             |                                  |
| 10399 | Random (BW=40 MHz, MOD=64QAM)  | X | 3.73    | 73.65                        | 17.31 | 0.00    | 105.0    | ±3.7%       | ±9.6%                            |
|       |                                | Y | 1.68    | 63.87                        | 12.91 |         | 108.0    |             |                                  |
|       |                                | Z | 3.71    | 73.67                        | 17.38 |         | 110.0    |             |                                  |
| 10414 | Random (BW=40 MHz, HIGH PAR)   | X | 4.44    | 71.39                        | 17.30 | 0.00    | 75.0     | ±1.7%       | ±9.6%                            |
|       |                                | Y | 1.96    | 61.61                        | 12.81 |         | 78.0     |             |                                  |
|       |                                | Z | 4.52    | 71.40                        | 17.38 |         | 80.0     |             |                                  |

Note: For details on UID parameters see Appendix

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of Norm X,Y,Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Pages 5 and 6).

<sup>B</sup> Linearization parameter uncertainty for maximum specified field strength.

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

## Parameters of Probe: EX3DV4 - SN:7700

### Sensor Model Parameters

|   | C1<br>fF | C2<br>fF | $\alpha$<br>$V^{-1}$ | T1<br>$ms V^{-2}$ | T2<br>$ms V^{-1}$ | T3<br>ms | T4<br>$V^{-2}$ | T5<br>$V^{-1}$ | T6   |
|---|----------|----------|----------------------|-------------------|-------------------|----------|----------------|----------------|------|
| x | 8.9      | 64.60    | 33.42                | 3.03              | 0.00              | 4.90     | 0.39           | 0.00           | 1.00 |
| y | 7.9      | 57.28    | 33.97                | 3.73              | 0.00              | 4.90     | 0.43           | 0.00           | 1.00 |
| z | 9.9      | 72.50    | 34.24                | 3.10              | 0.00              | 4.90     | 0.00           | 0.02           | 1.00 |

### Other Probe Parameters

|                                               |            |
|-----------------------------------------------|------------|
| Sensor Arrangement                            | Triangular |
| Connector Angle                               | -70.6°     |
| Mechanical Surface Detection Mode             | enabled    |
| Optical Surface Detection Mode                | disabled   |
| Probe Overall Length                          | 337 mm     |
| Probe Body Diameter                           | 12 mm      |
| Tip Length                                    | 9 mm       |
| Tip Diameter                                  | 2.5 mm     |
| Probe Tip to Sensor X Calibration Point       | 1 mm       |
| Probe Tip to Sensor Y Calibration Point       | 1 mm       |
| Probe Tip to Sensor Z Calibration Point       | 1 mm       |
| Recommended Measurement Distance from Surface | 1.4 mm     |

**Note:** Measurement distance from surface can be increased to 3–4 mm for an *Area Scan* job.

## Parameters of Probe: EX3DV4 - SN:7700

## Calibration Parameter Determined in HSL

| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity <sup>F</sup> (S/m) | ConvF X | ConvF Y | ConvF Z | Alpha <sup>G</sup> | Depth <sup>G</sup> (mm) | Unc <sup>H</sup> (k = 2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|--------------------------|
| 750                  | 41.9                               | 0.89                            | 9.98    | 9.68    | 9.75    | 0.39               | 1.27                    | ±11.0%                   |
| 835                  | 41.5                               | 0.90                            | 9.97    | 9.66    | 9.74    | 0.39               | 1.27                    | ±11.0%                   |
| 900                  | 41.5                               | 0.97                            | 9.55    | 9.25    | 9.33    | 0.38               | 1.27                    | ±11.0%                   |
| 1750                 | 40.1                               | 1.37                            | 8.26    | 8.00    | 8.07    | 0.37               | 1.27                    | ±11.0%                   |
| 1900                 | 40.0                               | 1.40                            | 8.08    | 7.83    | 7.89    | 0.37               | 1.27                    | ±11.0%                   |
| 2000                 | 40.0                               | 1.40                            | 7.82    | 7.58    | 7.64    | 0.37               | 1.27                    | ±11.0%                   |
| 2300                 | 39.5                               | 1.67                            | 7.76    | 7.52    | 7.57    | 0.37               | 1.27                    | ±11.0%                   |
| 2450                 | 39.2                               | 1.80                            | 7.46    | 7.23    | 7.29    | 0.37               | 1.27                    | ±11.0%                   |
| 2600                 | 39.0                               | 1.96                            | 7.62    | 7.39    | 7.44    | 0.36               | 1.27                    | ±11.0%                   |
| 3300                 | 38.2                               | 2.71                            | 6.80    | 6.59    | 6.64    | 0.36               | 1.27                    | ±13.1%                   |
| 3500                 | 37.9                               | 2.91                            | 6.73    | 6.52    | 6.57    | 0.35               | 1.27                    | ±13.1%                   |
| 3700                 | 37.7                               | 3.12                            | 6.87    | 6.66    | 6.71    | 0.35               | 1.27                    | ±13.1%                   |
| 3900                 | 37.5                               | 3.32                            | 6.84    | 6.63    | 6.68    | 0.35               | 1.27                    | ±13.1%                   |
| 4100                 | 37.2                               | 3.53                            | 6.64    | 6.43    | 6.48    | 0.35               | 1.27                    | ±13.1%                   |
| 5250                 | 35.9                               | 4.71                            | 5.66    | 5.49    | 5.53    | 0.31               | 1.27                    | ±13.1%                   |
| 5600                 | 35.5                               | 5.07                            | 5.27    | 5.11    | 5.15    | 0.28               | 1.27                    | ±13.1%                   |
| 5800                 | 35.3                               | 5.27                            | 5.21    | 5.05    | 5.09    | 0.26               | 1.27                    | ±13.1%                   |

<sup>C</sup> Frequency validity above 300 MHz of ±100 MHz only applies for DASY v4.4 and higher (see Page 2); else it is restricted to ±50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ±10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Validity of ConvF assessed at 6 MHz is 4–8 MHz, and ConvF assessed at 13 MHz is 9–19 MHz. Above 5 GHz frequency validity can be extended to ±110 MHz.

<sup>F</sup> The probes are calibrated using tissue simulating liquids (TSL) that deviate for  $\epsilon$  and  $\sigma$  by less than ±5% from the target values (typically better than ±3%) and are valid for TSL with deviations of up to ±10% if SAR correction is applied.

<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ±1% for frequencies below 3 GHz and below ±2% for frequencies between 3–6 GHz at any distance larger than half the probe tip diameter from the boundary.

<sup>H</sup> The stated uncertainty is the total calibration uncertainty (k = 2) of Norm-ConvF. This is equivalent to the uncertainty component with the symbol CF in Table 9 of IEC/IEEE 62209-1528:2020.

**Parameters of Probe: EX3DV4 - SN:7700****Calibration Parameter Determined in HSL**

| <b>f (MHz)<sup>C</sup></b> | <b>Relative Permittivity<sup>F</sup></b> | <b>Conductivity<sup>F</sup> (S/m)</b> | <b>ConvF X</b> | <b>ConvF Y</b> | <b>ConvF Z</b> | <b>Alpha<sup>G</sup></b> | <b>Depth<sup>G</sup> (mm)</b> | <b>Unc<sup>H</sup> (k = 2)</b> |
|----------------------------|------------------------------------------|---------------------------------------|----------------|----------------|----------------|--------------------------|-------------------------------|--------------------------------|
| 6500                       | 34.5                                     | 6.07                                  | 5.68           | 5.50           | 5.54           | 0.20                     | 1.27                          | ±18.6%                         |

<sup>C</sup> Frequency validity is -600/+700 MHz at 6.5 GHz, ±700 MHz at or above 7 GHz, and ±150 MHz at 9.85 GHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.


<sup>F</sup> The probes are calibrated using tissue simulating liquids (TSL) that deviate for  $\epsilon$  and  $\sigma$  by less than ±10% from the target values (typically better than ±6%) and are valid for TSL with deviations of up to ±10%.

<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ±1% for frequencies below 3 GHz; below ±2% for frequencies between 3–6 GHz; and below ±4% for frequencies between 6–10 GHz at any distance larger than half the probe tip diameter from the boundary.



<sup>H</sup> The stated uncertainty is the total calibration uncertainty (k = 2) of Norm-ConvF. This is equivalent to the uncertainty component with the symbol CF in Table 9 of IEC/IEEE 62209-1526:2020.



## Frequency Response of E-Field

(TEM-Cell:ifl110 EXX, Waveguide:R22)




Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  ( $k=2$ )

Receiving Pattern ( $\phi$ ),  $\vartheta = 0^\circ$ Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  ( $k=2$ )


**Dynamic Range  $f(\text{SAR}_{\text{HSL}})$** (TEM cell,  $f_{\text{eval}} = 1900 \text{ MHz}$ )Uncertainty of Linearity Assessment:  $\pm 0.6\%$  ( $k=2$ )

## Conversion Factor Assessment



## Deviation from Isotropy in Liquid

Error  $(\phi, \theta)$ ,  $f = 900\text{ MHz}$



## Appendix: Modulation Calibration Parameters

| UID   | Rev | Communication System Name                      | Group     | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|------------------------------------------------|-----------|----------|------------------------|
| 0     |     | Continuous Wave                                | CW        | 0.00     | ±4.7                   |
| 10010 | CAB | Pulse (D=10%, T=100 ms)                        | Test      | 10.00    | ±9.6                   |
| 10011 | CAC | Rel. 99, RMC, QPSK, 5.0 MHz                    | WCDMA     | 2.91     | ±9.6                   |
| 10012 | CAB | DSSS, DBPSK, 1.0 Mbps, 92.5% DC                | WLAN      | 1.87     | ±9.6                   |
| 10013 | CAB | OFDM, BPSK, 6.0 Mbps, 72.1% DC                 | WLAN      | 9.46     | ±9.6                   |
| 10021 | DAC | Voice, GMSK, 1 slot(s)                         | GSM       | 9.39     | ±9.6                   |
| 10023 | DAC | Data, GMSK, 1 slot(s)                          | GSM       | 9.57     | ±9.6                   |
| 10024 | DAC | Data, GMSK, 2 slot(s)                          | GSM       | 6.56     | ±9.6                   |
| 10025 | DAC | Data, 8PSK, 1 slot(s)                          | GSM       | 12.62    | ±9.6                   |
| 10026 | DAC | Data, 8PSK, 2 slot(s)                          | GSM       | 9.55     | ±9.6                   |
| 10027 | DAC | Data, GMSK, 3 slot(s)                          | GSM       | 4.80     | ±9.6                   |
| 10028 | DAC | Data, GMSK, 4 slot(s)                          | GSM       | 3.55     | ±9.6                   |
| 10029 | DAC | Data, 8PSK, 3 slot(s)                          | GSM       | 7.78     | ±9.6                   |
| 10030 | CAA | BR, DH1, GFSK                                  | Bluetooth | 5.30     | ±9.6                   |
| 10031 | CAA | BR, DH3, GFSK                                  | Bluetooth | 1.87     | ±9.6                   |
| 10032 | CAA | BR, DH5, GFSK                                  | Bluetooth | 1.16     | ±9.6                   |
| 10033 | CAA | EDR, DH1, pi/4-DQPSK                           | Bluetooth | 7.74     | ±9.6                   |
| 10034 | CAA | EDR, DH3, pi/4-DQPSK                           | Bluetooth | 4.53     | ±9.6                   |
| 10035 | CAA | EDR, DH5, pi/4-DQPSK                           | Bluetooth | 3.83     | ±9.6                   |
| 10036 | CAA | EDR, DH1, 8-DPSK                               | Bluetooth | 8.01     | ±9.6                   |
| 10037 | CAA | EDR, DH3, 8-DPSK                               | Bluetooth | 4.77     | ±9.6                   |
| 10038 | CAA | EDR, DH5, 8-DPSK                               | Bluetooth | 4.10     | ±9.6                   |
| 10039 | CAB | RC1, 1xRTT                                     | CDMA2000  | 4.57     | ±9.6                   |
| 10048 | CAA | Full Slot, GFSK, 1 slot(s)                     | DECT      | 13.80    | ±9.6                   |
| 10049 | CAA | Double Slot, GFSK, 2 slot(s)                   | DECT      | 10.79    | ±9.6                   |
| 10056 | CAA | TD-SCDMA, QPSK, 1.6 MHz                        | TD-SCDMA  | 11.01    | ±9.6                   |
| 10058 | DAC | Data, 8PSK, 4 slot(s)                          | GSM       | 6.52     | ±9.6                   |
| 10059 | CAB | DSSS, DQPSK, 2.0 Mbps, 87.4% DC                | WLAN      | 2.12     | ±9.6                   |
| 10060 | CAB | HR-DSSS, DQPSK, 5.5 Mbps, 72.7% DC             | WLAN      | 2.83     | ±9.6                   |
| 10061 | CAB | HR-DSSS, DQPSK, 11.0 Mbps, 57.5% DC            | WLAN      | 3.60     | ±9.6                   |
| 10062 | CAE | OFDM, BPSK, 6.0 Mbps, 89.1% DC                 | WLAN      | 8.68     | ±9.6                   |
| 10063 | CAE | OFDM, BPSK, 9.0 Mbps, 85.3% DC                 | WLAN      | 8.63     | ±9.6                   |
| 10064 | CAE | OFDM, QPSK, 12.0 Mbps, 82.0% DC                | WLAN      | 9.09     | ±9.6                   |
| 10065 | CAE | OFDM, QPSK, 18.0 Mbps, 76.0% DC                | WLAN      | 9.00     | ±9.6                   |
| 10066 | CAE | OFDM, 16QAM, 24.0 Mbps, 70.6% DC               | WLAN      | 9.38     | ±9.6                   |
| 10067 | CAE | OFDM, 16QAM, 36.0 Mbps, 62.9% DC               | WLAN      | 10.12    | ±9.6                   |
| 10068 | CAE | OFDM, 64QAM, 48.0 Mbps, 56.6% DC               | WLAN      | 10.24    | ±9.6                   |
| 10069 | CAE | OFDM, 64QAM, 54.0 Mbps, 54.4% DC               | WLAN      | 10.56    | ±9.6                   |
| 10071 | CAB | OFDM, BPSK, 9.0 Mbps, 65.1% DC                 | WLAN      | 9.83     | ±9.6                   |
| 10072 | CAB | OFDM, QPSK, 12.0 Mbps, 60.1% DC                | WLAN      | 9.62     | ±9.6                   |
| 10073 | CAB | OFDM, QPSK, 18.0 Mbps, 53.1% DC                | WLAN      | 9.94     | ±9.6                   |
| 10074 | CAB | OFDM, 16QAM, 24.0 Mbps, 48.5% DC               | WLAN      | 10.30    | ±9.6                   |
| 10075 | CAB | OFDM, 16QAM, 36.0 Mbps, 42.9% DC               | WLAN      | 10.77    | ±9.6                   |
| 10076 | CAB | OFDM, 64QAM, 48.0 Mbps, 39.5% DC               | WLAN      | 10.94    | ±9.6                   |
| 10077 | CAB | OFDM, 64QAM, 54.0 Mbps, 38.5% DC               | WLAN      | 11.00    | ±9.6                   |
| 10081 | CAB | RC3, 1xRTT                                     | CDMA2000  | 3.97     | ±9.6                   |
| 10097 | CAC | Rel. 5 HSDPA, QPSK, 5.0 MHz                    | WCDMA     | 3.98     | ±9.6                   |
| 10098 | CAC | Rel. 6 HSUPA, Subset 2, QPSK, 5.0 MHz          | WCDMA     | 3.98     | ±9.6                   |
| 10100 | CAF | 20.0 MHz, QPSK, 100% RB                        | LTE-FDD   | 5.67     | ±9.6                   |
| 10101 | CAF | 20.0 MHz, 16QAM, 100% RB                       | LTE-FDD   | 6.42     | ±9.6                   |
| 10102 | CAF | 20.0 MHz, 64QAM, 100% RB                       | LTE-FDD   | 6.60     | ±9.6                   |
| 10103 | CAH | 20.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB  | LTE-TDD   | 9.29     | ±9.6                   |
| 10104 | CAH | 20.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB | LTE-TDD   | 9.97     | ±9.6                   |
| 10105 | CAH | 20.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 100% RB | LTE-TDD   | 10.01    | ±9.6                   |
| 10108 | CAH | 10.0 MHz, QPSK, 100% RB                        | LTE-FDD   | 5.80     | ±9.6                   |
| 10109 | CAH | 10.0 MHz, 16QAM, 100% RB                       | LTE-FDD   | 6.43     | ±9.6                   |
| 10110 | CAH | 5.0 MHz, QPSK, 100% RB                         | LTE-FDD   | 5.75     | ±9.6                   |
| 10111 | CAH | 5.0 MHz, 16QAM, 100% RB                        | LTE-FDD   | 6.44     | ±9.6                   |
| 10112 | CAH | 10.0 MHz, 64QAM, 100% RB                       | LTE-FDD   | 6.59     | ±9.6                   |
| 10113 | CAH | 5.0 MHz, 64QAM, 100% RB                        | LTE-FDD   | 6.62     | ±9.6                   |
| 10114 | CAE | HT40 Greenfield, MCS0 (13.5 Mbps), 99.7% DC    | WLAN      | 8.10     | ±9.6                   |
| 10115 | CAE | HT40 Greenfield, MCS4 (81.0 Mbps), 99.7% DC    | WLAN      | 8.46     | ±9.6                   |
| 10116 | CAE | HT40 Greenfield, MCS7 (135.0 Mbps), 99.7% DC   | WLAN      | 8.15     | ±9.6                   |

| UID   | Rev | Communication System Name                     | Group   | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|-----------------------------------------------|---------|----------|------------------------|
| 10117 | CAE | HT40 Mixed, MCS0 (13.5 Mbps), 99.7% DC        | WLAN    | 8.07     | ±9.6                   |
| 10118 | CAE | HT40 Mixed, MCS4 (81.0 Mbps), 99.7% DC        | WLAN    | 8.59     | ±9.6                   |
| 10119 | CAE | HT40 Mixed, MCS7 (135.0 Mbps), 99.7% DC       | WLAN    | 8.13     | ±9.6                   |
| 10140 | CAF | 15.0 MHz, 16QAM, 100% RB                      | LTE-FDD | 6.49     | ±9.6                   |
| 10141 | CAF | 15.0 MHz, 64QAM, 100% RB                      | LTE-FDD | 6.53     | ±9.6                   |
| 10142 | CAF | 3.0 MHz, QPSK, 100% RB                        | LTE-FDD | 5.73     | ±9.6                   |
| 10143 | CAF | 3.0 MHz, 16QAM, 100% RB                       | LTE-FDD | 6.35     | ±9.6                   |
| 10144 | CAF | 3.0 MHz, 64QAM, 100% RB                       | LTE-FDD | 6.65     | ±9.6                   |
| 10145 | CAG | 1.4 MHz, QPSK, 100% RB                        | LTE-FDD | 5.76     | ±9.6                   |
| 10146 | CAG | 1.4 MHz, 16QAM, 100% RB                       | LTE-FDD | 6.41     | ±9.6                   |
| 10147 | CAG | 1.4 MHz, 64QAM, 100% RB                       | LTE-FDD | 6.72     | ±9.6                   |
| 10149 | CAF | 20.0 MHz, 16QAM, 50% RB                       | LTE-FDD | 6.42     | ±9.6                   |
| 10150 | CAF | 20.0 MHz, 64QAM, 50% RB                       | LTE-FDD | 6.60     | ±9.6                   |
| 10151 | CAH | 20.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB  | LTE-TDD | 9.28     | ±9.6                   |
| 10152 | CAH | 20.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB | LTE-TDD | 9.92     | ±9.6                   |
| 10153 | CAH | 20.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 50% RB | LTE-TDD | 10.05    | ±9.6                   |
| 10154 | CAH | 10.0 MHz, QPSK, 50% RB                        | LTE-FDD | 5.75     | ±9.6                   |
| 10155 | CAH | 10.0 MHz, 16QAM, 50% RB                       | LTE-FDD | 6.43     | ±9.6                   |
| 10156 | CAH | 5.0 MHz, QPSK, 50% RB                         | LTE-FDD | 5.79     | ±9.6                   |
| 10157 | CAH | 5.0 MHz, 16QAM, 50% RB                        | LTE-FDD | 6.49     | ±9.6                   |
| 10158 | CAH | 10.0 MHz, 64QAM, 50% RB                       | LTE-FDD | 6.62     | ±9.6                   |
| 10159 | CAH | 5.0 MHz, 64QAM, 50% RB                        | LTE-FDD | 6.56     | ±9.6                   |
| 10160 | CAF | 15.0 MHz, QPSK, 50% RB                        | LTE-FDD | 5.82     | ±9.6                   |
| 10161 | CAF | 15.0 MHz, 16QAM, 50% RB                       | LTE-FDD | 6.43     | ±9.6                   |
| 10162 | CAF | 15.0 MHz, 64QAM, 50% RB                       | LTE-FDD | 6.58     | ±9.6                   |
| 10166 | CAG | 1.4 MHz, QPSK, 50% RB                         | LTE-FDD | 5.46     | ±9.6                   |
| 10167 | CAG | 1.4 MHz, 16QAM, 50% RB                        | LTE-FDD | 6.21     | ±9.6                   |
| 10168 | CAG | 1.4 MHz, 64QAM, 50% RB                        | LTE-FDD | 6.79     | ±9.6                   |
| 10169 | CAF | 20.0 MHz, QPSK, 1 RB                          | LTE-FDD | 5.73     | ±9.6                   |
| 10170 | CAF | 20.0 MHz, 16QAM, 1 RB                         | LTE-FDD | 6.52     | ±9.6                   |
| 10171 | AAF | 20.0 MHz, 64QAM, 1 RB                         | LTE-FDD | 6.49     | ±9.6                   |
| 10172 | CAH | 20.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB    | LTE-TDD | 9.21     | ±9.6                   |
| 10173 | CAH | 20.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 1 RB   | LTE-TDD | 9.48     | ±9.6                   |
| 10174 | CAH | 20.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 1 RB   | LTE-TDD | 10.25    | ±9.6                   |
| 10175 | CAH | 10.0 MHz, QPSK, 1 RB                          | LTE-FDD | 5.72     | ±9.6                   |
| 10176 | CAH | 10.0 MHz, 16QAM, 1 RB                         | LTE-FDD | 6.52     | ±9.6                   |
| 10177 | CAJ | 5.0 MHz, QPSK, 1 RB                           | LTE-FDD | 5.73     | ±9.6                   |
| 10178 | CAH | 5.0 MHz, 16QAM, 1 RB                          | LTE-FDD | 6.52     | ±9.6                   |
| 10179 | CAH | 10.0 MHz, 64QAM, 1 RB                         | LTE-FDD | 6.50     | ±9.6                   |
| 10180 | CAH | 5.0 MHz, 64QAM, 1 RB                          | LTE-FDD | 6.50     | ±9.6                   |
| 10181 | CAF | 15.0 MHz, QPSK, 1 RB                          | LTE-FDD | 5.72     | ±9.6                   |
| 10182 | CAF | 15.0 MHz, 16QAM, 1 RB                         | LTE-FDD | 6.52     | ±9.6                   |
| 10183 | AAE | 15.0 MHz, 64QAM, 1 RB                         | LTE-FDD | 6.50     | ±9.6                   |
| 10184 | CAF | 3.0 MHz, QPSK, 1 RB                           | LTE-FDD | 5.73     | ±9.6                   |
| 10185 | CAF | 3.0 MHz, 16QAM, 1 RB                          | LTE-FDD | 6.51     | ±9.6                   |
| 10186 | AAF | 3.0 MHz, 64QAM, 1 RB                          | LTE-FDD | 6.50     | ±9.6                   |
| 10187 | CAG | 1.4 MHz, QPSK, 1 RB                           | LTE-FDD | 5.73     | ±9.6                   |
| 10188 | CAG | 1.4 MHz, 16QAM, 1 RB                          | LTE-FDD | 6.52     | ±9.6                   |
| 10189 | AAG | 1.4 MHz, 64QAM, 1 RB                          | LTE-FDD | 6.50     | ±9.6                   |
| 10193 | CAE | HT20 Greenfield, MCS0 (6.5 Mbps), 99.4% DC    | WLAN    | 8.09     | ±9.6                   |
| 10194 | CAE | HT20 Greenfield, MCS4 (39.0 Mbps), 99.5% DC   | WLAN    | 8.12     | ±9.6                   |
| 10195 | CAE | HT20 Greenfield, MCS7 (65.0 Mbps), 99.5% DC   | WLAN    | 8.21     | ±9.6                   |
| 10196 | CAE | HT20 Mixed, MCS0 (6.5 Mbps), 99.4% DC         | WLAN    | 8.10     | ±9.6                   |
| 10197 | CAE | HT20 Mixed, MCS4 (39.0 Mbps), 99.5% DC        | WLAN    | 8.13     | ±9.6                   |
| 10198 | CAE | HT20 Mixed, MCS7 (65.0 Mbps), 99.5% DC        | WLAN    | 8.27     | ±9.6                   |
| 10219 | CAE | HT20 Mixed, MCS0 (7.2 Mbps), 99.3% DC         | WLAN    | 8.03     | ±9.6                   |
| 10220 | CAE | HT20 Mixed, MCS4 (43.3 Mbps), 99.4% DC        | WLAN    | 8.13     | ±9.6                   |
| 10221 | CAE | HT20 Mixed, MCS7 (72.2 Mbps), 99.4% DC        | WLAN    | 8.27     | ±9.6                   |
| 10222 | CAE | HT40 Mixed, MCS0 (15.0 Mbps), 99.7% DC        | WLAN    | 8.06     | ±9.6                   |
| 10223 | CAE | HT40 Mixed, MCS4 (90.0 Mbps), 99.7% DC        | WLAN    | 8.46     | ±9.6                   |
| 10224 | CAE | HT40 Mixed, MCS7 (150.0 Mbps), 99.7% DC       | WLAN    | 8.08     | ±9.6                   |
| 10225 | CAC | Rel. 7 HSPA+, 16QAM, 5.0 MHz                  | WCDMA   | 5.97     | ±9.6                   |
| 10226 | CAC | 1.4 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 1 RB    | LTE-TDD | 9.49     | ±9.6                   |
| 10227 | CAC | 1.4 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 1 RB    | LTE-TDD | 10.26    | ±9.6                   |
| 10228 | CAC | 1.4 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB     | LTE-TDD | 9.22     | ±9.6                   |
| 10229 | CAE | 3.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 1 RB    | LTE-TDD | 9.48     | ±9.6                   |

| UID   | Rev | Communication System Name                        | Group    | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|--------------------------------------------------|----------|----------|------------------------|
| 10230 | CAE | 3.0 MHz, 84QAM, UL/DL CFG: 1, SSC: 4, 1 RB       | LTE-TDD  | 10.25    | ±9.6                   |
| 10231 | CAE | 3.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB        | LTE-TDD  | 9.19     | ±9.6                   |
| 10232 | CAH | 5.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 1 RB       | LTE-TDD  | 9.48     | ±9.6                   |
| 10233 | CAH | 5.0 MHz, 84QAM, UL/DL CFG: 1, SSC: 4, 1 RB       | LTE-TDD  | 10.25    | ±9.6                   |
| 10234 | CAH | 5.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB        | LTE-TDD  | 9.21     | ±9.6                   |
| 10235 | CAH | 10.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 1 RB      | LTE-TDD  | 9.48     | ±9.6                   |
| 10236 | CAH | 10.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 1 RB      | LTE-TDD  | 10.25    | ±9.6                   |
| 10237 | CAH | 10.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB       | LTE-TDD  | 9.21     | ±9.6                   |
| 10238 | CAG | 15.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 1 RB      | LTE-TDD  | 9.48     | ±9.6                   |
| 10239 | CAG | 15.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 1 RB      | LTE-TDD  | 10.25    | ±9.6                   |
| 10240 | CAG | 15.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB       | LTE-TDD  | 9.21     | ±9.6                   |
| 10241 | CAC | 1.4 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB     | LTE-TDD  | 9.82     | ±9.6                   |
| 10242 | CAC | 1.4 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 50% RB     | LTE-TDD  | 9.85     | ±9.6                   |
| 10243 | CAC | 1.4 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB      | LTE-TDD  | 9.46     | ±9.6                   |
| 10244 | CAE | 3.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB     | LTE-TDD  | 10.06    | ±9.6                   |
| 10245 | CAE | 3.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 50% RB     | LTE-TDD  | 10.06    | ±9.6                   |
| 10246 | CAE | 3.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB      | LTE-TDD  | 9.30     | ±9.6                   |
| 10247 | CAH | 5.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB     | LTE-TDD  | 9.91     | ±9.6                   |
| 10248 | CAH | 5.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 50% RB     | LTE-TDD  | 10.09    | ±9.6                   |
| 10249 | CAH | 5.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB      | LTE-TDD  | 9.29     | ±9.6                   |
| 10250 | CAH | 10.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB    | LTE-TDD  | 9.81     | ±9.6                   |
| 10251 | CAH | 10.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 50% RB    | LTE-TDD  | 10.17    | ±9.6                   |
| 10252 | CAH | 10.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB     | LTE-TDD  | 9.24     | ±9.6                   |
| 10253 | CAG | 15.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB    | LTE-TDD  | 9.90     | ±9.6                   |
| 10254 | CAG | 15.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 50% RB    | LTE-TDD  | 10.14    | ±9.6                   |
| 10255 | CAG | 15.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB     | LTE-TDD  | 9.20     | ±9.6                   |
| 10256 | CAC | 1.4 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB    | LTE-TDD  | 9.96     | ±9.6                   |
| 10257 | CAC | 1.4 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 100% RB    | LTE-TDD  | 10.08    | ±9.6                   |
| 10258 | CAC | 1.4 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB     | LTE-TDD  | 9.34     | ±9.6                   |
| 10259 | CAE | 3.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB    | LTE-TDD  | 9.98     | ±9.6                   |
| 10260 | CAE | 3.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 100% RB    | LTE-TDD  | 9.97     | ±9.6                   |
| 10261 | CAE | 3.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB     | LTE-TDD  | 9.24     | ±9.6                   |
| 10262 | CAH | 5.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB    | LTE-TDD  | 9.83     | ±9.6                   |
| 10263 | CAH | 5.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 100% RB    | LTE-TDD  | 10.16    | ±9.6                   |
| 10264 | CAH | 5.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB     | LTE-TDD  | 9.23     | ±9.6                   |
| 10265 | CAH | 10.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB   | LTE-TDD  | 9.92     | ±9.6                   |
| 10266 | CAH | 10.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 100% RB   | LTE-TDD  | 10.07    | ±9.6                   |
| 10267 | CAH | 10.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB    | LTE-TDD  | 9.30     | ±9.6                   |
| 10268 | CAG | 15.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB   | LTE-TDD  | 10.06    | ±9.6                   |
| 10269 | CAG | 15.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 100% RB   | LTE-TDD  | 10.13    | ±9.6                   |
| 10270 | CAG | 15.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB    | LTE-TDD  | 9.58     | ±9.6                   |
| 10274 | CAC | Rel. 6 HSUPA Subset 2, beta_d 0, QPSK, 5.0 MHz   | WCDMA    | 4.87     | ±9.6                   |
| 10275 | CAC | Rel. 6 HSUPA Subset 2, beta_d 15, QPSK, 5.0 MHz  | WCDMA    | 3.96     | ±9.6                   |
| 10290 | AAB | RC1, SO55, Full frame rate, 1xRTT                | CDMA2000 | 3.91     | ±9.6                   |
| 10291 | AAB | RC3, SO55, Full frame rate, 1xRTT                | CDMA2000 | 3.45     | ±9.6                   |
| 10292 | AAB | RC3, SO32, Full frame rate, SCH0 disabled, 1xRTT | CDMA2000 | 3.39     | ±9.6                   |
| 10293 | AAB | RC3, SO3, Full frame rate, 1xRTT                 | CDMA2000 | 3.50     | ±9.6                   |
| 10295 | AAB | RC3, SO3, 1/8 frame rate, 1xRTT                  | CDMA2000 | 12.49    | ±9.6                   |
| 10297 | AAE | 20.0 MHz, QPSK, 50% RB                           | LTE-FDD  | 5.81     | ±9.6                   |
| 10298 | AAE | 3.0 MHz, QPSK, 50% RB                            | LTE-FDD  | 5.72     | ±9.6                   |
| 10299 | AAE | 3.0 MHz, 16QAM, 50% RB                           | LTE-FDD  | 6.39     | ±9.6                   |
| 10300 | AAE | 3.0 MHz, 64QAM, 50% RB                           | LTE-FDD  | 6.60     | ±9.6                   |
| 10301 | AAA | PUSC, 29:18, QPSK, 5.0 ms, 18 TRAF SYM           | WiMAX    | 12.03    | ±9.6                   |
| 10302 | AAA | PUSC, 29:18, QPSK, 5.0 ms, 15 TRAF SYM           | WiMAX    | 12.57    | ±9.6                   |
| 10303 | AAA | PUSC, 31:15, 64QAM, 5.0 ms, 15 TRAF SYM          | WiMAX    | 12.52    | ±9.6                   |
| 10304 | AAA | PUSC, 29:18, 64QAM, 5.0 ms, 18 TRAF SYM          | WiMAX    | 11.85    | ±9.6                   |
| 10305 | AAA | PUSC, 31:15, 64QAM, 10.0 ms, 15 TRAF SYM         | WiMAX    | 15.24    | ±9.6                   |
| 10306 | AAA | PUSC, 29:18, 64QAM, 10.0 ms, 18 TRAF SYM         | WiMAX    | 14.67    | ±9.6                   |
| 10307 | AAA | PUSC, 29:18, QPSK, 10.0 ms, 18 TRAF SYM          | WiMAX    | 14.43    | ±9.6                   |
| 10308 | AAA | PUSC, 29:18, 16QAM, 10.0 ms, 18 TRAF SYM         | WiMAX    | 14.46    | ±9.6                   |
| 10309 | AAA | AMC 2x3, 29:18, 16QAM, 10.0 ms, 18 TRAF SYM      | WiMAX    | 14.58    | ±9.6                   |
| 10310 | AAA | AMC 2x3, 29:18, QPSK, 10.0 ms, 18 TRAF SYM       | WiMAX    | 14.57    | ±9.6                   |
| 10311 | AAE | 15.0 MHz, QPSK, 100% RB                          | LTE-FDD  | 6.06     | ±9.6                   |
| 10315 | AAB | DSSS, DBPSK, 1.0 Mbps, 96.0% DC                  | WLAN     | 1.71     | ±9.6                   |
| 10316 | AAB | OFDM, BPSK, 6.0 Mbps, 95.9% DC                   | WLAN     | 8.36     | ±9.6                   |
| 10317 | AAE | OFDM, BPSK, 6.0 Mbps, 95.9% DC                   | WLAN     | 8.36     | ±9.6                   |

| UID   | Rev | Communication System Name                                   | Group    | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|-------------------------------------------------------------|----------|----------|------------------------|
| 10352 | AAA | Pulse (D=10%, T=5 ms)                                       | Generic  | 10.00    | ±9.6                   |
| 10353 | AAA | Pulse (D=20%, T=5 ms)                                       | Generic  | 6.99     | ±9.6                   |
| 10354 | AAA | Pulse (D=40%, T=5 ms)                                       | Generic  | 3.98     | ±9.6                   |
| 10355 | AAA | Pulse (D=60%, T=5 ms)                                       | Generic  | 2.22     | ±9.6                   |
| 10356 | AAA | Pulse (D=80%, T=5 ms)                                       | Generic  | 0.97     | ±9.6                   |
| 10387 | AAA | Random (BW=1 MHz, MOD=QPSK)                                 | Generic  | 5.10     | ±9.6                   |
| 10388 | AAA | Random (BW=10 MHz, MOD=QPSK)                                | Generic  | 5.22     | ±9.6                   |
| 10396 | AAA | Random (BW=100 kHz, MOD=64QAM)                              | Generic  | 6.27     | ±9.6                   |
| 10399 | AAA | Random (BW=40 MHz, MOD=64QAM)                               | Generic  | 6.27     | ±9.6                   |
| 10400 | AAF | VHT20, MCS5 (52.0 Mbps), 99.0% DC                           | WLAN     | 8.37     | ±9.6                   |
| 10401 | AAF | VHT40, MCS5 (108.0 Mbps), 96.7% DC                          | WLAN     | 8.60     | ±9.6                   |
| 10402 | AAF | VHT80, MCS5 (234.0 Mbps), 99.0% DC                          | WLAN     | 8.53     | ±9.6                   |
| 10403 | AAB | Rev. 0, 1xEV-DO                                             | CDMA2000 | 3.76     | ±9.6                   |
| 10404 | AAB | Rev. A, 1xEV-DO                                             | CDMA2000 | 3.77     | ±9.6                   |
| 10406 | AAB | RC3, SO32, Full frame rate, SCH0 enabled, 1xRTT             | CDMA2000 | 5.22     | ±9.6                   |
| 10410 | AAH | 10.0 MHz, QPSK, UL/DL CFG: 0, SSC: 4, 1 RB                  | LTE-TDD  | 7.82     | ±9.6                   |
| 10414 | AAA | Random (BW=40 MHz, HIGH PAR)                                | Generic  | 8.54     | ±9.6                   |
| 10415 | AAA | DSSS, DBPSK, 1.0 Mbps, 99.9% DC                             | WLAN     | 1.54     | ±9.6                   |
| 10416 | AAA | OFDM, BPSK, 6.0 Mbps, 99.9% DC                              | WLAN     | 8.23     | ±9.6                   |
| 10417 | AAD | OFDM, BPSK, 6.0 Mbps, 99.9% DC                              | WLAN     | 8.23     | ±9.6                   |
| 10418 | AAA | OFDM (LTF), BPSK, 6.0 Mbps, 99.8% DC                        | WLAN     | 8.14     | ±9.6                   |
| 10419 | AAA | OFDM (STF), BPSK, 6.0 Mbps, 99.8% DC                        | WLAN     | 8.19     | ±9.6                   |
| 10422 | AAD | HT20 Greenfield, MCS0 (7.2 Mbps), 99.3% DC                  | WLAN     | 8.32     | ±9.6                   |
| 10423 | AAD | HT20 Greenfield, MCS4 (43.3 Mbps), 99.3% DC                 | WLAN     | 8.47     | ±9.6                   |
| 10424 | AAD | HT20 Greenfield, MCS7 (72.2 Mbps), 99.3% DC                 | WLAN     | 8.40     | ±9.6                   |
| 10425 | AAD | HT40 Greenfield, MCS0 (15.0 Mbps), 99.2% DC                 | WLAN     | 8.41     | ±9.6                   |
| 10426 | AAD | HT40 Greenfield, MCS4 (90.0 Mbps), 99.2% DC                 | WLAN     | 8.45     | ±9.6                   |
| 10427 | AAD | HT40 Greenfield, MCS7 (150.0 Mbps), 99.2% DC                | WLAN     | 8.41     | ±9.6                   |
| 10430 | AAE | 5.0 MHz, 64-QAM, 100% RB                                    | LTE-FDD  | 8.28     | ±9.6                   |
| 10431 | AAE | 10.0 MHz, 64-QAM, 100% RB                                   | LTE-FDD  | 8.38     | ±9.6                   |
| 10432 | AAD | 15.0 MHz, 64-QAM, 100% RB                                   | LTE-FDD  | 8.34     | ±9.6                   |
| 10433 | AAD | 20.0 MHz, 64-QAM, 100% RB                                   | LTE-FDD  | 8.34     | ±9.6                   |
| 10434 | AAB | BS Test Model 1, 64 DPCH, 64QAM, 5.0 MHz (DL)               | WCDMA    | 8.60     | ±9.6                   |
| 10435 | AAG | 20.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 7.82     | ±9.6                   |
| 10447 | AAE | 5.0 MHz, 64-QAM, 100% RB                                    | LTE-FDD  | 7.56     | ±9.6                   |
| 10448 | AAE | 10.0 MHz, 64-QAM, 100% RB                                   | LTE-FDD  | 7.53     | ±9.6                   |
| 10449 | AAD | 15.0 MHz, 64-QAM, 100% RB                                   | LTE-FDD  | 7.51     | ±9.6                   |
| 10450 | AAD | 20.0 MHz, 64-QAM, 100% RB                                   | LTE-FDD  | 7.48     | ±9.6                   |
| 10451 | AAB | BS Test Model 1, 64 DPCH, Clipping 44%, 64QAM, 5.0 MHz (DL) | WCDMA    | 7.59     | ±9.6                   |
| 10456 | AAD | VHT160, MCS5 (58.5 Mbps), 99.0% DC                          | WLAN     | 8.63     | ±9.6                   |
| 10457 | AAB | Rel. 5 DC-HSDPA, QPSK, 10.0 MHz                             | WCDMA    | 6.62     | ±9.6                   |
| 10458 | AAA | Rev. B, 2 carriers, 1xEV-DO                                 | CDMA2000 | 6.55     | ±9.6                   |
| 10459 | AAA | Rev. B, 3 carriers, 1xEV-DO                                 | CDMA2000 | 8.25     | ±9.6                   |
| 10460 | AAB | Rel. 99, AMR, QPSK, 5.0 MHz                                 | WCDMA    | 2.39     | ±9.6                   |
| 10461 | AAC | 1.4 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB                   | LTE-TDD  | 7.82     | ±9.6                   |
| 10462 | AAC | 1.4 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 8.30     | ±9.6                   |
| 10463 | AAC | 1.4 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 8.56     | ±9.6                   |
| 10464 | AAD | 3.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB                   | LTE-TDD  | 7.82     | ±9.6                   |
| 10465 | AAD | 3.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 8.32     | ±9.6                   |
| 10466 | AAD | 3.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 8.57     | ±9.6                   |
| 10467 | AAG | 5.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB                   | LTE-TDD  | 7.82     | ±9.6                   |
| 10468 | AAG | 5.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 8.32     | ±9.6                   |
| 10469 | AAG | 5.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 8.56     | ±9.6                   |
| 10470 | AAG | 10.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 7.82     | ±9.6                   |
| 10471 | AAG | 10.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB                 | LTE-TDD  | 8.32     | ±9.6                   |
| 10472 | AAG | 10.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB                 | LTE-TDD  | 8.57     | ±9.6                   |
| 10473 | AAF | 15.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 7.82     | ±9.6                   |
| 10474 | AAF | 15.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB                 | LTE-TDD  | 8.32     | ±9.6                   |
| 10475 | AAF | 15.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB                 | LTE-TDD  | 8.57     | ±9.6                   |
| 10477 | AAG | 20.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB                 | LTE-TDD  | 8.32     | ±9.6                   |
| 10478 | AAG | 20.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB                 | LTE-TDD  | 8.57     | ±9.6                   |
| 10479 | AAC | 1.4 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB                 | LTE-TDD  | 7.74     | ±9.6                   |
| 10480 | AAC | 1.4 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB                | LTE-TDD  | 8.18     | ±9.6                   |
| 10481 | AAC | 1.4 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 50% RB                | LTE-TDD  | 8.45     | ±9.6                   |
| 10482 | AAD | 3.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB                 | LTE-TDD  | 7.71     | ±9.6                   |
| 10483 | AAD | 3.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB                | LTE-TDD  | 8.39     | ±9.6                   |

| UID   | Rev | Communication System Name                      | Group   | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|------------------------------------------------|---------|----------|------------------------|
| 10484 | AAD | 3.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 50% RB   | LTE-TDD | 8.47     | ±9.6                   |
| 10485 | AAG | 5.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB    | LTE-TDD | 7.59     | ±9.6                   |
| 10486 | AAG | 5.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB   | LTE-TDD | 8.38     | ±9.6                   |
| 10487 | AAG | 5.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 50% RB   | LTE-TDD | 8.60     | ±9.6                   |
| 10488 | AAG | 10.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB   | LTE-TDD | 7.70     | ±9.6                   |
| 10489 | AAG | 10.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB  | LTE-TDD | 8.31     | ±9.6                   |
| 10490 | AAG | 10.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 50% RB  | LTE-TDD | 8.54     | ±9.6                   |
| 10491 | AAF | 15.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB   | LTE-TDD | 7.74     | ±9.6                   |
| 10492 | AAF | 15.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB  | LTE-TDD | 8.41     | ±9.6                   |
| 10493 | AAF | 15.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 50% RB  | LTE-TDD | 8.55     | ±9.6                   |
| 10494 | AAG | 20.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB   | LTE-TDD | 7.74     | ±9.6                   |
| 10495 | AAG | 20.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB  | LTE-TDD | 8.37     | ±9.6                   |
| 10496 | AAG | 20.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 50% RB  | LTE-TDD | 8.54     | ±9.6                   |
| 10497 | AAC | 1.4 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB   | LTE-TDD | 7.67     | ±9.6                   |
| 10498 | AAC | 1.4 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 8.40     | ±9.6                   |
| 10499 | AAC | 1.4 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 8.88     | ±9.6                   |
| 10500 | AAD | 3.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB   | LTE-TDD | 7.67     | ±9.6                   |
| 10501 | AAD | 3.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 8.44     | ±9.6                   |
| 10502 | AAD | 3.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 8.52     | ±9.6                   |
| 10503 | AAG | 5.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB   | LTE-TDD | 7.72     | ±9.6                   |
| 10504 | AAG | 5.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 8.31     | ±9.6                   |
| 10505 | AAG | 5.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 8.54     | ±9.6                   |
| 10506 | AAG | 10.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 7.74     | ±9.6                   |
| 10507 | AAG | 10.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB | LTE-TDD | 8.36     | ±9.6                   |
| 10508 | AAG | 10.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB | LTE-TDD | 8.55     | ±9.6                   |
| 10509 | AAF | 15.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 7.99     | ±9.6                   |
| 10510 | AAF | 15.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB | LTE-TDD | 8.49     | ±9.6                   |
| 10511 | AAF | 15.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB | LTE-TDD | 8.51     | ±9.6                   |
| 10512 | AAG | 20.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 7.74     | ±9.6                   |
| 10513 | AAG | 20.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB | LTE-TDD | 8.42     | ±9.6                   |
| 10514 | AAG | 20.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB | LTE-TDD | 8.45     | ±9.6                   |
| 10515 | AAA | DSSS, DQPSK, 2.0 Mbps, 99.0% DC                | WLAN    | 1.58     | ±9.6                   |
| 10516 | AAA | HR-DSSS, DQPSK, 5.5 Mbps, 99.2% DC             | WLAN    | 1.57     | ±9.6                   |
| 10517 | AAA | HR-DSSS, DQPSK, 11.0 Mbps, 99.0% DC            | WLAN    | 1.58     | ±9.6                   |
| 10518 | AAD | OFDM, BPSK, 9.0 Mbps, 98.8% DC                 | WLAN    | 8.23     | ±9.6                   |
| 10519 | AAD | OFDM, QPSK, 12.0 Mbps, 99.0% DC                | WLAN    | 8.39     | ±9.6                   |
| 10520 | AAD | OFDM, QPSK, 18.0 Mbps, 99.0% DC                | WLAN    | 8.12     | ±9.6                   |
| 10521 | AAD | OFDM, 16QAM, 24.0 Mbps, 99.0% DC               | WLAN    | 7.97     | ±9.6                   |
| 10522 | AAD | OFDM, 16QAM, 36.0 Mbps, 99.0% DC               | WLAN    | 8.45     | ±9.6                   |
| 10523 | AAD | OFDM, 64QAM, 48.0 Mbps, 99.0% DC               | WLAN    | 8.08     | ±9.6                   |
| 10524 | AAD | OFDM, 64QAM, 54.0 Mbps, 99.0% DC               | WLAN    | 8.27     | ±9.6                   |
| 10525 | AAD | VHT20, MCS0 (6.5 Mbps), 98.9% DC               | WLAN    | 8.36     | ±9.6                   |
| 10526 | AAD | VHT20, MCS1 (13.0 Mbps), 99.0% DC              | WLAN    | 8.42     | ±9.6                   |
| 10527 | AAD | VHT20, MCS2 (19.5 Mbps), 99.0% DC              | WLAN    | 8.21     | ±9.6                   |
| 10528 | AAD | VHT20, MCS3 (26.0 Mbps), 99.0% DC              | WLAN    | 8.36     | ±9.6                   |
| 10529 | AAD | VHT20, MCS4 (39.0 Mbps), 99.0% DC              | WLAN    | 8.36     | ±9.6                   |
| 10531 | AAD | VHT20, MCS6 (58.5 Mbps), 99.0% DC              | WLAN    | 8.43     | ±9.6                   |
| 10532 | AAD | VHT20, MCS7 (65.0 Mbps), 99.0% DC              | WLAN    | 8.29     | ±9.6                   |
| 10533 | AAD | VHT20, MCS8 (78.0 Mbps), 99.0% DC              | WLAN    | 8.38     | ±9.6                   |
| 10534 | AAD | VHT40, MCS0 (13.5 Mbps), 98.9% DC              | WLAN    | 8.45     | ±9.6                   |
| 10535 | AAD | VHT40, MCS1 (27.0 Mbps), 98.8% DC              | WLAN    | 8.45     | ±9.6                   |
| 10536 | AAD | VHT40, MCS2 (40.5 Mbps), 98.8% DC              | WLAN    | 8.32     | ±9.6                   |
| 10537 | AAD | VHT40, MCS3 (54.0 Mbps), 98.7% DC              | WLAN    | 8.44     | ±9.6                   |
| 10538 | AAD | VHT40, MCS4 (81.0 Mbps), 98.5% DC              | WLAN    | 8.54     | ±9.6                   |
| 10540 | AAD | VHT40, MCS6 (121.5 Mbps), 98.3% DC             | WLAN    | 8.39     | ±9.6                   |
| 10541 | AAD | VHT40, MCS7 (135.0 Mbps), 98.3% DC             | WLAN    | 8.46     | ±9.6                   |
| 10542 | AAD | VHT40, MCS8 (162.0 Mbps), 98.1% DC             | WLAN    | 8.65     | ±9.6                   |
| 10543 | AAD | VHT40, MCS9 (180.0 Mbps), 98.0% DC             | WLAN    | 8.65     | ±9.6                   |
| 10544 | AAD | VHT80, MCS0 (29.3 Mbps), 99.0% DC              | WLAN    | 8.47     | ±9.6                   |
| 10545 | AAD | VHT80, MCS1 (58.5 Mbps), 99.0% DC              | WLAN    | 8.55     | ±9.6                   |
| 10546 | AAD | VHT80, MCS2 (87.8 Mbps), 99.0% DC              | WLAN    | 8.35     | ±9.6                   |
| 10547 | AAD | VHT80, MCS3 (117.0 Mbps), 99.0% DC             | WLAN    | 8.49     | ±9.6                   |
| 10548 | AAD | VHT80, MCS4 (175.5 Mbps), 99.0% DC             | WLAN    | 8.37     | ±9.6                   |
| 10550 | AAD | VHT80, MCS6 (263.3 Mbps), 99.0% DC             | WLAN    | 8.38     | ±9.6                   |
| 10551 | AAD | VHT80, MCS7 (292.5 Mbps), 99.0% DC             | WLAN    | 8.50     | ±9.6                   |
| 10552 | AAD | VHT80, MCS8 (351.0 Mbps), 99.0% DC             | WLAN    | 8.42     | ±9.6                   |

| UID   | Rev | Communication System Name               | Group | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|-----------------------------------------|-------|----------|------------------------|
| 10553 | AAD | VHT80, MCS9 (390.0 Mbps), 99.0% DC      | WLAN  | 8.45     | ±9.6                   |
| 10554 | AAE | VHT160, MCS0 (58.5 Mbps), 99.0% DC      | WLAN  | 8.48     | ±9.6                   |
| 10555 | AAE | VHT160, MCS1 (117.0 Mbps), 99.0% DC     | WLAN  | 8.47     | ±9.6                   |
| 10556 | AAE | VHT160, MCS2 (175.5 Mbps), 99.0% DC     | WLAN  | 8.50     | ±9.6                   |
| 10557 | AAE | VHT160, MCS3 (234.0 Mbps), 99.0% DC     | WLAN  | 8.52     | ±9.6                   |
| 10558 | AAE | VHT160, MCS4 (351.0 Mbps), 99.0% DC     | WLAN  | 8.61     | ±9.6                   |
| 10560 | AAE | VHT160, MCS6 (526.5 Mbps), 99.0% DC     | WLAN  | 8.73     | ±9.6                   |
| 10561 | AAE | VHT160, MCS7 (585.0 Mbps), 99.0% DC     | WLAN  | 8.56     | ±9.6                   |
| 10562 | AAE | VHT160, MCS8 (702.0 Mbps), 99.0% DC     | WLAN  | 8.69     | ±9.6                   |
| 10563 | AAE | VHT160, MCS9 (780.0 Mbps), 99.0% DC     | WLAN  | 8.77     | ±9.6                   |
| 10564 | AAA | OFDM, BPSK, 9.0 Mbps, 99.9% DC          | WLAN  | 8.25     | ±9.6                   |
| 10565 | AAA | OFDM, QPSK, 12.0 Mbps, 99.0% DC         | WLAN  | 8.45     | ±9.6                   |
| 10566 | AAA | OFDM, QPSK, 18.0 Mbps, 99.0% DC         | WLAN  | 8.13     | ±9.6                   |
| 10567 | AAA | OFDM, 16QAM, 24.0 Mbps, 99.0% DC        | WLAN  | 8.00     | ±9.6                   |
| 10568 | AAA | OFDM, 16QAM, 36.0 Mbps, 99.0% DC        | WLAN  | 8.37     | ±9.6                   |
| 10569 | AAA | OFDM, 64QAM, 48.0 Mbps, 99.0% DC        | WLAN  | 8.10     | ±9.6                   |
| 10570 | AAA | OFDM, 64QAM, 54.0 Mbps, 99.0% DC        | WLAN  | 8.30     | ±9.6                   |
| 10571 | AAA | DSSS, DQPSK, 1.0 Mbps, 90.0% DC         | WLAN  | 1.99     | ±9.6                   |
| 10572 | AAA | DSSS, DQPSK, 2.0 Mbps, 90.0% DC         | WLAN  | 1.99     | ±9.6                   |
| 10573 | AAA | HR-DSSS, DQPSK, 5.5 Mbps, 90.1% DC      | WLAN  | 1.98     | ±9.6                   |
| 10574 | AAA | HR-DSSS, DQPSK, 11.0 Mbps, 90.3% DC     | WLAN  | 1.98     | ±9.6                   |
| 10575 | AAA | OFDM, BPSK, 6.0 Mbps, 89.9% DC          | WLAN  | 8.59     | ±9.6                   |
| 10576 | AAA | OFDM, BPSK, 9.0 Mbps, 89.9% DC          | WLAN  | 8.60     | ±9.6                   |
| 10577 | AAA | OFDM, QPSK, 12.0 Mbps, 90.0% DC         | WLAN  | 8.70     | ±9.6                   |
| 10578 | AAA | OFDM, QPSK, 18.0 Mbps, 90.0% DC         | WLAN  | 8.49     | ±9.6                   |
| 10579 | AAA | OFDM, 16QAM, 24.0 Mbps, 90.0% DC        | WLAN  | 8.36     | ±9.6                   |
| 10580 | AAA | OFDM, 16QAM, 36.0 Mbps, 90.0% DC        | WLAN  | 8.76     | ±9.6                   |
| 10581 | AAA | OFDM, 64QAM, 48.0 Mbps, 90.0% DC        | WLAN  | 8.35     | ±9.6                   |
| 10582 | AAA | OFDM, 64QAM, 54.0 Mbps, 90.0% DC        | WLAN  | 8.67     | ±9.6                   |
| 10583 | AAD | OFDM, BPSK, 6.0 Mbps, 89.9% DC          | WLAN  | 8.59     | ±9.6                   |
| 10584 | AAD | OFDM, BPSK, 9.0 Mbps, 89.9% DC          | WLAN  | 8.60     | ±9.6                   |
| 10585 | AAD | OFDM, QPSK, 12.0 Mbps, 90.0% DC         | WLAN  | 8.70     | ±9.6                   |
| 10586 | AAD | OFDM, QPSK, 18.0 Mbps, 90.0% DC         | WLAN  | 8.49     | ±9.6                   |
| 10587 | AAD | OFDM, 16QAM, 24.0 Mbps, 90.0% DC        | WLAN  | 8.36     | ±9.6                   |
| 10588 | AAD | OFDM, 16QAM, 36.0 Mbps, 90.0% DC        | WLAN  | 8.76     | ±9.6                   |
| 10589 | AAD | OFDM, 64QAM, 48.0 Mbps, 90.0% DC        | WLAN  | 8.35     | ±9.6                   |
| 10590 | AAD | OFDM, 64QAM, 54.0 Mbps, 90.0% DC        | WLAN  | 8.67     | ±9.6                   |
| 10591 | AAD | HT20 Mixed, MCS0 (6.5 Mbps), 89.9% DC   | WLAN  | 8.63     | ±9.6                   |
| 10592 | AAD | HT20 Mixed, MCS1 (13.0 Mbps), 90.0% DC  | WLAN  | 8.79     | ±9.6                   |
| 10593 | AAD | HT20 Mixed, MCS2 (19.5 Mbps), 90.0% DC  | WLAN  | 8.64     | ±9.6                   |
| 10594 | AAD | HT20 Mixed, MCS3 (26.0 Mbps), 90.0% DC  | WLAN  | 8.74     | ±9.6                   |
| 10595 | AAD | HT20 Mixed, MCS4 (39.0 Mbps), 90.0% DC  | WLAN  | 8.74     | ±9.6                   |
| 10596 | AAD | HT20 Mixed, MCS5 (52.0 Mbps), 90.0% DC  | WLAN  | 8.71     | ±9.6                   |
| 10597 | AAD | HT20 Mixed, MCS6 (58.5 Mbps), 90.0% DC  | WLAN  | 8.72     | ±9.6                   |
| 10598 | AAD | HT20 Mixed, MCS7 (65.0 Mbps), 90.0% DC  | WLAN  | 8.50     | ±9.6                   |
| 10599 | AAD | HT40 Mixed, MCS0 (13.5 Mbps), 89.9% DC  | WLAN  | 8.79     | ±9.6                   |
| 10600 | AAD | HT40 Mixed, MCS1 (27.0 Mbps), 89.7% DC  | WLAN  | 8.88     | ±9.6                   |
| 10601 | AAD | HT40 Mixed, MCS2 (40.5 Mbps), 89.6% DC  | WLAN  | 8.82     | ±9.6                   |
| 10602 | AAD | HT40 Mixed, MCS3 (54.0 Mbps), 89.4% DC  | WLAN  | 8.94     | ±9.6                   |
| 10603 | AAD | HT40 Mixed, MCS4 (81.0 Mbps), 89.2% DC  | WLAN  | 9.03     | ±9.6                   |
| 10604 | AAD | HT40 Mixed, MCS5 (108.0 Mbps), 88.9% DC | WLAN  | 8.76     | ±9.6                   |
| 10605 | AAD | HT40 Mixed, MCS6 (121.5 Mbps), 88.8% DC | WLAN  | 8.97     | ±9.6                   |
| 10606 | AAD | HT40 Mixed, MCS7 (135.0 Mbps), 88.7% DC | WLAN  | 8.82     | ±9.6                   |
| 10607 | AAD | VHT20, MCS0 (6.5 Mbps), 89.9% DC        | WLAN  | 8.64     | ±9.6                   |
| 10608 | AAD | VHT20, MCS1 (13.0 Mbps), 90.0% DC       | WLAN  | 8.77     | ±9.6                   |
| 10609 | AAD | VHT20, MCS2 (19.5 Mbps), 90.0% DC       | WLAN  | 8.57     | ±9.6                   |
| 10610 | AAD | VHT20, MCS3 (26.0 Mbps), 90.0% DC       | WLAN  | 8.78     | ±9.6                   |
| 10611 | AAD | VHT20, MCS4 (39.0 Mbps), 90.0% DC       | WLAN  | 8.70     | ±9.6                   |
| 10612 | AAD | VHT20, MCS5 (52.0 Mbps), 90.0% DC       | WLAN  | 8.77     | ±9.6                   |
| 10613 | AAD | VHT20, MCS6 (58.5 Mbps), 90.0% DC       | WLAN  | 8.94     | ±9.6                   |
| 10614 | AAD | VHT20, MCS7 (65.0 Mbps), 90.0% DC       | WLAN  | 8.59     | ±9.6                   |
| 10615 | AAD | VHT20, MCS8 (78.0 Mbps), 90.0% DC       | WLAN  | 8.82     | ±9.6                   |
| 10616 | AAD | VHT40, MCS0 (13.5 Mbps), 89.9% DC       | WLAN  | 8.82     | ±9.6                   |
| 10617 | AAD | VHT40, MCS1 (27.0 Mbps), 89.7% DC       | WLAN  | 8.81     | ±9.6                   |
| 10618 | AAD | VHT40, MCS2 (40.5 Mbps), 89.6% DC       | WLAN  | 8.58     | ±9.6                   |
| 10619 | AAD | VHT40, MCS3 (54.0 Mbps), 89.4% DC       | WLAN  | 8.86     | ±9.6                   |

| UID   | Rev | Communication System Name                  | Group     | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|--------------------------------------------|-----------|----------|------------------------|
| 10620 | AAD | VHT40, MCS4 (81.0 Mbps), 89.2% DC          | WLAN      | 8.87     | ±9.6                   |
| 10621 | AAD | VHT40, MCS5 (108.0 Mbps), 88.9% DC         | WLAN      | 8.77     | ±9.6                   |
| 10622 | AAD | VHT40, MCS6 (121.5 Mbps), 88.8% DC         | WLAN      | 8.88     | ±9.6                   |
| 10623 | AAD | VHT40, MCS7 (135.0 Mbps), 88.6% DC         | WLAN      | 8.82     | ±9.6                   |
| 10624 | AAD | VHT40, MCS8 (162.0 Mbps), 88.4% DC         | WLAN      | 8.96     | ±9.6                   |
| 10625 | AAD | VHT40, MCS9 (180.0 Mbps), 88.2% DC         | WLAN      | 8.96     | ±9.6                   |
| 10626 | AAD | VHT80, MCS0 (29.3 Mbps), 90.0% DC          | WLAN      | 8.83     | ±9.6                   |
| 10627 | AAD | VHT80, MCS1 (58.5 Mbps), 90.0% DC          | WLAN      | 8.88     | ±9.6                   |
| 10628 | AAD | VHT80, MCS2 (87.8 Mbps), 90.0% DC          | WLAN      | 8.71     | ±9.6                   |
| 10629 | AAD | VHT80, MCS3 (117.0 Mbps), 90.0% DC         | WLAN      | 8.85     | ±9.6                   |
| 10630 | AAD | VHT80, MCS4 (175.5 Mbps), 90.0% DC         | WLAN      | 8.72     | ±9.6                   |
| 10631 | AAD | VHT80, MCS5 (234.0 Mbps), 90.0% DC         | WLAN      | 8.81     | ±9.6                   |
| 10632 | AAD | VHT80, MCS6 (263.3 Mbps), 90.0% DC         | WLAN      | 8.74     | ±9.6                   |
| 10633 | AAD | VHT80, MCS7 (292.5 Mbps), 90.0% DC         | WLAN      | 8.83     | ±9.6                   |
| 10634 | AAD | VHT80, MCS8 (351.0 Mbps), 90.0% DC         | WLAN      | 8.80     | ±9.6                   |
| 10635 | AAD | VHT80, MCS9 (390.0 Mbps), 90.0% DC         | WLAN      | 8.81     | ±9.6                   |
| 10636 | AAE | VHT160, MCS0 (58.5 Mbps), 90.0% DC         | WLAN      | 8.83     | ±9.6                   |
| 10637 | AAE | VHT160, MCS1 (117.0 Mbps), 90.0% DC        | WLAN      | 8.79     | ±9.6                   |
| 10638 | AAE | VHT160, MCS2 (175.5 Mbps), 90.0% DC        | WLAN      | 8.85     | ±9.6                   |
| 10639 | AAE | VHT160, MCS3 (234.0 Mbps), 90.0% DC        | WLAN      | 8.85     | ±9.6                   |
| 10640 | AAE | VHT160, MCS4 (351.0 Mbps), 90.0% DC        | WLAN      | 8.98     | ±9.6                   |
| 10641 | AAE | VHT160, MCS5 (468.0 Mbps), 90.0% DC        | WLAN      | 9.06     | ±9.6                   |
| 10642 | AAE | VHT160, MCS6 (526.5 Mbps), 90.0% DC        | WLAN      | 9.06     | ±9.6                   |
| 10643 | AAE | VHT160, MCS7 (585.0 Mbps), 90.0% DC        | WLAN      | 8.88     | ±9.6                   |
| 10644 | AAE | VHT160, MCS8 (702.0 Mbps), 90.0% DC        | WLAN      | 9.05     | ±9.6                   |
| 10645 | AAE | VHT160, MCS9 (780.0 Mbps), 90.0% DC        | WLAN      | 9.11     | ±9.6                   |
| 10646 | AAH | 5.0 MHz, QPSK, UL/DL CFG: 2, SSC: 4, 1 RB  | LTE-TDD   | 11.96    | ±9.6                   |
| 10647 | AAG | 20.0 MHz, QPSK, UL/DL CFG: 2, SSC: 7, 1 RB | LTE-TDD   | 11.96    | ±9.6                   |
| 10648 | AAA | RC8, SO75, 1xAdvanced                      | CDMA2000  | 3.45     | ±9.6                   |
| 10670 | AAA | LE, Test, GF6K                             | Bluetooth | 2.19     | ±9.6                   |
| 10671 | AAC | ET20, MCS0 (8.6 Mbps), 90.0% DC            | WLAN      | 8.09     | ±9.6                   |
| 10672 | AAC | ET20, MCS1 (17.0 Mbps), 90.0% DC           | WLAN      | 8.57     | ±9.6                   |
| 10673 | AAC | ET20, MCS2 (26.0 Mbps), 90.0% DC           | WLAN      | 8.78     | ±9.6                   |
| 10674 | AAC | ET20, MCS3 (34.0 Mbps), 90.0% DC           | WLAN      | 8.74     | ±9.6                   |
| 10675 | AAC | ET20, MCS4 (52.0 Mbps), 90.0% DC           | WLAN      | 8.90     | ±9.6                   |
| 10676 | AAC | ET20, MCS5 (69.0 Mbps), 90.0% DC           | WLAN      | 8.77     | ±9.6                   |
| 10677 | AAC | ET20, MCS6 (77.0 Mbps), 90.0% DC           | WLAN      | 8.73     | ±9.6                   |
| 10678 | AAC | ET20, MCS7 (86.0 Mbps), 90.0% DC           | WLAN      | 8.78     | ±9.6                   |
| 10679 | AAC | ET20, MCS8 (103.0 Mbps), 90.0% DC          | WLAN      | 8.89     | ±9.6                   |
| 10680 | AAC | ET20, MCS9 (115.0 Mbps), 90.0% DC          | WLAN      | 8.80     | ±9.6                   |
| 10681 | AAC | ET20, MCS10 (122.0 Mbps), 90.0% DC         | WLAN      | 8.82     | ±9.6                   |
| 10682 | AAC | ET20, MCS11 (135.0 Mbps), 90.0% DC         | WLAN      | 8.83     | ±9.6                   |
| 10683 | AAC | ET20, MCS0 (8.6 Mbps), 100.0% DC           | WLAN      | 8.42     | ±9.6                   |
| 10684 | AAC | ET20, MCS1 (17.0 Mbps), 100.0% DC          | WLAN      | 8.26     | ±9.6                   |
| 10685 | AAC | ET20, MCS2 (26.0 Mbps), 100.0% DC          | WLAN      | 8.33     | ±9.6                   |
| 10686 | AAC | ET20, MCS3 (34.0 Mbps), 100.0% DC          | WLAN      | 8.28     | ±9.6                   |
| 10687 | AAC | ET20, MCS4 (52.0 Mbps), 100.0% DC          | WLAN      | 8.45     | ±9.6                   |
| 10688 | AAC | ET20, MCS5 (69.0 Mbps), 100.0% DC          | WLAN      | 8.29     | ±9.6                   |
| 10689 | AAC | ET20, MCS6 (77.0 Mbps), 100.0% DC          | WLAN      | 8.55     | ±9.6                   |
| 10690 | AAC | ET20, MCS7 (86.0 Mbps), 100.0% DC          | WLAN      | 8.29     | ±9.6                   |
| 10691 | AAC | ET20, MCS8 (103.0 Mbps), 100.0% DC         | WLAN      | 8.25     | ±9.6                   |
| 10692 | AAC | ET20, MCS9 (115.0 Mbps), 100.0% DC         | WLAN      | 8.29     | ±9.6                   |
| 10693 | AAC | ET20, MCS10 (122.0 Mbps), 100.0% DC        | WLAN      | 8.25     | ±9.6                   |
| 10694 | AAC | ET20, MCS11 (135.0 Mbps), 100.0% DC        | WLAN      | 8.57     | ±9.6                   |
| 10695 | AAC | ET40, MCS0 (17.2 Mbps), 89.8% DC           | WLAN      | 8.78     | ±9.6                   |
| 10696 | AAC | ET40, MCS1 (34.0 Mbps), 89.8% DC           | WLAN      | 8.91     | ±9.6                   |
| 10697 | AAC | ET40, MCS2 (52.0 Mbps), 89.7% DC           | WLAN      | 8.61     | ±9.6                   |
| 10698 | AAC | ET40, MCS3 (69.0 Mbps), 89.7% DC           | WLAN      | 8.89     | ±9.6                   |
| 10699 | AAC | ET40, MCS4 (103.0 Mbps), 89.9% DC          | WLAN      | 8.82     | ±9.6                   |
| 10700 | AAC | ET40, MCS5 (138.0 Mbps), 89.8% DC          | WLAN      | 8.73     | ±9.6                   |
| 10701 | AAC | ET40, MCS6 (155.0 Mbps), 89.8% DC          | WLAN      | 8.86     | ±9.6                   |
| 10702 | AAC | ET40, MCS7 (172.0 Mbps), 89.8% DC          | WLAN      | 8.70     | ±9.6                   |
| 10703 | AAC | ET40, MCS8 (207.0 Mbps), 89.8% DC          | WLAN      | 8.82     | ±9.6                   |
| 10704 | AAC | ET40, MCS9 (229.0 Mbps), 89.8% DC          | WLAN      | 8.56     | ±9.6                   |
| 10705 | AAC | ET40, MCS10 (258.0 Mbps), 89.8% DC         | WLAN      | 8.69     | ±9.6                   |
| 10706 | AAC | ET40, MCS11 (267.0 Mbps), 89.8% DC         | WLAN      | 8.66     | ±9.6                   |

| UID   | Rev | Communication System Name                        | Group         | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|--------------------------------------------------|---------------|----------|------------------------|
| 10707 | AAC | ET40, MCS0 (17.2 Mbps), 99.8% DC                 | WLAN          | 8.32     | ±9.6                   |
| 10708 | AAC | ET40, MCS1 (34.0 Mbps), 99.7% DC                 | WLAN          | 8.55     | ±9.6                   |
| 10709 | AAC | ET40, MCS2 (52.0 Mbps), 99.7% DC                 | WLAN          | 8.33     | ±9.6                   |
| 10710 | AAC | ET40, MCS3 (69.0 Mbps), 99.7% DC                 | WLAN          | 8.29     | ±9.6                   |
| 10711 | AAC | ET40, MCS4 (103.0 Mbps), 99.8% DC                | WLAN          | 8.39     | ±9.6                   |
| 10712 | AAC | ET40, MCS5 (138.0 Mbps), 99.8% DC                | WLAN          | 8.67     | ±9.6                   |
| 10713 | AAC | ET40, MCS6 (155.0 Mbps), 99.8% DC                | WLAN          | 8.33     | ±9.6                   |
| 10714 | AAC | ET40, MCS7 (172.0 Mbps), 99.8% DC                | WLAN          | 8.26     | ±9.6                   |
| 10715 | AAC | ET40, MCS8 (207.0 Mbps), 99.8% DC                | WLAN          | 8.45     | ±9.6                   |
| 10716 | AAC | ET40, MCS9 (229.0 Mbps), 99.8% DC                | WLAN          | 8.30     | ±9.6                   |
| 10717 | AAC | ET40, MCS10 (258.0 Mbps), 99.8% DC               | WLAN          | 8.48     | ±9.6                   |
| 10718 | AAC | ET40, MCS11 (267.0 Mbps), 99.8% DC               | WLAN          | 8.24     | ±9.6                   |
| 10719 | AAC | ET80, MCS0 (36.0 Mbps), 90.0% DC                 | WLAN          | 8.81     | ±9.6                   |
| 10720 | AAC | ET80, MCS1 (72.1 Mbps), 90.0% DC                 | WLAN          | 8.87     | ±9.6                   |
| 10721 | AAC | ET80, MCS2 (108.1 Mbps), 90.0% DC                | WLAN          | 8.76     | ±9.6                   |
| 10722 | AAC | ET80, MCS3 (144.1 Mbps), 90.0% DC                | WLAN          | 8.55     | ±9.6                   |
| 10723 | AAC | ET80, MCS4 (216.2 Mbps), 90.0% DC                | WLAN          | 8.70     | ±9.6                   |
| 10724 | AAC | ET80, MCS5 (288.2 Mbps), 90.0% DC                | WLAN          | 8.90     | ±9.6                   |
| 10725 | AAC | ET80, MCS6 (324.4 Mbps), 90.0% DC                | WLAN          | 8.74     | ±9.6                   |
| 10726 | AAC | ET80, MCS7 (360.3 Mbps), 90.0% DC                | WLAN          | 8.72     | ±9.6                   |
| 10727 | AAC | ET80, MCS8 (432.4 Mbps), 90.0% DC                | WLAN          | 8.66     | ±9.6                   |
| 10728 | AAC | ET80, MCS9 (480.4 Mbps), 90.0% DC                | WLAN          | 8.65     | ±9.6                   |
| 10729 | AAC | ET80, MCS10 (540.4 Mbps), 90.0% DC               | WLAN          | 8.64     | ±9.6                   |
| 10730 | AAC | ET80, MCS11 (72.0 Mbps), 90.0% DC                | WLAN          | 8.67     | ±9.6                   |
| 10731 | AAC | ET80, MCS0 (36.0 Mbps), 100.0% DC                | WLAN          | 8.42     | ±9.6                   |
| 10732 | AAC | ET80, MCS1 (72.1 Mbps), 100.0% DC                | WLAN          | 8.46     | ±9.6                   |
| 10733 | AAC | ET80, MCS2 (108.1 Mbps), 100.0% DC               | WLAN          | 8.40     | ±9.6                   |
| 10734 | AAC | ET80, MCS3 (144.1 Mbps), 100.0% DC               | WLAN          | 8.25     | ±9.6                   |
| 10735 | AAC | ET80, MCS4 (216.2 Mbps), 100.0% DC               | WLAN          | 8.33     | ±9.6                   |
| 10736 | AAC | ET80, MCS5 (288.2 Mbps), 100.0% DC               | WLAN          | 8.27     | ±9.6                   |
| 10737 | AAC | ET80, MCS6 (324.4 Mbps), 100.0% DC               | WLAN          | 8.36     | ±9.6                   |
| 10738 | AAC | ET80, MCS7 (360.3 Mbps), 100.0% DC               | WLAN          | 8.42     | ±9.6                   |
| 10739 | AAC | ET80, MCS8 (432.4 Mbps), 100.0% DC               | WLAN          | 8.29     | ±9.6                   |
| 10740 | AAC | ET80, MCS9 (480.4 Mbps), 100.0% DC               | WLAN          | 8.48     | ±9.6                   |
| 10741 | AAC | ET80, MCS10 (540.4 Mbps), 100.0% DC              | WLAN          | 8.40     | ±9.6                   |
| 10742 | AAC | ET80, MCS11 (600.5 Mbps), 100.0% DC              | WLAN          | 8.43     | ±9.6                   |
| 10743 | AAC | ET160, MCS0 (72.0 Mbps), 88.2% DC                | WLAN          | 8.94     | ±9.6                   |
| 10744 | AAC | ET160, MCS1 (144.0 Mbps), 87.1% DC               | WLAN          | 9.16     | ±9.6                   |
| 10745 | AAC | ET160, MCS2 (216.0 Mbps), 87.4% DC               | WLAN          | 8.93     | ±9.6                   |
| 10746 | AAC | ET160, MCS3 (282.0 Mbps), 87.1% DC               | WLAN          | 9.11     | ±9.6                   |
| 10747 | AAC | ET160, MCS4 (432.0 Mbps), 87.4% DC               | WLAN          | 9.04     | ±9.6                   |
| 10748 | AAC | ET160, MCS5 (576.0 Mbps), 85.8% DC               | WLAN          | 8.93     | ±9.6                   |
| 10749 | AAC | ET160, MCS6 (649.0 Mbps), 86.7% DC               | WLAN          | 8.90     | ±9.6                   |
| 10750 | AAC | ET160, MCS7 (721.0 Mbps), 86.7% DC               | WLAN          | 8.79     | ±9.6                   |
| 10751 | AAC | ET160, MCS8 (865.0 Mbps), 85.3% DC               | WLAN          | 8.82     | ±9.6                   |
| 10752 | AAC | ET160, MCS9 (961.0 Mbps), 85.3% DC               | WLAN          | 8.81     | ±9.6                   |
| 10753 | AAC | ET160, MCS10 (1081.0 Mbps), 86.7% DC             | WLAN          | 9.00     | ±9.6                   |
| 10754 | AAC | ET160, MCS11 (1201.0 Mbps), 86.7% DC             | WLAN          | 8.94     | ±9.6                   |
| 10755 | AAC | ET160, MCS0 (72.0 Mbps), 98.0% DC                | WLAN          | 8.64     | ±9.6                   |
| 10756 | AAC | ET160, MCS1 (144.0 Mbps), 96.8% DC               | WLAN          | 8.77     | ±9.6                   |
| 10757 | AAC | ET160, MCS2 (216.0 Mbps), 97.1% DC               | WLAN          | 8.77     | ±9.6                   |
| 10758 | AAC | ET160, MCS3 (282.0 Mbps), 95.8% DC               | WLAN          | 8.69     | ±9.6                   |
| 10759 | AAC | ET160, MCS4 (432.0 Mbps), 97.1% DC               | WLAN          | 8.58     | ±9.6                   |
| 10760 | AAC | ET160, MCS5 (576.0 Mbps), 96.5% DC               | WLAN          | 8.49     | ±9.6                   |
| 10761 | AAC | ET160, MCS6 (649.0 Mbps), 96.3% DC               | WLAN          | 8.58     | ±9.6                   |
| 10762 | AAC | ET160, MCS7 (721.0 Mbps), 95.3% DC               | WLAN          | 8.49     | ±9.6                   |
| 10763 | AAC | ET160, MCS8 (865.0 Mbps), 95.9% DC               | WLAN          | 8.53     | ±9.6                   |
| 10764 | AAC | ET160, MCS9 (961.0 Mbps), 95.9% DC               | WLAN          | 8.54     | ±9.6                   |
| 10765 | AAC | ET160, MCS10 (1081.0 Mbps), 96.3% DC             | WLAN          | 8.54     | ±9.6                   |
| 10766 | AAC | ET160, MCS11 (1201.0 Mbps), 96.3% DC             | WLAN          | 8.51     | ±9.6                   |
| 10767 | AAG | CP-OFDM, 5.0 MHz, QPSK, 15 kHz, 99.9% DC, 1 RB   | 5G NR FR1 TDD | 7.99     | ±9.6                   |
| 10768 | AAG | CP-OFDM, 10.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB | 5G NR FR1 TDD | 8.01     | ±9.6                   |
| 10769 | AAG | CP-OFDM, 15.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB | 5G NR FR1 TDD | 8.01     | ±9.6                   |
| 10770 | AAG | CP-OFDM, 20.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB | 5G NR FR1 TDD | 8.02     | ±9.6                   |
| 10771 | AAG | CP-OFDM, 25.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB | 5G NR FR1 TDD | 8.02     | ±9.6                   |
| 10772 | AAG | CP-OFDM, 30.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB | 5G NR FR1 TDD | 8.23     | ±9.6                   |

| UID   | Rev | Communication System Name                            | Group         | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|------------------------------------------------------|---------------|----------|------------------------|
| 10773 | AAF | CP-OFDM, 40.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 8.03     | ±9.6                   |
| 10774 | AAE | CP-OFDM, 50.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 8.02     | ±9.6                   |
| 10775 | AAF | CP-OFDM, 5.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB    | 5G NR FR1 TDD | 8.31     | ±9.6                   |
| 10776 | AAE | CP-OFDM, 10.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.30     | ±9.6                   |
| 10777 | AAC | CP-OFDM, 15.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.30     | ±9.6                   |
| 10778 | AAE | CP-OFDM, 20.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10779 | AAC | CP-OFDM, 25.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.42     | ±9.6                   |
| 10780 | AAE | CP-OFDM, 30.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.38     | ±9.6                   |
| 10781 | AAF | CP-OFDM, 40.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.38     | ±9.6                   |
| 10782 | AAE | CP-OFDM, 50.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.43     | ±9.6                   |
| 10783 | AAG | CP-OFDM, 5.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB   | 5G NR FR1 TDD | 8.31     | ±9.6                   |
| 10784 | AAE | CP-OFDM, 10.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.29     | ±9.6                   |
| 10785 | AAD | CP-OFDM, 15.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.40     | ±9.6                   |
| 10786 | AAE | CP-OFDM, 20.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.35     | ±9.6                   |
| 10787 | AAD | CP-OFDM, 25.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.44     | ±9.6                   |
| 10788 | AAE | CP-OFDM, 30.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.39     | ±9.6                   |
| 10789 | AAF | CP-OFDM, 40.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.37     | ±9.6                   |
| 10790 | AAE | CP-OFDM, 50.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.39     | ±9.6                   |
| 10791 | AAG | CP-OFDM, 5.0 MHz, QPSK, 30 kHz, 99.9% DC, 1 RB       | 5G NR FR1 TDD | 7.83     | ±9.6                   |
| 10792 | AAE | CP-OFDM, 10.0 MHz, QPSK, 30 kHz, 99.9% DC, 1 RB      | 5G NR FR1 TDD | 7.92     | ±9.6                   |
| 10793 | AAD | CP-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.95     | ±9.6                   |
| 10794 | AAE | CP-OFDM, 20.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.82     | ±9.6                   |
| 10795 | AAD | CP-OFDM, 25.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.84     | ±9.6                   |
| 10796 | AAE | CP-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.82     | ±9.6                   |
| 10797 | AAF | CP-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 8.01     | ±9.6                   |
| 10798 | AAE | CP-OFDM, 50.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.89     | ±9.6                   |
| 10799 | AAF | CP-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.93     | ±9.6                   |
| 10801 | AAF | CP-OFDM, 80.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.89     | ±9.6                   |
| 10802 | AAE | CP-OFDM, 90.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.87     | ±9.6                   |
| 10803 | AAF | CP-OFDM, 100.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB    | 5G NR FR1 TDD | 7.93     | ±9.6                   |
| 10805 | AAE | CP-OFDM, 10.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10806 | AAD | CP-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.37     | ±9.6                   |
| 10809 | AAE | CP-OFDM, 20.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10810 | AAF | CP-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10812 | AAF | CP-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.35     | ±9.6                   |
| 10817 | AAG | CP-OFDM, 5.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB   | 5G NR FR1 TDD | 8.35     | ±9.6                   |
| 10818 | AAE | CP-OFDM, 10.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10819 | AAD | CP-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.33     | ±9.6                   |
| 10820 | AAE | CP-OFDM, 20.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.30     | ±9.6                   |
| 10821 | AAD | CP-OFDM, 25.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.41     | ±9.6                   |
| 10822 | AAE | CP-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.41     | ±9.6                   |
| 10823 | AAF | CP-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.36     | ±9.6                   |
| 10824 | AAE | CP-OFDM, 50.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.39     | ±9.6                   |
| 10825 | AAF | CP-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.41     | ±9.6                   |
| 10827 | AAF | CP-OFDM, 80.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.42     | ±9.6                   |
| 10828 | AAE | CP-OFDM, 90.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.43     | ±9.6                   |
| 10829 | AAF | CP-OFDM, 100.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB | 5G NR FR1 TDD | 8.40     | ±9.6                   |
| 10830 | AAE | CP-OFDM, 10.0 MHz, QPSK, 60 kHz, 99.9% DC, 1 RB      | 5G NR FR1 TDD | 7.63     | ±9.6                   |
| 10831 | AAD | CP-OFDM, 15.0 MHz, QPSK, 60 kHz, 99.9% DC, 1 RB      | 5G NR FR1 TDD | 7.73     | ±9.6                   |
| 10832 | AAE | CP-OFDM, 20.0 MHz, QPSK, 60 kHz, 99.9% DC, 1 RB      | 5G NR FR1 TDD | 7.74     | ±9.6                   |
| 10833 | AAD | CP-OFDM, 25.0 MHz, QPSK, 60 kHz, 99.9% DC, 1 RB      | 5G NR FR1 TDD | 7.70     | ±9.6                   |
| 10834 | AAE | CP-OFDM, 30.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.75     | ±9.6                   |
| 10835 | AAF | CP-OFDM, 40.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.70     | ±9.6                   |
| 10836 | AAE | CP-OFDM, 50.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.86     | ±9.6                   |
| 10837 | AAF | CP-OFDM, 60.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.68     | ±9.6                   |
| 10839 | AAF | CP-OFDM, 80.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.70     | ±9.6                   |
| 10840 | AAE | CP-OFDM, 90.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.67     | ±9.6                   |
| 10841 | AAF | CP-OFDM, 100.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB    | 5G NR FR1 TDD | 7.71     | ±9.6                   |
| 10843 | AAD | CP-OFDM, 15.0 MHz, QPSK, 60 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.49     | ±9.6                   |
| 10844 | AAE | CP-OFDM, 20.0 MHz, QPSK, 60 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10846 | AAE | CP-OFDM, 30.0 MHz, QPSK, 60 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.41     | ±9.6                   |
| 10854 | AAE | CP-OFDM, 10.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10855 | AAD | CP-OFDM, 15.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.36     | ±9.6                   |
| 10856 | AAE | CP-OFDM, 20.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.37     | ±9.6                   |
| 10857 | AAD | CP-OFDM, 25.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.35     | ±9.6                   |
| 10858 | AAE | CP-OFDM, 30.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.36     | ±9.6                   |

| UID   | Rev | Communication System Name                                 | Group         | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|-----------------------------------------------------------|---------------|----------|------------------------|
| 10859 | AAF | CP-OFDM, 40.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB       | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10860 | AAE | CP-OFDM, 50.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB       | 5G NR FR1 TDD | 8.41     | ±9.6                   |
| 10861 | AAF | CP-OFDM, 60.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB       | 5G NR FR1 TDD | 8.40     | ±9.6                   |
| 10863 | AAF | CP-OFDM, 80.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB       | 5G NR FR1 TDD | 8.41     | ±9.6                   |
| 10864 | AAE | CP-OFDM, 90.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB       | 5G NR FR1 TDD | 8.37     | ±9.6                   |
| 10865 | AAF | CP-OFDM, 100.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB      | 5G NR FR1 TDD | 8.41     | ±9.6                   |
| 10866 | AAF | DFT-s-OFDM, 100.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB      | 5G NR FR1 TDD | 5.68     | ±9.6                   |
| 10868 | AAF | DFT-s-OFDM, 100.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB   | 5G NR FR1 TDD | 5.89     | ±9.6                   |
| 10869 | AAE | DFT-s-OFDM, 100.0 MHz, QPSK, 120 kHz, 100.0% DC, 1 RB     | 5G NR FR2 TDD | 5.75     | ±9.6                   |
| 10870 | AAE | DFT-s-OFDM, 100.0 MHz, QPSK, 120 kHz, 100.0% DC, 100% RB  | 5G NR FR2 TDD | 5.86     | ±9.6                   |
| 10871 | AAE | DFT-s-OFDM, 100.0 MHz, 16QAM, 120 kHz, 100.0% DC, 1 RB    | 5G NR FR2 TDD | 5.75     | ±9.6                   |
| 10872 | AAE | DFT-s-OFDM, 100.0 MHz, 16QAM, 120 kHz, 100.0% DC, 100% RB | 5G NR FR2 TDD | 6.52     | ±9.6                   |
| 10873 | AAE | DFT-s-OFDM, 100.0 MHz, 64QAM, 120 kHz, 100.0% DC, 1 RB    | 5G NR FR2 TDD | 6.61     | ±9.6                   |
| 10874 | AAE | DFT-s-OFDM, 100.0 MHz, 64QAM, 120 kHz, 100.0% DC, 100% RB | 5G NR FR2 TDD | 6.65     | ±9.6                   |
| 10875 | AAE | CP-OFDM, 100.0 MHz, QPSK, 120 kHz, 100.0% DC, 1 RB        | 5G NR FR2 TDD | 7.78     | ±9.6                   |
| 10876 | AAE | CP-OFDM, 100.0 MHz, QPSK, 120 kHz, 100.0% DC, 100% RB     | 5G NR FR2 TDD | 8.39     | ±9.6                   |
| 10877 | AAE | CP-OFDM, 100.0 MHz, 16QAM, 120 kHz, 100.0% DC, 1 RB       | 5G NR FR2 TDD | 7.95     | ±9.6                   |
| 10878 | AAE | CP-OFDM, 100.0 MHz, 16QAM, 120 kHz, 100.0% DC, 100% RB    | 5G NR FR2 TDD | 8.41     | ±9.6                   |
| 10879 | AAE | CP-OFDM, 100.0 MHz, 64QAM, 120 kHz, 100.0% DC, 1 RB       | 5G NR FR2 TDD | 8.12     | ±9.6                   |
| 10880 | AAE | CP-OFDM, 100.0 MHz, 64QAM, 120 kHz, 100.0% DC, 100% RB    | 5G NR FR2 TDD | 8.38     | ±9.6                   |
| 10881 | AAE | DFT-s-OFDM, 50.0 MHz, QPSK, 120 kHz, 100.0% DC, 1 RB      | 5G NR FR2 TDD | 5.75     | ±9.6                   |
| 10882 | AAE | DFT-s-OFDM, 50.0 MHz, QPSK, 120 kHz, 100.0% DC, 100% RB   | 5G NR FR2 TDD | 5.96     | ±9.6                   |
| 10883 | AAE | DFT-s-OFDM, 50.0 MHz, 16QAM, 120 kHz, 100.0% DC, 1 RB     | 5G NR FR2 TDD | 6.57     | ±9.6                   |
| 10884 | AAE | DFT-s-OFDM, 50.0 MHz, 16QAM, 120 kHz, 100.0% DC, 100% RB  | 5G NR FR2 TDD | 6.53     | ±9.6                   |
| 10885 | AAE | DFT-s-OFDM, 50.0 MHz, 64QAM, 120 kHz, 100.0% DC, 1 RB     | 5G NR FR2 TDD | 6.61     | ±9.6                   |
| 10886 | AAE | DFT-s-OFDM, 50.0 MHz, 64QAM, 120 kHz, 100.0% DC, 100% RB  | 5G NR FR2 TDD | 6.65     | ±9.6                   |
| 10887 | AAE | CP-OFDM, 50.0 MHz, QPSK, 120 kHz, 99.9% DC, 1 RB          | 5G NR FR2 TDD | 7.78     | ±9.6                   |
| 10888 | AAE | CP-OFDM, 50.0 MHz, QPSK, 120 kHz, 100.0% DC, 100% RB      | 5G NR FR2 TDD | 8.35     | ±9.6                   |
| 10889 | AAE | CP-OFDM, 50.0 MHz, 16QAM, 120 kHz, 100.0% DC, 1 RB        | 5G NR FR2 TDD | 8.02     | ±9.6                   |
| 10890 | AAE | CP-OFDM, 50.0 MHz, 16QAM, 120 kHz, 100.0% DC, 100% RB     | 5G NR FR2 TDD | 8.40     | ±9.6                   |
| 10891 | AAE | CP-OFDM, 50.0 MHz, 64QAM, 120 kHz, 100.0% DC, 1 RB        | 5G NR FR2 TDD | 8.13     | ±9.6                   |
| 10892 | AAE | CP-OFDM, 50.0 MHz, 64QAM, 120 kHz, 100.0% DC, 100% RB     | 5G NR FR2 TDD | 8.41     | ±9.6                   |
| 10897 | AAE | DFT-s-OFDM, 5.0 MHz, QPSK, 30 kHz, 99.9% DC, 1 RB         | 5G NR FR1 TDD | 5.65     | ±9.6                   |
| 10898 | AAC | DFT-s-OFDM, 10.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.67     | ±9.6                   |
| 10899 | AAB | DFT-s-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.67     | ±9.6                   |
| 10900 | AAC | DFT-s-OFDM, 20.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.68     | ±9.6                   |
| 10901 | AAB | DFT-s-OFDM, 25.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.68     | ±9.6                   |
| 10902 | AAC | DFT-s-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.68     | ±9.6                   |
| 10903 | AAD | DFT-s-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.68     | ±9.6                   |
| 10904 | AAC | DFT-s-OFDM, 50.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.68     | ±9.6                   |
| 10905 | AAD | DFT-s-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.68     | ±9.6                   |
| 10906 | AAD | DFT-s-OFDM, 80.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.68     | ±9.6                   |
| 10907 | AAE | DFT-s-OFDM, 5.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB      | 5G NR FR1 TDD | 5.78     | ±9.6                   |
| 10908 | AAC | DFT-s-OFDM, 10.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.93     | ±9.6                   |
| 10909 | AAB | DFT-s-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.96     | ±9.6                   |
| 10910 | AAC | DFT-s-OFDM, 20.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.83     | ±9.6                   |
| 10911 | AAB | DFT-s-OFDM, 25.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.93     | ±9.6                   |
| 10912 | AAC | DFT-s-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.84     | ±9.6                   |
| 10913 | AAD | DFT-s-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.84     | ±9.6                   |
| 10914 | AAC | DFT-s-OFDM, 50.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.85     | ±9.6                   |
| 10915 | AAD | DFT-s-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.83     | ±9.6                   |
| 10916 | AAD | DFT-s-OFDM, 80.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.87     | ±9.6                   |
| 10917 | AAD | DFT-s-OFDM, 100.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB    | 5G NR FR1 TDD | 5.94     | ±9.6                   |
| 10918 | AAE | DFT-s-OFDM, 5.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB     | 5G NR FR1 TDD | 5.86     | ±9.6                   |
| 10919 | AAC | DFT-s-OFDM, 10.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.86     | ±9.6                   |
| 10920 | AAB | DFT-s-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.87     | ±9.6                   |
| 10921 | AAC | DFT-s-OFDM, 20.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.84     | ±9.6                   |
| 10922 | AAB | DFT-s-OFDM, 25.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.82     | ±9.6                   |
| 10923 | AAC | DFT-s-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.84     | ±9.6                   |
| 10924 | AAD | DFT-s-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.84     | ±9.6                   |
| 10925 | AAC | DFT-s-OFDM, 50.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.95     | ±9.6                   |
| 10926 | AAD | DFT-s-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.84     | ±9.6                   |
| 10927 | AAD | DFT-s-OFDM, 80.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.94     | ±9.6                   |
| 10928 | AAD | DFT-s-OFDM, 5.0 MHz, QPSK, 15 kHz, 1 RB                   | 5G NR FR1 FDD | 5.52     | ±9.6                   |
| 10929 | AAD | DFT-s-OFDM, 10.0 MHz, QPSK, 15 kHz, 1 RB                  | 5G NR FR1 FDD | 5.52     | ±9.6                   |
| 10930 | AAC | DFT-s-OFDM, 15.0 MHz, QPSK, 15 kHz, 1 RB                  | 5G NR FR1 FDD | 5.52     | ±9.6                   |

| UID   | Rev | Communication System Name                   | Group         | PAR (dB) | Unc <sup>E</sup> $k = 2$ |
|-------|-----|---------------------------------------------|---------------|----------|--------------------------|
| 10931 | AAC | DFT-s-OFDM, 20.0 MHz, QPSK, 15 kHz, 1 RB    | 5G NR FR1 FDD | 5.51     | ±9.6                     |
| 10932 | AAC | DFT-s-OFDM, 25.0 MHz, QPSK, 15 kHz, 1 RB    | 5G NR FR1 FDD | 5.51     | ±9.6                     |
| 10933 | AAC | DFT-s-OFDM, 30.0 MHz, QPSK, 15 kHz, 1 RB    | 5G NR FR1 FDD | 5.51     | ±9.6                     |
| 10934 | AAC | DFT-s-OFDM, 40.0 MHz, QPSK, 15 kHz, 1 RB    | 5G NR FR1 FDD | 5.51     | ±9.6                     |
| 10935 | AAD | DFT-s-OFDM, 50.0 MHz, QPSK, 15 kHz, 1 RB    | 5G NR FR1 FDD | 5.51     | ±9.6                     |
| 10936 | AAD | DFT-s-OFDM, 5.0 MHz, QPSK, 15 kHz, 50% RB   | 5G NR FR1 FDD | 5.90     | ±9.6                     |
| 10937 | AAD | DFT-s-OFDM, 10.0 MHz, QPSK, 15 kHz, 50% RB  | 5G NR FR1 FDD | 5.77     | ±9.6                     |
| 10938 | AAC | DFT-s-OFDM, 15.0 MHz, QPSK, 15 kHz, 50% RB  | 5G NR FR1 FDD | 5.90     | ±9.6                     |
| 10939 | AAC | DFT-s-OFDM, 20.0 MHz, QPSK, 15 kHz, 50% RB  | 5G NR FR1 FDD | 5.82     | ±9.6                     |
| 10940 | AAC | DFT-s-OFDM, 25.0 MHz, QPSK, 15 kHz, 50% RB  | 5G NR FR1 FDD | 5.89     | ±9.6                     |
| 10941 | AAC | DFT-s-OFDM, 30.0 MHz, QPSK, 15 kHz, 50% RB  | 5G NR FR1 FDD | 5.83     | ±9.6                     |
| 10942 | AAC | DFT-s-OFDM, 40.0 MHz, QPSK, 15 kHz, 50% RB  | 5G NR FR1 FDD | 5.85     | ±9.6                     |
| 10943 | AAD | DFT-s-OFDM, 50.0 MHz, QPSK, 15 kHz, 50% RB  | 5G NR FR1 FDD | 5.95     | ±9.6                     |
| 10944 | AAD | DFT-s-OFDM, 5.0 MHz, QPSK, 15 kHz, 100% RB  | 5G NR FR1 FDD | 5.81     | ±9.6                     |
| 10945 | AAD | DFT-s-OFDM, 10.0 MHz, QPSK, 15 kHz, 100% RB | 5G NR FR1 FDD | 5.85     | ±9.6                     |
| 10946 | AAC | DFT-s-OFDM, 15.0 MHz, QPSK, 15 kHz, 100% RB | 5G NR FR1 FDD | 5.83     | ±9.6                     |
| 10947 | AAC | DFT-s-OFDM, 20.0 MHz, QPSK, 15 kHz, 100% RB | 5G NR FR1 FDD | 5.87     | ±9.6                     |
| 10948 | AAC | DFT-s-OFDM, 25.0 MHz, QPSK, 15 kHz, 100% RB | 5G NR FR1 FDD | 5.94     | ±9.6                     |
| 10949 | AAC | DFT-s-OFDM, 30.0 MHz, QPSK, 15 kHz, 100% RB | 5G NR FR1 FDD | 5.87     | ±9.6                     |
| 10950 | AAC | DFT-s-OFDM, 40.0 MHz, QPSK, 15 kHz, 100% RB | 5G NR FR1 FDD | 5.94     | ±9.6                     |
| 10951 | AAD | DFT-s-OFDM, 50.0 MHz, QPSK, 15 kHz, 100% RB | 5G NR FR1 FDD | 5.92     | ±9.6                     |
| 10978 | AAA | BDR, 1.0 MHz, 76.7% DC                      | ULLA          | 1.16     | ±9.6                     |
| 10979 | AAA | HDR4, 2.0 MHz, 25.1% DC                     | ULLA          | 8.58     | ±9.6                     |
| 10980 | AAA | HDR6, 4.0 MHz, 16.5% DC                     | ULLA          | 10.32    | ±9.6                     |
| 10981 | AAA | HDRp4, 2.0 MHz, 89.0% DC                    | ULLA          | 3.19     | ±9.6                     |
| 10982 | AAA | HDRp8, 4.0 MHz, 90.3% DC                    | ULLA          | 3.43     | ±9.6                     |
| 11013 | AAB | EHT320, MCS1 (272.0 Mbps), 100.0% DC        | WLAN          | 8.47     | ±9.6                     |
| 11014 | AAB | EHT320, MCS2 (408.0 Mbps), 100.0% DC        | WLAN          | 8.45     | ±9.6                     |
| 11015 | AAB | EHT320, MCS3 (544.0 Mbps), 100.0% DC        | WLAN          | 8.44     | ±9.6                     |
| 11016 | AAB | EHT320, MCS4 (817.0 Mbps), 100.0% DC        | WLAN          | 8.44     | ±9.6                     |
| 11017 | AAB | EHT320, MCS5 (1089.0 Mbps), 100.0% DC       | WLAN          | 8.41     | ±9.6                     |
| 11018 | AAB | EHT320, MCS6 (1225.0 Mbps), 100.0% DC       | WLAN          | 8.40     | ±9.6                     |
| 11019 | AAB | EHT320, MCS7 (1361.0 Mbps), 100.0% DC       | WLAN          | 8.29     | ±9.6                     |
| 11020 | AAB | EHT320, MCS8 (1633.0 Mbps), 100.0% DC       | WLAN          | 8.27     | ±9.6                     |
| 11021 | AAB | EHT320, MCS9 (1815.0 Mbps), 100.0% DC       | WLAN          | 8.46     | ±9.6                     |
| 11022 | AAB | EHT320, MCS10 (2042.0 Mbps), 100.0% DC      | WLAN          | 8.36     | ±9.6                     |
| 11023 | AAB | EHT320, MCS11 (2269.0 Mbps), 100.0% DC      | WLAN          | 8.08     | ±9.6                     |
| 11024 | AAB | EHT320, MCS12 (2450.0 Mbps), 100.0% DC      | WLAN          | 8.42     | ±9.6                     |
| 11025 | AAB | EHT320, MCS13 (2722.0 Mbps), 100.0% DC      | WLAN          | 8.37     | ±9.6                     |
| 11026 | AAB | EHT320, MCS0 (136.0 Mbps), 100.0% DC        | WLAN          | 8.39     | ±9.6                     |

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client

Sporton  
Taoyuan City

Certificate No.

EX-7793\_Feb26

## CALIBRATION CERTIFICATE

Object

EX3DV4 - SN:7793

Calibration procedure(s)

QA CAL-01.v10, QA CAL-12.v10, QA CAL-14.v7, QA CAL-23.v6,  
QA CAL-25.v8, QA CAL-48.v2  
Calibration procedure for dosimetric E-field probes

Calibration date

February 23, 2026

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility; environment temperature  $(22 \pm 3)^\circ\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID         | Calibration Date (Certificate No.)     | Sched. Cal. |
|-----------------------------|------------|----------------------------------------|-------------|
| Power Sensor R&S NRP40T     | SN: 101861 | 29-Apr-25 (No. 2025-001450)            | Apr-26      |
| N-type mismatch combination | SN: L1119  | 26-Mar-25 (No. 217-04292)              | Mar-26      |
| OCP DAK-12                  | SN: 1016   | 16-Sept-25 (No. OCP-DAK12-1016_Sep25)  | Sep-26      |
| OCP DAK-3.5                 | SN: 1249   | 16-Sept-25 (No. OCP-DAK3.5-1249_Sep25) | Sep-26      |
| Reference Probe EX3DV4      | SN: 7349   | 29-Jan-26 (No. EX3-7349_Jan26)         | Jan-27      |
| DAE4                        | SN: 1301   | 22-Jan-26 (No. DAE4-1301_Jan26)        | Jan-27      |

| Secondary Standards | ID        | Check Date (in house)                 | Sched. Check |
|---------------------|-----------|---------------------------------------|--------------|
| ACAP 2020 Setup 1   | SN: L1404 | 01-Oct-25 (No. IHCK_ACAP2020-1_Oct25) | Oct-26       |
| OCP DAK-12          | SN: 1029  | 27-Feb-25 (No. OCP-DAK12-1029_Feb25)  | Feb-26       |
| OCP DAK-3.5         | SN: 1336  | 10-Dec-25 (No. OCP-DAK3.5-1336_Dec25) | Dec-26       |

|               |                  |                       |           |
|---------------|------------------|-----------------------|-----------|
|               | Name             | Function              | Signature |
| Calibrated by | Henrique Almeida | Laboratory Technician |           |
| Approved by   | Sven Kühn        | Technical Manager     |           |

Issued: February 24, 2026

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

## Calibration Laboratory of

Schmid & Partner  
Engineering AG

Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
C Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

## Glossary

|                        |                                                                                                                                                |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| TSL                    | tissue simulating liquid                                                                                                                       |
| NORM <sub>x,y,z</sub>  | sensitivity in free space                                                                                                                      |
| ConvF                  | sensitivity in TSL / NORM <sub>x,y,z</sub>                                                                                                     |
| DCP                    | diode compression point                                                                                                                        |
| CF                     | crest factor (1/duty_cycle) of the RF signal                                                                                                   |
| A, B, C, D             | modulation dependent linearization parameters                                                                                                  |
| Polarization $\varphi$ | $\varphi$ rotation around probe axis                                                                                                           |
| Polarization $\theta$  | $\theta$ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\theta = 0$ is normal to probe axis |
| Connector Angle        | Information used in DASY system to align probe sensor X to the robot coordinate system                                                         |

## Calibration is Performed According to the Following Standards:

- IEC/IEEE 62209-1528, "Measurement Procedure For The Assessment Of Specific Absorption Rate Of Human Exposure To Radio Frequency Fields From Hand-Held And Body-Worn Wireless Communication Devices – Part 1528: Human Models, Instrumentation And Procedures (Frequency Range of 4 MHz to 10 GHz)", October 2020.
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

## Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\theta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not affect the E<sup>2</sup>-field uncertainty inside TSL (see below ConvF).
- NORM(f)<sub>x,y,z</sub> = NORM<sub>x,y,z</sub> \* frequency\_response** (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCPx,y,z**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal. DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics.
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; D<sub>x,y,z</sub>; VR<sub>x,y,z</sub>**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM<sub>x</sub> (no uncertainty required).

## Parameters of Probe: EX3DV4 - SN:7793

## Basic Calibration Parameters

|                                                           | Sensor X | Sensor Y | Sensor Z | Unc (k = 2) |
|-----------------------------------------------------------|----------|----------|----------|-------------|
| Norm ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) <sup>A</sup> | 0.57     | 0.66     | 0.58     | ±10.1%      |
| DCP (mV) <sup>B</sup>                                     | 107.4    | 109.2    | 108.3    | ±4.7%       |

## Calibration Results for Modulation Response

| UID   | Communication System Name      |   | A<br>dB | B<br>dB $\sqrt{\mu\text{V}}$ | C     | D<br>dB | VR<br>mV | Max<br>dev. | Max<br>Unc <sup>E</sup><br>k = 2 |
|-------|--------------------------------|---|---------|------------------------------|-------|---------|----------|-------------|----------------------------------|
| 0     | Continuous Wave                | X | 0.00    | 0.00                         | 1.00  | 0.00    | 123.8    | ±2.1%       | ±4.7%                            |
|       |                                | Y | 0.00    | 0.00                         | 1.00  |         | 141.8    |             |                                  |
|       |                                | Z | 0.00    | 0.00                         | 1.00  |         | 126.6    |             |                                  |
| 10352 | Pulse (D=10%, T=5 ms)          | X | 1.00    | 69.91                        | 17.50 | 10.00   | 23.0     | ±1.6%       | ±9.6%                            |
|       |                                | Y | 0.34    | 58.47                        | 13.48 |         | 24.0     |             |                                  |
|       |                                | Z | 0.30    | 60.00                        | 15.13 |         | 24.0     |             |                                  |
| 10353 | Pulse (D=20%, T=5 ms)          | X | 0.94    | 72.92                        | 17.53 | 6.99    | 47.0     | ±1.3%       | ±9.6%                            |
|       |                                | Y | 0.31    | 61.48                        | 13.54 |         | 48.0     |             |                                  |
|       |                                | Z | 0.27    | 63.01                        | 15.22 |         | 48.0     |             |                                  |
| 10354 | Pulse (D=40%, T=5 ms)          | X | 0.87    | 75.93                        | 17.56 | 3.98    | 93.0     | ±1.1%       | ±9.6%                            |
|       |                                | Y | 0.29    | 64.49                        | 13.59 |         | 95.0     |             |                                  |
|       |                                | Z | 0.24    | 66.02                        | 15.32 |         | 95.0     |             |                                  |
| 10355 | Pulse (D=60%, T=5 ms)          | X | 0.84    | 77.69                        | 17.57 | 2.22    | 139.0    | ±1.1%       | ±9.6%                            |
|       |                                | Y | 0.27    | 66.25                        | 13.63 |         | 142.0    |             |                                  |
|       |                                | Z | 0.22    | 67.78                        | 15.40 |         | 143.0    |             |                                  |
| 10387 | Random (BW=1 MHz, MOD=QPSK)    | X | 0.02    | 81.39                        | 18.62 | 0.25    | 106.0    | ±1.4%       | ±9.6%                            |
|       |                                | Y | 0.01    | 78.72                        | 14.96 |         | 108.0    |             |                                  |
|       |                                | Z | 0.00    | 64.90                        | 17.27 |         | 109.0    |             |                                  |
| 10388 | Random (BW=10 MHz, MOD=QPSK)   | X | 1.50    | 74.69                        | 17.37 | 0.00    | 112.0    | ±2.7%       | ±9.6%                            |
|       |                                | Y | 0.51    | 63.26                        | 13.14 |         | 115.0    |             |                                  |
|       |                                | Z | 0.49    | 64.79                        | 14.61 |         | 115.0    |             |                                  |
| 10396 | Random (BW=100 kHz, MOD=64QAM) | X | 0.05    | 73.64                        | 19.09 | 1.45    | 80.0     | ±2.5%       | ±9.6%                            |
|       |                                | Y | 0.00    | 62.20                        | 16.11 |         | 82.0     |             |                                  |
|       |                                | Z | 0.00    | 63.73                        | 18.40 |         | 82.0     |             |                                  |
| 10399 | Random (BW=40 MHz, MOD=64QAM)  | X | 3.67    | 73.64                        | 17.29 | 0.00    | 103.0    | ±3.9%       | ±9.6%                            |
|       |                                | Y | 1.48    | 62.20                        | 12.12 |         | 106.0    |             |                                  |
|       |                                | Z | 1.61    | 63.73                        | 13.03 |         | 107.0    |             |                                  |
| 10414 | Random (BW=40 MHz, HIGH PAR)   | X | 4.30    | 71.37                        | 17.29 | 0.00    | 74.0     | ±2.1%       | ±9.6%                            |
|       |                                | Y | 1.72    | 59.93                        | 12.03 |         | 76.0     |             |                                  |
|       |                                | Z | 1.81    | 61.46                        | 12.95 |         | 77.0     |             |                                  |

Note: For details on UID parameters see Appendix

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of Norm X,Y,Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Pages 5 and 6).

<sup>B</sup> Linearization parameter uncertainty for maximum specified field strength.

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

## Parameters of Probe: EX3DV4 - SN:7793

### Sensor Model Parameters

|   | C1<br>IF | C2<br>IF | $\alpha$<br>V <sup>-1</sup> | T1<br>ms V <sup>-2</sup> | T2<br>ms V <sup>-1</sup> | T3<br>ms | T4<br>V <sup>-2</sup> | T5<br>V <sup>-1</sup> | T6   |
|---|----------|----------|-----------------------------|--------------------------|--------------------------|----------|-----------------------|-----------------------|------|
| x | 7.8      | 55.77    | 32.93                       | 4.05                     | 0.00                     | 4.90     | 0.61                  | 0.00                  | 1.00 |
| y | 7.3      | 52.11    | 32.67                       | 3.79                     | 0.00                     | 4.91     | 0.51                  | 0.00                  | 1.00 |
| z | 6.6      | 47.69    | 33.12                       | 3.80                     | 0.00                     | 4.90     | 0.59                  | 0.00                  | 1.00 |

### Other Probe Parameters

|                                               |            |
|-----------------------------------------------|------------|
| Sensor Arrangement                            | Triangular |
| Connector Angle                               | 33.9°      |
| Mechanical Surface Detection Mode             | enabled    |
| Optical Surface Detection Mode                | disabled   |
| Probe Overall Length                          | 337 mm     |
| Probe Body Diameter                           | 12 mm      |
| Tip Length                                    | 9 mm       |
| Tip Diameter                                  | 2.5 mm     |
| Probe Tip to Sensor X Calibration Point       | 1 mm       |
| Probe Tip to Sensor Y Calibration Point       | 1 mm       |
| Probe Tip to Sensor Z Calibration Point       | 1 mm       |
| Recommended Measurement Distance from Surface | 1.4 mm     |

**Note:** Measurement distance from surface can be increased to 3–4 mm for an *Area Scan* job.

## Parameters of Probe: EX3DV4 - SN:7793

### Calibration Parameter Determined in HSL

| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity <sup>F</sup> (S/m) | ConvF X | ConvF Y | ConvF Z | Alpha <sup>G</sup> | Depth <sup>G</sup> (mm) | Unc <sup>H</sup> (k = 2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|--------------------------|
| 750                  | 41.9                               | 0.89                            | 8.87    | 9.21    | 9.40    | 0.33               | 1.27                    | ±11.0%                   |
| 835                  | 41.5                               | 0.90                            | 8.63    | 8.96    | 9.15    | 0.33               | 1.27                    | ±11.0%                   |
| 900                  | 41.5                               | 0.97                            | 8.48    | 8.81    | 8.99    | 0.33               | 1.27                    | ±11.0%                   |
| 1750                 | 40.1                               | 1.37                            | 7.25    | 7.53    | 7.69    | 0.32               | 1.27                    | ±11.0%                   |
| 1900                 | 40.0                               | 1.40                            | 6.85    | 7.12    | 7.26    | 0.32               | 1.27                    | ±11.0%                   |
| 2000                 | 40.0                               | 1.40                            | 6.90    | 7.17    | 7.32    | 0.32               | 1.27                    | ±11.0%                   |
| 2300                 | 39.5                               | 1.67                            | 6.68    | 6.93    | 7.08    | 0.32               | 1.27                    | ±11.0%                   |
| 2450                 | 39.2                               | 1.80                            | 6.55    | 6.81    | 6.95    | 0.31               | 1.27                    | ±11.0%                   |
| 2600                 | 39.0                               | 1.96                            | 6.54    | 6.80    | 6.94    | 0.31               | 1.27                    | ±11.0%                   |
| 5250                 | 35.9                               | 4.71                            | 4.94    | 5.14    | 5.24    | 0.28               | 1.27                    | ±13.1%                   |
| 5600                 | 35.5                               | 5.07                            | 4.51    | 4.68    | 4.78    | 0.26               | 1.27                    | ±13.1%                   |
| 5800                 | 35.3                               | 5.27                            | 4.42    | 4.59    | 4.69    | 0.25               | 1.27                    | ±13.1%                   |

<sup>C</sup> Frequency validity above 300 MHz of ±100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ±50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ±10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Validity of ConvF assessed at 6 MHz is 4–9 MHz; and ConvF assessed at 13 MHz is 9–19 MHz. Above 5 GHz frequency validity can be extended to ±110 MHz.

<sup>F</sup> The probes are calibrated using tissue simulating liquids (TSL) that deviate for  $\epsilon$  and  $\sigma$  by less than ±5% from the target values (typically better than ±3%) and are valid for TSL with deviations of up to ±10% if SAR correction is applied.

<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ±1% for frequencies below 3 GHz and below ±2% for frequencies between 3–6 GHz at any distance larger than half the probe tip diameter from the boundary.

<sup>H</sup> The stated uncertainty is the total calibration uncertainty (k = 2) of Norm-ConvF. This is equivalent to the uncertainty component with the symbol CF in Table 9 of IEC/IEEE 62209-1528:2020.

## Parameters of Probe: EX3DV4 - SN:7793

### Calibration Parameter Determined in HSL

| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity <sup>F</sup> (S/m) | ConvF X | ConvF Y | ConvF Z | Alpha <sup>G</sup> | Depth <sup>G</sup> (mm) | Unc <sup>H</sup> (k = 2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|--------------------------|
| 6500                 | 34.5                               | 6.07                            | 4.65    | 4.83    | 4.93    | 0.20               | 1.27                    | ±18.6%                   |

<sup>C</sup> Frequency validity is -600/+700 MHz at 6.5 GHz, ±700 MHz at or above 7 GHz, and ±150 MHz at 9.85 GHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.


<sup>F</sup> The probes are calibrated using tissue simulating liquids (TSL) that deviate for  $\epsilon$  and  $\sigma$  by less than ±10% from the target values (typically better than ±6%) and are valid for TSL with deviations of up to ±10%.

<sup>G</sup> Alpha/Depth are determined during calibration; SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ±1% for frequencies below 3 GHz; below ±2% for frequencies between 3–6 GHz; and below ±4% for frequencies between 6–10 GHz at any distance larger than half the probe tip diameter from the boundary.

<sup>H</sup> The stated uncertainty is the total calibration uncertainty (k = 2) of Norm ConvF. This is equivalent to the uncertainty component with the symbol CF in Table 9 of IEC/IEEE 62209-1528:2020.



## Frequency Response of E-Field

(TEM-Cell:III110 EXX, Waveguide:R22)



Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  ( $k=2$ )



### Receiving Pattern ( $\phi$ ), $\theta = 0^\circ$



Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  ( $k=2$ )


# Dynamic Range $f(SAR_{HSL})$

(TEM cell,  $f_{eval} = 1900\text{ MHz}$ )




Uncertainty of Linearity Assessment:  $\pm 0.6\%$  ( $k=2$ )

## Conversion Factor Assessment



## Deviation from Isotropy in Liquid

Error ( $\phi, \theta$ ),  $f = 900\text{ MHz}$



## Appendix: Modulation Calibration Parameters

| UID   | Rev | Communication System Name                      | Group     | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|------------------------------------------------|-----------|----------|------------------------|
| 0     |     | Continuous Wave                                | CW        | 0.00     | ±4.7                   |
| 10010 | CAB | Pulse (D=10%, T=100ms)                         | Test      | 10.00    | ±9.6                   |
| 10011 | CAC | Rel. 99, RMC, QPSK, 5.0 MHz                    | WCDMA     | 2.91     | ±9.6                   |
| 10012 | CAB | DSSS, DBPSK, 1.0 Mbps, 92.5% DC                | WLAN      | 1.87     | ±9.6                   |
| 10013 | CAB | OFDM, BPSK, 6.0 Mbps, 72.1% DC                 | WLAN      | 9.46     | ±9.6                   |
| 10021 | DAC | Voice, GSMK, 1 slot(s)                         | GSM       | 9.39     | ±9.6                   |
| 10023 | DAC | Data, GSMK, 1 slot(s)                          | GSM       | 9.57     | ±9.6                   |
| 10024 | DAC | Data, GSMK, 2 slot(s)                          | GSM       | 6.56     | ±9.6                   |
| 10025 | DAC | Data, 8PSK, 1 slot(s)                          | GSM       | 12.62    | ±9.6                   |
| 10026 | DAC | Data, 8PSK, 2 slot(s)                          | GSM       | 9.55     | ±9.6                   |
| 10027 | DAC | Data, GSMK, 3 slot(s)                          | GSM       | 4.80     | ±9.6                   |
| 10028 | DAC | Data, GSMK, 4 slot(s)                          | GSM       | 3.55     | ±9.6                   |
| 10029 | DAC | Data, 8PSK, 3 slot(s)                          | GSM       | 7.78     | ±9.6                   |
| 10030 | CAA | BR, DH1, GFSK                                  | Bluetooth | 5.30     | ±9.6                   |
| 10031 | CAA | BR, DH3, GFSK                                  | Bluetooth | 1.87     | ±9.6                   |
| 10032 | CAA | BR, DH5, GFSK                                  | Bluetooth | 1.16     | ±9.6                   |
| 10033 | CAA | EDR, DH1, pi/4-DQPSK                           | Bluetooth | 7.74     | ±9.6                   |
| 10034 | CAA | EDR, DH3, pi/4-DQPSK                           | Bluetooth | 4.53     | ±9.6                   |
| 10035 | CAA | EDR, DH5, pi/4-DQPSK                           | Bluetooth | 3.83     | ±9.6                   |
| 10036 | CAA | EDR, DH1, 8-DPSK                               | Bluetooth | 8.01     | ±9.6                   |
| 10037 | CAA | EDR, DH3, 8-DPSK                               | Bluetooth | 4.77     | ±9.6                   |
| 10038 | CAA | EDR, DH5, 8-DPSK                               | Bluetooth | 4.10     | ±9.6                   |
| 10039 | CAB | RC1, 1xRTT                                     | CDMA2000  | 4.57     | ±9.6                   |
| 10048 | CAA | Full Slot, GFSK, 1 slot(s)                     | DECT      | 13.80    | ±9.6                   |
| 10049 | CAA | Double Slot, GFSK, 2 slot(s)                   | DECT      | 10.79    | ±9.6                   |
| 10056 | CAA | TD-SCDMA, QPSK, 1.6 MHz                        | TD-SCDMA  | 11.01    | ±9.6                   |
| 10058 | DAC | Data, 8PSK, 4 slot(s)                          | GSM       | 6.52     | ±9.6                   |
| 10059 | CAB | DSSS, DQPSK, 2.0 Mbps, 87.4% DC                | WLAN      | 2.12     | ±9.6                   |
| 10060 | CAB | HR-DSSS, DQPSK, 5.5 Mbps, 72.7% DC             | WLAN      | 2.83     | ±9.6                   |
| 10061 | CAB | HR-DSSS, DQPSK, 11.0 Mbps, 57.5% DC            | WLAN      | 3.60     | ±9.6                   |
| 10062 | CAE | OFDM, BPSK, 6.0 Mbps, 89.1% DC                 | WLAN      | 8.68     | ±9.6                   |
| 10063 | CAE | OFDM, BPSK, 9.0 Mbps, 65.3% DC                 | WLAN      | 8.63     | ±9.6                   |
| 10064 | CAE | OFDM, QPSK, 12.0 Mbps, 82.0% DC                | WLAN      | 9.09     | ±9.6                   |
| 10065 | CAE | OFDM, QPSK, 18.0 Mbps, 76.0% DC                | WLAN      | 9.00     | ±9.6                   |
| 10066 | CAE | OFDM, 16QAM, 24.0 Mbps, 70.6% DC               | WLAN      | 9.38     | ±9.6                   |
| 10067 | CAE | OFDM, 16QAM, 36.0 Mbps, 62.9% DC               | WLAN      | 10.12    | ±9.6                   |
| 10068 | CAE | OFDM, 64QAM, 48.0 Mbps, 56.6% DC               | WLAN      | 10.24    | ±9.6                   |
| 10069 | CAE | OFDM, 64QAM, 54.0 Mbps, 54.4% DC               | WLAN      | 10.56    | ±9.6                   |
| 10071 | CAB | OFDM, BPSK, 9.0 Mbps, 65.1% DC                 | WLAN      | 9.83     | ±9.6                   |
| 10072 | CAB | OFDM, QPSK, 12.0 Mbps, 60.1% DC                | WLAN      | 9.62     | ±9.6                   |
| 10073 | CAB | OFDM, QPSK, 18.0 Mbps, 53.1% DC                | WLAN      | 9.94     | ±9.6                   |
| 10074 | CAB | OFDM, 16QAM, 24.0 Mbps, 48.5% DC               | WLAN      | 10.30    | ±9.6                   |
| 10075 | CAB | OFDM, 16QAM, 36.0 Mbps, 42.9% DC               | WLAN      | 10.77    | ±9.6                   |
| 10076 | CAB | OFDM, 64QAM, 48.0 Mbps, 39.5% DC               | WLAN      | 10.94    | ±9.6                   |
| 10077 | CAB | OFDM, 64QAM, 54.0 Mbps, 38.5% DC               | WLAN      | 11.00    | ±9.6                   |
| 10081 | CAB | RC3, 1xRTT                                     | CDMA2000  | 3.97     | ±9.6                   |
| 10097 | CAC | Rel. 5 HSDPA, QPSK, 5.0 MHz                    | WCDMA     | 3.98     | ±9.6                   |
| 10096 | CAC | Rel. 6 HSUPA, Subset 2, QPSK, 5.0 MHz          | WCDMA     | 3.98     | ±9.6                   |
| 10100 | CAF | 20.0 MHz, QPSK, 100% RB                        | LTE-FDD   | 5.67     | ±9.6                   |
| 10101 | CAF | 20.0 MHz, 16QAM, 100% RB                       | LTE-FDD   | 6.42     | ±9.6                   |
| 10102 | CAF | 20.0 MHz, 64QAM, 100% RB                       | LTE-FDD   | 6.60     | ±9.6                   |
| 10103 | CAH | 20.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB  | LTE-TDD   | 9.29     | ±9.6                   |
| 10104 | CAH | 20.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB | LTE-TDD   | 9.97     | ±9.6                   |
| 10105 | CAH | 20.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 100% RB | LTE-TDD   | 10.01    | ±9.6                   |
| 10106 | CAH | 10.0 MHz, QPSK, 100% RB                        | LTE-FDD   | 5.80     | ±9.6                   |
| 10109 | CAH | 10.0 MHz, 16QAM, 100% RB                       | LTE-FDD   | 6.43     | ±9.6                   |
| 10110 | CAH | 5.0 MHz, QPSK, 100% RB                         | LTE-FDD   | 5.75     | ±9.6                   |
| 10111 | CAH | 5.0 MHz, 16QAM, 100% RB                        | LTE-FDD   | 6.44     | ±9.6                   |
| 10112 | CAH | 10.0 MHz, 64QAM, 100% RB                       | LTE-FDD   | 6.59     | ±9.6                   |
| 10113 | CAH | 5.0 MHz, 64QAM, 100% RB                        | LTE-FDD   | 6.62     | ±9.6                   |
| 10114 | CAE | HT40 Greenfield, MCS0 (13.5 Mbps), 99.7% DC    | WLAN      | 8.10     | ±9.6                   |
| 10115 | CAE | HT40 Greenfield, MCS4 (81.0 Mbps), 99.7% DC    | WLAN      | 8.46     | ±9.6                   |
| 10116 | CAE | HT40 Greenfield, MCS7 (135.0 Mbps), 99.7% DC   | WLAN      | 8.15     | ±9.6                   |

| UID   | Rev | Communication System Name                     | Group   | PAR (dB) | Unc <sup>E</sup> $k = 2$ |
|-------|-----|-----------------------------------------------|---------|----------|--------------------------|
| 10117 | CAE | HT40 Mixed, MCS0 (13.5 Mbps), 99.7% DC        | WLAN    | 8.07     | ±9.6                     |
| 10118 | CAE | HT40 Mixed, MCS4 (81.0 Mbps), 99.7% DC        | WLAN    | 8.59     | ±9.6                     |
| 10119 | CAE | HT40 Mixed, MCS7 (135.0 Mbps), 99.7% DC       | WLAN    | 8.13     | ±9.6                     |
| 10140 | CAF | 15.0 MHz, 16QAM, 100% RB                      | LTE-FDD | 6.49     | ±9.6                     |
| 10141 | CAF | 15.0 MHz, 64QAM, 100% RB                      | LTE-FDD | 6.53     | ±9.6                     |
| 10142 | CAF | 3.0 MHz, QPSK, 100% RB                        | LTE-FDD | 5.73     | ±9.6                     |
| 10143 | CAF | 3.0 MHz, 16QAM, 100% RB                       | LTE-FDD | 6.35     | ±9.6                     |
| 10144 | CAF | 3.0 MHz, 64QAM, 100% RB                       | LTE-FDD | 6.85     | ±9.6                     |
| 10145 | CAG | 1.4 MHz, QPSK, 100% RB                        | LTE-FDD | 5.76     | ±9.6                     |
| 10146 | CAG | 1.4 MHz, 16QAM, 100% RB                       | LTE-FDD | 6.41     | ±9.6                     |
| 10147 | CAG | 1.4 MHz, 64QAM, 100% RB                       | LTE-FDD | 6.72     | ±9.6                     |
| 10149 | CAF | 20.0 MHz, 16QAM, 50% RB                       | LTE-FDD | 6.42     | ±9.6                     |
| 10150 | CAF | 20.0 MHz, 64QAM, 50% RB                       | LTE-FDD | 6.60     | ±9.6                     |
| 10151 | CAH | 20.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB  | LTE-TDD | 9.28     | ±9.6                     |
| 10152 | CAH | 20.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB | LTE-TDD | 9.92     | ±9.6                     |
| 10153 | CAH | 20.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 50% RB | LTE-TDD | 10.05    | ±9.6                     |
| 10154 | CAH | 10.0 MHz, QPSK, 50% RB                        | LTE-FDD | 5.75     | ±9.6                     |
| 10155 | CAH | 10.0 MHz, 16QAM, 50% RB                       | LTE-FDD | 6.43     | ±9.6                     |
| 10156 | CAH | 5.0 MHz, QPSK, 50% RB                         | LTE-FDD | 5.79     | ±9.6                     |
| 10157 | CAH | 5.0 MHz, 16QAM, 50% RB                        | LTE-FDD | 6.49     | ±9.6                     |
| 10158 | CAH | 10.0 MHz, 64QAM, 50% RB                       | LTE-FDD | 6.62     | ±9.6                     |
| 10159 | CAH | 5.0 MHz, 64QAM, 50% RB                        | LTE-FDD | 6.56     | ±9.6                     |
| 10160 | CAF | 15.0 MHz, QPSK, 50% RB                        | LTE-FDD | 5.82     | ±9.6                     |
| 10161 | CAF | 15.0 MHz, 16QAM, 50% RB                       | LTE-FDD | 6.43     | ±9.6                     |
| 10162 | CAF | 15.0 MHz, 64QAM, 50% RB                       | LTE-FDD | 6.58     | ±9.6                     |
| 10166 | CAG | 1.4 MHz, QPSK, 50% RB                         | LTE-FDD | 5.46     | ±9.6                     |
| 10167 | CAG | 1.4 MHz, 16QAM, 50% RB                        | LTE-FDD | 6.21     | ±9.6                     |
| 10168 | CAG | 1.4 MHz, 64QAM, 50% RB                        | LTE-FDD | 6.79     | ±9.6                     |
| 10169 | CAF | 20.0 MHz, QPSK, 1 RB                          | LTE-FDD | 5.73     | ±9.6                     |
| 10170 | CAF | 20.0 MHz, 16QAM, 1 RB                         | LTE-FDD | 6.52     | ±9.6                     |
| 10171 | AAF | 20.0 MHz, 64QAM, 1 RB                         | LTE-FDD | 6.49     | ±9.6                     |
| 10172 | CAH | 20.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB    | LTE-TDD | 9.21     | ±9.6                     |
| 10173 | CAH | 20.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 1 RB   | LTE-TDD | 9.48     | ±9.6                     |
| 10174 | CAH | 20.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 1 RB   | LTE-TDD | 10.25    | ±9.6                     |
| 10175 | CAH | 10.0 MHz, QPSK, 1 RB                          | LTE-FDD | 5.72     | ±9.6                     |
| 10176 | CAH | 10.0 MHz, 16QAM, 1 RB                         | LTE-FDD | 6.52     | ±9.6                     |
| 10177 | CAJ | 5.0 MHz, QPSK, 1 RB                           | LTE-FDD | 5.73     | ±9.6                     |
| 10178 | CAH | 5.0 MHz, 16QAM, 1 RB                          | LTE-FDD | 6.52     | ±9.6                     |
| 10179 | CAH | 10.0 MHz, 64QAM, 1 RB                         | LTE-FDD | 6.50     | ±9.6                     |
| 10180 | CAH | 5.0 MHz, 64QAM, 1 RB                          | LTE-FDD | 6.50     | ±9.6                     |
| 10181 | CAF | 15.0 MHz, QPSK, 1 RB                          | LTE-FDD | 5.72     | ±9.6                     |
| 10182 | CAF | 15.0 MHz, 16QAM, 1 RB                         | LTE-FDD | 6.52     | ±9.6                     |
| 10183 | AAE | 15.0 MHz, 64QAM, 1 RB                         | LTE-FDD | 6.50     | ±9.6                     |
| 10184 | CAF | 3.0 MHz, QPSK, 1 RB                           | LTE-FDD | 5.73     | ±9.6                     |
| 10185 | CAF | 3.0 MHz, 16QAM, 1 RB                          | LTE-FDD | 6.51     | ±9.6                     |
| 10186 | AAF | 3.0 MHz, 64QAM, 1 RB                          | LTE-FDD | 6.50     | ±9.6                     |
| 10187 | CAG | 1.4 MHz, QPSK, 1 RB                           | LTE-FDD | 5.73     | ±9.6                     |
| 10188 | CAG | 1.4 MHz, 16QAM, 1 RB                          | LTE-FDD | 6.52     | ±9.6                     |
| 10189 | AAG | 1.4 MHz, 64QAM, 1 RB                          | LTE-FDD | 6.50     | ±9.6                     |
| 10193 | CAE | HT20 Greenfield, MCS0 (6.5 Mbps), 99.4% DC    | WLAN    | 8.09     | ±9.6                     |
| 10194 | CAE | HT20 Greenfield, MCS4 (39.0 Mbps), 99.5% DC   | WLAN    | 8.12     | ±9.6                     |
| 10195 | CAE | HT20 Greenfield, MCS7 (65.0 Mbps), 99.5% DC   | WLAN    | 8.21     | ±9.6                     |
| 10196 | CAE | HT20 Mixed, MCS0 (6.5 Mbps), 99.4% DC         | WLAN    | 8.10     | ±9.6                     |
| 10197 | CAE | HT20 Mixed, MCS4 (39.0 Mbps), 99.5% DC        | WLAN    | 8.13     | ±9.6                     |
| 10198 | CAE | HT20 Mixed, MCS7 (65.0 Mbps), 99.5% DC        | WLAN    | 8.27     | ±9.6                     |
| 10219 | CAE | HT20 Mixed, MCS0 (7.2 Mbps), 99.3% DC         | WLAN    | 8.03     | ±9.6                     |
| 10220 | CAE | HT20 Mixed, MCS4 (43.3 Mbps), 99.4% DC        | WLAN    | 8.13     | ±9.6                     |
| 10221 | CAE | HT20 Mixed, MCS7 (72.2 Mbps), 99.4% DC        | WLAN    | 8.27     | ±9.6                     |
| 10222 | CAE | HT40 Mixed, MCS0 (15.0 Mbps), 99.7% DC        | WLAN    | 8.06     | ±9.6                     |
| 10223 | CAE | HT40 Mixed, MCS4 (80.0 Mbps), 99.7% DC        | WLAN    | 8.48     | ±9.6                     |
| 10224 | CAE | HT40 Mixed, MCS7 (150.0 Mbps), 99.7% DC       | WLAN    | 8.06     | ±9.6                     |
| 10225 | CAC | Rel. 7 HSPA+, 16QAM, 5.0 MHz                  | WCDMA   | 5.97     | ±9.6                     |
| 10226 | CAC | 1.4 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 1 RB    | LTE-TDD | 9.49     | ±9.6                     |
| 10227 | CAC | 1.4 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 1 RB    | LTE-TDD | 10.25    | ±9.6                     |
| 10228 | CAC | 1.4 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB     | LTE-TDD | 9.22     | ±9.6                     |
| 10229 | CAE | 3.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 1 RB    | LTE-TDD | 9.48     | ±9.6                     |

| UID   | Rev | Communication System Name                        | Group    | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|--------------------------------------------------|----------|----------|------------------------|
| 10230 | CAE | 3.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 1 RB       | LTE-TDD  | 10.25    | ±9.6                   |
| 10231 | CAE | 3.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB        | LTE-TDD  | 9.19     | ±9.6                   |
| 10232 | CAH | 5.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 1 RB       | LTE-TDD  | 9.48     | ±9.6                   |
| 10233 | CAH | 5.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 1 RB       | LTE-TDD  | 10.25    | ±9.6                   |
| 10234 | CAH | 5.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB        | LTE-TDD  | 9.21     | ±9.6                   |
| 10235 | CAH | 10.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 1 RB      | LTE-TDD  | 9.48     | ±9.6                   |
| 10236 | CAH | 10.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 1 RB      | LTE-TDD  | 10.25    | ±9.6                   |
| 10237 | CAH | 10.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB       | LTE-TDD  | 9.21     | ±9.6                   |
| 10238 | CAG | 15.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 1 RB      | LTE-TDD  | 9.48     | ±9.6                   |
| 10239 | CAG | 15.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 1 RB      | LTE-TDD  | 10.25    | ±9.6                   |
| 10240 | CAG | 15.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB       | LTE-TDD  | 9.21     | ±9.6                   |
| 10241 | CAC | 1.4 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB     | LTE-TDD  | 9.82     | ±9.6                   |
| 10242 | CAC | 1.4 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 50% RB     | LTE-TDD  | 9.86     | ±9.6                   |
| 10243 | CAC | 1.4 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB      | LTE-TDD  | 9.46     | ±9.6                   |
| 10244 | CAE | 3.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB     | LTE-TDD  | 10.06    | ±9.6                   |
| 10245 | CAE | 3.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 50% RB     | LTE-TDD  | 10.06    | ±9.6                   |
| 10246 | CAE | 3.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB      | LTE-TDD  | 9.30     | ±9.6                   |
| 10247 | CAH | 5.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB     | LTE-TDD  | 9.91     | ±9.6                   |
| 10248 | CAH | 5.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 50% RB     | LTE-TDD  | 10.09    | ±9.6                   |
| 10249 | CAH | 5.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB      | LTE-TDD  | 9.29     | ±9.6                   |
| 10250 | CAH | 10.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB    | LTE-TDD  | 9.81     | ±9.6                   |
| 10251 | CAH | 10.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 50% RB    | LTE-TDD  | 10.17    | ±9.6                   |
| 10252 | CAH | 10.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB     | LTE-TDD  | 9.24     | ±9.6                   |
| 10253 | CAG | 15.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB    | LTE-TDD  | 9.90     | ±9.6                   |
| 10254 | CAG | 15.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 50% RB    | LTE-TDD  | 10.14    | ±9.6                   |
| 10255 | CAG | 15.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB     | LTE-TDD  | 9.20     | ±9.6                   |
| 10256 | CAC | 1.4 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB    | LTE-TDD  | 9.96     | ±9.6                   |
| 10257 | CAC | 1.4 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 100% RB    | LTE-TDD  | 10.08    | ±9.6                   |
| 10258 | CAC | 1.4 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB     | LTE-TDD  | 9.34     | ±9.6                   |
| 10259 | CAE | 3.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB    | LTE-TDD  | 9.98     | ±9.6                   |
| 10260 | CAE | 3.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 100% RB    | LTE-TDD  | 9.97     | ±9.6                   |
| 10261 | CAE | 3.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB     | LTE-TDD  | 9.24     | ±9.6                   |
| 10262 | CAH | 5.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB    | LTE-TDD  | 9.83     | ±9.6                   |
| 10263 | CAH | 5.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 100% RB    | LTE-TDD  | 10.16    | ±9.6                   |
| 10264 | CAH | 5.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB     | LTE-TDD  | 9.23     | ±9.6                   |
| 10265 | CAH | 10.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB   | LTE-TDD  | 9.92     | ±9.6                   |
| 10266 | CAH | 10.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 100% RB   | LTE-TDD  | 10.07    | ±9.6                   |
| 10267 | CAH | 10.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB    | LTE-TDD  | 9.30     | ±9.6                   |
| 10268 | CAG | 15.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB   | LTE-TDD  | 10.06    | ±9.6                   |
| 10269 | CAG | 15.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 100% RB   | LTE-TDD  | 10.13    | ±9.6                   |
| 10270 | CAG | 15.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB    | LTE-TDD  | 9.58     | ±9.6                   |
| 10274 | CAC | Rel. 6 HSUPA Subset 2, beta_d 0, QPSK, 5.0 MHz   | WCDMA    | 4.87     | ±9.6                   |
| 10275 | CAC | Rel. 6 HSUPA Subset 2, beta_d 15, QPSK, 5.0 MHz  | WCDMA    | 3.96     | ±9.6                   |
| 10290 | AAB | RC1, SO55, Full frame rate, 1xRTT                | CDMA2000 | 3.91     | ±9.6                   |
| 10291 | AAB | RC3, SO55, Full frame rate, 1xRTT                | CDMA2000 | 3.46     | ±9.6                   |
| 10292 | AAB | RC3, SO32, Full frame rate, SCH0 disabled, 1xRTT | CDMA2000 | 3.39     | ±9.6                   |
| 10293 | AAB | RC3, SO3, Full frame rate, 1xRTT                 | CDMA2000 | 3.50     | ±9.6                   |
| 10295 | AAB | RC3, SO3, 1/8 frame rate, 1xRTT                  | CDMA2000 | 12.49    | ±9.6                   |
| 10297 | AAE | 20.0 MHz, QPSK, 50% RB                           | LTE-FDD  | 5.81     | ±9.6                   |
| 10298 | AAE | 3.0 MHz, QPSK, 50% RB                            | LTE-FDD  | 5.72     | ±9.6                   |
| 10299 | AAE | 3.0 MHz, 16QAM, 50% RB                           | LTE-FDD  | 6.39     | ±9.6                   |
| 10300 | AAE | 3.0 MHz, 64QAM, 50% RB                           | LTE-FDD  | 6.60     | ±9.6                   |
| 10301 | AAA | PUSC, 29:18, QPSK, 5.0 ms, 18 TRAF SYM           | WiMAX    | 12.03    | ±9.6                   |
| 10302 | AAA | PUSC, 29:18, QPSK, 5.0 ms, 15 TRAF SYM           | WiMAX    | 12.57    | ±9.6                   |
| 10303 | AAA | PUSC, 31:15, 64QAM, 5.0 ms, 15 TRAF SYM          | WiMAX    | 12.52    | ±9.6                   |
| 10304 | AAA | PUSC, 29:18, 64QAM, 5.0 ms, 18 TRAF SYM          | WiMAX    | 11.86    | ±9.6                   |
| 10305 | AAA | PUSC, 31:15, 64QAM, 10.0 ms, 15 TRAF SYM         | WiMAX    | 15.24    | ±9.6                   |
| 10306 | AAA | PUSC, 29:18, 64QAM, 10.0 ms, 18 TRAF SYM         | WiMAX    | 14.67    | ±9.6                   |
| 10307 | AAA | PUSC, 29:18, QPSK, 10.0 ms, 18 TRAF SYM          | WiMAX    | 14.49    | ±9.6                   |
| 10308 | AAA | PUSC, 29:18, 16QAM, 10.0 ms, 18 TRAF SYM         | WiMAX    | 14.46    | ±9.6                   |
| 10309 | AAA | AMC 2x3, 29:18, 16QAM, 10.0 ms, 18 TRAF SYM      | WiMAX    | 14.58    | ±9.6                   |
| 10310 | AAA | AMC 2x3, 29:18, QPSK, 10.0 ms, 18 TRAF SYM       | WiMAX    | 14.57    | ±9.6                   |
| 10311 | AAE | 15.0 MHz, QPSK, 100% RB                          | LTE-FDD  | 6.06     | ±9.6                   |
| 10315 | AAB | DSSS, DBPSK, 1.0 Mbps, 96.0% DC                  | WLAN     | 1.71     | ±9.6                   |
| 10316 | AAB | OFDM, BPSK, 6.0 Mbps, 95.9% DC                   | WLAN     | 8.36     | ±9.6                   |
| 10317 | AAE | OFDM, BPSK, 6.0 Mbps, 95.9% DC                   | WLAN     | 8.36     | ±9.6                   |

| UID   | Rev | Communication System Name                                   | Group    | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|-------------------------------------------------------------|----------|----------|------------------------|
| 10352 | AAA | Pulse (D=10%, T=5 ms)                                       | Generic  | 10.00    | ±9.6                   |
| 10353 | AAA | Pulse (D=20%, T=5 ms)                                       | Generic  | 6.99     | ±9.6                   |
| 10354 | AAA | Pulse (D=40%, T=5 ms)                                       | Generic  | 3.98     | ±9.6                   |
| 10355 | AAA | Pulse (D=60%, T=5 ms)                                       | Generic  | 2.22     | ±9.6                   |
| 10356 | AAA | Pulse (D=80%, T=5 ms)                                       | Generic  | 0.97     | ±9.6                   |
| 10387 | AAA | Random (BW=1 MHz, MOD=QPSK)                                 | Generic  | 5.10     | ±9.6                   |
| 10388 | AAA | Random (BW=10 MHz, MOD=QPSK)                                | Generic  | 5.22     | ±9.6                   |
| 10396 | AAA | Random (BW=100 kHz, MOD=64QAM)                              | Generic  | 6.27     | ±9.6                   |
| 10399 | AAA | Random (BW=40 MHz, MOD=64QAM)                               | Generic  | 6.27     | ±9.6                   |
| 10400 | AAF | VHT20, MCS5 (52.0 Mbps), 99.0% DC                           | WLAN     | 8.37     | ±9.6                   |
| 10401 | AAF | VHT40, MCS5 (108.0 Mbps), 96.7% DC                          | WLAN     | 8.60     | ±9.6                   |
| 10402 | AAF | VHT80, MCS5 (234.0 Mbps), 99.0% DC                          | WLAN     | 8.53     | ±9.6                   |
| 10403 | AAB | Rev. 0, 1xEV-DO                                             | CDMA2000 | 3.76     | ±9.6                   |
| 10404 | AAB | Rev. A, 1xEV-DO                                             | CDMA2000 | 3.77     | ±9.6                   |
| 10406 | AAB | RC3, SQ32, Full frame rate, SCH0 enabled, 1xRTT             | CDMA2000 | 5.22     | ±9.6                   |
| 10410 | AAH | 10.0 MHz, QPSK, UL/DL CFG: 0, SSC: 4, 1 RB                  | LTE-TDD  | 7.82     | ±9.6                   |
| 10414 | AAA | Random (BW=40 MHz, HIGH PAR)                                | Generic  | 8.54     | ±9.6                   |
| 10415 | AAA | DSSS, DBPSK, 1.0 Mbps, 99.9% DC                             | WLAN     | 1.54     | ±9.6                   |
| 10416 | AAA | OFDM, BPSK, 6.0 Mbps, 99.9% DC                              | WLAN     | 8.23     | ±9.6                   |
| 10417 | AAD | OFDM, BPSK, 6.0 Mbps, 99.9% DC                              | WLAN     | 8.23     | ±9.6                   |
| 10418 | AAA | OFDM (LTF), BPSK, 6.0 Mbps, 99.8% DC                        | WLAN     | 8.14     | ±9.6                   |
| 10419 | AAA | OFDM (STF), BPSK, 6.0 Mbps, 99.8% DC                        | WLAN     | 8.19     | ±9.6                   |
| 10422 | AAD | HT20 Greenfield, MCS0 (7.2 Mbps), 99.3% DC                  | WLAN     | 8.32     | ±9.6                   |
| 10423 | AAD | HT20 Greenfield, MCS4 (43.3 Mbps), 99.3% DC                 | WLAN     | 8.47     | ±9.6                   |
| 10424 | AAD | HT20 Greenfield, MCS7 (72.2 Mbps), 99.3% DC                 | WLAN     | 8.40     | ±9.6                   |
| 10425 | AAD | HT40 Greenfield, MCS0 (15.0 Mbps), 99.2% DC                 | WLAN     | 8.41     | ±9.6                   |
| 10426 | AAD | HT40 Greenfield, MCS4 (90.0 Mbps), 99.2% DC                 | WLAN     | 8.45     | ±9.6                   |
| 10427 | AAD | HT40 Greenfield, MCS7 (150.0 Mbps), 99.2% DC                | WLAN     | 8.41     | ±9.6                   |
| 10430 | AAE | 5.0 MHz, 64-QAM, 100% RB                                    | LTE-FDD  | 8.28     | ±9.6                   |
| 10431 | AAE | 10.0 MHz, 64-QAM, 100% RB                                   | LTE-FDD  | 8.38     | ±9.6                   |
| 10432 | AAD | 15.0 MHz, 64-QAM, 100% RB                                   | LTE-FDD  | 8.34     | ±9.6                   |
| 10433 | AAD | 20.0 MHz, 64-QAM, 100% RB                                   | LTE-FDD  | 8.34     | ±9.6                   |
| 10434 | AAB | BS Test Model 1, 64 DPCH, 64QAM, 5.0 MHz (DL)               | WCDMA    | 8.60     | ±9.6                   |
| 10435 | AAG | 20.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 7.82     | ±9.6                   |
| 10447 | AAE | 5.0 MHz, 64-QAM, 100% RB                                    | LTE-FDD  | 7.56     | ±9.6                   |
| 10448 | AAE | 10.0 MHz, 64-QAM, 100% RB                                   | LTE-FDD  | 7.53     | ±9.6                   |
| 10449 | AAD | 15.0 MHz, 64-QAM, 100% RB                                   | LTE-FDD  | 7.51     | ±9.6                   |
| 10450 | AAD | 20.0 MHz, 64-QAM, 100% RB                                   | LTE-FDD  | 7.48     | ±9.6                   |
| 10451 | AAB | BS Test Model 1, 64 DPCH, Clipping 44%, 64QAM, 5.0 MHz (DL) | WCDMA    | 7.59     | ±9.6                   |
| 10456 | AAD | VHT160, MCS5 (58.5 Mbps), 99.0% DC                          | WLAN     | 8.63     | ±9.6                   |
| 10457 | AAB | Rel. 5 DC-HSDPA, QPSK, 10.0 MHz                             | WCDMA    | 8.62     | ±9.6                   |
| 10458 | AAA | Rev. B, 2 carriers, 1xEV-DO                                 | CDMA2000 | 6.55     | ±9.6                   |
| 10459 | AAA | Rev. B, 3 carriers, 1xEV-DO                                 | CDMA2000 | 8.25     | ±9.6                   |
| 10460 | AAB | Rel. 99, AMR, QPSK, 5.0 MHz                                 | WCDMA    | 2.39     | ±9.6                   |
| 10461 | AAC | 1.4 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB                   | LTE-TDD  | 7.82     | ±9.6                   |
| 10462 | AAC | 1.4 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 8.30     | ±9.6                   |
| 10463 | AAC | 1.4 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 8.56     | ±9.6                   |
| 10464 | AAD | 3.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB                   | LTE-TDD  | 7.82     | ±9.6                   |
| 10465 | AAD | 3.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 8.32     | ±9.6                   |
| 10466 | AAD | 3.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 8.57     | ±9.6                   |
| 10467 | AAG | 5.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB                   | LTE-TDD  | 7.82     | ±9.6                   |
| 10468 | AAG | 5.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 8.32     | ±9.6                   |
| 10469 | AAG | 5.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 8.56     | ±9.6                   |
| 10470 | AAG | 10.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 7.82     | ±9.6                   |
| 10471 | AAG | 10.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB                 | LTE-TDD  | 8.32     | ±9.6                   |
| 10472 | AAG | 10.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB                 | LTE-TDD  | 8.57     | ±9.6                   |
| 10473 | AAF | 15.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 7.82     | ±9.6                   |
| 10474 | AAF | 15.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB                 | LTE-TDD  | 8.32     | ±9.6                   |
| 10475 | AAF | 15.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB                 | LTE-TDD  | 8.57     | ±9.6                   |
| 10477 | AAG | 20.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB                 | LTE-TDD  | 8.32     | ±9.6                   |
| 10478 | AAG | 20.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB                 | LTE-TDD  | 8.57     | ±9.6                   |
| 10479 | AAC | 1.4 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB                 | LTE-TDD  | 7.74     | ±9.6                   |
| 10480 | AAC | 1.4 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB                | LTE-TDD  | 8.18     | ±9.6                   |
| 10481 | AAC | 1.4 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 50% RB                | LTE-TDD  | 8.45     | ±9.6                   |
| 10482 | AAD | 3.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB                 | LTE-TDD  | 7.71     | ±9.6                   |
| 10483 | AAD | 3.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB                | LTE-TDD  | 8.39     | ±9.6                   |

| UID   | Rev | Communication System Name                      | Group   | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|------------------------------------------------|---------|----------|------------------------|
| 10484 | AAD | 3.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 50% RB   | LTE-TDD | 8.47     | ±9.6                   |
| 10485 | AAG | 5.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB    | LTE-TDD | 7.58     | ±9.6                   |
| 10486 | AAG | 5.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB   | LTE-TDD | 8.38     | ±9.6                   |
| 10487 | AAG | 5.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 50% RB   | LTE-TDD | 8.60     | ±9.6                   |
| 10488 | AAG | 10.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB   | LTE-TDD | 7.70     | ±9.6                   |
| 10489 | AAG | 10.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB  | LTE-TDD | 8.31     | ±9.6                   |
| 10490 | AAG | 10.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 50% RB  | LTE-TDD | 8.54     | ±9.6                   |
| 10491 | AAF | 15.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB   | LTE-TDD | 7.74     | ±9.6                   |
| 10492 | AAF | 15.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB  | LTE-TDD | 8.41     | ±9.6                   |
| 10493 | AAF | 15.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 50% RB  | LTE-TDD | 8.55     | ±9.6                   |
| 10494 | AAG | 20.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB   | LTE-TDD | 7.74     | ±9.6                   |
| 10495 | AAG | 20.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB  | LTE-TDD | 8.37     | ±9.6                   |
| 10496 | AAG | 20.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 50% RB  | LTE-TDD | 8.54     | ±9.6                   |
| 10497 | AAC | 1.4 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB   | LTE-TDD | 7.67     | ±9.6                   |
| 10498 | AAC | 1.4 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 8.40     | ±9.6                   |
| 10499 | AAC | 1.4 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 8.68     | ±9.6                   |
| 10500 | AAD | 3.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB   | LTE-TDD | 7.67     | ±9.6                   |
| 10501 | AAD | 3.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 8.44     | ±9.6                   |
| 10502 | AAD | 3.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 8.52     | ±9.6                   |
| 10503 | AAG | 5.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB   | LTE-TDD | 7.72     | ±9.6                   |
| 10504 | AAG | 5.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 8.31     | ±9.6                   |
| 10505 | AAG | 5.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 8.54     | ±9.6                   |
| 10506 | AAG | 10.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 7.74     | ±9.6                   |
| 10507 | AAG | 10.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB | LTE-TDD | 8.36     | ±9.6                   |
| 10508 | AAG | 10.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB | LTE-TDD | 8.55     | ±9.6                   |
| 10509 | AAF | 15.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 7.98     | ±9.6                   |
| 10510 | AAF | 15.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB | LTE-TDD | 8.49     | ±9.6                   |
| 10511 | AAF | 15.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB | LTE-TDD | 8.51     | ±9.6                   |
| 10512 | AAG | 20.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 7.74     | ±9.6                   |
| 10513 | AAG | 20.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB | LTE-TDD | 8.42     | ±9.6                   |
| 10514 | AAG | 20.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB | LTE-TDD | 8.45     | ±9.6                   |
| 10515 | AAA | DSSS, DQPSK, 2.0 Mbps, 99.0% DC                | WLAN    | 1.58     | ±9.6                   |
| 10516 | AAA | HR-DSSS, DQPSK, 5.5 Mbps, 99.2% DC             | WLAN    | 1.57     | ±9.6                   |
| 10517 | AAA | HR-DSSS, DQPSK, 11.0 Mbps, 99.0% DC            | WLAN    | 1.58     | ±9.6                   |
| 10518 | AAD | OFDM, BPSK, 9.0 Mbps, 98.9% DC                 | WLAN    | 8.23     | ±9.6                   |
| 10519 | AAD | OFDM, QPSK, 12.0 Mbps, 99.0% DC                | WLAN    | 8.39     | ±9.6                   |
| 10520 | AAD | OFDM, QPSK, 18.0 Mbps, 99.0% DC                | WLAN    | 8.12     | ±9.6                   |
| 10521 | AAD | OFDM, 16QAM, 24.0 Mbps, 99.0% DC               | WLAN    | 7.97     | ±9.6                   |
| 10522 | AAD | OFDM, 16QAM, 36.0 Mbps, 99.0% DC               | WLAN    | 8.45     | ±9.6                   |
| 10523 | AAD | OFDM, 64QAM, 48.0 Mbps, 99.0% DC               | WLAN    | 8.08     | ±9.6                   |
| 10524 | AAD | OFDM, 64QAM, 54.0 Mbps, 99.0% DC               | WLAN    | 8.27     | ±9.6                   |
| 10525 | AAD | VHT20, MCS0 (6.5 Mbps), 98.9% DC               | WLAN    | 8.36     | ±9.6                   |
| 10526 | AAD | VHT20, MCS1 (13.0 Mbps), 99.0% DC              | WLAN    | 8.42     | ±9.6                   |
| 10527 | AAD | VHT20, MCS2 (19.5 Mbps), 99.0% DC              | WLAN    | 8.21     | ±9.6                   |
| 10528 | AAD | VHT20, MCS3 (26.0 Mbps), 99.0% DC              | WLAN    | 8.35     | ±9.6                   |
| 10529 | AAD | VHT20, MCS4 (39.0 Mbps), 99.0% DC              | WLAN    | 8.36     | ±9.6                   |
| 10531 | AAD | VHT20, MCS6 (58.5 Mbps), 99.0% DC              | WLAN    | 8.43     | ±9.6                   |
| 10532 | AAD | VHT20, MCS7 (65.0 Mbps), 99.0% DC              | WLAN    | 8.29     | ±9.6                   |
| 10533 | AAD | VHT20, MCS8 (78.0 Mbps), 99.0% DC              | WLAN    | 8.38     | ±9.6                   |
| 10534 | AAD | VHT40, MCS0 (13.5 Mbps), 98.9% DC              | WLAN    | 8.45     | ±9.6                   |
| 10535 | AAD | VHT40, MCS1 (27.0 Mbps), 98.8% DC              | WLAN    | 8.45     | ±9.6                   |
| 10536 | AAD | VHT40, MCS2 (40.5 Mbps), 98.8% DC              | WLAN    | 8.32     | ±9.6                   |
| 10537 | AAD | VHT40, MCS3 (54.0 Mbps), 98.7% DC              | WLAN    | 8.44     | ±9.6                   |
| 10538 | AAD | VHT40, MCS4 (81.0 Mbps), 98.5% DC              | WLAN    | 8.54     | ±9.6                   |
| 10540 | AAD | VHT40, MCS6 (121.5 Mbps), 98.3% DC             | WLAN    | 8.39     | ±9.6                   |
| 10541 | AAD | VHT40, MCS7 (135.0 Mbps), 98.3% DC             | WLAN    | 8.46     | ±9.6                   |
| 10542 | AAD | VHT40, MCS8 (162.0 Mbps), 98.1% DC             | WLAN    | 8.65     | ±9.6                   |
| 10543 | AAD | VHT40, MCS9 (180.0 Mbps), 98.0% DC             | WLAN    | 8.65     | ±9.6                   |
| 10544 | AAD | VHT80, MCS0 (29.3 Mbps), 99.0% DC              | WLAN    | 8.47     | ±9.6                   |
| 10545 | AAD | VHT80, MCS1 (58.5 Mbps), 99.0% DC              | WLAN    | 8.55     | ±9.6                   |
| 10546 | AAD | VHT80, MCS2 (87.8 Mbps), 99.0% DC              | WLAN    | 8.35     | ±9.6                   |
| 10547 | AAD | VHT80, MCS3 (117.0 Mbps), 99.0% DC             | WLAN    | 8.49     | ±9.6                   |
| 10548 | AAD | VHT80, MCS4 (175.5 Mbps), 99.0% DC             | WLAN    | 8.37     | ±9.6                   |
| 10550 | AAD | VHT80, MCS6 (263.3 Mbps), 99.0% DC             | WLAN    | 8.38     | ±9.6                   |
| 10551 | AAD | VHT80, MCS7 (292.5 Mbps), 99.0% DC             | WLAN    | 8.50     | ±9.6                   |
| 10552 | AAD | VHT80, MCS8 (351.0 Mbps), 99.0% DC             | WLAN    | 8.42     | ±9.6                   |

| UID   | Rev | Communication System Name               | Group | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|-----------------------------------------|-------|----------|------------------------|
| 10553 | AAD | VHT80, MCS8 (390.0 Mbps), 99.0% DC      | WLAN  | 8.45     | ±9.6                   |
| 10554 | AAE | VHT160, MCS0 (58.5 Mbps), 99.0% DC      | WLAN  | 8.48     | ±9.6                   |
| 10555 | AAE | VHT160, MCS1 (117.0 Mbps), 99.0% DC     | WLAN  | 8.47     | ±9.6                   |
| 10556 | AAE | VHT160, MCS2 (175.5 Mbps), 99.0% DC     | WLAN  | 8.50     | ±9.6                   |
| 10557 | AAE | VHT160, MCS3 (234.0 Mbps), 99.0% DC     | WLAN  | 8.52     | ±9.6                   |
| 10558 | AAE | VHT160, MCS4 (351.0 Mbps), 99.0% DC     | WLAN  | 8.61     | ±9.6                   |
| 10560 | AAE | VHT160, MCS6 (528.5 Mbps), 99.0% DC     | WLAN  | 8.73     | ±9.6                   |
| 10561 | AAE | VHT160, MCS7 (585.0 Mbps), 99.0% DC     | WLAN  | 8.58     | ±9.6                   |
| 10562 | AAE | VHT160, MCS8 (702.0 Mbps), 99.0% DC     | WLAN  | 8.69     | ±9.6                   |
| 10563 | AAE | VHT160, MCS9 (780.0 Mbps), 99.0% DC     | WLAN  | 8.77     | ±9.6                   |
| 10564 | AAA | OFDM, BPSK, 9.0 Mbps, 98.9% DC          | WLAN  | 8.25     | ±9.6                   |
| 10565 | AAA | OFDM, QPSK, 12.0 Mbps, 99.0% DC         | WLAN  | 8.45     | ±9.6                   |
| 10566 | AAA | OFDM, QPSK, 18.0 Mbps, 99.0% DC         | WLAN  | 8.13     | ±9.6                   |
| 10567 | AAA | OFDM, 16QAM, 24.0 Mbps, 99.0% DC        | WLAN  | 8.00     | ±9.6                   |
| 10568 | AAA | OFDM, 16QAM, 36.0 Mbps, 99.0% DC        | WLAN  | 8.37     | ±9.6                   |
| 10569 | AAA | OFDM, 64QAM, 48.0 Mbps, 99.0% DC        | WLAN  | 8.10     | ±9.6                   |
| 10570 | AAA | OFDM, 64QAM, 54.0 Mbps, 99.0% DC        | WLAN  | 8.30     | ±9.6                   |
| 10571 | AAA | DSSS, DQPSK, 1.0 Mbps, 90.0% DC         | WLAN  | 1.99     | ±9.6                   |
| 10572 | AAA | DSSS, DQPSK, 2.0 Mbps, 90.0% DC         | WLAN  | 1.99     | ±9.6                   |
| 10573 | AAA | HR-DSSS, DQPSK, 5.5 Mbps, 90.1% DC      | WLAN  | 1.98     | ±9.6                   |
| 10574 | AAA | HR-DSSS, DQPSK, 11.0 Mbps, 90.3% DC     | WLAN  | 1.98     | ±9.6                   |
| 10575 | AAA | OFDM, BPSK, 6.0 Mbps, 89.9% DC          | WLAN  | 8.59     | ±9.6                   |
| 10576 | AAA | OFDM, BPSK, 9.0 Mbps, 89.9% DC          | WLAN  | 8.60     | ±9.6                   |
| 10577 | AAA | OFDM, QPSK, 12.0 Mbps, 90.0% DC         | WLAN  | 8.70     | ±9.6                   |
| 10578 | AAA | OFDM, QPSK, 18.0 Mbps, 90.0% DC         | WLAN  | 8.49     | ±9.6                   |
| 10579 | AAA | OFDM, 16QAM, 24.0 Mbps, 90.0% DC        | WLAN  | 8.36     | ±9.6                   |
| 10580 | AAA | OFDM, 16QAM, 36.0 Mbps, 90.0% DC        | WLAN  | 8.76     | ±9.6                   |
| 10581 | AAA | OFDM, 64QAM, 48.0 Mbps, 90.0% DC        | WLAN  | 8.35     | ±9.6                   |
| 10582 | AAA | OFDM, 64QAM, 54.0 Mbps, 90.0% DC        | WLAN  | 8.67     | ±9.6                   |
| 10583 | AAD | OFDM, BPSK, 6.0 Mbps, 89.9% DC          | WLAN  | 8.59     | ±9.6                   |
| 10584 | AAD | OFDM, BPSK, 9.0 Mbps, 89.9% DC          | WLAN  | 8.60     | ±9.6                   |
| 10585 | AAD | OFDM, QPSK, 12.0 Mbps, 90.0% DC         | WLAN  | 8.70     | ±9.6                   |
| 10586 | AAD | OFDM, QPSK, 18.0 Mbps, 90.0% DC         | WLAN  | 8.49     | ±9.6                   |
| 10587 | AAD | OFDM, 16QAM, 24.0 Mbps, 90.0% DC        | WLAN  | 8.36     | ±9.6                   |
| 10588 | AAD | OFDM, 16QAM, 36.0 Mbps, 90.0% DC        | WLAN  | 8.76     | ±9.6                   |
| 10589 | AAD | OFDM, 64QAM, 48.0 Mbps, 90.0% DC        | WLAN  | 8.35     | ±9.6                   |
| 10590 | AAD | OFDM, 64QAM, 54.0 Mbps, 90.0% DC        | WLAN  | 8.67     | ±9.6                   |
| 10591 | AAD | HT20 Mixed, MCS0 (6.5 Mbps), 89.9% DC   | WLAN  | 8.63     | ±9.6                   |
| 10592 | AAD | HT20 Mixed, MCS1 (13.0 Mbps), 90.0% DC  | WLAN  | 8.79     | ±9.6                   |
| 10593 | AAD | HT20 Mixed, MCS2 (19.5 Mbps), 90.0% DC  | WLAN  | 8.84     | ±9.6                   |
| 10594 | AAD | HT20 Mixed, MCS3 (26.0 Mbps), 90.0% DC  | WLAN  | 8.74     | ±9.6                   |
| 10595 | AAD | HT20 Mixed, MCS4 (39.0 Mbps), 90.0% DC  | WLAN  | 8.74     | ±9.6                   |
| 10596 | AAD | HT20 Mixed, MCS5 (52.0 Mbps), 90.0% DC  | WLAN  | 8.71     | ±9.6                   |
| 10597 | AAD | HT20 Mixed, MCS6 (58.5 Mbps), 90.0% DC  | WLAN  | 8.72     | ±9.6                   |
| 10598 | AAD | HT20 Mixed, MCS7 (65.0 Mbps), 90.0% DC  | WLAN  | 8.50     | ±9.6                   |
| 10599 | AAD | HT40 Mixed, MCS0 (13.5 Mbps), 89.9% DC  | WLAN  | 8.79     | ±9.6                   |
| 10600 | AAD | HT40 Mixed, MCS1 (27.0 Mbps), 89.7% DC  | WLAN  | 8.88     | ±9.6                   |
| 10601 | AAD | HT40 Mixed, MCS2 (40.5 Mbps), 89.6% DC  | WLAN  | 8.82     | ±9.6                   |
| 10602 | AAD | HT40 Mixed, MCS3 (54.0 Mbps), 89.4% DC  | WLAN  | 8.94     | ±9.6                   |
| 10603 | AAD | HT40 Mixed, MCS4 (61.0 Mbps), 89.2% DC  | WLAN  | 9.03     | ±9.6                   |
| 10604 | AAD | HT40 Mixed, MCS5 (108.0 Mbps), 88.9% DC | WLAN  | 8.76     | ±9.6                   |
| 10605 | AAD | HT40 Mixed, MCS6 (121.5 Mbps), 88.8% DC | WLAN  | 8.97     | ±9.6                   |
| 10606 | AAD | HT40 Mixed, MCS7 (135.0 Mbps), 88.7% DC | WLAN  | 8.82     | ±9.6                   |
| 10607 | AAD | VHT20, MCS0 (6.5 Mbps), 89.9% DC        | WLAN  | 8.64     | ±9.6                   |
| 10608 | AAD | VHT20, MCS1 (13.0 Mbps), 90.0% DC       | WLAN  | 8.77     | ±9.6                   |
| 10609 | AAD | VHT20, MCS2 (19.5 Mbps), 90.0% DC       | WLAN  | 8.57     | ±9.6                   |
| 10610 | AAD | VHT20, MCS3 (26.0 Mbps), 90.0% DC       | WLAN  | 8.78     | ±9.6                   |
| 10611 | AAD | VHT20, MCS4 (39.0 Mbps), 90.0% DC       | WLAN  | 8.70     | ±9.6                   |
| 10612 | AAD | VHT20, MCS5 (52.0 Mbps), 90.0% DC       | WLAN  | 8.77     | ±9.6                   |
| 10613 | AAD | VHT20, MCS6 (58.5 Mbps), 90.0% DC       | WLAN  | 8.94     | ±9.6                   |
| 10614 | AAD | VHT20, MCS7 (65.0 Mbps), 90.0% DC       | WLAN  | 8.59     | ±9.6                   |
| 10615 | AAD | VHT20, MCS8 (78.0 Mbps), 90.0% DC       | WLAN  | 8.82     | ±9.6                   |
| 10616 | AAD | VHT40, MCS0 (13.5 Mbps), 89.9% DC       | WLAN  | 8.82     | ±9.6                   |
| 10617 | AAD | VHT40, MCS1 (27.0 Mbps), 89.7% DC       | WLAN  | 8.81     | ±9.6                   |
| 10618 | AAD | VHT40, MCS2 (40.5 Mbps), 89.6% DC       | WLAN  | 8.58     | ±9.6                   |
| 10619 | AAD | VHT40, MCS3 (54.0 Mbps), 89.4% DC       | WLAN  | 8.86     | ±9.6                   |

| UID   | Rev | Communication System Name                  | Group     | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|--------------------------------------------|-----------|----------|------------------------|
| 10620 | AAD | VHT40, MCS4 (81.0 Mbps), 88.2% DC          | WLAN      | 8.87     | ±9.6                   |
| 10621 | AAD | VHT40, MCS5 (108.0 Mbps), 88.9% DC         | WLAN      | 8.77     | ±9.6                   |
| 10622 | AAD | VHT40, MCS6 (121.5 Mbps), 88.8% DC         | WLAN      | 8.68     | ±9.6                   |
| 10623 | AAD | VHT40, MCS7 (135.0 Mbps), 88.6% DC         | WLAN      | 8.82     | ±9.6                   |
| 10624 | AAD | VHT40, MCS8 (162.0 Mbps), 88.4% DC         | WLAN      | 8.96     | ±9.6                   |
| 10625 | AAD | VHT40, MCS9 (180.0 Mbps), 88.2% DC         | WLAN      | 8.96     | ±9.6                   |
| 10626 | AAD | VHT80, MCS0 (29.3 Mbps), 90.0% DC          | WLAN      | 8.83     | ±9.6                   |
| 10627 | AAD | VHT80, MCS1 (59.5 Mbps), 90.0% DC          | WLAN      | 8.88     | ±9.6                   |
| 10628 | AAD | VHT80, MCS2 (87.8 Mbps), 90.0% DC          | WLAN      | 8.71     | ±9.6                   |
| 10629 | AAD | VHT80, MCS3 (117.0 Mbps), 90.0% DC         | WLAN      | 8.85     | ±9.6                   |
| 10630 | AAD | VHT80, MCS4 (175.5 Mbps), 90.0% DC         | WLAN      | 8.72     | ±9.6                   |
| 10631 | AAD | VHT80, MCS5 (234.0 Mbps), 90.0% DC         | WLAN      | 8.81     | ±9.6                   |
| 10632 | AAD | VHT80, MCS6 (263.3 Mbps), 90.0% DC         | WLAN      | 8.74     | ±9.6                   |
| 10633 | AAD | VHT80, MCS7 (292.5 Mbps), 90.0% DC         | WLAN      | 8.83     | ±9.6                   |
| 10634 | AAD | VHT80, MCS8 (351.0 Mbps), 90.0% DC         | WLAN      | 8.80     | ±9.6                   |
| 10635 | AAD | VHT80, MCS9 (390.0 Mbps), 90.0% DC         | WLAN      | 8.81     | ±9.6                   |
| 10636 | AAE | VHT160, MCS0 (58.5 Mbps), 90.0% DC         | WLAN      | 8.83     | ±9.6                   |
| 10637 | AAE | VHT160, MCS1 (117.0 Mbps), 90.0% DC        | WLAN      | 8.79     | ±9.6                   |
| 10638 | AAE | VHT160, MCS2 (175.5 Mbps), 90.0% DC        | WLAN      | 8.86     | ±9.6                   |
| 10639 | AAE | VHT160, MCS3 (234.0 Mbps), 90.0% DC        | WLAN      | 8.85     | ±9.6                   |
| 10640 | AAE | VHT160, MCS4 (351.0 Mbps), 90.0% DC        | WLAN      | 8.98     | ±9.6                   |
| 10641 | AAE | VHT160, MCS5 (468.0 Mbps), 90.0% DC        | WLAN      | 9.06     | ±9.6                   |
| 10642 | AAE | VHT160, MCS6 (526.5 Mbps), 90.0% DC        | WLAN      | 9.06     | ±9.6                   |
| 10643 | AAE | VHT160, MCS7 (585.0 Mbps), 90.0% DC        | WLAN      | 8.89     | ±9.6                   |
| 10644 | AAE | VHT160, MCS8 (702.0 Mbps), 90.0% DC        | WLAN      | 9.05     | ±9.6                   |
| 10645 | AAE | VHT160, MCS9 (780.0 Mbps), 90.0% DC        | WLAN      | 9.11     | ±9.6                   |
| 10646 | AAH | 5.0 MHz, QPSK, UL/DL CFG: 2, SSC: 4, 1 RB  | LTE-TDD   | 11.96    | ±9.6                   |
| 10647 | AAG | 20.0 MHz, QPSK, UL/DL CFG: 2, SSC: 7, 1 RB | LTE-TDD   | 11.96    | ±9.6                   |
| 10648 | AAA | RCB, SO75, 1xAdvanced                      | CDMA2000  | 3.45     | ±9.6                   |
| 10670 | AAA | LE, Test, GFSK                             | Bluetooth | 2.19     | ±9.6                   |
| 10671 | AAC | ET20, MCS0 (8.6 Mbps), 90.0% DC            | WLAN      | 9.09     | ±9.6                   |
| 10672 | AAC | ET20, MCS1 (17.0 Mbps), 90.0% DC           | WLAN      | 8.57     | ±9.6                   |
| 10673 | AAC | ET20, MCS2 (26.0 Mbps), 90.0% DC           | WLAN      | 8.78     | ±9.6                   |
| 10674 | AAC | ET20, MCS3 (34.0 Mbps), 90.0% DC           | WLAN      | 8.74     | ±9.6                   |
| 10675 | AAC | ET20, MCS4 (52.0 Mbps), 90.0% DC           | WLAN      | 8.90     | ±9.6                   |
| 10676 | AAC | ET20, MCS5 (69.0 Mbps), 90.0% DC           | WLAN      | 8.77     | ±9.6                   |
| 10677 | AAC | ET20, MCS6 (77.0 Mbps), 90.0% DC           | WLAN      | 8.73     | ±9.6                   |
| 10678 | AAC | ET20, MCS7 (86.0 Mbps), 90.0% DC           | WLAN      | 8.78     | ±9.6                   |
| 10679 | AAC | ET20, MCS8 (103.0 Mbps), 90.0% DC          | WLAN      | 8.89     | ±9.6                   |
| 10680 | AAC | ET20, MCS9 (115.0 Mbps), 90.0% DC          | WLAN      | 8.80     | ±9.6                   |
| 10681 | AAC | ET20, MCS10 (122.0 Mbps), 90.0% DC         | WLAN      | 8.82     | ±9.6                   |
| 10682 | AAC | ET20, MCS11 (135.0 Mbps), 90.0% DC         | WLAN      | 8.83     | ±9.6                   |
| 10683 | AAC | ET20, MCS0 (8.6 Mbps), 100.0% DC           | WLAN      | 8.42     | ±9.6                   |
| 10684 | AAC | ET20, MCS1 (17.0 Mbps), 100.0% DC          | WLAN      | 8.28     | ±9.6                   |
| 10685 | AAC | ET20, MCS2 (26.0 Mbps), 100.0% DC          | WLAN      | 8.33     | ±9.6                   |
| 10686 | AAC | ET20, MCS3 (34.0 Mbps), 100.0% DC          | WLAN      | 8.28     | ±9.6                   |
| 10687 | AAC | ET20, MCS4 (52.0 Mbps), 100.0% DC          | WLAN      | 8.45     | ±9.6                   |
| 10688 | AAC | ET20, MCS5 (69.0 Mbps), 100.0% DC          | WLAN      | 8.29     | ±9.6                   |
| 10689 | AAC | ET20, MCS6 (77.0 Mbps), 100.0% DC          | WLAN      | 8.55     | ±9.6                   |
| 10690 | AAC | ET20, MCS7 (86.0 Mbps), 100.0% DC          | WLAN      | 8.29     | ±9.6                   |
| 10691 | AAC | ET20, MCS8 (103.0 Mbps), 100.0% DC         | WLAN      | 8.25     | ±9.6                   |
| 10692 | AAC | ET20, MCS9 (115.0 Mbps), 100.0% DC         | WLAN      | 8.29     | ±9.6                   |
| 10693 | AAC | ET20, MCS10 (122.0 Mbps), 100.0% DC        | WLAN      | 8.25     | ±9.6                   |
| 10694 | AAC | ET20, MCS11 (135.0 Mbps), 100.0% DC        | WLAN      | 8.57     | ±9.6                   |
| 10695 | AAC | ET40, MCS0 (17.2 Mbps), 89.8% DC           | WLAN      | 8.78     | ±9.6                   |
| 10696 | AAC | ET40, MCS1 (34.0 Mbps), 89.8% DC           | WLAN      | 8.91     | ±9.6                   |
| 10697 | AAC | ET40, MCS2 (52.0 Mbps), 89.7% DC           | WLAN      | 8.61     | ±9.6                   |
| 10698 | AAC | ET40, MCS3 (69.0 Mbps), 89.7% DC           | WLAN      | 8.89     | ±9.6                   |
| 10699 | AAC | ET40, MCS4 (103.0 Mbps), 89.9% DC          | WLAN      | 8.82     | ±9.6                   |
| 10700 | AAC | ET40, MCS5 (138.0 Mbps), 89.8% DC          | WLAN      | 8.73     | ±9.6                   |
| 10701 | AAC | ET40, MCS6 (155.0 Mbps), 89.8% DC          | WLAN      | 8.86     | ±9.6                   |
| 10702 | AAC | ET40, MCS7 (172.0 Mbps), 89.8% DC          | WLAN      | 8.70     | ±9.6                   |
| 10703 | AAC | ET40, MCS8 (207.0 Mbps), 89.8% DC          | WLAN      | 8.82     | ±9.6                   |
| 10704 | AAC | ET40, MCS9 (229.0 Mbps), 89.8% DC          | WLAN      | 8.56     | ±9.6                   |
| 10705 | AAC | ET40, MCS10 (258.0 Mbps), 89.8% DC         | WLAN      | 8.69     | ±9.6                   |
| 10706 | AAC | ET40, MCS11 (267.0 Mbps), 89.8% DC         | WLAN      | 8.66     | ±9.6                   |

| UID   | Rev | Communication System Name                        | Group         | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|--------------------------------------------------|---------------|----------|------------------------|
| 10707 | AAC | ET40, MCS0 (17.2 Mbps), 99.8% DC                 | WLAN          | 8.32     | ±9.6                   |
| 10708 | AAC | ET40, MCS1 (34.0 Mbps), 99.7% DC                 | WLAN          | 8.55     | ±9.6                   |
| 10709 | AAC | ET40, MCS2 (52.0 Mbps), 99.7% DC                 | WLAN          | 8.33     | ±9.6                   |
| 10710 | AAC | ET40, MCS3 (69.0 Mbps), 99.7% DC                 | WLAN          | 8.29     | ±9.6                   |
| 10711 | AAC | ET40, MCS4 (103.0 Mbps), 99.8% DC                | WLAN          | 8.39     | ±9.6                   |
| 10712 | AAC | ET40, MCS5 (138.0 Mbps), 99.8% DC                | WLAN          | 8.67     | ±9.6                   |
| 10713 | AAC | ET40, MCS6 (155.0 Mbps), 99.8% DC                | WLAN          | 8.33     | ±9.6                   |
| 10714 | AAC | ET40, MCS7 (172.0 Mbps), 99.8% DC                | WLAN          | 8.26     | ±9.6                   |
| 10715 | AAC | ET40, MCS8 (207.0 Mbps), 99.8% DC                | WLAN          | 8.45     | ±9.6                   |
| 10716 | AAC | ET40, MCS9 (229.0 Mbps), 99.8% DC                | WLAN          | 8.30     | ±9.6                   |
| 10717 | AAC | ET40, MCS10 (258.0 Mbps), 99.8% DC               | WLAN          | 8.48     | ±9.6                   |
| 10718 | AAC | ET40, MCS11 (267.0 Mbps), 99.8% DC               | WLAN          | 8.24     | ±9.6                   |
| 10719 | AAC | ET80, MCS0 (36.0 Mbps), 90.0% DC                 | WLAN          | 8.81     | ±9.6                   |
| 10720 | AAC | ET80, MCS1 (72.1 Mbps), 90.0% DC                 | WLAN          | 8.87     | ±9.6                   |
| 10721 | AAC | ET80, MCS2 (108.1 Mbps), 90.0% DC                | WLAN          | 8.76     | ±9.6                   |
| 10722 | AAC | ET80, MCS3 (144.1 Mbps), 90.0% DC                | WLAN          | 8.55     | ±9.6                   |
| 10723 | AAC | ET80, MCS4 (216.2 Mbps), 90.0% DC                | WLAN          | 8.70     | ±9.6                   |
| 10724 | AAC | ET80, MCS5 (288.2 Mbps), 90.0% DC                | WLAN          | 8.90     | ±9.6                   |
| 10725 | AAC | ET80, MCS6 (324.4 Mbps), 90.0% DC                | WLAN          | 8.74     | ±9.6                   |
| 10726 | AAC | ET80, MCS7 (360.3 Mbps), 90.0% DC                | WLAN          | 8.72     | ±9.6                   |
| 10727 | AAC | ET80, MCS8 (432.4 Mbps), 90.0% DC                | WLAN          | 8.66     | ±9.6                   |
| 10728 | AAC | ET80, MCS9 (480.4 Mbps), 90.0% DC                | WLAN          | 8.65     | ±9.6                   |
| 10729 | AAC | ET80, MCS10 (540.4 Mbps), 90.0% DC               | WLAN          | 8.64     | ±9.6                   |
| 10730 | AAC | ET80, MCS11 (72.0 Mbps), 90.0% DC                | WLAN          | 8.67     | ±9.6                   |
| 10731 | AAC | ET80, MCS0 (36.0 Mbps), 100.0% DC                | WLAN          | 8.42     | ±9.6                   |
| 10732 | AAC | ET80, MCS1 (72.1 Mbps), 100.0% DC                | WLAN          | 8.46     | ±9.6                   |
| 10733 | AAC | ET80, MCS2 (108.1 Mbps), 100.0% DC               | WLAN          | 8.40     | ±9.6                   |
| 10734 | AAC | ET80, MCS3 (144.1 Mbps), 100.0% DC               | WLAN          | 8.25     | ±9.6                   |
| 10735 | AAC | ET80, MCS4 (216.2 Mbps), 100.0% DC               | WLAN          | 8.33     | ±9.6                   |
| 10736 | AAC | ET80, MCS5 (288.2 Mbps), 100.0% DC               | WLAN          | 8.27     | ±9.6                   |
| 10737 | AAC | ET80, MCS6 (324.4 Mbps), 100.0% DC               | WLAN          | 8.36     | ±9.6                   |
| 10738 | AAC | ET80, MCS7 (360.3 Mbps), 100.0% DC               | WLAN          | 8.42     | ±9.6                   |
| 10739 | AAC | ET80, MCS8 (432.4 Mbps), 100.0% DC               | WLAN          | 8.29     | ±9.6                   |
| 10740 | AAC | ET80, MCS9 (480.4 Mbps), 100.0% DC               | WLAN          | 8.48     | ±9.6                   |
| 10741 | AAC | ET80, MCS10 (540.4 Mbps), 100.0% DC              | WLAN          | 8.40     | ±9.6                   |
| 10742 | AAC | ET80, MCS11 (600.5 Mbps), 100.0% DC              | WLAN          | 8.43     | ±9.6                   |
| 10743 | AAC | ET160, MCS0 (72.0 Mbps), 88.2% DC                | WLAN          | 8.94     | ±9.6                   |
| 10744 | AAC | ET160, MCS1 (144.0 Mbps), 87.1% DC               | WLAN          | 9.15     | ±9.6                   |
| 10745 | AAC | ET160, MCS2 (216.0 Mbps), 87.4% DC               | WLAN          | 8.93     | ±9.6                   |
| 10746 | AAC | ET160, MCS3 (288.0 Mbps), 87.1% DC               | WLAN          | 9.11     | ±9.6                   |
| 10747 | AAC | ET160, MCS4 (432.0 Mbps), 87.4% DC               | WLAN          | 9.04     | ±9.6                   |
| 10748 | AAC | ET160, MCS5 (576.0 Mbps), 88.8% DC               | WLAN          | 8.93     | ±9.6                   |
| 10749 | AAC | ET160, MCS6 (648.0 Mbps), 86.7% DC               | WLAN          | 8.90     | ±9.6                   |
| 10750 | AAC | ET160, MCS7 (721.0 Mbps), 86.7% DC               | WLAN          | 8.79     | ±9.6                   |
| 10751 | AAC | ET160, MCS8 (865.0 Mbps), 86.3% DC               | WLAN          | 8.82     | ±9.6                   |
| 10752 | AAC | ET160, MCS9 (961.0 Mbps), 86.3% DC               | WLAN          | 8.81     | ±9.6                   |
| 10753 | AAC | ET160, MCS10 (1081.0 Mbps), 86.7% DC             | WLAN          | 9.00     | ±9.6                   |
| 10754 | AAC | ET160, MCS11 (1201.0 Mbps), 86.7% DC             | WLAN          | 8.94     | ±9.6                   |
| 10755 | AAC | ET160, MCS0 (72.0 Mbps), 98.0% DC                | WLAN          | 8.64     | ±9.6                   |
| 10756 | AAC | ET160, MCS1 (144.0 Mbps), 96.8% DC               | WLAN          | 8.77     | ±9.6                   |
| 10757 | AAC | ET160, MCS2 (216.0 Mbps), 97.1% DC               | WLAN          | 8.77     | ±9.6                   |
| 10758 | AAC | ET160, MCS3 (288.0 Mbps), 96.8% DC               | WLAN          | 8.69     | ±9.6                   |
| 10759 | AAC | ET160, MCS4 (432.0 Mbps), 97.1% DC               | WLAN          | 8.58     | ±9.6                   |
| 10760 | AAC | ET160, MCS5 (576.0 Mbps), 96.5% DC               | WLAN          | 8.49     | ±9.6                   |
| 10761 | AAC | ET160, MCS6 (649.0 Mbps), 96.3% DC               | WLAN          | 8.58     | ±9.6                   |
| 10762 | AAC | ET160, MCS7 (721.0 Mbps), 96.3% DC               | WLAN          | 8.49     | ±9.6                   |
| 10763 | AAC | ET160, MCS8 (865.0 Mbps), 95.9% DC               | WLAN          | 8.53     | ±9.6                   |
| 10764 | AAC | ET160, MCS9 (961.0 Mbps), 95.9% DC               | WLAN          | 8.54     | ±9.6                   |
| 10765 | AAC | ET160, MCS10 (1081.0 Mbps), 96.3% DC             | WLAN          | 8.54     | ±9.6                   |
| 10766 | AAC | ET160, MCS11 (1201.0 Mbps), 96.3% DC             | WLAN          | 8.51     | ±9.6                   |
| 10767 | AAG | CP-OFDM, 5.0 MHz, QPSK, 15 kHz, 99.9% DC, 1 RB   | 5G NR FR1 TOD | 7.99     | ±9.6                   |
| 10768 | AAE | CP-OFDM, 10.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB | 5G NR FR1 TOD | 8.01     | ±9.6                   |
| 10769 | AAD | CP-OFDM, 15.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB | 5G NR FR1 TOD | 8.01     | ±9.6                   |
| 10770 | AAE | CP-OFDM, 20.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB | 5G NR FR1 TOD | 8.02     | ±9.6                   |
| 10771 | AAD | CP-OFDM, 25.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB | 5G NR FR1 TOD | 8.02     | ±9.6                   |
| 10772 | AAE | CP-OFDM, 30.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB | 5G NR FR1 TOD | 8.23     | ±9.6                   |

| UID   | Rev | Communication System Name                            | Group         | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|------------------------------------------------------|---------------|----------|------------------------|
| 10773 | AAF | CP-OFDM, 40.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 8.03     | ±9.6                   |
| 10774 | AAE | CP-OFDM, 50.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 8.02     | ±9.6                   |
| 10775 | AAF | CP-OFDM, 5.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB    | 5G NR FR1 TDD | 8.31     | ±9.6                   |
| 10776 | AAE | CP-OFDM, 10.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.30     | ±9.6                   |
| 10777 | AAC | CP-OFDM, 15.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.30     | ±9.6                   |
| 10778 | AAE | CP-OFDM, 20.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10779 | AAC | CP-OFDM, 25.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.42     | ±9.6                   |
| 10780 | AAE | CP-OFDM, 30.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.38     | ±9.6                   |
| 10781 | AAF | CP-OFDM, 40.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.38     | ±9.6                   |
| 10782 | AAE | CP-OFDM, 50.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.43     | ±9.6                   |
| 10783 | AAG | CP-OFDM, 5.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB   | 5G NR FR1 TDD | 8.31     | ±9.6                   |
| 10784 | AAE | CP-OFDM, 10.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.29     | ±9.6                   |
| 10785 | AAD | CP-OFDM, 15.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.40     | ±9.6                   |
| 10786 | AAE | CP-OFDM, 20.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.35     | ±9.6                   |
| 10787 | AAD | CP-OFDM, 25.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.44     | ±9.6                   |
| 10788 | AAE | CP-OFDM, 30.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.39     | ±9.6                   |
| 10789 | AAF | CP-OFDM, 40.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.37     | ±9.6                   |
| 10790 | AAE | CP-OFDM, 50.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.39     | ±9.6                   |
| 10791 | AAG | CP-OFDM, 5.0 MHz, QPSK, 30 kHz, 99.9% DC, 1 RB       | 5G NR FR1 TDD | 7.83     | ±9.6                   |
| 10792 | AAE | CP-OFDM, 10.0 MHz, QPSK, 30 kHz, 99.9% DC, 1 RB      | 5G NR FR1 TDD | 7.92     | ±9.6                   |
| 10793 | AAD | CP-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.95     | ±9.6                   |
| 10794 | AAE | CP-OFDM, 20.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.82     | ±9.6                   |
| 10795 | AAD | CP-OFDM, 25.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.84     | ±9.6                   |
| 10796 | AAE | CP-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.82     | ±9.6                   |
| 10797 | AAF | CP-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 8.01     | ±9.6                   |
| 10798 | AAE | CP-OFDM, 50.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.89     | ±9.6                   |
| 10799 | AAF | CP-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.93     | ±9.6                   |
| 10801 | AAF | CP-OFDM, 80.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.89     | ±9.6                   |
| 10802 | AAE | CP-OFDM, 90.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.87     | ±9.6                   |
| 10803 | AAF | CP-OFDM, 100.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB    | 5G NR FR1 TDD | 7.93     | ±9.6                   |
| 10805 | AAE | CP-OFDM, 10.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10806 | AAD | CP-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.37     | ±9.6                   |
| 10809 | AAE | CP-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10810 | AAF | CP-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10812 | AAF | CP-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.35     | ±9.6                   |
| 10817 | AAG | CP-OFDM, 5.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB   | 5G NR FR1 TDD | 8.35     | ±9.6                   |
| 10818 | AAE | CP-OFDM, 10.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10819 | AAD | CP-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.33     | ±9.6                   |
| 10820 | AAE | CP-OFDM, 20.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.30     | ±9.6                   |
| 10821 | AAD | CP-OFDM, 25.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.41     | ±9.6                   |
| 10822 | AAE | CP-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.41     | ±9.6                   |
| 10823 | AAF | CP-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.36     | ±9.6                   |
| 10824 | AAE | CP-OFDM, 50.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.39     | ±9.6                   |
| 10825 | AAF | CP-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.41     | ±9.6                   |
| 10827 | AAF | CP-OFDM, 80.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.42     | ±9.6                   |
| 10828 | AAE | CP-OFDM, 90.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.43     | ±9.6                   |
| 10829 | AAF | CP-OFDM, 100.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB | 5G NR FR1 TDD | 8.40     | ±9.6                   |
| 10830 | AAE | CP-OFDM, 10.0 MHz, QPSK, 60 kHz, 99.9% DC, 1 RB      | 5G NR FR1 TDD | 7.63     | ±9.6                   |
| 10831 | AAD | CP-OFDM, 15.0 MHz, QPSK, 60 kHz, 99.9% DC, 1 RB      | 5G NR FR1 TDD | 7.73     | ±9.6                   |
| 10832 | AAE | CP-OFDM, 20.0 MHz, QPSK, 60 kHz, 99.9% DC, 1 RB      | 5G NR FR1 TDD | 7.74     | ±9.6                   |
| 10833 | AAD | CP-OFDM, 25.0 MHz, QPSK, 60 kHz, 99.9% DC, 1 RB      | 5G NR FR1 TDD | 7.70     | ±9.6                   |
| 10834 | AAE | CP-OFDM, 30.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.75     | ±9.6                   |
| 10835 | AAF | CP-OFDM, 40.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.70     | ±9.6                   |
| 10836 | AAE | CP-OFDM, 50.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.66     | ±9.6                   |
| 10837 | AAF | CP-OFDM, 60.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.68     | ±9.6                   |
| 10839 | AAF | CP-OFDM, 80.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.70     | ±9.6                   |
| 10840 | AAE | CP-OFDM, 90.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.67     | ±9.6                   |
| 10841 | AAF | CP-OFDM, 100.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB    | 5G NR FR1 TDD | 7.71     | ±9.6                   |
| 10843 | AAD | CP-OFDM, 15.0 MHz, QPSK, 60 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.49     | ±9.6                   |
| 10844 | AAE | CP-OFDM, 20.0 MHz, QPSK, 60 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10846 | AAE | CP-OFDM, 30.0 MHz, QPSK, 60 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.41     | ±9.6                   |
| 10854 | AAE | CP-OFDM, 10.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10855 | AAD | CP-OFDM, 15.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.36     | ±9.6                   |
| 10856 | AAE | CP-OFDM, 20.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.37     | ±9.6                   |
| 10857 | AAD | CP-OFDM, 25.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.35     | ±9.6                   |
| 10858 | AAE | CP-OFDM, 30.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.36     | ±9.6                   |

| UID   | Rev | Communication System Name                                 | Group         | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|-----------------------------------------------------------|---------------|----------|------------------------|
| 10859 | AAF | CP-OFDM, 40.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB       | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10860 | AAE | CP-OFDM, 50.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB       | 5G NR FR1 TDD | 8.41     | ±9.6                   |
| 10861 | AAF | CP-OFDM, 60.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB       | 5G NR FR1 TDD | 8.40     | ±9.6                   |
| 10863 | AAF | CP-OFDM, 80.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB       | 5G NR FR1 TDD | 8.41     | ±9.6                   |
| 10864 | AAE | CP-OFDM, 90.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB       | 5G NR FR1 TDD | 8.37     | ±9.6                   |
| 10865 | AAF | CP-OFDM, 100.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB      | 5G NR FR1 TDD | 8.41     | ±9.6                   |
| 10866 | AAF | DFT-s-OFDM, 100.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB      | 5G NR FR1 TDD | 5.88     | ±9.6                   |
| 10868 | AAF | DFT-s-OFDM, 100.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB   | 5G NR FR1 TDD | 5.89     | ±9.6                   |
| 10869 | AAE | DFT-s-OFDM, 100.0 MHz, QPSK, 120 kHz, 100.0% DC, 1 RB     | 5G NR FR2 TDD | 5.75     | ±9.6                   |
| 10870 | AAE | DFT-s-OFDM, 100.0 MHz, QPSK, 120 kHz, 100.0% DC, 100% RB  | 5G NR FR2 TDD | 5.86     | ±9.6                   |
| 10871 | AAE | DFT-s-OFDM, 100.0 MHz, 16QAM, 120 kHz, 100.0% DC, 1 RB    | 5G NR FR2 TDD | 5.75     | ±9.6                   |
| 10872 | AAE | DFT-s-OFDM, 100.0 MHz, 16QAM, 120 kHz, 100.0% DC, 100% RB | 5G NR FR2 TDD | 6.52     | ±9.6                   |
| 10873 | AAE | DFT-s-OFDM, 100.0 MHz, 64QAM, 120 kHz, 100.0% DC, 1 RB    | 5G NR FR2 TDD | 6.61     | ±9.6                   |
| 10874 | AAE | DFT-s-OFDM, 100.0 MHz, 64QAM, 120 kHz, 100.0% DC, 100% RB | 5G NR FR2 TDD | 6.65     | ±9.6                   |
| 10875 | AAE | CP-OFDM, 100.0 MHz, QPSK, 120 kHz, 100.0% DC, 1 RB        | 5G NR FR2 TDD | 7.78     | ±9.6                   |
| 10876 | AAE | CP-OFDM, 100.0 MHz, QPSK, 120 kHz, 100.0% DC, 100% RB     | 5G NR FR2 TDD | 8.39     | ±9.6                   |
| 10877 | AAE | CP-OFDM, 100.0 MHz, 16QAM, 120 kHz, 100.0% DC, 1 RB       | 5G NR FR2 TDD | 7.95     | ±9.6                   |
| 10878 | AAE | CP-OFDM, 100.0 MHz, 16QAM, 120 kHz, 100.0% DC, 100% RB    | 5G NR FR2 TDD | 8.41     | ±9.6                   |
| 10879 | AAE | CP-OFDM, 100.0 MHz, 64QAM, 120 kHz, 100.0% DC, 1 RB       | 5G NR FR2 TDD | 8.12     | ±9.6                   |
| 10880 | AAE | CP-OFDM, 100.0 MHz, 64QAM, 120 kHz, 100.0% DC, 100% RB    | 5G NR FR2 TDD | 8.38     | ±9.6                   |
| 10881 | AAE | DFT-s-OFDM, 50.0 MHz, QPSK, 120 kHz, 100.0% DC, 1 RB      | 5G NR FR2 TDD | 5.75     | ±9.6                   |
| 10882 | AAE | DFT-s-OFDM, 50.0 MHz, QPSK, 120 kHz, 100.0% DC, 100% RB   | 5G NR FR2 TDD | 5.96     | ±9.6                   |
| 10883 | AAE | DFT-s-OFDM, 50.0 MHz, 16QAM, 120 kHz, 100.0% DC, 1 RB     | 5G NR FR2 TDD | 6.57     | ±9.6                   |
| 10884 | AAE | DFT-s-OFDM, 50.0 MHz, 16QAM, 120 kHz, 100.0% DC, 100% RB  | 5G NR FR2 TDD | 6.53     | ±9.6                   |
| 10885 | AAE | DFT-s-OFDM, 50.0 MHz, 64QAM, 120 kHz, 100.0% DC, 1 RB     | 5G NR FR2 TDD | 6.61     | ±9.6                   |
| 10886 | AAE | DFT-s-OFDM, 50.0 MHz, 64QAM, 120 kHz, 100.0% DC, 100% RB  | 5G NR FR2 TDD | 6.65     | ±9.6                   |
| 10887 | AAE | CP-OFDM, 50.0 MHz, QPSK, 120 kHz, 99.9% DC, 1 RB          | 5G NR FR2 TDD | 7.78     | ±9.6                   |
| 10888 | AAE | CP-OFDM, 50.0 MHz, QPSK, 120 kHz, 100.0% DC, 100% RB      | 5G NR FR2 TDD | 8.35     | ±9.6                   |
| 10889 | AAE | CP-OFDM, 50.0 MHz, 16QAM, 120 kHz, 100.0% DC, 1 RB        | 5G NR FR2 TDD | 8.02     | ±9.6                   |
| 10890 | AAE | CP-OFDM, 50.0 MHz, 16QAM, 120 kHz, 100.0% DC, 100% RB     | 5G NR FR2 TDD | 8.40     | ±9.6                   |
| 10891 | AAE | CP-OFDM, 50.0 MHz, 64QAM, 120 kHz, 100.0% DC, 1 RB        | 5G NR FR2 TDD | 8.13     | ±9.6                   |
| 10892 | AAE | CP-OFDM, 50.0 MHz, 64QAM, 120 kHz, 100.0% DC, 100% RB     | 5G NR FR2 TDD | 8.41     | ±9.6                   |
| 10897 | AAE | DFT-s-OFDM, 5.0 MHz, QPSK, 30 kHz, 99.9% DC, 1 RB         | 5G NR FR1 TDD | 5.66     | ±9.6                   |
| 10898 | AAC | DFT-s-OFDM, 10.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.67     | ±9.6                   |
| 10899 | AAB | DFT-s-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.67     | ±9.6                   |
| 10900 | AAC | DFT-s-OFDM, 20.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.68     | ±9.6                   |
| 10901 | AAB | DFT-s-OFDM, 25.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.68     | ±9.6                   |
| 10902 | AAC | DFT-s-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.68     | ±9.6                   |
| 10903 | AAD | DFT-s-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.68     | ±9.6                   |
| 10904 | AAC | DFT-s-OFDM, 50.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.68     | ±9.6                   |
| 10905 | AAD | DFT-s-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.68     | ±9.6                   |
| 10906 | AAD | DFT-s-OFDM, 80.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.68     | ±9.6                   |
| 10907 | AAE | DFT-s-OFDM, 5.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB      | 5G NR FR1 TDD | 5.79     | ±9.6                   |
| 10908 | AAC | DFT-s-OFDM, 10.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.93     | ±9.6                   |
| 10909 | AAB | DFT-s-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.96     | ±9.6                   |
| 10910 | AAC | DFT-s-OFDM, 20.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.93     | ±9.6                   |
| 10911 | AAB | DFT-s-OFDM, 25.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.93     | ±9.6                   |
| 10912 | AAC | DFT-s-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.84     | ±9.6                   |
| 10913 | AAD | DFT-s-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.84     | ±9.6                   |
| 10914 | AAC | DFT-s-OFDM, 50.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.85     | ±9.6                   |
| 10915 | AAD | DFT-s-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.83     | ±9.6                   |
| 10916 | AAD | DFT-s-OFDM, 80.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.87     | ±9.6                   |
| 10917 | AAD | DFT-s-OFDM, 100.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB    | 5G NR FR1 TDD | 5.94     | ±9.6                   |
| 10918 | AAE | DFT-s-OFDM, 5.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB     | 5G NR FR1 TDD | 5.86     | ±9.6                   |
| 10919 | AAC | DFT-s-OFDM, 10.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.86     | ±9.6                   |
| 10920 | AAB | DFT-s-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.87     | ±9.6                   |
| 10921 | AAC | DFT-s-OFDM, 20.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.84     | ±9.6                   |
| 10922 | AAB | DFT-s-OFDM, 25.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.82     | ±9.6                   |
| 10923 | AAC | DFT-s-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.84     | ±9.6                   |
| 10924 | AAD | DFT-s-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.84     | ±9.6                   |
| 10925 | AAC | DFT-s-OFDM, 50.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.95     | ±9.6                   |
| 10926 | AAD | DFT-s-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.84     | ±9.6                   |
| 10927 | AAD | DFT-s-OFDM, 80.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.94     | ±9.6                   |
| 10928 | AAD | DFT-s-OFDM, 5.0 MHz, QPSK, 15 kHz, 1 RB                   | 5G NR FR1 FDD | 5.52     | ±9.6                   |
| 10929 | AAD | DFT-s-OFDM, 10.0 MHz, QPSK, 15 kHz, 1 RB                  | 5G NR FR1 FDD | 5.52     | ±9.6                   |
| 10930 | AAC | DFT-s-OFDM, 15.0 MHz, QPSK, 15 kHz, 1 RB                  | 5G NR FR1 FDD | 5.52     | ±9.6                   |

| UID   | Rev | Communication System Name                   | Group         | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|---------------------------------------------|---------------|----------|------------------------|
| 10931 | AAC | DFT-s-OFDM, 20.0 MHz, QPSK, 15 kHz, 1 RB    | 5G NR FR1 FDD | 5.51     | ±9.6                   |
| 10932 | AAC | DFT-s-OFDM, 25.0 MHz, QPSK, 15 kHz, 1 RB    | 5G NR FR1 FDD | 5.51     | ±9.6                   |
| 10933 | AAC | DFT-s-OFDM, 30.0 MHz, QPSK, 15 kHz, 1 RB    | 5G NR FR1 FDD | 5.51     | ±9.6                   |
| 10934 | AAC | DFT-s-OFDM, 40.0 MHz, QPSK, 15 kHz, 1 RB    | 5G NR FR1 FDD | 5.51     | ±9.6                   |
| 10935 | AAD | DFT-s-OFDM, 50.0 MHz, QPSK, 15 kHz, 1 RB    | 5G NR FR1 FDD | 5.51     | ±9.6                   |
| 10936 | AAD | DFT-s-OFDM, 5.0 MHz, QPSK, 15 kHz, 50% RB   | 5G NR FR1 FDD | 5.90     | ±9.6                   |
| 10937 | AAD | DFT-s-OFDM, 10.0 MHz, QPSK, 15 kHz, 50% RB  | 5G NR FR1 FDD | 5.77     | ±9.6                   |
| 10938 | AAC | DFT-s-OFDM, 15.0 MHz, QPSK, 15 kHz, 50% RB  | 5G NR FR1 FDD | 5.90     | ±9.6                   |
| 10939 | AAC | DFT-s-OFDM, 20.0 MHz, QPSK, 15 kHz, 50% RB  | 5G NR FR1 FDD | 5.82     | ±9.6                   |
| 10940 | AAC | DFT-s-OFDM, 25.0 MHz, QPSK, 15 kHz, 50% RB  | 5G NR FR1 FDD | 5.89     | ±9.6                   |
| 10941 | AAC | DFT-s-OFDM, 30.0 MHz, QPSK, 15 kHz, 50% RB  | 5G NR FR1 FDD | 5.83     | ±9.6                   |
| 10942 | AAC | DFT-s-OFDM, 40.0 MHz, QPSK, 15 kHz, 50% RB  | 5G NR FR1 FDD | 5.85     | ±9.6                   |
| 10943 | AAD | DFT-s-OFDM, 50.0 MHz, QPSK, 15 kHz, 50% RB  | 5G NR FR1 FDD | 5.95     | ±9.6                   |
| 10944 | AAD | DFT-s-OFDM, 5.0 MHz, QPSK, 15 kHz, 100% RB  | 5G NR FR1 FDD | 5.81     | ±9.6                   |
| 10945 | AAD | DFT-s-OFDM, 10.0 MHz, QPSK, 15 kHz, 100% RB | 5G NR FR1 FDD | 5.85     | ±9.6                   |
| 10946 | AAC | DFT-s-OFDM, 15.0 MHz, QPSK, 15 kHz, 100% RB | 5G NR FR1 FDD | 5.83     | ±9.6                   |
| 10947 | AAC | DFT-s-OFDM, 20.0 MHz, QPSK, 15 kHz, 100% RB | 5G NR FR1 FDD | 5.87     | ±9.6                   |
| 10948 | AAC | DFT-s-OFDM, 25.0 MHz, QPSK, 15 kHz, 100% RB | 5G NR FR1 FDD | 5.94     | ±9.6                   |
| 10949 | AAC | DFT-s-OFDM, 30.0 MHz, QPSK, 15 kHz, 100% RB | 5G NR FR1 FDD | 5.87     | ±9.6                   |
| 10950 | AAC | DFT-s-OFDM, 40.0 MHz, QPSK, 15 kHz, 100% RB | 5G NR FR1 FDD | 5.94     | ±9.6                   |
| 10951 | AAD | DFT-s-OFDM, 50.0 MHz, QPSK, 15 kHz, 100% RB | 5G NR FR1 FDD | 5.92     | ±9.6                   |
| 10978 | AAA | BDR, 1.0 MHz, 76.7% DC                      | ULLA          | 1.16     | ±9.6                   |
| 10979 | AAA | HDR4, 2.0 MHz, 25.1% DC                     | ULLA          | 8.58     | ±9.6                   |
| 10980 | AAA | HDR8, 4.0 MHz, 16.5% DC                     | ULLA          | 10.32    | ±9.6                   |
| 10981 | AAA | HDRp4, 2.0 MHz, 89.0% DC                    | ULLA          | 3.19     | ±9.6                   |
| 10982 | AAA | HDRp8, 4.0 MHz, 90.3% DC                    | ULLA          | 3.43     | ±9.6                   |
| 11013 | AAB | EHT320, MCS1 (272.0 Mbps), 100.0% DC        | WLAN          | 8.47     | ±9.6                   |
| 11014 | AAB | EHT320, MCS2 (408.0 Mbps), 100.0% DC        | WLAN          | 8.45     | ±9.6                   |
| 11015 | AAB | EHT320, MCS3 (544.0 Mbps), 100.0% DC        | WLAN          | 8.44     | ±9.6                   |
| 11016 | AAB | EHT320, MCS4 (817.0 Mbps), 100.0% DC        | WLAN          | 8.44     | ±9.6                   |
| 11017 | AAB | EHT320, MCS5 (1089.0 Mbps), 100.0% DC       | WLAN          | 8.41     | ±9.6                   |
| 11018 | AAB | EHT320, MCS6 (1225.0 Mbps), 100.0% DC       | WLAN          | 8.40     | ±9.6                   |
| 11019 | AAB | EHT320, MCS7 (1361.0 Mbps), 100.0% DC       | WLAN          | 8.29     | ±9.6                   |
| 11020 | AAB | EHT320, MCS8 (1633.0 Mbps), 100.0% DC       | WLAN          | 8.27     | ±9.6                   |
| 11021 | AAB | EHT320, MCS9 (1815.0 Mbps), 100.0% DC       | WLAN          | 8.46     | ±9.6                   |
| 11022 | AAB | EHT320, MCS10 (2042.0 Mbps), 100.0% DC      | WLAN          | 8.36     | ±9.6                   |
| 11023 | AAB | EHT320, MCS11 (2269.0 Mbps), 100.0% DC      | WLAN          | 8.09     | ±9.6                   |
| 11024 | AAB | EHT320, MCS12 (2450.0 Mbps), 100.0% DC      | WLAN          | 8.42     | ±9.6                   |
| 11025 | AAB | EHT320, MCS13 (2722.0 Mbps), 100.0% DC      | WLAN          | 8.37     | ±9.6                   |
| 11026 | AAB | EHT320, MCS0 (136.0 Mbps), 100.0% DC        | WLAN          | 8.39     | ±9.6                   |

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.