TEST REPORT

Part 15 Subpart C 15.247

Equipment under test	Prota S
Model name	PRT-SAR1A-01PS
FCC ID	2AJO9PRT-SAR1A-01PS
Applicant	Naran Inc
Manufacturer	Platel Co., Ltd
Date of test(s)	2016.09.19 ~ 2016.10.18
Date of issue	2016.10.19

Issued to

Naran Inc

4th Floor, Munbal-dong, 57-9, Hoedong-gil Gyeonggi-do
Paju-si, South Korea
Tel: +82-70-4915-3140/ Fax: +82-70-8837-1191

Issued by

KES Co., Ltd.

C-3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si,
Gyeonggi-do, Korea
473-29, Gayeo-ro, Yeoju-si, Gyeonggi-do, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450

Test and report completed by :	**Report approval by :**
Kwang-yeol Choo Test engineer	Jeff Do Technical manager

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Revision history

Revision	Date of issue	Test report No.	Description
-	2016.10.06	KES-RF-16T0085	Initial
1	2016.10.19	KES-RF-16T0085-R1	Retest radiated emissions & AC conducted emissions

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

1. General information 4
1.1. EUT description 4
1.2. Test configuration 5
1.3. Frequency/channel operations 5
1.4. Accessory information 5
2. Summary of tests 6
3. Test results 7
3.1. Radiated restricted band and emissions 7
3.2. Conducted band edge and out of band emissions 27
3.3. 20 dB bandwidth 31
3.4. Output power 34
3.5. Carrier frequency separation 38
3.6. Number of hopping frequency 40
3.7. Time of occupancy 42
3.8. AC conducted emissions 46
Appendix A. Measurement equipment 48
Appendix B. Test setup photo 49

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

1. General information

Applicant:	Naran Inc
Applicant address:	4th Floor, Munbal-dong, 57-9, Hoedong-gil Gyeonggi-do Paju-si, South Korea
Test site:	KES Co., Ltd.
Test site address:	C-3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, Korea 473-29, Gayeo-ro, Yeoju-si, Gyeonggi-do, Korea
FCC rule part(s):	15.247
FCC ID:	2AJO9PRT-SAR1A-01PS
Test device serial No.:	☒ Production ☐ Pre-production ☐ Engineering

1.1. EUT description

Equipment under test	Prota S
Frequency range	BT : 2 402 ㎒ ~ 2 480 ㎒ (BDR/EDR/LE) WIFI : 2 412 ㎒ ~ 2 462 ㎒ (11b/g/n_HT20) 2 422 ㎒ ~ 2 452 ㎒(11n_HT40)
Model	PRT-SAR1A-01PS
Modulation technique	BT : FHSS, GFSK WIFI : DSSS, OFDM
Number of channels	BT : 79 (BDR/EDR), 40(LE) WIFI : 11(802.11b/g/n_HT20), 7(802.11n_HT40)
Antenna specification	Antenna type: PCB, Peak gain: 0.25 ㏈i
Power source	DC 5V

15.247(a)(1) that the rx input bandwidths shift frequencies in synchronization with the transmitted

15.247(g): In accordance with the Bluetooth Industry Standard, the system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) system.

15.247(h): In accordance with the Bluetooth Industry Standard, the system does not coordinate it channels selection/ hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.

Pseudorandom frequency hopping sequence

The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master; the phase in the hopping sequence is determined by the Bluetooth clock of the master. The channel is divided into time slots where each slot corresponds to an RF hop frequency. Consecutive hops correspond to different RF hop frequencies. The nominal hop rate is 1 600 hops/s.

Equal hopping frequency use

The channels of this system will be used equally over the long-term distribution of the hopsets.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Example of a 79 hopping sequence in data mode:
02, 05, 31, 24, 20, 10, 43, 36, 30, 23, 40, 06, 21, 50, 44, 09, 71, 78, 01, 13, 73, 07, 70, 72, 35, 62, 42, 11, 41, 08, 16, 29, 60, 15, 34, 61, 58, 04, 67, 12, 22, 53, 57, 18, 27, 76, 39, 32, 17, 77, 52, 33, 56, 46, 37, 47, 64, 49, 45, 38, 69, 14, 51, 26, 79, 19, 28, 65, 75, 54, 48, 03, 25, 66, 05, 16, 68, 74, 59, 63, 55,

System receiver input bandwidth
Each channel bandwidth is 1 ㎒.
The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

1.2. Test configuration

The **Naran Inc Prota S FCC ID: 2AJO9PRT-SAR1A-01PS** was tested per the guidance of ANSI C63.10-2013 and DA 00-705. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

1.3. Frequency/channel operations

Ch.	Frequency (㎒)	Rate(Mbps)
00	2402	1,2,3
. .	. .	. .
40	2442	1,2,3
. .	. .	. .
78	2480	1,2,3

1.4. Accessory information

Applicant	Equipment	Manufacturer	Model	Power source
-	-	-	-	-

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

2. Summary of tests

Reference	Test description	Test results
15.247(a)(1)(iii)	20 dB bandwidth	Pass
15.247(b)(1)	Output power	Pass
15.247(a)(1)	Channel separation	Pass
15.247(a)(1)(iii)	Number of channels	Pass
15.247(a)(1)(iii)	Time of occupancy	Pass
15.205, 15.209	Radiated restricted band and emission	Pass
15.207(d)	Conducted band edge and out of band emissions	Pass
15.207(a)	AC conducted emissions	Pass

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

3. Test results

3.1. Radiated restricted band and emissions

Test setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 9 ㎑ to 30 ㎒ Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 ㎒ to 1 ㎓ emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 ㎓ to the tenth harmonic of the highest fundamental frequency or to 40 ㎓ emissions, whichever is lower.



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Test procedure

1. The EUT is placed on a turntable, which is 0.8 m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. Spectrum analyzer settings for $f < 1$ ㎓:
   Span = wide enough to fully capture the emission being measured
   RBW = 100 ㎑
   VBW ≥ RBW
   Sweep = auto
   Detector function = quasi peak
   Trace = max hold
8. Spectrum analyzer settings for $f \geq 1$ ㎓: Peak
   Span = wide enough to fully capture the emission being measured
   RBW = 1 ㎒
   VBW ≥ RBW
   Sweep = auto
   Detector function = peak
   Trace = max hold
9. Spectrum analyzer settings for $f \geq 1$ ㎓: Average
   Span = wide enough to fully capture the emission being measured
   RBW = 1 ㎒
   VBW ≥ 1/T ㎐, where T= pulse width in seconds
   Sweep = auto
   Detector function = average
   Trace = max hold
10. Duty Cycle Correction Factor (79 channel hopping)
    a. Time to cycle through all channels = $\Delta t = \tau$[㎳] × 79 channels = 230.601 ㎳, where τ = pulse width
    b. 100 ㎳/ Δt[㎳] = H → Round up to next highest integer, H '=1
    c. Worst Case Dwell Time = τ[㎳] × H' = 2.919 ㎳
    d. Duty Cycle Correction = 20log (Worst Case Dwell Time/ 100㎳) ㏈ = -30.695 ㏈

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Note:

1. The spectrum is measured from 9 ㎑ to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1 ㎓. Above 1 ㎓, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported however emissions whose levels were not within 20 ㏈ of the respective limits were not reported.
2. When Average result is different from peak result over 20 ㏈ (over-averaging), according to 15.35 (c), as a "duty cycle correction factor", pulse averaging with 20 log(duty cycle) has to be used.
   Duty cycle correction factor = 20log(dwell time/100 ㎳)
3. Emissions below 18 ㎓ were measured at a 3 meter test distance while emissions above 18 ㎓ were measured at a 1 meter test distance with the application of a distance correction factor.
4. Average test would be performed if the peak result were greater than the average limit.
5. Field strength(㏈㎶/m) = Level(㏈㎶) + Correction factors(㏈/m) + Cable loss(㏈) + or F_d(㏈)
6. Correction factors(㏈/m) = Antenna factor(㏈/m) + Cable loss(㏈) + or Amp. gain(㏈)
7. Margin(㏈) = Limit(㏈㎶/m) - Field strength(㏈㎶/m)
8. To get a maximum emission level from the EUT, the EUT was moved throughout the XY, XZ and YZ planes.
9. f < 30 ㎒, extrapolation factor of 40 ㏈/decade of distance. $F_d = 40\log(D_m / Ds)$
   $f \geq$ 30 ㎒, extrapolation factor of 20 ㏈/decade of distance. $F_d = 20\log(D_m / Ds)$

Where:

F_d = Distance factor in ㏈
D_m = Measurement distance in meters
D_s = Specification distance in meters

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Limit

According to 15.209(a), for an intentional radiator devices, the general required of field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values：

Frequency (㎒)	Distance (Meters)	Radiated (㎶/m)
0.009 ~ 0.490	300	2 400 / F(㎑)
0.490 ~ 1.705	30	24 000 / F(㎑)
1.705 ~ 30.0	30	30
30 ~ 88	3	100**
88 ~ 216	3	150**
216 ~ 960	3	200**
Above 960	3	500

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 ~ 72 ㎒, 76 ~ 88 ㎒, 174 ~ 216 ㎒ or 470 ~ 806 ㎒. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Test results (Below 30 ㎒)

Mode:	EDR
Transfer rate:	3 Mbps
Distance of measurement:	3 meter
Channel:	00(Worst case)

Frequency (㎒)	Level (dBμV)	Ant. Pol. (H/V)	CF (dB)	F_d (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
No spurious emissions were detected within 20㏈ of the limit							

Horizontal	Vertical
	
	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Test results (Below 1 000 ㎒)

Mode:	EDR
Transfer rate:	3 Mbps
Distance of measurement:	3 meter
Channel:	00(Worst case)

Horizontal



	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	49.40	29.27	15.09	13.70	0.48	0.00	40.00	-10.73		horizontal
2	150.28	31.83	18.15	12.96	0.72	0.00	43.50	-11.67		horizontal
3	305.48	39.77	24.63	13.94	1.20	0.00	46.00	-6.23		horizontal
4	446.13	35.40	17.04	17.10	1.26	0.00	46.00	-10.60		horizontal
5	479.11	36.77	17.60	17.84	1.33	0.00	46.00	-9.23		horizontal
6	522.76	38.22	17.98	18.77	1.47	0.00	46.00	-7.78		horizontal
7	685.72	38.56	15.65	21.29	1.62	0.00	46.00	-7.44		horizontal
8 pp	739.07	40.07	16.29	22.08	1.70	0.00	46.00	-5.93		horizontal

Vertical



	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	49.40	26.28	12.10	13.70	0.48	0.00	40.00	-13.72		vertical
2	140.58	31.23	17.72	12.83	0.68	0.00	43.50	-12.27		vertical
3	274.44	33.93	19.96	12.88	1.09	0.00	46.00	-12.07		vertical
4	446.13	34.93	16.57	17.10	1.26	0.00	46.00	-11.07		vertical
5	456.80	38.03	19.41	17.34	1.28	0.00	46.00	-7.97		vertical
6	480.08	38.21	19.02	17.86	1.33	0.00	46.00	-7.79		vertical
7	521.79	40.01	19.79	18.75	1.47	0.00	46.00	-5.99		vertical
8 pp	547.98	40.91	20.05	19.29	1.57	0.00	46.00	-5.09		vertical
9	594.54	39.23	17.45	20.26	1.52	0.00	46.00	-6.77		vertical

Note.

1. All spurious emission at channels are almost the same below 1 ㎓, so that low channel was chosen at representative in final test.
2. To get a maximum emission level from the EUT, the EUT was moved throughout the XY, XZ and YZ planes.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Test results (Above 1 000 ㎒)

Mode: BDR

Transfer rate: 1 Mbps

Distance of measurement: 3 meter

Channel: 00

Frequency (㎒)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1004.30	58.88	Peak	H	-16.65	-	42.23	74.00	31.77
1635.30	57.76	Peak	H	-13.86	-	43.90	74.00	30.10
2005.80	56.13	Peak	H	-11.20	-	44.93	74.00	29.07
1635.30	58.89	Peak	V	-13.86	-	45.03	74.00	28.97
1782.90	57.96	Peak	V	-12.66	-	45.30	74.00	28.70
2005.80	58.19	Peak	V	-11.20	-	46.99	74.00	27.01
2390.00	61.56	Peak	H	-9.77	-	51.79	74.00	22.21
2388.61	61.92	Peak	V	-9.77	-	52.15	74.00	21.85

Restricted band // Horizontal // Peak



Restricted band // Vertical // Peak



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Horizontal // Peak for 1 ㎓ to 3 ㎓	Vertical // Peak for 1 ㎓ to 3 ㎓
	
Horizontal // Peak for 3 ㎓ to 18 ㎓	**Vertical // Peak for 3 ㎓ to 18 ㎓**
	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Mode:	BDR
Transfer rate:	1 Mbps
Distance of measurement:	3 meter
Channel:	40

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1635.30	56.75	Peak	H	-13.86	-	42.89	74.00	31.11
2005.80	55.80	Peak	H	-11.20	-	44.60	74.00	29.40
1635.30	58.07	Peak	V	-13.86	-	44.21	74.00	29.79
1733.70	59.22	Peak	V	-13.06	-	46.16	74.00	27.84
2005.80	59.31	Peak	V	-11.20	-	48.11	74.00	25.89

Restricted band // Horizontal // Peak	Restricted band // Vertical // Peak
N/A	N/A
Horizontal // Peak for 1 GHz to 3 GHz	**Vertical // Peak for 1 GHz to 3 GHz**
	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Horizontal // Peak for 3 ㎓ to 18 ㎓	Vertical // Peak for 3 ㎓ to 18 ㎓
	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Mode:	BDR
Transfer rate:	1 Mbps
Distance of measurement:	3 meter
Channel:	78

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1007.20	56.87	Peak	H	-16.64	-	40.23	74.00	33.77
1635.30	55.91	Peak	H	-13.86	-	42.05	74.00	31.95
2005.80	55.64	Peak	H	-11.20	-	44.44	74.00	29.56
1519.50	60.22	Peak	V	-14.71	-	45.51	74.00	28.49
1635.30	58.08	Peak	V	-13.86	-	44.22	74.00	29.78
2005.80	59.06	Peak	V	-11.20	-	47.86	74.00	26.14
2491.80	49.11	Peak	H	-9.37	-	39.74	74.00	34.26
2490.42	50.20	Peak	V	-9.38	-	40.82	74.00	33.18

Restricted band // Horizontal // Peak



Restricted band // Vertical // Peak



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Horizontal // Peak for 1 ㎓ to 3 ㎓	Vertical // Peak for 1 ㎓ to 3 ㎓
	

Horizontal // Peak for 3 ㎓ to 18 ㎓	Vertical // Peak for 3 ㎓ to 18 ㎓
	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Mode:	EDR
Transfer rate:	3 Mbps(Worst case)
Distance of measurement:	3 meter
Channel:	00

Frequency (㎒)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1186.70	57.47	Peak	H	-15.98	-	41.49	74.00	32.51
1635.30	57.99	Peak	H	-13.86	-	44.13	74.00	29.87
2228.70	56.59	Peak	H	-10.26	-	46.33	74.00	27.67
1635.30	60.29	Peak	V	-13.86	-	46.43	74.00	27.57
1782.90	57.93	Peak	V	-12.66	-	45.27	74.00	28.73
2005.80	59.24	Peak	V	-11.20	-	48.04	74.00	25.96
2388.48	61.61	Peak	H	-9.77	-	51.84	74.00	22.16
2390.00	61.27	Peak	V	-9.77	-	51.50	74.00	22.50

Restricted band // Horizontal // Peak



Restricted band // Vertical // Peak



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Horizontal // Peak for 1 ㎓ to 3 ㎓	Vertical // Peak for 1 ㎓ to 3 ㎓
	
Horizontal // Peak for 3 ㎓ to 18 ㎓	**Vertical // Peak for 3 ㎓ to 18 ㎓**
	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Mode: EDR

Transfer rate: 3 Mbps(Worst case)

Distance of measurement: 3 meter

Channel: 40

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1004.30	56.93	Peak	H	-16.65	-	40.28	74.00	33.72
1635.30	57.19	Peak	H	-13.86	-	43.33	74.00	30.67
2228.70	56.59	Peak	H	-10.26	-	46.33	74.00	27.67
1004.30	58.01	Peak	V	-16.65	-	41.36	74.00	32.64
1635.30	57.28	Peak	V	-13.86	-	43.42	74.00	30.58
1782.90	58.44	Peak	V	-12.66	-	45.78	74.00	28.22
2005.80	58.83	Peak	V	-11.20	-	47.63	74.00	26.37

Restricted band // Horizontal // Peak	Restricted band // Vertical // Peak
N/A	N/A

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Horizontal // Peak for 1 ㎓ to 3 ㎓	Vertical // Peak for 1 ㎓ to 3 ㎓
	
Horizontal // Peak for 3 ㎓ to 18 ㎓	**Vertical // Peak for 3 ㎓ to 18 ㎓**
	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Mode:	EDR
Transfer rate:	3 Mbps(Worst case)
Distance of measurement:	3 meter
Channel:	78

Frequency (㎒)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1004.30	56.87	Peak	H	-16.65	-	40.22	74.00	33.78
2005.80	54.91	Peak	H	-11.20	-	43.71	74.00	30.29
2228.70	56.40	Peak	H	-10.26	-	46.14	74.00	27.86
1635.30	58.20	Peak	V	-13.86	-	44.34	74.00	29.66
1782.90	58.61	Peak	V	-12.66	-	45.95	74.00	28.05
2005.80	58.74	Peak	V	-11.20	-	47.54	74.00	26.46
2500.00	48.84	Peak	H	-9.34	-	39.50	74.00	34.50
2483.50	52.01	Peak	V	-9.41	-	42.60	74.00	31.40

Restricted band // Horizontal // Peak



Restricted band // Vertical // Peak



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Horizontal // Peak for 1 ㎓ to 3 ㎓	Vertical // Peak for 1 ㎓ to 3 ㎓
	

Horizontal // Peak for 3 ㎓ to 18 ㎓	Vertical // Peak for 3 ㎓ to 18 ㎓
	

Test results (18 ㎓ to 30 ㎓)

Mode:	EDR
Transfer rate:	3 Mbps
Distance of measurement:	3 meter
Channel:	00(Worst case)

Frequency (㎒)	Level (dBμV)	Ant. Pol. (H/V)	CF (dB)	F_d (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
No spurious emissions were detected within 20㏈ of the limit							

Horizontal	Vertical
	

Note.

1. Average test would be performed if the peak result were greater than the average limit.
2. Actual = Reading + AFCL(Ant. factor – Amp. gain + Cable loss) + DCF(Duty cycle correction factor)
3. Duty cycle correction factor = 20log(dwell time/100 ㎳)

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

3.2. Conducted band edge and out of band emissions

Test setup



Test procedure

DA 00-705

Test setting

1. Span = wide enough to capture the peak level of the in-band emission and all spurious emissions(e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic.
2. RBW = 100 ㎑
3. VBW ≥ 300 ㎑
4. Detector = Peak
5. Number of sweep points ≥ 2 × Span/RBW
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Limit

According to 15.247(d), in any 100 ㎑ bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 ㏈ below that in the 100 ㎑ bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval , as permitted under paragraph(b)(3) of this section , the attenuation required under this paragraph shall be 30 ㏈ instead of 20 ㏈. Attenuation below the general limits specified in section 15.209(a) is not required. In addition, radiated emission which in the restricted band, as define in section 15.205(a), must also comply the radiated emission limits specified in section 15.209(a) (see section 15.205(c))

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Test results

BDR(1Mbps)	
	
N/A	
	

EDR(3Mbps)





N/A







This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Hopping mode_BDR(1Mbps)





Hopping mode_EDR(3Mbps)





This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

3.3. 20 dB bandwidth

Test setup

EUT — Attenuator — Spectrum analyzer

Test procedure
DA 00-705

Test setting
1. Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel
2. RBW ≥ 1% of the 20 dB bandwidth
3. VBW ≥ RBW
4. Sweep = auto
5. Detector function = peak
6. Sweep = auto couple
7. Trace mode = max hold

Limit
Not applicable

Frequency(㎒)	Channel no.	Data rate(Mbps)	Measured bandwidth(㎒)
2 402	00	1	0.894
2 441	39		0.886
2 480	78		0.886
2 402	00	2	1.237
2 441	39		1.250
2 480	78		1.255
2 402	00	3	1.250
2 441	39		1.211
2 480	78		1.268

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

BDR(1Mbps)	EDR(2Mbps)
	
	
	

EDR(3Mbps)





This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

3.4. Output power

Test setup

EUT	—	Attenuator	—	Spectrum analyzer

Test procedure
DA 00-705

Test setting
1. Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
2. RBW > the 20 dB bandwidth of the emission being measured
3. VBW ≥ RBW
4. Sweep = Auto
5. Detector function = Peak
6. Trace = Max hold

Limit
According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 ㎑ or the 20 ㏈ bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 ㎽.

According to §15.247(b)(1), For frequency hopping systems operating in the 2 400 ~ 2 483.5 ㎒ employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5 725 ~ 5 805 ㎒ band: 1 Watt.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Frequency(㎒)	Channel no.	Data rate(Mbps)	Measured power (dBm)	Peak Power Limit (dBm)
2 402	00	1	-0.09	20.97
2 441	39		-0.06	20.97
2 480	78		-0.45	20.97
2 402	00	2	1.18	20.97
2 441	39		1.09	20.97
2 480	78		0.71	20.97
2 402	00	3	1.48	20.97
2 441	39		1.36	20.97
2 480	78		0.96	20.97

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

BDR(1Mbps)	EDR(2Mbps)
	
	
	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

EDR(3Mbps)







This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

3.5. Carrier frequency separation

Test setup

EUT	Attenuator	Spectrum analyzer

Test procedure

DA 00-705

Test Setting

1. The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:
2. Span = wide enough to capture the peaks of two adjacent channels
3. Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span
4. Video (or Average) Bandwidth (VBW) ≥ RBW

5. Sweep = auto
6. Detector function = peak
7. Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.

Limit

According to 15.247(a)(1), frequency hopping system operating in 2 400 ~ 2 483.5 ㎒. Band may have hopping channel carrier frequencies that are separated by 25 ㎑ or two-third of 20 ㏈ bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 ㎽.

Frequency(㎒)	Channel no.	Data rate(Mbps)	Channel Separation (㎒)
2 441	39	1	0.999
2 441	39	3	0.999

Note:

Measurement is made with EUT operating in hopping mode between 79 channels providing a worse case scenario as compared to AFH mode hopping between 20 channels.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Hopping mode_BDR(1Mbps)	Hopping mode_EDR(3Mbps)
	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

3.6. Number of hopping frequency

Test setup



Test procedure
DA 00-705

Test setting
1. The EUT must have its hopping function enabled.
2. Frequency range: 2 400 ㎒ ~ 2 441.5 ㎒, 2 441.5 ㎒ ~ 2 483.5 ㎒
3. Span = the frequency band of operation
4. RBW = 300 ㎑ (≥ 1% of the span)
5. VBW = 1 ㎒ (≥ RBW)
6. Sweep = auto
7. Detector function = peak
8. Trace = max hold

All the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Limit
According to 15.247(a)(1)(iii), for frequency hopping system operating in the 2 400 ~ 2 483.5 ㎒ bands shall use at least 15 hopping frequencies.

Note: In case of AFH mode, minimum number of hopping channels is 20.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Hopping mode_BDR(1Mbps)	Hopping mode_EDR(3Mbps)
	
	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

3.7. Time of occupancy

Test setup



Test procedure
DA 00-705

Test setting
1. The EUT must have its hopping function enabled.
2. Span = zero span, centered on a hopping channel
4. RBW = 1 ㎒
5. VBW = 1 ㎒ (≥ RBW)
6. Sweep = as necessary to capture the entire dwell time per hopping channel
7. Detector function = peak
8. Trace = max hold

Limit
According to 15.247(a)(1)(iii), for frequency hopping system operating in the 2 400 ~ 2 483.5 ㎒ band, the average time of occupancy on any frequency shall not be greater than 0.4 second within a 31.6 second period.

A period time = 0.4(s) × 79 = 31.6(s)

Time of occupancy on the TX channel in 31.6 sec
= time domain slot length × (hop rate ÷ number of hop per channel) × 31.6

• Adaptive Frequency Hopping

A period time = 0.4(s) × 20 = 8.0(s)

Time of occupancy on the TX channel in 8.0 sec
= time domain slot length × (hop rate ÷ number of hop per channel) × 8.0

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Operation mode: GFSK , π/4-DQPSK, 8DPSK

Packet type	Frequency (㎒)	Dwell time (ms)	Time of occupancy on the Tx channel in 31.6 sec (ms)	Limit for time of occupancy on the Tx channel in 31.6 sec (ms)
DH1	2 441	0.407	134.08	400
DH3	2 441	1.657	268.48	400
DH5	2 441	2.909	312.32	400
2-DH1	2 441	0.417	139.20	400
2-DH3	2 441	1.670	269.60	400
2-DH5	2 441	2.917	312.85	400
3-DH1	2 441	0.417	140.16	400
3-DH3	2 441	1.667	269.60	400
3-DH5	2 441	2.919	313.49	400

Note:
Normal Mode
DH1: Dwell time (ms) × [(1 600 ÷ 2) ÷ 79] × 31.6(s) = 134.08 (ms)
DH3: Dwell time (ms) × [(1 600 ÷ 4) ÷ 79] × 31.6(s) = 268.48 (ms)
DH5: Dwell time (ms) × [(1 600 ÷ 6) ÷ 79] × 31.6(s) = 312.32 (ms)
2-DH1: Dwell time (ms) × [(1 600 ÷ 2) ÷ 79] × 31.6(s) = 139.20 (ms)
2-DH3: Dwell time (ms) × [(1 600 ÷ 4) ÷ 79] × 31.6(s) = 269.60 (ms)
2-DH5: Dwell time (ms) × [(1 600 ÷ 6) ÷ 79] × 31.6(s) = 312.85 (ms)
3-DH1: Dwell time (ms) × [(1 600 ÷ 2) ÷ 79] × 31.6(s) = 140.16 (ms)
3-DH3: Dwell time (ms) × [(1 600 ÷ 4) ÷ 79] × 31.6(s) = 269.60 (ms)
3-DH5: Dwell time (ms) × [(1 600 ÷ 6) ÷ 79] × 31.6(s) = 313.49 (ms)

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

BDR(1Mbps)	EDR(2Mbps)
	
	
	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

EDR(3Mbps)


Spectrum 3
Spectrum
Ref Level 23.00 dBm Offset 10.80 dB RBW 1 MHz
Att 20 dB SWT 1 ms VBW 1 MHz
SGL
1Pk Clrw
D2[1] 9.40 dB 416.67 µs
M1[1] -46.06 dBm 138.41 µs
CF 2.442 GHz 691 pts 100.0 µs/
Ready
Date: 26.SEP.2016 20:30:40


Spectrum 3
Spectrum
Ref Level 23.00 dBm Offset 10.80 dB RBW 1 MHz
Att 20 dB SWT 2.5 ms VBW 1 MHz
SGL
1Pk Clrw
D2[1] -38.39 dB 1.66667 ms
M1[1] 0.69 dBm 355.80 µs
CF 2.442 GHz 691 pts 250.0 µs/
Ready
Date: 26.SEP.2016 20:31:19


Spectrum 3
Spectrum
Ref Level 23.00 dBm Offset 10.80 dB RBW 1 MHz
Att 20 dB SWT 4 ms VBW 1 MHz
SGL
1Pk Clrw
D2[1] -38.35 dB 2.91884 ms
M1[1] 1.14 dBm 234.06 µs
CF 2.442 GHz 691 pts 400.0 µs/
Ready
Date: 26.SEP.2016 20:32:17

3.8. AC conducted emissions

Limit

According to 15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 ㎑ to 30 ㎒, shall not exceed the limits in the following table, as measured using a 50uH/50 ohm line impedance stabilization network (LISN). Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequencies ranges.

Frequency of Emission (㎒)	Conducted limit (dBμV/m)	
	Quasi-peak	Average
0.15 – 0.50	66 - 56*	56 - 46*
0.50 – 5.00	56	46
5.00 – 30.0	60	50

Note:

1. All AC line conducted spurious emission are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and the appropriate frequencies. All data rates and modes were investigated for conducted spurious emission. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.
3. Both Cable loss and LISN factor are included in measurement level(QP Level or AV Level).

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Test results

Hot Line



Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.510000	---	31.39	46.00	14.61	1000.0	9.000	L1	9.8
0.510000	41.13	---	56.00	14.87	1000.0	9.000	L1	9.8
3.885000	---	30.60	46.00	15.40	1000.0	9.000	L1	10.1
3.885000	40.30	---	56.00	15.70	1000.0	9.000	L1	10.1
4.585000	---	31.91	46.00	14.09	1000.0	9.000	L1	10.0
4.585000	40.46	---	56.00	15.54	1000.0	9.000	L1	10.0
5.200000	---	31.05	50.00	18.95	1000.0	9.000	L1	10.0
5.200000	37.82	---	60.00	22.18	1000.0	9.000	L1	10.0
12.440000	---	24.50	50.00	25.50	1000.0	9.000	L1	9.9
12.440000	32.69	---	60.00	27.31	1000.0	9.000	L1	9.9

Neutral Line



Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.505000	---	34.55	46.00	11.45	1000.0	9.000	N	9.8
0.505000	44.50	---	56.00	11.50	1000.0	9.000	N	9.8
4.590000	---	34.08	46.00	11.92	1000.0	9.000	N	10.0
4.590000	44.31	---	56.00	11.69	1000.0	9.000	N	10.0
4.675000	---	32.75	46.00	13.25	1000.0	9.000	N	10.0
4.675000	43.71	---	56.00	12.29	1000.0	9.000	N	10.0
5.220000	---	33.51	50.00	16.49	1000.0	9.000	N	10.0
5.220000	42.69	---	60.00	17.31	1000.0	9.000	N	10.0
18.640000	---	27.72	50.00	22.28	1000.0	9.000	N	10.1
18.640000	37.38	---	60.00	22.62	1000.0	9.000	N	10.1

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Appendix A. Measurement equipment

Equipment	Manufacturer	Model	Serial No.	Calibration interval	Calibration due.
Spectrum Analyzer	R&S	FSV40	101002	1 year	2017.07.06
Spectrum Analyzer	R&S	FSV30	10076	1 year	2017.07.06
8360B Series Swept Signal Generator	HP	83630B	3844A00786	1 year	2017.01.25
PSG Analog Signal Generator	AGILENT	E8257C	US42340237	1 year	2017.07.05
Attenuator	Agilent	8493C	51401	1 year	2017.07.05
Wideband Power Sensor	R&S	NRP-Z81	101886	1 year	2017.01.22
Power Meter	Anritsu	ML2495A	1438001	1 year	2017.01.25
Pulse Power Sensor	Anritsu	MA2411B	1339205	1 year	2017.01.25
Loop Antenna	R&S	HFH2-Z2.335.4711.52	826532	2 years	2017.03.03
Trilog-broadband antenna	SCHWARZBECK	VULB 9163	9168-713	2 years	2017.05.15
Horn Antenna	A.H.	SAS-571	781	2 years	2017.05.07
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170550	2 years	2017.04.30
High Pass Filter	WAINWRIGHT INSTRUMENT	WHJS3000-10TT	1	1 year	2017.07.04
Low Pass Filter	WEINSCHEL	WLK1.0/18G-10TT	1	1 year	2017.07.04
Preamplifier	SCHWARZBECK	BBV-9718	9718-246	1 year	2016.10.23
Broadband Amplifier	SCHWARZBECK	BBV-9721	PS9721-003	1 year	2017.01.25
EMI Test Receiver	R&S	ESR3	101781	1 year	2017.05.03
EMI Test Receiver	R&S	ESU26	100552	1 year	2017.04.24
EMI Test Receiver	R&S	ESR3	101783	1 year	2017.05.03
LISN	R&S	ENV216	101137	1 year	2017.02.04

Peripheral devices

Device	Manufacturer	Model No.	Serial No.
AC/DC Adapter	Weihai Sunlin electronics Co. Ltd	PPC-340-M5	N/A
Monitor	LG Electronics Inc.	FLATRON 23EN43V	312NDZJ75261
AC/DC Adapter	SHENZHEN HONOR ELECTRONIC CO.,Ltd.	ADS-40FSG-19	EAY62768606
Mouse	WORLD OF MAX TECHNOLOGIES COMPANY LIMITED	V200	N/A

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.

Appendix B. Test setup photo

Radiated	
	N/A
AC conducted	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The test results in the report only apply to the tested sample.