

Fig.A.6.2.7 Transmitter Spurious Emission - Radiated (802.11b, Ch6, 18GHz – 26.5GHz)



Fig.A.6.2.8 Transmitter Spurious Emission - Radiated (Power): 802.11b, ch11, 2.45 GHz - 2.50GHz

©Copyright. All rights reserved by CTTL.



Fig.A.6.2.9 Transmitter Spurious Emission - Radiated (802.11b, Ch11, 1 GHz-3 GHz)



Fig.A.6.2.10 Transmitter Spurious Emission - Radiated (802.11b, Ch11, 3 GHz-18 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.2.11 Transmitter Spurious Emission - Radiated (Power): 802.11g, ch1, 2.38 GHz - 2.45GHz



Fig.A.6.2.12 Transmitter Spurious Emission - Radiated (802.11g, Ch1, 1 GHz-3 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.2.13 Transmitter Spurious Emission - Radiated (802.11g, Ch1, 3 GHz-18 GHz)



Fig.A.6.2.14 Transmitter Spurious Emission - Radiated (802.11g, Ch6, 30 MHz-1 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.2.15 Transmitter Spurious Emission - Radiated (802.11g, Ch6, 1 GHz-3 GHz)



Fig.A.6.2.16 Transmitter Spurious Emission - Radiated (802.11g, Ch6, 3 GHz-18 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.2.17 Transmitter Spurious Emission - Radiated (802.11g, Ch6, 18GHz – 26.5GHz)



Fig.A.6.2.18 Transmitter Spurious Emission - Radiated (Power): 802.11g, ch11, 2.45 GHz - 2.50GHz

©Copyright. All rights reserved by CTTL.



Fig.A.6.2.19 Transmitter Spurious Emission - Radiated (802.11g, Ch11, 1 GHz-3 GHz)



Fig.A.6.2.20 Transmitter Spurious Emission - Radiated (802.11g, Ch11, 3 GHz-18 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.2.21 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT20, ch1, 2.38 GHz - 2.45GHz



Fig.A.6.2.22 Transmitter Spurious Emission - Radiated (802.11n-HT20, Ch1, 1 GHz-3 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.2.23 Transmitter Spurious Emission - Radiated (802.11n-HT20, Ch1, 3 GHz-18 GHz)



Fig.A.6.2.24 Transmitter Spurious Emission - Radiated (802.11n-HT20, Ch6, 30 MHz-1 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.2.25 Transmitter Spurious Emission - Radiated (802.11n-HT20, Ch6, 1 GHz-3 GHz)



Fig.A.6.2.26 Transmitter Spurious Emission - Radiated (802.11n-HT20, Ch6, 3 GHz-18 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.2.27 Transmitter Spurious Emission - Radiated (802.11n-HT20, Ch6, 18GHz – 26.5GHz)



Fig.A.6.2.28 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT20, ch11, 2.45 GHz - 2.50GHz

©Copyright. All rights reserved by CTTL.



Fig.A.6.2.29 Transmitter Spurious Emission - Radiated (802.11n-HT20, Ch11, 1 GHz-3 GHz)



Fig.A.6.2.30 Transmitter Spurious Emission - Radiated (802.11n-HT20, Ch11, 3 GHz-18 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.2.31 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT40, ch3, 2.38 GHz - 2.45GHz



Fig.A.6.2.32 Transmitter Spurious Emission - Radiated (802.11n-HT40, ch3, 1 GHz-3 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.2.33 Transmitter Spurious Emission - Radiated (802.11n-HT40, ch3, 3 GHz-18 GHz)



Fig.A.6.2.34 Transmitter Spurious Emission - Radiated (802.11n-HT40, Ch6, 30 MHz-1 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.2.35 Transmitter Spurious Emission - Radiated (802.11n-HT40, Ch6, 1 GHz-3 GHz)



Fig.A.6.2.36 Transmitter Spurious Emission - Radiated (802.11n-HT40, Ch6, 3 GHz-18 GHz)

©Copyright. All rights reserved by CTTL.



Fig.A.6.2.37 Transmitter Spurious Emission - Radiated (802.11n-HT40, Ch6, 18GHz – 26.5GHz)



Fig.A.6.2.38 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT40, ch9, 2.45 GHz - 2.50GHz

©Copyright. All rights reserved by CTTL.



Fig.A.6.2.39 Transmitter Spurious Emission - Radiated (802.11n-HT40, ch9, 1 GHz-3 GHz)



Fig.A.6.2.40 Transmitter Spurious Emission - Radiated (802.11n-HT40, ch9, 3 GHz-18 GHz)

©Copyright. All rights reserved by CTTL.

A.7. AC Power-line Conducted Emission

Method of Measurement: See ANSI C63.10-2013-clause 6.2

1 The one EUT cable configuration and arrangement and mode of operation that produced the emission with the highest amplitude relative to the limit is selected for the final measurement, while applying the appropriate modulating signal to the EUT.

2 If the EUT is relocated from an exploratory test site to a final test site, the highest emissions shall be remaximized at the final test location before final ac power-line conducted emission measurements are performed.

3 The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment in the system) is then performed for the full frequency range for which the EUT is being tested for compliance without further variation of the EUT arrangement, cable positions, or EUT mode of operation.

4 If the EUT is comprised of equipment units that have their own separate ac power connections, e.g., floor-standing equipment with independent power cords for each shelf that are able to connect directly to the ac power network, each current-carrying conductor of one unit is measured while the other units are connected to a second (or more) LISN(s). All units shall be separately measured. If a power strip is provided by the manufacturer, to supply all of the units making up the EUT, only the conductors in the power cord of the power strip shall be measured.

5 If the EUT uses a detachable antenna, these measurements shall be made with a suitable dummy load connected to the antenna output terminals; otherwise, the tests shall be made with the antenna connected and, if adjustable, fully extended. When measuring the ac conducted emissions from a device that operates between 150 kHz and 30 MHz a non-detachable antenna may be replaced with a dummy load for the measurements within the fundamental emission band of the transmitter, but only for those measurements.36 Record the six highest EUT emissions relative to the limit of each of the current-carrying conductors of the power cords of the equipment that comprises the EUT over the frequency range specified by the procuring or regulatory agency. Diagram or photograph the test setup that was used. See Clause 8 for full reporting requirements.

Test Condition:

Voltage（V）	Frequency（Hz）
120	60

©Copyright. All rights reserved by CTTL.

Measurement Result and limit:

WLAN (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dBμV)	Result (dBμV)		Conclusion
		With charger		
		802.11b	Idle	
0.15 to 0.5	66 to 56	Fig.A.7.1	Fig.A.7.2	**P**
0.5 to 5	56			
5 to 30	60			
NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.				

WLAN (Average Limit)

Frequency range (MHz)	Average Limit (dBμV)	Result (dBμV)		Conclusion
		With charger		
		802.11b	Idle	
0.15 to 0.5	56 to 46	Fig.A.7.1	Fig.A.7.2	**P**
0.5 to 5	46			
5 to 30	50			
NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.				

Conclusion: Pass

Test graphs as below:



Fig.A.7.1 AC Powerline Conducted Emission-802.11b

Note: The graphic result above is the maximum of the measurements for both phase line and

©Copyright. All rights reserved by CTTL.

neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.775500	41.9	GND	L1	10.7	14.1	56.0
16.462500	40.6	GND	L1	11.2	19.4	60.0
16.530000	40.1	GND	L1	11.2	19.9	60.0
17.052000	43.0	GND	L1	11.2	17.0	60.0
17.115000	42.5	GND	L1	11.2	17.5	60.0
17.479500	40.6	GND	L1	11.2	19.4	60.0

Final Result 2

Frequency (MHz)	Average (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.775500	33.9	GND	L1	10.7	12.1	46.0
0.874500	30.0	GND	L1	10.7	16.0	46.0
0.910500	30.2	GND	L1	10.7	15.8	46.0
0.973500	29.0	GND	L1	10.7	17.0	46.0
1.617000	29.0	GND	L1	10.7	17.0	46.0
17.754000	30.3	GND	L1	11.2	19.7	50.0

©Copyright. All rights reserved by CTTL.