



FCC RF Test Report

APPLICANT : FIH International Co., Ltd.
EQUIPMENT : GSM/WCDMA/LTE Mobile Phone
BRAND NAME : Nokia
MODEL NAME : TA-1079
FCC ID : 2AJOTTA-1079
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was completed on Jan. 17, 2018. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Approved by: James Huang / Manager



Sporton International (Kunshan) Inc.
No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335
China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	6
1.6 Testing Location	6
1.7 Applicable Standards.....	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Carrier Frequency and Channel	8
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	10
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	11
3 TEST RESULT	12
3.1 6dB and 99% Bandwidth Measurement	12
3.2 Output Power Measurement.....	14
3.3 Power Spectral Density Measurement	15
3.4 Conducted Band Edges and Spurious Emission Measurement	17
3.5 Radiated Band Edges and Spurious Emission Measurement	27
3.6 AC Conducted Emission Measurement.....	31
3.7 Antenna Requirements.....	35
4 LIST OF MEASURING EQUIPMENT	36
5 UNCERTAINTY OF EVALUATION	37
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. RADIATED SPURIOUS EMISSION	
APPENDIX C. DUTY CYCLE PLOTS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR7O2602-03C	Rev. 01	Initial issue of report	Jan. 29, 2018

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 1.44 dB at 2483.620 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 17.41 dB at 0.175 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

FIH International Co., Ltd.

No.18, Tongji zhonglu, Beijing Economic&Technological Development Area

1.2 Manufacturer

HMD Global Oy

Karaportti 2 02610 Espoo FINLAND

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	GSM/WCDMA/LTE Mobile Phone
Brand Name	Nokia
Model Name	TA-1079
FCC ID	2AJOTTA-1079
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/HSPA+/LTE WLAN 2.4GHz 802.11b/g/n HT20 Bluetooth v2.1+EDR/ Bluetooth v4.2 LE
HW Version	HW0342
SW Version	000C_0_190
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. This is a variant report for TA-1079. the difference between TA-1056(FCC ID: 2AJOTTA-1056) and TA-1079(FCC ID: 2AJOTTA-1079) is change dual SIM card to single SIM card. Since the test result is not affected by the difference, all the test results were leveraged from original report which can be referred to Sporton Report Number FR7O2602-02C for model TA-1056.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to antenna	802.11b : 18.94 dBm (0.0783 W) 802.11g : 21.89 dBm (0.1545 W) 802.11n HT20 : 21.98 dBm (0.1578 W)
99% Occupied Bandwidth	802.11b : 12.74MHz 802.11g : 17.88MHz 802.11n HT20 : 18.58MHz
Antenna Type / Gain	PIFA Antenna with gain 2.5 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0) and the FCC designation No. is CN5013.

Test Site	Sporton International (Kunshan) Inc.			
Test Site Location	No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335 China TEL : +86-512-57900158 FAX : +86-512-57900958			
Test Site No.	Sporton Site No.			FCC Test Firm Registration No.
	TH01-KS	03CH03-KS	CO01-KS	630927

Note: The test site complies with ANSI C63.4 2014 requirement.



1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-

2.2 Test Mode


Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0


Test Cases	
AC Conducted Emission	Mode 1 :GSM850 Idle + Bluetooth Link + WLAN Link(2.4G) + Earphone + USB Cable (Charging from Adapter)

2.3 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8m
2.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
3.	Notebook	Lenovo	G480	N/A	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
4.	WLAN AP	LINKSYS	WRT600N	Q87-WRT600NV11	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P 1.8m
5.	SD Card	Kingston	8GB	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5.5 dB.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} \\ &= 5.5 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1MHz and set the Video bandwidth (VBW) = 3MHz.
6. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04 section 9.1.2 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures


1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.4.4 Test Setup








3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	Temperature :	24~26℃
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	01	Test Engineer :	Sam Zheng






Test Mode :	802.11b	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Sam Zheng


WLAN 802.11b Channel 06**100kHz PSD reference Level****Spurious Emission 30MHz~3GHz****Spurious Emission 2GHz~25GHz**




Test Mode :	802.11b	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	11	Test Engineer :	Sam Zheng

WLAN 802.11b Channel 11**100kHz PSD reference Level**


Date: 14.NOV.2017 11:03:30

High Channel Plot

Date: 14.NOV.2017 11:04:13

Spurious Emission 30MHz~3GHz

Date: 14.NOV.2017 11:04:56

Spurious Emission 2GHz~25GHz


Date: 14.NOV.2017 11:05:17



Test Mode :	802.11g	Temperature :	24~26°C
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	01	Test Engineer :	Sam Zheng


WLAN 802.11g Channel 01

100kHz PSD reference Level




Date: 14.NOV.2017 11:08:59

Low Channel Plot




Date: 14.NOV.2017 11:09:14

Spurious Emission 30MHz~3GHz



Date: 14.NOV.2017 11:09:35

Spurious Emission 2GHz~25GHz




Date: 14.NOV.2017 11:09:50




Test Mode :	802.11g	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Sam Zheng

WLAN 802.11g Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Test Mode :	802.11g	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	11	Test Engineer :	Sam Zheng

WLAN 802.11g Channel 11


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	01	Test Engineer :	Sam Zheng

WLAN 802.11n HT20 Channel 01


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Sam Zheng

WLAN 802.11n HT20 Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	11	Test Engineer :	Sam Zheng

WLAN 802.11n HT20 Channel 11


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.5.7 Duty Cycle

Please refer to Appendix C.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	22 ~24℃
Test Engineer :	Amos Zhang	Relative Humidity :	42~46%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link(2.4G) + Earphone + USB Cable (Charging from Adapter)		




Site : CO01-KS
Condition : FCC PART 15C LISN-L-171013-060103 LINE

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 *	0.175	47.31	-17.41	64.72	36.60	0.18	10.53	QP
2	0.175	31.01	-23.71	54.72	20.30	0.18	10.53	Average
3	0.182	46.30	-18.07	64.37	35.60	0.19	10.51	QP
4	0.182	30.90	-23.47	54.37	20.20	0.19	10.51	Average
5	0.205	41.26	-22.14	63.40	30.61	0.20	10.45	QP
6	0.205	25.86	-27.54	53.40	15.21	0.20	10.45	Average
7	0.229	40.55	-21.93	62.48	29.89	0.21	10.45	QP
8	0.229	25.95	-26.53	52.48	15.29	0.21	10.45	Average
9	0.256	37.75	-23.81	61.56	27.09	0.22	10.44	QP
10	0.256	22.25	-29.31	51.56	11.59	0.22	10.44	Average
11	0.283	35.95	-24.77	60.72	25.30	0.22	10.43	QP
12	0.283	21.95	-28.77	50.72	11.30	0.22	10.43	Average



Test Mode :	Mode 1	Temperature :	22 ~24℃
Test Engineer :	Amos Zhang	Relative Humidity :	42~46%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link(2.4G) + Earphone + USB Cable (Charging from Adapter)		



Site : CO01-KS
Condition : FCC PART 15C LISN-N-171013-060103 NEUTRAL

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.168	45.63	-19.45	65.08	34.80	0.28	10.55	QP
2	0.168	31.03	-24.05	55.08	20.20	0.28	10.55	Average
3 *	0.182	45.09	-19.28	64.37	34.30	0.28	10.51	QP
4	0.182	29.99	-24.38	54.37	19.20	0.28	10.51	Average
5	0.200	43.04	-20.58	63.62	32.30	0.28	10.46	QP
6	0.200	27.64	-25.98	53.62	16.90	0.28	10.46	Average
7	0.212	39.33	-23.81	63.14	28.60	0.28	10.45	QP
8	0.212	24.53	-28.61	53.14	13.80	0.28	10.45	Average
9	0.227	39.93	-22.64	62.57	29.20	0.28	10.45	QP
10	0.227	25.33	-27.24	52.57	14.60	0.28	10.45	Average
11	0.255	37.62	-23.98	61.60	26.90	0.28	10.44	QP
12	0.255	23.92	-27.68	51.60	13.20	0.28	10.44	Average



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Oct. 12, 2017	Nov. 24, 2017~ Nov. 28, 2017	Oct. 11, 2018	Conducted (TH01-KS)
Spectrum Analyzer	R&S	FSV30	101338	10Hz~30GHz	May 25, 2017	Nov. 24, 2017~ Nov. 28, 2017	May 24, 2018	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 19, 2017	Nov. 24, 2017~ Nov. 28, 2017	Jan. 18, 2018	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 19, 2017	Nov. 24, 2017~ Nov. 28, 2017	Jan. 18, 2018	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY564000 04	3Hz~8.5GHz; Max 30dBm	Oct. 19, 2017	Jan. 17, 2018	Oct. 18, 2018	Radiation (03CH03-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY551502 44	10Hz~44GHz	Apr. 18, 2017	Jan. 17, 2018	Apr. 17, 2018	Radiation (03CH03-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 22, 2017	Jan. 17, 2018	Oct. 21, 2018	Radiation (03CH03-KS)
Bilog Antenna	TeseQ	CBL6112D	35406	25MHz~2GHz	Apr. 22, 2017	Jan. 17, 2018	Apr. 21, 2018	Radiation (03CH03-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-135 6	1GHz~18GHz	Apr. 22, 2017	Jan. 17, 2018	Apr. 21, 2018	Radiation (03CH03-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA1702 49	15GHz~40GHz	Feb. 15, 2017	Jan. 17, 2018	Feb. 14, 2018	Radiation (03CH03-KS)
Amplifier	com-power	PA-103A	161069	1MHz~1000MHz / 32 dB	Apr. 18, 2017	Jan. 17, 2018	Apr. 17, 2018	Radiation (03CH03-KS)
Amplifier	MITEQ	TTA1840-35-HG	1887435	18GHz~40GHz	Oct. 12, 2017	Jan. 17, 2018	Oct. 11, 2018	Radiation (03CH03-KS)
high gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	2025788	1GHz~18GHz	Apr. 18, 2017	Jan. 17, 2018	Apr. 17, 2018	Radiation (03CH03-KS)
Amplifier	Agilent	8449B	3008A023 70	1GHz~26.5GHz	Oct. 12, 2017	Jan. 17, 2018	Oct. 11, 2018	Radiation (03CH03-KS)
AC Power Source	Chroma	61601	F1040900 04	N/A	NCR	Jan. 17, 2018	NCR	Radiation (03CH03-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Jan. 17, 2018	NCR	Radiation (03CH03-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Jan. 17, 2018	NCR	Radiation (03CH03-KS)
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz;	Apr. 20, 2017	Dec. 04, 2017	Apr. 19, 2018	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 13, 2017	Dec. 04, 2017	Oct. 12, 2018	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 13, 2017	Dec. 04, 2017	Oct. 12, 2018	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000 0811	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2017	Dec. 04, 2017	Oct. 11, 2018	Conduction (CO01-KS)

NCR: No Calibration Required

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.3dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.6dB
---	-------

Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.5dB
---	-------

Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.5dB
---	-------



Appendix A. Conducted Test Results

A1 - DTS Part

Test Engineer:	Sam Zheng	Temperature:	24~26	°C
Test Date:	2017/11/24~2017/11/28	Relative Humidity:	50~53	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band								
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	12.34	9.53	0.50	Pass
11b	1Mbps	1	6	2437	12.74	10.01	0.50	Pass
11b	1Mbps	1	11	2462	12.74	9.53	0.50	Pass
11g	6Mbps	1	1	2412	17.43	15.11	0.50	Pass
11g	6Mbps	1	6	2437	17.88	15.45	0.50	Pass
11g	6Mbps	1	11	2462	17.68	15.68	0.50	Pass
HT20	MCS0	1	1	2412	18.13	15.43	0.50	Pass
HT20	MCS0	1	6	2437	18.58	17.02	0.50	Pass
HT20	MCS0	1	11	2462	18.33	16.08	0.50	Pass

TEST RESULTS DATA
Peak Power Table

2.4GHz Band										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
11b	1Mbps	1	1	2412	18.74	30.00	2.50	21.24	36.00	Pass
11b	1Mbps	1	6	2437	18.94	30.00	2.50	21.44	36.00	Pass
11b	1Mbps	1	11	2462	18.53	30.00	2.50	21.03	36.00	Pass
11g	6Mbps	1	1	2412	21.76	30.00	2.50	24.26	36.00	Pass
11g	6Mbps	1	6	2437	21.89	30.00	2.50	24.39	36.00	Pass
11g	6Mbps	1	11	2462	20.92	30.00	2.50	23.42	36.00	Pass
HT20	MCS0	1	1	2412	21.92	30.00	2.50	24.42	36.00	Pass
HT20	MCS0	1	6	2437	21.98	30.00	2.50	24.48	36.00	Pass
HT20	MCS0	1	11	2462	21.18	30.00	2.50	23.68	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

2.4GHz Band						
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
11b	1Mbps	1	1	2412	0.00	15.73
11b	1Mbps	1	6	2437	0.00	16.04
11b	1Mbps	1	11	2462	0.00	15.76
11g	6Mbps	1	1	2412	0.11	13.17
11g	6Mbps	1	6	2437	0.11	13.39
11g	6Mbps	1	11	2462	0.11	12.36
HT20	MCS0	1	1	2412	0.12	13.15
HT20	MCS0	1	6	2437	0.12	13.43
HT20	MCS0	1	11	2462	0.12	12.73

TEST RESULTS DATA
Peak Power Density

2.4GHz Band								
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
11b	1Mbps	1	1	2412	-8.70	2.50	8.00	Pass
11b	1Mbps	1	6	2437	-7.73	2.50	8.00	Pass
11b	1Mbps	1	11	2462	-8.36	2.50	8.00	Pass
11g	6Mbps	1	1	2412	-11.61	2.50	8.00	Pass
11g	6Mbps	1	6	2437	-12.46	2.50	8.00	Pass
11g	6Mbps	1	11	2462	-12.26	2.50	8.00	Pass
HT20	MCS0	1	1	2412	-11.96	2.50	8.00	Pass
HT20	MCS0	1	6	2437	-11.93	2.50	8.00	Pass
HT20	MCS0	1	11	2462	-13.17	2.50	8.00	Pass



Appendix B. Radiated Spurious Emission

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2367.72	57.11	-16.89	74	54.99	31.25	7.52	36.65	394	91	P	H
		2389.95	46.55	-7.45	54	44.3	31.3	7.59	36.64	394	91	A	H
	*	2410	107.32	-	-	105.01	31.33	7.62	36.64	394	91	P	H
	*	2410	103.85	-	-	101.54	31.33	7.62	36.64	394	91	A	H
		2348.48	57.35	-16.65	74	55.32	31.22	7.48	36.67	400	46	P	V
		2389.95	46.34	-7.66	54	44.09	31.3	7.59	36.64	400	46	A	V
	*	2412	103.86	-	-	101.55	31.33	7.62	36.64	400	46	P	V
	*	2410	100.76	-	-	98.45	31.33	7.62	36.64	400	46	A	V
802.11b CH 06 2437MHz		2387.35	58.04	-15.96	74	55.8	31.3	7.59	36.65	380	97	P	H
		2389.95	46.58	-7.42	54	44.33	31.3	7.59	36.64	380	97	A	H
	*	2438	109.24	-	-	106.83	31.39	7.67	36.65	380	97	P	H
	*	2438	105.81	-	-	103.4	31.39	7.67	36.65	380	97	A	H
		2487.7	58.55	-15.45	74	56.02	31.47	7.74	36.68	380	97	P	H
		2484.58	47.42	-6.58	54	44.94	31.44	7.72	36.68	380	97	A	H
		2369.54	57.88	-16.12	74	55.71	31.27	7.55	36.65	385	44	P	V
		2389.69	46.33	-7.67	54	44.09	31.3	7.59	36.65	385	44	A	V
	*	2438	104.36	-	-	101.95	31.39	7.67	36.65	385	44	P	V
	*	2438	101.48	-	-	99.07	31.39	7.67	36.65	385	44	A	V
		2489.92	57.57	-16.43	74	55.04	31.47	7.74	36.68	385	44	P	V
		2485.06	46.79	-7.21	54	44.31	31.44	7.72	36.68	385	44	A	V



802.11b CH 11 2462MHz	*	2462	108.86	-	-	106.43	31.41	7.69	36.67	375	95	P	H
	*	2460	105.34	-	-	102.91	31.41	7.69	36.67	375	95	A	H
		2484.46	58.72	-15.28	74	56.24	31.44	7.72	36.68	375	95	P	H
		2483.51	48.61	-5.39	54	46.13	31.44	7.72	36.68	375	95	A	H
	*	2462	106.49	-	-	104.06	31.41	7.69	36.67	379	46	P	V
	*	2460	103.27	-	-	100.84	31.41	7.69	36.67	379	46	A	V
		2486.62	58.38	-15.62	74	55.9	31.44	7.72	36.68	379	46	P	V
		2483.51	47.39	-6.61	54	44.91	31.44	7.72	36.68	379	46	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01 2412MHz		4824	41.95	-32.05	74	59.33	35.65	11.5	64.53	300	0	P	H
		4824	41.17	-32.83	74	58.55	35.65	11.5	64.53	100	0	P	V
802.11b CH 06 2437MHz		4874	40.43	-33.57	74	57.86	35.61	11.56	64.6	100	0	P	H
		7308	38.12	-35.88	74	53.26	35.89	13.98	65.01	100	0	P	H
		4872	39.45	-34.55	74	56.88	35.61	11.56	64.6	100	360	P	V
		7308	38.56	-35.44	74	53.7	35.89	13.98	65.01	100	360	P	V
802.11b CH 11 2462MHz		4926	39.95	-34.05	74	57.44	35.57	11.62	64.68	100	360	P	H
		7386	38.15	-35.85	74	53.29	35.94	13.97	65.05	100	360	P	H
		4926	38.21	-35.79	74	55.7	35.57	11.62	64.68	100	0	P	V
		7386	37.84	-36.16	74	52.98	35.94	13.97	65.05	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		2389.95	57.81	-16.19	74	55.56	31.3	7.59	36.64	394	107	P	H
		2389.95	47.18	-6.82	54	44.93	31.3	7.59	36.64	394	107	A	H
	*	2410	105.18	-	-	102.87	31.33	7.62	36.64	394	107	P	H
	*	2410	97.58	-	-	95.27	31.33	7.62	36.64	394	107	A	H
		2384.62	57.66	-16.34	74	55.49	31.27	7.55	36.65	395	60	P	V
		2388.91	46.82	-7.18	54	44.58	31.3	7.59	36.65	395	60	A	V
	*	2412	103.36	-	-	101.05	31.33	7.62	36.64	395	60	P	V
	*	2410	95.83	-	-	93.52	31.33	7.62	36.64	395	60	A	V
802.11g CH 06 2437MHz		2385.92	57.29	-16.71	74	55.05	31.3	7.59	36.65	380	94	P	H
		2387.87	46.74	-7.26	54	44.5	31.3	7.59	36.65	380	94	A	H
	*	2440	105.99	-	-	103.58	31.39	7.67	36.65	380	94	P	H
	*	2438	97.98	-	-	95.57	31.39	7.67	36.65	380	94	A	H
		2490.1	58.21	-15.79	74	55.68	31.47	7.74	36.68	380	94	P	H
		2483.86	47.97	-6.03	54	45.49	31.44	7.72	36.68	380	94	A	H
		2349.26	58.07	-15.93	74	56.04	31.22	7.48	36.67	383	50	P	V
		2389.82	46.76	-7.24	54	44.51	31.3	7.59	36.64	383	50	A	V
	*	2438	104.75	-	-	102.34	31.39	7.67	36.65	383	50	P	V
	*	2438	96.99	-	-	94.58	31.39	7.67	36.65	383	50	A	V
		2484.28	57.8	-16.2	74	55.32	31.44	7.72	36.68	383	50	P	V
		2483.8	47.91	-6.09	54	45.43	31.44	7.72	36.68	383	50	A	V



802.11g CH 11 2462MHz	*	2462	105.37	-	-	102.94	31.41	7.69	36.67	374	95	P	H
	*	2460	97.55	-	-	95.12	31.41	7.69	36.67	374	95	A	H
		2484.04	64.28	-9.72	74	61.8	31.44	7.72	36.68	374	95	P	H
		2483.62	50.39	-3.61	54	47.91	31.44	7.72	36.68	374	95	A	H
	*	2460	106.03	-	-	103.6	31.41	7.69	36.67	379	51	P	V
	*	2460	98.52	-	-	96.09	31.41	7.69	36.67	379	51	A	V
		2483.62	65.55	-8.45	74	63.07	31.44	7.72	36.68	379	51	P	V
		2483.51	50.11	-3.89	54	47.63	31.44	7.72	36.68	379	51	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		4824	39.37	-34.63	74	56.75	35.65	11.5	64.53	300	0	P	H
		4824	36.94	-37.06	74	54.32	35.65	11.5	64.53	100	0	P	V
802.11g CH 06 2437MHz		4872	36.85	-37.15	74	54.28	35.61	11.56	64.6	300	0	P	H
		7308	36.94	-37.06	74	52.08	35.89	13.98	65.01	300	0	P	H
		4872	36.43	-37.57	74	53.86	35.61	11.56	64.6	100	0	P	V
		7308	38.01	-35.99	74	53.15	35.89	13.98	65.01	100	0	P	V
802.11g CH 11 2462MHz		4926	37.84	-36.16	74	55.33	35.57	11.62	64.68	300	0	P	H
		7386	37.74	-36.26	74	52.88	35.94	13.97	65.05	300	0	P	H
		4926	36.56	-37.44	74	54.05	35.57	11.62	64.68	100	0	P	V
		7386	37.8	-36.2	74	52.94	35.94	13.97	65.05	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		2389.95	58.28	-15.72	74	56.03	31.3	7.59	36.64	303	110	P	H
		2389.95	47.03	-6.97	54	44.78	31.3	7.59	36.64	303	110	A	H
	*	2410	105	-	-	102.69	31.33	7.62	36.64	303	110	P	H
	*	2410	97.44	-	-	95.13	31.33	7.62	36.64	303	110	A	H
		2336.52	57.33	-16.67	74	55.31	31.22	7.48	36.68	400	49	P	V
		2389.95	46.86	-7.14	54	44.61	31.3	7.59	36.64	400	49	A	V
	*	2412	103.14	-	-	100.83	31.33	7.62	36.64	400	49	P	V
	*	2412	95.37	-	-	93.06	31.33	7.62	36.64	400	49	A	V
802.11n HT20 CH 06 2437MHz		2319.75	57.31	-16.69	74	55.36	31.19	7.44	36.68	377	99	P	H
		2382.54	46.97	-7.03	54	44.8	31.27	7.55	36.65	377	99	A	H
	*	2438	106.71	-	-	104.3	31.39	7.67	36.65	377	99	P	H
	*	2438	99.27	-	-	96.86	31.39	7.67	36.65	377	99	A	H
		2488.9	58.77	-15.23	74	56.24	31.47	7.74	36.68	377	99	P	H
		2484.16	48.58	-5.42	54	46.1	31.44	7.72	36.68	377	99	A	H
		2380.98	57.34	-16.66	74	55.17	31.27	7.55	36.65	384	64	P	V
		2388.39	46.76	-7.24	54	44.52	31.3	7.59	36.65	384	64	A	V
	*	2438	105.04	-	-	102.63	31.39	7.67	36.65	384	64	P	V
	*	2438	97.18	-	-	94.77	31.39	7.67	36.65	384	64	A	V
		2483.56	58.19	-15.81	74	55.71	31.44	7.72	36.68	384	64	P	V
		2483.8	47.94	-6.06	54	45.46	31.44	7.72	36.68	384	64	A	V



802.11n HT20 CH 11 2462MHz	*	2460	107.77	-	-	105.34	31.41	7.69	36.67	374	102	P	H
	*	2462	99.24	-	-	96.81	31.41	7.69	36.67	374	102	A	H
		2483.62	69.03	-4.97	74	66.55	31.44	7.72	36.68	374	102	P	H
		2483.62	52.56	-1.44	54	50.08	31.44	7.72	36.68	374	102	A	H
	*	2456	105.43	-	-	103	31.41	7.69	36.67	380	61	P	V
	*	2460	97.75	-	-	95.32	31.41	7.69	36.67	380	61	A	V
		2484.46	65.19	-8.81	74	62.71	31.44	7.72	36.68	380	61	P	V
		2483.51	50.88	-3.12	54	48.4	31.44	7.72	36.68	380	61	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		4824	36.32	-37.68	74	53.7	35.65	11.5	64.53	100	360	P	H
		4824	36.64	-37.36	74	54.02	35.65	11.5	64.53	100	0	P	V
802.11n HT20 CH 06 2437MHz		4872	34.84	-39.16	74	52.27	35.61	11.56	64.6	100	360	P	H
		7308	37.03	-36.97	74	52.17	35.89	13.98	65.01	100	360	P	H
		4872	34.11	-39.89	74	51.54	35.61	11.56	64.6	100	0	P	V
		7308	38.04	-35.96	74	53.18	35.89	13.98	65.01	100	0	P	V
802.11n HT20 CH 11 2462MHz		4926	35.67	-38.33	74	53.16	35.57	11.62	64.68	100	0	P	H
		7386	36.48	-37.52	74	51.62	35.94	13.97	65.05	100	0	P	H
		4926	35.34	-38.66	74	52.83	35.57	11.62	64.68	100	360	P	V
		7386	37.1	-36.9	74	52.24	35.94	13.97	65.05	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

Emission below 1GHz

2.4GHz WIFI 802.11n HT20 (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11n HT20 LF		32.91	24.89	-15.11	40	30.7	24.62	0.61	31.04	100	360	P	H
		99.84	17.47	-26.03	43.5	29.3	17.8	1.07	30.7	-	-	P	H
		184.23	18.02	-25.48	43.5	31.39	16.2	1.47	31.04	-	-	P	H
		216.24	21.29	-24.71	46	34.42	16.42	1.58	31.13	-	-	P	H
		378.23	22.64	-23.36	46	30.02	22	2.12	31.5	-	-	P	H
		511.12	23.95	-22.05	46	28.77	24.25	2.51	31.58	-	-	P	H
		30	23.84	-16.16	40	28.07	26.3	0.57	31.1	100	0	P	V
		72.68	19.54	-20.46	40	35.87	14.16	0.91	31.4	-	-	P	V
		92.08	21.23	-22.27	43.5	33.8	17.06	1.05	30.68	-	-	P	V
		288.02	22.47	-23.53	46	32.84	19.2	1.86	31.43	-	-	P	V
		305.48	23.78	-22.22	46	33.58	19.78	1.92	31.5	-	-	P	V
		323.91	26.34	-19.66	46	35.5	20.37	1.97	31.5	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix C. Duty Cycle Plots


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	100	-	-	10Hz
802.11g	97.46	1.391	0.719	1kHz
802.11n HT20	97.30	1.304	0.767	1kHz

802.11b





802.11g



802.11n HT20

