

FCC Test Report

(PART 24)

Report No.: RF180626C02-1

FCC ID: 2AJOTTA-1096

Test Model: TA-1096

Received Date: Jun. 26, 2018

Test Date: Jul. 20, 2018

Issued Date: Jul. 31, 2018

Applicant: HMD Global Oy

Address: Karaportti 2, 02610 Espoo, Finland

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
(R.O.C)

Test Location (1): No. 19, Hwa Ya 2nd Rd, Wen Hwa Vil, Kwei Shan Dist., Taoyuan City
33383, Taiwan (R.O.C)

Test Location (2): No.215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan,
R.O.C

**FCC Registration /
Designation Number:** 427177 / TW0011



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 Summary of Test Results.....	5
2.1 Measurement Uncertainty.....	5
2.2 Test Site and Instruments	6
3 General Information	8
3.1 General Description of EUT	8
3.2 Configuration of System under Test.....	9
3.2.1 Description of Support Units.....	9
3.3 Test Mode Applicability and Tested Channel Detail	10
3.4 EUT Operating Conditions	11
3.5 General Description of Applied Standards.....	11
4 Test Types and Results	12
4.1 Output Power Measurement.....	12
4.1.1 Limits of Output Power Measurement	12
4.1.2 Test Procedures.....	12
4.1.3 Test Setup.....	13
4.1.4 Test Results	14
4.2 Radiated Emission Measurement.....	15
4.2.1 Limits of Radiated Emission Measurement	15
4.2.2 Test Procedure	15
4.2.3 Deviation from Test Standard	15
4.2.4 Test Setup.....	16
4.2.5 Test Results	17
5 Pictures of Test Arrangements.....	29
Appendix – Information on the Testing Laboratories	30
Annex A – Test Report for TA-1085 (Dual SIM)	31

Release Control Record

Issue No.	Description	Date Issued
RF180626C02-1	Original Release	Jul. 31, 2018

1 Certificate of Conformity

Product: Smart Phone

Brand: NOKIA

Test Model: TA-1096

Sample Status: Engineering Sample

Applicant: HMD Global Oy

Test Date: Jul. 20, 2018

Standards: FCC Part 24, Subpart E

This report is issued as a supplementary report to BV CPS report no.: RF180626C09-1. This report shall be used by combining with its original report.

Prepared by :  , **Date:** Jul. 31, 2018
Ivonne Wu / Supervisor

Approved by :  , **Date:** Jul. 31, 2018
Dylan Chiou / Project Engineer

2 Summary of Test Results

Applied Standard: FCC Part 24 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 24.232	Effective Isotropic Radiated Power	Pass	Meet the requirement of limit.
2.1047	Modulation Characteristics	N/A	Refer to Note
2.1046 24.232(d)	Peak to Average Ratio	N/A	Refer to Note
2.1055 24.235	Frequency Stability	N/A	Refer to Note
2.1049 24.238(b)	Occupied Bandwidth	N/A	Refer to Note
24.238(b)	Band Edge Measurements	N/A	Refer to Note
2.1051 24.238	Conducted Spurious Emissions	N/A	Refer to Note
2.1053 24.238	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -23.65 dB at 5729.40 MHz.

Note: Only EIRP and radiated spurious emissions tests had been performed for the addendum. Refer to original report for other test data.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Radiated Emissions up to 1 GHz	30 MHz ~ 200 MHz	2.0153 dB
	200 MHz ~ 1000 MHz	2.0224 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	1.0121 dB
	18 GHz ~ 40 GHz	1.1508 dB

2.2 Test Site and Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent Technologies	N9010A	MY52220314	Nov. 24, 2017	Nov. 23, 2018
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Jan. 11, 2018	Jan. 10, 2019
Double Ridge Guide Horn Antenna EMCO	3115	5619	Nov. 30, 2017	Nov. 29, 2018
BILOG Antenna SCHWARZBECK	VULB 9168	9168-153	Dec. 06, 2017	Dec. 05, 2018
HORN Antenna Schwarzbeck	BBHA 9120D	9120D-969	Dec. 12, 2017	Dec. 11, 2018
Fixed Attenuator Woken	00801A1GGAM02Y	NA	May 17, 2018	May 16, 2019
MXG Vector signal generator Agilent	N5182B	MY53050430	Oct. 24, 2017	Oct. 23, 2018
Preamplifier Agilent	310N	187226	Jun. 19, 2018	Jun. 18, 2019
Preamplifier Agilent	83017A	MY39501357	Jun. 19, 2018	Jun. 18, 2019
RF signal cable ETS-LINDGREN	5D-FB	Cable-CH1-01(RF C-SMS-100-SMS- 120+RFC-SMS-1 00-SMS-400)	Jun. 19, 2018	Jun. 18, 2019
RF signal cable ETS-LINDGREN	8D-FB	Cable-CH1-02(RF C-SMS-100-SMS- 24)	Jun. 19, 2018	Jun. 18, 2019
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
Software BV ADT	E3 8.130425b	NA	NA	NA
Antenna Tower MF	NA	NA	NA	NA
Turn Table MF	NA	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Communications Tester-Wireless Agilent	8960 Series 10	MY53201073	Jun. 28, 2017	Jun. 27, 2019
Radio Communication Analyzer Anritsu	MT8820C	6201010284	Dec. 28, 2017	Dec. 27, 2018
Temperature & Humidity Chamber	GTH-120-40-CP-AR	MAA1306-019	Sep. 08, 2017	Sep. 07, 2018
DC Power Supply Topward	33010D	807748	Oct. 25, 2016	Oct. 24, 2018
Digital Multimeter Fluke	87-III	70360742	Jun. 29, 2018	Jun. 28, 2019

- Note:
1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HsinTien Chamber 1.
 3. The horn antenna and preamplifier (model: 83017A) are used only for the measurement of emission frequency above 1 GHz if tested.
 4. The IC Site Registration No. is IC7450I-1.

3 General Information

3.1 General Description of EUT

Product	Smart Phone	
Brand	NOKIA	
Test Model	TA-1096	
Status of EUT	Engineering Sample	
Power Supply Rating	5.0 Vdc or 9 Vdc or 12 Vdc (adapter) 5.0 Vdc (host equipment) 3.85 Vdc (Li-ion battery)	
Modulation Type	GSM/GPRS	GMSK
	EDGE	GMSK, 8PSK
	WCDMA	QPSK
	LTE	QPSK, 16QAM
Frequency Range	GSM/GPRS/EDGE	1850.2 ~ 1909.8 MHz
	WCDMA	1852.4 ~ 1907.6 MHz
	LTE Band 2 (Channel Bandwidth: 1.4 MHz)	1850.7 ~ 1909.3 MHz
	LTE Band 2 (Channel Bandwidth: 3 MHz)	1851.5 ~ 1908.5 MHz
	LTE Band 2 (Channel Bandwidth: 5 MHz)	1852.5 ~ 1907.5 MHz
	LTE Band 2 (Channel Bandwidth: 10 MHz)	1855.0 ~ 1905.0 MHz
	LTE Band 2 (Channel Bandwidth: 15 MHz)	1857.5 ~ 1902.5 MHz
	LTE Band 2 (Channel Bandwidth: 20 MHz)	1860.0 ~ 1900.0 MHz
Max. EIRP Power	GSM/GPRS	966.05 mW
	LTE Band 2 (Channel Bandwidth: 20 MHz)	207.97 mW
Antenna Type	PIFA Antenna with 0.62 dBi gain	
Accessory Device	Refer to Note as below	
Data Cable Supplied	Refer to Note as below	

Note:


1. This report is issued as a supplementary report to BV CPS report no.: RF180626C09-1. The difference is listed as below. Only EIRP and radiated spurious emissions tests were verified in this report.

Report No.	FCC ID	Model	Difference
RF180626C09-1	2AJOTTA-1085	TA-1085	Dual SIM
RF180626C02-1	2AJOTTA-1096	TA-1096	Single SIM
* The models have the same layout, circuit, and components, but different SIM tray.			


2. There're 2 configurations for the EUT listed as below.
Main Sample: EUT + Battery 1
2nd Sample: EUT + Battery 2
✧ Only the worst test data of main sample was presented in the report.
3. The EUT's accessories list refers to Ext. Pho.
4. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

3.2 Configuration of System under Test

<Radiated Emission Test>



<E.I.R.P. Test>



3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis, and antenna ports.

The worst case was found when positioned as the table below. Following channel(s) was (were) selected for the final test as listed below:

EUT Configure Mode	Description
A	Main Sample
B	2 nd Sample

SIM	Band	EIRP	Radiated Emission
1	GSM	Z-plane	Y-axis
	LTE Band 2	Z-plane	Y-axis

GSM

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Mode
A	EIRP	512 to 810	512, 661, 810	GSM
A	Radiated Emission	512 to 810	512, 661, 810	GSM

LTE Band 2

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
A	EIRP	18700 to 19100	18700, 18900, 19100	20 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
A	Radiated Emission	18700 to 19100	18700, 18900, 19100	20 MHz	QPSK	1 RB / 0 RB Offset

Test Condition:

Test Item	Environmental Conditions	Input Power	Tested By
EIRP	26 deg. C, 58 % RH	3.85 Vdc	Karl Lee
Radiated Emission	25 deg. C, 65 % RH	120 Vac, 60 Hz	Karl Lee

3.4 EUT Operating Conditions

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 24

KDB 971168 D01 Power Meas License Digital Systems v03r01

ANSI/TIA/EIA-603-E 2016

ANSI 63.26-2015

NOTE: All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Output Power Measurement

4.1.1 Limits of Output Power Measurement

Mobile / Portable station are limited to 2 watts e.i.r.p.

4.1.2 Test Procedures


EIRP / ERP Measurement:

- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 1 MHz for GSM and 10 MHz for LTE mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step b. Record the power level of S.G.
- d. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, $E.R.P \text{ power} = E.I.R.P \text{ power} - 2.15 \text{ dB}$.


4.1.3 Test Setup

EIRP / ERP Measurement:

<Radiated Emission below or equal 1 GHz>



<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.4 Test Results

EIRP Power (dBm)

Mode A

GSM							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	512	1850.2	-8.85	38.19	29.34	859.01	H
	661	1880.0	-8.99	38.70	29.71	935.41	
	810	1909.8	-9.50	39.35	29.85	966.05	
	512	1850.2	-14.62	38.48	23.86	243.22	V
	661	1880.0	-14.76	38.59	23.83	241.77	
	810	1909.8	-14.91	38.87	23.96	248.89	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 2							
Channel Bandwidth: 20 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	18700	1860.0	-21.52	44.70	23.18	207.97	H
	18900	1880.0	-21.62	44.70	23.08	203.24	
	19100	1900.0	-21.45	44.57	23.12	205.26	
	18700	1860.0	-26.85	44.27	17.42	55.21	V
	18900	1880.0	-26.91	44.87	17.96	62.52	
	19100	1900.0	-26.76	44.61	17.85	61.00	
Channel Bandwidth: 20 MHz / 16QAM							
Z	18700	1860.0	-22.21	44.70	22.49	177.42	H
	18900	1880.0	-22.36	44.70	22.34	171.40	
	19100	1900.0	-22.01	44.57	22.56	180.43	
	18700	1860.0	-27.89	44.27	16.38	43.45	V
	18900	1880.0	-27.91	44.87	16.96	49.66	
	19100	1900.0	-27.83	44.61	16.78	47.68	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

4.2 Radiated Emission Measurement

4.2.1 Limits of Radiated Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit is equal to -13 dBm.

4.2.2 Test Procedure

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G.
- c. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn.
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.R.P power - 2.15 dB.


NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz/3 MHz.

4.2.3 Deviation from Test Standard


No deviation.

4.2.4 Test Setup

<Radiated Emission below or equal 1 GHz>



<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.5 Test Results

Mode A

GSM:

Low Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-07-20



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : PCS 1900_Link_CH512
Tested by: Karl Lee

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3700.40	-51.49	-67.37	-13.00	-38.49	15.88	Peak
2 pp	5550.60	-45.24	-65.58	-13.00	-32.24	20.34	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-07-20



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : PCS 1900_Link_CH512
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3700.40	-52.16	-68.04	-13.00	-39.16	15.88	Peak
2 pp	5550.60	-39.65	-59.99	-13.00	-26.65	20.34	Peak

Middle Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-07-20



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : PCS 1900_Link_CH661
Tested by: Karl Lee

		Read	Limit	Over			
Freq	Level	Level	Line	Limit	Factor	Remark	
MHz	dBm	dBm	dBm	dB	dB		
1	3760.00	-51.89	-68.03	-13.00	-38.89	16.14	Peak
2 pp	5640.00	-45.54	-66.01	-13.00	-32.54	20.47	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-07-20



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : PCS 1900_Link_CH661
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3760.00	-51.85	-67.99	-13.00	-38.85	16.14	Peak
2 pp	5640.00	-38.89	-59.36	-13.00	-25.89	20.47	Peak


High Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 13



Site : 966 chamber 1
 Condition: PART 22/24 Horizontal
 Remark : PCS 1900_Link_CH810
 Tested by: Karl Lee

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	115.59	-79.53	-70.96	-13.00	-66.53	-8.57	Peak
2	219.00	-53.32	-47.40	-13.00	-40.32	-5.92	Peak
3	258.96	-76.30	-70.71	-13.00	-63.30	-5.59	Peak
4	444.90	-72.94	-69.20	-13.00	-59.94	-3.74	Peak
5	651.40	-69.60	-69.46	-13.00	-56.60	-0.14	Peak
6	886.60	-67.51	-70.01	-13.00	-54.51	2.50	Peak
7	3819.60	-51.00	-67.50	-13.00	-38.00	16.50	Peak
8 pp	5729.40	-45.16	-65.50	-13.00	-32.16	20.34	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 14

Date: 2018-07-20



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : PCS 1900_Link_CH810
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	89.40	-78.56	-67.78	-13.00	-65.56	-10.78	Peak
2	186.33	-70.25	-64.58	-13.00	-57.25	-5.67	Peak
3	267.60	-75.51	-69.84	-13.00	-62.51	-5.67	Peak
4	419.00	-74.79	-71.62	-13.00	-61.79	-3.17	Peak
5	655.60	-70.14	-69.98	-13.00	-57.14	-0.16	Peak
6	801.20	-68.84	-70.84	-13.00	-55.84	2.00	Peak
7	3819.60	-51.98	-68.48	-13.00	-38.98	16.50	Peak
8 pp	5729.40	-36.65	-56.99	-13.00	-23.65	20.34	Peak

LTE Band 2
Channel Bandwidth: 20 MHz / QPSK
Low Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 13

Date: 2018-07-20



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : LTE_Band 2_Link_CH18700
Tested by: Karl Lee

		Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor Remark
	MHz	dBm	dBm	dBm	dB	dB
1	94.53	-77.34	-66.94	-13.00	-64.34	-10.40 Peak
2	150.15	-70.75	-62.80	-13.00	-57.75	-7.95 Peak
3	243.30	-61.59	-55.99	-13.00	-48.59	-5.60 Peak
4	405.70	-74.31	-71.44	-13.00	-61.31	-2.87 Peak
5	624.80	-70.96	-71.11	-13.00	-57.96	0.15 Peak
6	781.60	-69.11	-69.91	-13.00	-56.11	0.80 Peak
7 pp	3720.00	-49.12	-65.09	-13.00	-36.12	15.97 Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 14

Date: 2018-07-20



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH18700
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	82.65	-82.90	-71.35	-13.00	-69.90	-11.55	Peak
2	154.47	-72.65	-64.81	-13.00	-59.65	-7.84	Peak
3	230.61	-72.37	-66.60	-13.00	-59.37	-5.77	Peak
4	402.90	-73.12	-70.32	-13.00	-60.12	-2.80	Peak
5	556.20	-70.69	-69.27	-13.00	-57.69	-1.42	Peak
6	970.60	-65.24	-70.41	-13.00	-52.24	5.17	Peak
7 pp	3720.00	-52.00	-67.97	-13.00	-39.00	15.97	Peak

Middle Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-07-20



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : LTE_Band 2_Link_CH18900
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3760.00	-51.00	-67.14	-13.00	-38.00	16.14	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-07-20



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH18900
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3760.00	-51.85	-67.99	-13.00	-38.85	16.14	Peak

High Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-07-20



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : LTE_Band 2_Link_CH19100
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3800.00	-51.54	-67.95	-13.00	-38.54	16.41	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-07-20



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH19100
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3800.00	-50.99	-67.40	-13.00	-37.99	16.41	Peak

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---

Annex A – Test Report for TA-1085 (Dual SIM)

FCC Test Report

(PART 24)

Report No.: RF180626C09-1

FCC ID: 2AJOTTA-1085

Test Model: TA-1085

Received Date: Jun. 26, 2018

Test Date: Jul. 05, 2018 ~ Jul. 20, 2018

Issued Date: Jul. 31, 2018

Applicant: HMD Global Oy

Address: Karaportti 2, 02610 Espoo, Finland

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
(R.O.C)

Test Location (1): No. 19, Hwa Ya 2nd Rd, Wen Hwa Vil, Kwei Shan Dist., Taoyuan City
33383, Taiwan (R.O.C)

Test Location (2): No.215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan,
R.O.C

**FCC Registration /
Designation Number:** 427177 / TW0011



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	4
1 Certificate of Conformity	5
2 Summary of Test Results.....	6
2.1 Measurement Uncertainty.....	6
2.2 Test Site and Instruments	7
3 General Information	9
3.1 General Description of EUT	9
3.2 Configuration of System under Test.....	10
3.2.1 Description of Support Units	10
3.3 Test Mode Applicability and Tested Channel Detail	11
3.4 EUT Operating Conditions	14
3.5 General Description of Applied Standards.....	14
4 Test Types and Results	15
4.1 Output Power Measurement.....	15
4.1.1 Limits of Output Power Measurement	15
4.1.2 Test Procedures.....	15
4.1.3 Test Setup.....	16
4.1.4 Test Results	17
4.2 Modulation Characteristics Measurement	24
4.2.1 Limits of Modulation Characteristics	24
4.2.2 Test Setup.....	24
4.2.3 Test Procedure	24
4.2.4 Test Results	25
4.3 Frequency Stability Measurement	26
4.3.1 Limits of Frequency Stability Measurement	26
4.3.2 Test Procedure	26
4.3.3 Test Setup.....	26
4.3.4 Test Results	27
4.4 Occupied Bandwidth Measurement.....	36
4.4.1 Test Procedure	36
4.4.2 Test Setup.....	36
4.4.3 Test Result.....	37
4.5 Band Edge Measurement	41
4.5.1 Limits of Band Edge Measurement	41
4.5.2 Test Setup.....	41
4.5.3 Test Procedures.....	41
4.5.4 Test Results	42
4.6 Peak to Average Ratio	49
4.6.1 Limits of Peak to Average Ratio Measurement	49
4.6.2 Test Setup.....	49
4.6.3 Test Procedures.....	49
4.6.4 Test Results	50
4.7 Conducted Spurious Emissions	54
4.7.1 Limits of Conducted Spurious Emissions Measurement.....	54
4.7.2 Test Setup.....	54
4.7.3 Test Procedure	54
4.7.4 Test Results	55
4.8 Radiated Emission Measurement.....	82
4.8.1 Limits of Radiated Emission Measurement	82
4.8.2 Test Procedure	82
4.8.3 Deviation from Test Standard	82
4.8.4 Test Setup.....	83
4.8.5 Test Results	84

5 Pictures of Test Arrangements.....	132
Appendix – Information on the Testing Laboratories	133

Release Control Record

Issue No.	Description	Date Issued
RF180626C09-1	Original Release	Jul. 31, 2018

1 Certificate of Conformity

Product: Smart Phone

Brand: NOKIA

Test Model: TA-1085

Sample Status: Engineering Sample

Applicant: HMD Global Oy

Test Date: Jul. 05, 2018 ~ Jul. 20, 2018

Standards: FCC Part 24, Subpart E

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by :



Date:

Jul. 31, 2018

Ivonne Wu / Supervisor

Approved by :



Date:

Jul. 31, 2018

Dylan Chiou / Project Engineer

2 Summary of Test Results

Applied Standard: FCC Part 24 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 24.232	Effective Isotropic Radiated Power	Pass	Meet the requirement of limit.
2.1047	Modulation Characteristics	Pass	Meet the requirement.
2.1046 24.232(d)	Peak to Average Ratio	Pass	Meet the requirement of limit.
2.1055 24.235	Frequency Stability	Pass	Meet the requirement of limit.
2.1049 24.238(b)	Occupied Bandwidth	Pass	Meet the requirement of limit.
24.238(b)	Band Edge Measurements	Pass	Meet the requirement of limit.
2.1051 24.238	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 24.238	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -21.74 dB at 5729.40 MHz.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) ($\pm$)
Radiated Emissions up to 1 GHz	30 MHz ~ 200 MHz	2.0153 dB
	200 MHz ~ 1000 MHz	2.0224 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	1.0121 dB
	18 GHz ~ 40 GHz	1.1508 dB

2.2 Test Site and Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent Technologies	N9010A	MY52220314	Nov. 24, 2017	Nov. 23, 2018
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Jan. 11, 2018	Jan. 10, 2019
Double Ridge Guide Horn Antenna EMCO	3115	5619	Nov. 30, 2017	Nov. 29, 2018
BILOG Antenna SCHWARZBECK	VULB 9168	9168-153	Dec. 06, 2017	Dec. 05, 2018
HORN Antenna Schwarzbeck	BBHA 9120D	9120D-969	Dec. 12, 2017	Dec. 11, 2018
Fixed Attenuator Woken	00801A1GGAM02Y	NA	May 17, 2018	May 16, 2019
MXG Vector signal generator Agilent	N5182B	MY53050430	Oct. 24, 2017	Oct. 23, 2018
Preamplifier Agilent	310N	187226	Jun. 19, 2018	Jun. 18, 2019
Preamplifier Agilent	83017A	MY39501357	Jun. 19, 2018	Jun. 18, 2019
RF signal cable ETS-LINDGREN	5D-FB	Cable-CH1-01(RF C-SMS-100-SMS- 120+RFC-SMS-1 00-SMS-400)	Jun. 19, 2018	Jun. 18, 2019
RF signal cable ETS-LINDGREN	8D-FB	Cable-CH1-02(RF C-SMS-100-SMS- 24)	Jun. 19, 2018	Jun. 18, 2019
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
Software BV ADT	E3 8.130425b	NA	NA	NA
Antenna Tower MF	NA	NA	NA	NA
Turn Table MF	NA	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Communications Tester-Wireless Agilent	8960 Series 10	MY53201073	Jun. 28, 2017	Jun. 27, 2019
Radio Communication Analyzer Anritsu	MT8820C	6201010284	Dec. 28, 2017	Dec. 27, 2018
Temperature & Humidity Chamber	GTH-120-40-CP-AR	MAA1306-019	Sep. 08, 2017	Sep. 07, 2018
DC Power Supply Topward	33010D	807748	Oct. 25, 2016	Oct. 24, 2018
Digital Multimeter Fluke	87-III	70360742	Jun. 29, 2018	Jun. 28, 2019

- Note:
1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HsinTien Chamber 1.
 3. The horn antenna and preamplifier (model: 83017A) are used only for the measurement of emission frequency above 1 GHz if tested.
 4. The IC Site Registration No. is IC7450I-1.

3 General Information

3.1 General Description of EUT


Product	Smart Phone	
Brand	NOKIA	
Test Model	TA-1085	
Status of EUT	Engineering Sample	
Power Supply Rating	5.0 Vdc or 9 Vdc or 12 Vdc (adapter) 5.0 Vdc (host equipment) 3.85 Vdc (Li-ion battery)	
Modulation Type	GSM/GPRS	GMSK
	EDGE	GMSK, 8PSK
	WCDMA	QPSK
	LTE	QPSK, 16QAM
Frequency Range	GSM/GPRS/EDGE	1850.2 ~ 1909.8 MHz
	WCDMA	1852.4 ~ 1907.6 MHz
	LTE Band 2 (Channel Bandwidth: 1.4 MHz)	1850.7 ~ 1909.3 MHz
	LTE Band 2 (Channel Bandwidth: 3 MHz)	1851.5 ~ 1908.5 MHz
	LTE Band 2 (Channel Bandwidth: 5 MHz)	1852.5 ~ 1907.5 MHz
	LTE Band 2 (Channel Bandwidth: 10 MHz)	1855.0 ~ 1905.0 MHz
	LTE Band 2 (Channel Bandwidth: 15 MHz)	1857.5 ~ 1902.5 MHz
	LTE Band 2 (Channel Bandwidth: 20 MHz)	1860.0 ~ 1900.0 MHz
Max. EIRP Power	GSM/GPRS	1140.25 mW
	EDGE	405.51 mW
	WCDMA	256.45 mW
	LTE Band 2 (Channel Bandwidth: 1.4 MHz)	254.68 mW
	LTE Band 2 (Channel Bandwidth: 3 MHz)	255.27 mW
	LTE Band 2 (Channel Bandwidth: 5 MHz)	255.86 mW
	LTE Band 2 (Channel Bandwidth: 10 MHz)	256.45 mW
	LTE Band 2 (Channel Bandwidth: 15 MHz)	257.04 mW
	LTE Band 2 (Channel Bandwidth: 20 MHz)	258.23 mW
Emission Designator	GSM/GPRS	248KGXW
	EDGE	248KG7W
	WCDMA	4M15F9W
	LTE Band 2 (Channel Bandwidth: 1.4 MHz)	1M09W7D
	LTE Band 2 (Channel Bandwidth: 3 MHz)	2M70G7D
	LTE Band 2 (Channel Bandwidth: 5 MHz)	4M50W7D
	LTE Band 2 (Channel Bandwidth: 10 MHz)	8M99W7D
	LTE Band 2 (Channel Bandwidth: 15 MHz)	13M5G7D
	LTE Band 2 (Channel Bandwidth: 20 MHz)	18M0W7D
Antenna Type	PIFA Antenna with 0.62 dBi gain	
Accessory Device	Refer to Note as below	
Data Cable Supplied	Refer to Note as below	

Note:


- There're 2 configurations for the EUT listed as below.
Main Sample: EUT + Battery 1
2nd Sample: EUT + Battery 2
✧ Only the worst test data was presented in the report.
- The EUT's accessories list refers to Ext. Pho.
- The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

3.2 Configuration of System under Test

<Radiated Emission Test>



<E.I.R.P. Test>



3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis, and antenna ports.

The worst case was found when positioned as the table below. Following channel(s) was (were) selected for the final test as listed below:

EUT Configure Mode	Description
A	Main Sample
B	2 nd Sample

SIM	Band	EIRP	Radiated Emission
1	GSM	Z-plane	Y-axis
	EDGE	Z-plane	Y-axis
	WCDMA	Z-plane	Y-axis
	LTE Band 2	Z-plane	Y-axis

GSM

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Mode
A	EIRP	512 to 810	512, 661, 810	GSM, EDGE
B		512 to 810	512, 661, 810	GSM
A	Modulation Characteristics	512 to 810	661	GSM, EDGE
A	Frequency Stability	512 to 810	512, 810	GSM, EDGE
A	Occupied Bandwidth	512 to 810	512, 661, 810	GSM, EDGE
A	Band Edge	512 to 810	512, 810	GSM, EDGE
A	Peak to Average Ratio	512 to 810	512, 661, 810	GSM, EDGE
A	Conducted Emission	512 to 810	512, 661, 810	GSM, EDGE
A	Radiated Emission	512 to 810	512, 661, 810	GSM, EDGE
B		512 to 810	512, 661, 810	GSM

WCDMA

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Mode
A	EIRP	9262 to 9538	9262, 9400, 9538	WCDMA
A	Modulation Characteristics	9262 to 9538	9400	WCDMA
A	Frequency Stability	9262 to 9538	9262, 9538	WCDMA
A	Occupied Bandwidth	9262 to 9538	9262, 9400, 9538	WCDMA
A	Band Edge	9262 to 9538	9262, 9538	WCDMA
A	Peak to Average Ratio	9262 to 9538	9262, 9400, 9538	WCDMA
A	Conducted Emission	9262 to 9538	9262, 9400, 9538	WCDMA
A	Radiated Emission	9262 to 9538	9262, 9400, 9538	WCDMA

LTE Band 2

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
A	EIRP	18607 to 19193	18607, 18900, 19193	1.4 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
B		18700 to 19100	18700, 18900, 19100	20 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
A	Modulation Characteristics	18700 to 19100	18900	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset
A	Frequency Stability	18607 to 19193	18607, 19193	1.4 MHz	QPSK	1 RB / 0 RB Offset
		18615 to 19185	18615, 19185	3 MHz	QPSK	1 RB / 0 RB Offset
		18625 to 19175	18625, 19175	5 MHz	QPSK	1 RB / 0 RB Offset
		18650 to 19150	18650, 19150	10 MHz	QPSK	1 RB / 0 RB Offset
		18675 to 19125	18675, 19125	15 MHz	QPSK	1 RB / 0 RB Offset
		18700 to 19100	18700, 19100	20 MHz	QPSK	1 RB / 0 RB Offset
A	Occupied Bandwidth	18607 to 19193	18607, 18900, 19193	1.4 MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3 MHz	QPSK, 16QAM	15 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15 MHz	QPSK, 16QAM	75 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20 MHz	QPSK, 16QAM	100 RB / 0 RB Offset
A	Peak to Average Ratio	18607 to 19193	18607, 18900, 19193	1.4 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20 MHz	QPSK, 16QAM	1 RB / 0 RB Offset

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
A	Band Edge	18607 to 19193	18607	1.4 MHz	QPSK	1 RB / 0 RB Offset
			19193	1.4 MHz	QPSK	6 RB / 0 RB Offset
		18615 to 19185	18615	3 MHz	QPSK	1 RB / 5 RB Offset
			19185	3 MHz	QPSK	6 RB / 0 RB Offset
		18625 to 19175	18625	5 MHz	QPSK	1 RB / 0 RB Offset
			19175	5 MHz	QPSK	15 RB / 0 RB Offset
		18650 to 19150	18650	10 MHz	QPSK	1 RB / 14 RB Offset
			19150	10 MHz	QPSK	15 RB / 0 RB Offset
		18675 to 19125	18675	15 MHz	QPSK	1 RB / 0 RB Offset
			19125	15 MHz	QPSK	25 RB / 0 RB Offset
		18700 to 19100	18700	20 MHz	QPSK	1 RB / 24 RB Offset
			19100	20 MHz	QPSK	25 RB / 0 RB Offset
A	Conducted Emission	18607 to 19193	18607, 18900, 19193	1.4 MHz	QPSK	1 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3 MHz	QPSK	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5 MHz	QPSK	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10 MHz	QPSK	1 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15 MHz	QPSK	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20 MHz	QPSK	1 RB / 0 RB Offset
A	Radiated Emission	18607 to 19193	18607, 18900, 19193	1.4 MHz	QPSK	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5 MHz	QPSK	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20 MHz	QPSK	1 RB / 0 RB Offset
B		18700 to 19100	18700, 18900, 19100	20 MHz	QPSK	1 RB / 0 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

Test Condition:

Test Item	Environmental Conditions	Input Power	Tested By
EIRP	26 deg. C, 58 % RH	3.85 Vdc	Karl Lee
Modulation Characteristics	26 deg. C, 58 % RH	3.85 Vdc	Wayne Lin
Frequency Stability	26 deg. C, 58 % RH	3.85 Vdc	Wayne Lin
Occupied Bandwidth	26 deg. C, 58 % RH	3.85 Vdc	Wayne Lin
Band Edge	26 deg. C, 58 % RH	3.85 Vdc	Wayne Lin
Peak to Average Ratio	26 deg. C, 58 % RH	3.85 Vdc	Wayne Lin
Conducted Emission	26 deg. C, 58 % RH	3.85 Vdc	Wayne Lin
Radiated Emission	25 deg. C, 65 % RH	120 Vac, 60 Hz	Karl Lee

3.4 EUT Operating Conditions

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 24

KDB 971168 D01 Power Meas License Digital Systems v03r01

ANSI/TIA/EIA-603-E 2016

ANSI 63.26-2015

NOTE: All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Output Power Measurement

4.1.1 Limits of Output Power Measurement

Mobile / Portable station are limited to 2 watts e.i.r.p.

4.1.2 Test Procedures

EIRP / ERP Measurement:

- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 1 MHz for GSM, GPRS & EDGE, 5 MHz for WCDMA, and 10 MHz for LTE mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step b. Record the power level of S.G.
- d. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$. E.R.P power can be calculated from E.I.R.P power by subtracting the gain of dipole, $E.R.P \text{ power} = E.I.R.P \text{ power} - 2.15 \text{ dB}$.


Conducted Power Measurement:

The EUT was set up for the maximum power with GSM, GPRS, EDGE, WCDMA, and LTE link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.


4.1.3 Test Setup

EIRP / ERP Measurement:

<Radiated Emission below or equal 1 GHz>




<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

Conducted Power Measurement:



4.1.4 Test Results

Conducted Output Power (dBm)

Band	GSM1900		
Channel	512	661	810
Frequency (MHz)	1850.2	1880.0	1909.8
GSM (GMSK, 1Tx-slot)	29.87	29.95	29.63
GPRS (GMSK, 1Tx-slot)	29.83	29.91	29.59
GPRS (GMSK, 2Tx-slot)	28.06	28.14	27.82
GPRS (GMSK, 3Tx-slot)	26.87	26.95	26.63
GPRS (GMSK, 4Tx-slot)	25.90	25.98	25.66
EDGE (8PSK, 1Tx-slot)	25.15	25.23	24.91
EDGE (8PSK, 2Tx-slot)	23.96	24.04	23.72
EDGE (8PSK, 3Tx-slot)	22.81	22.89	22.57
EDGE (8PSK, 4Tx-slot)	22.19	22.27	21.95

Band	WCDMA II		
Channel	9262	9400	9538
Frequency (MHz)	1852.4	1880.0	1907.6
RMC 12.2K	23.37	23.31	23.16
HSDPA Subtest-1	22.47	22.41	22.26
HSDPA Subtest-2	22.40	22.34	22.19
HSDPA Subtest-3	22.03	21.97	21.82
HSDPA Subtest-4	22.01	21.95	21.80
DC-HSDPA Subtest-1	22.38	22.32	22.17
DC-HSDPA Subtest-2	22.31	22.25	22.10
DC-HSDPA Subtest-3	21.94	21.88	21.73
DC-HSDPA Subtest-4	21.92	21.86	21.71
HSUPA Subtest-1	22.52	22.46	22.31
HSUPA Subtest-2	20.47	20.41	20.26
HSUPA Subtest-3	21.45	21.39	21.24
HSUPA Subtest-4	20.48	20.42	20.27
HSUPA Subtest-5	22.47	22.41	22.26

LTE Band 2															
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		18700	18900	19100				Channel		18675	18900	19125	
		Frequency (MHz)		1860.0	1880.0	1900.0				Frequency (MHz)		1857.5	1880.0	1902.5	
20M	QPSK	1	0	23.33	23.49	23.24	0	15M	QPSK	1	0	23.21	23.37	23.12	0
		1	50	23.31	23.47	23.22	0			1	37	23.19	23.35	23.10	0
		1	99	23.12	23.28	23.03	0			1	74	23.00	23.16	22.91	0
		50	0	22.32	22.48	22.23	1			36	0	22.20	22.36	22.11	1
		50	25	22.30	22.46	22.21	1			36	19	22.18	22.34	22.09	1
		50	50	22.25	22.41	22.16	1			36	39	22.13	22.29	22.04	1
	16QAM	100	0	22.27	22.43	22.18	1		75	0	22.15	22.31	22.06	1	
		1	0	22.28	22.44	22.19	1		1	0	22.16	22.32	22.07	1	
		1	50	22.26	22.42	22.17	1		1	37	22.14	22.30	22.05	1	
		1	99	22.07	22.23	21.98	1		1	74	21.95	22.11	21.86	1	
		50	0	21.27	21.43	21.18	2		36	0	21.15	21.31	21.06	2	
		50	25	21.25	21.41	21.16	2		36	19	21.13	21.29	21.04	2	
10M	16QAM	50	50	21.20	21.36	21.11	2	36	39	21.08	21.24	20.99	2		
		100	0	21.22	21.38	21.13	2	75	0	21.10	21.26	21.01	2		
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		18650	18900	19150				Channel		18625	18900	19175	
		Frequency (MHz)		1855.0	1880.0	1905.0				Frequency (MHz)		1852.5	1880.0	1907.5	
10M	QPSK	1	0	23.12	23.28	23.03	0	5M	QPSK	1	0	22.99	23.15	22.90	0
		1	24	23.10	23.26	23.01	0			1	12	22.97	23.13	22.88	0
		1	49	22.91	23.07	22.82	0			1	24	22.78	22.94	22.69	0
		25	0	22.11	22.27	22.02	1			12	0	21.98	22.14	21.89	1
		25	12	22.09	22.25	22.00	1			12	6	21.96	22.12	21.87	1
		25	25	22.04	22.20	21.95	1			12	13	21.91	22.07	21.82	1
	16QAM	50	0	22.06	22.22	21.97	1		25	0	21.93	22.09	21.84	1	
		1	0	22.07	22.23	21.98	1		1	0	21.94	22.10	21.85	1	
		1	24	22.05	22.21	21.96	1		1	12	21.92	22.08	21.83	1	
		1	49	21.86	22.02	21.77	1		1	24	21.73	21.89	21.64	1	
		25	0	21.06	21.22	20.97	2		12	0	20.93	21.09	20.84	2	
		25	12	21.04	21.20	20.95	2		12	6	20.91	21.07	20.82	2	
5M	16QAM	25	25	20.99	21.15	20.90	2	12	13	20.86	21.02	20.77	2		
		50	0	21.01	21.17	20.92	2	25	0	20.88	21.04	20.79	2		
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		18615	18900	19185				Channel		18607	18900	19193	
		Frequency (MHz)		1851.5	1880.0	1908.5				Frequency (MHz)		1850.7	1880.0	1909.3	
3M	QPSK	1	0	22.90	23.06	22.81	0	1.4M	QPSK	1	0	22.76	22.92	22.67	0
		1	7	22.88	23.04	22.79	0			1	2	22.74	22.90	22.65	0
		1	14	22.69	22.85	22.60	0			1	5	22.55	22.71	22.46	0
		8	0	21.89	22.05	21.80	1			3	0	22.66	22.82	22.57	0
		8	3	21.87	22.03	21.78	1			3	1	22.64	22.80	22.55	0
		8	7	21.82	21.98	21.73	1			3	3	22.59	22.75	22.50	0
	16QAM	15	0	21.84	22.00	21.75	1		6	0	21.70	21.86	21.61	1	
		1	0	21.85	22.01	21.76	1		1	0	21.71	21.87	21.62	1	
		1	7	21.83	21.99	21.74	1		1	2	21.69	21.85	21.60	1	
		1	14	21.64	21.80	21.55	1		1	5	21.50	21.66	21.41	1	
		8	0	20.84	21.00	20.75	2		3	0	21.61	21.77	21.52	1	
		8	3	20.82	20.98	20.73	2		3	1	21.59	21.75	21.50	1	
1.4M	16QAM	8	7	20.77	20.93	20.68	2	3	3	21.54	21.70	21.45	1		
		15	0	20.79	20.95	20.70	2	6	0	20.65	20.81	20.56	2		
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		18615	18900	19185				Channel		18607	18900	19193	
		Frequency (MHz)		1851.5	1880.0	1908.5				Frequency (MHz)		1850.7	1880.0	1909.3	

EIRP Power (dBm)

Mode A

GSM							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	512	1850.2	-7.62	38.19	30.57	1140.25	H
	661	1880.0	-8.16	38.70	30.54	1132.40	
	810	1909.8	-8.86	39.35	30.49	1119.44	
	512	1850.2	-13.90	38.48	24.58	287.08	V
	661	1880.0	-14.04	38.59	24.55	285.10	
	810	1909.8	-14.35	38.87	24.52	283.14	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

EDGE							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	512	1850.2	-12.11	38.19	26.08	405.51	H
	661	1880.0	-12.65	38.70	26.05	402.72	
	810	1909.8	-13.33	39.35	26.02	399.94	
	512	1850.2	-18.42	38.48	20.06	101.39	V
	661	1880.0	-18.57	38.59	20.02	100.46	
	810	1909.8	-18.87	38.87	20.00	100.00	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

WCDMA							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	9262	1852.4	-14.10	38.19	24.09	256.45	H
	9400	1880.0	-14.65	38.70	24.05	254.10	
	9538	1907.6	-15.31	39.35	24.04	253.51	
	9262	1852.4	-19.43	38.48	19.05	80.35	V
	9400	1880.0	-19.58	38.59	19.01	79.62	
	9538	1907.6	-19.90	38.87	18.97	78.89	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 2							
Channel Bandwidth: 1.4 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	18607	1850.7	-20.64	44.70	24.06	254.68	H
	18900	1880.0	-20.68	44.70	24.02	252.35	
	19193	1909.3	-20.60	44.57	23.97	249.63	
	18607	1850.7	-26.21	44.27	18.06	63.97	V
	18900	1880.0	-26.85	44.87	18.02	63.39	
	19193	1909.3	-26.66	44.61	17.95	62.42	
Channel Bandwidth: 1.4 MHz / 16QAM							
Z	18607	1850.7	-21.68	44.70	23.02	200.45	H
	18900	1880.0	-21.71	44.70	22.99	199.07	
	19193	1909.3	-21.63	44.57	22.94	196.92	
	18607	1850.7	-27.22	44.27	17.05	50.70	V
	18900	1880.0	-27.86	44.87	17.01	50.23	
	19193	1909.3	-27.68	44.61	16.93	49.35	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 2							
Channel Bandwidth: 3 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	18615	1851.5	-20.63	44.70	24.07	255.27	H
	18900	1880.0	-20.67	44.70	24.03	252.93	
	19185	1908.5	-20.58	44.57	23.99	250.78	
	18615	1851.5	-26.19	44.27	18.08	64.27	V
	18900	1880.0	-26.84	44.87	18.03	63.53	
	19185	1908.5	-26.63	44.61	17.98	62.85	
Channel Bandwidth: 3 MHz / 16QAM							
Z	18615	1851.5	-21.65	44.70	23.05	201.84	H
	18900	1880.0	-21.70	44.70	23.00	199.53	
	19185	1908.5	-21.59	44.57	22.98	198.75	
	18615	1851.5	-27.19	44.27	17.08	51.05	V
	18900	1880.0	-27.85	44.87	17.02	50.35	
	19185	1908.5	-27.64	44.61	16.97	49.81	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 2							
Channel Bandwidth: 5 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	18625	1852.5	-20.62	44.70	24.08	255.86	H
	18900	1880.0	-20.64	44.70	24.06	254.68	
	19175	1907.5	-20.57	44.57	24.00	251.36	
	18625	1852.5	-26.18	44.27	18.09	64.42	V
	18900	1880.0	-26.82	44.87	18.05	63.83	
	19175	1907.5	-26.61	44.61	18.00	63.14	
Channel Bandwidth: 5 MHz / 16QAM							
Z	18625	1852.5	-21.63	44.70	23.07	202.77	H
	18900	1880.0	-21.65	44.70	23.05	201.84	
	19175	1907.5	-21.58	44.57	22.99	199.20	
	18625	1852.5	-27.19	44.27	17.08	51.05	V
	18900	1880.0	-27.83	44.87	17.04	50.58	
	19175	1907.5	-27.61	44.61	17.00	50.15	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 2							
Channel Bandwidth: 10 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	18650	1855.0	-20.61	44.70	24.09	256.45	H
	18900	1880.0	-20.63	44.70	24.07	255.27	
	19150	1905.0	-20.55	44.57	24.02	252.52	
	18650	1855.0	-26.17	44.27	18.10	64.57	V
	18900	1880.0	-26.80	44.87	18.07	64.12	
	19150	1905.0	-26.59	44.61	18.02	63.43	
Channel Bandwidth: 10 MHz / 16QAM							
Z	18650	1855.0	-21.61	44.70	23.09	203.70	H
	18900	1880.0	-21.64	44.70	23.06	202.30	
	19150	1905.0	-21.56	44.57	23.01	200.12	
	18650	1855.0	-27.18	44.27	17.09	51.17	V
	18900	1880.0	-27.82	44.87	17.05	50.70	
	19150	1905.0	-27.60	44.61	17.01	50.27	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 2							
Channel Bandwidth: 15 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	18675	1857.5	-20.60	44.70	24.10	257.04	H
	18900	1880.0	-20.61	44.70	24.09	256.45	
	19125	1902.5	-20.53	44.57	24.04	253.69	
	18675	1857.5	-26.15	44.27	18.12	64.86	V
	18900	1880.0	-26.78	44.87	18.09	64.42	
	19125	1902.5	-26.57	44.61	18.04	63.72	
Channel Bandwidth: 15 MHz / 16QAM							
Z	18675	1857.5	-21.62	44.70	23.08	203.24	H
	18900	1880.0	-21.63	44.70	23.07	202.77	
	19125	1902.5	-21.54	44.57	23.03	201.05	
	18675	1857.5	-27.16	44.27	17.11	51.40	V
	18900	1880.0	-27.79	44.87	17.08	51.05	
	19125	1902.5	-27.58	44.61	17.03	50.50	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 2							
Channel Bandwidth: 20 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	18700	1860.0	-20.58	44.70	24.12	258.23	H
	18900	1880.0	-20.60	44.70	24.10	257.04	
	19100	1900.0	-20.51	44.57	24.06	254.86	
	18700	1860.0	-26.13	44.27	18.14	65.16	V
	18900	1880.0	-26.76	44.87	18.11	64.71	
	19100	1900.0	-26.54	44.61	18.07	64.17	
Channel Bandwidth: 20 MHz / 16QAM							
Z	18700	1860.0	-21.60	44.70	23.10	204.17	H
	18900	1880.0	-21.61	44.70	23.09	203.70	
	19100	1900.0	-21.52	44.57	23.05	201.98	
	18700	1860.0	-27.14	44.27	17.13	51.64	V
	18900	1880.0	-27.78	44.87	17.09	51.17	
	19100	1900.0	-27.55	44.61	17.06	50.85	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

Mode B

GSM							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	512	1850.2	-8.65	38.19	29.54	899.50	H
	661	1880.0	-8.88	38.70	29.82	959.40	
	810	1909.8	-9.56	39.35	29.79	952.80	
	512	1850.2	-14.69	38.48	23.79	239.33	V
	661	1880.0	-14.85	38.59	23.74	236.59	
	810	1909.8	-14.90	38.87	23.97	249.46	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 2							
Channel Bandwidth: 20 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	18700	1860.0	-21.65	44.70	23.05	201.84	H
	18900	1880.0	-21.41	44.70	23.29	213.30	
	19100	1900.0	-21.13	44.57	23.45	221.21	
	18700	1860.0	-26.85	44.27	17.42	55.21	V
	18900	1880.0	-26.92	44.87	17.95	62.37	
	19100	1900.0	-26.88	44.61	17.73	59.33	
Channel Bandwidth: 20 MHz / 16QAM							
Z	18700	1860.0	-22.62	44.70	22.08	161.44	H
	18900	1880.0	-22.12	44.70	22.58	181.13	
	19100	1900.0	-21.88	44.57	22.69	185.91	
	18700	1860.0	-27.96	44.27	16.31	42.76	V
	18900	1880.0	-28.21	44.87	16.66	46.34	
	19100	1900.0	-27.81	44.61	16.80	47.90	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

4.2 Modulation Characteristics Measurement

4.2.1 Limits of Modulation Characteristics

N/A


4.2.2 Test Setup



4.2.3 Test Procedure

Connect the EUT to Communication Simulator via the antenna connector. The frequency band is set as EUT supported Modulation and Channels, the EUT output is matched with 50 ohm load, the waveform quality and constellation of the EUT was tested.

4.2.4 Test Results



4.3 Frequency Stability Measurement

4.3.1 Limits of Frequency Stability Measurement


The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

4.3.2 Test Procedure

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the ± 0.5 °C during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

4.3.3 Test Setup



4.3.4 Test Results

Frequency Error vs. Voltage

Voltage (Volts)	GSM				Limit (ppm)
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.85	1850.200001	0.001	1909.800002	0.001	2.5
3.27	1850.200003	0.001	1909.800002	0.001	2.5
4.42	1850.200004	0.002	1909.800002	0.001	2.5

Note: The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.42 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	GSM				Limit (ppm)
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1850.200003	0.001	1909.800003	0.002	2.5
-20	1850.200002	0.001	1909.800003	0.002	2.5
-10	1850.200002	0.001	1909.800001	0.001	2.5
0	1850.200002	0.001	1909.800002	0.001	2.5
10	1850.200004	0.002	1909.800004	0.002	2.5
20	1850.199997	-0.002	1909.799997	-0.001	2.5
30	1850.199996	-0.002	1909.799996	-0.002	2.5
40	1850.199999	-0.001	1909.799998	-0.001	2.5
50	1850.199997	-0.002	1909.799999	-0.001	2.5
55	1850.199998	-0.001	1909.799998	-0.001	2.5

Frequency Error vs. Voltage

Voltage (Volts)	EDGE				Limit (ppm)
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.85	1850.200003	0.001	1909.800001	0.001	2.5
3.27	1850.200001	0.001	1909.800003	0.002	2.5
4.42	1850.200002	0.001	1909.800002	0.001	2.5

Note: The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.42 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	EDGE				Limit (ppm)
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1850.200002	0.001	1909.800003	0.001	2.5
-20	1850.200004	0.002	1909.800004	0.002	2.5
-10	1850.200002	0.001	1909.800003	0.001	2.5
0	1850.200003	0.002	1909.800004	0.002	2.5
10	1850.200003	0.002	1909.800001	0.001	2.5
20	1850.199999	-0.001	1909.799999	-0.001	2.5
30	1850.199998	-0.001	1909.799997	-0.002	2.5
40	1850.199997	-0.002	1909.799999	-0.001	2.5
50	1850.199998	-0.001	1909.799996	-0.002	2.5
55	1850.199998	-0.001	1909.799997	-0.002	2.5

Frequency Error vs. Voltage

Voltage (Volts)	WCDMA				Limit (ppm)
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.85	1852.400002	0.001	1907.600002	0.001	2.5
3.27	1852.400004	0.002	1907.600002	0.001	2.5
4.42	1852.400004	0.002	1907.600001	0.001	2.5

Note: The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.42 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	WCDMA				Limit (ppm)
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1852.400004	0.002	1907.600002	0.001	2.5
-20	1852.400002	0.001	1907.600002	0.001	2.5
-10	1852.400002	0.001	1907.600002	0.001	2.5
0	1852.400001	0.001	1907.600003	0.002	2.5
10	1852.400004	0.002	1907.600003	0.002	2.5
20	1852.399996	-0.002	1907.599997	-0.001	2.5
30	1852.399998	-0.001	1907.599998	-0.001	2.5
40	1852.399996	-0.002	1907.599999	-0.001	2.5
50	1852.399999	-0.001	1907.599997	-0.002	2.5
55	1852.399998	-0.001	1907.599997	-0.001	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 2				Limit (ppm)
	Channel Bandwidth: 1.4 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.85	1850.700004	0.002	1909.300004	0.002	2.5
3.27	1850.700001	0.001	1909.300002	0.001	2.5
4.42	1850.700003	0.002	1909.300003	0.002	2.5

Note: The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.42 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 2				Limit (ppm)
	Channel Bandwidth: 1.4 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1850.700004	0.002	1909.300003	0.001	2.5
-20	1850.700002	0.001	1909.300002	0.001	2.5
-10	1850.700002	0.001	1909.300003	0.001	2.5
0	1850.700003	0.002	1909.300003	0.002	2.5
10	1850.700002	0.001	1909.300001	0.001	2.5
20	1850.699998	-0.001	1909.299999	-0.001	2.5
30	1850.699997	-0.002	1909.299996	-0.002	2.5
40	1850.699999	-0.001	1909.299998	-0.001	2.5
50	1850.699997	-0.002	1909.299998	-0.001	2.5
55	1850.699998	-0.001	1909.299998	-0.001	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 2				Limit (ppm)
	Channel Bandwidth: 3 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.85	1851.500002	0.001	1907.500002	0.001	2.5
3.27	1851.500003	0.001	1907.500003	0.002	2.5
4.42	1851.500002	0.001	1907.500002	0.001	2.5

Note: The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.42 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 2				Limit (ppm)
	Channel Bandwidth: 3 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1851.500002	0.001	1907.500002	0.001	2.5
-20	1851.500003	0.001	1907.500003	0.001	2.5
-10	1851.500002	0.001	1907.500003	0.002	2.5
0	1851.500001	0.001	1907.500002	0.001	2.5
10	1851.500002	0.001	1907.500004	0.002	2.5
20	1851.499997	-0.001	1907.499998	-0.001	2.5
30	1851.499997	-0.002	1907.499996	-0.002	2.5
40	1851.499997	-0.002	1907.499999	-0.001	2.5
50	1851.499997	-0.002	1907.499999	-0.001	2.5
55	1851.499997	-0.001	1907.499998	-0.001	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 2				Limit (ppm)
	Channel Bandwidth: 5 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.85	1852.500003	0.002	1907.500004	0.002	2.5
3.27	1852.500004	0.002	1907.500001	0.001	2.5
4.42	1852.500003	0.001	1907.500003	0.002	2.5

Note: The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.42 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 2				Limit (ppm)
	Channel Bandwidth: 5 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1852.500001	0.001	1907.500003	0.001	2.5
-20	1852.500001	0.001	1907.500003	0.001	2.5
-10	1852.500002	0.001	1907.500003	0.002	2.5
0	1852.500002	0.001	1907.500002	0.001	2.5
10	1852.500002	0.001	1907.500002	0.001	2.5
20	1852.499998	-0.001	1907.499998	-0.001	2.5
30	1852.499998	-0.001	1907.499999	-0.001	2.5
40	1852.499997	-0.002	1907.499999	-0.001	2.5
50	1852.499998	-0.001	1907.499997	-0.002	2.5
55	1852.499998	-0.001	1907.499997	-0.002	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 2				Limit (ppm)
	Channel Bandwidth: 10 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.85	1855.000002	0.001	1905.000001	0.001	2.5
3.27	1855.000003	0.001	1905.000003	0.002	2.5
4.42	1855.000003	0.001	1905.000001	0.001	2.5

Note: The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.42 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 2				Limit (ppm)
	Channel Bandwidth: 10 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1855.000004	0.002	1905.000004	0.002	2.5
-20	1855.000002	0.001	1905.000003	0.001	2.5
-10	1855.000003	0.002	1905.000004	0.002	2.5
0	1855.000001	0.001	1905.000004	0.002	2.5
10	1855.000001	0.001	1905.000004	0.002	2.5
20	1854.999996	-0.002	1904.999998	-0.001	2.5
30	1854.999997	-0.002	1904.999997	-0.002	2.5
40	1854.999997	-0.001	1904.999998	-0.001	2.5
50	1854.999999	-0.001	1904.999998	-0.001	2.5
55	1854.999998	-0.001	1904.999998	-0.001	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 2				Limit (ppm)
	Channel Bandwidth: 15 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.85	1857.500003	0.002	1902.500003	0.002	2.5
3.27	1857.500002	0.001	1902.500002	0.001	2.5
4.42	1857.500002	0.001	1902.500001	0.001	2.5

Note: The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.42 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 2				Limit (ppm)
	Channel Bandwidth: 15 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1857.500004	0.002	1902.500001	0.001	2.5
-20	1857.500002	0.001	1902.500003	0.002	2.5
-10	1857.500004	0.002	1902.500002	0.001	2.5
0	1857.500002	0.001	1902.500001	0.001	2.5
10	1857.500003	0.001	1902.500004	0.002	2.5
20	1857.499997	-0.002	1902.499999	-0.001	2.5
30	1857.499996	-0.002	1902.499997	-0.002	2.5
40	1857.499999	-0.001	1902.499997	-0.002	2.5
50	1857.499996	-0.002	1902.499998	-0.001	2.5
55	1857.499997	-0.001	1902.499998	-0.001	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 2				Limit (ppm)
	Channel Bandwidth: 20 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.85	1860.000003	0.002	1900.000002	0.001	2.5
3.27	1860.000004	0.002	1900.000002	0.001	2.5
4.42	1860.000003	0.001	1900.000001	0.001	2.5

Note: The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.42 Vdc.

Frequency Error vs. Temperature


Temp. (°C)	LTE Band 2				Limit (ppm)
	Channel Bandwidth: 20 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1860.000003	0.002	1900.000002	0.001	2.5
-20	1860.000003	0.002	1900.000001	0.001	2.5
-10	1860.000003	0.001	1900.000002	0.001	2.5
0	1860.000004	0.002	1900.000001	0.001	2.5
10	1860.000001	0.001	1900.000003	0.001	2.5
20	1859.999999	-0.001	1899.999999	-0.001	2.5
30	1859.999996	-0.002	1899.999998	-0.001	2.5
40	1859.999999	-0.001	1899.999996	-0.002	2.5
50	1859.999998	-0.001	1899.999996	-0.002	2.5
55	1859.999999	-0.001	1899.999997	-0.002	2.5

4.4 Occupied Bandwidth Measurement

4.4.1 Test Procedure


The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

4.4.2 Test Setup




4.4.3 Test Result


Channel	Frequency (MHz)	99 % Occupied Bandwidth (kHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)
		GSM	EDGE			
512	1850.2	243.52	247.62	9262	1852.4	4.1475
661	1880.0	245.80	243.25	9400	1880.0	4.1422
810	1909.8	247.70	247.47	9538	1907.6	4.1433



LTE Band 2							
Channel Bandwidth: 1.4 MHz				Channel Bandwidth: 3 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
18607	1850.7	1.0867	1.0875	18615	1851.5	2.6989	2.6961
18900	1880.0	1.0880	1.0908	18900	1880.0	2.7031	2.6995
19193	1909.3	1.0869	1.0899	19185	1908.5	2.7027	2.7008




LTE Band 2							
Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
18625	1852.5	4.4914	4.4927	18650	1855.0	8.9625	8.9694
18900	1880.0	4.4953	4.4992	18900	1880.0	8.9762	8.9857
19175	1907.5	4.4983	4.5013	19150	1905.0	8.9869	8.9920



LTE Band 2

Channel Bandwidth: 15 MHz				Channel Bandwidth: 20 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
18675	1857.5	13.428	13.422	18700	1860.0	17.887	17.909
18900	1880.0	13.476	13.466	18900	1880.0	17.954	17.971
19125	1902.5	13.479	13.469	19100	1900.0	17.935	17.948

Spectrum Plot of Worst Value




4.5 Band Edge Measurement

4.5.1 Limits of Band Edge Measurement

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.


4.5.2 Test Setup





4.5.3 Test Procedures


- All measurements were done at low and high operational frequency range.
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 10 kHz and VB of the spectrum is 30 kHz (GSM/GPRS/EDGE).
- The center frequency of spectrum is the band edge frequency and span is 5 MHz. RB of the spectrum is 100 kHz and VB of the spectrum is 300 kHz (WCDMA).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 30 kHz and VB of the spectrum is 100 kHz (LTE Bandwidth 1.4 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 62 kHz and VB of the spectrum is 200 kHz (LTE Bandwidth 3 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 100 kHz and VB of the spectrum is 300 kHz (LTE Bandwidth 5 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 200 kHz and VB of the spectrum is 1 MHz (LTE Bandwidth 10 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 300 kHz and VB of the spectrum is 1 MHz (LTE Bandwidth 15 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 300 kHz and VB of the spectrum is 1 MHz (LTE Bandwidth 20 MHz).
- Record the max trace plot into the test report.


4.5.4 Test Results


















4.6 Peak to Average Ratio

4.6.1 Limits of Peak to Average Ratio Measurement

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB.

4.6.2 Test Setup




4.6.3 Test Procedures


1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1 %.

4.6.4 Test Results


Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)
		GSM	EDGE			
512	1850.2	0.42	3.41	9262	1852.4	3.02
661	1880.0	0.39	3.28	9400	1880.0	3.42
810	1909.8	0.36	3.24	9538	1907.6	3.29



LTE Band 2							
Channel Bandwidth: 1.4 MHz				Channel Bandwidth: 3 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
18607	1850.7	3.95	5.32	18615	1851.5	3.81	5.21
18900	1880.0	4.51	6.19	18900	1880.0	4.40	6.09
19193	1909.3	4.34	5.93	19185	1908.5	4.29	6.01



LTE Band 2							
Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
18625	1852.5	3.79	5.18	18650	1855.0	3.70	5.18
18900	1880.0	4.34	6.17	18900	1880.0	4.25	6.13
19175	1907.5	4.27	6.02	19150	1905.0	3.98	5.63



LTE Band 2

Channel Bandwidth: 15 MHz				Channel Bandwidth: 20 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
18675	1857.5	3.70	5.12	18700	1860.0	3.70	5.15
18900	1880.0	4.16	6.09	18900	1880.0	4.05	5.97
19125	1902.5	3.62	5.30	19100	1900.0	3.66	5.41

Spectrum Plot of Worst Value

15 MHz / 16QAM



20 MHz / 16QAM




4.7 Conducted Spurious Emissions

4.7.1 Limits of Conducted Spurious Emissions Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13 dBm.


4.7.2 Test Setup



4.7.3 Test Procedure

- The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- Measuring frequency range from 9 kHz to 1 GHz, 10 dB attenuation pad is connected with spectrum. RBW = 100 kHz and VBW = 300 kHz is used for conducted emission measurement.
- Measuring frequency range from 9 kHz to 26.5 GHz / 27 GHz, 10 dB attenuation pad is connected with spectrum. RBW = 1 MHz and VBW = 3 MHz is used for conducted emission measurement.


4.7.4 Test Results




GSM

Channel 661


Frequency Range: 9 kHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz




Frequency Range: 10 GHz ~ 26.5 GHz




GSM

Channel 810


Frequency Range: 9 kHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz




Frequency Range: 10 GHz ~ 26.5 GHz




EDGE Channel 512


Frequency Range: 9 kHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz




Frequency Range: 10 GHz ~ 26.5 GHz




EDGE

Channel 661


Frequency Range: 9 kHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz




Frequency Range: 10 GHz ~ 26.5 GHz




EDGE Channel 810


Frequency Range: 9 kHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz




Frequency Range: 10 GHz ~ 26.5 GHz




WCDMA Channel 9262


Frequency Range: 9 kHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz




Frequency Range: 10 GHz ~ 26.5 GHz




WCDMA Channel 9400


Frequency Range: 9 kHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz




Frequency Range: 10 GHz ~ 26.5 GHz




WCDMA Channel 9538


Frequency Range: 9 kHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 26.5 GHz




LTE Band 2


Channel Bandwidth: 1.4 MHz

Channel 18607


Frequency Range: 9 kHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 27 GHz




LTE Band 2


Channel Bandwidth: 1.4 MHz

Channel 18900


Frequency Range: 9 kHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 27 GHz




LTE Band 2


Channel Bandwidth: 1.4 MHz

Channel 19193


Frequency Range: 9 kHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 27 GHz




LTE Band 2


Channel Bandwidth: 3 MHz

Channel 18615


Frequency Range: 9 kHz ~ 1 GHz





Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 27 GHz








LTE Band 2


Channel Bandwidth: 5 MHz

Channel 18625


Frequency Range: 9 kHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 27 GHz




LTE Band 2


Channel Bandwidth: 5 MHz

Channel 18900


Frequency Range: 9 kHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 27 GHz




LTE Band 2


Channel Bandwidth: 5 MHz

Channel 19175


Frequency Range: 9 kHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 27 GHz




LTE Band 2


Channel Bandwidth: 10 MHz

Channel 18650


Frequency Range: 9 kHz ~ 1 GHz




Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 27 GHz






LTE Band 2


Channel Bandwidth: 15 MHz

Channel 18675


Frequency Range: 9 kHz ~ 1 GHz




Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 27 GHz






LTE Band 2


Channel Bandwidth: 15 MHz

Channel 19125


Frequency Range: 9 kHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 27 GHz




LTE Band 2


Channel Bandwidth: 20 MHz

Channel 18700


Frequency Range: 9 kHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 27 GHz




LTE Band 2


Channel Bandwidth: 20 MHz

Channel 18900


Frequency Range: 9 kHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 27 GHz




LTE Band 2


Channel Bandwidth: 20 MHz

Channel 19100


Frequency Range: 9 kHz ~ 1 GHz



Frequency Range: 1 GHz ~ 10 GHz



Frequency Range: 10 GHz ~ 27 GHz



4.8 Radiated Emission Measurement

4.8.1 Limits of Radiated Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit is equal to -13 dBm.

4.8.2 Test Procedure

- Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G.
- $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}.$
- E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, $E.R.P \text{ power} = E.I.R.P \text{ power} - 2.15 \text{ dB}.$


NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz/3 MHz.

4.8.3 Deviation from Test Standard


No deviation.

4.8.4 Test Setup

<Radiated Emission below or equal 1 GHz>



<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.8.5 Test Results

Mode A

GSM:


Low Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : PCS 1900_Link_CH512
Tested by: Karl Lee

		Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor Remark
	MHz	dBm	dBm	dBm	dB	dB
1	3700.40	-51.76	-67.64	-13.00	-38.76	15.88 Peak
2 pp	5550.60	-43.79	-64.13	-13.00	-30.79	20.34 Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-07-06



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : PCS 1900_Link_CH512
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3700.40	-51.02	-66.90	-13.00	-38.02	15.88	Peak
2 pp	5550.60	-37.56	-57.90	-13.00	-24.56	20.34	Peak

Middle Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-07-06



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : PCS 1900_Link_CH661
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3760.00	-51.67	-67.81	-13.00	-38.67	16.14	Peak
2	5640.00	-42.83	-63.30	-13.00	-29.83	20.47	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-07-06



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : PCS 1900_Link_CH661
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3760.00	-51.00	-67.14	-13.00	-38.00	16.14	Peak
2 pp	5640.00	-35.64	-56.11	-13.00	-22.64	20.47	Peak

High Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 13

Date: 2018-07-06



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : PCS 1900_Link_CH810
Tested by: Karl Lee

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	170.13	-66.27	-59.56	-13.00	-53.27	-6.71	Peak
2	245.73	-67.07	-61.50	-13.00	-54.07	-5.57	Peak
3	280.29	-72.60	-66.82	-13.00	-59.60	-5.78	Peak
4	533.80	-71.95	-69.08	-13.00	-58.95	-2.87	Peak
5	740.30	-71.03	-69.90	-13.00	-58.03	-1.13	Peak
6	814.50	-68.53	-70.38	-13.00	-55.53	1.85	Peak
7	3819.60	-50.88	-67.38	-13.00	-37.88	16.50	Peak
8 pp	5729.40	-44.01	-64.35	-13.00	-31.01	20.34	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 14

Date: 2018-07-06



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : PCS 1900_Link_CH810
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	119.37	-80.79	-72.47	-13.00	-67.79	-8.32	Peak
2	181.47	-67.38	-61.79	-13.00	-54.38	-5.59	Peak
3	215.49	-72.28	-66.30	-13.00	-59.28	-5.98	Peak
4	482.00	-74.72	-69.96	-13.00	-61.72	-4.76	Peak
5	862.10	-68.21	-70.02	-13.00	-55.21	1.81	Peak
6	892.90	-66.42	-69.11	-13.00	-53.42	2.69	Peak
7	3819.60	-51.06	-67.56	-13.00	-38.06	16.50	Peak
8 pp	5729.40	-34.74	-55.08	-13.00	-21.74	20.34	Peak

EDGE:
Low Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-07-06



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : EDGE 1900_Link_CH512
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3700.40	-52.09	-67.97	-13.00	-39.09	15.88	Peak
2	5550.60	-44.70	-65.04	-13.00	-31.70	20.34	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-07-06



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : EDGE 1900_Link_CH512
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3700.40	-51.65	-67.53	-13.00	-38.65	15.88	Peak
2 pp	5550.60	-45.38	-65.72	-13.00	-32.38	20.34	Peak

Middle Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-07-06



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : EDGE 1900_Link_CH661
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3760.00	-51.77	-67.91	-13.00	-38.77	16.14	Peak
2	5640.00	-42.57	-63.04	-13.00	-29.57	20.47	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-07-06



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : EDGE 1900_Link_CH661
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3760.00	-52.14	-68.28	-13.00	-39.14	16.14	Peak
2 pp	5640.00	-41.55	-62.02	-13.00	-28.55	20.47	Peak

High Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-07-06



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : EDGE 1900_Link_CH810
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3819.60	-51.69	-68.19	-13.00	-38.69	16.50	Peak
2	5729.40	-44.67	-65.01	-13.00	-31.67	20.34	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-07-06



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : EDGE 1900_Link_CH810
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3819.60	-51.32	-67.82	-13.00	-38.32	16.50	Peak
2 pp	5729.40	-40.77	-61.11	-13.00	-27.77	20.34	Peak

WCDMA:
Low Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-07-06



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : Band II_Link_CH9400
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3704.80	-51.33	-67.21	-13.00	-38.33	15.88	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-07-06



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : Band II_Link_CH9400
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3704.80	-50.94	-66.82	-13.00	-37.94	15.88	Peak

Middle Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-07-06



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : Band II_Link_CH9400
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3760.00	-50.36	-66.50	-13.00	-37.36	16.14	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-07-06



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : Band II_Link_CH9400
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3760.00	-52.02	-68.16	-13.00	-39.02	16.14	Peak

High Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-07-06



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : Band II_Link_CH9400
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3815.20	-50.97	-67.38	-13.00	-37.97	16.41	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-07-06



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : Band II_Link_CH9400
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3815.20	-50.51	-66.92	-13.00	-37.51	16.41	Peak

LTE Band 2
Channel Bandwidth: 1.4 MHz / QPSK
Low Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-07-05



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : LTE_Band 2_Link_CH18607
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3701.40	-51.30	-67.18	-13.00	-38.30	15.88	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-07-05



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH18607
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3701.40	-50.54	-66.42	-13.00	-37.54	15.88	Peak

Middle Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-07-05



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : LTE_Band 2_Link_CH18900
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3760.00	-50.20	-66.34	-13.00	-37.20	16.14	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-07-05



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH18900
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3760.00	-50.74	-66.88	-13.00	-37.74	16.14	Peak

High Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-07-05



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : LTE_Band 2_Link_CH19193
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3818.60	-50.74	-67.24	-13.00	-37.74	16.50	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-07-05



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH19193
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3818.60	-51.35	-67.85	-13.00	-38.35	16.50	Peak

Channel Bandwidth: 5 MHz / QPSK
Low Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-07-05



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : LTE_Band 2_Link_CH18625
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3705.00	-52.09	-67.97	-13.00	-39.09	15.88	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-07-05



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH18625
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3705.00	-51.43	-67.31	-13.00	-38.43	15.88	Peak

Middle Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-07-05



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : LTE_Band 2_Link_CH18900
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3760.00	-49.61	-65.75	-13.00	-36.61	16.14	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-07-05



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH18900
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3760.00	-51.76	-67.90	-13.00	-38.76	16.14	Peak

High Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-07-05



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : LTE_Band 2_Link_CH19175
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3815.00	-50.74	-67.15	-13.00	-37.74	16.41	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-07-05



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH19175
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3815.00	-51.35	-67.76	-13.00	-38.35	16.41	Peak

Channel Bandwidth: 20 MHz / QPSK
Low Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 13

Date: 2018-07-05



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : LTE_Band 2_Link_CH18700
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	172.56	-65.94	-59.54	-13.00	-52.94	-6.40	Peak
2	250.32	-67.28	-61.77	-13.00	-54.28	-5.51	Peak
3	283.80	-71.65	-65.83	-13.00	-58.65	-5.82	Peak
4	519.80	-73.20	-69.34	-13.00	-60.20	-3.86	Peak
5	758.50	-70.95	-70.21	-13.00	-57.95	-0.74	Peak
6	934.90	-65.58	-70.03	-13.00	-52.58	4.45	Peak
7 pp	3720.00	-48.63	-64.60	-13.00	-35.63	15.97	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 14

Date: 2018-07-05



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH18700
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	111.00	-82.62	-73.80	-13.00	-69.62	-8.82	Peak
2	192.27	-70.88	-65.06	-13.00	-57.88	-5.82	Peak
3	231.96	-71.11	-65.36	-13.00	-58.11	-5.75	Peak
4	477.80	-74.63	-69.98	-13.00	-61.63	-4.65	Peak
5	800.50	-68.61	-70.62	-13.00	-55.61	2.01	Peak
6	947.50	-64.21	-69.23	-13.00	-51.21	5.02	Peak
7 pp	3720.00	-51.47	-67.44	-13.00	-38.47	15.97	Peak

Middle Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-07-05



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : LTE_Band 2_Link_CH18900
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3760.00	-50.20	-66.34	-13.00	-37.20	16.14	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-07-05



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH18900
Tested by: Karl Lee

			Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark	
MHz	dBm	dBm	dBm	dB	dB		
1 pp 3760.00	-50.74	-66.88	-13.00	-37.74	16.14	Peak	

High Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-07-05



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : LTE_Band 2_Link_CH19100
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3800.00	-49.58	-65.99	-13.00	-36.58	16.41	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-07-05



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH19100
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3800.00	-50.54	-66.95	-13.00	-37.54	16.41	Peak

Mode B
GSM:
Low Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-07-20



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : PCS 1900_Link_CH512
Tested by: Karl Lee

		Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor Remark
	MHz	dBm	dBm	dBm	dB	dB
1	3700.40	-52.65	-68.53	-13.00	-39.65	15.88 Peak
2 pp	5550.60	-46.55	-66.89	-13.00	-33.55	20.34 Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-07-20



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : PCS 1900_Link_CH512
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3700.40	-51.44	-67.32	-13.00	-38.44	15.88	Peak
2 pp	5550.60	-40.36	-60.70	-13.00	-27.36	20.34	Peak

Middle Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-07-20



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : PCS 1900_Link_CH661
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3760.00	-51.99	-68.13	-13.00	-38.99	16.14	Peak
2	5640.00	-44.36	-64.83	-13.00	-31.36	20.47	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-07-20



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : PCS 1900_Link_CH661
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3760.00	-51.85	-67.99	-13.00	-38.85	16.14	Peak
2 pp	5640.00	-38.55	-59.02	-13.00	-25.55	20.47	Peak


High Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 13



Site : 966 chamber 1
 Condition: PART 22/24 Horizontal
 Remark : PCS 1900_Link_CH810
 Tested by: Karl Lee

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	142.59	-75.25	-67.49	-13.00	-62.25	-7.76	Peak
2	199.83	-62.34	-56.16	-13.00	-49.34	-6.18	Peak
3	234.93	-59.55	-53.83	-13.00	-46.55	-5.72	Peak
4	567.40	-72.53	-71.59	-13.00	-59.53	-0.94	Peak
5	694.10	-69.55	-69.20	-13.00	-56.55	-0.35	Peak
6	757.80	-71.57	-70.77	-13.00	-58.57	-0.80	Peak
7	3819.60	-51.62	-68.12	-13.00	-38.62	16.50	Peak
8 pp	5729.40	-45.62	-65.96	-13.00	-32.62	20.34	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 14

Date: 2018-07-20



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : PCS 1900_Link_CH810
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	104.79	-81.56	-72.03	-13.00	-68.56	-9.53	Peak
2	192.00	-72.46	-66.64	-13.00	-59.46	-5.82	Peak
3	213.87	-71.80	-65.81	-13.00	-58.80	-5.99	Peak
4	346.90	-78.08	-72.67	-13.00	-65.08	-5.41	Peak
5	594.00	-69.98	-70.13	-13.00	-56.98	0.15	Peak
6	694.80	-69.00	-68.65	-13.00	-56.00	-0.35	Peak
7	3819.60	-51.11	-67.61	-13.00	-38.11	16.50	Peak
8 pp	5729.40	-36.05	-56.39	-13.00	-23.05	20.34	Peak

LTE Band 2
Channel Bandwidth: 20 MHz / QPSK
Low Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 13

Date: 2018-07-20



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : LTE_Band 2_Link_CH18700
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	104.52	-81.53	-72.00	-13.00	-68.53	-9.53	Peak
2	205.23	-59.16	-53.05	-13.00	-46.16	-6.11	Peak
3	268.14	-72.89	-67.21	-13.00	-59.89	-5.68	Peak
4	493.90	-76.21	-71.12	-13.00	-63.21	-5.09	Peak
5	741.70	-71.29	-70.13	-13.00	-58.29	-1.16	Peak
6	941.90	-65.21	-69.97	-13.00	-52.21	4.76	Peak
7 pp	3720.00	-49.00	-64.97	-13.00	-36.00	15.97	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 14

Date: 2018-07-20



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH18700
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	96.15	-82.97	-72.63	-13.00	-69.97	-10.34	Peak
2	180.12	-70.61	-65.03	-13.00	-57.61	-5.58	Peak
3	216.57	-65.75	-59.79	-13.00	-52.75	-5.96	Peak
4	507.90	-75.00	-70.29	-13.00	-62.00	-4.71	Peak
5	630.40	-69.12	-69.21	-13.00	-56.12	0.09	Peak
6	761.30	-69.79	-69.25	-13.00	-56.79	-0.54	Peak
7 pp	3720.00	-51.88	-67.85	-13.00	-38.88	15.97	Peak

Middle Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-07-20



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : LTE_Band 2_Link_CH18900
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3760.00	-50.99	-67.13	-13.00	-37.99	16.14	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-07-20



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH18900
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3760.00	-51.32	-67.46	-13.00	-38.32	16.14	Peak

High Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2018-07-20



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : LTE_Band 2_Link_CH19100
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3800.00	-50.32	-66.73	-13.00	-37.32	16.41	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2018-07-20



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH19100
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3800.00	-50.87	-67.28	-13.00	-37.87	16.41	Peak

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---