



FCC RADIO TEST REPORT

FCC ID : 2AJOTTA-1108
Equipment : Smart Phone
Brand Name : NOKIA
Model Name : TA-1108
Applicant : HMD Global Oy
Bertel Jungin aukio 9, 02600 Espoo, Finland
Manufacturer : HMD Global Oy
Bertel Jungin aukio 9, 02600 Espoo, Finland
Standard : FCC Part 15 Subpart C §15.247

The product was received on Apr. 30, 2018 and testing was started from May 16, 2018 and completed on Oct. 31, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Joseph Lin

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	5
1.4 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test	7
2.1 Carrier Frequency and Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	9
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	10
3 Test Result	11
3.1 6dB and 99% Bandwidth Measurement	11
3.2 Output Power Measurement.....	13
3.3 Power Spectral Density Measurement	14
3.4 Conducted Band Edges and Spurious Emission Measurement	16
3.5 Radiated Band Edges and Spurious Emission Measurement	26
3.6 AC Conducted Emission Measurement.....	30
3.7 Antenna Requirements	32
4 List of Measuring Equipment.....	33
5 Uncertainty of Evaluation	35
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission	
Appendix D. Radiated Spurious Emission Plots	
Appendix E. Duty Cycle Plots	
Appendix F. Setup Photographs	



History of this test report

Report No.	Version	Description	Issued Date
FR843024-03C	01	Initial issue of report	Nov. 15, 2018



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.247(b)	Power Output Measurement	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges	Pass	-
		Conducted Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	Under limit 6.41 dB at 2487.960 MHz
3.6	15.207	AC Conducted Emission	Pass	Under limit 11.46 dB at 3.377 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	Pass	-

Remark: FR843024-03C test report of Conducted and Radiated reuse test data from the FR843024C test report.

Declaration of Conformity:

The judgment of conformity in the report is based on the measurement results excluding the measurement uncertainty.

Comments and Explanations:

None

Reviewed by: Wii Chang

Report Producer: Nancy Yang



1 General Description

1.1 Product Feature of Equipment Under Test

GSM/WCDMA/LTE, Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, Wi-Fi 5GHz 802.11a/n/ac, FM Receiver, and GNSS

Product Specification subjective to this standard	
Antenna Type	WWAN: Monopole Antenna WLAN: Monopole Antenna Bluetooth: Monopole Antenna GPS/Glonass/Galileo/BDS: PIFA Antenna FM: using earphone as antenna

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1190 and TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	03CH10-HY	

Note: The test site complies with ANSI C63.4 2014 requirement.



1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437		


2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20 (Covered by g)	MCS0
802.11n HT40	MCS0

Test Cases	
AC Conducted Emission	Mode 1: GSM850 Idle + WLAN (2.4GHz) Link + Bluetooth Link + GPS Rx + Earphone + USB Type C Cable (Charging from Adapter 1) Mode 2: GSM1900 Idle + WLAN (5GHz) Link + Bluetooth Link + Camera (Front) + Earphone + USB Type C Cable (Charging from Adapter 2) Mode 3: WCDMA Band II Idle + WLAN (2.4GHz) Link + Bluetooth Link + Camera (Rear) + Earphone + USB Type C Cable (Charging from Adapter 1) Mode 4: WCDMA Band V Idle + WLAN (5GHz) Link + Bluetooth Link + MPEG4 + Earphone + USB Type C Cable (Charging from Adapter 2) Mode 5: LTE Band 4 Idle + WLAN (2.4GHz) Idle + Bluetooth Idle + FM Rx + Earphone + USB Type C Cable (Data Link with Notebook)
Remark: - The worst case of conducted emission is mode 1; only the test data of it was reported. - For Radiated test cases, the tests were performed with Adapter 1, Earphone, and USB Cable 1. - Data Linking with Notebook means data application transferred mode between EUT and Notebook.	

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	GPS Station	Pendulum	GSG-54	N/A	N/A	Unshielded, 1.8 m
3.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
4.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
5.	iPod	Apple	A1285	FCC DoC	Shielded, 1.0 m	N/A
6.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
7.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A



2.5 EUT Operation Test Setup

The RF test items, make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v05.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * RBW$.
6. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

1. For Peak Power, the testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v05 section 9.1.3 PKPM1 Peak power meter method.
2. For Average Power, the testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v05 section 9.2.3.1 Method AVGPM.
3. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures


1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Engineer :	Eason Huang, Shiang Wang, and Kai Liao	Temperature :	21~25°C
		Relative Humidity :	51~54%

Number of TX = 1, Ant. 1 (Measured)


Test Mode :	802.11b	Test Channel :	01
-------------	---------	----------------	----






Test Mode :	802.11b	Test Channel :	06
-------------	---------	----------------	----

100kHz PSD reference Level




Date: 25.MAY.2018 06:25:03

Spurious Emission 30MHz~3GHz



Date: 25.MAY.2018 06:25:42


Spurious Emission 2GHz~25GHz



Date: 25.MAY.2018 06:26:33




Test Mode :	802.11b	Test Channel :	11
-------------	---------	----------------	----






Test Mode :	802.11g	Test Channel :	01
-------------	---------	----------------	----

100kHz PSD reference Level




Date: 25.MAY.2018 06:36:52

Channel Plot




Date: 27.MAY.2018 01:50:05

Spurious Emission 30MHz~3GHz



Date: 25.MAY.2018 06:38:27

Spurious Emission 2GHz~25GHz




Date: 25.MAY.2018 06:39:12




Test Mode :	802.11g	Test Channel :	06
-------------	---------	----------------	----

100kHz PSD reference Level




Date: 25.MAY.2018 06:43:31

Spurious Emission 30MHz~3GHz



Date: 25.MAY.2018 06:44:19


Spurious Emission 2GHz~25GHz



Date: 25.MAY.2018 06:45:20




Test Mode :	802.11g	Test Channel :	11
-------------	---------	----------------	----






Test Mode :	802.11n HT40	Test Channel :	03
-------------	--------------	----------------	----

100kHz PSD reference Level




Date: 25.MAY.2018 07:23:00

Channel Plot




Date: 25.MAY.2018 07:23:32

Spurious Emission 30MHz~3GHz



Date: 25.MAY.2018 07:25:01


Spurious Emission 2GHz~25GHz



Date: 25.MAY.2018 07:25:18




Test Mode :	802.11n HT40	Test Channel :	06
-------------	--------------	----------------	----





Test Mode :	802.11n HT40	Test Channel :	09
-------------	--------------	----------------	----



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

3.5.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Anritsu	ML2495A	1240001	N/A	Sep. 07, 2017	May 16, 2018 ~ May 27, 2018	Sep. 06, 2018	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	1207349	300MHz~40GHz	Sep. 07, 2017	May 16, 2018 ~ May 27, 2018	Sep. 06, 2018	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 20, 2017	May 16, 2018 ~ May 27, 2018	Jun. 19, 2018	Conducted (TH05-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL890001	1V~20V 0.5A~4A	Oct. 06, 2017	May 16, 2018 ~ May 27, 2018	Oct. 05, 2018	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC130048 4	N/A	Mar. 01, 2018	May 16, 2018 ~ May 27, 2018	Feb. 28, 2019	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Oct. 31, 2018	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9KHz~3.6GHz	Dec. 08, 2017	Oct. 31, 2018	Dec. 07, 2018	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 30, 2017	Oct. 31, 2018	Nov. 29, 2018	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Dec. 08, 2017	Oct. 31, 2018	Dec. 07, 2018	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Oct. 31, 2018	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 03, 2018	Oct. 31, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 03, 2018	Oct. 31, 2018	Jan. 02, 2019	Conduction (CO05-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Amplifier	SONOMA	310N	187311	9kHz~1GHz	Oct. 19, 2017	May 17, 2018 ~ May 18, 2018	Oct. 18, 2018	Radiation (03CH10-HY)
Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 18, 2017	May 17, 2018 ~ May 18, 2018	Jul. 17, 2018	Radiation (03CH10-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	35413&02	30MHz~1GHz	Dec. 18, 2017	May 17, 2018 ~ May 18, 2018	Dec. 17, 2018	Radiation (03CH10-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1325	1GHz ~ 18GHz	Sep. 27, 2017	May 17, 2018 ~ May 18, 2018	Sep. 26, 2018	Radiation (03CH10-HY)
Preamplifier	Keysight	83017A	MY53270078	1GHz~26.5GHz	Oct. 25, 2017	May 17, 2018 ~ May 18, 2018	Oct. 24, 2018	Radiation (03CH10-HY)
Preamplifier	Jet-Power	JAP00101800-30-10P	160118550004	1GHz~18GHz	Apr. 17, 2018	May 17, 2018 ~ May 18, 2018	Apr. 16, 2019	Radiation (03CH10-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200485	10Hz ~ 44GHz	Oct. 31, 2017	May 17, 2018 ~ May 18, 2018	Oct. 30, 2018	Radiation (03CH10-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	May 17, 2018 ~ May 18, 2018	N/A	Radiation (03CH10-HY)
Turn Table	EMEC	TT 2200	N/A	0~360 Degree	N/A	May 17, 2018 ~ May 18, 2018	N/A	Radiation (03CH10-HY)
Software	Audix	E3 6.2009-8-24	RK-001042	N/A	N/A	May 17, 2018 ~ May 18, 2018	N/A	Radiation (03CH10-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Nov. 23, 2017	May 17, 2018 ~ May 18, 2018	Nov. 22, 2018	Radiation (03CH10-HY)
Filter	Wainwright	WHKX12-270 0-3000-18000-60ST	SN1	3G High Pass	Sep. 18, 2017	May 17, 2018 ~ May 18, 2018	Sep. 17, 2018	Radiation (03CH10-HY)
Filter	Wainwright	WLKS1200-12SS	SN2	1.2G Low Pass	Jul. 17, 2017	May 17, 2018 ~ May 18, 2018	Jul. 16, 2018	Radiation (03CH10-HY)
Attenuator	Fairview Microwave	SA18S5W-10	n/a	10db	Jul. 17, 2017	May 17, 2018 ~ May 18, 2018	Jul. 16, 2018	Radiation (03CH10-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24971/4,MY28655/4	9K-30M	Jan. 02, 2018	May 17, 2018 ~ May 18, 2018	Jan. 01, 2019	Radiation (03CH10-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104 / 102	MY11692/4PE, MY11693/4PE, MY2855/2	30M-1G	Nov. 14, 2017	May 17, 2018 ~ May 18, 2018	Nov. 13, 2018	Radiation (03CH10-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104 / 102	MY11692/4PE, MY11693/4PE, MY2855/2	1G-18G	Nov. 14, 2017	May 17, 2018 ~ May 18, 2018	Nov. 13, 2018	Radiation (03CH10-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	800740/2	30M~40G	Oct. 17, 2017	May 17, 2018 ~ May 18, 2018	Oct. 16, 2018	Radiation (03CH10-HY)
EMI Test Receiver	Agilent	N9038A(MXE)	MY53290053	20Hz to 26.5GHz	Jan. 16, 2018	May 17, 2018 ~ May 18, 2018	Jan. 15, 2019	Radiation (03CH10-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Nov. 27, 2017	May 17, 2018 ~ May 18, 2018	Nov. 26, 2018	Radiation (03CH10-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.2
---	-----

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.6
---	-----

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.9
---	-----

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.2
---	-----

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Eason Huang / Shiang Wang / Kai Liao	Temperature:	21~25	°C
Test Date:	2018/05/16~2018/05/27	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)		6dB BW (MHz)		6dB BW Limit (MHz)	Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2		
11b	1Mbps	1	1	2412	13.35	-	8.04	-	0.50	Pass
11b	1Mbps	1	6	2437	13.15	-	8.56	-	0.50	Pass
11b	1Mbps	1	11	2462	13.20	-	8.08	-	0.50	Pass
11g	6Mbps	1	1	2412	17.80	-	15.28	-	0.50	Pass
11g	6Mbps	1	6	2437	17.40	-	15.08	-	0.50	Pass
11g	6Mbps	1	11	2462	17.60	-	15.08	-	0.50	Pass
HT20	MCS0	1	1	2412	18.15	-	15.04	-	0.50	Pass
HT20	MCS0	1	6	2437	18.10	-	15.08	-	0.50	Pass
HT20	MCS0	1	11	2462	18.15	-	15.08	-	0.50	Pass
HT40	MCS0	1	3	2422	36.40	-	35.04	-	0.50	Pass
HT40	MCS0	1	6	2437	36.10	-	30.08	-	0.50	Pass
HT40	MCS0	1	9	2452	36.40	-	35.12	-	0.50	Pass

TEST RESULTS DATA
Peak Output Power

2.4GHz Band																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
11b	1Mbps	1	1	2412	20.94	-	-	30.00	-	-1.34	-	19.60	-	36.00	-	Pass
11b	1Mbps	1	6	2437	21.08	-	-	30.00	-	-1.34	-	19.74	-	36.00	-	Pass
11b	1Mbps	1	11	2462	21.24	-	-	30.00	-	-1.34	-	19.90	-	36.00	-	Pass
11g	6Mbps	1	1	2412	24.58	-	-	30.00	-	-1.34	-	23.24	-	36.00	-	Pass
11g	6Mbps	1	6	2437	24.99	-	-	30.00	-	-1.34	-	23.65	-	36.00	-	Pass
11g	6Mbps	1	11	2462	24.76	-	-	30.00	-	-1.34	-	23.42	-	36.00	-	Pass
HT20	MCS0	1	1	2412	24.98	-	-	30.00	-	-1.34	-	23.64	-	36.00	-	Pass
HT20	MCS0	1	6	2437	24.95	-	-	30.00	-	-1.34	-	23.61	-	36.00	-	Pass
HT20	MCS0	1	11	2462	24.91	-	-	30.00	-	-1.34	-	23.57	-	36.00	-	Pass
HT40	MCS0	1	3	2422	24.74	-	-	30.00	-	-1.34	-	23.40	-	36.00	-	Pass
HT40	MCS0	1	6	2437	25.04	-	-	30.00	-	-1.34	-	23.70	-	36.00	-	Pass
HT40	MCS0	1	9	2452	24.64	-	-	30.00	-	-1.34	-	23.30	-	36.00	-	Pass

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
Average Output Power

2.4GHz Band									
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)		
					Ant 1	Ant 2	Ant 1	Ant 2	SUM
11b	1Mbps	1	1	2412	0.00	-	18.62	-	-
11b	1Mbps	1	6	2437	0.00	-	18.74	-	
11b	1Mbps	1	11	2462	0.00	-	18.93	-	
11g	6Mbps	1	1	2412	0.12	-	15.64	-	
11g	6Mbps	1	6	2437	0.12	-	15.86	-	
11g	6Mbps	1	11	2462	0.12	-	15.76	-	
HT20	MCS0	1	1	2412	0.13	-	14.63	-	
HT20	MCS0	1	6	2437	0.13	-	14.76	-	
HT20	MCS0	1	11	2462	0.13	-	14.67	-	
HT40	MCS0	1	3	2422	0.26	-	14.61	-	
HT40	MCS0	1	6	2437	0.26	-	14.90	-	
HT40	MCS0	1	9	2452	0.26	-	14.84	-	

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
Peak Power Spectral Density

2.4GHz Band												
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak PSD (dBm/3kHz)			DG (dBi)		Peak PSD Limit (dBm/3kHz)		Pass/Fail
					Ant 1	Ant 2	Worse + 3.01	Ant 1	Ant 2	Ant 1	Ant 2	
11b	1Mbps	1	1	2412	-5.87	-	-	-1.34	-	8.00	-	Pass
11b	1Mbps	1	6	2437	-5.46	-	-	-1.34	-	8.00	-	Pass
11b	1Mbps	1	11	2462	-4.89	-	-	-1.34	-	8.00	-	Pass
11g	6Mbps	1	1	2412	-10.41	-	-	-1.34	-	8.00	-	Pass
11g	6Mbps	1	6	2437	-9.78	-	-	-1.34	-	8.00	-	Pass
11g	6Mbps	1	11	2462	-11.07	-	-	-1.34	-	8.00	-	Pass
HT20	MCS0	1	1	2412	-12.12	-	-	-1.34	-	8.00	-	Pass
HT20	MCS0	1	6	2437	-12.28	-	-	-1.34	-	8.00	-	Pass
HT20	MCS0	1	11	2462	-12.07	-	-	-1.34	-	8.00	-	Pass
HT40	MCS0	1	3	2422	-13.46	-	-	-1.34	-	8.00	-	Pass
HT40	MCS0	1	6	2437	-13.02	-	-	-1.34	-	8.00	-	Pass
HT40	MCS0	1	9	2452	-14.12	-	-	-1.34	-	8.00	-	Pass

Measured power density (dBm) has offset with cable loss.




Appendix B. AC Conducted Emission Test Results

Test Engineer :	Rick Lin	Temperature :	23~24℃
		Relative Humidity :	55~57%

EUT Information

Report NO : 843024-03
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Line

Full Spectrum



Final Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.631500	---	27.72	46.00	18.28	L1	OFF	19.6
0.631500	38.71	---	56.00	17.29	L1	OFF	19.6
0.692250	---	27.75	46.00	18.25	L1	OFF	19.6
0.692250	39.04	---	56.00	16.96	L1	OFF	19.6
0.744000	---	31.81	46.00	14.19	L1	OFF	19.6
0.744000	41.16	---	56.00	14.84	L1	OFF	19.6
0.798000	---	28.38	46.00	17.62	L1	OFF	19.6
0.798000	39.01	---	56.00	16.99	L1	OFF	19.6
0.831750	---	30.01	46.00	15.99	L1	OFF	19.6
0.831750	40.86	---	56.00	15.14	L1	OFF	19.6
2.024250	---	29.42	46.00	16.58	L1	OFF	19.6
2.024250	38.54	---	56.00	17.46	L1	OFF	19.6
2.289750	---	30.31	46.00	15.69	L1	OFF	19.5
2.289750	41.23	---	56.00	14.77	L1	OFF	19.5
2.582250	---	29.63	46.00	16.37	L1	OFF	19.6
2.582250	40.82	---	56.00	15.18	L1	OFF	19.6
2.834250	---	31.12	46.00	14.88	L1	OFF	19.6
2.834250	40.78	---	56.00	15.22	L1	OFF	19.6
3.018750	---	30.08	46.00	15.92	L1	OFF	19.6
3.018750	39.49	---	56.00	16.51	L1	OFF	19.6
3.187500	---	29.28	46.00	16.72	L1	OFF	19.6

3.187500	40.34	---	56.00	15.66	L1	OFF	19.6
3.275250	---	31.41	46.00	14.59	L1	OFF	19.7
3.275250	42.82	---	56.00	13.18	L1	OFF	19.7
3.376500	---	32.31	46.00	13.69	L1	OFF	19.7
3.376500	44.54	---	56.00	11.46	L1	OFF	19.7
3.462000	---	29.40	46.00	16.60	L1	OFF	19.7
3.462000	39.85	---	56.00	16.15	L1	OFF	19.7

EUT Information

Report NO : 843024-03
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Neutral

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	30.54	55.88	25.34	N	OFF	19.5
0.152250	49.13	---	65.88	16.75	N	OFF	19.5
0.827250	---	28.98	46.00	17.02	N	OFF	19.6
0.827250	38.64	---	56.00	17.36	N	OFF	19.6
1.583250	---	29.19	46.00	16.81	N	OFF	19.6
1.583250	39.50	---	56.00	16.50	N	OFF	19.6
1.709250	---	30.34	46.00	15.66	N	OFF	19.6
1.709250	40.87	---	56.00	15.13	N	OFF	19.6
1.848750	---	28.92	46.00	17.08	N	OFF	19.6
1.848750	38.75	---	56.00	17.25	N	OFF	19.6
1.965750	---	29.99	46.00	16.01	N	OFF	19.6
1.965750	40.05	---	56.00	15.95	N	OFF	19.6
2.087250	---	29.89	46.00	16.11	N	OFF	19.4
2.087250	40.27	---	56.00	15.73	N	OFF	19.4
2.181750	---	29.60	46.00	16.40	N	OFF	19.5
2.181750	40.78	---	56.00	15.22	N	OFF	19.5
2.292000	---	30.50	46.00	15.50	N	OFF	19.5
2.292000	43.27	---	56.00	12.73	N	OFF	19.5
2.568750	---	27.27	46.00	18.73	N	OFF	19.6
2.568750	38.29	---	56.00	17.71	N	OFF	19.6
3.401250	---	30.93	46.00	15.07	N	OFF	19.7

3.401250	40.24	---	56.00	15.76	N	OFF	19.7
----------	-------	-----	-------	-------	---	-----	------



Appendix C. Radiated Spurious Emission

Test Engineer :	Daniel Lee and JC Liang	Temperature :	22~25°C
		Relative Humidity :	50~54%

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01 2412MHz		2331.63	51.39	-22.61	74	42.35	26.92	15.3	33.18	114	199	P	H
		2387.7	41.16	-12.84	54	31.84	27.11	15.37	33.16	114	199	A	H
	*	2412	96.85	-	-	87.43	27.16	15.41	33.15	114	199	P	H
	*	2412	93.64	-	-	84.22	27.16	15.41	33.15	114	199	A	H
													H
													H
		2366.49	51.76	-22.24	74	42.57	27.01	15.34	33.16	383	163	P	V
		2387.49	40.95	-13.05	54	31.63	27.11	15.37	33.16	383	163	A	V
	*	2412	93.46	-	-	84.04	27.16	15.41	33.15	383	163	P	V
	*	2412	90.16	-	-	80.74	27.16	15.41	33.15	383	163	A	V
													V
													V
802.11b CH 06 2437MHz		2379.02	51.79	-22.21	74	42.52	27.06	15.37	33.16	100	196	P	H
		2389.38	40.92	-13.08	54	31.6	27.11	15.37	33.16	100	196	A	H
	*	2437	100.02	-	-	90.47	27.26	15.43	33.14	100	196	P	H
	*	2437	96.74	-	-	87.19	27.26	15.43	33.14	100	196	A	H
		2497.69	52.18	-21.82	74	42.4	27.4	15.48	33.1	100	196	P	H
		2487.75	41.42	-12.58	54	31.65	27.4	15.48	33.11	100	196	A	H
		2385.04	51.89	-22.11	74	42.62	27.06	15.37	33.16	374	180	P	V
		2387	40.94	-13.06	54	31.62	27.11	15.37	33.16	374	180	A	V
	*	2437	96.92	-	-	87.37	27.26	15.43	33.14	374	180	P	V
	*	2437	93.51	-	-	83.96	27.26	15.43	33.14	374	180	A	V
		2499.16	52.14	-21.86	74	42.36	27.4	15.48	33.1	374	180	P	V
		2492.86	41.37	-12.63	54	31.59	27.4	15.48	33.1	374	180	A	V



802.11b CH 11 2462MHz	*	2462	103.66	-	-	94.04	27.3	15.44	33.12	141	248	P	H
	*	2462	99.37	-	-	89.75	27.3	15.44	33.12	141	248	A	H
		2489.24	53.87	-20.13	74	44.1	27.4	15.48	33.11	141	248	P	H
		2487.84	44.3	-9.7	54	34.53	27.4	15.48	33.11	141	248	A	H
													H
													H
	*	2462	99.91	-	-	90.29	27.3	15.44	33.12	371	144	P	V
	*	2462	96.94	-	-	87.32	27.3	15.44	33.12	371	144	A	V
		2489.96	52.62	-21.38	74	42.85	27.4	15.48	33.11	371	144	P	V
		2487.92	42.46	-11.54	54	32.69	27.4	15.48	33.11	371	144	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01 2412MHz		4824	41.08	-32.92	74	63.29	31.19	8.9	62.3	100	0	P	H
													H
													H
													H
		4824	41.44	-32.56	74	63.65	31.19	8.9	62.3	100	0	P	V
													V
													V
													V
802.11b CH 06 2437MHz		4874	40.5	-33.5	74	62.66	31.28	8.86	62.3	100	0	P	H
		7311	44.46	-29.54	74	61.42	36.18	10.52	63.66	100	0	P	H
													H
													H
		4874	40.58	-33.42	74	62.74	31.28	8.86	62.3	100	0	P	V
		7311	44.39	-29.61	74	61.35	36.18	10.52	63.66	100	0	P	V
													V
													V
802.11b CH 11 2462MHz		4924	41.18	-32.82	74	63.26	31.38	8.37	62.3	100	0	P	H
		7386	43.29	-30.71	74	60.16	36.37	10.09	63.68	100	0	P	H
													H
													H
		4924	43.67	-30.33	74	65.75	31.38	8.37	62.3	100	0	P	V
		7386	43.24	-30.76	74	60.11	36.37	10.09	63.68	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		2369.535	51.98	-22.02	74	42.74	27.06	15.34	33.16	100	198	P	H
		2389.905	42.21	-11.79	54	32.88	27.11	15.37	33.15	100	198	A	H
	*	2412	95.45	-	-	86.03	27.16	15.41	33.15	100	198	P	H
	*	2412	88.15	-	-	78.73	27.16	15.41	33.15	100	198	A	H
													H
													H
		2336.355	52.01	-21.99	74	42.92	26.97	15.3	33.18	390	163	P	V
		2390	42.21	-11.79	54	32.88	27.11	15.37	33.15	390	163	A	V
	*	2412	92.78	-	-	83.36	27.16	15.41	33.15	390	163	P	V
	*	2412	83.88	-	-	74.46	27.16	15.41	33.15	390	163	A	V
													V
													V
802.11g CH 06 2437MHz		2310.7	51.82	-22.18	74	42.88	26.87	15.27	33.2	100	194	P	H
		2375.24	41.8	-12.2	54	32.53	27.06	15.37	33.16	100	194	A	H
	*	2437	99.18	-	-	89.63	27.26	15.43	33.14	100	194	P	H
	*	2437	91.87	-	-	82.32	27.26	15.43	33.14	100	194	A	H
		2498.25	52.09	-21.91	74	42.31	27.4	15.48	33.1	100	194	P	H
		2488.24	42.41	-11.59	54	32.64	27.4	15.48	33.11	100	194	A	H
		2342.62	51.23	-22.77	74	42.11	26.97	15.32	33.17	376	180	P	V
		2388.96	41.91	-12.09	54	32.59	27.11	15.37	33.16	376	180	A	V
	*	2437	96.1	-	-	86.55	27.26	15.43	33.14	376	180	P	V
	*	2437	89.17	-	-	79.62	27.26	15.43	33.14	376	180	A	V
		2487.54	52.44	-21.56	74	42.67	27.4	15.48	33.11	376	180	P	V
		2487.19	42.38	-11.62	54	32.66	27.35	15.48	33.11	376	180	A	V



802.11g CH 11 2462MHz	*	2462	101.71	-	-	92.09	27.3	15.44	33.12	132	248	P	H
	*	2462	93.82	-	-	84.2	27.3	15.44	33.12	132	248	A	H
		2483.76	58.75	-15.25	74	49.03	27.35	15.48	33.11	132	248	P	H
		2483.6	46.79	-7.21	54	37.07	27.35	15.48	33.11	132	248	A	H
													H
													H
	*	2462	99.12	-	-	89.5	27.3	15.44	33.12	372	139	P	V
	*	2462	91.45	-	-	81.83	27.3	15.44	33.12	372	139	A	V
		2484.08	54.65	-19.35	74	44.93	27.35	15.48	33.11	372	139	P	V
		2483.72	44.96	-9.04	54	35.24	27.35	15.48	33.11	372	139	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		4824	40.25	-33.75	74	62.46	31.19	8.9	62.3	100	0	P	H
													H
													H
													H
		4824	40.12	-33.88	74	62.33	31.19	8.9	62.3	100	0	P	V
													V
													V
													V
802.11g CH 06 2437MHz		4874	39.66	-34.34	74	61.82	31.28	8.86	62.3	100	0	P	H
		7311	42.93	-31.07	74	59.89	36.18	10.52	63.66	100	0	P	H
													H
													H
		4874	39.46	-34.54	74	61.62	31.28	8.86	62.3	100	0	P	V
		7311	43.7	-30.3	74	60.66	36.18	10.52	63.66	100	0	P	V
													V
													V
802.11g CH 11 2462MHz		4924	40.3	-33.7	74	62.38	31.38	8.84	62.3	100	0	P	H
		7386	43.09	-30.91	74	59.96	36.37	10.44	63.68	100	0	P	H
													H
													H
		4924	39.98	-34.02	74	62.06	31.38	8.84	62.3	100	0	P	V
		7386	43.06	-30.94	74	59.93	36.37	10.44	63.68	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 03 2422MHz		2389.8	54.45	-19.55	74	45.12	27.11	15.37	33.15	133	264	P	H
		2389.8	43.65	-10.35	54	34.32	27.11	15.37	33.15	133	264	A	H
	*	2422	97.72	-	-	88.24	27.21	15.41	33.14	133	264	P	H
	*	2422	90.66	-	-	81.18	27.21	15.41	33.14	133	264	P	H
		2484.67	52.58	-21.42	74	42.86	27.35	15.48	33.11	133	264	P	H
		2485.72	43.2	-10.8	54	33.48	27.35	15.48	33.11	133	264	A	H
		2388.54	52.19	-21.81	74	42.87	27.11	15.37	33.16	377	162	P	V
		2360.12	42.77	-11.23	54	33.59	27.01	15.34	33.17	377	162	A	V
	*	2422	93.75	-	-	84.27	27.21	15.41	33.14	377	162	P	V
	*	2422	86.2	-	-	76.72	27.21	15.41	33.14	377	162	P	V
		2488.17	51.99	-22.01	74	42.22	27.4	15.48	33.11	377	162	P	V
		2499.02	43.04	-10.96	54	33.26	27.4	15.48	33.1	377	162	A	V
802.11n HT40 CH 06 2437MHz		2388.54	52.37	-21.63	74	43.05	27.11	15.37	33.16	137	264	P	H
		2389.38	42.91	-11.09	54	33.59	27.11	15.37	33.16	137	264	A	H
	*	2437	98.7	-	-	89.15	27.26	15.43	33.14	137	264	P	H
	*	2437	91.29	-	-	81.74	27.26	15.43	33.14	137	264	A	H
		2489.57	56.56	-17.44	74	46.79	27.4	15.48	33.11	137	264	P	H
		2488.59	44.87	-9.13	54	35.1	27.4	15.48	33.11	137	264	A	H
		2367.54	51.39	-22.61	74	42.2	27.01	15.34	33.16	376	162	P	V
		2385.88	42.49	-11.51	54	33.17	27.11	15.37	33.16	376	162	A	V
	*	2437	96.42	-	-	86.87	27.26	15.43	33.14	376	162	P	V
	*	2437	89.18	-	-	79.63	27.26	15.43	33.14	376	162	A	V
		2490.69	52.76	-21.24	74	42.99	27.4	15.48	33.11	376	162	P	V
		2485.65	43.55	-10.45	54	33.83	27.35	15.48	33.11	376	162	A	V



802.11n HT40 CH 09 2452MHz		2376.92	51.45	-22.55	74	42.18	27.06	15.37	33.16	100	196	P	H
		2389.38	42.51	-11.49	54	33.19	27.11	15.37	33.16	100	196	A	H
	*	2452	98.38	-	-	88.8	27.26	15.44	33.12	100	196	P	H
	*	2452	90.99	-	-	81.41	27.26	15.44	33.12	100	196	A	H
		2484.74	60.12	-13.88	74	50.4	27.35	15.48	33.11	100	196	P	H
		2487.96	47.59	-6.41	54	37.82	27.4	15.48	33.11	100	196	A	H
		2387.84	52.08	-21.92	74	42.76	27.11	15.37	33.16	379	158	P	V
		2349.76	42.55	-11.45	54	33.43	26.97	15.32	33.17	379	158	A	V
	*	2452	95.23	-	-	85.65	27.26	15.44	33.12	379	158	P	V
	*	2452	87.88	-	-	78.3	27.26	15.44	33.12	379	158	A	V
		2484.81	53.25	-20.75	74	43.53	27.35	15.48	33.11	379	158	P	V
		2484.39	43.99	-10.01	54	34.27	27.35	15.48	33.11	379	158	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 03 2422MHz		4844	39.22	-34.78	74	61.41	31.22	8.89	62.3	100	0	P	H
		7266	43.27	-30.73	74	60.25	36.11	10.56	63.65	100	0	P	H
													H
													H
		4844	39.73	-34.27	74	61.92	31.22	8.89	62.3	100	0	P	V
		7266	43.12	-30.88	74	60.1	36.11	10.56	63.65	100	0	P	V
													V
													V
802.11n HT40 CH 06 2437MHz		4874	39.65	-34.35	74	61.81	31.28	8.86	62.3	100	0	P	H
		7311	43.02	-30.98	74	59.98	36.18	10.52	63.66	100	0	P	H
													H
													H
		4874	39.3	-34.7	74	61.46	31.28	8.86	62.3	100	0	P	V
		7311	42.89	-31.11	74	59.85	36.18	10.52	63.66	100	0	P	V
													V
													V
802.11n HT40 CH 09 2452MHz		4904	41.63	-32.37	74	63.74	31.34	8.85	62.3	100	0	P	H
		7356	44.81	-29.19	74	61.72	36.3	10.46	63.67	100	0	P	H
													H
													H
		4904	40.79	-33.21	74	62.9	31.34	8.85	62.3	100	0	P	V
		7356	43.35	-30.65	74	60.26	36.3	10.46	63.67	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

2.4GHz WIFI 802.11g (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11g LF		30.27	23.2	-16.8	40	30.73	24.57	0.68	32.78	-	-	P	H
		92.37	20.51	-22.99	43.5	36.95	15.03	1.25	32.72	-	-	P	H
		249.78	19.87	-26.13	46	31.89	18.51	2.08	32.61	-	-	P	H
		844.6	31.09	-14.91	46	30.88	28.86	3.75	32.4	-	-	P	H
		885.9	32.05	-13.95	46	31.27	29.06	3.89	32.17	-	-	P	H
		952.4	33.69	-12.31	46	30.32	30.77	4.1	31.5	100	0	P	H
													H
													H
													H
													H
													H
													H
													H
		30.81	31.16	-8.84	40	39.18	24.07	0.68	32.77	100	0	P	V
		35.94	30.01	-9.99	40	40.53	21.56	0.69	32.77	-	-	P	V
		60.24	24.61	-15.39	40	44.4	11.94	1.02	32.75	-	-	P	V
		786.5	30.34	-15.66	46	31.01	28.4	3.6	32.67	-	-	P	V
		868.4	32.45	-13.55	46	31.73	29.15	3.84	32.27	-	-	P	V
		950.3	33.22	-12.78	46	29.96	30.68	4.1	31.52	-	-	P	V
													V
													V
													V
													V
													V
												V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

$$1. \text{ Path Loss(dB)} = \text{Cable loss(dB)} + \text{Filter loss(dB)} + \text{Attenuator loss(dB)}$$

$$2. \text{ Level(dB}\mu\text{V/m)} =$$

$$\text{Antenna Factor(dB/m)} + \text{Path Loss(dB)} + \text{Read Level(dB}\mu\text{V)} - \text{Preamp Factor(dB)}$$

$$3. \text{ Over Limit(dB)} = \text{Level(dB}\mu\text{V/m)} - \text{Limit Line(dB}\mu\text{V/m)}$$

For Peak Limit @ 2390MHz:

$$1. \text{ Level(dB}\mu\text{V/m)}$$

$$= \text{Antenna Factor(dB/m)} + \text{Path Loss(dB)} + \text{Read Level(dB}\mu\text{V)} - \text{Preamp Factor(dB)}$$

$$= 32.22(\text{dB/m}) + 4.58(\text{dB}) + 54.51(\text{dB}\mu\text{V}) - 35.86(\text{dB})$$

$$= 55.45(\text{dB}\mu\text{V/m})$$

$$2. \text{ Over Limit(dB)}$$

$$= \text{Level(dB}\mu\text{V/m)} - \text{Limit Line(dB}\mu\text{V/m)}$$

$$= 55.45(\text{dB}\mu\text{V/m}) - 74(\text{dB}\mu\text{V/m})$$

$$= -18.55(\text{dB})$$

For Average Limit @ 2390MHz:

$$1. \text{ Level(dB}\mu\text{V/m)}$$

$$= \text{Antenna Factor(dB/m)} + \text{Path Loss(dB)} + \text{Read Level(dB}\mu\text{V)} - \text{Preamp Factor(dB)}$$

$$= 32.22(\text{dB/m}) + 4.58(\text{dB}) + 42.6(\text{dB}\mu\text{V}) - 35.86(\text{dB})$$

$$= 43.54(\text{dB}\mu\text{V/m})$$

$$2. \text{ Over Limit(dB)}$$

$$= \text{Level(dB}\mu\text{V/m)} - \text{Limit Line(dB}\mu\text{V/m)}$$

$$= 43.54(\text{dB}\mu\text{V/m}) - 54(\text{dB}\mu\text{V/m})$$

$$= -10.46(\text{dB})$$

Both peak and average measured complies with the limit line, so test result is "PASS".







Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Daniel Lee and JC Liang	Temperature :	22~25℃
		Relative Humidity :	50~54%





Note symbol

-L	Low channel location
-R	High channel location





2.4GHz 2400~2483.5MHz
WIFI 802.11b (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH01 2412MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak
	 Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : AVG_54 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak
Avg.		









WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH01 2412MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak
Avg.	 Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : AVG_54 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - L	
1	Horizontal	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak
Avg.	 Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : AVG_54 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak











WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - R	
1	Horizontal	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	Left blank
Avg.	 Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak	Left blank

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - L	
1	Vertical	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak
	 Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : AVG_54 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - R	
1	Vertical	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	Left blank
Avg.	 Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak	Left blank



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH11 2462MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak
Avg.	 Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : AVG_54 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH11 2462MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak
	 Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : AVG_54 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak







2.4GHz 2400~2483.5MHz





WIFI 802.11g (Band Edge @ 3m)



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH01 2412MHz	
1	Horizontal	Fundamental
Peak	Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	Site : 03CH10-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak
Avg.	Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak	Site : 03CH10-HY Condition : AVG_54 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH01 2412MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak
Avg.	 Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : AVG_54 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - L	
1	Horizontal	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak
Avg.	 Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : AVG_54 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - R	
1	Horizontal	Fundamental
Peak		Left blank
Avg.		Left blank







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - L	
1	Vertical	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak
Avg.	 Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : AVG_54 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - R	
1	Vertical	Fundamental
Peak		Left Blank
Avg.		Left Blank





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH11 2462MHz	
1	Horizontal	Fundamental
Peak	Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak
Avg.	Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak	Site : 03CH10-HY Condition : AVG_54 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH11 2462MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak
	 Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : AVG_54 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:1000KHz SWT:Auto Detector : Peak

2.4GHz 2400~2483.5MHz
WIFI 802.11n HT40 (Band Edge @ 3m)



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH03 2422MHz - L	
1	Horizontal	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto : Peak	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto : Peak
Avg.	 Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 91200-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto : Peak	 Site : 03CH10-HY Condition : AVG_54 3m HORN 91200-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto : Peak

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH03 2422MHz - R	
1	Horizontal	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	Left Blank
Avg.	 Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 91200-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	Left Blank









WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH03 2422MHz - L	
1	Vertical	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak
	 Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : AVG_54 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH03 2422MHz - R	
1	Vertical	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	Left blank
Avg.	 Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak	Left blank





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH06 2437MHz - L	
1	Horizontal	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak
Avg.	 Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : AVG_54 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH06 2437MHz - R	
1	Horizontal	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	Left blank
Avg.	 Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak	Left blank





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH06 2437MHz - L	
1	Vertical	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak
Avg.	 Site : 03CH10-HY Condition : AVG_54 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : AVG_54 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH06 2437MHz - R	
1	Horizontal	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	Left blank
Avg.	 Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak	Left blank





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH09 2452MHz - L	
1	Horizontal	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak
Avg.	 Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : AVG_54 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH09 2452MHz - R	
1	Horizontal	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	Left blank
Avg.	 Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak	Left blank





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH09 2452MHz - L	
1	Vertical	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak
Avg.	 Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak	 Site : 03CH10-HY Condition : AVG_54 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT40 CH09 2452MHz - R	
1	Vertical	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak	Left blank
Avg.	 Site : 03CH10-HY Condition : AVG_BE_54 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak	Left blank



2.4GHz 2400~2483.5MHz
WIFI 802.11b (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH01 2412MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak





WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH06 2437MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak





WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH11 2462MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak



2.4GHz 2400~2483.5MHz
WIFI 802.11g (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH01 2412MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak





WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH06 2437MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH11 2462MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak

2.4GHz 2400~2483.5MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT40 CH03 2422MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak	 Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT40 CH06 2437MHz	
1	Horizontal	Vertical
Peak Avg.	Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak	Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak





WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT40 CH09 2452MHz	
1	Horizontal	Vertical
Peak Avg.	Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak	Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak



Emission below 1GHz


2.4GHz WIFI 802.11g (LF)

WIFI	2.4GHz 2400~2483.5MHz																																																																																																																																																																																	
ANT	802.11g LF																																																																																																																																																																																	
1	Horizontal	Vertical																																																																																																																																																																																
QP / Peak	 Site : 03CH10-HY Condition : QP 3m BE-LOG 6111D-LF HORIZONTAL Detector : Peak <table><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>30.27</td><td>23.20</td><td>-16.80</td><td>40.00</td><td>30.73</td><td>24.57</td><td>0.60</td><td>32.78</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>92.37</td><td>20.51</td><td>-22.99</td><td>43.50</td><td>36.95</td><td>15.83</td><td>1.00</td><td>32.72</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>249.78</td><td>19.87</td><td>-26.13</td><td>46.00</td><td>31.89</td><td>18.51</td><td>1.66</td><td>32.61</td><td>---</td><td>Peak</td></tr><tr><td>4</td><td>844.60</td><td>31.09</td><td>-14.91</td><td>46.00</td><td>30.88</td><td>28.86</td><td>3.09</td><td>32.40</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>885.90</td><td>32.05</td><td>-13.95</td><td>46.00</td><td>31.27</td><td>29.06</td><td>3.19</td><td>32.17</td><td>---</td><td>Peak</td></tr><tr><td>6</td><td>952.40</td><td>33.69</td><td>-12.31</td><td>46.00</td><td>30.32</td><td>30.77</td><td>3.29</td><td>31.50</td><td>100</td><td>0 Peak</td></tr></table>	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Freq	Level	Line	Level Factor	Loss Factor			MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm	deg	1	30.27	23.20	-16.80	40.00	30.73	24.57	0.60	32.78	---	Peak	2	92.37	20.51	-22.99	43.50	36.95	15.83	1.00	32.72	---	Peak	3	249.78	19.87	-26.13	46.00	31.89	18.51	1.66	32.61	---	Peak	4	844.60	31.09	-14.91	46.00	30.88	28.86	3.09	32.40	---	Peak	5	885.90	32.05	-13.95	46.00	31.27	29.06	3.19	32.17	---	Peak	6	952.40	33.69	-12.31	46.00	30.32	30.77	3.29	31.50	100	0 Peak	 Site : 03CH10-HY Condition : QP 3m BE-LOG 6111D-LF VERTICAL Detector : Peak <table><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>30.81</td><td>31.16</td><td>-8.34</td><td>40.00</td><td>39.18</td><td>24.87</td><td>0.60</td><td>32.77</td><td>---</td><td>0 Peak</td></tr><tr><td>2</td><td>35.94</td><td>30.01</td><td>-9.99</td><td>40.00</td><td>40.53</td><td>21.56</td><td>0.60</td><td>32.77</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>60.24</td><td>24.61</td><td>-15.39</td><td>40.00</td><td>44.40</td><td>11.94</td><td>0.88</td><td>32.75</td><td>---</td><td>Peak</td></tr><tr><td>4</td><td>785.50</td><td>30.34</td><td>-15.66</td><td>46.00</td><td>31.01</td><td>28.40</td><td>2.97</td><td>32.67</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>868.40</td><td>32.45</td><td>-13.55</td><td>46.00</td><td>31.73</td><td>29.15</td><td>3.16</td><td>32.27</td><td>---</td><td>Peak</td></tr><tr><td>6</td><td>950.30</td><td>33.22</td><td>-12.78</td><td>46.00</td><td>29.96</td><td>30.68</td><td>3.29</td><td>31.52</td><td>---</td><td>Peak</td></tr></table>	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Freq	Level	Line	Level Factor	Loss Factor			MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm	deg	1	30.81	31.16	-8.34	40.00	39.18	24.87	0.60	32.77	---	0 Peak	2	35.94	30.01	-9.99	40.00	40.53	21.56	0.60	32.77	---	Peak	3	60.24	24.61	-15.39	40.00	44.40	11.94	0.88	32.75	---	Peak	4	785.50	30.34	-15.66	46.00	31.01	28.40	2.97	32.67	---	Peak	5	868.40	32.45	-13.55	46.00	31.73	29.15	3.16	32.27	---	Peak	6	950.30	33.22	-12.78	46.00	29.96	30.68	3.29	31.52	---	Peak
	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark																																																																																																																																																																											
Freq	Level	Line	Level Factor	Loss Factor																																																																																																																																																																														
MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm	deg																																																																																																																																																																											
1	30.27	23.20	-16.80	40.00	30.73	24.57	0.60	32.78	---	Peak																																																																																																																																																																								
2	92.37	20.51	-22.99	43.50	36.95	15.83	1.00	32.72	---	Peak																																																																																																																																																																								
3	249.78	19.87	-26.13	46.00	31.89	18.51	1.66	32.61	---	Peak																																																																																																																																																																								
4	844.60	31.09	-14.91	46.00	30.88	28.86	3.09	32.40	---	Peak																																																																																																																																																																								
5	885.90	32.05	-13.95	46.00	31.27	29.06	3.19	32.17	---	Peak																																																																																																																																																																								
6	952.40	33.69	-12.31	46.00	30.32	30.77	3.29	31.50	100	0 Peak																																																																																																																																																																								
Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark																																																																																																																																																																												
Freq	Level	Line	Level Factor	Loss Factor																																																																																																																																																																														
MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm	deg																																																																																																																																																																											
1	30.81	31.16	-8.34	40.00	39.18	24.87	0.60	32.77	---	0 Peak																																																																																																																																																																								
2	35.94	30.01	-9.99	40.00	40.53	21.56	0.60	32.77	---	Peak																																																																																																																																																																								
3	60.24	24.61	-15.39	40.00	44.40	11.94	0.88	32.75	---	Peak																																																																																																																																																																								
4	785.50	30.34	-15.66	46.00	31.01	28.40	2.97	32.67	---	Peak																																																																																																																																																																								
5	868.40	32.45	-13.55	46.00	31.73	29.15	3.16	32.27	---	Peak																																																																																																																																																																								
6	950.30	33.22	-12.78	46.00	29.96	30.68	3.29	31.52	---	Peak																																																																																																																																																																								




Appendix E. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
802.11b	100.00	-	-	10Hz	0.00
802.11g	97.22	1400.00	0.71	1kHz	0.12
2.4GHz 802.11n HT20	97.01	1300.00	0.77	1kHz	0.13
2.4GHz 802.11n HT40	94.19	648.00	1.54	3kHz	0.26

802.11b



Date: 14.MAY.2018 16:55:20

802.11g


Date: 14.MAY.2018 17:13:49




802.11n HT20



Date: 14.MAY.2018 17:15:48

802.11n HT40



Date: 14.MAY.2018 17:33:18