


FCC SAR TEST REPORT

FCC ID : 2AJOTTA-1222
Equipment : Mobile phone
Brand Name : Nokia
Model Name : TA-1222
Applicant : HMD Global Oy
Bertel Jungin aukio 9, 02600 Espoo, Finland
Manufacturer : HMD Global Oy
Bertel Jungin aukio 9, 02600 Espoo, Finland
Standard : FCC 47 CFR Part 2 (2.1093)
ANSI/IEEE C95.1-1992
IEEE 1528-2013


The product was received on Jan. 02, 2020 and testing was started from Jan. 03, 2020 and completed on Feb. 29, 2020. We, Sporton International Inc. (KunShan), would like to declare that the tested sample has been evaluated in accordance with the procedures and had been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (KunShan), the test report shall not be reproduced except in full.



Reviewed by: Rose Wang / Supervisor



Approved by: Kat Yin / Manager

Sporton International (Kunshan) Inc.

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**





Table of Contents

1. Statement of Compliance	4
2. Administration Data	5
3. Guidance Applied.....	5
4. Equipment Under Test (EUT) Information.....	6
4.1 General Information	6
4.2 General LTE SAR Test and Reporting Considerations	7
5. Proximity Sensor Triggering Test.....	9
5.1 Tilt angle influences to proximity sensor triggering(Per KDB616217 §6.4).....	13
6. RF Exposure Limits.....	14
6.1 Uncontrolled Environment.....	14
6.2 Controlled Environment.....	14
7. Specific Absorption Rate (SAR).....	15
7.1 Introduction	15
7.2 SAR Definition.....	15
8. System Description and Setup	16
8.1 E-Field Probe	17
8.2 Data Acquisition Electronics (DAE)	17
8.3 Phantom.....	18
8.4 Device Holder.....	19
9. Measurement Procedures	20
9.1 Spatial Peak SAR Evaluation.....	20
9.2 Power Reference Measurement.....	21
9.3 Area Scan	21
9.4 Zoom Scan.....	22
9.5 Volume Scan Procedures.....	22
9.6 Power Drift Monitoring.....	22
10. Test Equipment List.....	23
11. System Verification	24
11.1 Tissue Simulating Liquids	24
11.2 Tissue Verification	25
11.3 System Performance Check Results	26
12. RF Exposure Positions	27
12.1 Ear and handset reference point.....	27
12.2 Definition of the cheek position	28
12.3 Definition of the tilt position	29
12.4 Body Worn Accessory	30
12.5 Wireless Router.....	30
13. Conducted RF Output Power (Unit: dBm).....	31
14. Antenna Location	76
15. SAR Test Results	77
15.1 Head SAR	80
15.2 Hotspot SAR	82
15.3 Body Worn Accessory SAR	87
15.4 Repeated SAR Measurement	90
16. Simultaneous Transmission Analysis.....	91
16.1 Head Exposure Conditions	92
16.2 Hotspot Exposure Conditions.....	93
16.3 Body-Worn Accessory Exposure Conditions	95
17. Uncertainty Assessment	96
18. References.....	96
Appendix A. Plots of System Performance Check	
Appendix B. Plots of High SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Test Setup Photos	

History of this test report

Report No.	Version	Description	Issued Date
FA9D3107	01	Initial issue of report	Mar. 05, 2020

1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for HMD Global Oy, Mobile phone, TA-1222, are as follows.

Equipment Class	Frequency Band	Highest SAR Summary			Highest Simultaneous Transmission 1g SAR (W/kg)
		Head (Separation 0mm)	Body-worn (Separation 10mm)	Hotspot (Separation 10mm)	
		1g SAR (W/kg)			
Licensed	GSM850	0.64	0.70	0.70	1.37
	GSM1900	0.34	0.84	0.84	
	WCDMA II	0.51	1.05	1.05	
	WCDMA IV	0.40	1.02	1.02	
	WCDMA V	0.35	0.57	0.57	
	LTE Band 2	0.53	1.04	1.04	
	LTE Band 5	0.36	0.49	0.49	
	LTE Band 12	0.39	0.49	0.49	
	LTE Band 14	0.30	0.37	0.46	
	LTE Band 4/ 66	0.40	1.08	1.08	
	LTE Band 30	0.26	1.10	1.03	
DTS	2.4GHz WLAN	0.71	0.30	0.30	1.37
DSS	Bluetooth	0.25	<0.10	<0.10	1.15
Date of Testing:		2020/1/3 ~ 2020/2/29			

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.



2. Administration Data

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Testing Laboratory		
Test Firm	Sporton International (Kunshan) Inc.	
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958	
Test Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CN1257	314309

3. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r03
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 941225 D01 3G SAR Procedures v03r01
- FCC KDB 941225 D05 SAR for LTE Devices v02r05
- FCC KDB 941225 D05A Rel.10 LTE SAR Test Guidance v01r02
- FCC KDB 941225 D06 Hotspot Mode SAR v02r01

4. Equipment Under Test (EUT) Information

4.1 General Information

Product Feature & Specification	
Equipment Name	Mobile phone
Brand Name	Nokia
Model Name	TA-1222
FCC ID	2AJOTTA-1222
IMEI Code	355787100003691
Wireless Technology and Frequency Range	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz WCDMA Band IV: 1712.4 MHz ~ 1752.6 MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz LTE Band 2: 1850.7 MHz ~ 1909.3 MHz LTE Band 4: 1710.7 MHz ~ 1754.3 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 12: 699.7 MHz ~ 715.3 MHz LTE Band 14: 790.5 MHz ~ 795.5 MHz LTE Band 30: 2307.5 MHz ~ 2312.5 MHz LTE Band 66: 1710.7 MHz ~ 1779.3 MHz WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Mode	GSM/GPRS/EGPRS RMC/AMR 12.2Kbps HSDPA HSUPA DC-HSDPA HSPA+ (16QAM uplink) LTE: QPSK, 16QAM, 64QAM WLAN: 802.11b/g/n HT20 Bluetooth BR/EDR/LE
HW Version	V1.0
SW version	Paramore-Z26K00E01V010-user-Cricket
GSM / (E)GPRS Transfer mode	Class B – EUT cannot support Packet Switched and Circuit Switched Network simultaneously but can automatically switch between Packet and Circuit Switched Network.
EUT Stage	Production Unit
Remark: - This device supports GPRS/EGPRS Class 12. - This device WLAN 2.4GHz supports Hotspot operation and Bluetooth support tethering applications. - Reduce power for different RF exposure conditions: Body worn: The device employs proximity sensors that detect the presence of the user's body at the front or back faces of the device, when operating in near-body condition by end user; the device will reduced maximum output powers on the WCDMA B4/B2 and LTE B2 / B4 / B30 / B66. Hotspot: When the mobile hotspot session is turned on by end user, the device will reduce output powers on the WCDMA B4/B2 and LTE B2 / B4 / B30 / B66. Handheld: the device additionally employs proximity sensors that detect the presence of tissue near the currently active transmit antenna, the device will reduced output power on the WCDMA B4/B2 and LTE B2 / B4 / B30 / B66. - The device is used earpiece receiver to detect user head or body usage scenarios and separate head and body power table for WLAN, when the receiver worked mean head condition is detected and head power table is used, when the receiver not worked mean body/hotspot//extremity condition is detected and body power table is used.	

4.2 General LTE SAR Test and Reporting Considerations


Summarized necessary items addressed in KDB 941225 D05 v02r05									
FCC ID		2AJOTTA-1222							
Equipment Name		Mobile phone							
Operating Frequency Range of each LTE transmission band		LTE Band 2: 1850.7 MHz ~ 1909.3 MHz LTE Band 4: 1710.7 MHz ~ 1754.3 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 12: 699.7 MHz ~ 715.3 MHz LTE Band 14: 790.5 MHz ~ 795.5 MHz LTE Band 30: 2307.5 MHz ~ 2312.5 MHz LTE Band 66: 1710.7 MHz ~ 1779.3 MHz							
Channel Bandwidth		LTE Band 02:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 04:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 05:1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 12:1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 14: 5MHz, 10MHz LTE Band 30: 5MHz, 10MHz LTE Band 66:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz							
uplink modulations used		QPSK / 16QAM / 64QAM							
LTE Voice / Data requirements		Data only							
LTE Release		R11							
CA supports		Yes, Downlink only							
LTE MPR permanently built-in by design		Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3							
		Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)
			1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
		QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
		16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
		16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2
		64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2
		64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3
		256 QAM	≥ 1						≤ 5
LTE A-MPR		In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)							
Spectrum plots for RB configuration		A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.							
Power reduction applied to satisfy SAR compliance		Yes, when operating in hotspot/body-worn/extremity mode that LTE B2 / B4 / B30 / B66 power reduction applied to satisfy SAR compliance.							
LTE Carrier Aggregation Combinations		Inter-Band and Intra-Band possible combinations and the detail power measurement please referred to section 13.							
LTE Carrier Aggregation Additional Information		1. This device supports maximum of 2 carriers in the downlink. Additional following LTE Release features are not supported: Relay, HetNet, Enhanced MIMO, eICI, WiFi Offloading, MDH, eMBMA, Cross-Carrier Scheduling, Enhanced SC-FDMA.							

Transmission (H, M, L) channel numbers and frequencies in each LTE band												
LTE Band 2												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	18607	1850.7	18615	1851.5	18625	1852.5	18650	1855	18675	1857.5	18700	1860
M	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880
H	19193	1909.3	19185	1908.5	19175	1907.5	19150	1905	19125	1902.5	19100	1900
LTE Band 4												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	19957	1710.7	19965	1711.5	19975	1712.5	20000	1715	20025	1717.5	20050	1720
M	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5
H	20393	1754.3	20385	1753.5	20375	1752.5	20350	1750	20325	1747.5	20300	1745
LTE Band 5												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20407	824.7	20415	825.5	20425	826.5	20450	829				
M	20525	836.5	20525	836.5	20525	836.5	20525	836.5				
H	20643	848.3	20635	847.5	20625	846.5	20600	844				
LTE Band 12												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	23017	699.7	23025	700.5	23035	701.5	23060	704				
M	23095	707.5	23095	707.5	23095	707.5	23095	707.5				
H	23173	715.3	23165	714.5	23155	713.5	23130	711				
LTE Band 14												
	Bandwidth 5 MHz				Bandwidth 10 MHz							
	Channel #		Channel #		Channel #		Freq.(MHz)					
L	23305		790.5		23330		793					
M	23330		793									
H	23355		795.5									
LTE Band 30												
	Bandwidth 5 MHz				Bandwidth 10 MHz							
	Channel #		Freq.(MHz)		Channel #		Freq.(MHz)					
L	27685		2307.5		27710		2310					
M	27710		2310									
H	27735		2312.5									
LTE Band 66												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	131979	1710.7	131987	1711.5	131997	1712.5	132022	1715	132047	1717.5	132072	1720
M	132322	1745	132322	1745	132322	1745	132322	1745	132322	1745	132322	1745
H	132665	1779.3	132657	1778.5	132647	1777.5	132622	1775	132597	1772.5	132572	1770

5. Proximity Sensor Triggering Test



<Proximity Sensor Triggering Distance>:



1. Proximity sensor triggering distance testing was performed according to the procedures outlined in KDB 616217 D04 section 6.2, and EUT moving further away from the flat phantom and EUT moving toward the flat phantom were both assessed and the tissue-equivalent medium for highest frequency (2300MHz) and lowest (1750MHz) frequency was used for proximity sensor triggering testing.
2. Capacitive proximity sensors placed coincident with antenna elements at bottom ends of the phone is utilized to determine when the device comes in proximity of the user's body at the front, back or Bottom of the device.
3. The output power will reduce to body worn power level when bottom sensor pad be detected.
4. The sensors used to detect the proximity of the user's body (Body-Worn condition) at the front or back surface of the device use a detection threshold distance.
5. The device additionally employs proximity sensors that detect the presence of tissue near the currently active transmit antenna (if that antenna may require reduced power relative the Default power table in order to meet extremity SAR limits). The control logic is such that, if the Body-Worn, At-Head or WiFi Hotspot conditions are not detected, but tissue (as a finger or hand, for example) is detected near the transmitting antenna, the Handheld Reduced power table will be applied
6. When the sensor is active, the device will reduced maximum output powers on the WCDMA B4/B2 and LTE B2/B4 / B30/ B66 transmitter.





Proximity Sensor Trigger Distance (mm)						
Position	Front		Back		Bottom Side	
Position	Moving towards	Moving away	Moving towards	Moving away	Moving towards	Moving away
Minimum	13	17	19	22	20	27

<Sensor Trigger Distance and Measured Power>








5.1 Tilt angle influences to proximity sensor triggering(Per KDB616217 §6.4)

The DUT was positioned directly below the flat phantom at the minimum measured trigger distance with bottom side parallel to the base of the flat phantom for each band.

The EUT was rotated about bottom side for angles up to $\pm 45^\circ$. If the output power increased during the rotation the DUT was moved 1mm toward the phantom and the rotation repeated. This procedure was repeated until the power remained reduced for all angles up to $\pm 45^\circ$.



Proximity Sensor Coverage Assesment(Bottom Side)

Table: Summary of Tablet Tilt Angle Influence to Proximity Sensor Triggering (Bottom Side)

Main ant Band(MHz)	Minimum trigger distance at which power reduction was maintained over $\pm 45^\circ$	Power Reduction Status											
		-45°	-35°	-25°	-15°	-5°	0°	5°	15°	25°	35°	45°	
WCDMA Band II	20mm	on	on	on	on	on	on	on	on	on	on	on	
WCDMA Band IV	20mm	on	on	on	on	on	on	on	on	on	on	on	
LTE Band 2	20mm	on	on	on	on	on	on	on	on	on	on	on	
LTE Band 4	20mm	on	on	on	on	on	on	on	on	on	on	on	
LTE Band 30	20mm	on	on	on	on	on	on	on	on	on	on	on	
LTE Band 66	20mm	on	on	on	on	on	on	on	on	on	on	on	

Conclusion: As is shown from the validation data, it can be ensured that the proximity sensor can be valid triggered for the DUT tilt coverage exposure condition.

6. RF Exposure Limits

6.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

6.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

7. Specific Absorption Rate (SAR)

7.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

7.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

8. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

8.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

<ES3DV3 Probe>

Construction	Symmetric design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – 4 GHz; Linearity: ± 0.2 dB (30 MHz – 4 GHz)	
Directivity	± 0.2 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)	
Dynamic Range	5 μ W/g – >100 mW/g; Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 3.9 mm (body: 12 mm) Distance from probe tip to dipole centers: 3.0 mm	

<EX3DV4 Probe>

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – >6 GHz Linearity: ± 0.2 dB (30 MHz – 6 GHz)	
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 μ W/g – >100 mW/g Linearity: ± 0.2 dB (noise: typically <1 μ W/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

8.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.




Fig 5.1 Photo of DAE

8.3 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

8.4 Device Holder

<Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

<Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

9. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

9.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

9.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

9.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

9.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

9.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

9.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

10. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	750MHz System Validation Kit	D750V3	1087	2019/3/27	2020/3/26
SPEAG	835MHz System Validation Kit	D835V2	4d151	2019/3/27	2020/3/26
SPEAG	1750MHz System Validation Kit	D1750V2	1090	2019/3/27	2020/3/26
SPEAG	1900MHz System Validation Kit	D1900V2	5d170	2019/3/26	2020/3/25
SPEAG	2300MHz System Validation Kit	D2300V2	1006	2019/1/28	2020/1/27
SPEAG	2450MHz System Validation Kit	D2450V2	908	2019/3/25	2020/3/24
SPEAG	Dosimetric E-Field Probe	EX3DV4	3857	2019/5/27	2020/5/26
SPEAG	Data Acquisition Electronics	DAE4	690	2019/1/23	2020/1/22
SPEAG	Data Acquisition Electronics	DAE4	1210	2019/7/23	2020/7/22
SPEAG	SAM Twin Phantom	QD 000 P40 CB	TP-1503	NCR	NCR
SPEAG	SAM Twin Phantom	QD 000 P40 CB	TP-1697	NCR	NCR
SPEAG	Phone Positioner	N/A	N/A	NCR	NCR
Anritsu	Radio Communication Analyzer	MT8821C	6201432831	2019/4/17	2020/4/16
Agilent	Wireless Communication Test Set	E5515C	MY52102706	2019/4/17	2020/4/16
Agilent	ENA Series Network Analyzer	E5071C	MY46111157	2019/4/17	2020/4/16
SPEAG	Dielectric Probe Kit	DAK-3.5	1071	2019/10/28	2020/10/27
Anritsu	Vector Signal Generator	MG3710A	6201682672	2020/1/17	2021/1/16
Rohde & Schwarz	Power Meter	NRVD	102081	2019/8/15	2020/8/14
Rohde & Schwarz	Power Sensor	NRV-Z5	100538	2019/8/14	2020/8/13
Rohde & Schwarz	Power Sensor	NRV-Z5	100539	2019/8/14	2020/8/13
R&S	CBT BLUETOOTH TESTER	CBT	101246	2019/4/15	2020/4/14
EXA	Spectrum Analyzer	FSV7	100319	2019/10/18	2020/10/17
Testo	Hygrometer	608-H1	1241332088	2020/1/8	2021/1/7
FLUKE	DIGITAC THERMOMETER	51II	97240029	2019/8/15	2020/8/14
ARRA	Power Divider	A3200-2	N/A	Note 1	
MCL	Attenuation1	BW-S10W5+	N/A	Note 1	
MCL	Attenuation2	BW-S10W5+	N/A	Note 1	
MCL	Attenuation3	BW-S10W5+	N/A	Note 1	
BONN	POWER AMPLIFIER	BLMA 0830-3	087193A	Note 1	
BONN	POWER AMPLIFIER	BLMA 2060-2	087193B	Note 1	
Agilent	Dual Directional Coupler	778D	20500	Note 1	
Agilent	Dual Directional Coupler	11691D	MY48151020	Note 1	

General Note:

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.

11. System Verification

11.1 Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.2.




Fig 10.1Photo of Liquid Height for Head SAR



Fig 10.2 Photo of Liquid Height for Body SAR

11.2 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
2600	54.8	0	0	0.1	0	45.1	1.96	39.0

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
750	22.8	0.872	41.200	0.89	41.90	-2.02	-1.67	±5	2020/1/3
835	22.8	0.911	42.722	0.90	41.50	1.22	2.94	±5	2020/1/5
1750	22.6	1.343	38.539	1.37	40.10	-1.97	-3.89	±5	2020/1/11
1900	22.9	1.391	40.645	1.40	40.00	-0.64	1.61	±5	2020/1/18
2300	22.8	1.687	41.314	1.67	39.50	1.02	4.59	±5	2020/1/20
2450	22.7	1.793	40.768	1.80	39.20	-0.39	4.00	±5	2020/1/22
2450	22.6	1.860	38.535	1.80	39.20	3.33	-1.70	±5	2020/2/29

11.3 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
2020/1/3	750	250	D750V3-1087	3857	690	2.08	8.36	8.32	-0.48
2020/1/5	835	250	D835V2-4d151	3857	690	2.40	9.30	9.6	3.23
2020/1/11	1750	250	D1750V2-1090	3857	690	8.44	36.40	33.76	-7.25
2020/1/18	1900	250	D1900V2-5d170	3857	690	9.51	39.00	38.04	-2.46
2020/1/20	2300	250	D2300V2-1006	3857	690	12.60	48.70	50.4	3.49
2020/1/22	2450	250	D2450V2-908	3857	690	12.50	52.80	50	-5.30
2020/2/29	2450	250	D2450V2-908	3857	1210	12.80	52.80	51.2	-3.03




Fig 8.3.1 System Performance Check Setup



Fig 8.3.2 Setup Photo

12. RF Exposure Positions

12.1 Ear and handset reference point

Figure 9.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled “M,” the left ear reference point (ERP) is marked “LE,” and the right ERP is marked “RE.” Each ERP is 15 mm along the B-M (back-mouth) line behind the entrance-to-ear-canal (EEC) point, as shown in Figure 9.1.2 The Reference Plane is defined as passing through the two ear reference points and point M. The line N-F (neck-front), also called the reference pivoting line, is normal to the Reference Plane and perpendicular to both a line passing through RE and LE and the B-M line (see Figure 9.1.3). Both N-F and B-M lines should be marked on the exterior of the phantom shell to facilitate handset positioning. Posterior to the N-F line the ear shape is a flat surface with 6 mm thickness at each ERP, and forward of the N-F line the ear is truncated, as illustrated in Figure 9.1.2. The ear truncation is introduced to preclude the ear lobe from interfering with handset tilt, which could lead to unstable positioning at the cheek.




Fig 9.1.1 Front, back, and side views of SAM twin phantom




Fig 9.1.2 Close-up side view of phantom showing the ear region.




Fig 9.1.3 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

12.2 Definition of the cheek position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 9.2.1 and Figure 9.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 9.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 9.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
3. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 9.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
4. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.
5. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
6. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
7. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 9.2.3. The actual rotation angles should be documented in the test report.




Fig 9.2.1 Handset vertical and horizontal reference lines—"fixed case"




Fig 9.2.2 Handset vertical and horizontal reference lines—"clam-shell case"




Fig 9.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

12.3 Definition of the tilt position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15°.
3. Rotate the handset around the horizontal line by 15°.
4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure 9.3.1. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point




Fig 9.3.1 Tilt position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which define the Reference Plane for handset positioning, are indicated.

12.4 Body Worn Accessory

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 9.4). Per KDB648474 D04v01r03, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $> 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a handset attached to the handset.

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Fig 9.4 Body Worn Position

12.5 Wireless Router

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 v02r01 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

13. Conducted RF Output Power (Unit: dBm)

<GSM Conducted Power>

1. Per KDB 447498 D01v06, the maximum output power channel is used for SAR testing and for further SAR test reduction.
2. Per KDB 941225 D01v03r01, for SAR test reduction for GSM / GPRS / EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the GPRS (4Tx slots) for GSM850/GSM1900 is considered as the primary mode.
3. Other configurations of GSM / GPRS / EDGE are considered as secondary modes. The 3G SAR test reduction procedure is applied, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode, SAR measurement is not required for the secondary mode

<Default, Hotspot, Near-Body, Extremity Power Mode>

GSM850	Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel	128	189	251		128	189	251	
Frequency (MHz)	824.2	836.4	848.8		824.2	836.4	848.8	
GSM 1 Tx slot	32.13	32.19	32.18	33.50	23.13	23.19	23.18	24.50
GPRS 1 Tx slot	32.12	32.18	32.17	33.50	23.12	23.18	23.17	24.50
GPRS 2 Tx slots	31.56	31.63	31.64	32.50	25.56	25.63	25.64	26.50
GPRS 3 Tx slots	29.99	30.07	30.16	31.00	25.73	25.81	25.90	26.74
GPRS 4 Tx slots	28.92	29.04	29.09	30.00	25.92	26.04	26.09	27.00
EDGE 1 Tx slot	27.63	27.66	27.82	28.50	18.63	18.66	18.82	19.50
EDGE 2 Tx slots	26.85	26.50	26.65	27.50	20.85	20.50	20.65	21.50
EDGE 3 Tx slots	24.40	24.35	24.50	25.50	20.14	20.09	20.24	21.24
EDGE 4 Tx slots	23.12	23.00	23.30	24.00	20.12	20.00	20.30	21.00

GSM1900	Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel	512	661	810		512	661	810	
Frequency (MHz)	1850.2	1880	1909.8		1850.2	1880	1909.8	
GSM 1 Tx slot	29.27	29.24	29.22	30.50	20.27	20.24	20.22	21.50
GPRS 1 Tx slot	29.26	29.23	29.21	30.50	20.26	20.23	20.21	21.50
GPRS 2 Tx slots	28.58	28.60	28.59	29.50	22.58	22.60	22.59	23.50
GPRS 3 Tx slots	26.85	26.89	26.90	27.50	22.59	22.63	22.64	23.24
GPRS 4 Tx slots	25.77	25.82	25.86	26.50	22.77	22.82	22.86	23.50
EDGE 1 Tx slot	26.61	26.60	26.67	27.50	17.61	17.60	17.67	18.50
EDGE 2 Tx slots	25.71	25.72	26.02	27.00	19.71	19.72	20.02	21.00
EDGE 3 Tx slots	23.67	23.65	23.66	24.50	19.41	19.39	19.40	20.24
EDGE 4 Tx slots	22.53	22.53	22.52	23.50	19.53	19.53	19.52	20.50

<WCDMA Conducted Power>

1. The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
2. The procedures in KDB 941225 D01v03r01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.
3. For HSPA+ devices supporting 16 QAM in the uplink, power measurements procedure is according to the configurations in Table C.11.1.4 of 3GPP TS 34.121-1.
4. For DC-HSDPA, the device was configured according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1, with the primary and the secondary serving HS-DSCH Cell enabled during the power measurement.

A summary of these settings are illustrated below:

HSDPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each
 - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - iii. Set RMC 12.2Kbps + HSDPA mode.
 - iv. Set Cell Power = -86 dBm
 - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - vi. Select HSDPA Uplink Parameters
 - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
 - viii. Set Ack-Nack Repetition Factor to 3
 - ix. Set CQI Feedback Cycle (k) to 4 ms
 - x. Set CQI Repetition Factor to 2
 - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5
Note 1: Δ_{ACK}, Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$. Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$, and $\Delta_{CQI} = 24/15$ with $\beta_{HS} = 24/15 * \beta_c$. Note 3: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{HS}/\beta_c = 24/15$. For all other combinations of DPDCCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases. Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.							

Setup Configuration

HSUPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting * :
 - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - ii. Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
 - iii. Set Cell Power = -86 dBm
 - iv. Set Channel Type = 12.2k + HSPA
 - v. Set UE Target Power
 - vi. Power Ctrl Mode= Alternating bits
 - vii. Set and observe the E-TFCI
 - viii. Confirm that E-TFCI is equal to the target E-TFCI of 75 for sub-test 1, and other subtest's E-TFCI
- d. The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (Note 4) (Note 5)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2) (Note 6)	AG Index (Note 5)	E-TFCI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1} : 47/15 β_{ed2} : 47/15	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15	0	-	-	5/15	5/15	47/15	4	1	1.0	0.0	12	67

Note 1: For sub-test 1 to 4, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$. For sub-test 5, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 5/15$ with $\beta_{hs} = 5/15 * \beta_c$.

Note 2: CM = 1 for $\beta_d/\beta_c = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 5: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Note 6: For subtests 2, 3 and 4, UE may perform E-DPDCH power scaling at max power which could results in slightly smaller MPR values.

Setup Configuration


DC-HSDPA 3GPP release 8 Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration below
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set RMC 12.2Kbps + HSDPA mode.
 - ii. Set Cell Power = -25 dBm
 - iii. Set HS-DSCH Configuration Type to FRC (H-set 12, QPSK)
 - iv. Select HSDPA Uplink Parameters
 - v. Set Gain Factors (β_c and β_d) and parameters were set according to each Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - a). Subtest 1: $\beta_c/\beta_d=2/15$
 - b). Subtest 2: $\beta_c/\beta_d=12/15$
 - c). Subtest 3: $\beta_c/\beta_d=15/8$
 - d). Subtest 4: $\beta_c/\beta_d=15/4$
 - vi. Set Delta ACK, Delta NACK and Delta CQI = 8
 - vii. Set Ack-Nack Repetition Factor to 3
 - viii. Set CQI Feedback Cycle (k) to 4 ms
 - ix. Set CQI Repetition Cycle to 2
 - x. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
A summary of these settings are illustrated below:

C.8.1.12 Fixed Reference Channel Definition H-Set 12
Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table.		
Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		


Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)
Setup Configuration

HSPA+ 3GPP release 7 (uplink category 7) 16QAM, Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting * :
 - i. Call Configs = 5.2E:HSPA+:UL with 16QAM
 - ii. Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.4, quoted from the TS 34.121-1 s5.2E
 - iii. Set Channel Params
 - iv. Set Cell Power = -86 dBm
 - v. Set Channel Type = HSPA
 - vi. Set UE Target Power =21 dBm
 - vii. Power Ctrl Mode= All Up Bits
 - viii. Set Manual Uplink DPCH Bc/Bd = Manual
 - ix. Set Manual Uplink DPCH Bc and Bd=15,15(for 34.121-1 v8.10.0 table C11.1.4 sub-test 1)
 - x. Set HSPA Conn DL Channel Levels
 - xi. Set HS-SCCH Configs
 - xii. Set RB Test Mode Setup
 - xiii. Set Common HSUPA Parameters
 - xiv. Set Serving Grant
 - xv. Confirm that E-TFCI is equal to the target E-TFCI of 105 for sub-test 1, and other subtest's E-TFCI
- d. The transmitted maximum output power was recorded.

Table C.11.1.4: β values for transmitter characteristics tests with HS-DPCCH and E-DCH with 16QAM

Sub-test	β_c (Note 3)	β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (2xSF2) (Note 4)	β_{ed} (2xSF4) (Note 4)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 4)	E-TFCI (Note 5)	E-TFCI (boost)
1	1	0	30/15	30/15	β_{ed1} : 30/15 β_{ed2} : 30/15	β_{ed3} : 24/15 β_{ed4} : 24/15	3.5	2.5	14	105	105
Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$. Note 2: CM = 3.5 and the MPR is based on the relative CM difference, MPR = MAX(CM-1,0). Note 3: DPDCH is not configured, therefore the β_c is set to 1 and $\beta_d = 0$ by default. Note 4: β_{ed} can not be set directly; it is set by Absolute Grant Value. Note 5: All the sub-tests require the UE to transmit 2SF2+2SF4 16QAM EDCH and they apply for UE using E-DPDCH category 7. E-DCH TTI is set to 2ms TTI and E-DCH table index = 2. To support these E-DCH configurations DPDCH is not allocated. The UE is signaled to use the extrapolation algorithm.											

Setup Configuration

<WCDMA Conducted Power>
General Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA / HSPA+ is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA / HSPA+ to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA / HSPA+, and according to the following RF output power, the output power results of the secondary modes (HSUPA, HSDPA, DC-HSDPA / HSPA+) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA / HSPA+.

<Default Power Mode>

Band		WCDMA II			Tune-up Limit (dBm)	WCDMA IV			Tune-up Limit (dBm)	WCDMA V			Tune-up Limit (dBm)
TX Channel		9262	9400	9538		1312	1413	1513		4132	4182	4233	
Rx Channel		9662	9800	9938		1537	1638	1738		4357	4407	4458	
Frequency (MHz)		1852.4	1880	1907.6		1712.4	1732.6	1752.6		826.4	836.4	846.6	
3GPP Rel 99	AMR 12.2Kbps	23.89	23.85	23.89	25.00	23.60	23.56	23.54	25.00	23.83	23.76	23.79	25.00
3GPP Rel 99	RMC 12.2Kbps	23.90	23.88	23.91	25.00	23.64	23.58	23.56	25.00	23.85	23.78	23.81	25.00
3GPP Rel 6	HSDPA Subtest-1	22.90	22.94	22.81	24.00	23.11	23.02	23.13	24.00	22.77	22.71	22.66	24.00
3GPP Rel 6	HSDPA Subtest-2	22.83	22.86	22.69	24.00	22.98	22.99	23.01	24.00	22.69	22.61	22.61	24.00
3GPP Rel 6	HSDPA Subtest-3	22.33	22.38	22.16	23.50	22.51	22.51	22.54	23.50	22.18	22.15	22.12	23.50
3GPP Rel 6	HSDPA Subtest-4	22.27	22.36	22.12	23.50	22.48	22.47	22.51	23.50	22.16	22.07	22.07	23.50
3GPP Rel 8	DC-HSDPA Subtest-1	22.89	22.89	22.88	24.00	22.99	23.00	22.80	24.00	22.70	22.70	22.65	24.00
3GPP Rel 8	DC-HSDPA Subtest-2	22.87	22.90	22.89	24.00	22.98	22.99	23.01	24.00	22.76	22.71	22.69	24.00
3GPP Rel 8	DC-HSDPA Subtest-3	22.32	22.41	22.31	23.50	22.51	22.45	22.46	23.50	22.20	22.23	22.21	23.50
3GPP Rel 8	DC-HSDPA Subtest-4	22.31	22.30	22.21	23.50	22.45	22.50	22.45	23.50	22.12	22.12	22.12	23.50
3GPP Rel 6	HSUPA Subtest-1	20.97	20.85	20.89	22.00	20.83	20.79	20.76	22.00	21.10	21.02	21.18	22.00
3GPP Rel 6	HSUPA Subtest-2	20.97	20.91	20.93	22.00	20.79	20.71	20.69	22.00	21.05	21.02	21.07	22.00
3GPP Rel 6	HSUPA Subtest-3	21.93	21.91	21.81	23.00	21.79	21.74	21.73	23.00	22.10	22.08	22.13	23.00
3GPP Rel 6	HSUPA Subtest-4	20.44	20.41	20.36	22.00	20.34	20.25	20.22	22.00	20.63	20.53	20.63	22.00
3GPP Rel 6	HSUPA Subtest-5	21.90	22.40	21.97	23.50	21.70	21.60	21.70	23.50	22.00	22.00	22.00	23.50
3GPP Rel 7	HSPA+ (16QAM) Subtest-1	21.82	21.74	21.73	23.50	21.55	21.53	21.53	23.50	21.79	21.76	21.83	23.50


<Hotspot, Near-Body, Extremity Power Mode>

Band		WCDMA II			Tune-up Limit (dBm)	WCDMA IV			Tune-up Limit (dBm)	WCDMA V			Tune-up Limit (dBm)
TX Channel		9262	9400	9538		1312	1413	1513		4132	4182	4233	
Rx Channel		9662	9800	9938		1537	1638	1738		4357	4407	4458	
Frequency (MHz)		1852.4	1880	1907.6		1712.4	1732.6	1752.6		826.4	836.4	846.6	
3GPP Rel 99	AMR 12.2Kbps	23.89	23.85	23.89	24.50	20.80	20.68	20.65	22.00	23.83	23.76	23.79	25.00
3GPP Rel 99	RMC 12.2Kbps	23.90	23.88	23.91	24.50	20.81	20.71	20.67	22.00	23.85	23.78	23.81	25.00
3GPP Rel 6	HSDPA Subtest-1	22.90	22.94	22.81	23.50	20.12	20.09	20.16	21.50	22.77	22.71	22.66	24.00
3GPP Rel 6	HSDPA Subtest-2	22.83	22.86	22.69	23.50	20.17	20.10	20.17	21.50	22.69	22.61	22.61	24.00
3GPP Rel 6	HSDPA Subtest-3	22.33	22.38	22.16	23.00	19.67	19.80	19.89	21.00	22.18	22.15	22.12	23.50
3GPP Rel 6	HSDPA Subtest-4	22.27	22.36	22.12	23.00	19.97	19.96	19.94	21.00	22.16	22.07	22.07	23.50
3GPP Rel 8	DC-HSDPA Subtest-1	22.89	22.89	22.88	23.50	20.10	20.05	20.14	21.50	22.70	22.70	22.65	24.00
3GPP Rel 8	DC-HSDPA Subtest-2	22.87	22.90	22.89	23.50	20.15	20.06	20.15	21.50	22.76	22.71	22.69	24.00
3GPP Rel 8	DC-HSDPA Subtest-3	22.32	22.41	22.31	23.00	19.67	19.97	20.00	21.00	22.20	22.23	22.21	23.50
3GPP Rel 8	DC-HSDPA Subtest-4	22.31	22.30	22.21	23.00	19.95	19.92	19.92	21.00	22.12	22.12	22.12	23.50
3GPP Rel 6	HSUPA Subtest-1	20.97	20.85	20.89	21.50	18.67	18.78	18.76	20.00	21.10	21.02	21.18	22.00
3GPP Rel 6	HSUPA Subtest-2	20.97	20.91	20.93	21.50	18.38	18.28	18.19	20.00	21.05	21.02	21.07	22.00
3GPP Rel 6	HSUPA Subtest-3	21.93	21.91	21.81	22.50	19.25	19.37	19.32	21.00	22.10	22.08	22.13	23.00
3GPP Rel 6	HSUPA Subtest-4	20.44	20.41	20.36	21.50	18.33	18.23	18.34	20.00	20.63	20.53	20.63	22.00
3GPP Rel 6	HSUPA Subtest-5	21.90	22.40	21.97	23.00	19.56	19.60	19.56	21.00	22.00	22.00	22.00	23.50
3GPP Rel 7	HSPA+ (16QAM) Subtest-1	21.82	21.74	21.73	23.00	19.16	19.40	19.37	21.00	21.79	21.76	21.83	23.50


<LTE Conducted Power>

General Note:

1. Anritsu MT8820C base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
7. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
8. For LTE B4 / B5 / B12 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
9. LTE band 4 SAR test was covered by Band 66; according to April 2015 TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. the maximum output power, including tolerance, for the smaller band is $\leq$ the larger band to qualify for the SAR test exclusion
 - b. the channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band
10. According to 2017 TCB workshop, for 64 QAM and 16 QAM should be verified by checking the signal constellation with a call box to avoid incorrect maximum power levels due to MPR and other requirements associated with signal modulation, and the following figure is taken from the "Fundamental Measurement >> Modulation Analysis >> constellation" mode of the device connect to the MT8821C base station, therefore, the device 64QAM and 16QAM signal modulation are correct.



64QAM



16QAM

<Default Power Mode>
<LTE Band 2>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				18700	18900	19100		
Frequency (MHz)				1860	1880	1900		
20	QPSK	1	0	22.36	22.43	22.43	24	0
20	QPSK	1	49	22.75	22.58	22.58		
20	QPSK	1	99	22.45	22.43	22.34		
20	QPSK	50	0	21.47	21.46	21.54	23	1
20	QPSK	50	24	21.60	21.50	21.48		
20	QPSK	50	50	21.47	21.27	21.44		
20	QPSK	100	0	21.52	21.39	21.51		
20	16QAM	1	0	21.44	21.48	21.66	23	1
20	16QAM	1	49	21.86	21.74	21.71		
20	16QAM	1	99	21.45	21.40	21.42		
20	16QAM	50	0	20.47	20.53	20.54	22	2
20	16QAM	50	24	20.51	20.41	20.49		
20	16QAM	50	50	20.40	20.36	20.42		
20	16QAM	100	0	20.43	20.44	20.48		
20	64QAM	1	0	20.55	20.50	20.77	22	2
20	64QAM	1	49	20.68	20.62	20.73		
20	64QAM	1	99	20.49	20.53	20.32		
20	64QAM	50	0	19.68	19.86	19.82	21	3
20	64QAM	50	24	19.76	19.79	19.84		
20	64QAM	50	50	19.68	19.62	19.66		
20	64QAM	100	0	19.76	19.71	19.73		
Channel				18675	18900	19125	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1857.5	1880	1902.5		
15	QPSK	1	0	22.47	22.45	22.36	24	0
15	QPSK	1	37	22.45	22.47	22.49		
15	QPSK	1	74	22.36	22.30	22.25		
15	QPSK	36	0	21.46	21.47	21.50	23	1
15	QPSK	36	20	21.44	21.44	21.53		
15	QPSK	36	39	21.46	21.45	21.55		
15	QPSK	75	0	22.51	22.47	22.35	23	1
15	16QAM	1	0	21.60	21.59	21.49		
15	16QAM	1	37	21.94	21.51	21.56		
15	16QAM	1	74	21.55	21.47	21.54	22	2
15	16QAM	36	0	20.50	20.46	20.50		
15	16QAM	36	20	20.59	20.47	20.38		
15	16QAM	36	39	20.51	20.45	20.41	22	2
15	16QAM	75	0	21.39	21.58	21.32		
15	64QAM	1	0	20.81	20.79	20.56		
15	64QAM	1	37	20.86	20.70	20.73	22	2
15	64QAM	1	74	20.96	20.80	20.57		
15	64QAM	36	0	19.73	19.78	19.78		
15	64QAM	36	20	19.71	19.79	19.74	21	3
15	64QAM	36	39	19.73	19.72	19.77		
15	64QAM	75	0	19.96	20.07	19.86		
Channel				18650	18900	19150	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1855	1880	1905		
10	QPSK	1	0	22.47	22.42	22.33	24	0
10	QPSK	1	25	22.55	22.55	22.55		
10	QPSK	1	49	22.38	22.31	22.29		

10	QPSK	25	0	21.57	21.51	21.48	23	1
10	QPSK	25	12	21.56	21.48	21.53		
10	QPSK	25	25	21.51	21.53	21.41		
10	QPSK	50	0	21.44	21.57	21.52		
10	16QAM	1	0	21.46	21.37	21.55	23	1
10	16QAM	1	25	21.56	21.45	21.56		
10	16QAM	1	49	21.42	21.27	21.54		
10	16QAM	25	0	20.51	20.50	20.47	22	2
10	16QAM	25	12	20.40	20.35	20.42		
10	16QAM	25	25	20.54	20.42	20.45		
10	16QAM	50	0	20.37	20.52	20.49		
10	64QAM	1	0	20.84	20.84	20.72	22	2
10	64QAM	1	25	20.94	20.82	20.73		
10	64QAM	1	49	20.81	20.58	20.78		
10	64QAM	25	0	19.69	19.82	19.88	21	3
10	64QAM	25	12	19.70	19.70	19.83		
10	64QAM	25	25	19.61	19.72	19.64		
10	64QAM	50	0	19.75	19.82	19.67		
Channel				18625	18900	19175	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1852.5	1880	1907.5		
5	QPSK	1	0	22.33	22.28	22.25	24	0
5	QPSK	1	12	22.74	22.70	22.46		
5	QPSK	1	24	22.35	22.33	22.27		
5	QPSK	12	0	21.45	21.43	21.39	23	1
5	QPSK	12	7	21.54	21.46	21.55		
5	QPSK	12	13	21.48	21.58	21.40		
5	QPSK	25	0	21.46	21.53	21.36		
5	16QAM	1	0	21.56	21.56	21.62	23	1
5	16QAM	1	12	21.76	21.95	21.76		
5	16QAM	1	24	21.58	21.52	21.45		
5	16QAM	12	0	20.31	20.44	20.50	22	2
5	16QAM	12	7	20.39	20.54	20.57		
5	16QAM	12	13	20.37	20.50	20.49		
5	16QAM	25	0	20.54	20.49	20.44		
5	64QAM	1	0	20.74	20.74	20.71	22	2
5	64QAM	1	12	20.93	21.13	20.95		
5	64QAM	1	24	20.73	20.71	20.78		
5	64QAM	12	0	19.76	19.61	19.78	21	3
5	64QAM	12	7	19.68	19.80	19.84		
5	64QAM	12	13	19.83	19.72	19.80		
5	64QAM	25	0	19.64	19.73	19.76		
Channel				18615	18900	19185	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1851.5	1880	1908.5		
3	QPSK	1	0	22.44	22.53	22.41	24	0
3	QPSK	1	8	22.46	22.44	22.44		
3	QPSK	1	14	22.56	22.44	22.50		
3	QPSK	8	0	21.51	21.49	21.38	23	1
3	QPSK	8	4	21.49	21.51	21.45		
3	QPSK	8	7	21.53	21.60	21.40		
3	QPSK	15	0	21.52	21.47	21.51		
3	16QAM	1	0	21.51	21.57	21.53	23	1
3	16QAM	1	8	21.82	21.48	21.51		
3	16QAM	1	14	21.83	21.84	21.93		
3	16QAM	8	0	20.49	20.54	20.51	22	2
3	16QAM	8	4	20.57	20.59	20.56		
3	16QAM	8	7	20.64	20.56	20.60		



FCC SAR TEST REPORT

Report No. : FA9D3107

3	16QAM	15	0	20.35	20.50	20.48		
3	64QAM	1	0	20.62	20.84	20.95		
3	64QAM	1	8	21.05	20.94	20.84	22	2
3	64QAM	1	14	20.83	20.88	20.82		
3	64QAM	8	0	19.92	19.80	19.83		
3	64QAM	8	4	19.90	19.83	19.83	21	3
3	64QAM	8	7	19.75	19.66	19.76		
3	64QAM	15	0	19.70	19.67	19.79		
Channel				18607	18900	19193	Tune-up limit	MPR
Frequency (MHz)				1850.7	1880	1909.3	(dBm)	(dB)
1.4	QPSK	1	0	22.47	22.43	22.35		
1.4	QPSK	1	3	22.71	22.69	22.60		
1.4	QPSK	1	5	22.48	22.49	22.31		
1.4	QPSK	3	0	22.67	22.45	22.54	24	0
1.4	QPSK	3	1	22.68	22.60	22.53		
1.4	QPSK	3	3	22.62	22.54	22.48		
1.4	QPSK	6	0	21.68	21.64	21.48	23	1
1.4	16QAM	1	0	21.58	21.89	21.53		
1.4	16QAM	1	3	21.64	21.68	21.62		
1.4	16QAM	1	5	21.49	21.87	21.61		
1.4	16QAM	3	0	21.55	21.44	21.54	23	1
1.4	16QAM	3	1	21.67	21.40	21.70		
1.4	16QAM	3	3	21.44	21.64	21.52		
1.4	16QAM	6	0	20.64	20.59	20.62	22	2
1.4	64QAM	1	0	20.93	20.69	20.78		
1.4	64QAM	1	3	21.05	20.98	20.70		
1.4	64QAM	1	5	20.88	20.94	20.69		
1.4	64QAM	3	0	20.78	20.86	20.69	22	2
1.4	64QAM	3	1	20.79	20.75	20.80		
1.4	64QAM	3	3	20.83	20.85	20.82		
1.4	64QAM	6	0	19.68	19.89	19.74	21	3

<LTE Band 4>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20050	20175	20300	24	0
Frequency (MHz)				1720	1732.5	1745		
20	QPSK	1	0	22.16	22.17	22.13		
20	QPSK	1	49	22.38	22.58	22.29	23	1
20	QPSK	1	99	22.23	22.32	22.31		
20	QPSK	50	0	21.35	21.45	21.37		
20	QPSK	50	24	21.39	21.33	21.37	23	1
20	QPSK	50	50	21.44	21.26	21.23		
20	QPSK	100	0	21.42	21.43	21.34		
20	16QAM	1	0	21.43	21.51	21.40	23	1
20	16QAM	1	49	21.65	21.60	21.72		
20	16QAM	1	99	21.45	21.42	21.34		
20	16QAM	50	0	20.39	20.45	20.42	22	2
20	16QAM	50	24	20.51	20.49	20.48		
20	16QAM	50	50	20.45	20.32	20.33		
20	16QAM	100	0	20.40	20.39	20.48	22	2
20	64QAM	1	0	20.61	20.41	20.34		
20	64QAM	1	49	20.72	20.84	20.49		
20	64QAM	1	99	20.83	20.45	20.42	21	3
20	64QAM	50	0	19.63	19.67	19.82		
20	64QAM	50	24	19.81	19.81	19.75		
20	64QAM	50	50	19.65	19.54	19.52	21	3
20	64QAM	100	0	19.75	19.71	19.66		
Channel				20025	20175	20325	24	0
Frequency (MHz)				1717.5	1732.5	1747.5		
15	QPSK	1	0	22.29	22.32	22.20		
15	QPSK	1	37	22.36	22.42	22.35	23	1
15	QPSK	1	74	22.07	22.12	22.14		
15	QPSK	36	0	21.47	21.49	21.46		
15	QPSK	36	20	21.37	21.37	21.39	23	1
15	QPSK	36	39	21.35	21.34	21.32		
15	QPSK	75	0	21.44	21.41	21.45		
15	16QAM	1	0	21.56	21.86	21.78	23	1
15	16QAM	1	37	21.95	21.95	21.96		
15	16QAM	1	74	21.71	21.51	21.67		
15	16QAM	36	0	20.45	20.39	20.52	22	2
15	16QAM	36	20	20.38	20.53	20.44		
15	16QAM	36	39	20.38	20.24	20.28		
15	16QAM	75	0	20.52	20.38	20.49	22	2
15	64QAM	1	0	20.61	20.65	20.93		
15	64QAM	1	37	20.84	20.93	20.71		
15	64QAM	1	74	20.48	20.53	20.48	21	3
15	64QAM	36	0	19.77	19.79	19.78		
15	64QAM	36	20	19.71	19.71	19.64		
15	64QAM	36	39	19.65	19.62	19.68	21	3
15	64QAM	75	0	19.68	19.60	19.70		
Channel				20000	20175	20350	24	0
Frequency (MHz)				1715	1732.5	1750		
10	QPSK	1	0	22.35	22.36	22.29		
10	QPSK	1	25	22.38	22.34	22.51	24	0
10	QPSK	1	49	22.18	22.19	22.28		
10	QPSK	25	0	21.45	21.46	21.37	23	1
10	QPSK	25	12	21.40	21.37	21.32		

10	QPSK	25	25	21.44	21.38	21.37		
10	QPSK	50	0	21.48	21.44	21.40		
10	16QAM	1	0	21.63	21.86	21.41		
10	16QAM	1	25	21.82	21.83	21.47	23	1
10	16QAM	1	49	21.76	21.63	21.36		
10	16QAM	25	0	20.39	20.50	20.40		
10	16QAM	25	12	20.43	20.38	20.35	22	2
10	16QAM	25	25	20.39	20.37	20.36		
10	16QAM	50	0	20.53	20.50	20.33		
10	64QAM	1	0	20.98	21.17	20.73	22	2
10	64QAM	1	25	21.08	20.90	21.00		
10	64QAM	1	49	20.91	20.73	20.73		
10	64QAM	25	0	19.74	19.90	19.85	21	3
10	64QAM	25	12	19.78	19.70	19.68		
10	64QAM	25	25	19.78	19.64	19.70		
10	64QAM	50	0	19.75	19.64	19.65		
Channel				19975	20175	20375	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1732.5	1752.5		
5	QPSK	1	0	22.22	22.25	22.29	24	0
5	QPSK	1	12	22.54	22.57	22.35		
5	QPSK	1	24	22.09	22.13	22.16		
5	QPSK	12	0	21.38	21.32	21.31	23	1
5	QPSK	12	7	21.39	21.32	21.30		
5	QPSK	12	13	21.36	21.42	21.37		
5	QPSK	25	0	21.40	21.38	21.28	23	1
5	16QAM	1	0	21.52	21.69	21.33		
5	16QAM	1	12	21.58	21.65	21.56		
5	16QAM	1	24	21.56	21.63	21.63	22	2
5	16QAM	12	0	20.35	20.39	20.33		
5	16QAM	12	7	20.36	20.40	20.41		
5	16QAM	12	13	20.36	20.32	20.32	22	2
5	16QAM	25	0	20.31	20.40	20.46		
5	64QAM	1	0	20.67	20.73	20.64		
5	64QAM	1	12	21.04	21.06	20.72	22	2
5	64QAM	1	24	20.67	20.92	20.71		
5	64QAM	12	0	19.64	19.66	19.63		
5	64QAM	12	7	19.67	19.70	19.77	21	3
5	64QAM	12	13	19.63	19.69	19.71		
5	64QAM	25	0	19.64	19.68	19.70		
Channel				19965	20175	20385	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1732.5	1753.5		
3	QPSK	1	0	22.38	22.40	22.31	24	0
3	QPSK	1	8	22.37	22.26	22.34		
3	QPSK	1	14	22.33	22.18	22.23		
3	QPSK	8	0	21.31	21.29	21.35	23	1
3	QPSK	8	4	21.33	21.33	21.31		
3	QPSK	8	7	21.41	21.37	21.32		
3	QPSK	15	0	21.39	21.29	21.32	23	1
3	16QAM	1	0	21.47	21.88	21.48		
3	16QAM	1	8	21.65	21.75	21.63		
3	16QAM	1	14	21.62	21.83	21.86	22	2
3	16QAM	8	0	20.41	20.53	20.48		
3	16QAM	8	4	20.41	20.48	20.58		
3	16QAM	8	7	20.41	20.46	20.44	22	2
3	16QAM	15	0	20.45	20.50	20.48		
3	64QAM	1	0	20.98	20.93	21.06	22	2



FCC SAR TEST REPORT

Report No. : FA9D3107

3	64QAM	1	8	20.63	21.03	20.98	21	3
3	64QAM	1	14	20.96	21.03	20.77		
3	64QAM	8	0	19.64	19.73	19.78		
3	64QAM	8	4	19.61	19.70	19.75		
3	64QAM	8	7	19.75	19.71	19.71		
3	64QAM	15	0	19.67	19.62	19.68		
Channel				19957	20175	20393	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1732.5	1754.3		
1.4	QPSK	1	0	22.30	22.22	22.18	24	0
1.4	QPSK	1	3	22.39	22.37	22.29		
1.4	QPSK	1	5	22.33	22.21	22.16		
1.4	QPSK	3	0	22.39	22.35	22.35		
1.4	QPSK	3	1	22.52	22.35	22.43		
1.4	QPSK	3	3	22.36	22.27	22.31		
1.4	QPSK	6	0	21.33	21.46	21.40	23	1
1.4	16QAM	1	0	21.56	21.67	21.68	23	1
1.4	16QAM	1	3	21.79	21.93	21.82		
1.4	16QAM	1	5	21.56	21.68	21.76		
1.4	16QAM	3	0	21.37	21.37	21.35		
1.4	16QAM	3	1	21.48	21.41	21.45		
1.4	16QAM	3	3	21.40	21.20	21.28		
1.4	16QAM	6	0	20.67	20.55	20.43	22	2
1.4	64QAM	1	0	20.62	20.64	21.05	22	2
1.4	64QAM	1	3	20.73	20.73	21.12		
1.4	64QAM	1	5	20.71	21.07	20.99		
1.4	64QAM	3	0	20.38	20.47	20.62		
1.4	64QAM	3	1	20.79	20.67	20.70		
1.4	64QAM	3	3	20.53	20.47	20.68		
1.4	64QAM	6	0	19.63	19.75	19.62	21	3

<LTE Band 5>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20450	20525	20600		
Frequency (MHz)				829	836.5	844		
10	QPSK	1	0	22.62	22.62	22.60		
10	QPSK	1	25	22.77	22.94	22.71	24	0
10	QPSK	1	49	22.57	22.59	22.60		
10	QPSK	25	0	21.82	21.78	21.76		
10	QPSK	25	12	21.83	21.83	21.80	23	1
10	QPSK	25	25	21.71	21.85	21.67		
10	QPSK	50	0	21.70	21.80	21.74		
10	16QAM	1	0	21.98	22.00	21.94	23	1
10	16QAM	1	25	22.11	22.09	21.97		
10	16QAM	1	49	22.01	21.96	21.82		
10	16QAM	25	0	20.81	20.82	20.70	22	2
10	16QAM	25	12	20.79	20.80	20.78		
10	16QAM	25	25	20.74	20.83	20.57		
10	16QAM	50	0	20.79	20.79	20.68	22	2
10	64QAM	1	0	20.97	21.01	20.91		
10	64QAM	1	25	20.98	20.98	20.85		
10	64QAM	1	49	21.05	21.07	20.92	21	3
10	64QAM	25	0	19.87	19.91	19.81		
10	64QAM	25	12	19.90	19.96	19.83		
10	64QAM	25	25	19.90	19.91	19.80	21	3
10	64QAM	50	0	19.85	19.87	19.78		
Channel				20425	20525	20625	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				826.5	836.5	846.5		
5	QPSK	1	0	22.53	22.54	22.47		
5	QPSK	1	12	22.93	22.76	22.70	24	0
5	QPSK	1	24	22.50	22.49	22.47		
5	QPSK	12	0	21.72	21.70	21.70	23	1
5	QPSK	12	7	21.74	21.77	21.71		
5	QPSK	12	13	21.78	21.79	21.65		
5	QPSK	25	0	21.70	21.72	21.65	23	1
5	16QAM	1	0	21.78	21.90	21.75		
5	16QAM	1	12	22.19	22.19	21.97		
5	16QAM	1	24	21.86	21.92	21.74	22	2
5	16QAM	12	0	20.67	20.71	20.65		
5	16QAM	12	7	20.78	20.77	20.66		
5	16QAM	12	13	20.74	20.75	20.62	22	2
5	16QAM	25	0	20.70	20.75	20.61		
5	64QAM	1	0	21.01	21.03	21.00	22	2
5	64QAM	1	12	21.24	21.32	21.15		
5	64QAM	1	24	21.01	21.04	20.94		
5	64QAM	12	0	19.96	19.96	19.94	21	3
5	64QAM	12	7	20.02	20.06	19.92		
5	64QAM	12	13	19.97	20.02	19.86		
5	64QAM	25	0	20.00	20.00	19.86	21	3
Channel				20415	20525	20635		
Frequency (MHz)				825.5	836.5	847.5		
3	QPSK	1	0	22.62	22.64	22.57	24	0
3	QPSK	1	8	22.69	22.60	22.56		
3	QPSK	1	14	22.64	22.59	22.61		
3	QPSK	8	0	21.73	21.73	21.63	23	1
3	QPSK	8	4	21.76	21.79	21.71		



FCC SAR TEST REPORT

Report No. : FA9D3107

3	QPSK	8	7	21.71	21.70	21.63		
3	QPSK	15	0	21.66	21.74	21.68		
3	16QAM	1	0	22.00	22.06	21.75		
3	16QAM	1	8	21.95	21.97	21.82	23	1
3	16QAM	1	14	21.95	21.98	21.84		
3	16QAM	8	0	20.76	20.79	20.67		
3	16QAM	8	4	20.80	20.81	20.73	22	2
3	16QAM	8	7	20.82	20.78	20.66		
3	16QAM	15	0	20.68	20.71	20.65		
3	64QAM	1	0	21.09	21.13	21.03	22	2
3	64QAM	1	8	21.10	21.10	20.97		
3	64QAM	1	14	21.17	21.19	21.04		
3	64QAM	8	0	19.99	20.03	19.93	21	3
3	64QAM	8	4	20.02	20.08	19.95		
3	64QAM	8	7	20.02	20.03	19.92		
3	64QAM	15	0	19.97	19.99	19.90		
Channel				20407	20525	20643	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				824.7	836.5	848.3		
1.4	QPSK	1	0	22.60	22.60	22.53	24	0
1.4	QPSK	1	3	22.78	22.75	22.67		
1.4	QPSK	1	5	22.61	22.57	22.54		
1.4	QPSK	3	0	22.73	22.70	22.62		
1.4	QPSK	3	1	22.76	22.77	22.77		
1.4	QPSK	3	3	22.73	22.70	22.64		
1.4	QPSK	6	0	21.68	21.79	21.78	23	1
1.4	16QAM	1	0	21.91	21.94	21.81	23	1
1.4	16QAM	1	3	22.05	22.10	21.92		
1.4	16QAM	1	5	21.87	21.95	21.78		
1.4	16QAM	3	0	21.70	21.78	21.62		
1.4	16QAM	3	1	21.81	21.87	21.70		
1.4	16QAM	3	3	21.73	21.77	21.65		
1.4	16QAM	6	0	20.82	20.85	20.73	22	2
1.4	64QAM	1	0	21.03	21.18	20.97	22	2
1.4	64QAM	1	3	21.26	21.18	21.12		
1.4	64QAM	1	5	21.08	21.16	20.99		
1.4	64QAM	3	0	21.05	21.14	20.93		
1.4	64QAM	3	1	21.02	21.11	21.05		
1.4	64QAM	3	3	21.08	21.05	21.01		
1.4	64QAM	6	0	19.97	20.07	19.95	21	3



<LTE Band 12>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23060	23095	23130	24	0
Frequency (MHz)				704	707.5	711		
10	QPSK	1	0	22.57	22.52	22.55		
10	QPSK	1	25	22.71	22.53	22.56	23	1
10	QPSK	1	49	22.55	22.56	22.48		
10	QPSK	25	0	21.57	21.67	21.65		
10	QPSK	25	12	21.62	21.68	21.65	23	1
10	QPSK	25	25	21.62	21.59	21.59		
10	QPSK	50	0	21.67	21.66	21.65		
10	16QAM	1	0	21.77	22.00	22.09	23	1
10	16QAM	1	25	22.05	22.01	22.06		
10	16QAM	1	49	22.07	22.00	22.01		
10	16QAM	25	0	20.72	20.62	20.77	22	2
10	16QAM	25	12	20.86	20.70	20.69		
10	16QAM	25	25	20.82	20.65	20.69		
10	16QAM	50	0	20.72	20.71	20.71	22	2
10	64QAM	1	0	20.79	20.83	21.16		
10	64QAM	1	25	21.19	20.78	21.17		
10	64QAM	1	49	20.91	20.86	21.24	21	3
10	64QAM	25	0	19.79	19.77	19.83		
10	64QAM	25	12	19.90	19.83	19.91		
10	64QAM	25	25	19.84	19.74	19.69	21	3
10	64QAM	50	0	19.88	19.84	19.92		
Channel				23035	23095	23155	24	0
Frequency (MHz)				701.5	707.5	713.5		
5	QPSK	1	0	22.39	22.33	22.41		
5	QPSK	1	12	22.67	22.51	22.67	23	1
5	QPSK	1	24	22.33	22.40	22.36		
5	QPSK	12	0	21.48	21.60	21.55		
5	QPSK	12	7	21.66	21.64	21.62	23	1
5	QPSK	12	13	21.65	21.57	21.65		
5	QPSK	25	0	21.50	21.63	21.49		
5	16QAM	1	0	21.62	21.71	21.72	23	1
5	16QAM	1	12	22.00	21.95	21.68		
5	16QAM	1	24	21.84	21.69	21.64		
5	16QAM	12	0	20.47	20.54	20.51	22	2
5	16QAM	12	7	20.56	20.61	20.56		
5	16QAM	12	13	20.58	20.46	20.56		
5	16QAM	25	0	20.60	20.57	20.60	22	2
5	64QAM	1	0	20.98	20.60	20.66		
5	64QAM	1	12	20.89	20.98	20.85		
5	64QAM	1	24	20.68	20.77	20.67	21	3
5	64QAM	12	0	19.52	19.72	19.65		
5	64QAM	12	7	19.62	19.81	19.87		
5	64QAM	12	13	19.79	19.76	19.81	21	3
5	64QAM	25	0	19.75	19.82	19.74		
Channel				23025	23095	23165	24	0
Frequency (MHz)				700.5	707.5	714.5		
3	QPSK	1	0	22.50	22.50	22.48		
3	QPSK	1	8	22.49	22.46	22.49	24	0
3	QPSK	1	14	22.48	22.49	22.41		
3	QPSK	8	0	21.50	21.60	21.58	23	1
3	QPSK	8	4	21.55	21.61	21.58		



FCC SAR TEST REPORT

Report No. : FA9D3107

3	QPSK	8	7	21.55	21.52	21.52		
3	QPSK	15	0	21.60	21.59	21.58		
3	16QAM	1	0	21.70	21.93	22.02		
3	16QAM	1	8	21.98	21.94	21.99	23	1
3	16QAM	1	14	22.00	21.93	21.94		
3	16QAM	8	0	20.65	20.55	20.70		
3	16QAM	8	4	20.79	20.63	20.62	22	2
3	16QAM	8	7	20.75	20.58	20.62		
3	16QAM	15	0	20.65	20.64	20.64		
3	64QAM	1	0	20.72	20.76	21.09	22	2
3	64QAM	1	8	21.12	20.71	21.10		
3	64QAM	1	14	20.84	20.79	21.17		
3	64QAM	8	0	19.72	19.70	19.76	21	3
3	64QAM	8	4	19.83	19.76	19.84		
3	64QAM	8	7	19.77	19.67	19.62		
3	64QAM	15	0	19.81	19.77	19.85		
Channel				23017	23095	23173	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				699.7	707.5	715.3		
1.4	QPSK	1	0	22.41	22.46	22.43	24	0
1.4	QPSK	1	3	22.67	22.56	22.48		
1.4	QPSK	1	5	22.45	22.50	22.50		
1.4	QPSK	3	0	22.51	22.43	22.49		
1.4	QPSK	3	1	22.62	22.48	22.50		
1.4	QPSK	3	3	22.59	22.59	22.54		
1.4	QPSK	6	0	21.57	21.58	21.69	23	1
1.4	16QAM	1	0	21.67	21.34	21.48	23	1
1.4	16QAM	1	3	21.59	21.70	21.70		
1.4	16QAM	1	5	21.69	21.54	21.57		
1.4	16QAM	3	0	21.54	21.59	21.51		
1.4	16QAM	3	1	21.57	21.41	21.48		
1.4	16QAM	3	3	21.66	21.55	21.36		
1.4	16QAM	6	0	20.63	20.57	20.58	22	2
1.4	64QAM	1	0	20.81	20.75	20.67	22	2
1.4	64QAM	1	3	21.03	20.83	20.86		
1.4	64QAM	1	5	20.84	20.74	20.76		
1.4	64QAM	3	0	20.73	20.64	20.71		
1.4	64QAM	3	1	20.58	20.61	20.84		
1.4	64QAM	3	3	20.62	20.71	20.73		
1.4	64QAM	6	0	19.81	19.67	19.72	21	3

<LTE Band 14>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23330				
Frequency (MHz)				793				
10	QPSK	1	0		22.44		24	0
10	QPSK	1	25		22.66			
10	QPSK	1	49		22.41			
10	QPSK	25	0		21.54		23	1
10	QPSK	25	12		21.56			
10	QPSK	25	25		21.45			
10	QPSK	50	0		21.53		23	1
10	16QAM	1	0		21.73			
10	16QAM	1	25		21.74			
10	16QAM	1	49		21.60		22	2
10	16QAM	25	0		20.48			
10	16QAM	25	12		20.50			
10	16QAM	25	25		20.41		22	2
10	16QAM	50	0		20.46			
10	64QAM	1	0		20.59			
10	64QAM	1	25		20.63		22	2
10	64QAM	1	49		20.59			
10	64QAM	25	0		19.51		21	3
10	64QAM	25	12		19.50			
10	64QAM	25	25		19.45			
10	64QAM	50	0		19.47			
Channel				23305	23330	23355	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				790.5	793	795.5		
5	QPSK	1	0	22.32	22.34	22.36	24	0
5	QPSK	1	12	22.63	22.65	22.63		
5	QPSK	1	24	22.33	22.35	22.37		
5	QPSK	12	0	21.43	21.54	21.56	23	1
5	QPSK	12	7	21.50	21.54	21.55		
5	QPSK	12	13	21.41	21.46	21.50		
5	QPSK	25	0	21.42	21.50	21.51	23	1
5	16QAM	1	0	21.60	21.48	21.54		
5	16QAM	1	12	21.74	21.71	21.80		
5	16QAM	1	24	21.48	21.54	21.62	22	2
5	16QAM	12	0	20.40	20.48	20.49		
5	16QAM	12	7	20.48	20.46	20.49		
5	16QAM	12	13	20.33	20.39	20.44	22	2
5	16QAM	25	0	20.42	20.44	20.48		
5	64QAM	1	0	20.50	20.42	20.47		
5	64QAM	1	12	20.70	20.75	20.78	22	2
5	64QAM	1	24	20.41	20.46	20.55		
5	64QAM	12	0	19.43	19.51	19.53		
5	64QAM	12	7	19.49	19.48	19.53	21	3
5	64QAM	12	13	19.39	19.42	19.50		
5	64QAM	25	0	19.41	19.44	19.52		

<LTE Band 30>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				27710				
Frequency (MHz)				2310				
10	QPSK	1	0		22.51		24	0
10	QPSK	1	25		22.83			
10	QPSK	1	49		22.61			
10	QPSK	25	0		21.64		23	1
10	QPSK	25	12		21.66			
10	QPSK	25	25		21.70			
10	QPSK	50	0		21.67		23	1
10	16QAM	1	0		21.73			
10	16QAM	1	25		21.87			
10	16QAM	1	49		21.65		22	2
10	16QAM	25	0		20.77			
10	16QAM	25	12		20.81			
10	16QAM	25	25		20.72		22	2
10	16QAM	50	0		20.70			
10	64QAM	1	0		21.01			
10	64QAM	1	25		21.05		22	2
10	64QAM	1	49		20.61			
10	64QAM	25	0		20.00			
10	64QAM	25	12		19.93		21	3
10	64QAM	25	25		19.94			
10	64QAM	50	0		19.79			
Channel				27685	27710	27735	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2307.5	2310	2312.5		
5	QPSK	1	0	22.46	22.55	22.46	24	0
5	QPSK	1	12	22.79	22.82	22.79		
5	QPSK	1	24	22.43	22.54	22.54		
5	QPSK	12	0	21.68	21.62	21.62	23	1
5	QPSK	12	7	21.77	21.68	21.71		
5	QPSK	12	13	21.71	21.78	21.68		
5	QPSK	25	0	21.68	21.67	21.64	23	1
5	16QAM	1	0	21.69	21.82	21.69		
5	16QAM	1	12	22.02	22.15	22.16		
5	16QAM	1	24	21.71	21.92	21.66	22	2
5	16QAM	12	0	20.70	20.71	20.58		
5	16QAM	12	7	20.65	20.79	20.64		
5	16QAM	12	13	20.76	20.77	20.62	22	2
5	16QAM	25	0	20.74	20.74	20.69		
5	64QAM	1	0	20.90	20.83	20.83		
5	64QAM	1	12	21.30	21.18	21.21	22	2
5	64QAM	1	24	20.85	20.83	20.96		
5	64QAM	12	0	19.85	19.79	19.84		
5	64QAM	12	7	19.93	19.93	19.87	21	3
5	64QAM	12	13	19.94	19.97	19.78		
5	64QAM	25	0	19.85	19.82	19.74		



<LTE Band 66>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				132072	132322	132572		
Frequency (MHz)				1720	1745	1770		
20	QPSK	1	0	22.01	22.45	22.19		
20	QPSK	1	49	22.21	22.42	22.26	24	0
20	QPSK	1	99	22.00	22.01	22.00		
20	QPSK	50	0	21.17	21.32	21.16		
20	QPSK	50	24	21.28	21.27	21.22	23	1
20	QPSK	50	50	21.26	21.19	21.08		
20	QPSK	100	0	21.29	21.30	21.10		
20	16QAM	1	0	21.22	21.48	21.65	23	1
20	16QAM	1	49	21.63	21.34	21.35		
20	16QAM	1	99	21.19	21.45	21.32		
20	16QAM	50	0	20.43	20.39	20.24	22	2
20	16QAM	50	24	20.35	20.28	20.22		
20	16QAM	50	50	20.31	20.18	20.10		
20	16QAM	100	0	20.38	20.23	20.29	22	2
20	64QAM	1	0	20.61	20.36	20.47		
20	64QAM	1	49	20.63	20.83	20.73		
20	64QAM	1	99	20.52	20.57	20.52	21	3
20	64QAM	50	0	19.58	19.55	19.46		
20	64QAM	50	24	19.55	19.50	19.57		
20	64QAM	50	50	19.57	19.35	19.35	21	3
20	64QAM	100	0	19.59	19.34	19.44		
Channel				132047	132322	132597	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1717.5	1745	1772.5		
15	QPSK	1	0	22.16	22.07	22.08		
15	QPSK	1	37	22.24	22.42	22.30	24	0
15	QPSK	1	74	22.00	22.00	22.34		
15	QPSK	36	0	21.25	21.27	21.27	23	1
15	QPSK	36	20	21.23	21.29	21.20		
15	QPSK	36	39	21.24	21.15	21.14		
15	QPSK	75	0	21.27	21.16	21.13	23	1
15	16QAM	1	0	21.25	21.52	21.69		
15	16QAM	1	37	21.71	21.53	21.65		
15	16QAM	1	74	21.28	21.44	21.24	22	2
15	16QAM	36	0	20.37	20.33	20.29		
15	16QAM	36	20	20.30	20.26	20.30		
15	16QAM	36	39	20.34	20.32	20.20	22	2
15	16QAM	75	0	20.32	20.30	20.32		
15	64QAM	1	0	20.38	20.41	20.51		
15	64QAM	1	37	20.65	20.55	20.74	22	2
15	64QAM	1	74	20.74	20.43	20.63		
15	64QAM	36	0	19.38	19.40	19.50		
15	64QAM	36	20	19.52	19.51	19.42	21	3
15	64QAM	36	39	19.49	19.41	19.42		
15	64QAM	75	0	19.54	19.37	19.47		
Channel				132022	132322	132622	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1715	1745	1775		
10	QPSK	1	0	22.11	22.19	22.17		
10	QPSK	1	25	22.25	22.28	22.34	24	0
10	QPSK	1	49	22.04	22.12	22.08		
10	QPSK	25	0	21.31	21.24	21.38	23	1
10	QPSK	25	12	21.28	21.22	21.19		



FCC SAR TEST REPORT

Report No. : FA9D3107

10	QPSK	25	25	21.31	21.16	21.26		
10	QPSK	50	0	21.31	21.28	21.27		
10	16QAM	1	0	21.63	21.45	21.27		
10	16QAM	1	25	21.34	21.68	21.44	23	1
10	16QAM	1	49	21.63	21.34	21.45		
10	16QAM	25	0	20.20	20.42	20.20		
10	16QAM	25	12	20.36	20.24	20.41	22	2
10	16QAM	25	25	20.29	20.28	20.28		
10	16QAM	50	0	20.36	20.30	20.27		
10	64QAM	1	0	20.69	20.45	20.54	22	2
10	64QAM	1	25	20.64	20.60	20.74		
10	64QAM	1	49	20.47	20.35	20.41		
10	64QAM	25	0	19.51	19.49	19.55	21	3
10	64QAM	25	12	19.55	19.56	19.45		
10	64QAM	25	25	19.58	19.54	19.56		
10	64QAM	50	0	19.49	19.52	19.44		
Channel				131997	132322	132647	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1745	1777.5		
5	QPSK	1	0	22.23	22.34	22.34	24	0
5	QPSK	1	12	22.22	22.39	22.41		
5	QPSK	1	24	22.31	22.11	22.34		
5	QPSK	12	0	21.31	21.27	21.29	23	1
5	QPSK	12	7	21.21	21.34	21.27		
5	QPSK	12	13	21.22	21.18	21.21		
5	QPSK	25	0	21.22	21.25	21.18	23	1
5	16QAM	1	0	21.48	21.30	21.24		
5	16QAM	1	12	21.65	21.56	21.49		
5	16QAM	1	24	21.49	21.32	21.26	22	2
5	16QAM	12	0	20.27	20.20	20.30		
5	16QAM	12	7	20.41	20.38	20.24		
5	16QAM	12	13	20.26	20.31	20.13	22	2
5	16QAM	25	0	20.32	20.30	20.37		
5	64QAM	1	0	20.82	20.62	20.73		
5	64QAM	1	12	20.84	20.99	20.71	22	2
5	64QAM	1	24	20.50	20.74	20.73		
5	64QAM	12	0	19.49	19.45	19.63		
5	64QAM	12	7	19.42	19.63	19.63	21	3
5	64QAM	12	13	19.69	19.51	19.67		
5	64QAM	25	0	19.66	19.55	19.61		
Channel				131987	132322	132657	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1745	1778.5		
3	QPSK	1	0	22.19	22.12	22.18	24	0
3	QPSK	1	8	22.17	22.16	22.25		
3	QPSK	1	14	22.19	22.06	22.04		
3	QPSK	8	0	21.25	21.14	21.28	23	1
3	QPSK	8	4	21.19	21.19	21.25		
3	QPSK	8	7	21.28	21.13	21.22		
3	QPSK	15	0	21.24	21.26	21.19	23	1
3	16QAM	1	0	21.20	21.26	21.54		
3	16QAM	1	8	21.26	21.28	21.45		
3	16QAM	1	14	21.35	21.31	21.64	22	2
3	16QAM	8	0	20.30	20.35	20.38		
3	16QAM	8	4	20.38	20.48	20.38		
3	16QAM	8	7	20.25	20.39	20.19	22	2
3	16QAM	15	0	20.37	20.16	20.38		
3	64QAM	1	0	20.32	20.35	20.52		

3	64QAM	1	8	20.64	20.47	20.54	21	3
3	64QAM	1	14	20.54	20.31	20.52		
3	64QAM	8	0	19.62	19.57	19.51		
3	64QAM	8	4	19.65	19.55	19.62		
3	64QAM	8	7	19.52	19.62	19.54		
3	64QAM	15	0	19.65	19.50	19.58		
Channel				131979	132322	132665	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1745	1779.3		
1.4	QPSK	1	0	22.16	22.16	22.13	24	0
1.4	QPSK	1	3	22.20	22.23	22.23		
1.4	QPSK	1	5	22.10	22.12	22.23		
1.4	QPSK	3	0	22.25	22.13	22.12		
1.4	QPSK	3	1	22.14	22.11	22.24		
1.4	QPSK	3	3	22.13	22.18	22.06		
1.4	QPSK	6	0	21.20	21.15	21.25	23	1
1.4	16QAM	1	0	21.38	21.23	21.54	23	1
1.4	16QAM	1	3	21.36	21.31	21.66		
1.4	16QAM	1	5	21.28	21.19	21.52		
1.4	16QAM	3	0	21.19	21.22	21.24		
1.4	16QAM	3	1	21.18	21.23	21.25		
1.4	16QAM	3	3	21.26	21.01	21.01		
1.4	16QAM	6	0	20.38	20.31	20.46	22	2
1.4	64QAM	1	0	20.48	20.84	20.40	22	2
1.4	64QAM	1	3	20.57	20.58	20.73		
1.4	64QAM	1	5	20.50	20.51	20.78		
1.4	64QAM	3	0	20.47	20.51	20.70		
1.4	64QAM	3	1	20.49	20.48	20.78		
1.4	64QAM	3	3	20.49	20.49	20.74		
1.4	64QAM	6	0	19.49	19.57	19.63	21	3

<Hotspot, Near-Body, Extremity Power Mode>
<LTE Band 2>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				18700	18900	19100		
Frequency (MHz)				1860	1880	1900		
20	QPSK	1	0	22.36	22.43	22.43	23.5	0
20	QPSK	1	49	22.75	22.58	22.58		
20	QPSK	1	99	22.45	22.43	22.34		
20	QPSK	50	0	21.47	21.46	21.54	23	0.5
20	QPSK	50	24	21.60	21.50	21.48		
20	QPSK	50	50	21.47	21.27	21.44		
20	QPSK	100	0	21.52	21.39	21.51	23	0.5
20	16QAM	1	0	21.44	21.48	21.66		
20	16QAM	1	49	21.86	21.74	21.71		
20	16QAM	1	99	21.45	21.40	21.42	22	1.5
20	16QAM	50	0	20.47	20.53	20.54		
20	16QAM	50	24	20.51	20.41	20.49		
20	16QAM	50	50	20.40	20.36	20.42	22	1.5
20	16QAM	100	0	20.43	20.44	20.48		
20	64QAM	1	0	20.55	20.50	20.77		
20	64QAM	1	49	20.68	20.62	20.73	22	1.5
20	64QAM	1	99	20.49	20.53	20.32		
20	64QAM	50	0	19.68	19.86	19.82		
20	64QAM	50	24	19.76	19.79	19.84	21	2.5
20	64QAM	50	50	19.68	19.62	19.66		
20	64QAM	100	0	19.76	19.71	19.73		
Channel				18675	18900	19125	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1857.5	1880	1902.5		
15	QPSK	1	0	22.47	22.45	22.36	23.5	0
15	QPSK	1	37	22.45	22.47	22.49		
15	QPSK	1	74	22.36	22.30	22.25		
15	QPSK	36	0	21.46	21.47	21.50	23	0.5
15	QPSK	36	20	21.44	21.44	21.53		
15	QPSK	36	39	21.46	21.45	21.55		
15	QPSK	75	0	22.51	22.47	22.35	23	0.5
15	16QAM	1	0	21.60	21.59	21.49		
15	16QAM	1	37	21.94	21.51	21.56		
15	16QAM	1	74	21.55	21.47	21.54	22	1.5
15	16QAM	36	0	20.50	20.46	20.50		
15	16QAM	36	20	20.59	20.47	20.38		
15	16QAM	36	39	20.51	20.45	20.41	22	1.5
15	16QAM	75	0	21.39	21.58	21.32		
15	64QAM	1	0	20.81	20.79	20.56		
15	64QAM	1	37	20.86	20.70	20.73	22	1.5
15	64QAM	1	74	20.96	20.80	20.57		
15	64QAM	36	0	19.73	19.78	19.78		
15	64QAM	36	20	19.71	19.79	19.74	21	2.5
15	64QAM	36	39	19.73	19.72	19.77		
15	64QAM	75	0	19.96	20.07	19.86		
Channel				18650	18900	19150	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1855	1880	1905		
10	QPSK	1	0	22.47	22.42	22.33	23.5	0
10	QPSK	1	25	22.55	22.55	22.55		
10	QPSK	1	49	22.38	22.31	22.29		

10	QPSK	25	0	21.57	21.51	21.48	23	0.5
10	QPSK	25	12	21.56	21.48	21.53		
10	QPSK	25	25	21.51	21.53	21.41		
10	QPSK	50	0	21.44	21.57	21.52		
10	16QAM	1	0	21.46	21.37	21.55	23	0.5
10	16QAM	1	25	21.56	21.45	21.56		
10	16QAM	1	49	21.42	21.27	21.54		
10	16QAM	25	0	20.51	20.50	20.47	22	1.5
10	16QAM	25	12	20.40	20.35	20.42		
10	16QAM	25	25	20.54	20.42	20.45		
10	16QAM	50	0	20.37	20.52	20.49		
10	64QAM	1	0	20.84	20.84	20.72	22	1.5
10	64QAM	1	25	20.94	20.82	20.73		
10	64QAM	1	49	20.81	20.58	20.78		
10	64QAM	25	0	19.69	19.82	19.88	21	2.5
10	64QAM	25	12	19.70	19.70	19.83		
10	64QAM	25	25	19.61	19.72	19.64		
10	64QAM	50	0	19.75	19.82	19.67		
Channel				18625	18900	19175	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1852.5	1880	1907.5		
5	QPSK	1	0	22.33	22.28	22.25	23.5	0
5	QPSK	1	12	22.74	22.70	22.46		
5	QPSK	1	24	22.35	22.33	22.27		
5	QPSK	12	0	21.45	21.43	21.39	23	0.5
5	QPSK	12	7	21.54	21.46	21.55		
5	QPSK	12	13	21.48	21.58	21.40		
5	QPSK	25	0	21.46	21.53	21.36		
5	16QAM	1	0	21.56	21.56	21.62	23	0.5
5	16QAM	1	12	21.76	21.95	21.76		
5	16QAM	1	24	21.58	21.52	21.45		
5	16QAM	12	0	20.31	20.44	20.50	22	1.5
5	16QAM	12	7	20.39	20.54	20.57		
5	16QAM	12	13	20.37	20.50	20.49		
5	16QAM	25	0	20.54	20.49	20.44		
5	64QAM	1	0	20.74	20.74	20.71	22	1.5
5	64QAM	1	12	20.93	21.13	20.95		
5	64QAM	1	24	20.73	20.71	20.78		
5	64QAM	12	0	19.76	19.61	19.78		
5	64QAM	12	7	19.68	19.80	19.84	21	2.5
5	64QAM	12	13	19.83	19.72	19.80		
5	64QAM	25	0	19.64	19.73	19.76		
Channel				18615	18900	19185	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1851.5	1880	1908.5		
3	QPSK	1	0	22.44	22.53	22.41	23.5	0
3	QPSK	1	8	22.46	22.44	22.44		
3	QPSK	1	14	22.56	22.44	22.50		
3	QPSK	8	0	21.51	21.49	21.38	23	0.5
3	QPSK	8	4	21.49	21.51	21.45		
3	QPSK	8	7	21.53	21.60	21.40		
3	QPSK	15	0	21.52	21.47	21.51		
3	16QAM	1	0	21.51	21.57	21.53	23	0.5
3	16QAM	1	8	21.82	21.48	21.51		
3	16QAM	1	14	21.83	21.84	21.93		
3	16QAM	8	0	20.49	20.54	20.51	22	1.5
3	16QAM	8	4	20.57	20.59	20.56		
3	16QAM	8	7	20.64	20.56	20.60		

3	16QAM	15	0	20.35	20.50	20.48		
3	64QAM	1	0	20.62	20.84	20.95	22	1.5
3	64QAM	1	8	21.05	20.94	20.84		
3	64QAM	1	14	20.83	20.88	20.82		
3	64QAM	8	0	19.92	19.80	19.83	21	2.5
3	64QAM	8	4	19.90	19.83	19.83		
3	64QAM	8	7	19.75	19.66	19.76		
3	64QAM	15	0	19.70	19.67	19.79		
Channel				18607	18900	19193	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1850.7	1880	1909.3		
1.4	QPSK	1	0	22.47	22.43	22.35	23.5	0
1.4	QPSK	1	3	22.71	22.69	22.60		
1.4	QPSK	1	5	22.48	22.49	22.31		
1.4	QPSK	3	0	22.67	22.45	22.54		
1.4	QPSK	3	1	22.68	22.60	22.53		
1.4	QPSK	3	3	22.62	22.54	22.48		
1.4	QPSK	6	0	21.68	21.64	21.48	23	0.5
1.4	16QAM	1	0	21.58	21.89	21.53	23	0.5
1.4	16QAM	1	3	21.64	21.68	21.62		
1.4	16QAM	1	5	21.49	21.87	21.61		
1.4	16QAM	3	0	21.55	21.44	21.54		
1.4	16QAM	3	1	21.67	21.40	21.70		
1.4	16QAM	3	3	21.44	21.64	21.52		
1.4	16QAM	6	0	20.64	20.59	20.62	22	1.5
1.4	64QAM	1	0	20.93	20.69	20.78	22	1.5
1.4	64QAM	1	3	21.05	20.98	20.70		
1.4	64QAM	1	5	20.88	20.94	20.69		
1.4	64QAM	3	0	20.78	20.86	20.69		
1.4	64QAM	3	1	20.79	20.75	20.80		
1.4	64QAM	3	3	20.83	20.85	20.82		
1.4	64QAM	6	0	19.68	19.89	19.74	21	2.5



<LTE Band 4>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20050	20175	20300		
Frequency (MHz)				1720	1732.5	1745		
20	QPSK	1	0	19.22	19.23	19.22		
20	QPSK	1	49	19.40	19.44	19.41	21	0
20	QPSK	1	99	19.03	19.08	19.04		
20	QPSK	50	0	18.37	18.34	18.43		
20	QPSK	50	24	18.39	18.37	18.41	20	1
20	QPSK	50	50	18.30	18.25	18.24		
20	QPSK	100	0	18.36	18.32	18.34		
20	16QAM	1	0	18.62	18.64	18.61	20	1
20	16QAM	1	49	18.86	18.85	18.81		
20	16QAM	1	99	18.47	18.46	18.41		
20	16QAM	50	0	17.46	17.42	17.46	19	2
20	16QAM	50	24	17.46	17.46	17.45		
20	16QAM	50	50	17.39	17.32	17.33		
20	16QAM	100	0	17.44	17.39	17.41	19	2
20	64QAM	1	0	17.71	17.69	17.67		
20	64QAM	1	49	17.91	17.93	17.87		
20	64QAM	1	99	17.51	17.52	17.48	18	3
20	64QAM	50	0	16.69	16.67	16.68		
20	64QAM	50	24	16.71	16.67	16.66		
20	64QAM	50	50	16.60	16.53	16.54	18	3
20	64QAM	100	0	16.69	16.63	16.65		
Channel				20025	20175	20325	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1717.5	1732.5	1747.5		
15	QPSK	1	0	19.35	19.32	19.32		
15	QPSK	1	37	19.57	19.53	19.53	21	0
15	QPSK	1	74	19.19	19.20	19.17		
15	QPSK	36	0	18.44	18.40	18.43	20	1
15	QPSK	36	20	18.43	18.40	18.38		
15	QPSK	36	39	18.38	18.31	18.36		
15	QPSK	75	0	18.41	18.37	18.38	20	1
15	16QAM	1	0	18.74	18.69	18.67		
15	16QAM	1	37	18.86	18.90	18.88		
15	16QAM	1	74	18.60	18.54	18.53	19	2
15	16QAM	36	0	17.48	17.45	17.43		
15	16QAM	36	20	17.45	17.43	17.42		
15	16QAM	36	39	17.42	17.34	17.35	19	2
15	16QAM	75	0	17.48	17.42	17.42		
15	64QAM	1	0	17.83	17.76	17.76	19	2
15	64QAM	1	37	17.97	17.97	17.99		
15	64QAM	1	74	17.65	17.61	17.59		
15	64QAM	36	0	16.71	16.66	16.67	18	3
15	64QAM	36	20	16.68	16.68	16.65		
15	64QAM	36	39	16.64	16.60	16.60		
15	64QAM	75	0	16.71	16.66	16.66	Tune-up limit (dBm)	MPR (dB)
Channel				20000	20175	20350		
Frequency (MHz)				1715	1732.5	1750		
10	QPSK	1	0	19.46	19.37	19.37	21	0
10	QPSK	1	25	19.48	19.51	19.44		
10	QPSK	1	49	19.29	19.34	19.25		
10	QPSK	25	0	18.51	18.43	18.47	20	1
10	QPSK	25	12	18.47	18.41	18.42		

10	QPSK	25	25	18.41	18.40	18.36		
10	QPSK	50	0	18.50	18.41	18.41		
10	16QAM	1	0	18.81	18.76	18.71		
10	16QAM	1	25	18.81	18.84	18.80	20	1
10	16QAM	1	49	18.68	18.69	18.62		
10	16QAM	25	0	17.53	17.49	17.50		
10	16QAM	25	12	17.52	17.50	17.46	19	2
10	16QAM	25	25	17.47	17.47	17.41		
10	16QAM	50	0	17.54	17.49	17.48		
10	64QAM	1	0	17.91	17.86	17.81	19	2
10	64QAM	1	25	17.97	17.94	17.90		
10	64QAM	1	49	17.78	17.79	17.70		
10	64QAM	25	0	16.76	16.73	16.74	18	3
10	64QAM	25	12	16.77	16.71	16.71		
10	64QAM	25	25	16.72	16.71	16.65		
10	64QAM	50	0	16.75	16.70	16.68		
Channel				19975	20175	20375	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1732.5	1752.5		
5	QPSK	1	0	19.31	19.27	19.24	21	0
5	QPSK	1	12	19.58	19.55	19.51		
5	QPSK	1	24	19.24	19.25	19.17		
5	QPSK	12	0	18.42	18.39	18.38	20	1
5	QPSK	12	7	18.48	18.45	18.39		
5	QPSK	12	13	18.42	18.38	18.34		
5	QPSK	25	0	18.43	18.39	18.35		
5	16QAM	1	0	18.68	18.64	18.59	20	1
5	16QAM	1	12	18.92	18.94	18.87		
5	16QAM	1	24	18.62	18.61	18.54		
5	16QAM	12	0	17.44	17.45	17.43	19	2
5	16QAM	12	7	17.51	17.51	17.45		
5	16QAM	12	13	17.46	17.44	17.39		
5	16QAM	25	0	17.48	17.47	17.39		
5	64QAM	1	0	17.77	17.76	17.68	19	2
5	64QAM	1	12	18.08	18.02	17.99		
5	64QAM	1	24	17.76	17.71	17.62		
5	64QAM	12	0	16.66	16.67	16.62	18	3
5	64QAM	12	7	16.73	16.71	16.66		
5	64QAM	12	13	16.70	16.65	16.59		
5	64QAM	25	0	16.70	16.67	16.63		
Channel				19965	20175	20385	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1732.5	1753.5		
3	QPSK	1	0	19.42	19.36	19.33	21	0
3	QPSK	1	8	19.42	19.40	19.32		
3	QPSK	1	14	19.38	19.37	19.29		
3	QPSK	8	0	18.47	18.40	18.34	20	1
3	QPSK	8	4	18.49	18.42	18.36		
3	QPSK	8	7	18.44	18.37	18.33		
3	QPSK	15	0	18.43	18.36	18.30		
3	16QAM	1	0	18.81	18.80	18.72	20	1
3	16QAM	1	8	18.79	18.77	18.70		
3	16QAM	1	14	18.75	18.77	18.65		
3	16QAM	8	0	17.57	17.53	17.45	19	2
3	16QAM	8	4	17.59	17.53	17.46		
3	16QAM	8	7	17.53	17.53	17.44		
3	16QAM	15	0	17.46	17.47	17.38		
3	64QAM	1	0	17.85	17.83	17.77	19	2

3	64QAM	1	8	17.87	17.87	17.77	18	3
3	64QAM	1	14	17.82	17.83	17.75		
3	64QAM	8	0	16.76	16.72	16.63		
3	64QAM	8	4	16.77	16.75	16.67		
3	64QAM	8	7	16.72	16.71	16.63		
3	64QAM	15	0	16.64	16.66	16.59		
Channel				19957	20175	20393	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1732.5	1754.3		
1.4	QPSK	1	0	19.36	19.30	19.26	21	0
1.4	QPSK	1	3	19.48	19.48	19.37		
1.4	QPSK	1	5	19.33	19.33	19.23		
1.4	QPSK	3	0	19.46	19.39	19.36		
1.4	QPSK	3	1	19.48	19.42	19.40		
1.4	QPSK	3	3	19.45	19.43	19.35		
1.4	QPSK	6	0	18.43	18.37	18.34	20	1
1.4	16QAM	1	0	18.75	18.71	18.62	20	1
1.4	16QAM	1	3	18.85	18.86	18.74		
1.4	16QAM	1	5	18.74	18.75	18.66		
1.4	16QAM	3	0	18.50	18.44	18.36		
1.4	16QAM	3	1	18.54	18.47	18.43		
1.4	16QAM	3	3	18.49	18.47	18.39		
1.4	16QAM	6	0	17.54	17.53	17.45	19	2
1.4	64QAM	1	0	17.87	17.80	17.74	19	2
1.4	64QAM	1	3	17.97	17.91	17.83		
1.4	64QAM	1	5	17.83	17.84	17.72		
1.4	64QAM	3	0	17.76	17.75	17.68		
1.4	64QAM	3	1	17.82	17.77	17.74		
1.4	64QAM	3	3	17.77	17.73	17.67		
1.4	64QAM	6	0	16.69	16.68	16.63	18	3

<LTE Band 5>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20450	20525	20600	24	0
Frequency (MHz)				829	836.5	844		
10	QPSK	1	0	22.62	22.62	22.60		
10	QPSK	1	25	22.77	22.94	22.71	23	1
10	QPSK	1	49	22.57	22.59	22.60		
10	QPSK	25	0	21.82	21.78	21.76		
10	QPSK	25	12	21.83	21.83	21.80	23	1
10	QPSK	25	25	21.71	21.85	21.67		
10	QPSK	50	0	21.70	21.80	21.74		
10	16QAM	1	0	21.98	22.00	21.94	23	1
10	16QAM	1	25	22.11	22.09	21.97		
10	16QAM	1	49	22.01	21.96	21.82		
10	16QAM	25	0	20.81	20.82	20.70	22	2
10	16QAM	25	12	20.79	20.80	20.78		
10	16QAM	25	25	20.74	20.83	20.57		
10	16QAM	50	0	20.79	20.79	20.68	22	2
10	64QAM	1	0	20.97	21.01	20.91		
10	64QAM	1	25	20.98	20.98	20.85		
10	64QAM	1	49	21.05	21.07	20.92	21	3
10	64QAM	25	0	19.87	19.91	19.81		
10	64QAM	25	12	19.90	19.96	19.83		
10	64QAM	25	25	19.90	19.91	19.80	21	3
10	64QAM	50	0	19.85	19.87	19.78		
Channel				20425	20525	20625	24	0
Frequency (MHz)				826.5	836.5	846.5		
5	QPSK	1	0	22.53	22.54	22.47		
5	QPSK	1	12	22.93	22.76	22.70	23	1
5	QPSK	1	24	22.50	22.49	22.47		
5	QPSK	12	0	21.72	21.70	21.70		
5	QPSK	12	7	21.74	21.77	21.71	23	1
5	QPSK	12	13	21.78	21.79	21.65		
5	QPSK	25	0	21.70	21.72	21.65		
5	16QAM	1	0	21.78	21.90	21.75	23	1
5	16QAM	1	12	22.19	22.19	21.97		
5	16QAM	1	24	21.86	21.92	21.74		
5	16QAM	12	0	20.67	20.71	20.65	22	2
5	16QAM	12	7	20.78	20.77	20.66		
5	16QAM	12	13	20.74	20.75	20.62		
5	16QAM	25	0	20.70	20.75	20.61	22	2
5	64QAM	1	0	21.01	21.03	21.00		
5	64QAM	1	12	21.24	21.32	21.15		
5	64QAM	1	24	21.01	21.04	20.94	21	3
5	64QAM	12	0	19.96	19.96	19.94		
5	64QAM	12	7	20.02	20.06	19.92		
5	64QAM	12	13	19.97	20.02	19.86	21	3
5	64QAM	25	0	20.00	20.00	19.86		
Channel				20415	20525	20635	24	0
Frequency (MHz)				825.5	836.5	847.5		
3	QPSK	1	0	22.62	22.64	22.57		
3	QPSK	1	8	22.69	22.60	22.56	23	1
3	QPSK	1	14	22.64	22.59	22.61		
3	QPSK	8	0	21.73	21.73	21.63		
3	QPSK	8	4	21.76	21.79	21.71	23	1



FCC SAR TEST REPORT

Report No. : FA9D3107

3	QPSK	8	7	21.71	21.70	21.63		
3	QPSK	15	0	21.66	21.74	21.68		
3	16QAM	1	0	22.00	22.06	21.75		
3	16QAM	1	8	21.95	21.97	21.82	23	1
3	16QAM	1	14	21.95	21.98	21.84		
3	16QAM	8	0	20.76	20.79	20.67		
3	16QAM	8	4	20.80	20.81	20.73	22	2
3	16QAM	8	7	20.82	20.78	20.66		
3	16QAM	15	0	20.68	20.71	20.65		
3	64QAM	1	0	21.09	21.13	21.03	22	2
3	64QAM	1	8	21.10	21.10	20.97		
3	64QAM	1	14	21.17	21.19	21.04		
3	64QAM	8	0	19.99	20.03	19.93	21	3
3	64QAM	8	4	20.02	20.08	19.95		
3	64QAM	8	7	20.02	20.03	19.92		
3	64QAM	15	0	19.97	19.99	19.90		
Channel				20407	20525	20643	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				824.7	836.5	848.3		
1.4	QPSK	1	0	22.60	22.60	22.53	24	0
1.4	QPSK	1	3	22.78	22.75	22.67		
1.4	QPSK	1	5	22.61	22.57	22.54		
1.4	QPSK	3	0	22.73	22.70	22.62		
1.4	QPSK	3	1	22.76	22.77	22.77		
1.4	QPSK	3	3	22.73	22.70	22.64		
1.4	QPSK	6	0	21.68	21.79	21.78	23	1
1.4	16QAM	1	0	21.91	21.94	21.81	23	1
1.4	16QAM	1	3	22.05	22.10	21.92		
1.4	16QAM	1	5	21.87	21.95	21.78		
1.4	16QAM	3	0	21.70	21.78	21.62		
1.4	16QAM	3	1	21.81	21.87	21.70		
1.4	16QAM	3	3	21.73	21.77	21.65		
1.4	16QAM	6	0	20.82	20.85	20.73	22	2
1.4	64QAM	1	0	21.03	21.18	20.97	22	2
1.4	64QAM	1	3	21.26	21.18	21.12		
1.4	64QAM	1	5	21.08	21.16	20.99		
1.4	64QAM	3	0	21.05	21.14	20.93		
1.4	64QAM	3	1	21.02	21.11	21.05		
1.4	64QAM	3	3	21.08	21.05	21.01		
1.4	64QAM	6	0	19.97	20.07	19.95	21	3

<LTE Band 12>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23060	23095	23130	24	0
Frequency (MHz)				704	707.5	711		
10	QPSK	1	0	22.57	22.52	22.55		
10	QPSK	1	25	22.71	22.53	22.56	23	1
10	QPSK	1	49	22.55	22.56	22.48		
10	QPSK	25	0	21.57	21.67	21.65		
10	QPSK	25	12	21.62	21.68	21.65	23	1
10	QPSK	25	25	21.62	21.59	21.59		
10	QPSK	50	0	21.67	21.66	21.65		
10	16QAM	1	0	21.77	22.00	22.09	23	1
10	16QAM	1	25	22.05	22.01	22.06		
10	16QAM	1	49	22.07	22.00	22.01		
10	16QAM	25	0	20.72	20.62	20.77	22	2
10	16QAM	25	12	20.86	20.70	20.69		
10	16QAM	25	25	20.82	20.65	20.69		
10	16QAM	50	0	20.72	20.71	20.71	22	2
10	64QAM	1	0	20.79	20.83	21.16		
10	64QAM	1	25	21.19	20.78	21.17		
10	64QAM	1	49	20.91	20.86	21.24	21	3
10	64QAM	25	0	19.79	19.77	19.83		
10	64QAM	25	12	19.90	19.83	19.91		
10	64QAM	25	25	19.84	19.74	19.69	21	3
10	64QAM	50	0	19.88	19.84	19.92		
Channel				23035	23095	23155	24	0
Frequency (MHz)				701.5	707.5	713.5		
5	QPSK	1	0	22.39	22.33	22.41		
5	QPSK	1	12	22.67	22.51	22.67	23	1
5	QPSK	1	24	22.33	22.40	22.36		
5	QPSK	12	0	21.48	21.60	21.55		
5	QPSK	12	7	21.66	21.64	21.62	23	1
5	QPSK	12	13	21.65	21.57	21.65		
5	QPSK	25	0	21.50	21.63	21.49		
5	16QAM	1	0	21.62	21.71	21.72	23	1
5	16QAM	1	12	22.00	21.95	21.68		
5	16QAM	1	24	21.84	21.69	21.64		
5	16QAM	12	0	20.47	20.54	20.51	22	2
5	16QAM	12	7	20.56	20.61	20.56		
5	16QAM	12	13	20.58	20.46	20.56		
5	16QAM	25	0	20.60	20.57	20.60	22	2
5	64QAM	1	0	20.98	20.60	20.66		
5	64QAM	1	12	20.89	20.98	20.85		
5	64QAM	1	24	20.68	20.77	20.67	21	3
5	64QAM	12	0	19.52	19.72	19.65		
5	64QAM	12	7	19.62	19.81	19.87		
5	64QAM	12	13	19.79	19.76	19.81	21	3
5	64QAM	25	0	19.75	19.82	19.74		
Channel				23025	23095	23165	24	0
Frequency (MHz)				700.5	707.5	714.5		
3	QPSK	1	0	22.50	22.50	22.48		
3	QPSK	1	8	22.49	22.46	22.49	24	0
3	QPSK	1	14	22.48	22.49	22.41		
3	QPSK	8	0	21.50	21.60	21.58	23	1
3	QPSK	8	4	21.55	21.61	21.58		

3	QPSK	8	7	21.55	21.52	21.52		
3	QPSK	15	0	21.60	21.59	21.58		
3	16QAM	1	0	21.70	21.93	22.02		
3	16QAM	1	8	21.98	21.94	21.99	23	1
3	16QAM	1	14	22.00	21.93	21.94		
3	16QAM	8	0	20.65	20.55	20.70		
3	16QAM	8	4	20.79	20.63	20.62	22	2
3	16QAM	8	7	20.75	20.58	20.62		
3	16QAM	15	0	20.65	20.64	20.64		
3	64QAM	1	0	20.72	20.76	21.09	22	2
3	64QAM	1	8	21.12	20.71	21.10		
3	64QAM	1	14	20.84	20.79	21.17		
3	64QAM	8	0	19.72	19.70	19.76	21	3
3	64QAM	8	4	19.83	19.76	19.84		
3	64QAM	8	7	19.77	19.67	19.62		
3	64QAM	15	0	19.81	19.77	19.85		
Channel				23017	23095	23173	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				699.7	707.5	715.3		
1.4	QPSK	1	0	22.41	22.46	22.43	24	0
1.4	QPSK	1	3	22.67	22.56	22.48		
1.4	QPSK	1	5	22.45	22.50	22.50		
1.4	QPSK	3	0	22.51	22.43	22.49		
1.4	QPSK	3	1	22.62	22.48	22.50		
1.4	QPSK	3	3	22.59	22.59	22.54		
1.4	QPSK	6	0	21.57	21.58	21.69	23	1
1.4	16QAM	1	0	21.67	21.34	21.48	23	1
1.4	16QAM	1	3	21.59	21.70	21.70		
1.4	16QAM	1	5	21.69	21.54	21.57		
1.4	16QAM	3	0	21.54	21.59	21.51		
1.4	16QAM	3	1	21.57	21.41	21.48		
1.4	16QAM	3	3	21.66	21.55	21.36		
1.4	16QAM	6	0	20.63	20.57	20.58	22	2
1.4	64QAM	1	0	20.81	20.75	20.67	22	2
1.4	64QAM	1	3	21.03	20.83	20.86		
1.4	64QAM	1	5	20.84	20.74	20.76		
1.4	64QAM	3	0	20.73	20.64	20.71		
1.4	64QAM	3	1	20.58	20.61	20.84		
1.4	64QAM	3	3	20.62	20.71	20.73		
1.4	64QAM	6	0	19.81	19.67	19.72	21	3

<LTE Band 14>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23330				
Frequency (MHz)				793				
10	QPSK	1	0		22.44		24	0
10	QPSK	1	25		22.66			
10	QPSK	1	49		22.41			
10	QPSK	25	0		21.54		23	1
10	QPSK	25	12		21.56			
10	QPSK	25	25		21.45			
10	QPSK	50	0		21.53		23	1
10	16QAM	1	0		21.73			
10	16QAM	1	25		21.74			
10	16QAM	1	49		21.60		22	2
10	16QAM	25	0		20.48			
10	16QAM	25	12		20.50			
10	16QAM	25	25		20.41		22	2
10	16QAM	50	0		20.46			
10	64QAM	1	0		20.59			
10	64QAM	1	25		20.63		22	2
10	64QAM	1	49		20.59			
10	64QAM	25	0		19.51		21	3
10	64QAM	25	12		19.50			
10	64QAM	25	25		19.45			
10	64QAM	50	0		19.47			
Channel				23305	23330	23355	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				790.5	793	795.5		
5	QPSK	1	0	22.32	22.34	22.36	24	0
5	QPSK	1	12	22.63	22.65	22.63		
5	QPSK	1	24	22.33	22.35	22.37		
5	QPSK	12	0	21.43	21.54	21.56	23	1
5	QPSK	12	7	21.50	21.54	21.55		
5	QPSK	12	13	21.41	21.46	21.50		
5	QPSK	25	0	21.42	21.50	21.51	23	1
5	16QAM	1	0	21.60	21.48	21.54		
5	16QAM	1	12	21.74	21.71	21.80		
5	16QAM	1	24	21.48	21.54	21.62	22	2
5	16QAM	12	0	20.40	20.48	20.49		
5	16QAM	12	7	20.48	20.46	20.49		
5	16QAM	12	13	20.33	20.39	20.44	22	2
5	16QAM	25	0	20.42	20.44	20.48		
5	64QAM	1	0	20.50	20.42	20.47		
5	64QAM	1	12	20.70	20.75	20.78	22	2
5	64QAM	1	24	20.41	20.46	20.55		
5	64QAM	12	0	19.43	19.51	19.53		
5	64QAM	12	7	19.49	19.48	19.53	21	3
5	64QAM	12	13	19.39	19.42	19.50		
5	64QAM	25	0	19.41	19.44	19.52		

<LTE Band 30>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				27710				
Frequency (MHz)				2310				
10	QPSK	1	0		17.26		19	0
10	QPSK	1	25		17.40			
10	QPSK	1	49		17.22			
10	QPSK	25	0		16.42		18	1
10	QPSK	25	12		16.42			
10	QPSK	25	25		16.43			
10	QPSK	50	0		16.43			
10	16QAM	1	0		16.62		18	1
10	16QAM	1	25		16.74			
10	16QAM	1	49		16.57			
10	16QAM	25	0		15.36		17	2
10	16QAM	25	12		15.40			
10	16QAM	25	25		15.37			
10	16QAM	50	0		15.39			
10	64QAM	1	0		15.69		17	2
10	64QAM	1	25		15.83			
10	64QAM	1	49		15.67			
10	64QAM	25	0		14.63			
10	64QAM	25	12		14.62		16	3
10	64QAM	25	25		14.61			
10	64QAM	50	0		14.62			
Channel				27685	27710	27735	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2307.5	2310	2312.5		
5	QPSK	1	0	17.22	17.22	17.22	19	0
5	QPSK	1	12	17.22	17.23	17.21		
5	QPSK	1	24	17.18	17.22	17.17		
5	QPSK	12	0	16.37	16.36	16.34	18	1
5	QPSK	12	7	16.35	16.39	16.39		
5	QPSK	12	13	16.33	16.33	16.31		
5	QPSK	25	0	16.35	16.36	16.33	18	1
5	16QAM	1	0	16.57	16.54	16.58		
5	16QAM	1	12	16.79	16.80	16.77		
5	16QAM	1	24	16.53	16.55	16.53	17	2
5	16QAM	12	0	15.29	15.31	15.29		
5	16QAM	12	7	15.35	15.37	15.35		
5	16QAM	12	13	15.29	15.34	15.26		
5	16QAM	25	0	15.32	15.33	15.29	17	2
5	64QAM	1	0	15.69	15.69	15.71		
5	64QAM	1	12	15.89	15.95	15.89		
5	64QAM	1	24	15.67	15.67	15.64		
5	64QAM	12	0	14.52	14.52	14.51	16	3
5	64QAM	12	7	14.55	14.58	14.54		
5	64QAM	12	13	14.52	14.51	14.46		
5	64QAM	25	0	14.56	14.55	14.53		



<LTE Band 66>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				132072	132322	132572	21	0
Frequency (MHz)				1720	1745	1770		
20	QPSK	1	0	19.40	19.59	19.45		
20	QPSK	1	49	19.51	19.41	19.43	20	1
20	QPSK	1	99	19.23	19.23	19.32		
20	QPSK	50	0	18.38	18.46	18.38		
20	QPSK	50	24	18.45	18.38	18.37	20	1
20	QPSK	50	50	18.39	18.26	18.20		
20	QPSK	100	0	18.31	18.33	18.30		
20	16QAM	1	0	18.61	18.56	18.57	20	1
20	16QAM	1	49	18.78	18.80	18.83		
20	16QAM	1	99	18.90	18.55	18.42		
20	16QAM	50	0	17.46	17.45	17.46	19	2
20	16QAM	50	24	17.54	17.48	17.45		
20	16QAM	50	50	17.46	17.33	17.27		
20	16QAM	100	0	17.47	17.37	17.35	19	2
20	64QAM	1	0	17.75	17.70	17.71		
20	64QAM	1	49	18.00	18.00	17.98		
20	64QAM	1	99	17.63	17.56	17.56	18	3
20	64QAM	50	0	16.77	16.76	16.77		
20	64QAM	50	24	16.84	16.75	16.77		
20	64QAM	50	50	16.79	16.64	16.58	18	3
20	64QAM	100	0	16.81	16.72	16.68		
Channel				132047	132322	132597	21	0
Frequency (MHz)				1717.5	1745	1772.5		
15	QPSK	1	0	19.36	19.28	19.27		
15	QPSK	1	37	19.55	19.47	19.47	20	1
15	QPSK	1	74	19.24	19.18	19.19		
15	QPSK	36	0	18.46	18.41	18.40		
15	QPSK	36	20	18.44	18.40	18.36	20	1
15	QPSK	36	39	18.42	18.35	18.32		
15	QPSK	75	0	18.43	18.37	18.36		
15	16QAM	1	0	18.73	18.63	18.64	20	1
15	16QAM	1	37	18.95	18.87	18.86		
15	16QAM	1	74	18.60	18.54	18.55		
15	16QAM	36	0	17.50	17.45	17.44	19	2
15	16QAM	36	20	17.49	17.43	17.42		
15	16QAM	36	39	17.47	17.36	17.34		
15	16QAM	75	0	17.50	17.42	17.41	19	2
15	64QAM	1	0	17.92	17.80	17.81		
15	64QAM	1	37	18.14	18.04	18.00		
15	64QAM	1	74	17.77	17.70	17.72	18	3
15	64QAM	36	0	16.80	16.74	16.78		
15	64QAM	36	20	16.82	16.75	16.73		
15	64QAM	36	39	16.80	16.68	16.69	18	3
15	64QAM	75	0	16.84	16.73	16.72		
Channel				132022	132322	132622	21	0
Frequency (MHz)				1715	1745	1775		
10	QPSK	1	0	19.41	19.32	19.29		
10	QPSK	1	25	19.50	19.45	19.43	21	0
10	QPSK	1	49	19.33	19.27	19.23		
10	QPSK	25	0	18.47	18.41	18.39	20	1
10	QPSK	25	12	18.47	18.41	18.36		

10	QPSK	25	25	18.44	18.38	18.31		
10	QPSK	50	0	18.47	18.39	18.33		
10	16QAM	1	0	18.80	18.64	18.69		
10	16QAM	1	25	18.83	18.73	18.77	20	1
10	16QAM	1	49	18.74	18.62	18.62		
10	16QAM	25	0	17.49	17.46	17.45		
10	16QAM	25	12	17.53	17.46	17.44	19	2
10	16QAM	25	25	17.52	17.40	17.40		
10	16QAM	50	0	17.53	17.44	17.40		
10	64QAM	1	0	17.97	17.84	17.83	19	2
10	64QAM	1	25	18.00	17.95	17.94		
10	64QAM	1	49	17.88	17.75	17.78		
10	64QAM	25	0	16.82	16.78	16.79	18	3
10	64QAM	25	12	16.85	16.77	16.78		
10	64QAM	25	25	16.85	16.71	16.71		
10	64QAM	50	0	16.84	16.74	16.70		
Channel				131997	132322	132647	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1745	1777.5		
5	QPSK	1	0	19.34	19.26	19.23	21	0
5	QPSK	1	12	19.50	19.49	19.51		
5	QPSK	1	24	19.24	19.24	19.23		
5	QPSK	12	0	18.41	18.38	18.40	20	1
5	QPSK	12	7	18.45	18.40	18.39		
5	QPSK	12	13	18.37	18.36	18.36		
5	QPSK	25	0	18.42	18.36	18.35		
5	16QAM	1	0	18.72	18.60	18.60	20	1
5	16QAM	1	12	18.88	18.83	18.88		
5	16QAM	1	24	18.64	18.59	18.64		
5	16QAM	12	0	17.43	17.41	17.47	19	2
5	16QAM	12	7	17.47	17.46	17.46		
5	16QAM	12	13	17.45	17.39	17.40		
5	16QAM	25	0	17.45	17.43	17.46		
5	64QAM	1	0	17.90	17.81	17.82	19	2
5	64QAM	1	12	18.09	18.05	18.10		
5	64QAM	1	24	17.80	17.78	17.82		
5	64QAM	12	0	16.73	16.73	16.74	18	3
5	64QAM	12	7	16.79	16.77	16.77		
5	64QAM	12	13	16.74	16.69	16.70		
5	64QAM	25	0	16.76	16.75	16.76		
Channel				131987	132322	132657	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1745	1778.5		
3	QPSK	1	0	19.45	19.35	19.37	21	0
3	QPSK	1	8	19.37	19.31	19.33		
3	QPSK	1	14	19.40	19.32	19.34		
3	QPSK	8	0	18.45	18.34	18.37	20	1
3	QPSK	8	4	18.45	18.35	18.38		
3	QPSK	8	7	18.40	18.33	18.36		
3	QPSK	15	0	18.40	18.32	18.32		
3	16QAM	1	0	18.84	18.72	18.76	20	1
3	16QAM	1	8	18.76	18.70	18.72		
3	16QAM	1	14	18.77	18.70	18.74		
3	16QAM	8	0	17.55	17.46	17.50	19	2
3	16QAM	8	4	17.53	17.45	17.49		
3	16QAM	8	7	17.51	17.46	17.47		
3	16QAM	15	0	17.43	17.41	17.42		
3	64QAM	1	0	17.96	17.91	17.92	19	2

3	64QAM	1	8	17.94	17.86	17.90	18	3
3	64QAM	1	14	17.94	17.90	17.89		
3	64QAM	8	0	16.85	16.74	16.77		
3	64QAM	8	4	16.83	16.74	16.78		
3	64QAM	8	7	16.80	16.74	16.76		
3	64QAM	15	0	16.74	16.68	16.72		
Channel				131979	132322	132665	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1745	1779.3		
1.4	QPSK	1	0	19.34	19.33	19.28	21	0
1.4	QPSK	1	3	19.48	19.39	19.39		
1.4	QPSK	1	5	19.31	19.25	19.28		
1.4	QPSK	3	0	19.44	19.34	19.38		
1.4	QPSK	3	1	19.46	19.38	19.40		
1.4	QPSK	3	3	19.45	19.36	19.38		
1.4	QPSK	6	0	18.43	18.32	18.35	20	1
1.4	16QAM	1	0	18.72	18.65	18.68	20	1
1.4	16QAM	1	3	18.87	18.76	18.82		
1.4	16QAM	1	5	18.71	18.63	18.69		
1.4	16QAM	3	0	18.45	18.38	18.43		
1.4	16QAM	3	1	18.49	18.42	18.45		
1.4	16QAM	3	3	18.48	18.38	18.40		
1.4	16QAM	6	0	17.57	17.46	17.47	19	2
1.4	64QAM	1	0	17.96	17.82	17.81	19	2
1.4	64QAM	1	3	18.02	17.96	17.99		
1.4	64QAM	1	5	17.91	17.86	17.85		
1.4	64QAM	3	0	17.85	17.77	17.75		
1.4	64QAM	3	1	17.91	17.81	17.85		
1.4	64QAM	3	3	17.84	17.74	17.75		
1.4	64QAM	6	0	16.81	16.74	16.75	18	3

<LTE Carrier Aggregation combinations>
General Note:

1. This device supports Carrier Aggregation on downlink only for inter and intra band, Uplink CA is not supported. For the device supports combination bands and configurations are according to 3GPP.
2. In applying the existing power measurement procedure of KDB 941225 D05A for DL CA SAR test exclusion, only the subset with the largest number of combinations of the frequency band and CCs in each row need consideration, and that configurations require power measurement should be highlighted in the below table.

2CC Downlink Carrier Aggregation		
Number	Combination	Covered by Measurement Superset
1	2A-2A	
2	2A-4A	
3	2A-5A	
4	2A-12A	
5	2A-14A	
6	2A-66A	
7	2A-29A	
8	4A-4A	
9	4A-5A	
10	4A-12A	
11	4A-29A	
12	5A-30A	
13	5A-66A	
14	5B	
15	12A-30A	
16	12A-66A	
17	14A-30A	
18	14A-66A	
19	29A-30A	
20	29A-66A	
21	30A-66A	
22	66A-66A	

<Power verification when LTE Carrier Aggregation Active>
General Note:

- i. According to KDB941225 D05A v01r02, Uplink maximum output power measurement with downlink carrier aggregation active should be measured, using the highest output channel measured without downlink carrier aggregation, to confirm that uplink maximum output power with downlink carrier aggregation active remains within the specified tune-up tolerance limits and not more than ¼ dB higher than the maximum output measured without downlink carrier aggregation active.
- ii. Uplink maximum output power with downlink carrier aggregation active does not show more than ¼ dB higher than the maximum output power without downlink carrier aggregation active, therefore SAR evaluation with downlink carrier aggregation active can be excluded.
- iii. The device supports downlink two carrier aggregation. For power measurement were control and acknowledge data is sent on uplink channels that operate identical to specifications when downlink carrier aggregation is inactive.
- iv. Selected highest measured power when downlink carrier aggregation is inactive for conducted power comparison with downlink carrier aggregation is active, to confirm that when downlink carrier aggregation is active uplink maximum output power remains within the specified tune-up tolerance limits and not more than ¼ dB higher than the maximum output power measured when downlink carrier aggregation inactive.
- v. For non-contiguous intra-band CA, the SCC selected to provide maximum separation from the PCC and must remain fully within the downlink transmission band.
- vi. For Intra-band, contiguous CA, the downlink channels selected to perform the uplink power measurement must satisfy 3GPP channel spacing (5.4.1A of 3GPP TS 36.521 or equivalent) and channel bandwidth (5.4.2A) requirements.

$$\text{Nominal channel spacing} = \left\lceil \frac{BW_{\text{Channel}(1)} + BW_{\text{Channel}(2)} - 0.1|BW_{\text{Channel}(1)} - BW_{\text{Channel}(2)}|}{0.6} \right\rceil 0.3 \text{ [MHz]}$$

<Two Carrier power verification>
<Default Power Mode>

Configure		CA List	PCC							SCC				Power	
			LTE	BW	UL	UL	Mod.	UL#	UL	LTE	BW	DL	DL	With CA	Without CA
			Band	(MHz)	Freq. (MHz)	Channel		RB	Offset	Band	(MHz)	Freq. (MHz)	Channel	Tx. Power (dBm)	Tx. Power (dBm)
Inter-Band	CA_2A-4A	Band 2	20M	1860	18700	QPSK	1	49	Band 4	20M	2132.5	2175	22.31	22.75	
		Band 4	20M	1732.5	20175	QPSK	1	49	Band 2	20M	1960	900	22.21	22.58	
	CA_2A-5A	Band 2	20M	1860	18700	QPSK	1	49	Band 5	10M	881.5	2525	22.33	22.75	
		Band 5	10M	836.5	20525	QPSK	1	25	Band 2	20M	1960	900	22.82	22.94	
	CA_2A-12A	Band 2	20M	1860	18700	QPSK	1	49	Band 12	10M	737.5	5095	22.34	22.75	
		Band 12	10M	704	23060	QPSK	1	25	Band 2	20M	1960	900	22.34	22.71	
	CA_2A-14A	Band 2	20M	1860	18700	QPSK	1	49	Band 14	10M	763	5330	22.33	22.75	
		Band 14	10M	793	23330	QPSK	1	25	Band 2	20M	1960	900	22.76	22.66	
	CA_2A-66A	Band 2	20M	1860	18700	QPSK	1	49	Band 66	20M	2155	66886	22.32	22.75	
		Band 66	20M	1745	132322	QPSK	1	0	Band 2	20M	1960	900	22.06	22.45	
	CA_2A-29A	Band 2	20M	1860	18700	QPSK	1	49	Band 29	10M	722.5	9715	22.45	22.75	
	CA_4A-5A	Band 4	20M	1732.5	20175	QPSK	1	49	Band 5	10M	881.5	2525	22.25	22.58	
		Band 5	10M	836.5	20525	QPSK	1	25	Band 4	20M	2132.5	2175	22.81	22.94	
	CA_4A-12A	Band 4	20M	1732.5	20175	QPSK	1	49	Band 12	10M	737.5	5095	22.22	22.58	
		Band 12	10M	704	23060	QPSK	1	25	Band 4	20M	2132.5	2175	22.34	22.71	
	CA_4A-29A	Band 4	20M	1732.5	20175	QPSK	1	49	Band 29	10M	722.5	9715	22.25	22.58	
	CA_5A-30A	Band 5	10M	836.5	20525	QPSK	1	25	Band 30	10M	2355	9820	22.88	22.94	
		Band 30	10M	2310	27710	QPSK	1	25	Band 5	10M	881.5	2525	22.43	22.83	
	CA_5A-66A	Band 5	10M	836.5	20525	QPSK	1	25	Band 66	20M	2155	66886	22.83	22.94	
		Band 66	20M	1745	132322	QPSK	1	0	Band 5	10M	881.5	2525	22.07	22.45	
	CA_12A-30A	Band 12	10M	704	23060	QPSK	1	25	Band 30	10M	2355	9820	22.81	22.71	
		Band 30	10M	2310	27710	QPSK	1	25	Band 12	10M	737.5	5095	22.23	22.83	
	CA_12A-66A	Band 12	10M	704	23060	QPSK	1	25	Band 66	20M	2155	66886	22.45	22.71	
		Band 66	20M	1745	132322	QPSK	1	0	Band 12	10M	737.5	5095	22.06	22.45	
	CA_14A-30A	Band 14	10M	793	23330	QPSK	1	25	Band 30	10M	2355	9820	22.76	22.66	
		Band 30	10M	2310	27710	QPSK	1	25	Band 14	10M	763	5330	22.21	22.83	
	CA_14A-66A	Band 14	10M	793	23330	QPSK	1	25	Band 66	20M	2155	66886	22.56	22.66	
		Band 66	20M	1745	132322	QPSK	1	0	Band 14	10M	763	5330	22.08	22.45	
	CA_29A-30A	Band 30	10M	2310	27710	QPSK	1	25	Band 29	10M	722.5	9715	22.56	22.83	
	CA_29A-66A	Band 66	20M	1745	132322	QPSK	1	0	Band 29	10M	722.5	9715	22.07	22.45	
	CA_30A-66A	Band 30	10M	2310	27710	QPSK	1	25	Band 66	20M	2155	66886	22.54	22.83	
		Band 66	20M	1745	132322	QPSK	1	0	Band 30	10M	2355	9820	22.10	22.45	
Intra-Band	Contiguous	CA_5B	Band 5	10M	836.5	20525	QPSK	1	25	Band 5	5M	871.5	2425	22.67	22.94
	Non-Contiguous	CA_2A-2A	Band 2	20M	1860	18700	QPSK	1	49	Band 2	5M	1987.5	1175	22.34	22.75
		CA_4A-4A	Band 4	20M	1732.5	20175	QPSK	1	49	Band 4	5M	2152.5	2375	22.22	22.58
		CA_66A-66A	Band 66	20M	1745	132322	QPSK	1	0	Band 66	5M	2197.5	67311	22.08	22.45

<Hotspot, Near-Body, Extremity Power Mode>

Configure	CA List	PCC							SCC				Power	
		LTE	BW	UL	UL	Mod.	UL#	UL	LTE	BW	DL	DL	With CA	Without CA
		Band	(MHz)	Freq. (MHz)	Channel		RB	RB Offset	Band	(MHz)	Freq. (MHz)	Channel	Tx. Power (dBm)	Tx. Power (dBm)
Inter-Band	CA_2A-4A	Band 2	20M	1860	18700	QPSK	1	49	Band 4	20M	2132.5	2175	22.33	22.75
		Band 4	20M	1732.5	20175	QPSK	1	49	Band 2	20M	1960	900	19.32	19.44
	CA_2A-66A	Band 2	20M	1860	18700	QPSK	1	49	Band 66	20M	2155	66886	22.30	22.75
		Band 66	20M	1745	132322	QPSK	1	0	Band 2	20M	1960	900	19.31	19.59
	CA_4A-5A	Band 4	20M	1732.5	20175	QPSK	1	49	Band 5	10M	881.5	2525	19.27	19.44
		Band 5	10M	836.5	20525	QPSK	1	25	Band 4	20M	2132.5	2175	22.48	22.94
	CA_4A-12A	Band 4	20M	1732.5	20175	QPSK	1	49	Band 12	10M	737.5	5095	19.24	19.44
		Band 12	10M	704	23060	QPSK	1	25	Band 4	20M	2132.5	2175	22.20	22.71
	CA_4A-29A	Band 4	20M	1732.5	20175	QPSK	1	49	Band 29	10M	722.5	9715	19.26	19.44
	CA_5A-30A	Band 5	10M	836.5	20525	QPSK	1	25	Band 30	10M	2355	9820	22.77	22.94
		Band 30	10M	2310	27710	QPSK	1	25	Band 5	10M	881.5	2525	17.33	17.40
	CA_5A-66A	Band 5	10M	836.5	20525	QPSK	1	25	Band 66	20M	2155	66886	22.74	22.94
		Band 66	20M	1745	132322	QPSK	1	0	Band 5	10M	881.5	2525	19.31	19.59
	CA_12A-30A	Band 12	10M	704	23060	QPSK	1	25	Band 30	10M	2355	9820	22.75	22.71
		Band 30	10M	2310	27710	QPSK	1	25	Band 12	10M	737.5	5095	17.35	17.40
	CA_12A-66A	Band 12	10M	704	23060	QPSK	1	25	Band 66	20M	2155	66886	22.16	22.71
		Band 66	20M	1745	132322	QPSK	1	0	Band 12	10M	737.5	5095	19.30	19.59
	CA_14A-30A	Band 14	10M	793	23330	QPSK	1	25	Band 30	10M	2355	9820	22.61	22.66
		Band 30	10M	2310	27710	QPSK	1	25	Band 14	10M	763	5330	17.37	17.40
	CA_14A-66A	Band 14	10M	793	23330	QPSK	1	25	Band 66	20M	2155	66886	22.57	22.66
		Band 66	20M	1745	132322	QPSK	1	0	Band 14	10M	763	5330	19.28	19.59
	CA_29A-30A	Band 30	10M	2310	27710	QPSK	1	25	Band 29	10M	722.5	9715	17.37	17.40
	CA_29A-66A	Band 66	20M	1745	132322	QPSK	1	0	Band 29	10M	722.5	9715	19.28	19.59
	CA_30A-66A	Band 30	10M	2310	27710	QPSK	1	25	Band 66	20M	2155	66886	17.19	17.40
		Band 66	20M	1745	132322	QPSK	1	0	Band 30	10M	2355	9820	19.19	19.59
Intra-Band Non-Contiguous	CA_4A-4A	Band 4	20M	1732.5	20175	QPSK	1	49	Band 4	5M	2152.5	2375	19.24	19.44
	CA_66A-66A	Band 66	20M	1745	132322	QPSK	1	0	Band 66	5M	2197.5	67311	19.22	19.59

<WLAN Conducted Power>**General Note:**

1. Per KDB 248227 D01v02r02, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
2. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
3. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
4. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures.18 The initial test position procedure is described in the following:
 - a. When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
 - b. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
 - c. For all positions/configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.

<2.4GHz WLAN>
<Default Power Mode>

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
2.4GHz WLAN	802.11b 1Mbps	1	2412	16.40	18.00	99.31
		6	2437	17.60	18.00	
		11	2462	17.00	18.00	
	802.11g 6Mbps	1	2412	14.30	16.00	96.77
		6	2437	15.10	16.00	
		11	2462	14.60	16.00	
	802.11n-HT20 MCS0	1	2412	12.70	14.00	96.55
		6	2437	13.70	14.00	
		11	2462	13.10	14.00	

<At-Head Power Mode>

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
2.4GHz WLAN	802.11b 1Mbps	1	2412	14.50	15.50	99.31
		6	2437	15.00	15.50	
		11	2462	14.70	15.50	
	802.11g 6Mbps	1	2412	14.30	15.50	96.77
		6	2437	15.10	15.50	
		11	2462	14.60	15.50	
	802.11n-HT20 MCS0	1	2412	12.70	14.00	96.55
		6	2437	13.70	14.00	
		11	2462	13.10	14.00	

<2.4GHz Bluetooth>


Mode	Channel	Frequency (MHz)	Average power (dBm)		
			1Mbps	2Mbps	3Mbps
BR / EDR	CH 00	2402	8.40	6.60	6.60
	CH 39	2441	9.60	7.80	7.80
	CH 78	2480	9.40	7.50	7.50
Tune-up Limit			10	8	8

Mode	Channel	Frequency (MHz)	Average power (dBm)
			GFSK
LE v4.0	CH 00	2402	-4.10
	CH 19	2440	-2.20
	CH 39	2480	-2.10
Tune-up Limit			-1

Mode	Channel	Frequency (MHz)	Average power (dBm)
			2Mbps
LE v5.0	CH 00	2402	-4.00
	CH 19	2440	-2.10
	CH 39	2480	-2.00
Tune-up Limit			-1


General Note:

- For 2.4GHz Bluetooth SAR testing was selected 1Mbps due to its highest average power and duty cycle is 76.86% considered in SAR testing, and the duty cycle would be scaled to theoretical 83.3% in reported SAR calculation.



14. Antenna Location

<Mobile Phone>



Back View

Distance of the Antenna to the EUT surface/edge						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN Main	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	≤ 25mm	≤ 25mm
BT&WLAN	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	>25mm

Positions for SAR tests; Hotspot mode						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN Main	Yes	Yes	No	Yes	Yes	Yes
BT&WLAN	Yes	Yes	Yes	No	Yes	No

General Note:

- Referring to KDB 941225 D06 v02r01, when the overall device length and width are $\geq 9\text{cm} \times 5\text{cm}$, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge

15. SAR Test Results

General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
 - c. For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
 - d. For WLAN/Bluetooth: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.
4. Per KDB 648474 D04v01r03, when the reported SAR for a body-worn accessory measured without a headset connected to the handset is ≤ 1.2 W/kg, SAR testing with a headset connected to the handset is not required.
5. Per KDB648474 D04v01r03, for smart phones with a display diagonal dimension > 15cm or an overall diagonal dimension > 16cm, when hotspot mode applies, 10-g product specific SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg, in this report all the hotspot mode results are < 1.2W/kg.
6. Reduce power for different RF exposure conditions:
 - Body worn: The device employs proximity sensors that detect the presence of the user's body at the front or back faces of the device, when operating in near-body condition by end user; the device will reduced maximum output powers on the WCDMA B4/ B2 and LTE B2 / B4 / B30 / B66.
 - Hotspot: When the mobile hotspot session is turned on by end user, the device will reduce output powers on the WCDMA B4/ B2 and LTE B2 / B4 / B30 / B66.
 - Handheld: the device additionally employs proximity sensors that detect the presence of tissue near the currently active transmit antenna, the device will reduced output power on the CDMA B4/ B2 and LTE B2 / B4 / B30 / B66..
7. The device is used earpiece receiver to detect user head or body usage scenarios and separate head and body power table for WLAN, when the receiver worked mean head condition is detected and head power table is used, when the receiver not worked mean body/hotspot/extremity condition is detected and body power table is used.
8. For verification of compliance of power reduction scheme, additional SAR testing with EUT transmitting at full RF power at a conservative trigger distance was performed:
 - a. For Body-worn:
 - Front: [12 mm](#)
 - Back: [18 mm](#)

GSM Note:

1. Per KDB 941225 D01v03r01, for SAR test reduction for GSM / GPRS / EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the GPRS (4Tx slots) for GSM850/GSM1900 is considered as the primary mode.
2. Other configurations of GSM / GPRS / EDGE are considered as secondary modes. The 3G SAR test reduction procedure is applied, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode, SAR measurement is not required for the secondary mode.

UMTS Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA / HSPA+ is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA / HSPA+ to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA / HSPA+, and according to the following RF output power, the output power results of the secondary modes (HSUPA, HSDPA, DC-HSDPA, HSPA+) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA / HSPA+.

LTE Note:

1. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
2. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
3. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
4. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
5. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
6. For LTE B4 / B5 / B12 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
7. LTE band 4 SAR test was covered by Band 66; according to TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. The maximum output power, including tolerance, for the smaller band is $\leq$ the larger band to qualify for the SAR test exclusion.
 - b. The channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band.

**WLAN Note:**

1. Per KDB 248227 D01v02r02, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
2. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
3. For all positions / configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
4. During SAR testing the WLAN transmission was verified using a spectrum analyzer.
5. Since the same RF amplifier and antenna is used for WiFi / Bluetooth transmitter and the Bluetooth output power is least 2 dB below the output power of WiFi, therefore, for Bluetooth SAR testing is selected worst position from each exposure condition to be tested.

15.1 Head SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS 4 Tx slots	Right Cheek	0mm	251	848.8	29.09	30.00	1.233	0.02	0.479	0.591
	GSM850	GPRS 4 Tx slots	Right Tilted	0mm	251	848.8	29.09	30.00	1.233	0.04	0.219	0.270
01	GSM850	GPRS 4 Tx slots	Left Cheek	0mm	251	848.8	29.09	30.00	1.233	0.19	0.517	0.638
	GSM850	GPRS 4 Tx slots	Left Tilted	0mm	251	848.8	29.09	30.00	1.233	0.08	0.236	0.291
	GSM1900	GPRS 4 Tx slots	Right Cheek	0mm	810	1909.8	25.86	26.50	1.159	0.1	0.205	0.238
	GSM1900	GPRS 4 Tx slots	Right Tilted	0mm	810	1909.8	25.86	26.50	1.159	0.06	0.161	0.187
02	GSM1900	GPRS 4 Tx slots	Left Cheek	0mm	810	1909.8	25.86	26.50	1.159	0.04	0.297	0.344
	GSM1900	GPRS 4 Tx slots	Left Tilted	0mm	810	1909.8	25.86	26.50	1.159	0.06	0.178	0.206

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA V	RMC 12.2Kbps	Right Cheek	0mm	4132	826.4	23.85	25.00	1.303	0.04	0.258	0.336
	WCDMA V	RMC 12.2Kbps	Right Tilted	0mm	4132	826.4	23.85	25.00	1.303	-0.04	0.125	0.163
03	WCDMA V	RMC 12.2Kbps	Left Cheek	0mm	4132	826.4	23.85	25.00	1.303	-0.07	0.269	0.351
	WCDMA V	RMC 12.2Kbps	Left Tilted	0mm	4132	826.4	23.85	25.00	1.303	-0.02	0.119	0.155
	WCDMA IV	RMC 12.2Kbps	Right Cheek	0mm	1312	1712.4	23.64	25.00	1.368	0.07	0.229	0.313
	WCDMA IV	RMC 12.2Kbps	Right Tilted	0mm	1312	1712.4	23.64	25.00	1.368	-0.05	0.262	0.358
04	WCDMA IV	RMC 12.2Kbps	Left Cheek	0mm	1312	1712.4	23.64	25.00	1.368	0.05	0.292	0.399
	WCDMA IV	RMC 12.2Kbps	Left Tilted	0mm	1312	1712.4	23.64	25.00	1.368	0.03	0.202	0.276
	WCDMA II	RMC 12.2Kbps	Right Cheek	0mm	9538	1907.6	23.91	25.00	1.285	-0.03	0.278	0.357
	WCDMA II	RMC 12.2Kbps	Right Tilted	0mm	9538	1907.6	23.91	25.00	1.285	0.03	0.238	0.306
05	WCDMA II	RMC 12.2Kbps	Left Cheek	0mm	9538	1907.6	23.91	25.00	1.285	0.01	0.400	0.514
	WCDMA II	RMC 12.2Kbps	Left Tilted	0mm	9538	1907.6	23.91	25.00	1.285	0.05	0.233	0.299

<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
06	LTE Band 12	10M	QPSK	1	25	Right Cheek	0mm	23095	707.5	22.53	24.00	1.403	-0.07	0.281	0.394
	LTE Band 12	10M	QPSK	25	12	Right Cheek	0mm	23095	707.5	21.68	23.00	1.355	-0.02	0.221	0.299
	LTE Band 12	10M	QPSK	1	25	Right Tilted	0mm	23095	707.5	22.53	24.00	1.403	0.03	0.140	0.196
	LTE Band 12	10M	QPSK	25	12	Right Tilted	0mm	23095	707.5	21.68	23.00	1.355	-0.05	0.106	0.144
	LTE Band 12	10M	QPSK	1	25	Left Cheek	0mm	23095	707.5	22.53	24.00	1.403	0.07	0.277	0.389
	LTE Band 12	10M	QPSK	25	12	Left Cheek	0mm	23095	707.5	21.68	23.00	1.355	0.01	0.228	0.309
	LTE Band 12	10M	QPSK	1	25	Left Tilted	0mm	23095	707.5	22.53	24.00	1.403	0.01	0.131	0.184
	LTE Band 12	10M	QPSK	25	12	Left Tilted	0mm	23095	707.5	21.68	23.00	1.355	0.05	0.107	0.145
07	LTE Band 14	10M	QPSK	1	25	Right Cheek	0mm	23330	793	22.66	24.00	1.361	0.06	0.220	0.300
	LTE Band 14	10M	QPSK	25	12	Right Cheek	0mm	23330	793	21.56	23.00	1.393	-0.05	0.177	0.247
	LTE Band 14	10M	QPSK	1	25	Right Tilted	0mm	23330	793	22.66	24.00	1.361	-0.07	0.111	0.151
	LTE Band 14	10M	QPSK	25	12	Right Tilted	0mm	23330	793	21.56	23.00	1.393	-0.08	0.090	0.125
	LTE Band 14	10M	QPSK	1	25	Left Cheek	0mm	23330	793	22.66	24.00	1.361	0.04	0.211	0.287
	LTE Band 14	10M	QPSK	25	12	Left Cheek	0mm	23330	793	21.56	23.00	1.393	0.06	0.165	0.230
	LTE Band 14	10M	QPSK	1	25	Left Tilted	0mm	23330	793	22.66	24.00	1.361	0.03	0.109	0.148
	LTE Band 14	10M	QPSK	25	12	Left Tilted	0mm	23330	793	21.56	23.00	1.393	0.09	0.089	0.123

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
08	LTE Band 5	10M	QPSK	1	25	Right Cheek	0mm	20525	836.5	22.94	24.00	1.276	0.04	0.284	0.363
	LTE Band 5	10M	QPSK	25	25	Right Cheek	0mm	20525	836.5	21.85	23.00	1.303	0.01	0.235	0.306
	LTE Band 5	10M	QPSK	1	25	Right Tilted	0mm	20525	836.5	22.94	24.00	1.276	0.01	0.135	0.172
	LTE Band 5	10M	QPSK	25	25	Right Tilted	0mm	20525	836.5	21.85	23.00	1.303	-0.04	0.113	0.147
	LTE Band 5	10M	QPSK	1	25	Left Cheek	0mm	20525	836.5	22.94	24.00	1.276	0.19	0.276	0.352
	LTE Band 5	10M	QPSK	25	25	Left Cheek	0mm	20525	836.5	21.85	23.00	1.303	0.09	0.226	0.295
	LTE Band 5	10M	QPSK	1	25	Left Tilted	0mm	20525	836.5	22.94	24.00	1.276	0.03	0.166	0.212
	LTE Band 5	10M	QPSK	25	25	Left Tilted	0mm	20525	836.5	21.85	23.00	1.303	0.06	0.129	0.168
	LTE Band 66	20M	QPSK	1	0	Right Cheek	0mm	132322	1745	22.45	24.00	1.429	-0.09	0.183	0.261
	LTE Band 66	20M	QPSK	50	0	Right Cheek	0mm	132322	1745	21.32	23.00	1.472	0.05	0.162	0.239
	LTE Band 66	20M	QPSK	1	0	Right Tilted	0mm	132322	1745	22.45	24.00	1.429	0.06	0.205	0.293
	LTE Band 66	20M	QPSK	50	0	Right Tilted	0mm	132322	1745	21.32	23.00	1.472	-0.06	0.185	0.272
09	LTE Band 66	20M	QPSK	1	0	Left Cheek	0mm	132322	1745	22.45	24.00	1.429	0.05	0.279	0.399
	LTE Band 66	20M	QPSK	50	0	Left Cheek	0mm	132322	1745	21.32	23.00	1.472	0.02	0.248	0.365
	LTE Band 66	20M	QPSK	1	0	Left Tilted	0mm	132322	1745	22.45	24.00	1.429	0.07	0.176	0.251
	LTE Band 66	20M	QPSK	50	0	Left Tilted	0mm	132322	1745	21.32	23.00	1.472	-0.04	0.153	0.225
	LTE Band 2	20M	QPSK	1	49	Right Cheek	0mm	18700	1860	22.75	24.00	1.334	-0.03	0.257	0.343
	LTE Band 2	20M	QPSK	50	24	Right Cheek	0mm	18700	1860	21.60	23.00	1.380	0.02	0.203	0.280
	LTE Band 2	20M	QPSK	1	49	Right Tilted	0mm	18700	1860	22.75	24.00	1.334	0.03	0.233	0.311
	LTE Band 2	20M	QPSK	50	24	Right Tilted	0mm	18700	1860	21.60	23.00	1.380	-0.06	0.180	0.248
10	LTE Band 2	20M	QPSK	1	49	Left Cheek	0mm	18700	1860	22.75	24.00	1.334	0.03	0.396	0.528
	LTE Band 2	20M	QPSK	50	24	Left Cheek	0mm	18700	1860	21.60	23.00	1.380	0.08	0.313	0.432
	LTE Band 2	20M	QPSK	1	49	Left Tilted	0mm	18700	1860	22.75	24.00	1.334	0.01	0.236	0.315
	LTE Band 2	20M	QPSK	50	24	Left Tilted	0mm	18700	1860	21.60	23.00	1.380	0.09	0.186	0.257
11	LTE Band 30	10M	QPSK	1	25	Right Cheek	0mm	27710	2310	22.83	24.00	1.309	-0.09	0.201	0.263
	LTE Band 30	10M	QPSK	25	25	Right Cheek	0mm	27710	2310	21.70	23.00	1.349	-0.02	0.143	0.193
	LTE Band 30	10M	QPSK	1	25	Right Tilted	0mm	27710	2310	22.83	24.00	1.309	-0.02	0.076	0.100
	LTE Band 30	10M	QPSK	25	25	Right Tilted	0mm	27710	2310	21.70	23.00	1.349	-0.07	0.061	0.082
	LTE Band 30	10M	QPSK	1	25	Left Cheek	0mm	27710	2310	22.83	24.00	1.309	0.06	0.082	0.107
	LTE Band 30	10M	QPSK	25	25	Left Cheek	0mm	27710	2310	21.70	23.00	1.349	0.06	0.061	0.082
	LTE Band 30	10M	QPSK	1	25	Left Tilted	0mm	27710	2310	22.83	24.00	1.309	0.02	0.105	0.137
	LTE Band 30	10M	QPSK	25	25	Left Tilted	0mm	27710	2310	21.70	23.00	1.349	0.05	0.093	0.126

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	0mm	Receiver On	6	2437	15.00	15.50	1.122	99.31	1.007	-0.02	0.247	0.279
	WLAN2.4GHz	802.11b 1Mbps	Right Tilted	0mm	Receiver On	6	2437	15.00	15.50	1.122	99.31	1.007	0.02	0.211	0.238
12	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	Receiver On	6	2437	15.00	15.50	1.122	99.31	1.007	-0.1	0.632	0.714
	WLAN2.4GHz	802.11b 1Mbps	Left Tilted	0mm	Receiver On	6	2437	15.00	15.50	1.122	99.31	1.007	-0.05	0.464	0.524

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
13	Bluetooth	1Mbps	Left Cheek	0mm	39	2441	9.60	10.00	1.096	76.86	1.084	0.09	0.209	0.248

Based on WLAN2.4GHz and Bluetooth share the same antenna, so Bluetooth RF exposure evaluation chose the worst position of WLAN 2.4GHz Ant to perform Bluetooth SAR test, and used this Bluetooth SAR value conservatively represent other position do co-located analysis with WWAN.

15.2 Hotspot SAR
<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS 4 Tx slots	Front	10mm	251	848.8	29.09	30.00	1.233	0.01	0.422	0.520
14	GSM850	GPRS 4 Tx slots	Back	10mm	251	848.8	29.09	30.00	1.233	0.08	0.568	0.700
	GSM850	GPRS 4 Tx slots	Left Side	10mm	251	848.8	29.09	30.00	1.233	0.01	0.472	0.582
	GSM850	GPRS 4 Tx slots	Right Side	10mm	251	848.8	29.09	30.00	1.233	-0.02	0.473	0.583
	GSM850	GPRS 4 Tx slots	Bottom Side	10mm	251	848.8	29.09	30.00	1.233	-0.02	0.081	0.100
	GSM1900	GPRS 4 Tx slots	Front	10mm	810	1909.8	25.86	26.50	1.159	-0.03	0.614	0.711
15	GSM1900	GPRS 4 Tx slots	Back	10mm	810	1909.8	25.86	26.50	1.159	-0.04	0.728	0.844
	GSM1900	GPRS 4 Tx slots	Back	10mm	512	1850.2	25.77	26.50	1.183	-0.07	0.686	0.812
	GSM1900	GPRS 4 Tx slots	Back	10mm	661	1880	25.82	26.50	1.169	-0.07	0.682	0.798
	GSM1900	GPRS 4 Tx slots	Left Side	10mm	810	1909.8	25.86	26.50	1.159	0.02	0.351	0.407
	GSM1900	GPRS 4 Tx slots	Right Side	10mm	810	1909.8	25.86	26.50	1.159	0.04	0.137	0.159
	GSM1900	GPRS 4 Tx slots	Bottom Side	10mm	810	1909.8	25.86	26.50	1.159	0.09	0.501	0.581

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA V	RMC 12.2Kbps	Front	10mm	4132	826.4	23.85	25.00	1.303	-0.1	0.296	0.386
16	WCDMA V	RMC 12.2Kbps	Back	10mm	4132	826.4	23.85	25.00	1.303	-0.02	0.438	0.571
	WCDMA V	RMC 12.2Kbps	Left Side	10mm	4132	826.4	23.85	25.00	1.303	-0.02	0.297	0.387
	WCDMA V	RMC 12.2Kbps	Right Side	10mm	4132	826.4	23.85	25.00	1.303	0.07	0.287	0.374
	WCDMA V	RMC 12.2Kbps	Bottom Side	10mm	4132	826.4	23.85	25.00	1.303	-0.01	0.048	0.062
	WCDMA IV	RMC 12.2Kbps	Front	10mm	1312	1712.4	20.81	22.00	1.315	-0.06	0.333	0.438
17	WCDMA IV	RMC 12.2Kbps	Back	10mm	1312	1712.4	20.81	22.00	1.315	-0.1	0.778	1.023
	WCDMA IV	RMC 12.2Kbps	Back	10mm	1413	1732.6	20.71	22.00	1.346	-0.06	0.718	0.966
	WCDMA IV	RMC 12.2Kbps	Back	10mm	1513	1752.6	20.67	22.00	1.358	-0.05	0.663	0.901
	WCDMA IV	RMC 12.2Kbps	Left Side	10mm	1312	1712.4	20.81	22.00	1.315	0.07	0.144	0.189
	WCDMA IV	RMC 12.2Kbps	Right Side	10mm	1312	1712.4	20.81	22.00	1.315	0.01	0.046	0.060
	WCDMA IV	RMC 12.2Kbps	Bottom Side	10mm	1312	1712.4	20.81	22.00	1.315	0.16	0.725	0.954
	WCDMA IV	RMC 12.2Kbps	Bottom Side	10mm	1413	1732.6	20.71	22.00	1.346	0.08	0.676	0.910
	WCDMA IV	RMC 12.2Kbps	Bottom Side	10mm	1513	1752.6	20.67	22.00	1.358	0.17	0.657	0.892
	WCDMA II	RMC 12.2Kbps	Front	10mm	9538	1907.6	23.91	24.50	1.146	0.02	0.778	0.891
	WCDMA II	RMC 12.2Kbps	Front	10mm	9262	1852.4	23.90	24.50	1.148	-0.07	0.887	1.018
	WCDMA II	RMC 12.2Kbps	Front	10mm	9400	1880	23.88	24.50	1.153	-0.06	0.866	0.999
	WCDMA II	RMC 12.2Kbps	Back	10mm	9538	1907.6	23.91	24.50	1.146	0.07	0.863	0.989
18	WCDMA II	RMC 12.2Kbps	Back	10mm	9262	1852.4	23.90	24.50	1.148	-0.01	0.913	1.048
	WCDMA II	RMC 12.2Kbps	Back	10mm	9262	1852.4	23.90	24.50	1.148	-0.11	0.899	1.032
	WCDMA II	RMC 12.2Kbps	Back	10mm	9400	1880	23.88	24.50	1.153	0.01	0.897	1.035
	WCDMA II	RMC 12.2Kbps	Left Side	10mm	9538	1907.6	23.91	24.50	1.146	0.05	0.420	0.481
	WCDMA II	RMC 12.2Kbps	Right Side	10mm	9538	1907.6	23.91	24.50	1.146	0.02	0.155	0.178
	WCDMA II	RMC 12.2Kbps	Bottom Side	10mm	9538	1907.6	23.91	24.50	1.146	0.17	0.673	0.771
	WCDMA II	RMC 12.2Kbps	Bottom Side	10mm	9262	1852.4	23.90	24.50	1.148	-0.01	0.807	0.927
	WCDMA II	RMC 12.2Kbps	Bottom Side	10mm	9400	1880	23.88	24.50	1.153	-0.01	0.729	0.841



<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 12	10M	QPSK	1	25	Front	10mm	23095	707.5	22.53	24.00	1.403	-0.08	0.275	0.386
	LTE Band 12	10M	QPSK	25	12	Front	10mm	23095	707.5	21.68	23.00	1.355	-0.08	0.219	0.297
19	LTE Band 12	10M	QPSK	1	25	Back	10mm	23095	707.5	22.53	24.00	1.403	0.01	0.350	0.491
	LTE Band 12	10M	QPSK	25	12	Back	10mm	23095	707.5	21.68	23.00	1.355	0.03	0.271	0.367
	LTE Band 12	10M	QPSK	1	25	Left Side	10mm	23095	707.5	22.53	24.00	1.403	0.09	0.249	0.349
	LTE Band 12	10M	QPSK	25	12	Left Side	10mm	23095	707.5	21.68	23.00	1.355	0.06	0.196	0.266
	LTE Band 12	10M	QPSK	1	25	Right Side	10mm	23095	707.5	22.53	24.00	1.403	-0.06	0.348	0.488
	LTE Band 12	10M	QPSK	25	12	Right Side	10mm	23095	707.5	21.68	23.00	1.355	-0.08	0.277	0.375
	LTE Band 12	10M	QPSK	1	25	Bottom Side	10mm	23095	707.5	22.53	24.00	1.403	0.02	0.042	0.058
	LTE Band 12	10M	QPSK	25	12	Bottom Side	10mm	23095	707.5	21.68	23.00	1.355	-0.17	0.031	0.042
	LTE Band 14	10M	QPSK	1	25	Front	10mm	23330	793	22.66	24.00	1.361	-0.03	0.207	0.282
	LTE Band 14	10M	QPSK	25	12	Front	10mm	23330	793	21.56	23.00	1.393	-0.07	0.166	0.231
	LTE Band 14	10M	QPSK	1	25	Back	10mm	23330	793	22.66	24.00	1.361	-0.07	0.272	0.370
	LTE Band 14	10M	QPSK	25	12	Back	10mm	23330	793	21.56	23.00	1.393	-0.06	0.208	0.290
	LTE Band 14	10M	QPSK	1	25	Left Side	10mm	23330	793	22.66	24.00	1.361	0.01	0.309	0.421
	LTE Band 14	10M	QPSK	25	12	Left Side	10mm	23330	793	21.56	23.00	1.393	0.08	0.253	0.352
20	LTE Band 14	10M	QPSK	1	25	Right Side	10mm	23330	793	22.66	24.00	1.361	0.11	0.336	0.457
	LTE Band 14	10M	QPSK	25	12	Right Side	10mm	23330	793	21.56	23.00	1.393	-0.09	0.265	0.369
	LTE Band 14	10M	QPSK	1	25	Bottom Side	10mm	23330	793	22.66	24.00	1.361	0.01	0.044	0.060
	LTE Band 14	10M	QPSK	25	12	Bottom Side	10mm	23330	793	21.56	23.00	1.393	-0.01	0.035	0.049
	LTE Band 5	10M	QPSK	1	25	Front	10mm	20525	836.5	22.94	24.00	1.276	0.03	0.306	0.391
	LTE Band 5	10M	QPSK	25	25	Front	10mm	20525	836.5	21.85	23.00	1.303	0.01	0.238	0.310
21	LTE Band 5	10M	QPSK	1	25	Back	10mm	20525	836.5	22.94	24.00	1.276	0.03	0.381	0.486
	LTE Band 5	10M	QPSK	25	25	Back	10mm	20525	836.5	21.85	23.00	1.303	-0.02	0.330	0.430
	LTE Band 5	10M	QPSK	1	25	Left Side	10mm	20525	836.5	22.94	24.00	1.276	0.02	0.333	0.425
	LTE Band 5	10M	QPSK	25	25	Left Side	10mm	20525	836.5	21.85	23.00	1.303	0.01	0.249	0.324
	LTE Band 5	10M	QPSK	1	25	Right Side	10mm	20525	836.5	22.94	24.00	1.276	0.01	0.277	0.354
	LTE Band 5	10M	QPSK	25	25	Right Side	10mm	20525	836.5	21.85	23.00	1.303	0.1	0.226	0.295
	LTE Band 5	10M	QPSK	1	25	Bottom Side	10mm	20525	836.5	22.94	24.00	1.276	-0.03	0.044	0.057
	LTE Band 5	10M	QPSK	25	25	Bottom Side	10mm	20525	836.5	21.85	23.00	1.303	-0.1	0.044	0.057
	LTE Band 66	20M	QPSK	1	0	Front	10mm	132322	1745	19.59	21.00	1.384	-0.08	0.297	0.411
	LTE Band 66	20M	QPSK	50	0	Front	10mm	132322	1745	18.46	20.00	1.426	0.01	0.264	0.376
	LTE Band 66	20M	QPSK	1	0	Back	10mm	132322	1745	19.59	21.00	1.384	-0.12	0.634	0.877
22	LTE Band 66	20M	QPSK	1	0	Back	10mm	132072	1720	19.40	21.00	1.445	-0.03	0.746	1.078
	LTE Band 66	20M	QPSK	1	0	Back	10mm	132572	1770	19.45	21.00	1.429	-0.05	0.591	0.844
	LTE Band 66	20M	QPSK	50	0	Back	10mm	132322	1745	18.46	20.00	1.426	-0.13	0.524	0.747
	LTE Band 66	20M	QPSK	100	0	Back	10mm	132322	1745	18.33	20.00	1.469	-0.04	0.508	0.746
	LTE Band 66	20M	QPSK	1	0	Left Side	10mm	132322	1745	19.59	21.00	1.384	0.08	0.145	0.201
	LTE Band 66	20M	QPSK	50	0	Left Side	10mm	132322	1745	18.46	20.00	1.426	0.03	0.137	0.195
	LTE Band 66	20M	QPSK	1	0	Right Side	10mm	132322	1745	19.59	21.00	1.384	0.11	0.058	0.080
	LTE Band 66	20M	QPSK	50	0	Right Side	10mm	132322	1745	18.46	20.00	1.426	0.03	0.054	0.076
	LTE Band 66	20M	QPSK	1	0	Bottom Side	10mm	132322	1745	19.59	21.00	1.384	0.16	0.596	0.825
	LTE Band 66	20M	QPSK	1	0	Bottom Side	10mm	132072	1720	19.40	21.00	1.445	0.17	0.700	1.012
	LTE Band 66	20M	QPSK	1	0	Bottom Side	10mm	132572	1770	19.45	21.00	1.429	0.15	0.583	0.833
	LTE Band 66	20M	QPSK	50	0	Bottom Side	10mm	132322	1745	18.46	20.00	1.426	0.16	0.514	0.733
	LTE Band 66	20M	QPSK	100	0	Bottom Side	10mm	132322	1745	18.33	20.00	1.469	0.06	0.496	0.729

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 2	20M	QPSK	1	49	Front	10mm	18700	1860	22.75	23.50	1.189	-0.03	0.779	0.926
	LTE Band 2	20M	QPSK	1	49	Front	10mm	18900	1880	22.58	23.50	1.236	0.01	0.757	0.936
	LTE Band 2	20M	QPSK	1	49	Front	10mm	19100	1900	22.58	23.50	1.236	-0.04	0.705	0.871
	LTE Band 2	20M	QPSK	50	24	Front	10mm	18700	1860	21.60	23.00	1.380	-0.05	0.611	0.843
	LTE Band 2	20M	QPSK	50	24	Front	10mm	18900	1880	21.50	23.00	1.413	-0.03	0.603	0.852
	LTE Band 2	20M	QPSK	50	24	Front	10mm	19100	1900	21.48	23.00	1.419	-0.02	0.565	0.802
	LTE Band 2	20M	QPSK	100	0	Front	10mm	18700	1860	21.52	23.00	1.406	-0.07	0.530	0.745
	LTE Band 2	20M	QPSK	1	49	Back	10mm	18700	1860	22.75	23.50	1.189	-0.08	0.873	1.038
23	LTE Band 2	20M	QPSK	1	49	Back	10mm	18900	1880	22.58	23.50	1.236	-0.03	0.845	1.044
	LTE Band 2	20M	QPSK	1	49	Back	10mm	19100	1900	22.58	23.50	1.236	-0.08	0.789	0.975
	LTE Band 2	20M	QPSK	50	24	Back	10mm	18700	1860	21.60	23.00	1.380	-0.07	0.691	0.954
	LTE Band 2	20M	QPSK	50	24	Back	10mm	18900	1880	21.50	23.00	1.413	0.01	0.680	0.961
	LTE Band 2	20M	QPSK	50	24	Back	10mm	19100	1900	21.48	23.00	1.419	-0.02	0.629	0.893
	LTE Band 2	20M	QPSK	100	0	Back	10mm	18700	1860	21.52	23.00	1.406	-0.08	0.690	0.970
	LTE Band 2	20M	QPSK	1	49	Left Side	10mm	18700	1860	22.75	23.50	1.189	0.07	0.447	0.531
	LTE Band 2	20M	QPSK	50	24	Left Side	10mm	18700	1860	21.60	23.00	1.380	-0.04	0.342	0.472
	LTE Band 2	20M	QPSK	1	49	Right Side	10mm	18700	1860	22.75	23.50	1.189	0.08	0.158	0.188
	LTE Band 2	20M	QPSK	50	24	Right Side	10mm	18700	1860	21.60	23.00	1.380	-0.07	0.121	0.167
	LTE Band 2	20M	QPSK	1	49	Bottom Side	10mm	18700	1860	22.75	23.50	1.189	0.03	0.628	0.746
	LTE Band 2	20M	QPSK	1	49	Bottom Side	10mm	18900	1880	22.58	23.50	1.236	0.08	0.639	0.790
	LTE Band 2	20M	QPSK	1	49	Bottom Side	10mm	19100	1900	22.58	23.50	1.236	0.08	0.579	0.716
	LTE Band 2	20M	QPSK	50	24	Bottom Side	10mm	18700	1860	21.60	23.00	1.380	0.1	0.581	0.802
	LTE Band 2	20M	QPSK	50	24	Bottom Side	10mm	18900	1880	21.50	23.00	1.413	-0.05	0.517	0.730
	LTE Band 2	20M	QPSK	50	24	Bottom Side	10mm	19100	1900	21.48	23.00	1.419	-0.06	0.454	0.644
	LTE Band 2	20M	QPSK	100	0	Bottom Side	10mm	18700	1860	21.52	23.00	1.406	-0.1	0.575	0.808
	LTE Band 30	10M	QPSK	1	25	Front	10mm	27710	2310	17.40	19.00	1.445	-0.14	0.374	0.541
	LTE Band 30	10M	QPSK	25	25	Front	10mm	27710	2310	16.43	18.00	1.435	-0.01	0.296	0.425
	LTE Band 30	10M	QPSK	1	25	Back	10mm	27710	2310	17.40	19.00	1.445	-0.08	0.709	1.025
	LTE Band 30	10M	QPSK	25	25	Back	10mm	27710	2310	16.43	18.00	1.435	0.03	0.561	0.805
	LTE Band 30	10M	QPSK	50	0	Back	10mm	27710	2310	16.43	18.00	1.435	0.09	0.566	0.812
	LTE Band 30	10M	QPSK	1	25	Left Side	10mm	27710	2310	17.40	19.00	1.445	0.01	0.042	0.061
	LTE Band 30	10M	QPSK	25	25	Left Side	10mm	27710	2310	16.43	18.00	1.435	0.03	0.034	0.049
	LTE Band 30	10M	QPSK	1	25	Right Side	10mm	27710	2310	17.40	19.00	1.445	0.07	0.090	0.131
	LTE Band 30	10M	QPSK	25	25	Right Side	10mm	27710	2310	16.43	18.00	1.435	0.01	0.070	0.101
24	LTE Band 30	10M	QPSK	1	25	Bottom Side	10mm	27710	2310	17.40	19.00	1.445	0.13	0.711	1.028
	LTE Band 30	10M	QPSK	25	25	Bottom Side	10mm	27710	2310	16.43	18.00	1.435	0.1	0.567	0.814
	LTE Band 30	10M	QPSK	50	0	Bottom Side	10mm	27710	2310	16.43	18.00	1.435	0.12	0.570	0.818

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	10mm	6	2437	17.60	18.00	1.096	99.31	1.007	-0.06	0.201	0.222
25	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	6	2437	17.60	18.00	1.096	99.31	1.007	-0.02	0.267	0.295
	WLAN2.4GHz	802.11b 1Mbps	Right Side	10mm	6	2437	17.60	18.00	1.096	99.31	1.007	0.02	0.031	0.034
	WLAN2.4GHz	802.11b 1Mbps	Top Side	10mm	6	2437	17.60	18.00	1.096	99.31	1.007	-0.11	0.108	0.119

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
26	Bluetooth	1Mbps	Back	10mm	39	2441	9.60	10.00	1.096	76.86	1.084	-0.02	0.042	0.050

Based on WLAN2.4GHz and Bluetooth share the same antenna, so Bluetooth RF exposure evaluation chose the worst position of WLAN 2.4GHz Ant to perform Bluetooth SAR test, and used this Bluetooth SAR value conservatively represent other position do co-located analysis with WWAN.

15.3 Body Worn Accessory SAR
<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS 4 Tx slots	Front	10mm	251	848.8	29.09	30.00	1.233	0.01	0.422	0.520
27	GSM850	GPRS 4 Tx slots	Back	10mm	251	848.8	29.09	30.00	1.233	0.08	0.568	0.700
	GSM1900	GPRS 4 Tx slots	Front	10mm	810	1909.8	25.86	26.50	1.159	-0.03	0.614	0.711
28	GSM1900	GPRS 4 Tx slots	Back	10mm	810	1909.8	25.86	26.50	1.159	-0.04	0.728	0.844
	GSM1900	GPRS 4 Tx slots	Back	10mm	512	1850.2	25.77	26.50	1.183	-0.07	0.686	0.812
	GSM1900	GPRS 4 Tx slots	Back	10mm	661	1880	25.82	26.50	1.169	-0.07	0.682	0.798

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA V	RMC 12.2Kbps	Front	10mm	4132	826.4	23.85	25.00	1.303	-0.1	0.296	0.386
29	WCDMA V	RMC 12.2Kbps	Back	10mm	4132	826.4	23.85	25.00	1.303	-0.02	0.438	0.571
	WCDMA IV	RMC 12.2Kbps	Front	10mm	1312	1712.4	20.81	22.00	1.315	-0.06	0.333	0.438
30	WCDMA IV	RMC 12.2Kbps	Back	10mm	1312	1712.4	20.81	22.00	1.315	-0.1	0.778	1.023
	WCDMA IV	RMC 12.2Kbps	Back	10mm	1413	1732.6	20.71	22.00	1.346	-0.06	0.718	0.966
	WCDMA IV	RMC 12.2Kbps	Back	10mm	1513	1752.6	20.67	22.00	1.358	-0.05	0.663	0.901
	WCDMA IV	RMC 12.2Kbps	Front	12mm	1312	1712.4	23.64	25.00	1.368	-0.02	0.716	0.979
	WCDMA IV	RMC 12.2Kbps	Front	12mm	1413	1732.6	23.58	25.00	1.387	-0.17	0.634	0.879
	WCDMA IV	RMC 12.2Kbps	Front	12mm	1513	1752.6	23.56	25.00	1.393	0.05	0.601	0.837
	WCDMA IV	RMC 12.2Kbps	Back	18mm	1312	1712.4	23.64	25.00	1.368	-0.06	0.692	0.946
	WCDMA IV	RMC 12.2Kbps	Back	18mm	1413	1732.6	23.58	25.00	1.387	-0.06	0.584	0.810
	WCDMA IV	RMC 12.2Kbps	Back	18mm	1513	1752.6	23.56	25.00	1.393	0.04	0.528	0.736
	WCDMA II	RMC 12.2Kbps	Front	10mm	9538	1907.6	23.91	24.50	1.146	0.02	0.778	0.891
	WCDMA II	RMC 12.2Kbps	Front	10mm	9262	1852.4	23.90	24.50	1.148	-0.07	0.887	1.018
	WCDMA II	RMC 12.2Kbps	Front	10mm	9400	1880	23.88	24.50	1.153	-0.06	0.866	0.999
	WCDMA II	RMC 12.2Kbps	Back	10mm	9538	1907.6	23.91	24.50	1.146	0.07	0.863	0.989
31	WCDMA II	RMC 12.2Kbps	Back	10mm	9262	1852.4	23.90	24.50	1.148	-0.01	0.913	1.048
	WCDMA II	RMC 12.2Kbps	Back	10mm	9262	1852.4	23.90	24.50	1.148	-0.11	0.899	1.032
	WCDMA II	RMC 12.2Kbps	Back	10mm	9400	1880	23.88	24.50	1.153	0.01	0.897	1.035
	WCDMA II	RMC 12.2Kbps	Front	12mm	9262	1852.4	23.90	25.00	1.288	-0.13	0.642	0.827
	WCDMA II	RMC 12.2Kbps	Front	12mm	9400	1880	23.88	25.00	1.294	-0.09	0.616	0.797
	WCDMA II	RMC 12.2Kbps	Front	12mm	9538	1907.6	23.91	25.00	1.285	-0.06	0.591	0.760
	WCDMA II	RMC 12.2Kbps	Back	18mm	9262	1852.4	23.90	25.00	1.288	-0.11	0.368	0.474

<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 12	10M	QPSK	1	25	Front	10mm	23095	707.5	22.53	24.00	1.403	-0.08	0.275	0.386
	LTE Band 12	10M	QPSK	25	12	Front	10mm	23095	707.5	21.68	23.00	1.355	-0.08	0.219	0.297
32	LTE Band 12	10M	QPSK	1	25	Back	10mm	23095	707.5	22.53	24.00	1.403	0.01	0.350	0.491
	LTE Band 12	10M	QPSK	25	12	Back	10mm	23095	707.5	21.68	23.00	1.355	0.03	0.271	0.367
	LTE Band 14	10M	QPSK	1	25	Front	10mm	23330	793	22.66	24.00	1.361	-0.03	0.207	0.282
	LTE Band 14	10M	QPSK	25	12	Front	10mm	23330	793	21.56	23.00	1.393	-0.07	0.166	0.231
33	LTE Band 14	10M	QPSK	1	25	Back	10mm	23330	793	22.66	24.00	1.361	-0.07	0.272	0.370
	LTE Band 14	10M	QPSK	25	12	Back	10mm	23330	793	21.56	23.00	1.393	-0.06	0.208	0.290
	LTE Band 5	10M	QPSK	1	25	Front	10mm	20525	836.5	22.94	24.00	1.276	0.03	0.306	0.391
	LTE Band 5	10M	QPSK	25	25	Front	10mm	20525	836.5	21.85	23.00	1.303	0.01	0.238	0.310
34	LTE Band 5	10M	QPSK	1	25	Back	10mm	20525	836.5	22.94	24.00	1.276	0.03	0.381	0.486
	LTE Band 5	10M	QPSK	25	25	Back	10mm	20525	836.5	21.85	23.00	1.303	-0.02	0.330	0.430

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 66	20M	QPSK	1	0	Front	10mm	132322	1745	19.59	21.00	1.384	-0.08	0.297	0.411
	LTE Band 66	20M	QPSK	50	0	Front	10mm	132322	1745	18.46	20.00	1.426	0.01	0.264	0.376
	LTE Band 66	20M	QPSK	1	0	Back	10mm	132322	1745	19.59	21.00	1.384	-0.12	0.634	0.877
35	LTE Band 66	20M	QPSK	1	0	Back	10mm	132072	1720	19.40	21.00	1.445	-0.03	0.746	1.078
	LTE Band 66	20M	QPSK	1	0	Back	10mm	132572	1770	19.45	21.00	1.429	-0.05	0.591	0.844
	LTE Band 66	20M	QPSK	50	0	Back	10mm	132322	1745	18.46	20.00	1.426	-0.13	0.524	0.747
	LTE Band 66	20M	QPSK	100	0	Back	10mm	132322	1745	18.33	20.00	1.469	-0.04	0.508	0.746
	LTE Band 66	20M	QPSK	1	0	Front	12mm	132322	1745	22.45	24.00	1.429	-0.16	0.476	0.680
	LTE Band 66	20M	QPSK	1	0	Back	18mm	132072	1720	22.01	24.00	1.581	-0.09	0.548	0.867
	LTE Band 66	20M	QPSK	1	0	Back	18mm	132322	1745	22.45	24.00	1.429	-0.08	0.474	0.677
	LTE Band 66	20M	QPSK	1	0	Back	18mm	132572	1770	22.19	24.00	1.517	-0.04	0.424	0.643
	LTE Band 2	20M	QPSK	1	49	Front	10mm	18700	1860	22.75	23.50	1.189	-0.03	0.779	0.926
	LTE Band 2	20M	QPSK	1	49	Front	10mm	18900	1880	22.58	23.50	1.236	0.01	0.757	0.936
	LTE Band 2	20M	QPSK	1	49	Front	10mm	19100	1900	22.58	23.50	1.236	-0.04	0.705	0.871
	LTE Band 2	20M	QPSK	50	24	Front	10mm	18700	1860	21.60	23.00	1.380	-0.05	0.611	0.843
	LTE Band 2	20M	QPSK	50	24	Front	10mm	18900	1880	21.50	23.00	1.413	-0.03	0.603	0.852
	LTE Band 2	20M	QPSK	50	24	Front	10mm	19100	1900	21.48	23.00	1.419	-0.02	0.565	0.802
	LTE Band 2	20M	QPSK	100	0	Front	10mm	18700	1860	21.52	23.00	1.406	-0.07	0.530	0.745
	LTE Band 2	20M	QPSK	1	49	Back	10mm	18700	1860	22.75	23.50	1.189	-0.08	0.873	1.038
36	LTE Band 2	20M	QPSK	1	49	Back	10mm	18900	1880	22.58	23.50	1.236	-0.03	0.845	1.044
	LTE Band 2	20M	QPSK	1	49	Back	10mm	19100	1900	22.58	23.50	1.236	-0.08	0.789	0.975
	LTE Band 2	20M	QPSK	50	24	Back	10mm	18700	1860	21.60	23.00	1.380	-0.07	0.691	0.954
	LTE Band 2	20M	QPSK	50	24	Back	10mm	18900	1880	21.50	23.00	1.413	0.01	0.680	0.961
	LTE Band 2	20M	QPSK	50	24	Back	10mm	19100	1900	21.48	23.00	1.419	-0.02	0.629	0.893
	LTE Band 2	20M	QPSK	100	0	Back	10mm	18700	1860	21.52	23.00	1.406	-0.08	0.690	0.970
	LTE Band 2	20M	QPSK	1	49	Front	12mm	18900	1880	22.58	24.00	1.387	0.09	0.546	0.757
	LTE Band 2	20M	QPSK	1	49	Back	18mm	18900	1880	22.58	24.00	1.387	-0.04	0.307	0.426
	LTE Band 30	10M	QPSK	1	25	Front	10mm	27710	2310	17.40	19.00	1.445	-0.14	0.374	0.541
	LTE Band 30	10M	QPSK	25	25	Front	10mm	27710	2310	16.43	18.00	1.435	-0.01	0.296	0.425
	LTE Band 30	10M	QPSK	1	25	Back	10mm	27710	2310	17.40	19.00	1.445	-0.08	0.709	1.025
	LTE Band 30	10M	QPSK	25	25	Back	10mm	27710	2310	16.43	18.00	1.435	0.03	0.561	0.805
	LTE Band 30	10M	QPSK	50	0	Back	10mm	27710	2310	16.43	18.00	1.435	0.09	0.566	0.812
37	LTE Band 30	10M	QPSK	1	25	Front	12mm	27710	2310	22.83	24.00	1.309	-0.05	0.842	1.102
	LTE Band 30	10M	QPSK	1	25	Back	18mm	27710	2310	22.83	24.00	1.309	-0.09	0.822	1.076

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	10mm	6	2437	17.60	18.00	1.096	99.31	1.007	-0.06	0.201	0.222
38	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	6	2437	17.60	18.00	1.096	99.31	1.007	-0.02	0.267	0.295

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
39	Bluetooth	1Mbps	Back	10mm	39	2441	9.60	10.00	1.096	76.86	1.084	-0.02	0.042	0.050

Based on WLAN2.4GHz and Bluetooth share the same antenna, so Bluetooth RF exposure evaluation chose the worst position of WLAN 2.4GHz Ant to perform Bluetooth SAR test, and used this Bluetooth SAR value conservatively represent other position do co-located analysis with WWAN.

15.4 Repeated SAR Measurement

No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Ratio	Reported 1g SAR (W/kg)
1st	WCDMA II	RMC 12.2Kbps	Back	10mm	9262	1852.4	23.90	24.50	1.148	-	1.000	-0.01	0.913	-	1.048
2nd	WCDMA II	RMC 12.2Kbps	Back	10mm	9262	1852.4	23.90	24.50	1.148	-	1.000	-0.11	0.899	1.02	1.032
1st	LTE Band 30	10M_QPSK_1_25	Front	12mm	27710	2310	22.83	24.00	1.309	-	1.000	-0.05	0.842	-	1.102
2nd	LTE Band 30	10M_QPSK_1_25	Front	12mm	27710	2310	22.83	24.00	1.309	-	1.000	0.07	0.838	1.00	1.097

General Note:

1. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is $\geq 0.8\text{W/kg}$.
2. Per KDB 865664 D01v01r04, if the ratio among the repeated measurement is ≤ 1.2 and the measured SAR $< 1.45\text{W/kg}$, only one repeated measurement is required.
3. The ratio is the difference in percentage between original and repeated *measured SAR*.
4. All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

16. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Portable Handset		
		Head	Body-worn	Hotspot
1.	GSM Voice + WLAN2.4GHz	Yes	Yes	
2.	GPRS/EDGE + WLAN2.4GHz	Yes	Yes	Yes
3.	WCDMA + WLAN2.4GHz	Yes	Yes	Yes
4.	LTE + WLAN2.4GHz	Yes	Yes	Yes
5.	GSM Voice + Bluetooth	Yes	Yes	
6.	GPRS/EDGE + Bluetooth	Yes	Yes	Yes
7.	WCDMA+ Bluetooth	Yes	Yes	Yes
8.	LTE + Bluetooth	Yes	Yes	Yes

General Note:

1. This device WLAN 2.4GHz supports Hotspot operation and Bluetooth support tethering applications.
2. WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously.
3. All licensed modes share the same antenna part and cannot transmit simultaneously.
4. The Scaled SAR summation is calculated based on the same configuration and test position.
5. Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
 - i) Scalar SAR summation < 1.6W/kg.
 - ii) $SPLSR = (SAR1 + SAR2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - iii) If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
 - iv) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.
 - v) The SPLSR calculated results please refer to section 16.4.

16.1 Head Exposure Conditions

WWAN Band		Exposure Position	1	2	3	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN Ant 1	Bluetooth Ant 1		
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)		
GSM	GSM850	Right Cheek	0.591	0.279	0.248	0.870	0.839
		Right Tilted	0.270	0.238	0.248	0.508	0.518
		Left Cheek	0.638	0.714	0.248	1.352	0.886
		Left Tilted	0.291	0.524	0.248	0.815	0.539
	GSM1900	Right Cheek	0.238	0.279	0.248	0.517	0.486
		Right Tilted	0.187	0.238	0.248	0.425	0.435
		Left Cheek	0.344	0.714	0.248	1.058	0.592
		Left Tilted	0.206	0.524	0.248	0.730	0.454
WCDMA	WCDMA II	Right Cheek	0.357	0.279	0.248	0.636	0.605
		Right Tilted	0.306	0.238	0.248	0.544	0.554
		Left Cheek	0.514	0.714	0.248	1.228	0.762
		Left Tilted	0.299	0.524	0.248	0.823	0.547
	WCDMA IV	Right Cheek	0.313	0.279	0.248	0.592	0.561
		Right Tilted	0.358	0.238	0.248	0.596	0.606
		Left Cheek	0.399	0.714	0.248	1.113	0.647
		Left Tilted	0.276	0.524	0.248	0.800	0.524
	WCDMA V	Right Cheek	0.336	0.279	0.248	0.615	0.584
		Right Tilted	0.163	0.238	0.248	0.401	0.411
		Left Cheek	0.351	0.714	0.248	1.065	0.599
		Left Tilted	0.155	0.524	0.248	0.679	0.403
LTE	LTE Band 2	Right Cheek	0.343	0.279	0.248	0.622	0.591
		Right Tilted	0.311	0.238	0.248	0.549	0.559
		Left Cheek	0.528	0.714	0.248	1.242	0.776
		Left Tilted	0.315	0.524	0.248	0.839	0.563
	LTE Band 5	Right Cheek	0.363	0.279	0.248	0.642	0.611
		Right Tilted	0.172	0.238	0.248	0.410	0.420
		Left Cheek	0.352	0.714	0.248	1.066	0.600
		Left Tilted	0.212	0.524	0.248	0.736	0.460
	LTE Band 12	Right Cheek	0.394	0.279	0.248	0.673	0.642
		Right Tilted	0.196	0.238	0.248	0.434	0.444
		Left Cheek	0.389	0.714	0.248	1.103	0.637
		Left Tilted	0.184	0.524	0.248	0.708	0.432
	LTE Band 14	Right Cheek	0.300	0.279	0.248	0.579	0.548
		Right Tilted	0.151	0.238	0.248	0.389	0.399
		Left Cheek	0.287	0.714	0.248	1.001	0.535
		Left Tilted	0.148	0.524	0.248	0.672	0.396
	LTE Band 66	Right Cheek	0.261	0.279	0.248	0.540	0.509
		Right Tilted	0.293	0.238	0.248	0.531	0.541
		Left Cheek	0.399	0.714	0.248	1.113	0.647
		Left Tilted	0.251	0.524	0.248	0.775	0.499
	LTE Band 30	Right Cheek	0.263	0.279	0.248	0.542	0.511
		Right Tilted	0.100	0.238	0.248	0.338	0.348
		Left Cheek	0.107	0.714	0.248	0.821	0.355
		Left Tilted	0.137	0.524	0.248	0.661	0.385

16.2 Hotspot Exposure Conditions

WWAN Band		Exposure Position	1	2	3	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)
			WWAN 1g SAR (W/kg)	2.4GHz WLAN Ant 1 1g SAR (W/kg)	Bluetooth Ant 1 1g SAR (W/kg)		
GSM	GSM850	Front	0.520	0.222	0.050	0.742	0.570
		Back	0.700	0.295	0.050	0.995	0.750
		Left side	0.582			0.582	0.582
		Right side	0.583	0.034	0.050	0.617	0.633
		Top side		0.119	0.050	0.119	0.050
		Bottom side	0.100			0.100	0.100
	GSM1900	Front	0.711	0.222	0.050	0.933	0.761
		Back	0.844	0.295	0.050	1.139	0.894
		Left side	0.407			0.407	0.407
		Right side	0.159	0.034	0.050	0.193	0.209
		Top side		0.119	0.050	0.119	0.050
		Bottom side	0.581			0.581	0.581
WCDMA	WCDMA II	Front	1.018	0.222	0.050	1.240	1.068
		Back	1.048	0.295	0.050	1.343	1.098
		Left side	0.481			0.481	0.481
		Right side	0.178	0.034	0.050	0.212	0.228
		Top side		0.119	0.050	0.119	0.050
		Bottom side	0.927			0.927	0.927
	WCDMA IV	Front	0.438	0.222	0.050	0.660	0.488
		Back	1.023	0.295	0.050	1.318	1.073
		Left side	0.189			0.189	0.189
		Right side	0.060	0.034	0.050	0.094	0.110
		Top side		0.119	0.050	0.119	0.050
		Bottom side	0.954			0.954	0.954
	WCDMA V	Front	0.386	0.222	0.050	0.608	0.436
		Back	0.571	0.295	0.050	0.866	0.621
		Left side	0.387			0.387	0.387
		Right side	0.374	0.034	0.050	0.408	0.424
		Top side		0.119	0.050	0.119	0.050
		Bottom side	0.062			0.062	0.062
LTE	LTE Band 2	Front	0.936	0.222	0.050	1.158	0.986
		Back	1.044	0.295	0.050	1.339	1.094
		Left side	0.531			0.531	0.531
		Right side	0.188	0.034	0.050	0.222	0.238
		Top side		0.119	0.050	0.119	0.050
		Bottom side	0.808			0.808	0.808
	LTE Band 5	Front	0.391	0.222	0.050	0.613	0.441
		Back	0.486	0.295	0.050	0.781	0.536
		Left side	0.425			0.425	0.425
		Right side	0.354	0.034	0.050	0.388	0.404
		Top side		0.119	0.050	0.119	0.050
		Bottom side	0.057			0.057	0.057
	LTE Band 12	Front	0.386	0.222	0.050	0.608	0.436
		Back	0.491	0.295	0.050	0.786	0.541
		Left side	0.349			0.349	0.349
		Right side	0.488	0.034	0.050	0.522	0.538
		Top side		0.119	0.050	0.119	0.050
		Bottom side	0.058			0.058	0.058
	LTE Band 14	Front	0.282	0.222	0.050	0.504	0.332
		Back	0.370	0.295	0.050	0.665	0.420

		Left side	0.421			0.421	0.421
		Right side	0.457	0.034	0.050	0.491	0.507
		Top side		0.119	0.050	0.119	0.050
		Bottom side	0.060			0.060	0.060
	LTE Band 66	Front	0.411	0.222	0.050	0.633	0.461
		Back	1.078	0.295	0.050	1.373	1.128
		Left side	0.201			0.201	0.201
		Right side	0.080	0.034	0.050	0.114	0.130
		Top side		0.119	0.050	0.119	0.050
		Bottom side	1.012			1.012	1.012
	LTE Band 30	Front	0.541	0.222	0.050	0.763	0.591
		Back	1.025	0.295	0.050	1.320	1.075
		Left side	0.061			0.061	0.061
		Right side	0.131	0.034	0.050	0.165	0.181
		Top side		0.119	0.050	0.119	0.050
		Bottom side	1.028			1.028	1.028

16.3 Body-Worn Accessory Exposure Conditions

WWAN Band		Exposure Position	1	2	3	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)	
			WWAN	2.4GHz WLAN Ant 1	Bluetooth Ant 1			
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)			
GSM	GSM850	Front	0.520	0.222	0.050	0.742	0.570	
		Back	0.700	0.295	0.050	0.995	0.750	
	GSM1900	Front	0.711	0.222	0.050	0.933	0.761	
		Back	0.844	0.295	0.050	1.139	0.894	
WCDMA	WCDMA II	Front	1.018	0.222	0.050	1.240	1.068	
		Back	1.048	0.295	0.050	1.343	1.098	
		Front at 12mm	0.827	0.222	0.050	1.049	0.877	
		Back at 18mm	0.474	0.295	0.050	0.769	0.524	
	WCDMA IV	Front	0.438	0.222	0.050	0.660	0.488	
		Back	1.023	0.295	0.050	1.318	1.073	
		Front at 12mm	0.979	0.222	0.050	1.201	1.029	
		Back at 18mm	0.946	0.295	0.050	1.241	0.996	
	WCDMA V	Front	0.386	0.222	0.050	0.608	0.436	
		Back	0.571	0.295	0.050	0.866	0.621	
	LTE	LTE Band 2	Front	0.936	0.222	0.050	1.158	0.986
			Back	1.044	0.295	0.050	1.339	1.094
Front at 12mm			0.757	0.222	0.050	0.979	0.807	
Back at 18mm			0.426	0.295	0.050	0.721	0.476	
LTE Band 5		Front	0.391	0.222	0.050	0.613	0.441	
		Back	0.486	0.295	0.050	0.781	0.536	
LTE Band 12		Front	0.386	0.222	0.050	0.608	0.436	
		Back	0.491	0.295	0.050	0.786	0.541	
LTE Band 14		Front	0.282	0.222	0.050	0.504	0.332	
		Back	0.370	0.295	0.050	0.665	0.420	
LTE Band 66		Front	0.411	0.222	0.050	0.633	0.461	
		Back	1.078	0.295	0.050	1.373	1.128	
		Front at 12mm	0.680	0.222	0.050	0.902	0.730	
		Back at 18mm	0.867	0.295	0.050	1.162	0.917	
LTE Band 30		Front	0.541	0.222	0.050	0.763	0.591	
		Back	1.025	0.295	0.050	1.320	1.075	
		Front at 12mm	1.102	0.222	0.050	1.324	1.152	
		Back at 18mm	1.076	0.295	0.050	1.371	1.126	

Test Engineer : Nick Hu, Yuan Zhao, Jiaxing Chang, Yuankai Kong

17. Uncertainty Assessment

Per KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg. Therefore, the measurement uncertainty table is not required in this report.

18. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v02r02, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Oct 2015.
- [6] FCC KDB 447498 D01 v06, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Oct 2015
- [7] FCC KDB 648474 D04 v01r03, "SAR Evaluation Considerations for Wireless Handsets", Oct 2015.
- [8] FCC KDB 941225 D01 v03r01, "3G SAR MEAUREMENT PROCEDURES", Oct 2015
- [9] FCC KDB 941225 D05 v02r05, "SAR Evaluation Considerations for LTE Devices", Dec 2015
- [10] FCC KDB 941225 D05A v01r02, "Rel. 10 LTE SAR Test Guidance and KDB Inquiries", Oct 2015
- [11] FCC KDB 941225 D06 v02r01, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", Oct 2015.
- [12] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [13] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.