

# FCC TEST REPORT

## (PART 27)

|            |                                             |
|------------|---------------------------------------------|
| Applicant: | HMD Global Oy                               |
| Address:   | Bertel Jungin aukio 9, 02600 Espoo, Finland |

|                           |                                             |
|---------------------------|---------------------------------------------|
| Manufacturer or Supplier: | HMD Global Oy                               |
| Address:                  | Bertel Jungin aukio 9, 02600 Espoo, Finland |
| Product:                  | GSM/WCDMA/LTE Mobile Phone                  |
| Brand Name:               | Nokia                                       |
| Model Name:               | TA-1280                                     |
| FCC ID:                   | 2AJOTTA-1280                                |
| Date of tests:            | Jul. 3, 2020 ~ Jul. 27, 2020                |

The tests have been carried out according to the requirements of the following standard:

- ☒ FCC Part 27, Subpart C, L    ☒ ANSI/TIA/EIA-603- D  
☒ FCC Part 2                      ☒ ANSI/TIA/EIA-603-E    ☒ ANSI C63.26-2015

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

|                                                                                     |                                                                                       |
|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Prepared by Alex Chen<br>Engineer / Mobile Department                               | Approved by Luke Lu<br>Manager / Mobile Department                                    |
|  |  |
| Date: Jul. 29, 2020                                                                 | Date: Jul. 29, 2020                                                                   |

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

## TABLE OF CONTENTS

|                                                                |           |
|----------------------------------------------------------------|-----------|
| <b>RELEASE CONTROL RECORD .....</b>                            | <b>4</b>  |
| <b>1 SUMMARY OF TEST RESULTS .....</b>                         | <b>5</b>  |
| 1.1 MEASUREMENT UNCERTAINTY .....                              | 5         |
| 1.2 TEST SITE AND INSTRUMENTS .....                            | 7         |
| <b>2 GENERAL INFORMATION.....</b>                              | <b>8</b>  |
| 2.1 GENERAL DESCRIPTION OF EUT .....                           | 8         |
| 2.2 CONFIGURATION OF SYSTEM UNDER TEST .....                   | 10        |
| 2.3 DESCRIPTION OF SUPPORT UNITS .....                         | 11        |
| 2.4 DESCRIPTION OF TEST MODES.....                             | 11        |
| 2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS .....             | 13        |
| <b>3 TEST TYPES AND RESULTS .....</b>                          | <b>14</b> |
| 3.1 OUTPUT POWER MEASUREMENT .....                             | 14        |
| 3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT .....                 | 14        |
| 3.1.2 TEST PROCEDURES .....                                    | 14        |
| 3.1.3 TEST SETUP .....                                         | 15        |
| 3.1.4 TEST RESULTS .....                                       | 15        |
| 3.2 FREQUENCY STABILITY MEASUREMENT .....                      | 18        |
| 3.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT .....          | 18        |
| 3.2.2 TEST PROCEDURE .....                                     | 18        |
| 3.2.3 TEST SETUP .....                                         | 18        |
| 3.2.4 TEST RESULTS .....                                       | 19        |
| 3.3 OCCUPIED BANDWIDTH MEASUREMENT .....                       | 20        |
| 3.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT .....           | 20        |
| 3.3.2 TEST SETUP .....                                         | 20        |
| 3.3.3 TEST PROCEDURES .....                                    | 20        |
| 3.3.4 TEST RESULTS .....                                       | 21        |
| 3.4 PEAK TO AVERAGE RATIO .....                                | 22        |
| 3.4.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT .....        | 22        |
| 3.4.2 TEST SETUP .....                                         | 22        |
| 3.4.3 TEST PROCEDURES .....                                    | 22        |
| 3.4.4 TEST RESULTS .....                                       | 23        |
| 3.5 BAND EDGE MEASUREMENT .....                                | 24        |
| 3.5.1 LIMITS OF BAND EDGE MEASUREMENT .....                    | 24        |
| 3.5.2 TEST SETUP .....                                         | 24        |
| 3.5.3 TEST PROCEDURES .....                                    | 25        |
| 3.5.4 TEST RESULTS .....                                       | 25        |
| 3.6 CONDUCTED SPURIOUS EMISSIONS.....                          | 26        |
| 3.6.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT ..... | 26        |
| 3.6.2 TEST PROCEDURE .....                                     | 26        |
| 3.6.3 TEST SETUP .....                                         | 26        |
| 3.6.4 TEST RESULTS .....                                       | 27        |
| 3.7 RADIATED EMISSION MEASUREMENT .....                        | 28        |
| 3.7.1 LIMITS OF RADIATED EMISSION MEASUREMENT .....            | 28        |
| 3.7.2 TEST PROCEDURES .....                                    | 28        |
| 3.7.3 DEVIATION FROM TEST STANDARD .....                       | 28        |
| 3.7.4 TEST SETUP .....                                         | 29        |
| 3.7.5 TEST RESULTS .....                                       | 30        |



Test Report No.: RF200701W006-5

|   |                                                                                             |    |
|---|---------------------------------------------------------------------------------------------|----|
| 4 | INFORMATION ON THE TESTING LABORATORIES .....                                               | 34 |
| 5 | APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT<br>BY THE LAB ..... | 35 |



Test Report No.: RF200701W006-5

## RELEASE CONTROL RECORD

| ISSUE NO.      | REASON FOR CHANGE                                                                                                                                                                                  | DATE ISSUED   |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| RF200629W001-5 | Original release                                                                                                                                                                                   | Jul. 21, 2020 |
| RF200701W006-5 | Based on the original report RF200629W001-5 remove back camera and 2pcs keymat LED, change Keypad materials and FCC ID, HW version and model name. In this report verify power and RSE worst case. | Jul. 29, 2020 |

## 1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

| APPLIED STANDARD: FCC Part 27 & Part 2 |                              |            |                                |
|----------------------------------------|------------------------------|------------|--------------------------------|
| STANDARD SECTION                       | TEST TYPE AND LIMIT          | RESULT     | REMARK                         |
| 2.1046<br>27.50(d)(4)                  | Maximum Peak Output Power    | Compliance | Meet the requirement of limit. |
| 2.1055<br>27.54                        | Frequency Stability          | N.A        | See note                       |
| 2.1049<br>27.53(h)                     | Occupied Bandwidth           | N.A        | See note                       |
| 27.50(d)(5)                            | Peak to average ratio        | N.A        | See note                       |
| 27.53(h)                               | Band Edge Measurements       | N.A        | See note                       |
| 2.1051<br>27.53(h)                     | Conducted Spurious Emissions | N.A        | See note                       |
| 2.1053<br>27.53(h)                     | Radiated Spurious Emissions  | Compliance | Meet the requirement of limit. |

\* Refer to KDB 971168 D01 Power Meas License Digital Systems v03r01.

Note:

Per the change notice provide by manufactory, the difference is remove back camera and 2pcs keymat LED, change Keypad materials and FCC ID, HW version and model name., all the change no effect any RF parameter, Therefore only verify the radiated emission worse case, power and show the verify test data on this report.

Other test data re-use from test report RF200629W001-5, more details please refer test report RF200629W001-5 (FCC ID: 2AJOTTA-1282)

## 1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| MEASUREMENT                                        | UNCERTAINTY           |
|----------------------------------------------------|-----------------------|
| Frequency Stability                                | $\pm 76.97\text{Hz}$  |
| Radiated emissions & Radiated Power (30MHz~1GMHz)  | $\pm 4.98\text{dB}$   |
| Radiated emissions & Radiated Power (1GMHz ~6GMHz) | $\pm 4.70\text{dB}$   |
| Radiated emissions (6GMHz ~18GMHz)                 | $\pm 4.60\text{dB}$   |
| Radiated emissions (18GMHz ~40GMHz)                | $\pm 4.12\text{dB}$   |
| Conducted emissions                                | $\pm 4.01\text{dB}$   |
| Occupied Channel Bandwidth                         | $\pm 43.58\text{KHz}$ |
| Conducted Output power                             | $\pm 2.06\text{dB}$   |
| Band Edge Measurements                             | $\pm 4.70\text{dB}$   |
| Peak to average ratio                              | $\pm 0.76\text{dB}$   |

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

## 1.2 TEST SITE AND INSTRUMENTS

| Equipment                                   | Manufacturer | Model No.                           | Serial No.                      | Last Cal.   | Next Cal.   |
|---------------------------------------------|--------------|-------------------------------------|---------------------------------|-------------|-------------|
| MXE EMI Receiver                            | KEYSIGHT     | N9038A-544                          | MY54450026                      | Apr. 27,20  | Apr. 26,21  |
| EXA Signal Analyzer                         | KEYSIGHT     | N9010A-526                          | MY54510322                      | Feb. 26,20  | Feb. 25,21  |
| Bilog Antenna                               | ETS-LINDGREN | 3143B                               | 00161965                        | Mar. 27,20  | Mar. 26,21  |
| Horn Antenna<br>(1GHz-18GHz)                | ETS-LINDGREN | 3117                                | 00168692                        | Mar. 27,20  | Mar. 26,21  |
| Horn Antenna<br>(18GHz-40GHz)               | N/A          | QWH-SL-18-40<br>-K-SG/QMS-00<br>361 | 15433                           | Nov. 24, 19 | Nov. 23, 20 |
| Radio<br>Communication<br>Analyzer          | ANRITSU      | MT8820C                             | 6201465426                      | Feb. 27,20  | Feb. 26,21  |
| Signal Pre-Amplifier                        | EMSI         | EMC 9135                            | 980249                          | Jun. 02,20  | Jun. 01,21  |
| Signal Pre-Amplifier                        | EMSI         | EMC 012645B                         | 980257                          | Jun. 02,20  | Jun. 01,21  |
| Signal Pre-Amplifier                        | EMSI         | EMC 184045B                         | 980259                          | Apr. 30,20  | Apr. 29,21  |
| 3m Semi-anechoic<br>Chamber                 | ETS-LINDGREN | 9m*6m*6m                            | Euroshieldpn-<br>CT0001143-1216 | May. 19,20  | May. 18,23  |
| Test Software                               | E3           | V 9.160323                          | N/A                             | N/A         | N/A         |
| Test Software                               | ADT          | ADT_Radiated<br>V7.6.15.9.2         | N/A                             | N/A         | N/A         |
| 10dB Attenuator                             | JFW/USA      | 50HF-010-SM<br>A                    | 1505                            | Jun. 03,20  | Jun. 02,21  |
| Power Meter                                 | Anritsu      | ML2495A                             | 1506002                         | Feb. 26,20  | Feb. 25,21  |
| Power Sensor                                | Anritsu      | MA2411B                             | 1339352                         | Feb. 26,20  | Feb. 25,21  |
| Humid & Temp<br>Programmable Tester         | Juyi         | ITH-120-45-CP<br>-AR                | IAA1504-001                     | Jun. 02,20  | Jun. 01,21  |
| MXG Analog<br>Microvave<br>Signal Generator | KEYSIGHT     | N5183A                              | MY50143024                      | Mar. 11,20  | Mar. 10,21  |
| Power Divider                               | MCLI/USA     | PS2-15                              | 24880                           | N/A         | N/A         |

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
  2. The test was performed in 3m Semi-anechoic Chamber and RF Oven Room.
  3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
  4. The FCC Site Registration No. is 525120; The Designation No. is CN1171.

## 2 GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

|                              |                                                                                             |                     |
|------------------------------|---------------------------------------------------------------------------------------------|---------------------|
| <b>PRODUCT</b>               | GSM/WCDMA/LTE Mobile Phone                                                                  |                     |
| <b>BRAND NAME</b>            | Nokia                                                                                       |                     |
| <b>MODEL NAME</b>            | TA-1280                                                                                     |                     |
| <b>POWER SUPPLY</b>          | 5.0Vdc (adapter or host equipment)<br>3.7Vdc (Li-ion, battery)                              |                     |
| <b>MODULATION TECHNOLOGY</b> | LTE                                                                                         | QPSK, 16QAM         |
| <b>FREQUENCY RANGE</b>       | LTE Band 17<br>Channel Bandwidth: 5MHz                                                      | 706.5MHz ~ 713.5MHz |
|                              | LTE Band 17<br>Channel Bandwidth: 10MHz                                                     | 709.0MHz ~ 711.0MHz |
| <b>EMISSION DESIGNATOR</b>   | LTE Band 17<br>Channel Bandwidth: 5MHz                                                      | QPSK: 4M48G7D       |
|                              |                                                                                             | 16QAM: 4M49W7D      |
|                              | LTE Band 17<br>Channel Bandwidth: 10MHz                                                     | QPSK: 8M96G7D       |
|                              |                                                                                             | 16QAM: 8M97W7D      |
| <b>MAX. ERP/EIRP POWER</b>   | LTE Band 17<br>Channel Bandwidth: 5MHz                                                      | 31mW                |
|                              | LTE Band 17<br>Channel Bandwidth: 10MHz                                                     | 32mW                |
| <b>ANTENNA TYPE</b>          | Fixed Internal Antenna with -5.58dBi gain for LTE B17                                       |                     |
| <b>HW VERSION</b>            | 0144                                                                                        |                     |
| <b>SW VERSION</b>            | 0.2025.11.05                                                                                |                     |
| <b>I/O PORTS</b>             | Refer to user's manual                                                                      |                     |
| <b>CABLE SUPPLIED</b>        | USB cable: non-shielded, detachable, 1meter<br>Earphone: non-shielded, detachable, 1.5meter |                     |

**NOTE:**

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.



**BUREAU  
VERITAS**


**Test Report No.: RF200629W001-5**

**List of Accessory:**

| ACCESSORIES  | BRAND | MODEL    | MANUFACTURER | SPECIFICATION                                   |
|--------------|-------|----------|--------------|-------------------------------------------------|
| Battery 1    | Nokia | BL-4WL   | TM           | Power Rating:3.7 Vdc, 1150 mAh                  |
| AC Adapter 1 | Nokia | AC-18U   | DVE          | I/P: 100 - 240 Vac, 100mA,<br>O/P: 5Vdc, 550 mA |
| AC Adapter 2 | Nokia | AC-18U   | Aohai        | I/P: 100 - 240 Vac, 100mA,<br>O/P: 5Vdc, 550 mA |
| Earphone 1   | Nokia | WH-108   | RTF          | 1.5m non-shielded cable w/ core                 |
| USB Cable 1  | Nokia | CA-190CD | RTF          | 1m non-shielded cable w/ core                   |

## 2.2 CONFIGURATION OF SYSTEM UNDER TEST

### FOR RADIATION EMISSION TEST



## 2.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| NO. | PRODUCT   | BRAND    | MODEL NO. | SERIAL NO. | FCC ID |
|-----|-----------|----------|-----------|------------|--------|
| 1   | DC source | LONG WEI | PS-6403D  | 010934269  | N/A    |

| NO. | SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS |
|-----|-----------------------------------------------------|
| 1   | DC Line: Unshielded, Detachable 1.8m                |

**NOTE:**

1. All power cords of the above support units are non shielded.

## 2.4 DESCRIPTION OF TEST MODES

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case in ERP/EIRP and radiated emission was found when positioned on X-plane for LTE. Following channel(s) was (were) selected for the final test as listed below:

| EUT<br>CONFIGURE<br>MODE | DESCRIPTION                                       |
|--------------------------|---------------------------------------------------|
| A                        | EUT + Adapter + USB Cable+ Earphone with LTE link |
| B                        | EUT + Battery with LTE link                       |

**LTE BAND 17**

| EUT CONFIGURE MODE | TEST ITEM         | AVAILABLE CHANNEL | TESTED CHANNEL      | CHANNEL BANDWIDTH | MODULATION  | MODE               |
|--------------------|-------------------|-------------------|---------------------|-------------------|-------------|--------------------|
| A                  | RADIATED EMISSION | 23780 to 23800    | 23790               | 10MHz             | QPSK        | 1 RB / 0 RB Offset |
| B                  | ERP               | 23755 to 23825    | 23755, 23790, 23825 | 5MHz              | QPSK, 16QAM | 1 RB / 0 RB Offset |
|                    |                   | 23780 to 23800    | 23780, 23790, 23800 | 10MHz             | QPSK, 16QAM | 1 RB / 0 RB Offset |

**Note:** This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

**TEST CONDITION:**

| TEST ITEM         | ENVIRONMENTAL CONDITIONS | INPUT POWER      | TESTED BY |
|-------------------|--------------------------|------------------|-----------|
| RADIATED EMISSION | 23deg. C, 70%RH          | DC 5V By Adapter | Star Le   |
| EIRP              | 23deg. C, 70%RH          | DC 5V By Adapter | Star Le   |



Test Report No.: RF200629W001-5

## 2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC 47 CFR Part 2**

**FCC 47 CFR Part 27**

**KDB 971168 D01 Power Meas License Digital Systems v03r01**

**ANSI/TIA/EIA-603-D**

**ANSI/TIA/EIA-603-E**

**ANSI C63.26-2015**

**NOTE:** All test items have been performed and recorded as per the above standards.

### 3 TEST TYPES AND RESULTS

#### 3.1 OUTPUT POWER MEASUREMENT

##### 3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

27.50(c)(10) Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP.

##### 3.1.2 TEST PROCEDURES

###### EIRP / ERP MEASUREMENT:

Per KDB 971168 D01 Power Meas License Digital Systems v03r01 or subclause 5.2.5.5 of ANSI C63.26-2015, the relevant equation for determining the ERP or EIRP from the conducted RF output power measured using the guidance provided above is:

$$\text{ERP or EIRP} = P_{\text{Meas}} + G_{\text{T}} - L_{\text{C}}$$

Where:

ERP or EIRP = effective radiated power or equivalent isotropically radiated power, respectively  
(expressed in the same units as  $P_{\text{Meas}}$ , typically dBW or dBm);

$P_{\text{Meas}}$  = measured transmitter output power or PSD, in dBm or dBW;

$G_{\text{T}}$  = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

$L_{\text{C}}$  = signal attenuation in the connecting cable between the transmitter and antenna, in dB.


###### CONDUCTED POWER MEASUREMENT:

- The EUT was set up for the maximum power with LTE link data modulation and link up with simulator.
- Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

### 3.1.3 TEST SETUP

#### EIRP MEASUREMENT:

#### CONDUCTED POWER MEASUREMENT:



### 3.1.4 TEST RESULTS

#### AVERAGE CONDUCTED OUTPUT POWER (dBm)

| Band/BW | Modulation | RB Size | RB Offset | Low CH<br>23755        | Mid CH<br>23790      | High CH<br>23825       | MPR |
|---------|------------|---------|-----------|------------------------|----------------------|------------------------|-----|
|         |            |         |           | Frequency<br>706.5 MHz | Frequency<br>710 MHz | Frequency<br>713.5 MHz |     |
| 17/ 5   | QPSK       | 1       | 0         | 22.62                  | 22.62                | 22.58                  | 0   |
|         |            | 1       | 12        | 22.71                  | 22.67                | 22.67                  | 0   |
|         |            | 1       | 24        | 22.69                  | 22.68                | 22.69                  | 0   |
|         |            | 12      | 0         | 21.71                  | 21.72                | 21.66                  | 1   |
|         |            | 12      | 6         | 21.78                  | 21.87                | 21.77                  | 1   |
|         |            | 12      | 13        | 21.67                  | 21.68                | 21.66                  | 1   |
|         |            | 25      | 0         | 21.83                  | 21.89                | 21.80                  | 1   |
|         | 16QAM      | 1       | 0         | 22.07                  | 22.11                | 22.08                  | 1   |
|         |            | 1       | 12        | 22.10                  | 22.18                | 22.09                  | 1   |
|         |            | 1       | 24        | 22.15                  | 22.11                | 22.11                  | 1   |
|         |            | 12      | 0         | 21.02                  | 21.06                | 20.98                  | 2   |
|         |            | 12      | 6         | 21.10                  | 21.16                | 21.06                  | 2   |
|         |            | 12      | 13        | 21.12                  | 21.16                | 21.13                  | 2   |
|         |            | 25      | 0         | 21.14                  | 21.15                | 21.11                  | 2   |

| Band/BW | Modulation | RB<br>Size | RB<br>Offset | Low CH<br>23780      | Mid CH<br>23790      | High CH<br>23800     | MPR |
|---------|------------|------------|--------------|----------------------|----------------------|----------------------|-----|
|         |            |            |              | Frequency<br>709 MHz | Frequency<br>710 MHz | Frequency<br>711 MHz |     |
| 17/ 10  | QPSK       | 1          | 0            | 22.67                | 22.69                | 22.63                | 0   |
|         |            | 1          | 24           | 22.73                | 22.75                | 22.69                | 0   |
|         |            | 1          | 49           | 22.74                | 22.76                | 22.70                | 0   |
|         |            | 25         | 0            | 21.75                | 21.77                | 21.71                | 1   |
|         |            | 25         | 12           | 21.86                | 21.88                | 21.82                | 1   |
|         |            | 25         | 25           | 21.71                | 21.73                | 21.67                | 1   |
|         |            | 50         | 0            | 21.89                | 21.91                | 21.85                | 1   |
|         | 16QAM      | 1          | 0            | 22.14                | 22.16                | 22.10                | 1   |
|         |            | 1          | 24           | 22.18                | 22.20                | 22.14                | 1   |
|         |            | 1          | 49           | 22.17                | 22.19                | 22.13                | 1   |
|         |            | 25         | 0            | 21.10                | 21.12                | 21.06                | 2   |
|         |            | 25         | 12           | 21.16                | 21.18                | 21.12                | 2   |
|         |            | 25         | 25           | 21.19                | 21.21                | 21.15                | 2   |
|         |            | 50         | 0            | 21.20                | 21.22                | 21.16                | 2   |

## EIRP

### LTE BAND 17

#### CHANNEL BANDWIDTH: 5MHz QPSK

| Channel | Frequency<br>(MHz) | Conducted<br>Power<br>(dBm) | G <sub>T</sub> -L <sub>c</sub><br>(dB) | ERP<br>(dBm) | ERP<br>(mW) | Limit<br>(W) |
|---------|--------------------|-----------------------------|----------------------------------------|--------------|-------------|--------------|
| 23755   | 706.5              | 22.71                       | -5.58                                  | 14.98        | 31.48       | 3            |
| 23790   | 710.0              | 22.68                       | -5.58                                  | 14.95        | 31.26       | 3            |
| 23825   | 713.5              | 22.69                       | -5.58                                  | 14.96        | 31.33       | 3            |

#### CHANNEL BANDWIDTH: 5MHz 16QAM

| Channel | Frequency<br>(MHz) | Conducted<br>Power<br>(dBm) | G <sub>T</sub> -L <sub>c</sub><br>(dB) | ERP<br>(dBm) | ERP<br>(mW) | Limit<br>(W) |
|---------|--------------------|-----------------------------|----------------------------------------|--------------|-------------|--------------|
| 23755   | 706.5              | 22.15                       | -5.58                                  | 14.42        | 27.67       | 3            |
| 23790   | 710.0              | 22.18                       | -5.58                                  | 14.45        | 27.86       | 3            |
| 23825   | 713.5              | 22.11                       | -5.58                                  | 14.38        | 27.42       | 3            |

#### CHANNEL BANDWIDTH: 10MHz QPSK

| Channel | Frequency<br>(MHz) | Conducted<br>Power<br>(dBm) | G <sub>T</sub> -L <sub>c</sub><br>(dB) | ERP<br>(dBm) | ERP<br>(mW) | Limit<br>(W) |
|---------|--------------------|-----------------------------|----------------------------------------|--------------|-------------|--------------|
| 23780   | 709.0              | 22.74                       | -5.58                                  | 15.01        | 31.7        | 3            |
| 23790   | 710.0              | 22.76                       | -5.58                                  | 15.03        | 31.84       | 3            |
| 23800   | 711.0              | 22.70                       | -5.58                                  | 14.97        | 31.41       | 3            |

#### CHANNEL BANDWIDTH: 10MHz 16QAM

| Channel | Frequency<br>(MHz) | Conducted<br>Power<br>(dBm) | G <sub>T</sub> -L <sub>c</sub><br>(dB) | ERP<br>(dBm) | ERP<br>(mW) | Limit<br>(W) |
|---------|--------------------|-----------------------------|----------------------------------------|--------------|-------------|--------------|
| 23780   | 709.0              | 22.18                       | -5.58                                  | 14.45        | 27.86       | 3            |
| 23790   | 710.0              | 22.20                       | -5.58                                  | 14.47        | 27.99       | 3            |
| 23800   | 711.0              | 22.14                       | -5.58                                  | 14.41        | 27.61       | 3            |

**REMARKS:** ERP Output Power (dBm) = EIRP (dBm) -2.15(dB).

## 3.2 FREQUENCY STABILITY MEASUREMENT

### 3.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT


The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

### 3.2.2 TEST PROCEDURE

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the  $\pm 0.5^{\circ}\text{C}$  during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

**NOTE:** The frequency error was recorded frequency error from the communication simulator.

### 3.2.3 TEST SETUP





Test Report No.: RF200629W001-5

### 3.2.4 TEST RESULTS


N/A

### 3.3 OCCUPIED BANDWIDTH MEASUREMENT

#### 3.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

#### 3.3.2 TEST SETUP



#### 3.3.3 TEST PROCEDURES

- The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.



Test Report No.: RF200629W001-5

### 3.3.4 TEST RESULTS


N/A

### 3.4 PEAK TO AVERAGE RATIO

#### 3.4.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

#### 3.4.2 TEST SETUP



#### 3.4.3 TEST PROCEDURES

1. Set resolution/measurement bandwidth  $\geq$  signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.



Test Report No.: RF200629W001-5

#### 3.4.4 TEST RESULTS

N/A


### 3.5 BAND EDGE MEASUREMENT

#### 3.5.1 LIMITS OF BAND EDGE MEASUREMENT

The power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least  $43 + 10 \log (P)$  dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater.

However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

#### 3.5.2 TEST SETUP



### 3.5.3 TEST PROCEDURES

- a. The EUT was set up for the maximum peak power with LTE link data modulation. The power was measured with R&S Spectrum Analyzer. All measurements were done at 2 channels (low and high operational frequency range.).
- b. The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- c. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 50kHz and VBW of the spectrum is 200kHz. (LTE bandwidth 5MHz)
- d. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 100kHz and VBW of the spectrum is 300kHz. (LTE bandwidth 10MHz)
- e. Record the max trace plot into the test report.

### 3.5.4 TEST RESULTS

N/A

### 3.6 CONDUCTED SPURIOUS EMISSIONS


#### 3.6.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log_{10}(P)$  dB. The limit of emission equal to  $-13\text{dBm}$

#### 3.6.2 TEST PROCEDURE

- a. The EUT makes a phone call to the communication simulator. All measurements were done at middle operational frequency range.
- b. Measuring frequency range is from 30 MHz to 7.2GHz for LTE Band 17. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz are used for conducted emission measurement.

#### 3.6.3 TEST SETUP





Test Report No.: RF200629W001-5

### 3.6.4 TEST RESULTS

N/A

### 3.7 RADIATED EMISSION MEASUREMENT

#### 3.7.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log_{10}(P)$  dB. The limit of emission equal to  $-13\text{dBm}$

#### 3.7.2 TEST PROCEDURES

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G
- c.  $\text{EIRP} = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}.$
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole,  $\text{E.R.P power} = \text{E.I.P.R power} - 2.15\text{dBi}.$


**NOTE:** The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.

#### 3.7.3 DEVIATION FROM TEST STANDARD


No deviation

### 3.7.4 TEST SETUP

#### < Frequency Range 30MHz~1GHz >



#### <Frequency Range above 1GHz>



**Note:** Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 3.7.5 TEST RESULTS

#### BELOW 1GHz WORST-CASE DATA


30 MHz – 1GHz data:

LTE BAND 17

CHANNEL BANDWIDTH: 10MHz / QPSK


|                                                     |                  |                 |                    |
|-----------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                                | TX channel 23790 | FREQUENCY RANGE | Below 1000MHz      |
| ENVIRONMENTAL CONDITIONS                            | 23deg. C, 70%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                           | Star Le          |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                  |                 |                    |

|      | Freq    | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|------|---------|--------|------------|------------|------------|--------|--------|------------|
|      | MHz     | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |            |
| 1 PP | 34.120  | -37.68 | -56.52     | -13.00     | -24.68     | 18.84  | Peak   | Horizontal |
| 2    | 130.220 | -44.52 | -51.74     | -13.00     | -31.52     | 7.22   | Peak   | Horizontal |
| 3    | 263.410 | -46.04 | -59.57     | -13.00     | -33.04     | 13.53  | Peak   | Horizontal |
| 4    | 302.540 | -40.06 | -53.74     | -13.00     | -27.06     | 13.68  | Peak   | Horizontal |
| 5    | 373.120 | -53.11 | -69.05     | -13.00     | -40.11     | 15.94  | Peak   | Horizontal |
| 6    | 531.150 | -48.83 | -68.25     | -13.00     | -35.83     | 19.42  | Peak   | Horizontal |



|                                                   |                  |                 |                   |
|---------------------------------------------------|------------------|-----------------|-------------------|
| MODE                                              | TX channel 23790 | FREQUENCY RANGE | Below 1000MHz     |
| ENVIRONMENTAL CONDITIONS                          | 23deg. C, 70%RH  | INPUT POWER     | DC 5Vfrom adapter |
| TESTED BY                                         | Star Le          |                 |                   |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                  |                 |                   |

|   |    | Freq    | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase |
|---|----|---------|--------|------------|------------|------------|--------|--------|-----------|
|   |    | MHz     | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |           |
| 1 | PP | 36.140  | -37.94 | -55.25     | -13.00     | -24.94     | 17.31  | Peak   | Vertical  |
| 2 |    | 52.850  | -43.27 | -51.24     | -13.00     | -30.27     | 7.97   | Peak   | Vertical  |
| 3 |    | 108.120 | -41.09 | -49.58     | -13.00     | -28.09     | 8.49   | Peak   | Vertical  |
| 4 |    | 251.220 | -47.97 | -61.47     | -13.00     | -34.97     | 13.50  | Peak   | Vertical  |
| 5 |    | 338.520 | -50.91 | -65.74     | -13.00     | -37.91     | 14.83  | Peak   | Vertical  |
| 6 |    | 637.140 | -45.27 | -66.25     | -13.00     | -32.27     | 20.98  | Peak   | Vertical  |



**ABOVE 1GHz WORST-CASE DATA**


**LTE BAND 17**

**CHANNEL BANDWIDTH: 10MHz / QPSK**

**CH 23790**


|                                                     |                  |                 |                    |
|-----------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                                | TX channel 23790 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                            | 23deg. C, 70%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                           | Star Le          |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                  |                 |                    |

|   |    | Freq     | Level  | Read Level | Limit Line | Over Limit | Factor | Remark | Pol/Phase  |
|---|----|----------|--------|------------|------------|------------|--------|--------|------------|
|   |    | MHz      | dBm/m  | dBm        | dBm/m      | dB         | dB/m   |        |            |
| 1 | PP | 1416.000 | -42.56 | -43.64     | -13.00     | -29.56     | 1.08   | Peak   | Horizontal |
| 2 |    | 2130.000 | -48.85 | -56.53     | -13.00     | -35.85     | 7.68   | Peak   | Horizontal |



|                                                   |                  |                 |                    |
|---------------------------------------------------|------------------|-----------------|--------------------|
| MODE                                              | TX channel 23790 | FREQUENCY RANGE | Above 1000MHz      |
| ENVIRONMENTAL CONDITIONS                          | 23deg. C, 70%RH  | INPUT POWER     | DC 5V from adapter |
| TESTED BY                                         | Star Le          |                 |                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                  |                 |                    |

|      |          |        | Read   | Limit  | Over   |        |        |           |
|------|----------|--------|--------|--------|--------|--------|--------|-----------|
|      | Freq     | Level  | Level  | Line   | Limit  | Factor | Remark | Pol/Phase |
|      | MHz      | dBm/m  | dBm    | dBm/m  | dB     | dB/m   |        |           |
| 1 PP | 1416.000 | -48.37 | -50.06 | -13.00 | -35.37 | 1.69   | Peak   | Vertical  |
| 2    | 2130.000 | -50.10 | -56.80 | -13.00 | -37.10 | 6.70   | Peak   | Vertical  |





BUREAU  
VERITAS

Test Report No.: RF200629W001-5

## 4 INFORMATION ON THE TESTING LABORATORIES

We, BV 7LAYERS COMMUNICATIONS TECHNOLOGY (SHENZHEN) CO. LTD., were founded in 2015 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Shenzhen EMC/RF Lab:**

Tel: +86-755-88696566

Fax: +86-755-88696577

**Email:** [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.



Test Report No.: RF200629W001-5

## 5 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

---END---